


Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1695.513	14.05	36.64	50.69	74.00	23.31	PASS	Vertical	PK
2	2937.0625	17.68	37.03	54.71	74.00	19.29	PASS	Vertical	PK
3	3982.0655	-11.77	56.44	44.67	74.00	29.33	PASS	Vertical	PK
4	6644.243	-3.97	49.19	45.22	74.00	28.78	PASS	Vertical	PK
5	11297.5532	2.44	44.23	46.67	74.00	27.33	PASS	Vertical	PK
6	17179.9453	12.82	40.07	52.89	74.00	21.11	PASS	Vertical	PK
7	2926.2618	17.67	17.97	35.64	54.00	18.36	PASS	Vertical	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19226.4291	-26.00	62.12	36.12	74.00	37.88	PASS	Horizontal	PK
2	20837.7535	-25.72	60.97	35.25	74.00	38.75	PASS	Horizontal	PK
3	22125.045	-25.55	60.12	34.57	74.00	39.43	PASS	Horizontal	PK
4	23375.275	-23.65	58.74	35.09	74.00	38.91	PASS	Horizontal	PK
5	25107.6443	-21.55	57.48	35.93	74.00	38.07	PASS	Horizontal	PK
6	26063.0825	-21.04	59.06	38.02	74.00	35.98	PASS	Horizontal	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2440MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19312.4525	-25.82	62.72	36.90	74.00	37.10	PASS	Vertical	PK
2	20661.6265	-25.94	61.15	35.21	74.00	38.79	PASS	Vertical	PK
3	21881.5953	-25.64	60.79	35.15	74.00	38.85	PASS	Vertical	PK
4	23296.7319	-23.93	58.39	34.46	74.00	39.54	PASS	Vertical	PK
5	24662.2265	-21.90	57.39	35.49	74.00	38.51	PASS	Vertical	PK
6	26001.8801	-20.90	57.94	37.04	74.00	36.96	PASS	Vertical	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1598.1732	13.73	35.64	49.37	74.00	24.63	PASS	Horizontal	PK
2	2690.5127	17.23	37.68	54.91	74.00	19.09	PASS	Horizontal	PK
3	3796.0531	-12.47	54.07	41.60	74.00	32.40	PASS	Horizontal	PK
4	5218.1479	-7.64	50.32	42.68	74.00	31.32	PASS	Horizontal	PK
5	8759.384	-0.18	45.21	45.03	74.00	28.97	PASS	Horizontal	PK
6	16503.9003	11.93	41.39	53.32	74.00	20.68	PASS	Horizontal	PK
7	2713.1809	17.08	18.58	35.66	54.00	18.34	PASS	Horizontal	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1570.5714	13.47	35.85	49.32	74.00	24.68	PASS	Vertical	PK
2	2756.9171	16.94	36.75	53.69	74.00	20.31	PASS	Vertical	PK
3	3992.0661	-11.72	56.15	44.43	74.00	29.57	PASS	Vertical	PK
4	6666.2444	-3.76	49.46	45.70	74.00	28.30	PASS	Vertical	PK
5	10203.4802	1.55	43.52	45.07	74.00	28.93	PASS	Vertical	PK
6	17054.937	12.38	41.64	54.02	74.00	19.98	PASS	Vertical	PK
7	17051.9368	12.33	21.61	33.94	54.00	20.06	PASS	Vertical	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18887.4355	-26.28	62.43	36.15	74.00	37.85	PASS	Horizontal	PK
2	20344.7338	-25.49	61.23	35.74	74.00	38.26	PASS	Horizontal	PK
3	21800.672	-25.53	60.76	35.23	74.00	38.77	PASS	Horizontal	PK
4	23306.9323	-23.89	58.84	34.95	74.00	39.05	PASS	Horizontal	PK
5	24547.3019	-21.82	57.72	35.90	74.00	38.10	PASS	Horizontal	PK
6	25917.5567	-20.87	57.29	36.42	74.00	37.58	PASS	Horizontal	PK

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18826.233	-26.29	63.99	37.70	74.00	36.30	PASS	Vertical	PK
2	20050.962	-24.85	61.18	36.33	74.00	37.67	PASS	Vertical	PK
3	21010.1404	-25.99	61.10	35.11	74.00	38.89	PASS	Vertical	PK
4	22182.1673	-25.44	60.81	35.37	74.00	38.63	PASS	Vertical	PK
5	23556.5023	-23.17	58.34	35.17	74.00	38.83	PASS	Vertical	PK
6	25069.2228	-21.76	57.67	35.91	74.00	38.09	PASS	Vertical	PK

Remark:


- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. The report records the lowest Peak value. If the Peak value is greater than 54dBμV/m, then the Average value at that time is recorded.

Restricted bands:

Test plot as follows:

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	9.96	32.57	42.53	74.00	31.47	PASS	Horizontal	PK
2	2390	9.96	21.54	31.50	74.00	42.50	PASS	Horizontal	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2402MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	9.96	33.17	43.13	74.00	30.87	PASS	Vertical	PK
2	2390	9.96	21.64	31.60	74.00	42.40	PASS	Vertical	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	10.38	33.23	43.61	74.00	30.39	PASS	Horizontal	PK
2	2483.5	10.38	21.03	31.41	74.00	42.59	PASS	Horizontal	AV

Test_Mode	BLE 1M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	10.38	33.47	43.85	74.00	30.15	PASS	Vertical	PK
2	2483.5	10.38	21.39	31.77	74.00	42.23	PASS	Vertical	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	9.96	33.35	43.31	74.00	30.69	PASS	Horizontal	PK
2	2390	9.96	21.43	31.39	74.00	42.61	PASS	Horizontal	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2402MHz
Remark:	/	Test_Date	2026/5/19


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	9.96	33.55	43.51	74.00	30.49	PASS	Vertical	PK
2	2390	9.96	21.78	31.74	74.00	42.26	PASS	Vertical	AV

Test_Mode	BLE 2M GFSK Transmitting	Test_Frequency	2480MHz
Remark:	/	Test_Date	2026/5/19

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	10.38	33.82	44.20	74.00	29.80	PASS	Horizontal	PK
2	2483.5	10.38	20.92	31.30	74.00	42.70	PASS	Horizontal	AV