

TEST REPORT

Report No.: BCTC2509241207E

Applicant: Shenzhen Efercro Electronic Technology Co., Ltd.

Product Name: Tablet

Test Model: G13

Tested Date: 2025-09-17 to 2025-11-10

Issued Date: 2025-11-10

Shenzhen **BCTC** Testing Co., Ltd.



FCC ID: 2AW9M-G13A

Product Name: Tablet

Trademark: N/A

Model/Type Reference: G13
G13A, G13L, G01, G02, G03, G04, G05, G06, G07, G08, G09, G101, G101L,
G101PRO, G102, G102L, G102PRO, G103, G103L, G103PRO, G104, G104L,
G105, G105L, G106, G106L, G107, G108, G109, G113, G113L, G116, G116L,
G117, G117L, G118, G118L

Prepared For: Shenzhen Efercro Electronic Technology Co., Ltd.

Address: Room 901, Block E, Building 1, Section 1, Chuangzhi Yuncheng, Liuxian Avenue,
Xili Community, Xili Street, Nanshan District, Shenzhen, China

Manufacturer: Shenzhen Efercro Electronic Technology Co., Ltd.

Address: Room 901, Block E, Building 1, Section 1, Chuangzhi Yuncheng, Liuxian Avenue,
Xili Community, Xili Street, Nanshan District, Shenzhen, China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng,
Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-09-16

Sample tested Date: 2025-09-17 to 2025-11-10


Issue Date: 2025-11-10

Test Standards: IEEE Std C95.1-2019
IEEE Std 1528-2013
FCC Part 2.1093

Test Results: PASS

Remark: This is SAR test report

Tested by:



Min Zhi Cheng / Project Handler

Approved by:



Zero Zhou / Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.


Table Of Content

Test Report Declaration	Page
1. Version	5
2. Test Standards	6
3. Test Summary	7
4. SAR Limits.....	8
5. Measurement Uncertainty	9
6. Product Information and Test Setup	10
6.1 Product Information	10
6.3 Support Equipment	12
6.4 Test Environment.....	12
7. Test Facility and Test Instrument Used	13
7.1 Test Facility	13
7.2 Test Instrument Used.....	14
8. Specific Absorption Rate (SAR)	15
8.1 Introduction	15
8.2 SAR Definition.....	15
9. SAR Measurement System	16
9.1 The Measurement System	16
9.2 Probe	16
9.3 Probe Calibration Process	18
9.4 Phantom.....	19
9.5 Device Holder	19
10. Tissue Simulating Liquids	20
10.1 Composition of Tissue Simulating Liquid	20
10.2 Limit	21
10.3 Tissue Calibration Result	22
11. System Check	23
11.1 Purpose of System Performance Check	23
11.2 System Setup.....	23
11.3 Validation Results	24
12. EUT Testing Position	25
13. SAR Measurement Procedures	26
13.1 Measurement Procedures.....	26
13.2 Spatial Peak SAR Evaluation.....	26
13.3 Area & Zoom Scan Procedures	27
13.4 Volume Scan Procedures	28
13.5 SAR Averaged Methods.....	28
13.6 Power Drift Monitoring.....	28
14. SAR Test Result	29
14.1 Conducted RF Output Power	29
14.2 Transmit Antennas and SAR Measurement Position	35
14.3 Measured and Reported (Scaled) SAR Results.....	36
14.4 SAR Measurement Variability	37
14.5 Simultaneous Transmission Evaluation	38

15.	Test Plots.....	39
15.1	System Performance Check	39
15.2	SAR Test Graph Results.....	49
16.	CALIBRATION CERTIFICATES	59
17.	EUT Photographs	97
18.	Photographs Of The Liquid	98
19.	EUT Test Setup Photographs.....	99


(Note: N/A Means Not Applicable)

TE
TC
OVE
t See



1. Version

Report No.	Issue Date	Description	Approved
BCTC2509241207E	2025-11-10	Original	Valid



2. Test Standards

IEEE Std C95.1-2019: IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

IEEE Std 1528-2013: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

FCC Part 2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices

KDB 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies.

KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB 865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations.

KDB 248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS.


KDB 941225 D01 3G SAR Procedures: 3G SAR MEAUREMENT PROCEDURES.

KDB 941225 D05 SAR for LTE Devices: SAR EVALUATION CONSIDERATIONS FOR LTE DEVICES.

KDB 941225 D06 Hotspot Mode v02r01: SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES.

KDB 648474 D04 Handset SAR v01r03: SAR EVALUATION CONSIDERATIONS FOR WIRELESS HANDSETS.

C0.L7n




3. Test Summary

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Maximum SAR _{1g} (W/kg)	Limit SAR _{1g} (W/kg)
	Body (5mm Gap)	
Bluetooth	0.042	1.6
WIFI 2.4G	0.698	1.6
WIFI 5.1G	0.924	1.6
WIFI 5.3G	1.110	1.6
WIFI 5.6G	0.664	1.6
WIFI 5.8G	0.824	1.6
Simultaneous Transmission	1.152	1.6

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedure specified in IEEE 1528-2013.




4. SAR Limits

EXPOSURE LIMITS	FCC Limit (1g Tissue)	
	SAR (W/kg)	
	General Population / Uncontrolled Exposure Environment	Occupational / Controlled Exposure Environment
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1g of tissue)	1.6	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.


Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).



5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k=2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.


Therefore, the measurement uncertainty is not required.



6. Product Information and Test Setup

6.1 Product Information

Model/Type Reference:	G13 G13A, G13L, G01, G02, G03, G04, G05, G06, G07, G08, G09, G101, G101L, G101PRO, G102, G102L, G102PRO, G103, G103L, G103PRO, G104, G104L, G105, G105L, G106, G106L, G107, G108, G109, G113, G113L, G116, G116L, G117, G117L, G118, G118L
Model Differences:	All the model are the same circuit and RF module, except model names and color.
Ratings:	DC 3.8V From battery ,DC 5V/9V From Adapter
BDR,EDR	
Operation Frequency:	2402-2480MHz
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number Of Channel:	79CH
Antenna installation:	FPC antenna
Antenna Gain:	1.62 dBi Remark: ☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. ☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
BLE	
Operation Frequency:	2402-2480MHz
Type of Modulation:	GFSK 1Mbps, GFSK 2Mbps
Number Of Channel	40CH
Antenna installation:	FPC antenna
Antenna Gain:	1.62 dBi Remark: ☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. ☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.



WIFI 2.4G

Operation Frequency: 802.11b/g/n/ax20MHz:2412~2462 MHz
802.11n/ax40MHz:2422~2452 MHz

Bit Rate of Transmitter: 802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n Up to 150Mbps

Type of Modulation: WIFI: OFDM/DSSS

Number Of Channel: 802.11b/g/n/ax20MHz:11 CH
802.11n/ax40MHz: 7 CH

Antenna installation: FPC antenna

Antenna Gain: 1.86 dBi
Remark:
☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information.
☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.

WIFI 5G

IEEE 802.11 WLAN 802.11a/n/ac/ax(20MHz channel bandwidth)
Mode Supported: 802.11n/ac/ax(40MHz channel bandwidth)
802.11ac/ax(80MHz channel bandwidth)

Operation Frequency: 5180-5240MHz for 802.11a/n(HT20)/ac(VHT20)/ax(HE20);
5190-5230MHz for 802.11n(HT40)/ac(VHT40)/ax(HE40);
5210MHz for 802.11 ac(VHT80)/ax(HE80);
5260-5320MHz for 802.11a/n(HT20)/ac(VHT20)/ax(HE20);
5270-5310MHz for 802.11n (HT40)/ac(VHT40)/ax(HE40);
5290MHz for 802.11 ac(VHT80)/ax(HE80);
5500-5700MHz for 802.11a/n(HT20)/ac(VHT20)/ax(HE20);
5410-5670MHz for 802.11n (HT40)/ac(VHT40)/ax(HE40);
5530-5610MHz for 802.11 ac(VHT80)/ax(HE80);
5745-5825 MHz for 802.11a/n(HT20)/ac(VHT20)/ax(HE20);
5755-5795 MHz for 802.11n(HT40)/ac(VHT40)/ax(HE40);
5775MHz for 802.11 ac(VHT80)/ax(HE80);

Data Rate: 802.11a: 6,9,12,18,24,36,48,54Mbps;
802.11n(HT20/HT40):MCS0-MCS15;
802.11ac(VHT20/VHT40/VHT80): NSS1, MCS0-MCS8
802.11ax(HE20/HE40/HE80):NSS1, MCS0-MCS9

Type of Modulation: OFDM with BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM for 802.11a/n/ac/ax;

Antenna installation: FPC antenna

Antenna Gain: 1.96 dBi
Remark:
☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information.
☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.

6.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

6.3 Support Equipment

Cable of Product

No.	Cable Type	Quantity	Provider	Length (m)	Shielded	Note
1	--	--	Applicant	---	Yes/No	--
2	--	--	BCTC	--	Yes/No	--

No.	Device Type	Brand	Model	Series No.	Note
1.	---	---	---	---	---
2.	--	--	--	--	--

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

6.4 Test Environment

1. Normal Test Conditions:

Humidity(%):	35-75
Atmospheric Pressure(kPa):	95-105
Temperature(°C):	18-25

2. Extreme Test Conditions:

N/A

7. Test Facility and Test Instrument Used

7.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850
A2LA certificate registration number is: CN1212
ISED Registered No.: 23583
ISED CAB identifier: CN0017

7.2 Test Instrument Used

Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
PC	DELL	\	\	N/A	N/A
Testing software	MVG	OpenSAR	V5.3.15.5	N/A	N/A
Measurement system	MVG	\	\	N/A	N/A
Signal Generator	Keysight	N5182B	MY56200519	May 16, 2025	May 15, 2026
Multimeter	Keithley	1160271	\	Nov 10, 2024	Nov 09, 2025
Network Analyzer	R&S	ZVB 8	101353	May 14, 2025	May 13, 2026
Wideband Radio Communication Tester	R&S	CMW500	\	Nov 10, 2024	Nov 09, 2025
E SAR PROBE 6GHz	MVG	SSE2	2623-EPGO-420	July 18, 2025	July 17, 2026
DIPOLE 2450	MVG	SID 2450	SN 47/21 DIP 2G450-627	Nov. 25, 2024	Nov. 24, 2027
DIPOLE 5000	MVG	SID 5000	SN 47/21 DIP 5G000-629	Nov. 25, 2024	Nov. 24, 2027
COMOSAR OPEN Coaxial Probe	SATIMO	\	\	Nov 18, 2024	Nov 17, 2025
SAR Locator	SATIMO	\	\	Nov 18, 2024	Nov 17, 2025
Communication Antenna	SATIMO	\	\	Nov 18, 2024	Nov 17, 2025
FEATURE PHONEPOSITIONING DEVICE	SATIMO	\	\	N/A	N/A
DUMMY PROBE	SATIMO	\	\	N/A	N/A
SAM Phantom	MVG	\	SN 13/09 SAM68	N/A	N/A
Liquid measurement Kit	HP	85033D	3423A08186	N/A	N/A
Power meter	Keysight	E4419	A00065	May 14, 2025	May 13, 2026
Power sensor	Keysight	E9300A	US39211659	May 14, 2025	May 13, 2026
Power sensor	Keysight	E9300A	US39211305	May 14, 2025	May 13, 2026
Directional Coupler	Krytar 158020	131467	\	N/A	N/A
Thermometer	BTE	\	\	N/A	N/A
Broad Band Tissue Simulation Liquid	Schmid	\	\	N/A	N/A

Note:

Per KDB865664D01 requirements for dipole calibration, the test laboratory has adopted three year extended calibration interval. Each measured dipole is expected to evaluate with following criteria at least on annual interval.

1. There is no physical damage on the dipole;
2. System check with specific dipole is within 10% of calibrated values;
3. The most recent return-loss results, measured at least annually, deviates by no more than 20% from the previous measurement;
4. The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 5Ω from the previous measurement.

8. Specific Absorption Rate (SAR)

8.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

8.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the

electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

9. SAR Measurement System

9.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.


9.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 26/23 EPG0420 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Tip Diameter: 5 mm
- Distance between probe tip and sensor center: 2.10mm
- Distance between sensor center and the inner phantom surface: 4 mm (repeatability better than +/- 1mm)
- Probe linearity: <0.25 dB
- Axial Isotropy: <0.25 dB
- Spherical Isotropy: <0.50 dB
- Calibration range: 835 to 2500MHz for head & body simulating liquid.

Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annex technique using reference guide at the five frequencies.



$$SAR = \frac{4(p_{fw} - p_{pbw})}{ab\delta} \cos^2 \left(\pi \frac{y}{a} \right) e^{(2\pi/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

δ = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N) = SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N) = V(N) * (1 + V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

9.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

$$SAR = C \frac{\Delta T}{\Delta t}$$

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

9.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

9.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005

10. Tissue Simulating Liquids

10.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	1,2-Propane diol (%)	HEC (%)	Preventol (%)	DGBE (%)
Head/Body						
835	40.3	1.4	57.9	0.2	0.2	0
900	40.3	1.4	57.9	0.2	0.2	0
1800-2000	55.2	0.3	0	0	0	44.5
2450	55.0	0.1	0	0	0	44.9
2600	54.9	0.1	0	0	0	45.0

Frequency (MHz)	Water (%)	Hexyl Carbitol (%)	Triton X-100 (%)
Head/Body			
5000-6000	65.52	17.24	17.24

10.2 Limit

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters

computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency (MHz)	Head	
	Conductivity (σ)	Permittivity (ϵ_r)
150	0.76	52.3
300	0.87	45.3
450	0.87	43.5
750	0.89	41.9
835	0.90	41.5
900	0.97	41.5
915	0.98	41.5
1450	1.20	40.5
1610	1.29	40.3
1800-2000	1.40	40.0
2450	1.80	39.2
2600	1.96	39.0
3000	2.40	38.5
5200	4.66	36.0
5400	4.86	35.8
5600	5.07	35.5
5800	5.27	35.3

10.3 Tissue Calibration Result


The dielectric parameters of the liquids were verified prior to the SAR evaluation using an R&S ZVB 8. Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Frequency (MHz)	Target		Measured		Deviation		Limit	Air (°C)	Date
	(σ)	(ϵ_r)	(σ)	(ϵ_r)	(σ)	(ϵ_r)			
2450	1.80	39.20	1.797	40.721	-0.17	3.88	±5	22.8	24/9/2025
5200	4.66	36.00	4.820	37.030	3.43	2.86	±5	22.8	24/9/2025
5400	4.86	35.80	4.897	36.556	0.76	2.11	±5	22.8	24/9/2025
5600	5.07	35.50	5.209	34.962	2.74	-1.52	±5	22.8	24/9/2025
5800	5.27	35.30	5.288	35.030	0.34	-0.76	±5	22.8	24/9/2025

Remark:

1. The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.
2. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.




11. System Check

11.1 Purpose of System Performance Check

At the device test frequencies. System check verifies the measurement repeatability of a SAR system before compliance testing and is not a validation of all system specifications. The latter is not required for testing a device but is mandatory before the system is deployed. The system check detects possible short-term drift and unacceptable measurement errors or uncertainties in the system.

11.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 600MHz-6000MHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The output power on dipole port must be calibrated to 20 dBm (100 mW) before dipole is connected.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

11.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. The following table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency (MHz)	Power	Measured SAR _{1g} (W/Kg)	Measured Normalized	Target Normalized	Drift	Limit	Liquid (°C)	Date
2450	100mW	5.549	55.486	55.16	0.59	±10	23.1	24/9/2025
5200	100mW	7.805	78.045	76.41	2.14	±10	23.1	24/9/2025
5400	100mW	8.132	81.317	80.52	0.99	±10	23.1	24/9/2025
5600	100mW	8.079	80.785	79.08	2.16	±10	23.1	24/9/2025
5800	100mW	7.337	73.368	76.49	-4.08	±10	23.1	24/9/2025


12. EUT Testing Position

Body Position

A typical example of a body supported device is a wireless enabled laptop device that among other orientations may be supported on the thighs of a sitting user. To represent this orientation, the device shall be positioned with its base against the flat phantom. Other orientations may be specified by the manufacturer in the user instructions. If the intended use is not specified, the device shall be tested directly against the flat phantom in all usable orientations.

The example shows a tablet form factor portable computer for which SAR should be separately assessed with

- each surface and
- the separation distances



Tablet form factor portable computer

13. SAR Measurement Procedures

13.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex D demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement


13.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g



13.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 mm $\pm$ 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm $\pm$ 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° $\pm$ 1°	20° $\pm$ 1°
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

13.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

13.5 SAR Averaged Methods


The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

13.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.



TE
TO
OVB
t See

14. SAR Test Result

14.1 Conducted RF Output Power

Bluetooth			
Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)
1-DH1	2402	-0.67	-0.5
1-DH1	2441	-1.09	
1-DH1	2480	-1.52	
2-DH1	2402	-1.66	-1.5
2-DH1	2441	-2.06	
2-DH1	2480	-2.42	
3-DH1	2402	-1.24	-1.0
3-DH1	2441	-1.74	
3-DH1	2480	-2.13	
GFSK(1Mbps)	2402	-0.17	0.0
GFSK(1Mbps)	2440	-0.56	
GFSK(1Mbps)	2480	-1.01	
GFSK(1Mbps)	2402	-0.15	0.0
GFSK(1Mbps)	2440	-0.56	
GFSK(1Mbps)	2480	-0.98	

Note:

Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq 50\text{mm}$ are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^{1/2} \times f(\text{GHz})$

≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation


The result is rounded to one decimal place for comparison

Turn-up Power (dBm)	Turn-up Power (mW)	Separation Distance (mm)	Frequency (GHz)	Result	Exclusion Thresholds
0.0	1.00	5.0	2.480	0.31	3.0

Per KDB 447498 D01v06, when the minimum test separation distance is $< 5\text{ mm}$, a distance of 5 mm is applied to determine SAR test exclusion.


According to the calculation results in the table above, Bluetooth SAR does not need to be tested.

WIFI 2.4G			
Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)
802.11b	2412	14.32	15.5
802.11b	2437	15.17	
802.11b	2462	15.43	
802.11g	2412	13.54	15.5
802.11g	2437	15.08	
802.11g	2462	14.84	
802.11n20	2412	13.28	15.0
802.11n20	2437	14.69	
802.11n20	2462	14.58	
802.11n40	2422	12.86	15.0
802.11n40	2437	14.54	
802.11n40	2452	14.58	
802.11ax20	2412	13.53	15.5
802.11ax20	2437	15.43	
802.11ax20	2462	15.30	
802.11ax40	2422	12.91	14.5
802.11ax40	2437	14.27	
802.11ax40	2452	14.32	



WIFI 5.1G			
Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)
802.11a	5180	11.89	13.0
802.11a	5200	11.71	
802.11a	5240	12.84	
802.11n20	5180	9.91	12.0
802.11n20	5200	10.38	
802.11n20	5240	11.57	
802.11n40	5190	9.72	10.0
802.11n40	5230	9.22	
802.11ac20	5180	9.70	11.5
802.11ac20	5200	10.41	
802.11ac20	5240	11.45	
802.11ac40	5190	9.20	11.0
802.11ac40	5230	10.53	
802.11ac80	5210	9.71	10.0
802.11ax20	5180	9.66	11.5
802.11ax20	5200	10.14	
802.11ax20	5240	11.19	
802.11ax40	5190	9.30	11.0
802.11ax40	5230	10.66	
802.11ax80	5210	9.32	9.5

WIFI 5.3G			
Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)
802.11a	5260	11.44	13.0
802.11a	5280	12.11	
802.11a	5320	12.99	
802.11n20	5260	10.86	11.0
802.11n20	5280	10.08	
802.11n20	5320	10.07	
802.11n40	5270	9.07	9.5
802.11n40	5310	9.16	
802.11ac20	5260	9.67	10.5
802.11ac20	5280	10.18	
802.11ac20	5320	10.13	
802.11ac40	5270	9.22	9.5
802.11ac40	5310	9.03	
802.11ac80	5290	9.50	10.0
802.11ax20	5260	9.65	10.5
802.11ax20	5280	9.90	
802.11ax20	5320	10.01	
802.11ax40	5270	9.36	10.0
802.11ax40	5310	9.82	
802.11ax80	5290	9.74	10.0




WIFI 5.6G			
Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)
802.11a	5500	12.25	12.5
802.11a	5580	12.23	
802.11a	5700	10.78	
802.11n20	5500	11.99	12.5
802.11n20	5580	12.07	
802.11n20	5700	10.64	
802.11n40	5510	10.08	10.5
802.11n40	5550	9.96	
802.11n40	5670	8.19	
802.11ac20	5500	11.66	12.0
802.11ac20	5580	11.99	
802.11ac20	5700	10.63	
802.11ac40	5510	9.95	10.0
802.11ac40	5550	9.91	
802.11ac40	5670	9.50	
802.11ac80	5530	9.22	9.5
802.11ax20	5500	11.42	12.5
802.11ax20	5580	12.06	
802.11ax20	5700	10.49	
802.11ax40	5510	8.86	9.0
802.11ax40	5550	8.59	
802.11ax40	5670	7.98	
802.11ax80	5530	10.13	10.5

BCTC
 BCTC
 PPR
 Report

WIFI 5.8G			
Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)
802.11a	5745	12.63	13.0
802.11a	5785	12.39	
802.11a	5825	12.11	
802.11n20	5745	12.07	12.5
802.11n20	5785	12.19	
802.11n20	5825	12.04	
802.11n40	5755	10.39	11.0
802.11n40	5795	10.56	
802.11ac20	5745	10.90	11.5
802.11ac20	5785	11.32	
802.11ac20	5825	11.16	
802.11ac40	5755	10.64	11.0
802.11ac40	5795	10.55	
802.11ac80	5775	9.44	9.5
802.11ax20	5745	10.92	11.5
802.11ax20	5785	11.30	
802.11ax20	5825	10.82	
802.11ax40	5755	10.35	11.0
802.11ax40	5795	10.53	
802.11ax80	5775	9.45	9.5

14.2 Transmit Antennas and SAR Measurement Position

EUT Back view Antenna Location:



Distance of The Antenna to the EUT surface and edge (mm)						
Antennas	Front	Back	Top Side	Bottom Side	Left Side	Right Side
WIFI	<25	<25	<25	144	50	132

Positions for SAR tests; Body mode						
Antennas	Front	Back	Top Side	Bottom Side	Left Side	Right Side
WIFI	Yes	Yes	Yes	No	No	No

Note: For details, please refer to the test photo.

14.3 Measured and Reported (Scaled) SAR Results

WIFI 2.4G								
RF Exposure Conditions	Mode	Test Position	Freq. (MHz)	Power (dBm)		SAR _{1g} (W/kg)		Plot No.
				Meas.	Turn-up	Meas.	Scaled	
Body (5mm)	802.11b	Front Face	2462	15.43	15.5	0.357	0.363	
	802.11b	Back Face	2462	15.43	15.5	0.687	0.698	1
	802.11b	Top Side	2462	15.43	15.5	0.671	0.682	

WIFI 5.1G								
RF Exposure Conditions	Mode	Test Position	Freq. (MHz)	Power (dBm)		SAR _{1g} (W/kg)		Plot No.
				Meas.	Turn-up	Meas.	Scaled	
Body (5mm)	802.11a	Front Face	5240	12.84	13.0	0.431	0.447	
	802.11a	Back Face	5240	12.84	13.0	0.600	0.623	
	802.11a	Top Side	5240	12.84	13.0	0.891	0.924	2
	802.11a	Top Side	5180	11.89	13.0	0.709	0.915	
	802.11a	Top Side	5200	11.71	13.0	0.653	0.879	

WIFI 5.3G								
RF Exposure Conditions	Mode	Test Position	Freq. (MHz)	Power (dBm)		SAR _{1g} (W/kg)		Plot No.
				Meas.	Turn-up	Meas.	Scaled	
Body (5mm)	802.11a	Front Face	5320	12.99	13.0	0.130	0.130	
	802.11a	Back Face	5320	12.99	13.0	1.107	1.110	3
	802.11a	Top Side	5320	12.99	13.0	0.647	0.648	
	802.11a	Back Face	5260	11.44	13.0	0.702	1.005	
	802.11a	Back Face	5280	12.11	13.0	0.806	0.989	

WIFI 5.6G								
RF Exposure Conditions	Mode	Test Position	Freq. (MHz)	Power (dBm)		SAR _{1g} (W/kg)		Plot No.
				Meas.	Turn-up	Meas.	Scaled	
Body (5mm)	802.11a	Front Face	5500	12.25	12.5	0.465	0.493	
	802.11a	Back Face	5500	12.25	12.5	0.627	0.664	4
	802.11a	Top Side	5500	12.25	12.5	0.330	0.350	

WIFI 5.8G								
RF Exposure Conditions	Mode	Test Position	Freq. (MHz)	Power (dBm)		SAR _{1g} (W/kg)		Plot No.
				Meas.	Turn-up	Meas.	Scaled	
Body (5mm)	802.11a	Front Face	5745	12.63	13.0	0.408	0.444	
	802.11a	Back Face	5745	12.63	13.0	0.667	0.726	
	802.11a	Top Side	5745	12.63	13.0	0.757	0.824	5

14.4 SAR Measurement Variability

According to KDB865664, Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR value of the initial repeated measurement is < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. A second repeated measurement is required only if the measured result for the initial repeated measurement is within 10% of the SAR limit and vary by more than 20%, which are often related to device and measurement setup difficulties. The following procedures are applied to determine if repeated measurements are required. The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.¹⁹ The repeated measurement results must be clearly identified in the SAR report. All measured SAR, including the repeated results, must be considered to determine compliance and for reporting according to KDB 690783. Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 3) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Test Mode	Frequency (MHz)	RF Exposure Configuration	Test Position	Repeated SAR (yes/no)	Highest Measured SAR1-g (W/Kg)	First Repeated	
						Measured SAR1-g (W/Kg)	Largest to Smallest SAR Ratio
WIFI 5.1G	5240	Top Side	Body	Yes	0.891	0.839	1.062
WIFI 5.3G	5320	Back Face	Body	Yes	1.107	1.009	1.097
WIFI 5.3G	5280	Back Face	Body	Yes	0.806	0.770	1.047

14.5 Simultaneous Transmission Evaluation

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

Application Simultaneous Transmission information:

No.	Configurations	Body SAR
1	WWAN + Bluetooth	No
2	WWAN + WIFI	No
3	WIFI + Bluetooth	Yes

Remark:

- EUT does not have the WWAN function.
- According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)/x] W/kg for test separation distances ≤ 50 mm; where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
 - 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

Estimated stand alone SAR					
Mode	Maximum Power (dBm)	Maximum Power (mW)	Separation Distance (mm)	X	Estimated SAR1-g (W/kg)
Bluetooth	0.0	1.00	5.0	7.5	0.042

Note:

- Maximum average power including tune-up tolerance;
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion
- Per FCC KD B447498 D01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the transmitting antenna in a specific a physical test configuration is ≤1.6 W/Kg. When the sum is greater than the SAR limit, SAR test exclusion is determined by the SAR to peak location separation ratio.

$$\text{Ratio} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{(\text{peak location separation, mm})} < 0.04$$

- Simultaneous transmission of maximum SAR sum calculation.

RF Exposure Conditions	Scaled SAR _{1g} (W/kg)		Summed SAR _{1g} (W/kg)	Limit SAR _{1g} (W/kg)
	Bluetooth	WIFI		
Body (5mm)	0.042	1.110	1.152	1.6

15. Test Plots

15.1 System Performance Check

System check at 2450 MHz

Date of measurement: 24/9/2025


A. Experimental conditions.

Probe	SN 26/23 EPGO420
ConvF	1.11
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=8mm dy=8mm dz=5.0mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	CW

B. Permittivity

Frequency (MHz)	2450.000
Relative permittivity (real part)	40.721
Relative permittivity (imaginary part)	14.330
Conductivity (S/m)	1.797

C. SAR Surface and Volume




Maximum location: X=-3.00, Y=1.00 ; SAR Peak: 9.50 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.390
SAR 1g (W/Kg)	5.549
Variation (%)	0.269
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	61.752849

E. Z Axis Scan

Z (mm)	0.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00
SAR (W/Kg)	9.380	5.078	3.712	2.709	2.001	1.499	1.138	0.871	0.667



F. 3D Image



System check at 5200 MHz

Date of measurement: 24/9/2025


A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	0.97
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Signal	CW

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	37.030
Relative permittivity (imaginary part)	18.140
Conductivity (S/m)	4.820

C. SAR Surface and Volume




Maximum location: X=5.00, Y=0.00 ; SAR Peak: 30.79 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.306
SAR 1g (W/Kg)	7.805
Variation (%)	2.562
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	44.519682

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	29.452	16.989	9.130	4.585	2.232	1.083	0.552	0.315	0.209



F. 3D Image



CO., LTD

System check at 5400 MHz


Date of measurement: 24/9/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.17
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Signal	CW

B. Permittivity


Frequency (MHz)	5400.000
Relative permittivity (real part)	36.556
Relative permittivity (imaginary part)	18.300
Conductivity (S/m)	4.897

C. SAR Surface and Volume

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.340
SAR 1g (W/Kg)	8.132
Variation (%)	2.250
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	52.381274

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	32.476	18.686	10.034	5.088	2.563	1.347	0.796	0.566	0.487



F. 3D Image



System check at 5600 MHz


Date of measurement: 24/9/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.20
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Signal	CW

B. Permittivity

Frequency (MHz)	5600.000
Relative permittivity (real part)	34.962
Relative permittivity (imaginary part)	18.460
Conductivity (S/m)	5.209

C. SAR Surface and Volume



Maximum location: X=1.00, Y=0.00 ; SAR Peak: 31.08 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.394
SAR 1g (W/Kg)	8.079
Variation (%)	2.318
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	53.992195

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	30.005	17.140	9.077	4.467	2.119	0.999	0.495	0.280	0.189



F. 3D Image



System check at 5800 MHz


Date of measurement: 24/9/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.05
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Signal	CW

B. Permittivity

Frequency (MHz)	5800.000
Relative permittivity (real part)	35.030
Relative permittivity (imaginary part)	18.620
Conductivity (S/m)	5.288

C. SAR Surface and Volume



Maximum location: X=5.00, Y=0.00 ; SAR Peak: 28.22 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	2.075
SAR 1g (W/Kg)	7.337
Variation (%)	0.132
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	51.802513

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	26.852	14.914	7.581	3.559	1.627	0.770	0.423	0.303	0.288



F. 3D Image



CO., LTD

15.2 SAR Test Graph Results

Plot 1

Date of measurement: 24/9/2025


A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.11
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm
Phantom	Validation plane
Device Position	Body
Band	WIFI 2.4G
Signal	802.11b

B. Permittivity

Frequency (MHz)	2462.000
Relative permittivity (real part)	40.721
Relative permittivity (imaginary part)	13.207
Conductivity (S/m)	1.797

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.279
SAR 1g (W/Kg)	0.687
Variation (%)	2.270
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	63.992195

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.370	0.791	0.376	0.175	0.086



F. 3D Image



Plot 2


Date of measurement: 27/8/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.18
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Body
Band	WIFI5.1G
Signal	802.11a

B. Permittivity

Frequency (MHz)	5240.000
Relative permittivity (real part)	37.030
Relative permittivity (imaginary part)	16.130
Conductivity (S/m)	4.820

C. SAR Surface and Volume



Maximum location: X=-6.00, Y=24.00 ; SAR Peak: 2.88 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.272
SAR 1g (W/Kg)	0.891
Variation (%)	3.360
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	41.802513

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	2.958	1.614	0.812	0.284	0.135	0.009	0.001	0.002	0.011



F. 3D Image



Plot 3


Date of measurement: 24/9/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.18
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Body
Band	WIFI5.3G
Signal	802.11a

B. Permittivity

Frequency (MHz)	5320.000
Relative permittivity (real part)	36.556
Relative permittivity (imaginary part)	16.158
Conductivity (S/m)	4.897

C. SAR Surface and Volume



Maximum location: X=-5.00, Y=-13.00 ; SAR Peak: 3.99 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.303
SAR 1g (W/Kg)	1.107
Variation (%)	-3.100
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	46.014016

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	4.329	2.302	1.226	0.304	0.006	0.027	0.102	0.120	0.018



F. 3D Image



CO., LTD

Plot 4


Date of measurement: 24/9/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.20
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Body
Band	WIFI5.6G
Signal	802.11a

B. Permittivity

Frequency (MHz)	5500.000
Relative permittivity (real part)	34.962
Relative permittivity (imaginary part)	16.300
Conductivity (S/m)	5.209

C. SAR Surface and Volume



Maximum location: X=8.00, Y=-22.00 ; SAR Peak: 2.29 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.163
SAR 1g (W/Kg)	0.627
Variation (%)	1.780
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	47.094416

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	2.235	1.283	0.654	0.304	0.087	0.026	0.001	0.001	0.034



F. 3D Image



Plot 5


Date of measurement: 24/9/2025

A. Experimental conditions.

Probe	SN 26/23 EPG0420
ConvF	1.15
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm
Phantom	Validation plane
Device Position	Body
Band	WIFI5.8G
Signal	802.11a

B. Permittivity

Frequency (MHz)	5745.000
Relative permittivity (real part)	35.030
Relative permittivity (imaginary part)	16.355
Conductivity (S/m)	5.288

C. SAR Surface and Volume



Maximum location: X=-5.00, Y=-12.00 ; SAR Peak: 2.39 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.219
SAR 1g (W/Kg)	0.757
Variation (%)	2.000
Horizontal validation criteria: minimum distance (mm)	4.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	50.88313

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	2.394	1.444	0.816	0.438	0.232	0.083	0.100	0.028	0.040




F. 3D Image



16 CALIBRATION CERTIFICATES

Probe-EPGO420 Calibration Certificate
SID2450Dipole Calibration Certificate
SID2600Dipole Calibration Certificate



**COMOSAR E-Field Probe Calibration Report**

Ref : ACR.199.1.25.BES.A

SHENZHEN BCTC TECHNOLOGY CO., LTD.
1 ~2/ F, NO. B FACTORY BUILDING, PENGZHOU
INDUSTRIAL PARK, FUYUAN 1ST ROAD,
TANGWEI COMMUNITY, FUHAI STREET, BAO'AN
DISTRICT, SHENZHEN, GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: 2623-EPGO-420

Calibrated at MVG
Z.I. de la pointe du diable
Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 7/18/2025



Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).

Page: 1/11


COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.199.1.25.BES.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Cyrille ONNEE	Measurement Responsible	7/18/2025	
<i>Checked & approved by:</i>	Jérôme Luc	Technical Manager	7/18/2025	
<i>Authorized by:</i>	Yann Toutain	Laboratory Director	7/18/2025	

Yann
Toutain ID

Signature numérique
de Yann Toutain ID
Date : 2025.07.18
10:38:49 +02'00'

	<i>Customer Name</i>
<i>Distribution :</i>	Shenzhen BCTC Technology Co., Ltd.

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Cyrille ONNEE	7/18/2025	Initial release

Page: 2/11

Template: ACR.DDD-N.TY.MVGB.ISSUE - COMOSAR Probe vE

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Sensitivity	4
3.2	Linearity	5
3.3	Isotropy	5
3.4	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Results	6
5.1	Calibration in air	6
5.2	Calibration in liquid	7
6	Verification Results	9
7	List of Equipment	10



1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	2623-EPGO-420
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-7.5GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.228 MΩ Dipole 2: R2=0.238 MΩ Dipole 3: R3=0.230 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – *MVG COMOSAR Dosimetric E field Probe*

Probe Length	330 mm
Length of Individual Dipoles	24.5 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.55 mm
Distance between dipoles / probe extremity	12.7 mm

3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their effect. All calibrations / measurements performed meet the fore-mentioned standards.

3.1 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards for frequency range 600-7500MHz and using the calorimeter cell method (transfer method) as outlined in the standards for frequency 150-450 MHz.



3.2 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01 W/kg to 100 W/kg.

3.3 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.4 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \pm SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta} - e^{-(d_{be} + d_{step})/\delta})}{\delta/2} \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

The measured worst case boundary effect $SAR_{uncertainty}[\%]$ for scanning distances larger than 4mm is 1.0% Limit, 2%).



4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty associated with a SAR probe calibration using the waveguide or calorimetric cell technique depending on the frequency.

The estimated expanded uncertainty (k=2) in calibration for SAR (W/kg) is +/-11% for the frequency range 150-450MHz.


The estimated expanded uncertainty (k=2) in calibration for SAR (W/kg) is +/-14% for the frequency range 600-7500MHz.

5 CALIBRATION RESULTS

Ambient condition	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 CALIBRATION IN AIR

The following curve represents the measurement in waveguide of the voltage picked up by the probe toward the E-field generated inside the waveguide.



From this curve, the sensitivity in air is calculated using the below formula.

$$E^2 = \sum_{i=1}^3 \frac{V_i (1 + V_i / DCP_i)}{Norm_i}$$

where

V_i =voltage readings on the 3 channels of the probe

DCP_i =diode compression point given below for the 3 channels of the probe

$Norm_i$ =dipole sensitivity given below for the 3 channels of the probe


COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.199.1.25.BES.A

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
1.21	1.09	1.56

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
106	109	103

5.2 CALIBRATION IN LIQUID

The calorimeter cell or the waveguide is used to determine the calibration in liquid using the formula below.

$$ConvF = \frac{E_{liquid}^2}{E_{air}^2}$$

The E-field in the liquid is determined from the SAR measurement according to the below formula.

$$E_{liquid}^2 = \frac{\rho SAR}{\sigma}$$

where

σ =the conductivity of the liquid

ρ =the volumetric density of the liquid

SAR=the SAR measured from the formula that depends on the setup used. The SAR formulas are given below

For the calorimeter cell (150-450 MHz), the formula is:

$$SAR = c \frac{dT}{dt}$$

where

c =the specific heat for the liquid

dT/dt =the temperature rises over the time

For the waveguide setup (600-75000 MHz), the formula is:

$$SAR = \frac{4P_{1W}}{ab\delta} e^{-\frac{2z}{\delta}}$$

where

a =the larger cross-sectional of the waveguide

b =the smaller cross-sectional of the waveguide

δ =the skin depth for the liquid in the waveguide

P_{1W} =the power delivered to the liquid

Page: 7/11

Template_ACR.BDD-N.TE.MVG.U.ISSUE_COMOSAR_Probe.v1.

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.199.1.25.BES.A

The below table summarize the ConvF for the calibrated liquid. The curves give examples for the measured SAR depending on the voltage in some liquid.

Liquid	Frequenc y (MHz*)	ConvF
HL450	450	0.86
BL450	450	0.78
HL750	750	0.80
BL750	750	0.87
HL850	835	0.81
BL850	835	0.80
HL900	900	0.76
BL900	900	0.87
HL1800	1800	0.96
BL1800	1800	1.01
HL1900	1900	1.04
BL1900	1900	1.11
HL2100	2100	1.00
BL2100	2100	1.16
HL2300	2300	1.11
BL2300	2300	1.23
HL2450	2450	1.11
BL2450	2450	1.32
HL2600	2600	1.03
BL2600	2600	1.19
HL5200	5200	1.18
BL5200	5200	0.97
HL5400	5400	1.17
BL5400	5400	1.00
HL5600	5600	1.20
BL5600	5600	0.95
HL5800	5800	1.15
BL5800	5800	1.05

(*) Frequency validity is +/-50MHz below 600MHz, +/-100MHz from 600MHz to 6GHz and +/-700MHz above 6GHz






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.199.1.25.BES.A

6 VERIFICATION RESULTS

The figures below represent the measured linearity and axial isotropy for this probe. The probe specification is ± 0.2 dB for linearity and ± 0.15 dB for axial isotropy.





7 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
CALIPROBE Test Bench	Version 2	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	08/2024	08/2027
Network Analyzer	Agilent 8753ES	MY40003210	10/2023	10/2027
Network Analyzer – Calibration kit	HP 85033D	3423A08186	06/2021	06/2027
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	07/2025	07/2028
Multimeter	Keithley 2000	4013982	02/2023	02/2026
Signal Generator	Rohde & Schwarz SMB	106589	03/2025	03/2028
Amplifier	MVG	MODU-023-C-0002	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	06/2024	06/2027
Power Meter	Keysight U2000A	SN: MY62340002	10/2022	10/2025
Directional Coupler	Krytar 158020	131467	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Fluoroptic Thermometer	LumaSense Luxtron 812	94264	09/2022	09/2025
Coaxial cell	MVG	SN 32/16 COAXCELL_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG2_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_0G600_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG4_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_0G900_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG6_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_1G500_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG8_1	Validated. No cal required.	Validated. No cal required.

Page: 10/11

Template: ACR.DDD-N.TY.MVG.U.ISSUE: COMOSAR Probe vE

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.


COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.199.1.25.BES.A

Liquid transition	MVG	SN 32/16 WGLIQ_1G800B_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_1G800H_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG10_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_3G500_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG12_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_5G000_	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG14_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_7G000_1	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44225320	06/2024	06/2027

Page: 11/11

Template ACR.DDD-N.YE.MVGB.ISSUE COMOSAR Probe vE.

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR Reference Dipole Calibration Report

Ref : ACR.329.15.24.BES.A

SHENZHEN BCTC TECHNOLOGY CO., LTD.

**1 ~2/ F, NO. B FACTORY BUILDING, PENGZHOU
INDUSTRIAL PARK, FUYUAN 1ST ROAD,
TANGWEI COMMUNITY, FUHAI STREET, BAO'AN
DISTRICT, SHENZHEN, GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE**

FREQUENCY: 2450 MHZ

SERIAL NO.: SN 47/21 DIP 2G450-627

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 11/25/2024



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.

Page: 1/13


SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.329.15.24.BES.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme Luc	Technical Manager	11/25/2024	
<i>Checked by :</i>	Jérôme Luc	Technical Manager	11/25/2024	
<i>Approved by :</i>	Yann Toutain	Laboratory Director	11/25/2024	 2024.11.25 11:56:55 +01'00'

	<i>Customer Name</i>
<i>Distribution :</i>	Shenzhen BCTC Technology Co., Ltd.

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Jérôme Luc	11/25/2024	Initial release

Page: 2/13

Template: ACR.DDD.N.YY.MVGB-ISSUE - SAR Reference Dipole v1

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.

CO.LTD



TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	7
7	Validation measurement	7
7.1	Head Liquid Measurement	8
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	11
7.4	SAR Measurement Result With Body Liquid	12
8	List of Equipment	13



1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 2450 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID2450
Serial Number	SN 47/21 DIP 2G450-627
Product Condition (new / used)	New

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

Page: 4/13

Template ACR.DDD.N.YY.MVGB.ISSUE SAR Reference Dipole vJ

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.