

TEST REPORT

Product : Tablet
Trade mark : N/A
Model/Type reference : X7, X7L, X6, X6L, X6PRO,
X6PROL, X8, X8L, X9, X9L,
X9PRO, X9PROL
Serial Number : N/A
Report Number : EED32S80471104
FCC ID : 2AW9M-X7
Date of Issue : Apr. 23, 2026
Test Standards : 47 CFR Part 15 Subpart E
Test result : PASS


Prepared for:

Shenzhen Efercro Electronic Technology Co., Ltd.
Room 901, Block E, Building 1, Section 1, Chuangzhi Yuncheng,
Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen

Prepared by:


Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:



Win Wei

Reviewed by:



Keven Tan

Approved by:



Aaron Ma

Date:

Apr. 23, 2026



Check No.: 7833110326

1 Content

1 CONTENT	2
2 TEST SUMMARY	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 TEST ENVIRONMENT	7
3.4 DESCRIPTION OF SUPPORT UNITS	8
3.5 TEST LOCATION	8
3.6 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
4 EQUIPMENT LIST	9
5 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	13
5.1 ANTENNA REQUIREMENT	13
5.2 AC POWER LINE CONDUCTED EMISSIONS	14
5.3 MAXIMUM CONDUCTED OUTPUT POWER	19
5.4 6dB EMISSION BANDWIDTH	20
5.5 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	21
5.6 MAXIMUM POWER SPECTRAL DENSITY	22
5.7 FREQUENCY STABILITY	23
5.8 RADIATED EMISSION	24
5.9 RADIATED EMISSION WHICH FALL IN THE RESTRICTED BANDS	134
6 APPENDIX A	265
7 PHOTOGRAPHS	266

2 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	PASS
Duty Cycle	47 CFR Part 15 Subpart E Section 15.407	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
26dB Emission Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
99% Occupied Bandwidth	\	PASS
6dB Emission Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (e)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	PASS
Radiated Emissions	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS
Radiated Emissions which fall in the restricted bands	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS

3 General Information

3.1 Client Information

Applicant:	Shenzhen Efercro Electronic Technology Co., Ltd.
Address of Applicant:	Room 901, Block E, Building 1, Section 1, Chuangzhi Yuncheng, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen
Manufacturer:	Shenzhen Efercro Electronic Technology Co., Ltd.
Address of Manufacturer:	Room 901, Block E, Building 1, Section 1, Chuangzhi Yuncheng, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen

3.2 General Description of EUT

Product Name:	Tablet
Model No.:	X7, X7L, X6, X6L, X6PRO, X6PROL, X8, X8L, X9, X9L, X9PRO, X9PROL
Test Model No.:	X7
Model difference:	They have the same electrical circuit design, layout, components used and internal wiring, only the model names and color are different for marketing requirements.
Trade mark:	N/A
EUT Function:	☐ Outdoor AP ☐ Indoor AP ☐ Fixed P2P AP ☒ Indoor
Type of Modulation:	IEEE 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11n(HT20/HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac(VHT20/VHT40/VHT80): OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) IEEE 802.11ax(HE20/HE40/HE80): OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Operating Frequency	U-NII-1 & U-NII-2A: 5150-5350MHz U-NII-2C: 5500-5700MHz U-NII-3: 5745-5825MHz
Weather Band	☒ With 5600-5650MHz ☐ Without 5600-5650MHz
DFS (Dynamic Frequency Selection) Operational mode:	☐ Master ☒ Slaver without radar detection ☐ Slaver with radar detection
TPC Function	☒ With TPC Function ☐ Without TPC Function
Antenna Configuration:	☒ Single Transmitting; ☐ MIMO (☐ 2T2R, ☐ 3T3R, ☐ 4T4R, ☐ Other);
Antenna Type:	FPC antenna
Antenna Gain:	2.45dBi
Power Supply:	Adapter: Input: AC 100V-240V 50-60Hz 0.4A Max Output: DC 5.0V 2A(10.0W)
	Battery: DC3.8V
	USB Port: DC 5V
Test voltage:	DC 5V
Sample Received Date:	Mar. 11, 2026
Sample tested Date:	Mar. 11, 2026 to Apr. 08, 2026

Operation Frequency each of channel

802.11a/802.11n/802.11ac(20MHz)/802.11ax(20MHz) Frequency/Channel Operations:

U-NII-1		U-NII-2A		U-NII-2C		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
-	-	-	-	116	5580	165	5825
-	-	-	-	120	5600	-	-
-	-	-	-	124	5620	-	-
-	-	-	-	128	5640	-	-
-	-	-	-	132	5660	-	-
-	-	-	-	136	5680	-	-
-	-	-	-	140	5700	-	-

802.11n/802.11ac(40MHz)/802.11ax(40MHz) Frequency/Channel Operations:

U-NII-1		U-NII-2A		U-NII-2C		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
-	-	-	-	118	5590	-	-
-	-	-	-	126	5630	-	-
-	-	-	-	134	5670	-	-

802.11ac(80MHz)/802.11ax(80MHz) Frequency/Channel Operations:

U-NII-1		U-NII-2A		U-NII-2C		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
42	5210	58	5290	106	5530	155	5775
-	-	-	-	122	5610	-	-

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test.

Test Configuration

EUT Test Software Settings:	
Software:	ADB
EUT Power Grade:	Default
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ac(VHT20)	MCS0
802.11ac(VHT40)	MCS0
802.11ac(VHT80)	MCS0
802.11ax(HE20)	MCS0
802.11ax(HE40)	MCS0
802.11ax(HE80)	MCS0

3.3 Test Environment

Operating Environment:		
Radiated Spurious Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Conducted Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
RF Conducted:		
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Temperature:	NT (Normal Temperature)	22~25.0 °C
	LT (Low Temperature)	0 °C
	HT (High Temperature)	45 °C
Working Voltage of the EUT:	NV (Normal Voltage)	3.8 V
	LV (Low Voltage)	3.5 V
	HV (High Voltage)	5 V

3.4 Description of Support Units

The EUT has been tested independently.

3.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164, Test Firm Registration No.: 260439

3.6 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

4 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Spectrum Analyzer	Keysight	N9010A	MY54510339	11-25-2025	11-24-2026
Spectrum Analyzer	R&S	FSW43	102978	08-11-2025	08-10-2026
Signal Generator	Keysight	N5182B	MY53051549	11-13-2025	11-12-2026
Signal Generator	Agilent	N5181A	MY46240094	11-25-2025	11-24-2026
DC Power	Keysight	E3642A	MY56376072	11-13-2025	11-12-2026
Communication test set	R&S	CMW500	169004	03-03-2025 02-06-2026	03-02-2026 02-05-2027
RF control unit(power unit)	JS Tonscend	JS0806-2	24I80620925	07-21-2025	07-20-2026
Wi-Fi 7GHz Band Extender	JS Tonscend	TS-WF7U2	2206200002	05-12-2025	05-11-2026
high-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-13-2025	11-12-2026
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-26-2025	05-25-2026
BT&WI-FI Automatic test software	JS Tonscend	JS1120-3	V3.6.21	---	---
Digital multimeter	FLUKE	17B MAX	59545050WS	10-15-2025	10-14-2026

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-08-2025 04-06-2026	04-07-2026 04-05-2027
Temperature/ Humidity Indicator	Defu	TH128	/	03-31-2025 03-24-2026	03-30-2026 03-23-2027
LISN	R&S	ENV216	100098	09-13-2025	09-12-2026
Barometer	changchun	DYM3	1188	---	---
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---
Capacitive voltage probe	Schwarzbeck	CVP 9222C	00124	06-07-2025	06-06-2026
ISN	TESEQ	ISN T800	30297	11-24-2025	11-23-2026

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	01/13/2024	01/12/2027
Receiver	R&S	ESCI7	100938-003	09/03/2025	09/02/2026
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/14/2025	05/13/2026
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04/07/2025 03-29-2026	04/06/2026 03-28-2027
Microwave Preamplifier	Tonscend	EMC051845SE	980380	11/25/2025	11/24/2026
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023	07/01/2026
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/07/2025 03-31-2026	04/06/2026 03-30-2027
Preamplifier	Agilent	11909A	12-1	03/03/2025 02/06/2026	03/02/2026 02/07/2027
Preamplifier	CD	PAP-1840-60	6041.6042	05/26/2025	05/25/2026
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	01/13/2024	01/12/2027
Cable line	Fulai(6M)	SF106	5220/6A	01/13/2024	01/12/2027
Cable line	Fulai(3M)	SF106	5216/6A	01/13/2024	01/12/2027
Cable line	Fulai(3M)	SF106	5217/6A	01/13/2024	01/12/2027


3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-29-2024	01-28-2027
Receiver	Keysight	N9038A	MY57290136	12-22-2025	12-21-2026
Spectrum Analyzer	Keysight	N9020B	MY57111112	12-21-2025	12-20-2026
Spectrum Analyzer	Keysight	N9030B	MY57140871	12-21-2025	12-20-2026
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-12-2025 03-29-2026	04-11-2026 03-28-2027
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-12-2025 03-29-2026	04-11-2026 03-28-2027
Horn Antenna	ETS-LINDGREN	3117	57407	06-29-2025	06-28-2026
Preamplifier	EMCI	EMC001330	980563	03-03-2025 02-06-2026	03-02-2026 02-05-2027
Preamplifier	EMCI	EMC051845SE	980380	11-25-2025	11-24-2026
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-07-2025	07-06-2026
Communication test set	R&S	CMW500	104466	11-25-2025	11-24-2026
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	03-31-2025 03-24-2026	03-30-2026 03-23-2027
RSE Automatic test software	JS Tonscend	JS36-RSE	V5.0.0.1	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	01-29-2024	01-28-2027
Cable line	Times	EMC104-NMNM-1000	SN160710	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	01-29-2024	01-28-2027
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	01-29-2024	01-28-2027
Cable line	Times	HF160-KMKM-3.00M	393493-0001	01-29-2024	01-28-2027

5 Radio Technical Requirements Specification

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	Please see Internal photos
The antenna is FPC antenna. The best case gain of the antenna is 2.45dBi.	


5.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10-2020		
Test Frequency Range:	150kHz to 30MHz		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Setup:			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2020 on conducted measurement.		

Test Mode:	All modes were tested, only the worst case was recorded in the report.
Test Results:	Pass

Measurement Data

Live line:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.2400	29.91	10.18	40.09	62.10	-22.01	QP	
2		0.3435	17.10	10.11	27.21	49.12	-21.91	AVG	
3	*	0.5505	39.64	10.09	49.73	56.00	-6.27	QP	
4		0.5595	25.19	10.09	35.28	46.00	-10.72	AVG	
5		1.4100	29.74	10.18	39.92	56.00	-16.08	QP	
6		1.7115	15.84	10.17	26.01	46.00	-19.99	AVG	
7		3.2100	27.19	10.13	37.32	56.00	-18.68	QP	
8		5.5275	9.27	10.05	19.32	50.00	-30.68	AVG	
9		15.4320	16.14	9.85	25.99	60.00	-34.01	QP	
10		15.9900	1.98	9.85	11.83	50.00	-38.17	AVG	
11		26.0520	4.60	9.81	14.41	50.00	-35.59	AVG	
12		26.5290	16.68	9.81	26.49	60.00	-33.51	QP	

Remark:


1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. Margin = Measurement - Limit.

4. Measurement=Reading Level+Correct Factor.

5. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit.

6. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.4425	29.22	10.09	39.31	57.01	-17.70	QP	
2		0.5550	38.90	10.09	48.99	56.00	-7.01	QP	
3	*	0.5550	31.72	10.09	41.81	46.00	-4.19	AVG	
4		0.9375	21.48	10.17	31.65	46.00	-14.35	AVG	
5		1.6710	26.80	10.17	36.97	56.00	-19.03	QP	
6		1.6845	18.54	10.17	28.71	46.00	-17.29	AVG	
7		3.4845	24.65	10.12	34.77	56.00	-21.23	QP	
8		3.5565	14.96	10.11	25.07	46.00	-20.93	AVG	
9		5.7435	12.29	10.05	22.34	50.00	-27.66	AVG	
10		8.6505	20.02	9.99	30.01	60.00	-29.99	QP	
11		10.1895	8.57	9.95	18.52	50.00	-31.48	AVG	
12		23.3205	14.02	9.81	23.83	60.00	-36.17	QP	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. Margin = Measurement - Limit.
4. Measurement = Reading Level + Correct Factor.
5. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit.
6. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.407 (a)													
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E													
Test Setup:														
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report.													
Limit:	<table border="1"> <thead> <tr> <th>Frequency band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td rowspan="2">5150-5250</td><td>≤1W(30dBm) for master device</td></tr> <tr> <td>≤250mW(24dBm) for client device</td></tr> <tr> <td>5250-5350</td><td>≤250mW(24dBm) for client device or 11dBm+10logB*</td></tr> <tr> <td>5470-5725</td><td>≤250mW(24dBm) for client device or 11dBm+10logB*</td></tr> <tr> <td>5725-5850</td><td>≤1W(30dBm)</td></tr> <tr> <td>Remark:</td><td>* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.</td></tr> </tbody> </table>	Frequency band (MHz)	Limit	5150-5250	≤1W(30dBm) for master device	≤250mW(24dBm) for client device	5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*	5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*	5725-5850	≤1W(30dBm)	Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.
Frequency band (MHz)	Limit													
5150-5250	≤1W(30dBm) for master device													
	≤250mW(24dBm) for client device													
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*													
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*													
5725-5850	≤1W(30dBm)													
Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.													
Test Mode:	Transmitting mode with modulation													
Test Results:	Refer to Appendix A													


5.4 6dB Emission Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (e)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Limit:	≥ 500 kHz
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix A


5.5 26dB Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C&D
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	For 26dB Occupied Bandwidth: 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. 4. Measure and record the results in the test report. For 99% Occupied Bandwidth: 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$. 4. Measure and record the results in the test report.
Limit:	No restriction limits
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix A

5.6 Maximum Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.407 (a)													
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F													
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.													
Test Procedure:	- Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. - Allow the sweeps to continue until the trace stabilizes. - Use the peak marker function to determine the maximum amplitude level.													
Limit:	<table border="1"> <thead> <tr> <th>Frequency band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td rowspan="2">5150-5250</td><td>≤17dBm in 1MHz for master device</td></tr> <tr> <td>≤11dBm in 1MHz for client device</td></tr> <tr> <td>5250-5350</td><td>≤11dBm in 1MHz for client device</td></tr> <tr> <td>5470-5725</td><td>≤11dBm in 1MHz for client device</td></tr> <tr> <td>5725-5850</td><td>≤30dBm in 500kHz</td></tr> <tr> <td>Remark:</td><td>The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.</td></tr> </tbody> </table>	Frequency band (MHz)	Limit	5150-5250	≤17dBm in 1MHz for master device	≤11dBm in 1MHz for client device	5250-5350	≤11dBm in 1MHz for client device	5470-5725	≤11dBm in 1MHz for client device	5725-5850	≤30dBm in 500kHz	Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.
Frequency band (MHz)	Limit													
5150-5250	≤17dBm in 1MHz for master device													
	≤11dBm in 1MHz for client device													
5250-5350	≤11dBm in 1MHz for client device													
5470-5725	≤11dBm in 1MHz for client device													
5725-5850	≤30dBm in 500kHz													
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.													
Test Mode:	Transmitting mode with modulation													
Test Results:	Refer to Appendix A													

5.7 Frequency Stability

Test Requirement:	47 CFR Part 15C Section 15.407 (g)
Test Method:	ANSI C63.10-2020
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1.The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. 2. Turn the EUT on and couple its output to a spectrum analyzer. 3. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. 4. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. 5. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix A

5.8 Radiated Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.407 (b)																																	
Test Method:	ANSI C63.10-2020																																	
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																																	
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark																													
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak																													
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average																													
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak																													
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak																													
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average																													
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak																													
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak																													
	Above 1GHz	Peak	1MHz	3MHz	Peak																													
Peak		1MHz	10kHz	Average																														
Limit:	(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.																																	
	(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.																																	
	(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.																																	
	(4) For transmitters operating in the 5.725-5.85 GHz band:																																	
	(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.																																	
	<table><tr><td>EIRP(dBm)</td><td>Field Strength at 3m (dBμV/m)</td></tr><tr><td>-27(RMS)</td><td>68.2</td></tr><tr><td>-7(Peak)</td><td>88.2</td></tr></table>					EIRP(dBm)	Field Strength at 3m (dBμV/m)	-27(RMS)	68.2	-7(Peak)	88.2																							
	EIRP(dBm)	Field Strength at 3m (dBμV/m)																																
	-27(RMS)	68.2																																
	-7(Peak)	88.2																																
	Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table:																																	
<table><tr><td>Frequency</td><td>Field strength (microvolt/meter)</td><td>Limit (dBuV/m)</td><td>Remark</td><td>Measurement distance (m)</td></tr><tr><td>0.009MHz-0.490MHz</td><td>2400/F(kHz)</td><td>-</td><td>-</td><td>300</td></tr><tr><td>0.490MHz-1.705MHz</td><td>24000/F(kHz)</td><td>-</td><td>-</td><td>30</td></tr><tr><td>1.705MHz-30MHz</td><td>30</td><td>-</td><td>-</td><td>30</td></tr><tr><td>30MHz-88MHz</td><td>100</td><td>40.0</td><td>Quasi-peak</td><td>3</td></tr><tr><td>88MHz-216MHz</td><td>150</td><td>43.5</td><td>Quasi-peak</td><td>3</td></tr></table>					Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30	1.705MHz-30MHz	30	-	-	30	30MHz-88MHz	100	40.0	Quasi-peak	3	88MHz-216MHz	150	43.5	Quasi-peak	3
Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)																														
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300																														
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30																														
1.705MHz-30MHz	30	-	-	30																														
30MHz-88MHz	100	40.0	Quasi-peak	3																														
88MHz-216MHz	150	43.5	Quasi-peak	3																														

	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

When the peak radio frequency emissions exceed the maximum permitted average limits specified above by less than 20 dB, the average radio frequency emissions will be recorded whether it meets the limit requirements.

Note:

(i) $EIRP = ((E \cdot d)^2) / 30$
 where:

- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

(ii) Working in dB units, the above equation is equivalent to:
 $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$

(iii) Or, if d is 3 meters:
 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel and the highest

	channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting mode with modulation
Test Results:	Pass


Radiated Spurious Emissions test Data: Radiated Emission below 1GHz

Remark: During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case middle channel of 6Mbps for 802.11a was recorded in the report.

Test Graph

Horizontal:

72.0 dBuV/m




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Comment
1		34.9006	9.32	12.84	22.16	40.00	-17.84	QP	100	354
2		77.7289	12.33	10.05	22.38	40.00	-17.62	QP	100	0
3		414.6496	7.33	19.63	26.96	46.00	-19.04	QP	100	29
4		484.5886	8.11	20.34	28.45	46.00	-17.55	QP	100	337
5	*	828.6548	11.47	25.43	36.90	46.00	-9.10	QP	100	89
6		931.2913	-0.08	27.19	27.11	46.00	-18.89	QP	100	29

Remark:

1. Margin=Measurement(Level)-Limit.
2. Measurement(Level)=Reading Level+Correct Factor.
3. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit, an exclamation mark (!) indicates over -6dB margin Limit.

Vertical:

72.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree	Comment
1		32.1908	20.59	12.63	33.22	40.00	-6.78	QP	100	118	
2	*	34.7480	20.59	12.83	33.42	40.00	-6.58	QP	100	14	
3		44.5946	17.32	13.87	31.19	40.00	-8.81	QP	100	57	
4		51.1747	14.58	14.52	29.10	40.00	-10.90	QP	100	6	
5		77.2805	20.99	10.09	31.08	40.00	-8.92	QP	100	118	
6		467.7267	13.73	20.27	34.00	46.00	-12.00	QP	100	57	

Remark:

1. $\text{Margin} = \text{Measurement (Level)} - \text{Limit}$.
2. $\text{Measurement (Level)} = \text{Reading Level} + \text{Correct Factor}$.
3. In the test results, an asterisk (*) indicates Maximum Data, a cross (X) indicates over Limit, an exclamation mark (!) indicates over -6dB margin Limit.


Transmitter Emission above 1GHz

Remark: Through Pre-scan, for 20MHz Occupied Bandwidth, 802.11 n(HT20) was the worst case; for 40MHz Occupied Bandwidth, 802.11 ac(VHT40) was the worst case; for 80MHz Occupied Bandwidth, 802.11 ax(HE80) was the worst case; only the worst case was in the report.

U-NII-1:

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1409.8764	13.08	34.69	47.77	74.00	26.23	PASS	Horizon	PK
2	2535.2214	16.72	34.71	51.43	68.20	16.77	PASS	Horizon	PK
3	3726.7891	20.56	32.47	53.03	74.00	20.97	PASS	Horizon	PK
4	6926.0963	-3.08	48.92	45.84	68.20	22.36	PASS	Horizon	PK
5	10366.4933	1.90	50.50	52.40	68.20	15.80	PASS	Horizon	PK
6	15883.8942	9.99	43.66	53.65	74.00	20.35	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1140.3656	11.38	36.23	47.61	74.00	26.39	PASS	Vertical	PK
2	2099.604	15.27	34.38	49.65	68.20	18.55	PASS	Vertical	PK
3	3536.4815	19.43	33.67	53.10	68.20	15.10	PASS	Vertical	PK
4	7619.006	-1.71	47.80	46.09	74.00	27.91	PASS	Vertical	PK
5	10352.6926	1.94	47.66	49.60	68.20	18.60	PASS	Vertical	PK
6	15541.7521	9.99	43.82	53.81	74.00	20.19	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1410.3164	13.09	35.29	48.38	74.00	25.62	PASS	Horizon	PK
2	2338.3135	15.95	35.75	51.70	74.00	22.30	PASS	Horizon	PK
3	3530.5412	19.37	33.42	52.79	68.20	15.41	PASS	Horizon	PK
4	6923.2212	-3.11	48.12	45.01	68.20	23.19	PASS	Horizon	PK
5	10362.4681	1.92	48.64	50.56	68.20	17.64	PASS	Horizon	PK
6	14998.3499	9.62	41.65	51.27	68.20	16.93	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1481.5993	13.29	33.98	47.27	74.00	26.73	PASS	Vertical	PK
2	2327.7531	15.93	35.69	51.62	74.00	22.38	PASS	Vertical	PK
3	3822.2729	20.77	32.48	53.25	74.00	20.75	PASS	Vertical	PK
4	6960.598	-2.92	49.78	46.86	68.20	21.34	PASS	Vertical	PK
5	10359.593	1.92	48.78	50.70	68.20	17.50	PASS	Vertical	PK
6	14479.674	8.71	41.79	50.50	74.00	23.50	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5240MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1362.1345	12.69	34.10	46.79	74.00	27.21	PASS	Horizon	PK
2	2044.3818	14.86	34.18	49.04	68.20	19.16	PASS	Horizon	PK
3	3428.8972	19.45	33.54	52.99	68.20	15.21	PASS	Horizon	PK
4	6975.5488	-3.11	48.26	45.15	68.20	23.05	PASS	Horizon	PK
5	10359.593	1.92	46.73	48.65	68.20	19.55	PASS	Horizon	PK
6	15950.0225	9.85	43.28	53.13	74.00	20.87	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5240MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1308.2323	12.32	34.13	46.45	74.00	27.55	PASS	Vertical	PK
2	1806.5523	14.43	33.87	48.30	68.20	19.90	PASS	Vertical	PK
3	3430.4372	19.47	33.72	53.19	68.20	15.01	PASS	Vertical	PK
4	6962.8981	-2.95	48.13	45.18	68.20	23.02	PASS	Vertical	PK
5	10356.1428	1.93	49.46	51.39	68.20	16.81	PASS	Vertical	PK
6	15032.2766	10.04	41.55	51.59	68.20	16.61	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1495.2398	13.47	34.42	47.89	74.00	26.11	PASS	Horizon	PK
2	2296.2919	15.84	34.46	50.30	74.00	23.70	PASS	Horizon	PK
3	3543.3017	19.44	33.53	52.97	68.20	15.23	PASS	Horizon	PK
4	7633.3817	-1.78	47.72	45.94	74.00	28.06	PASS	Horizon	PK
5	11810.3905	2.42	46.58	49.00	74.00	25.00	PASS	Horizon	PK
6	15492.2996	10.02	42.15	52.17	74.00	21.83	PASS	Horizon	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1523.6209	13.52	34.22	47.74	74.00	26.26	PASS	Vertical	PK
2	2120.7248	15.39	33.47	48.86	68.20	19.34	PASS	Vertical	PK
3	3425.817	19.41	33.13	52.54	68.20	15.66	PASS	Vertical	PK
4	6886.4193	-3.46	49.01	45.55	68.20	22.65	PASS	Vertical	PK
5	10379.719	1.87	48.13	50.00	68.20	18.20	PASS	Vertical	PK
6	14352.0176	8.97	42.94	51.91	68.20	16.29	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1280.9512	11.82	35.03	46.85	68.20	21.35	PASS	Horizon	PK
2	1931.2973	14.78	33.58	48.36	68.20	19.84	PASS	Horizon	PK
3	3077.1031	18.26	34.63	52.89	68.20	15.31	PASS	Horizon	PK
4	6965.1983	-2.98	48.90	45.92	68.20	22.28	PASS	Horizon	PK
5	11285.3893	2.40	45.81	48.21	74.00	25.79	PASS	Horizon	PK
6	14989.1495	9.54	42.29	51.83	68.20	16.37	PASS	Horizon	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1317.2527	12.40	34.94	47.34	74.00	26.66	PASS	Vertical	PK
2	2440.3976	16.46	34.24	50.70	68.20	17.50	PASS	Vertical	PK
3	3785.5314	20.59	32.09	52.68	74.00	21.32	PASS	Vertical	PK
4	6909.4205	-3.28	48.99	45.71	68.20	22.49	PASS	Vertical	PK
5	10460.798	2.14	47.59	49.73	68.20	18.47	PASS	Vertical	PK
6	15474.4737	9.92	41.68	51.60	74.00	22.40	PASS	Vertical	PK

Test_Mode	802.11ax(HE80)Transmittin g	Test_Frequency	5210MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1407.6763	13.03	34.72	47.75	74.00	26.25	PASS	Horizon	PK
2	2301.132	15.89	34.44	50.33	68.20	17.87	PASS	Horizon	PK
3	3560.0224	19.34	34.10	53.44	68.20	14.76	PASS	Horizon	PK
4	7001.4251	-3.41	48.76	45.35	68.20	22.85	PASS	Horizon	PK
5	10417.0959	1.94	45.54	47.48	68.20	20.72	PASS	Horizon	PK
6	15327.8414	9.91	41.67	51.58	68.20	16.62	PASS	Horizon	PK

Test_Mode	802.11ax(HE80)Transmittin g	Test_Frequency	5210MHz
Remark:	/	Test_Date	2026/3/26

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1271.2709	11.93	34.81	46.74	68.20	21.46	PASS	Vertical	PK
2	2586.2635	16.60	34.04	50.64	68.20	17.56	PASS	Vertical	PK
3	3951.6381	21.54	32.13	53.67	74.00	20.33	PASS	Vertical	PK
4	7751.2626	-1.88	47.40	45.52	68.20	22.68	PASS	Vertical	PK
5	11285.3893	2.40	46.05	48.45	74.00	25.55	PASS	Vertical	PK
6	15891.9446	10.06	42.89	52.95	74.00	21.05	PASS	Vertical	PK

Above 18GHz

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19828.7131	-25.14	59.08	33.94	74.00	40.06	PASS	Horizon	PK
2	22129.1252	-25.54	58.09	32.55	74.00	41.45	PASS	Horizon	PK
3	24548.3419	-21.82	55.48	33.66	68.20	34.54	PASS	Horizon	PK
4	28779.5512	-21.53	55.13	33.60	68.20	34.60	PASS	Horizon	PK
5	31566.6227	-19.65	52.75	33.10	74.00	40.90	PASS	Horizon	PK
6	35511.8205	-16.13	48.05	31.92	68.20	36.28	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20010.8804	-24.67	57.76	33.09	74.00	40.91	PASS	Vertical	PK
2	23344.4538	-23.75	57.09	33.34	68.20	34.86	PASS	Vertical	PK
3	25598.2239	-20.72	55.22	34.50	68.20	33.70	PASS	Vertical	PK
4	28366.8147	-21.47	55.23	33.76	68.20	34.44	PASS	Vertical	PK
5	31600.944	-19.63	53.24	33.61	74.00	40.39	PASS	Vertical	PK
6	35520.6208	-16.13	48.11	31.98	68.20	36.22	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20010.8804	-24.67	58.23	33.56	74.00	40.44	PASS	Horizon	PK
2	22148.4859	-25.50	58.10	32.60	74.00	41.40	PASS	Horizon	PK
3	24421.6169	-21.70	54.99	33.29	68.20	34.91	PASS	Horizon	PK
4	27436.6175	-21.62	55.74	34.12	68.20	34.08	PASS	Horizon	PK
5	30901.3161	-19.48	53.85	34.37	68.20	33.83	PASS	Horizon	PK
6	35667.5867	-16.36	48.77	32.41	68.20	35.79	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19913.1965	-24.89	58.25	33.36	74.00	40.64	PASS	Vertical	PK
2	22324.493	-25.22	58.02	32.80	74.00	41.20	PASS	Vertical	PK
3	25284.9314	-21.21	55.46	34.25	68.20	33.95	PASS	Vertical	PK
4	28386.1754	-21.48	54.54	33.06	68.20	35.14	PASS	Vertical	PK
5	30985.7994	-19.35	52.73	33.38	68.20	34.82	PASS	Vertical	PK
6	34136.3255	-17.55	49.69	32.14	68.20	36.06	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20045.2018	-24.82	58.02	33.20	74.00	40.80	PASS	Horizon	PK
2	22414.2566	-25.09	57.45	32.36	74.00	41.64	PASS	Horizon	PK
3	24785.0714	-21.96	55.27	33.31	68.20	34.89	PASS	Horizon	PK
4	27247.4099	-21.84	54.89	33.05	68.20	35.15	PASS	Horizon	PK
5	30459.5384	-20.41	53.77	33.36	68.20	34.84	PASS	Horizon	PK
6	34344.8938	-17.26	48.43	31.17	68.20	37.03	PASS	Horizon	PK
7	37631.8253	-14.91	46.28	31.37	68.20	36.83	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Remark:	/	Test_Date	2026/3/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20020.5608	-24.71	57.78	33.07	74.00	40.93	PASS	Vertical	PK
2	23927.9171	-22.08	55.41	33.33	74.00	40.67	PASS	Vertical	PK
3	26956.9983	-21.77	55.86	34.09	68.20	34.11	PASS	Vertical	PK
4	30127.7651	-21.23	53.61	32.38	68.20	35.82	PASS	Vertical	PK
5	33335.4934	-18.17	50.87	32.70	68.20	35.50	PASS	Vertical	PK
6	37203.2481	-16.24	46.93	30.69	68.20	37.51	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19841.0336	-25.10	58.94	33.84	74.00	40.16	PASS	Horizon	PK
2	22727.5491	-25.03	57.10	32.07	74.00	41.93	PASS	Horizon	PK
3	25798.872	-20.82	55.40	34.58	68.20	33.62	PASS	Horizon	PK
4	27884.5554	-21.12	56.12	35.00	68.20	33.20	PASS	Horizon	PK
5	30902.1961	-19.48	53.52	34.04	68.20	34.16	PASS	Horizon	PK
6	33495.6598	-17.75	50.98	33.23	68.20	34.97	PASS	Horizon	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20117.3647	-25.14	58.47	33.33	74.00	40.67	PASS	Vertical	PK
2	23339.1736	-23.77	56.15	32.38	68.20	35.82	PASS	Vertical	PK
3	26230.0892	-21.34	55.64	34.30	68.20	33.90	PASS	Vertical	PK
4	29106.9243	-21.39	54.32	32.93	68.20	35.27	PASS	Vertical	PK
5	32173.847	-19.49	52.35	32.86	68.20	35.34	PASS	Vertical	PK
6	37520.0608	-15.24	46.53	31.29	68.20	36.91	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19785.5914	-25.25	58.46	33.21	74.00	40.79	PASS	Horizon	PK
2	22418.6567	-25.09	58.22	33.13	74.00	40.87	PASS	Horizon	PK
3	24858.9944	-22.01	55.05	33.04	68.20	35.16	PASS	Horizon	PK
4	27826.4731	-21.08	55.44	34.36	68.20	33.84	PASS	Horizon	PK
5	30906.5963	-19.47	53.58	34.11	68.20	34.09	PASS	Horizon	PK
6	35526.7811	-16.13	48.06	31.93	68.20	36.27	PASS	Horizon	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20051.3621	-24.85	58.31	33.46	74.00	40.54	PASS	Vertical	PK
2	23013.5605	-25.58	58.10	32.52	74.00	41.48	PASS	Vertical	PK
3	26086.6435	-21.10	55.02	33.92	68.20	34.28	PASS	Vertical	PK
4	29597.9839	-20.61	54.64	34.03	68.20	34.17	PASS	Vertical	PK
5	32356.0142	-18.32	51.93	33.61	68.20	34.59	PASS	Vertical	PK
6	37388.0555	-15.87	47.16	31.29	68.20	36.91	PASS	Vertical	PK

Test_Mode	802.11ax(HE80)Transmittin g	Test_Frequency	5210MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19962.4785	-24.74	58.09	33.35	74.00	40.65	PASS	Horizon	PK
2	22715.2286	-25.03	56.67	31.64	74.00	42.36	PASS	Horizon	PK
3	26390.2556	-21.18	55.61	34.43	68.20	33.77	PASS	Horizon	PK
4	29934.1574	-21.04	53.80	32.76	68.20	35.44	PASS	Horizon	PK
5	33630.3052	-17.39	51.48	34.09	68.20	34.11	PASS	Horizon	PK
6	38059.5224	-14.76	46.76	32.00	68.20	36.20	PASS	Horizon	PK

Test_Mode	802.11ax(HE80)Transmittin g	Test_Frequency	5210MHz
Remark:	/	Test_Date	2026/3/26

Test Graph




Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19198.6079	-26.06	59.39	33.33	74.00	40.67	PASS	Vertical	PK
2	22373.775	-25.14	57.35	32.21	74.00	41.79	PASS	Vertical	PK
3	25058.7624	-21.82	55.96	34.14	68.20	34.06	PASS	Vertical	PK
4	27349.494	-21.71	55.20	33.49	68.20	34.71	PASS	Vertical	PK
5	30907.4763	-19.47	53.80	34.33	68.20	33.87	PASS	Vertical	PK
6	36592.5037	-15.78	47.44	31.66	68.20	36.54	PASS	Vertical	PK

U-NII-2A:

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5260MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1410.3164	13.09	34.35	47.44	74.00	26.56	PASS	Horizon	PK
2	1955.4982	14.86	31.29	46.15	68.20	22.05	PASS	Horizon	PK
3	2818.5927	17.34	34.45	51.79	74.00	22.21	PASS	Horizon	PK
4	6637.4319	-3.67	48.29	44.62	68.20	23.58	PASS	Horizon	PK
5	10520.026	2.00	47.40	49.40	68.20	18.80	PASS	Horizon	PK
6	15499.2	10.06	41.67	51.73	74.00	22.27	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5260MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1454.5382	13.09	33.80	46.89	74.00	27.11	PASS	Vertical	PK
2	2279.7912	15.84	33.55	49.39	74.00	24.61	PASS	Vertical	PK
3	3585.7634	19.81	32.71	52.52	68.20	15.68	PASS	Vertical	PK
4	6938.7469	-2.93	48.23	45.30	68.20	22.90	PASS	Vertical	PK
5	10526.9263	1.97	49.33	51.30	68.20	16.90	PASS	Vertical	PK
6	15372.6936	9.81	41.29	51.10	74.00	22.90	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5300MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1347.8339	12.47	34.40	46.87	74.00	27.13	PASS	Horizon	PK
2	2327.7531	15.93	33.69	49.62	74.00	24.38	PASS	Horizon	PK
3	3507.0003	19.18	32.61	51.79	68.20	16.41	PASS	Horizon	PK
4	7098.6049	-2.90	47.70	44.80	68.20	23.40	PASS	Horizon	PK
5	10515.4258	2.02	46.52	48.54	68.20	19.66	PASS	Horizon	PK
6	15468.7234	9.89	43.11	53.00	74.00	21.00	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5300MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1607.0043	13.90	33.47	47.37	74.00	26.63	PASS	Vertical	PK
2	2685.0474	17.37	34.49	51.86	68.20	16.34	PASS	Vertical	PK
3	3702.1481	20.20	32.86	53.06	74.00	20.94	PASS	Vertical	PK
4	7008.3254	-3.39	48.51	45.12	68.20	23.08	PASS	Vertical	PK
5	10581.5541	2.03	45.31	47.34	68.20	20.86	PASS	Vertical	PK
6	15090.3545	10.19	42.28	52.47	68.20	15.73	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5320MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1422.1969	13.00	33.89	46.89	74.00	27.11	PASS	Horizon	PK
2	2593.9638	16.59	34.87	51.46	68.20	16.74	PASS	Horizon	PK
3	3596.1038	19.80	33.15	52.95	68.20	15.25	PASS	Horizon	PK
4	6884.6942	-3.46	48.49	45.03	68.20	23.17	PASS	Horizon	PK
5	10634.4567	2.42	45.85	48.27	74.00	25.73	PASS	Horizon	PK
6	14911.5206	9.33	41.98	51.31	68.20	16.89	PASS	Horizon	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5320MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1280.5112	11.81	34.66	46.47	68.20	21.73	PASS	Vertical	PK
2	1948.6779	14.93	31.80	46.73	68.20	21.47	PASS	Vertical	PK
3	3385.5554	19.22	34.06	53.28	68.20	14.92	PASS	Vertical	PK
4	7030.1765	-3.34	49.30	45.96	68.20	22.24	PASS	Vertical	PK
5	10645.3823	2.51	48.60	51.11	74.00	22.89	PASS	Vertical	PK
6	15412.3706	10.16	41.07	51.23	74.00	22.77	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5270MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1327.3731	12.39	35.19	47.58	74.00	26.42	PASS	Horizon	PK
2	2285.9514	15.79	33.19	48.98	74.00	25.02	PASS	Horizon	PK
3	3309.4324	18.46	34.75	53.21	68.20	14.99	PASS	Horizon	PK
4	7049.1525	-3.28	48.51	45.23	68.20	22.97	PASS	Horizon	PK
5	9599.98	1.26	45.81	47.07	68.20	21.13	PASS	Horizon	PK
6	15408.3454	10.21	41.92	52.13	74.00	21.87	PASS	Horizon	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5270MHz
Remark:	/	Test_Date	2026/3/26


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1364.5546	12.72	33.63	46.35	74.00	27.65	PASS	Vertical	PK
2	2242.8297	15.57	33.70	49.27	74.00	24.73	PASS	Vertical	PK
3	3591.0436	19.78	32.74	52.52	68.20	15.68	PASS	Vertical	PK
4	7127.9314	-3.00	48.52	45.52	68.20	22.68	PASS	Vertical	PK
5	10494.7247	2.10	45.25	47.35	68.20	20.85	PASS	Vertical	PK
6	14541.7771	8.58	41.77	50.35	68.20	17.85	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5310MHz
Remark:	/	Test_Date	2026/3/26

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1359.7144	12.65	33.84	46.49	74.00	27.51	PASS	Horizon	PK
2	2166.2667	15.58	33.55	49.13	68.20	19.07	PASS	Horizon	PK
3	3341.7737	18.75	33.77	52.52	68.20	15.68	PASS	Horizon	PK
4	7357.3679	-2.88	48.10	45.22	74.00	28.78	PASS	Horizon	PK
5	10986.3743	2.18	45.32	47.50	74.00	26.50	PASS	Horizon	PK
6	14404.3452	9.14	41.60	50.74	68.20	17.46	PASS	Horizon	PK