FCC TEST REPORT

FCC ID： 2AWB2-YOUFACE800HS

Product	:	Infrared thermal imaging face recognition all-in-one machine
Model Name	:	YOUFACE800HS
Additional Model Number	:	YOUFACE800I, YOUFACE800H, YOUFACE800X
Brand	:	YOUFACE
Report No.	:	PTC20032702701E-FC01

Prepared for

Shenzhen geesuntar technology co., LTD

704, complex building, no. 21, jizheng road, buji street, longgang district, shenzhen city, guangdong province, China

Prepared by

Precise Testing & Certification (Guangdong) Co., Ltd.

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.

1 TEST RESULT CERTIFICATION

Applicant's name	:	Shenzhen geesuntar technology co., LTD
Address	:	704, complex building, no. 21, jizheng road, buji street, longgang district, shenzhen city, guangdong province, China
Manufacture's name	:	Shenzhen geesuntar technology co., LTD
Address	:	704, complex building, no. 21, jizheng road, buji street, longgang district, shenzhen city, guangdong province, China
Product name	:	Infrared thermal imaging face recognition all-in-one machine
Model name	:	YOUFACE800HS
Additional Model Number		YOUFACE800I, YOUFACE800H, YOUFACE800X
Standards	:	FCC CFR47 Part 15 Section 15.247
Test procedure	:	ANSI C63.10:2013
Test Date	:	Apr. 20 , 2020 ~ Apr. 27, 2020
Date of Issue	:	Apr. 27, 2020
Test Result	:	Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

Leo Yang

Leo Yang / Engineer

Technical Manager:

Chris Du / Manager

Contents

Page

1 TEST RESULT CERTIFICATION 2

2 TEST SUMMARY 5

3 GENERAL INFORMATION 6

3.1 GENERAL DESCRIPTION OF E.U.T 6

3.2 CHANNEL LIST 7

3.3 TEST SITE 11

4 EQUIPMENT DURING TEST 12

4.1 EQUIPMENTS LIST 12

4.2 MEASUREMENT UNCERTAINTY 14

4.3 DESCRIPTION OF SUPPORT UNITS 15

5 CONDUCTED EMISSION 16

5.1 E.U.T. OPERATION 16

5.2 EUT SETUP 16

5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 17

5.4 MEASUREMENT PROCEDURE 17

5.5 CONDUCTED EMISSION LIMIT 17

5.6 MEASUREMENT DESCRIPTION 17

5.7 CONDUCTED EMISSION TEST RESULT 17

6 RADIATED SPURIOUS EMISSIONS 20

6.1 EUT OPERATION 20

6.2 TEST SETUP 21

6.3 SPECTRUM ANALYZER SETUP 22

6.4 TEST PROCEDURE 23

6.5 SUMMARY OF TEST RESULTS 24

7 CONDUCTED SPURIOUS EMISSION 29

7.1 TEST PROCEDURE 29

7.2 TEST RESULT 29

8 BAND EDGE MEASUREMENT 36

8.1 TEST PROCEDURE 36

8.2 TEST RESULT 37

9 6DB BANDWIDTH MEASUREMENT 41

9.1 TEST PROCEDURE 41

9.2 TEST RESULT 41

10 MAXIMUM PEAK OUTPUT POWER 48

10.1 TEST PROCEDURE 48

10.2 TEST RESULT 48

11 POWER SPECTRAL DENSITY 49

11.1 TEST PROCEDURE 49

11.2 TEST RESULT 49

12 ANTENNA APPLICATION 55

12.1 ANTENNA REQUIREMENT 55

12.2 RESULT 56

13 TEST SETUP 57

14 EUT PHOTOS 59

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS
Remark: N/A: Not Applicable		

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Infrared thermal imaging face recognition all-in-one machine
Model Name	:	YOUFACE800HS
Additional Model Number	:	YOUFACE800I, YOUFACE800H, YOUFACE800X
Specification	:	802.11b/g/n HT20/HT40
Operation Frequency	:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
Number of Channel	:	11 channels for802.11b/g/n(HT20) 7 channels for 802.11b/g/n(HT40)
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	Rod Antenna
Antenna Gain	:	0 dBi
Power supply	:	Input: DC 12V, 2A
Hardware Version	:	N/A
Software Version	:	N/A

3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list :

802.11b/g/n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	1	--
2	2417	2	--
3	2422	3	2422
4	2427	4	2427
5	2432	5	2432
6	2437	6	2437
7	2442	7	2442
8	2447	8	2447
9	2452	9	2452
10	2457	10	--
11	2462	11	--

The maximum duty cycle as following table:

Test Mode	T_{on}(ms)	T_{on+off}(ms)	Duty Cycle(%)
802.11b	100	100	100%
802.11g	100	100	100%
802.11n(HT20)	100	100	100%
802.11n(HT40)	100	100	100%

Test Plots:

802.11b



802.11g



802.11n(HT20)



802.11n(HT40)


Spectrum
Ref Level 11.00 dBm
RBW 10 MHz
Att 30 dB
SWT 10 ms
VBW 10 MHz
1AP Clrw
2Pk Max
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.412 GHz
691 pts
1.0 ms/

3.3 Test Site

Precise Testing & Certification (Guangdong) Co., Ltd.

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1

4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
MXG Signal Analyzer	Agilent	N9020A	MY56070279	10Hz-30GHz	Sep.18, 2020
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Sep.18, 2020
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Sep.18, 2020
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Sep.18, 2020

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep.18, 2020
Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	Sep.18, 2020
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Sep.18, 2020
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Sep.18, 2020
Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	Sep.18, 2020
Spectrum Analyzer	Agilent	E4407B	MY45109572	9KHz-40GHz	Sep.18, 2020
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Sep.18, 2020
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	Sep.18, 2020
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	14GHz-40GHz	Sep.18, 2020
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Sep.18, 2020
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Sep.18, 2020
RF Cable	R&S	R204	R21X	1GHz-40GHz	Sep.18, 2020

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Due
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Sep.18, 2020
Artificial Mains Network	Rohde&Schwarz	L2-16B	000WX31025	9KHz-300MHz	Sep.18, 2020
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Sep.18, 2020

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10^{-6}
Bandwidth	± 1.5 x 10^{-6}
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB

4.3 Description of Support Units

Equipment	Model No.	Series No.
Adapter	Model: XED-3C120200CC Input: AC120V, 50/60Hz, Output: DC 12V, 2A	N/A

5 Conducted Emission

Test Requirement:	:	FCC CFR 47 Part 15 Section 15.207
Test Method	:	ANSI C63.10: 2013
Test Result	:	PASS
Frequency Range	:	150kHz to 30MHz
Class/Severity	:	Class B

5.1 E.U.T. Operation

Operating Environment :

Temperature	:	25.5 °C
Humidity	:	51 % RH
Atmospheric Pressure	:	101.2kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:
1. The lower limit shall apply at the transition frequencies
2.The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Pass.

Please refer to the following pages.

Line-AC 120V/60Hz



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBμV	Emission Level dBμV	Limit dBμV	Over Limit dB	Remark
1.	0.174	0.24	9.59	28.12	37.95	54.77	-16.82	Average
2.	0.174	0.24	9.59	42.62	52.45	64.77	-12.32	QP
3.	0.206	0.29	9.59	23.13	33.01	53.36	-20.35	Average
4.	0.206	0.29	9.59	38.36	48.24	63.36	-15.12	QP
5.	0.253	0.33	9.60	22.59	32.52	51.64	-19.12	Average
6.	0.253	0.33	9.60	32.08	42.01	61.64	-19.63	QP
7.	0.346	0.39	9.60	24.78	34.77	49.05	-14.28	Average
8.	0.346	0.39	9.60	31.50	41.49	59.05	-17.56	QP
9.	0.505	0.43	9.61	10.33	20.37	46.00	-25.63	Average
10.	0.505	0.43	9.61	21.74	31.78	56.00	-24.22	QP
11.	0.844	0.45	9.61	6.35	16.41	46.00	-29.59	Average
12.	0.844	0.45	9.61	15.80	25.86	56.00	-30.14	QP

Neutral-AC 120V/60Hz



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBμV	Emission Level dBμV	Limit dBμV	Over Limit dB	Remark
1.	0.150	0.21	9.60	26.82	36.63	56.00	-19.37	Average
2.	0.150	0.21	9.60	44.16	53.97	66.00	-12.03	QP
3.	0.174	0.24	9.60	21.66	31.50	54.77	-23.27	Average
4.	0.174	0.24	9.60	39.91	49.75	64.77	-15.02	QP
5.	0.277	0.35	9.62	23.90	33.87	50.90	-17.03	Average
6.	0.277	0.35	9.62	31.21	41.18	60.90	-19.72	QP
7.	0.327	0.38	9.62	24.15	34.15	49.53	-15.38	Average
8.	0.327	0.38	9.62	34.75	44.75	59.53	-14.78	QP
9.	0.417	0.41	9.63	8.80	18.84	47.51	-28.67	Average
10.	0.417	0.41	9.63	19.24	29.28	57.51	-28.23	QP
11.	0.595	0.44	9.63	6.54	16.61	46.00	-29.39	Average
12.	0.595	0.44	9.63	17.36	27.43	56.00	-28.57	QP

6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method : ANSI C63.10:2013

Test Result : PASS

Measurement Distance : 3m

Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation

Operating Environment :

Temperature: : 23.5 °C

Humidity: : 51.1 % RH

Atmospheric Pressure: : 101.2kPa

6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site

The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value

6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.

5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

6. Repeat above procedures until the measurements for all frequencies are complete.

7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room

6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:

Antenna Polarization: Horizontal



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	108.647	3.42	10.64	39.08	30.00	23.14	43.50	-20.36	QP
2.	178.133	4.26	12.64	44.00	30.03	30.87	43.50	-12.63	QP
3.	239.987	4.77	12.23	50.63	30.17	37.46	46.00	-8.54	QP
4.	346.809	5.41	14.33	53.19	30.51	42.42	46.00	-3.58	QP
5.	528.246	6.13	17.91	49.30	30.93	42.41	46.00	-3.59	QP
6.	962.162	7.16	22.50	42.93	31.05	41.54	54.00	-12.46	QP

Antenna Polarization: Vertical



No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	48.843	2.04	12.14	45.07	29.92	29.33	40.00	-10.67	QP
2.	64.433	2.51	11.08	46.29	29.95	29.93	40.00	-10.07	QP
3.	178.758	4.27	12.59	43.12	30.03	29.95	43.50	-13.55	QP
4.	297.224	5.14	13.16	42.25	30.31	30.24	46.00	-15.76	QP
5.	528.246	6.13	17.91	49.70	30.93	42.81	46.00	-3.19	QP
6.	645.120	6.48	19.52	39.13	31.04	34.09	46.00	-11.91	QP

Test Frequency: From 1GHz to 18GHz

Low Channel (2412MHz) Worst case 802.11g

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4824	25.12	AV	V	9.08	7.89	8.69	33.40	54	-20.60
4824	27.22	AV	H	9.08	7.89	8.69	35.50	54	-18.50
4824	31.43	PK	V	9.08	7.89	8.69	39.71	74	-34.29
4824	32.87	PK	H	9.08	7.89	8.69	41.15	74	-32.85
14238	28.37	AV	V	9.64	8.11	10.03	36.09	54	-17.91
14238	29.55	AV	H	9.64	8.11	10.03	37.27	54	-16.73
14238	33.18	PK	V	9.64	8.11	10.03	40.90	74	-33.10
14238	35.63	PK	H	9.64	8.11	10.03	43.35	74	-30.65

Middle Channel (2437MHz) Worst case 802.11n (HT20)

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874	28.34	AV	V	9.08	8.29	9.23	36.48	54	-17.52
4874	29.37	AV	H	9.08	8.29	9.23	37.51	54	-16.49
4874	32.16	PK	V	9.08	8.29	9.23	40.30	74	-33.70
4874	36.02	PK	H	9.08	8.29	9.23	44.16	74	-29.84
15876	28.12	AV	V	11.35	9.15	10.48	38.14	54	-15.86
15876	30.55	AV	H	11.35	9.15	10.48	40.57	54	-13.43
15876	34.87	PK	V	11.35	9.15	10.48	44.89	74	-29.11
15876	36.61	PK	H	11.35	9.15	10.48	44.63	74	-27.37

High Channel (2462MHz) Worst case 802.11b

Frequency (MHz)	S.A Reading (dBuV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4924	26.83	AV	V	9.05	8.29	8.97	35.20	54	-18.80
4924	28.52	AV	H	9.05	8.29	8.97	36.89	54	-17.11
4924	32.48	PK	V	9.05	8.29	8.97	40.85	74	-33.15
4924	35.26	PK	H	9.05	8.29	8.97	43.63	74	-30.37
13263	27.42	AV	V	10.43	9.68	10.46	37.07	54	-16.93
13263	31.27	AV	H	10.43	9.68	10.46	40.92	54	-13.08
13263	33.82	PK	V	10.43	9.68	10.46	43.47	74	-30.53
13263	40.27	PK	H	10.43	9.68	10.46	49.92	74	-24.08

Note:

1. The testing has been conformed to 10*2462MHz=24620MHz.
2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
   Emission Level = Reading + Factor
   Margin=Emission Level-Limit
4. X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

2.4G WiFi (802.11b/g/n)mode have been tested, and the worst result(802.11g) was report as below

Test Mode: 802.11g Low Channel 2412MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2310.00	29.22	27.27	6.62	0	63.11	74	-10.89	V	Peak
2390.00	27.14	27.53	6.75	0	61.42	74	-12.58	V	
2310.00	28.98	27.27	6.62	0	62.87	74	-11.13	H	
2390.00	27.55	27.53	6.75	0	61.83	74	-12.17	H	
2310.00	12.32	27.27	6.62	0	46.21	54	-7.79	V	Average
2390.00	13.07	27.53	6.75	0	47.35	54	-6.65	V	
2310.00	12.14	27.27	6.62	0	46.03	54	-7.97	H	
2390.00	11.56	27.53	6.75	0	45.84	54	-8.16	H	

Test Mode: 802.11g High Channel 2462MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2483.50	28.25	27.85	6.83	0	62.93	74	-11.07	V	Peak
2500.00	26.21	27.9	6.84	0	60.95	74	-13.05	V	
2483.50	26.89	27.85	6.83	0	61.57	74	-12.43	H	
2500.00	29.22	27.9	6.84	0	63.96	74	-10.04	H	
2483.50	13.12	27.85	6.83	0	47.80	54	-6.20	V	Average
2500.00	11.34	27.9	6.84	0	46.08	54	-7.92	V	
2483.50	13.08	27.85	6.83	0	47.76	54	-6.24	H	
2500.00	10.74	27.9	6.84	0	45.48	54	-8.52	H	

Test Frequency: From 18GHz to 25GHz

The measurements were more than 20dB below the limit and not reported.

7 Conducted Spurious Emission

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Result

802.11 b

Low Channel



Middle Channel



High Channel



802.11g

Low Channel



Middle Channel



High Channel



802.11n-HT20

Low Channel



Middle Channel



High Channel



802.11n-HT40

Low Channel



Middle Channel



High Channel



8 Band Edge Measurement

Test Requirement	:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

8.2 Test Result

802.11b





802.11g


*RBW 100 kHz
*VBW 300 kHz
SWT 15 ms
Marker 1 [T1]
99.14 dBµV
2.418828000 GHz
Ref 122 dBµV
*Att 30 dB
Marker 2 [T1]
53.78 dBµV
2.390000000 GHz
1 PK
MAXH
A
PS
3DB
AC


*RBW 100 kHz
*VBW 300 kHz
SWT 10 ms
Marker 1 [T1]
100.38 dBµV
2.459370000 GHz
Ref 122 dBµV
*Att 30 dB
Marker 2 [T1]
54.07 dBµV
2.483500000 GHz
1 PK
MAXH
A
PS
3DB
AC
Start 2.455 GHz
9.5 MHz/
Stop 2.55 GHz

802.11n-HT20


*RBW 100 kHz
*VBW 300 kHz
SWT 15 ms
Marker 1 [T1]
98.37 dBµV
2.409312000 GHz
Ref 122 dBµV
*Att 30 dB
Marker 2 [T1]
55.27 dBµV
2.389024000 GHz
1 PK MAXH
PS
3DB AC


*RBW 100 kHz
*VBW 300 kHz
SWT 10 ms
Marker 1 [T1]
98.77 dBµV
2.456508000 GHz
Ref 122 dBµV
*Att 30 dB
Marker 2 [T1]
55.00 dBµV
2.484088000 GHz
1 PK MAXH
PS
3DB AC
Start 2.452 GHz
9.8 MHz/
Stop 2.55 GHz

802.11n-HT40


*RBW 100 kHz
*VBW 300 kHz
SWT 15 ms
Marker 1 [T1]
95.32 dBµV
2.431670000 GHz
Ref 122 dBµV
*Att 30 dB
Marker 2 [T1]
64.49 dBµV
2.398920000 GHz
1 PK
MAXH
A
PS
3DB
AC


*RBW 100 kHz
*VBW 300 kHz
SWT 15 ms
Marker 1 [T1]
95.53 dBµV
2.460000000 GHz
Ref 122 dBµV
*Att 30 dB
Marker 2 [T1]
54.36 dBµV
2.483500000 GHz
1 PK
MAXH
A
PS
3DB
AC
Start 2.43 GHz
12 MHz/
Stop 2.55 GHz

9 6dB Bandwidth Measurement

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit		Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

9.2 Test Result

Modulation	Bandwidth(MHz)			Limit
	Low Channel	Middle Channel	High Channel	
802.11b	6.66	7.14	7.08	≥500kHz
802.11g	16.45	16.55	16.525	≥500kHz
802.11n-HT20	17.70	17.675	17.675	≥500kHz
802.11n-HT40	36.36	36.36	36.36	≥500kHz

802.11b Low Channel



802.11b Middle Channel



802.11b High Channel



802.11g Low Channel



802.11g Middle Channel



802.11g High Channel



802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel



802.11n-HT20 High Channel



802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



10 Maximum Peak Output Power

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10:2013
Test Limit	:	Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

10.1 Test Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.1.2 PKPM1 Peak Power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

10.2 Test Result

Modulation	Maximum Peak Output Power (dBm)			Limit
	Low Channel	Middle Channel	High Channel	
802.11b	16.78	16.54	17.04	1W(30dBm)
802.11g	15.15	15.03	15.26	1W(30dBm)
802.11n-HT20	13.18	13.36	13.40	1W(30dBm)
802.11-HT40	13.29	13.28	13.27	1W(30dBm)

11 Power Spectral density

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

Test Limit : Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz, Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.

3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

11.2 Test Result

Modulation	Power Spectral density（dBm/3kHz）			Limit
	Low Channel	Middle Channel	High Channel	
802.11b	-9.93	-10.28	-10.19	8dBm/3kHz
802.11g	-21.71	-21.08	-20.99	8dBm/3kHz
802.11n-HT20	-22.52	-22.24	-22.18	8dBm/3kHz
802.11n-HT40	-24.69	-24.00	-24.71	8dBm/3kHz

802.11b Low Channel



802.11b Middle Channel



802.11b High Channel



802.11g Low Channel



802.11g Middle Channel



802.11g High Channel



802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel



802.11n-HT20 High Channel



802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



12 Antenna Application

12.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT'S antenna, permanent attached antenna, is rod antenna. The antenna's gain is 0dBi and meets the requirement.

13 Test Setup

Conducted Emissions

Radiated Spurious Emissions
From 30MHz-1000MHz



Test frequency from 1GHz-26.5GHz



14 EUT Photos

Photo 1

Photo 2

Photo 3

Photo 4

Photo 5

Photo 6

Photo 7

Photo 8

Photo 9



Photo 10

Photo 11



Photo 12



Photo 13



Photo 14

Photo 15



Photo 16

*********** End of test report **********