

FCC ID: 2AWF7-CT10W-B1VO

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

MAX OUTPUT POWER
wifi

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVHT	802.11b	2412	Ant 1	11.08	30	Pass
NVHT	802.11b	2437	Ant 1	11.25	30	Pass
NVHT	802.11b	2462	Ant 1	11.01	30	Pass
NVHT	802.11g	2412	Ant 1	10.82	30	Pass
NVHT	802.11g	2437	Ant 1	11.19	30	Pass
NVHT	802.11g	2462	Ant 1	10.85	30	Pass
NVHT	802.11n(HT20)	2412	Ant 1	10.9	30	Pass
NVHT	802.11n(HT20)	2437	Ant 1	11.21	30	Pass
NVHT	802.11n(HT20)	2462	Ant 1	10.7	30	Pass

Measurement Result

Operation Frequency: WIFI: 2412-2462MHz for 802.11b/g/11n(HT20);

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: PCB Antenna

Antenna gain: 0.5dBi,
R=20cm

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
2412	802.11b	11.08	11±1	12	15.849	0.50	1.12	0.0035	1
2437		11.25	11±1	12	15.849	0.50	1.12	0.0035	1
2462		11.01	11±1	12	15.849	0.50	1.12	0.0035	1
2412	802.11g	10.82	11±1	12	15.849	0.50	1.12	0.0035	1
2437		11.19	11±1	12	15.849	0.50	1.12	0.0035	1
2462		10.85	11±1	12	15.849	0.50	1.12	0.0035	1
2412	802.11n(HT2 0)	10.9	11±1	12	15.849	0.50	1.12	0.0035	1
2437		11.21	11±1	12	15.849	0.50	1.12	0.0035	1
2462		10.7	11±1	12	15.849	0.50	1.12	0.0035	1

Conclusion:

For the max result : $0.0035 \leq 1.0$ for Max Power Density, compliance RF exposure..



Signature:

Date: 2020-06-01

NAME AND TITLE (Please print or type): Alex Li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.