TEST REPORT

Applicant	GOLABS INC.
Address	3900 W Plano Pkwy, Plano, TX 75075-7807, USA

Manufacturer or Supplier	ZHEJIANG TAOTAO VEHICLES CO., LTD
Address	No.10 XINYUAN ROAD, XINBI STREET, JINYUN COUNTY LISHUI CITY ZHEJIANG 321400, CHINA
Product	ELECTRIC DIRT BIKE
Brand Name	GOTRAX, Coleman
Model	M122
Additional Model & Model Difference	MK2, CRUISER; see items 3.1
Date of tests	Jun. 25, 2026 ~ Jun. 30, 2026

The tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Jul. 23, 2026

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

1 SUMMARY OF TEST RESULTS 5
2 MEASUREMENT UNCERTAINTY 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 8
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.4 DESCRIPTION OF SUPPORT UNITS 10
3.5 CONFIGURATION OF SYSTEM UNDER TEST 11
3.6 DUTY CYCLE OF TESET SIGNAL 11
4 TEST TYPES AND RESULTS 12
4.1 CONDUCTED EMISSION MEASUREMENT 12
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 12
4.1.2 TEST INSTRUMENTS 12
4.1.3 TEST PROCEDURES 13
4.1.4 DEVIATION FROM TEST STANDARD 13
4.1.5 TEST SETUP 14
4.1.6 EUT OPERATING CONDITIONS 14
4.1.7 TEST RESULTS 15
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT 17
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 17
4.2.2 TEST INSTRUMENTS 18
4.2.3 TEST PROCEDURES 19
4.2.4 DEVIATION FROM TEST STANDARD 19
4.2.5 TEST SETUP 20
4.2.6 EUT OPERATING CONDITIONS 21
4.2.7 TEST RESULTS 22
4.3 NUMBER OF HOPPING FREQUENCY USED 42
4.3.1 LIMIT OF HOPPING FREQUENCY USED 42
4.3.2 TEST SETUP 42
4.3.3 TEST INSTRUMENTS 42
4.3.4 TEST PROCEDURES 43
4.3.5 DEVIATION FROM TEST STANDARD 43
4.3.6 TEST RESULTS 44
4.4 DWELL TIME ON EACH CHANNEL 44
4.4.1 LIMIT OF DWELL TIME USED 46
4.4.2 TEST SETUP 46
4.4.3 TEST INSTRUMENTS 46
4.4.4 TEST PROCEDURES 46
4.4.5 DEVIATION FROM TEST STANDARD 46
4.4.6 TEST RESULTS 47

4.5 CHANNEL BANDWIDTH 50
4.5.1 LIMITS OF CHANNEL BANDWIDTH 50
4.5.2 TEST SETUP 50
4.5.3 TEST INSTRUMENTS 50
4.5.4 TEST PROCEDURE 50
4.5.5 DEVIATION FROM TEST STANDARD 50
4.5.6 EUT OPERATING CONDITION 50
4.5.7 TEST RESULTS 51
4.6 HOPPING CHANNEL SEPARATION 55
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 55
4.6.2 TEST SETUP 55
4.6.3 TEST INSTRUMENTS 55
4.6.4 TEST PROCEDURES 55
4.6.5 DEVIATION FROM TEST STANDARD 55
4.6.6 TEST RESULTS 56
4.7 CONDUCTED OUTPUT POWER 60
4.7.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 60
4.7.2 TEST SETUP 60
4.7.3 TEST INSTRUMENTS 60
4.7.4 TEST PROCEDURES 60
4.7.5 DEVIATION FROM TEST STANDARD 60
4.7.6 EUT OPERATING CONDITION 60
4.7.7 TEST RESULTS 61
4.8 OUT OF BAND EMISSION MEASUREMENT 62
4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 62
4.8.2 TEST INSTRUMENTS 62
4.8.3 TEST PROCEDURE 62
4.8.4 DEVIATION FROM TEST STANDARD 62
4.8.5 EUT OPERATING CONDITION 62
4.8.6 TEST RESULTS 62
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 67
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 68

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2606WDG0046	Original release	Jul. 23, 2026

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of Band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	0.15MHz ~ 30MHz	3.36dB
Radiated emissions	9KHz ~ 30MHz	2.48dB
	30MHz ~ 1GMHz	4.32dB
	1GHz ~ 18GHz	4.76dB
	18GHz ~ 40GHz	4.50dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	ELECTRIC DIRT BIKE
MODEL NO.	M122
ADDITIONAL MODEL	MK2, CRUISER
FCC ID	2AWFV-MK2
POWER SUPPLY	DC 24V from Li-ion battery; Charging: DC24V from Adapter
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, π/4 DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	2.208mW (Max. Measured)
ANTENNA TYPE	PCB Antenna, 2.499dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2606WDG0046-1) for detailed product photo.
4. Additional models (see above table) are identical with test model M122 except for color of appearance and model No. for trading purposes.
5. The EUT can be powered by adapter as list as following

ADAPTER	
BRAND:	
MODEL:	FY0422401000
INPUT:	AC 100-240V 50/60HZ 1.5A
OUTPUT:	DC 24V/1A
DC LINE:	Unshielded, Non-detachable, 150cm

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, power supply voltage range and antenna ports
The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	-	-	-	√	**Powered by Fully Battery**
B	√	√	√	-	**Powered by Adapter**

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
B	0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
B	0 to 78	0, 39, 78	FHSS	GFSK	DH5
B	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
B	BT Link

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
A	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	25deg. C, 58%RH	DC 24V From Fully Battery	Jeffery
RE≥1G	25deg. C, 58%RH	DC 24V From Fully Battery	Jeffery
PLC	25deg. C, 56%RH	DC 5V from Adapter	Summer
APCM	25deg. C, 58%RH	DC 24V From Fully Battery	Jeffery

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247
KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2020

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	REMARK
1	iPhone X	Apple	MQA52CH/A	N/A	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

3.5 CONFIGURATION OF SYSTEM UNDER TEST



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.6 DUTY CYCLE OF TESET SIGNAL

Test Mode	Packet Type	On Time (ms)	Period (ms)	Duty Cycle (%)	1/T Min. VBW (KHz)	VBW Setting (Hz)
BDR(GFSK)	DH5	2.884	3.752	76.87	0.347	500
EDR(8DPSK)	3DH5	2.889	3.768	76.67	0.346	500

BDR(GFSK)_DH5



EDR(8DPSK)_3DH5

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Oct. 10, 26
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Oct. 10, 26
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Oct. 10, 26
Artificial Mains Network	SCHWARZBECK	NSLK 8122	8122-05001	Nov. 04, 26
V-LISN (CISPR 25)	SCHWARZBECK	NNBM 8124-200	8124-200 05857	Apr. 08, 27
V-LISN (CISPR 25)	SCHWARZBECK	NNBM 8124-200	8124-200 05858	Apr. 08, 27
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jul. 02, 27
Coaxial RF Cable	SUHNER	RG 223/U-CE	C2310066DG	Jun. 21, 27
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A

NOTES: 1. The test was performed at Shielded Room 553.

2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.
b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: BT Link

PHASE	Line	6dB BANDWIDTH	9kHz

No.	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17838	9.57	30.78	12.31	40.35	21.88	64.56	54.56	-24.21	-32.68
2	0.36485	9.59	23.55	8.46	33.14	18.05	58.62	48.62	-25.48	-30.57
3	0.52523	9.60	23.56	9.90	33.16	19.50	56.00	46.00	-22.84	-26.50
4	0.64195	9.61	26.27	18.13	35.88	27.74	56.00	46.00	-20.12	-18.26
5	1.92750	9.65	25.06	10.66	34.71	20.31	56.00	46.00	-21.29	-25.69
6	4.49925	9.74	26.85	14.22	36.59	23.96	56.00	46.00	-19.41	-22.04

REMARKS:
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz

No.	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18364	9.58	30.45	13.07	40.03	22.65	64.32	54.32	-24.29	-31.67
2	0.37560	9.59	25.03	7.51	34.62	17.10	58.38	48.38	-23.75	-31.27
3	0.53362	9.61	24.59	10.35	34.20	19.96	56.00	46.00	-21.80	-26.04
4	0.63825	9.61	26.85	16.47	36.46	26.08	56.00	46.00	-19.54	-19.92
5	0.73254	9.62	25.12	8.64	34.74	18.26	56.00	46.00	-21.26	-27.74
6	**4.46775**	**9.74**	**28.99**	**17.05**	**38.73**	**26.79**	**56.00**	**46.00**	**-17.27**	**-19.21**

REMARKS:
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Oct. 09, 26
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Apr. 08, 27
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	Apr. 13, 27
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Feb. 12, 27
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 14, 26
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	0085519	Oct. 11, 26
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Apr. 19, 27
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 16, 27
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A

NOTES:

1. The test was performed in 966 Chamber.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.
3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
4. The FCC Site registration No. is 749762, and the designation number is CN1174.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz) and 0.1 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1.3m above the ground.

g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
4. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP

Below 30MHz test setup



Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

GFSK DH5

CHANNEL	Channel 39	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	51.76	29.58 QP	40.00	-10.42	1.44 H	63	46.23	-16.65
2	95.29	34.93 QP	43.50	-8.57	1.78 H	13	56.42	-21.49
3	191.67	36.45 QP	43.50	-7.05	1.98 H	45	55.88	-19.43
4	289.60	40.06 QP	46.00	-5.94	1.00 H	0	56.26	-16.20
5	308.25	41.15 QP	46.00	-4.85	1.00 H	0	56.77	-15.62
6	370.00	42.90 QP	46.00	-3.10	1.36 H	147	56.84	-13.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	38.01	37.50 QP	40.00	-2.50	2.17 V	132	54.89	-17.39
2	98.40	38.30 QP	43.50	-5.20	1.18 V	67	59.37	-21.07
3	128.00	40.70 QP	43.50	-2.80	1.51 V	163	58.54	-17.84
4	**149.70**	**41.60 QP**	**43.50**	**-1.90**	**1.64 V**	**52**	**58.10**	**-16.50**
5	340.90	42.60 QP	46.00	-3.40	1.32 V	140	57.24	-14.64
6	393.75	41.40 QP	46.00	-4.60	1.55 V	51	54.59	-13.19

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



ABOVE 1GHz WORST-CASE DATA:
GFSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.85 PK	74.00	-29.15	1.66 H	21	42.60	2.25
2	2390.00	32.31 AV	54.00	-21.69	1.66 H	21	30.06	2.25
3	*2402.00	87.21 PK			1.52 H	312	84.94	2.27
4	*2402.00	86.70 AV			1.52 H	312	84.43	2.27
5	4804.00	47.36 PK	74.00	-26.64	1.52 H	37	41.47	5.89
6	4804.00	46.43 AV	54.00	-7.57	1.52 H	37	40.54	5.89
7	7206.00	47.58 PK	74.00	-26.42	1.44 H	21	39.64	7.94
8	7206.00	37.25 AV	54.00	-16.75	1.44 H	21	29.31	7.94
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.14 PK	74.00	-29.86	1.27 V	14	41.89	2.25
2	2390.00	31.65 AV	54.00	-22.35	1.27 V	14	29.40	2.25
3	*2402.00	78.79 PK			1.22 V	52	76.52	2.27
4	*2402.00	78.30 AV			1.22 V	52	76.03	2.27
5	4804.00	47.05 PK	74.00	-26.95	1.86 V	64	41.16	5.89
6	4804.00	43.62 AV	54.00	-10.38	1.86 V	64	37.73	5.89
7	7206.00	47.17 PK	74.00	-26.83	1.53 V	25	39.23	7.94
8	7206.00	35.25 AV	54.00	-18.75	1.53 V	25	27.31	7.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

2402MHz Horizontal



2402MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

2402MHz Horizontal



2402MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	81.22 PK			1.62 H	125	78.91	2.31
2	*2441.00	80.78 AV			1.62 H	125	78.47	2.31
3	4882.00	46.83 PK	74.00	-27.17	1.53 H	69	41.10	5.73
4	4882.00	42.65 AV	54.00	-11.35	1.53 H	69	36.92	5.73
5	7323.00	47.53 PK	74.00	-26.47	1.66 H	32	39.97	7.56
6	7323.00	35.69 AV	54.00	-18.31	1.66 H	32	28.13	7.56
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	75.69 PK			1.25 V	36	73.38	2.31
2	*2441.00	75.33 AV			1.25 V	36	73.02	2.31
3	4882.00	47.34 PK	74.00	-26.66	1.32 V	62	41.61	5.73
4	4882.00	41.35 AV	54.00	-12.65	1.32 V	62	35.62	5.73
5	7323.00	47.01 PK	74.00	-26.99	1.20 V	113	39.45	7.56
6	7323.00	36.54 AV	54.00	-17.46	1.20 V	113	28.98	7.56

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

2441MHz Horizontal



2441MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

2441MHz Horizontal



2441MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	77.81 PK			1.25 H	24	75.45	2.36
2	*2480.00	77.43 AV			1.25 H	24	75.07	2.36
3	2483.50	44.60 PK	74.00	-29.40	1.24 H	84	42.24	2.36
4	2483.50	31.78 AV	54.00	-22.22	1.24 H	84	29.42	2.36
5	4960.00	46.20 PK	74.00	-27.80	1.65 H	42	40.62	5.58
6	4960.00	41.32 AV	54.00	-12.68	1.65 H	42	35.74	5.58
7	7440.00	47.62 PK	74.00	-26.38	1.49 H	41	40.45	7.17
8	7440.00	35.21 AV	54.00	-18.79	1.49 H	41	28.04	7.17
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	73.42 PK			1.62 V	42	71.06	2.36
2	*2480.00	73.07 AV			1.62 V	42	70.71	2.36
3	2483.50	43.36 PK	74.00	-30.64	1.25 V	69	41.00	2.36
4	2483.50	31.65 AV	54.00	-22.35	1.25 V	69	29.29	2.36
5	4960.00	46.88 PK	74.00	-27.12	1.20 V	130	41.30	5.58
6	4960.00	42.36 AV	54.00	-11.64	1.20 V	130	36.78	5.58
7	7440.00	47.74 PK	74.00	-26.26	1.03 V	36	40.57	7.17
8	7440.00	36.21 AV	54.00	-17.79	1.03 V	36	29.04	7.17

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

2480MHz Horizontal



2480MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

2480MHz Horizontal



2480MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

BT_8-DPSK 3DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	45.15 PK	74.00	-28.85	1.33 H	120	42.90	2.25
2	2390.00	32.30 AV	54.00	-21.70	1.33 H	120	30.05	2.25
3	*2402.00	86.91 PK			1.42 H	177	84.64	2.27
4	*2402.00	83.11 AV			1.42 H	177	80.84	2.27
5	4804.00	47.75 PK	74.00	-26.25	1.20 H	33	41.86	5.89
6	4804.00	43.32 AV	54.00	-10.68	1.20 H	33	37.43	5.89
7	7206.00	47.53 PK	74.00	-26.47	1.30 H	21	39.59	7.94
8	7206.00	38.21 AV	54.00	-15.79	1.30 H	21	30.27	7.94
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.06 PK	74.00	-29.94	1.58 V	47	41.81	2.25
2	2390.00	31.63 AV	54.00	-22.37	1.58 V	47	29.38	2.25
3	*2402.00	77.02 PK			1.72 V	36	74.75	2.27
4	*2402.00	74.43 AV			1.72 V	36	72.16	2.27
5	4804.00	46.92 PK	74.00	-27.08	1.25 V	314	41.03	5.89
6	4804.00	42.36 AV	54.00	-11.64	1.25 V	314	36.47	5.89
7	7206.00	48.21 PK	74.00	-25.79	1.88 V	142	40.27	7.94
8	7206.00	37.36 AV	54.00	-16.64	1.88 V	142	29.42	7.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

2402MHz Horizontal



2402MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

2402MHz Horizontal



2402MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	81.77 PK			1.35 H	136	79.46	2.31
2	*2441.00	78.43 AV			1.35 H	136	76.12	2.31
3	4882.00	47.05 PK	74.00	-26.95	1.36 H	21	41.32	5.73
4	4882.00	41.38 AV	54.00	-12.62	1.36 H	21	35.65	5.73
5	7323.00	47.74 PK	74.00	-26.26	1.02 H	124	40.18	7.56
6	7323.00	37.69 AV	54.00	-16.31	1.02 H	124	30.13	7.56
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	75.65 PK			1.20 V	136	73.34	2.31
2	*2441.00	73.73 AV			1.20 V	136	71.42	2.31
3	4882.00	46.92 PK	74.00	-27.08	1.05 V	79	41.19	5.73
4	4882.00	40.53 AV	54.00	-13.47	1.05 V	79	34.80	5.73
5	7323.00	47.18 PK	74.00	-26.82	1.60 V	108	39.62	7.56
6	7323.00	38.06 AV	54.00	-15.94	1.60 V	108	30.50	7.56

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

2441MHz Horizontal



2441MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

2441MHz Horizontal



2441MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	78.81 PK			1.35 H	114	76.45	2.36
2	*2480.00	78.45 AV			1.35 H	114	76.09	2.36
3	2483.50	45.97 PK	74.00	-28.03	1.36 H	144	43.61	2.36
4	2483.50	32.02 AV	54.00	-21.98	1.36 H	144	29.66	2.36
5	4960.00	46.85 PK	74.00	-27.15	1.24 H	7	41.27	5.58
6	4960.00	41.36 AV	54.00	-12.64	1.24 H	7	35.78	5.58
7	7440.00	47.86 PK	74.00	-26.14	1.20 H	13	40.69	7.17
8	7440.00	38.05 AV	54.00	-15.95	1.20 H	13	30.88	7.17
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	74.36 PK			1.20 V	130	72.00	2.36
2	*2480.00	73.92 AV			1.20 V	130	71.56	2.36
3	2483.50	43.36 PK	74.00	-30.64	1.20 V	188	41.00	2.36
4	2483.50	31.53 AV	54.00	-22.47	1.20 V	188	29.17	2.36
5	4960.00	48.02 PK	74.00	-25.98	1.54 V	117	42.44	5.58
6	4960.00	43.36 AV	54.00	-10.64	1.54 V	117	37.78	5.58
7	7440.00	47.28 PK	74.00	-26.72	1.62 V	28	40.11	7.17
8	7440.00	37.08 AV	54.00	-16.92	1.62 V	28	29.91	7.17

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

2480MHz Horizontal



2480MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

2480MHz Horizontal



2480MHz Vertical



Note: When the harmonic frequency test a fundamental frequency filter is used.

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY57320002	Apr. 08, 27
Digital Multimeter	FLUKE	15B	12151063	Apr. 07, 27
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Oct. 10, 26
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101003	Oct. 09, 26
Signal Generator	Agilent	N5183A	MY50140980	Jul. 02, 27
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jul. 02, 27
Attenuator	MINI	BW-S10W2+	S130129FGE2	Jul. 02, 27
DC Source	Rohde&Schwarz	HMP2020	101295	Apr. 07, 27
Test software	ADT	ADT_RF Test Software V6.6.5.3	N/A	N/A

NOTES:

1. The test was performed in RF Test Shielded Room.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.

4.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK





8DPSK


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-0.41 dBm
2.40200 GHz
Marker 2 [T1]
-0.10 dBm
2.44200 GHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
1
2
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-2.22 dBm
2.44300 GHz
Marker 2 [T1]
-0.40 dBm
2.48000 GHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
1
2
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.426	137.31	400	PASS
DH3	79	31.6	5	25	158	1.67	263.86	400	PASS
DH5	79	31.6	5	18	113.76	3.024	344.01	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	51	322.32	0.456	146.98	400	PASS
3DH3	79	31.6	5	26	164.32	1.68	276.06	400	PASS
3DH5	79	31.6	5	15	94.8	2.944	279.09	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK

DH1





DH3





DH5





8DPSK

3DH1





3DH3





3DH5





4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.07
39	2441	1.07
78	2480	1.08

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-21.87 dBm
2.44047 GHz
Delta 2 [T1]
0.00 dB
1.07 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
D1 -1.87 dBm
D2 -21.87 dBm
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-22.47 dBm
2.47946 GHz
Delta 2 [T1]
0.00 dB
1.08 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
D1 -2.47 dBm
D2 -22.47 dBm
Center 2.48 GHz
300 kHz/
Span 3 MHz

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.29
39	2441	1.30
78	2480	1.31

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-21.84 dBm
2.44036 GHz
Delta 2 [T1]
0.00 dB
1.30 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
D1 -1.84 dBm
D2 -21.84 dBm
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
F1
F2
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-22.43 dBm
2.47935 GHz
Delta 2 [T1]
0.00 dB
1.31 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
D1 -2.43 dBm
D2 -22.43 dBm
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
F1
F2
Center 2.48 GHz
300 kHz/
Span 3 MHz

4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHZ)	ADJACENT CHANNEL SEPARATION (MHZ)	20DB BANDWIDTH (MHZ)	MINIMUM LIMIT (MHZ)	PASS / FAIL
0	2402	1.00	1.07	0.72	PASS
39	2441	1.00	1.07	0.72	PASS
78	2480	1.00	1.08	0.72	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-1.89 dBm
2.44086 GHz
Delta 2 [T2]
0.02 dB
1.00 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
1
2
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
-2.47 dBm
2.47886 GHz
Delta 2 [T1]
0.25 dB
1.00 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
1
2
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	FREQUENCY (MHZ)	ADJACENT CHANNEL SEPARATION (MHZ)	20DB BANDWIDTH (MHZ)	MINIMUM LIMIT (MHZ)	PASS / FAIL
0	2402	1.00	1.29	0.86	PASS
39	2441	1.00	1.30	0.87	PASS
78	2480	1.00	1.31	0.88	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-1.81 dBm
2.44086 GHz
Delta 2 [T2]
0.14 dB
1.00 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
1
2
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
-2.47 dBm
2.47886 GHz
Delta 2 [T1]
0.03 dB
1.00 MHz
Ref 21 dBm
Att 20 dB
Offset 11 dB
21
10
0
-10
-20
-30
-40
-50
-60
-70
-79
1
2
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

4.7 CONDUCTED OUTPUT POWER

4.7.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 0.125W.

4.7.2 TEST SETUP



10dB ATTENUATION PAD

4.7.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	3.15	2.065	0.125	PASS
39	2441	3.16	2.07	0.125	PASS
78	2480	2.66	1.845	0.125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	**2402**	**3.44**	**2.208**	**0.125**	**PASS**
39	2441	3.31	2.143	0.125	PASS
78	2480	2.87	1.936	0.125	PASS

AVERAGE OUTPUT POWER (FOR REFERENCE)

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	1.08	1.282
39	2441	1.07	1.279
78	2480	0.59	1.146

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.58	1.143
39	2441	0.45	1.109
78	2480	-0.05	0.9886

4.8 OUT OF BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK

Low Channel





High Channel





8DPSK

Low Channel





High Channel





GFSK

Hopping on Low Channel





Hopping on High Channel





8DPSK

Hopping on Low Channel





Hopping on High Channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---