



FCC / ISED Test Report

For:

Smith & Nephew Medical, Ltd.

Model No:

66803126

Product Description:

The RENASYS EDGE is a Negative Pressure Wound Therapy device that has wireless interfaces to a user smartphone/tablet and the device canister.

FCC ID: 2AWH9-EDGE

IC ID: 26135-EDGE

Applied Rules and Standards:

47 CFR Part 15.247 (DTS)

RSS-247 Issue 2 (DTSS) & RSS-Gen Issue 5

REPORT #: EMC_SMITH-015-21001_FCC_15.247_Rev2

DATE: 2022-02-24



A2LA Accredited

IC recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: contact@cetecom.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT	3
2	ADMINISTRATIVE DATA	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER	4
3	EQUIPMENT UNDER TEST (EUT)	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS	6
3.3	ACCESSORY EQUIPMENT (AE) DETAILS	6
3.4	TEST SAMPLE CONFIGURATION	6
3.5	JUSTIFICATION FOR WORST CASE MODE OF OPERATION	6
4	SUBJECT OF INVESTIGATION	7
5	MEASUREMENT RESULTS SUMMARY	7
6	MEASUREMENT UNCERTAINTY	8
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING	8
6.2	DATES OF TESTING	8
7	MEASUREMENT PROCEDURES	9
7.1	RADIATED MEASUREMENT	9
7.2	POWER LINE CONDUCTED MEASUREMENT PROCEDURE	11
7.3	RF CONDUCTED MEASUREMENT PROCEDURE	11
8	TEST RESULT DATA	12
8.1	MAXIMUM PEAK CONDUCTED OUTPUT POWER	12
8.2	POWER SPECTRAL DENSITY	20
8.3	DUTY CYCLE	28
8.4	BAND EDGE COMPLIANCE	31
8.5	EMISSION BANDWIDTH 6dB AND 99% OCCUPIED BANDWIDTH	40
8.6	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS	54
8.7	AC POWER LINE CONDUCTED EMISSIONS	68
9	TEST SETUP PHOTOS	70
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	70
11	HISTORY	71

1 **Assessment**

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
Smith & Nephew Medical, Ltd.	The RENASYS EDGE is a Negative Pressure Wound Therapy device that has wireless interfaces to a user smartphone/tablet and the device canister.	66803126

Responsible for Testing Laboratory:

2022-02-24	Compliance	Kevin Wang (EMC Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2022-02-24	Compliance	Cheng Song (EMC Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.
CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Kevin Wang
Responsible Project Leader:	Cathy Palacios

2.2 Identification of the Client

Client's Name:	Smith & Nephew Medical, Ltd.
Street Address:	101 Hessle Road
City/Zip Code	Hull, HU3 2BN
Country	United Kingdom

2.3 Identification of the Manufacturer

Manufacturer's Name:	Plexus Corp
Manufacturers Address:	Pinnacle Hill Industrial Estate
City/Zip Code	Kelso, TD5 8XX, Scotland
Country	United Kingdom

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	66803126
HW Version :	1000026187 REV A.2
SW Version :	1000026850 REV 1.3.1
FCC-ID :	2AWH9-EDGE
IC-ID:	26135-EDGE
Product Description:	The RENASYS EDGE is a Negative Pressure Wound Therapy device that has wireless interfaces to a user smartphone/tablet and the device canister.
Radio Information:	<u>NFC:</u> • NXP SLRC61003HNY • Frequency of Operating: 13.56 MHz <u>Bluetooth:</u> • Nordic nRF52840 SoC • Frequency of Operating: 2402 MHz - 2480 MHz
Antenna Information:	<u>NFC:</u> • PCB Loop Antenna <u>Bluetooth:</u> • PCB Antenna
Power Supply/ Rated Operating Voltage Range:	Vmin: 10.8 V, Vmax: 13.2 V, Vnom: 12 V
Operating Temperature Range	Tmin: 5 °C , Tmax: 40 °C, Tnom: 25 °C
Sample Revision	☐ Prototype Unit; ☐ Production Unit; ☒ Pre-Production

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	21PEDL210020	1000026187 REV A.2	1000026850 REV 1.3.1	Radiated Measurement
2	21PEDL210011	1000026187 REV A.2	1000026850 REV 1.3.1	Conducted RF

3.3 Accessory Equipment (AE) details

AE #	Type	Manufacturer	Serial Number
1	AC / DC Adapter	SL Power Electronics	-
2	Canister (300ml or 800 ml)	Smith & Nephew Medical, Ltd.	-
3	Carry Bag	Smith & Nephew Medical, Ltd.	-

3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1 + AE#1 + AE#2	Radiated Measurement
2	EUT#2 + AE#1 + AE#2	Conducted RF

3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and highest possible duty cycle. For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISSED Canada.

This test report is to support a request for new equipment authorization under the

- FCC ID: 2AWH9-EDGE
- IC ID: 26135-EDGE

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(a)	Emission Bandwidth	Nominal	BTLE	■	□	□	Complies
§15.247(e) RSS-247 5.2(b)	Power Spectral Density	Nominal	BTLE	■	□	□	Complies
§15.247(b)(1) RSS-247 5.4(d)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	■	□	□	Complies
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BTLE	■	□	□	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	BTLE	■	□	□	Complies

Note: NA= Not Applicable; NP= Not Performed.

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Measurement System	EMC 1	EMC 2
Conducted Emissions (mains port)	1.12 dB	0.46 dB
Radiated Emissions		
(<30 MHz)	3.66 dB	3.88 dB
(30 MHz – 1 GHz)	3.17 dB	3.34 dB
(1 GHz – 3 GHz)	5.01 dB	4.45 dB
(> 3 GHz)	4.0 dB	4.79 dB

RF conducted measurement ± 0.5 dB

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

6.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 Dates of Testing:


12/17/2021 - 01/12/2022

7 Measurement Procedures


7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:


Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7.2 Power Line Conducted Measurement Procedure

AC Power Line conducted emissions measurements performed according to: ANSI C63.4 (2014)

7.3 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.

8 Test Result Data

8.1 Maximum Peak Conducted Output Power

8.1.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings:

- RBW $\geq$ DTS bandwidth
- VBW $\geq 3 \times$ RBW
- Span $\geq 3 \times$ RBW
- Sweep = Auto couple
- Detector function = Peak
- Trace = Max hold
- Use peak marker function to determine the peak amplitude level

8.1.2 Limits:

Maximum Peak Output Power:

- FCC §15.247 (b)(1): 1 W
- IC RSS-247: 1 W


8.1.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	2	BLE	120 VAC	2.13 dBi

8.1.4 Measurement result:

Plot #	Frequency (MHz)	Physical Layer	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	2402	LE 1M	-0.18	1.95	30 (Pk) / 36 (EIRP)	Pass
2	2440	LE 1M	-0.36	1.77	30 (Pk) / 36 (EIRP)	Pass
3	2480	LE 1M	-0.58	1.55	30 (Pk) / 36 (EIRP)	Pass
4	2402	LE 2M	-0.06	2.07	30 (Pk) / 36 (EIRP)	Pass
5	2440	LE 2M	-0.29	1.84	30 (Pk) / 36 (EIRP)	Pass
6	2480	LE 2M	-0.39	1.74	30 (Pk) / 36 (EIRP)	Pass

8.1.5 Measurement Plots:



Plot # 2

MARKER 1

2.439978333 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

-0.36 dBm


Ref 25 dBm

* Att 10 dB

SWT 15 ms

2.439978333 GHz

Offset 13.2 dB

1 PK
MAXH

Center 2.44 GHz

500 kHz/

Span 5 MHz

low

Date: 17.DEC.2021 12:42:38

Plot # 3

MARKER 1

2.479993333 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

-0.58 dBm


Ref 25 dBm

* Att 10 dB

SWT 15 ms

2.479993333 GHz

Offset 13.2 dB

1 PK
MAXH

Center 2.48 GHz

500 kHz/

Span 5 MHz

A

LVL

3DB

low

Date: 17.DEC.2021 12:44:13

Plot # 4

MARKER 1

2.402 GHz

* RBW 2 MHz

Marker 1 [T1]

* VBW 10 MHz

-0.06 dBm


Ref 25 dBm

* Att 10 dB

SWT 2.5 ms

2.402000000 GHz

Offset 13.2 dB

1 PK
MAXH

Center 2.402 GHz

1 MHz/

Span 10 MHz

low

Date: 3.FEB.2022 15:57:32

Plot # 5

MARKER 1

2.439903846 GHz

* RBW 2 MHz

Marker 1 [T1]

* VBW 10 MHz

-0.29 dBm


Ref 25 dBm

* Att 10 dB

SWT 2.5 ms

2.439903846 GHz

Offset 13.2 dB

1 PK
MAXH

Center 2.44 GHz

1 MHz/

Span 10 MHz

low

Date: 3.FEB.2022 15:59:20

Plot # 6

MARKER 1

2.479967949 GHz

* RBW 2 MHz

Marker 1 [T1]

* VBW 10 MHz

-0.39 dBm


Ref 25 dBm

* Att 10 dB

SWT 2.5 ms

2.479967949 GHz

Offset 13.2 dB

1 PK
MAXH

A

LVL

3DB

Center 2.48 GHz

1 MHz/

Span 10 MHz

low

Date: 3.FEB.2022 16:00:55

8.2 Power Spectral Density

8.2.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

8.2.2 Limits:

FCC§15.247(e) & RSS-247 5.2(b)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


8.2.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	2	BLE	120 VAC	2.13 dBi

8.2.4 Measurement result:

Plot #	Frequency (MHz)	Physical Layer	Maximum Power Spectral Density (dBm/3 kHz)	Limit (dBm / 3 kHz)	Result
1	2402	LE 1M	-16.03	8	Pass
2	2440	LE 1M	-16.31	8	Pass
3	2480	LE 1M	-16.60	8	Pass
4	2402	LE 2M	-18.60	8	Pass
5	2440	LE 2M	-18.81	8	Pass
6	2480	LE 2M	-18.99	8	Pass

8.2.5 Measurement Plots:



Plot # 2

MARKER 1

2.4399525 GHz

* RBW 3 kHz

Marker 1 [T1]

* VBW 10 kHz


-16.31 dBm

Ref 25 dBm

* Att 10 dB

SWT 170 ms

2.439952500 GHz



low

Date: 17.DEC.2021 12:50:18

Plot # 3

MARKER 1

2.4799515 GHz

* RBW 3 kHz

Marker 1 [T1]

* VBW 10 kHz


-16.60 dBm

Ref 25 dBm

* Att 10 dB

SWT 170 ms

2.479951500 GHz



low

Date: 17.DEC.2021 12:47:46

Plot # 4

MARKER 1

2.401975962 GHz

* RBW 3 kHz

Marker 1 [T1]

* VBW 10 kHz


-18.60 dBm

Ref 25 dBm

* Att 10 dB

SWT 340 ms

2.401975962 GHz



low

Date: 3.FEB.2022 16:10:53

Plot # 5

MARKER 1

2.439975962 GHz

* RBW 3 kHz

Marker 1 [T1]

* VBW 10 kHz


-18.81 dBm

Ref 25 dBm

* Att 10 dB

SWT 340 ms

2.439975962 GHz



low

Date: 3.FEB.2022 16:10:24

Plot # 6

MARKER 1

2.479975962 GHz

* RBW 3 kHz

Marker 1 [T1]

* VBW 10 kHz


-18.99 dBm

Ref 25 dBm

* Att 10 dB

SWT 340 ms

2.479975962 GHz



low

Date: 3.FEB.2022 16:09:50


8.3 Duty cycle

8.3.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings:

- Set the center frequency and of the instrument to the center frequency of the transmission
- Zero span
- Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value
- Detector = Peak or average

8.3.2 Measurement result




Duty cycle = 62.32%

Duty cycle correction factor = $10 \cdot \log(1/0.6232) = 2.05$ dB

Plot # 2

LE 2M



low

Date: 3.FEB.2022 16:14:55

Duty cycle = 32.69%

Duty cycle correction factor = $10 \cdot \log(1/0.3269) = 4.86$ dB

8.4 Band Edge Compliance

8.4.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW $\geq 3 \times$ RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

8.4.2 Limits non restricted band:

FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5/5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=1 MHz

8.4.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10

- *PEAK LIMIT= 74 dB μ V/m @3m =-21.23 dBm
- *AVG. LIMIT= 54 dB μ V/m @3m =-41.23 dBm
- Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
- Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

8.4.4 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	2	BLE	120 VAC	2.13 dBi

8.4.5 Measurement result:

Plot #	Physical Layer	Band Edge	Band Edge Delta (dBc)	Limit (dBc)	Result
1	LE 1M	Lower, Non-restricted	44.25	> 20	Pass
2	LE 2M	Lower, Non-restricted	32.93	> 20	Pass

Plot #	Physical Layer	Band Edge	Measured Peak Value (dBm)	Corrected by duty cycle	Corrected by Antenna Gain (dBm)	Limit (dBm)	Result
3	LE 1M	Upper Restricted Peak	-44.73	-42.68	-40.55	-21.23 Peak	Pass
4	LE 1M	Upper Restricted AVG	-58.03	-55.98	-53.85	-41.23 AVG	Pass
5	LE 2M	Upper Restricted Peak	-42.73	-37.87	-35.74	-21.23 Peak	Pass
6	LE 2M	Upper Restricted AVG	-57.63	-52.77	-50.64	-41.23 AVG	Pass

8.4.6 Measurement Plots:



Plot # 2

MARKER 1

2.402 GHz

Ref 25 dBm

* Att 10 dB

* RBW 100 kHz

* VBW 300 kHz

SWT 2.5 ms

Marker 1 [T1]

-0.74 dBm


2.402000000 GHz

Offset 13.2 dB

Delta 2 [T1]

-32.93 dB

-2.025641026 MHz

1 PK
MAXH

LVL

6DB

Center 2.4 GHz

800 kHz/

Span 8 MHz

low

Date: 3.FEB.2022 16:19:16

Plot # 3

MARKER 1

2.483607821 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

-44.73 dBm


Ref 25 dBm

* Att 10 dB

SWT 15 ms

2.483607821 GHz

Offset 13.2 dB

1 PK
MAXH

Center 2.4835 GHz

1 MHz/

Span 10 MHz

low

Date: 17.DEC.2021 14:14:24

Plot #4

MARKER 1

2.483543718 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

-58.03 dBm


Ref 25 dBm

* Att 10 dB

SWT 15 ms

2.483543718 GHz

Offset 13.2 dB

1 RM
AVG

Center 2.4835 GHz

1 MHz/

Span 10 MHz

A
SGL

LVL

6DB

low

Date: 17.DEC.2021 14:18:55

Plot # 5

MARKER 1

2.483511026 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

-42.73 dBm


Ref 25 dBm

* Att 10 dB

SWT 2.5 ms

2.483511026 GHz

Offset 13.2 dB

1 PK
MAXH

Center 2.4835 GHz

1 MHz/

Span 10 MHz

low

Date: 3.FEB.2022 16:24:22

Plot # 6

MARKER 1

2.483527051 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

-57.63 dBm


Ref 25 dBm

* Att 10 dB

SWT 2.5 ms

2.483527051 GHz

Offset 13.2 dB

1 RM
AVG

Center 2.4835 GHz

1 MHz/

Span 10 MHz

low

Date: 3.FEB.2022 16:27:13

8.5 Emission Bandwidth 6dB and 99% Occupied Bandwidth

8.5.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings:

6dB (DTS) Bandwidth:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99% Occupied Bandwidth:

- Set frequency = nominal EUT channel center frequency
- Set Span = 1.5 x to 5.0 x OBW
- Set RBW = 1% to 5% of OBW
- Set the video bandwidth (VBW) $\approx 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

8.5.2 Limits:

FCC §15.247(a)(2) and RSS-247 5.2(a)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.5.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22° C	2	BLE	120 VAC

8.5.4 Measurement result:

Plot #	Frequency (MHz)	Physical Layer	6dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
1	2402	LE 1M	0.692	> 0.5	Pass
2	2440	LE 1M	0.692	> 0.5	Pass
3	2480	LE 1M	0.693	> 0.5	Pass
4	2402	LE 2M	0.737	> 0.5	Pass
5	2440	LE 2M	1.186	> 0.5	Pass
6	2480	LE 2M	1.202	> 0.5	Pass

Plot #	Frequency (MHz)	Physical Layer	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
7	2402	LE 1M	1.055	> 0.5	Pass
8	2440	LE 1M	1.057	> 0.5	Pass
9	2480	LE 1M	1.055	> 0.5	Pass
10	2402	LE 2M	2.083	> 0.5	Pass
11	2440	LE 2M	2.083	> 0.5	Pass
12	2480	LE 2M	2.083	> 0.5	Pass

8.5.5 Measurement Plots:



Plot # 2

MARKER 1

2.439991667 GHz

* RBW 100 kHz

Marker 1 [T1]

* VBW 300 kHz

-0.91 dBm

Ref 25 dBm

* Att 10 dB

SWT 15 ms

2.439991667 GHz

Offset 13.2 dB

ndB [T1] 6.00 dB


BW 691.66666667 kHz

Temp 1 [T1 ndB] -6.97 dBm

2.439640000 GHz

Temp 2 [T1 ndB] -6.92 dBm

2.440331667 GHz

1 PK
MAXH

Center 2.44 GHz

500 kHz/

Span 5 MHz


A

LVL

3DB

low

Date: 17.DEC.2021 12:22:11



Plot # 4

MARKER 1

2.402 GHz

Ref 25 dBm

* Att 10 dB

* RBW 100 kHz

* VBW 300 kHz

SWT 5 ms

Marker 1 [T1]

-0.58 dBm

2.402000000 GHz

Offset 13.2 dB

ndB [T1] 6.00 dB

BW 737.179487179 kHz

Temp 1 [T1 ndB]


-6.57 dBm

2.401423077 GHz

Temp 2 [T1 ndB]

-6.59 dBm

2.402160256 GHz

1 PK
MAXH

Center 2.402 GHz

1 MHz/

Span 10 MHz

low

Date: 3.FEB.2022 16:05:53

Plot # 5

MARKER 1

2.439967949 GHz

* RBW 100 kHz

Marker 1 [T1]

* VBW 300 kHz


-1.38 dBm

Ref 25 dBm

* Att 10 dB

SWT 5 ms


2.439967949 GHz



low

Date: 3.FEB.2022 16:04:29

Plot # 6



low

Date: 3.FEB.2022 16:03:45

Plot # 7

MARKER 1

2.401996667 GHz

* RBW 50 kHz

Marker 1 [T1]

* VBW 200 kHz

-1.26 dBm

Ref 25 dBm

* Att 10 dB

SWT 15 ms

2.401996667 GHz

Offset 13.2 dB

OBW 1.055000000 MHz

Temp 1 [T1 OBW]


-17.38 dBm

2.401470000 GHz

Temp 2 [T1 OBW]

-16.56 dBm

2.402525000 GHz

1 PK
MAXH

low

Date: 17.DEC.2021 12:37:09

Plot # 8

MARKER 1

2.439995 GHz

* RBW 50 kHz

Marker 1 [T1]

* VBW 200 kHz


-1.29 dBm

Ref 25 dBm

* Att 10 dB


SWT 15 ms

2.439995000 GHz



low

Date: 17.DEC.2021 12:35:02



Plot # 10

MARKER 1

2.402 GHz

Ref 25 dBm

* Att 10 dB

* RBW 100 kHz

* VBW 300 kHz

SWT 5 ms

Marker 1 [T1]

-0.57 dBm

2.402000000 GHz

Offset 13.2 dB

OBW 2.083333333 MHz

Temp 1 [T1 OBW]


-15.09 dBm

2.400958333 GHz

Temp 2 [T1 OBW]

-15.29 dBm

2.403041667 GHz

1 PK
MAXH

low

Date: 3.FEB.2022 16:06:52

Plot # 11

MARKER 1

2.44 GHz

Ref 25 dBm

* Att 10 dB

* RBW 100 kHz

* VBW 300 kHz

SWT 5 ms

Marker 1 [T1]

-0.82 dBm

2.440000000 GHz

Offset 13.2 dB

OBW 2.083333333 MHz

Temp 1 [T1 OBW]


-15.10 dBm

2.438958333 GHz

Temp 2 [T1 OBW]


-15.59 dBm

2.441041667 GHz

1 PK
MAXH

low

Date: 3.FEB.2022 16:07:31



8.6 Radiated Transmitter Spurious Emissions and Restricted Bands

8.6.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing frequencies below 30 MHz at distance other than the specified in the standard, the limit conversion is calculated by using the FCC materials for the ANSI 63 committee issued on January, 27 1991.

8.6.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (μV/m)	Measurement Distance (m)	Field strength @ 3m (dBμV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBμV/m
88–216	150	3	43.5 dBμV/m
216–960	200	3	46 dBμV/m
Above 960	500	3	54 dBμV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74 dBμV/m

*AVG. LIMIT= 54 dBμV/m

8.6.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22° C	1	BT LE 1M	120 VAC


8.6.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low	30 MHz – 18 GHz	See section 8.6.2	Pass
4-8	Mid	9 kHz – 26 GHz	See section 8.6.2	Pass
9-11	High	30 MHz – 18 GHz	See section 8.6.2	Pass


8.6.5 Measurement Plots:

Plot # 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
66.883	37.25	40.00	2.75	500.0	120.000	188.0	V	180.0	11.3	
148.048	36.99	43.50	6.51	500.0	120.000	149.0	V	147.0	13.5	




— Preview Result 1-PK+ — FCC 15.209 QP at 3m ◆ Final_Result QPK




Plot # 3

Frequency	MaxPeak (dBμV/m)	CAverage	Limit (dBμV/m)	Margin	Meas.	Bandwidth	Height	Polarization	Azimuth	Corr. (dB/m)	Comment
7206.790	---	39.48	53.98	14.50	500.0	1000.000	150.0	H	244.0	1.1	
7206.790	52.06	---	73.98	21.92	500.0	1000.000	150.0	H	244.0	1.1	




◆ Preview Result 1-PK+ Final_Result PK+ ◆ FCC 15.209 PK at 3m Final_Result CAV — FCC 15.209 AVG at 3m



Plot # 5


Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
41.699	32.24	40.00	7.76	500.0	120.000	150.0	V	73.0	13.8	
67.083	37.70	40.00	2.30	500.0	120.000	150.0	V	169.0	11.3	
146.568	33.86	43.50	9.64	500.0	120.000	149.0	V	146.0	13.4	
923.313	24.37	46.02	21.65	500.0	120.000	293.0	V	103.0	30.1	



Preview Result 1-PK+ FCC 15.209 QP at 3m Final_Result QPK

Plot # 6


Frequency	MaxPeak (dBμV/m)	CAverage	Limit (dBμV/m)	Margin	Meas.	Bandwidth	Height	Pol	Azimuth	Corr. (dB/m)	Comment
1195.371	---	33.36	53.98	20.62	500.0	1000.000	150.0	V	208.0	3.7	
1195.371	53.59	---	73.98	20.39	500.0	1000.000	150.0	V	208.0	3.7	



◆ Preview Result 1-PK+ Final_Result PK+ ◆ FCC 15.209 PK at 3m Final_Result CAV — FCC 15.209 AVG at 3m


Plot # 7

Frequency	MaxPeak (dBμV/m)	CAverage	Limit (dBμV/m)	Margin	Meas.	Bandwidth	Height	Po l	Azimuth	Corr. (dB/m)	Comment
7319.257	---	40.03	53.98	13.95	500.0	1000.000	174.0	V	19.0	1.3	
7319.257	51.80	---	73.98	22.18	500.0	1000.000	174.0	V	19.0	1.3	



Plot # 8


Frequency	MaxPeak (dB μ V/m)	CAverage	Limit (dB μ V/m)	Margin	Meas.	Bandwidth	Height	Pol	Azimuth	Corr. (dB/m)	Comment
---	---	---	---	---	---	---	---		---	---	




Preview Result 1-PK+	*	Critical_Freqs PK+	FCC 15.209 PK at 1m
FCC 15.209 AVG at 1m	◆	Final_Result PK+	Final_Result CAV

Plot # 9

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
68.471	38.01	40.00	1.99	500.0	120.000	174.0	V	163.0	11.4	
150.403	40.32	43.50	3.18	500.0	120.000	150.0	V	145.0	13.8	




— Preview Result 1-PK+ — FCC 15.209 QP at 3m ◆ Final_Result QPK



Plot # 11

Frequency	MaxPeak (dBμV/m)	CAverage	Limit (dBμV/m)	Margin	Meas.	Bandwidth	Height	Polarization	Azimuth	Corr. (dB/m)	Comment
7439.353	---	39.54	53.98	14.44	500.0	1000.000	149.0	V	21.0	1.5	
7439.353	51.00	---	73.98	22.98	500.0	1000.000	149.0	V	21.0	1.5	



◆ Preview Result 1-PK+ Final_Result PK+ ◆ FCC 15.209 PK at 3m Final_Result CAV ◆ FCC 15.209 AVG at 3m

8.7 AC Power Line Conducted Emissions

8.7.1 Measurement according to ANSI C63.4

Analyzer Settings:

- RBW = 9 KHz (CISPR Bandwidth)
- Detector: Peak / Average for Pre-scan
- Quasi-Peak/Average for Final Measurements

8.7.2 Limits: §15.207 & RSS-Gen 8.8

FCC §15.207(a) & RSS-Gen 8.8

- Except as shown in paragraphs (b) and (c) of this section of the CFR, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table (1), as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

8.7.3 Test conditions and setup:

Ambient Temperature $^{\circ}$ C	EUT Set-Up #	EUT operating mode	Power line (L1, L2, L3, N)	Power Input
22 $^{\circ}$ C	1	BT LE 1M	Line & Neutral	120 VAC


8.7.4 Measurement Result:

Plot #	Port	Scan Frequency	Limit	Result
1	AC Mains	150 kHz – 30 MHz	See section 8.7.2	Pass

8.7.5 Measurement Plots:

Plot # 1

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	PE	Corr. (dB)	Comment
0.154	---	37.14	55.77	18.63	500.0	9.000	N	GND	10.4	
0.154	48.49	---	65.77	17.28	500.0	9.000	N	GND	10.4	



Preview Result 1-PK+
Final_Result QPK

EN 55032 Voltage on Mains QP
Final_Result CAV

EN 55032 Voltage on Mains A

9 Test setup photos

Setup photos are included in supporting file name: "EMC_SMITH-015-21001_FCC_Setup_Photos_Rev2.pdf"

10 Test Equipment And Ancillaries Used For Testing

Equipment Name/Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Biconilog Antenna	A.H. Systems	BiLA2G	569343	2 years	12/01/2020
Horn Antenna	ETS Lindgren	3115	35114	2 years	10/10/2020
Horn Antenna	ETS Lindgren	3117-PA	215984	2 years	01/31/2021
Active Loop Antenna	ETS Lindgren	6507	161344	2 years	10/30/2020
Horn Antenna	ETS Lindgren	3116C	70497	2 years	11/23/2020
LISN	FCC	FCC-LISN-50-25-2-08	8014	2 years	08/31/2021
Spectrum Analyzer	R&S	ESU40	100251	2 years	09/13/2021
Thermometer Humidity Monitor	CONTROL COMPANY	36934-164	191871986	2 years	10/20/2021

Note:

Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels.

Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

11 History

Date	Template Revision	Changes to report	Prepared by
2022-01-28	EMC_SMITH-015-21001_FCC_15.247	Initial Version	Cheng Song
2022-02-11	EMC_SMITH-015-21001_FCC_15.247_Rev1	Updated software version	Cheng Song
2022-02-24	EMC_SMITH-015-21001_FCC_15.247_Rev2	Updated supporting setup photos file name in section 9	Cheng Song

<<< The End >>>