



Fanguang Inspection & Testing Co., Ltd.  
Phone: +86-510-68790033  
Web: www.fgtest.cn



# MEASUREMENT REPORT

## FCC PART 15.247 / RSS-247 Bluetooth

Report No.: S202005114008E03

Report Version: V01

Issue Date: 07-01-2020

**Applicant:** kantiantech Inc.  
**Address:** NO.3 JinPin Street, Ya An Road, NanKai District. Tianjin  
China  
**FCC ID:** 2AWHIWSPRK1  
**IC:** 26041-WSPRK1  
**Application Type:** Certification  
**Product:** WYZE SPRINKLER CONTROLLER  
**Model No.:** WSPRK1  
**FCC Classification:** FCC Part 15 Spread Spectrum Transmitter (DSS)  
**FCC Rule Part(s):** Part 15 Subpart C (15.247)  
**IC Rule(s):** RSS-247 Issue 2, RSS-GEN Issue 5  
**Test Procedure(s):** ANSI C63.10-2013  
**Test Date:** May 19 ~ June 22, 2020

Reviewed By

*Line Chen*

(Line Chen)

Senior Test Engineer

Approved By

*Roy Cheng*

(Roy Cheng)

Senior Test Engineer

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fanguang Inspection & Testing Co., Ltd.

## CONTENTS

| Description                                                 | Page      |
|-------------------------------------------------------------|-----------|
| <b>§2.1033 General Information.....</b>                     | <b>5</b>  |
| <b>1. INTRODUCTION .....</b>                                | <b>6</b>  |
| 1.1. Scope .....                                            | 6         |
| 1.2. MRT Test Location .....                                | 6         |
| <b>2. PRODUCT INFORMATION.....</b>                          | <b>7</b>  |
| 2.1. Equipment Description .....                            | 7         |
| 2.2. Product Specification Subjective to this Standard..... | 7         |
| 2.3. Operation Frequency / Channel List.....                | 8         |
| 2.4. Pseudorandom Frequency Hopping Sequence .....          | 9         |
| 2.5. Device Capabilities.....                               | 10        |
| 2.6. Test Configuration .....                               | 10        |
| 2.7. EMI Suppression Device(s)/Modifications.....           | 10        |
| 2.8. Labeling Requirements .....                            | 11        |
| <b>3. DESCRIPTION of TEST.....</b>                          | <b>12</b> |
| 3.1. Evaluation Procedure .....                             | 12        |
| 3.2. AC Line Conducted Emissions.....                       | 12        |
| 3.3. Radiated Emissions.....                                | 13        |
| <b>4. ANTENNA REQUIREMENTS .....</b>                        | <b>14</b> |
| <b>5. TEST EQUIPMENT CALIBRATION DATE .....</b>             | <b>15</b> |
| <b>6. TEST RESULT .....</b>                                 | <b>16</b> |
| 6.1. Summary .....                                          | 16        |
| 6.2. 20dB Bandwidth Measurement .....                       | 17        |
| 6.2.1. Test Limit .....                                     | 17        |
| 6.2.2. Test Procedure used .....                            | 17        |
| 6.2.3. Test Setting.....                                    | 17        |
| 6.2.4. Test Setup .....                                     | 17        |
| 6.2.5. Test Result.....                                     | 18        |
| 6.3. Output Power Measurement .....                         | 23        |
| 6.3.1. Test Limit .....                                     | 23        |
| 6.3.2. Test Procedure Used.....                             | 23        |
| 6.3.3. Test Setting.....                                    | 23        |
| 6.3.4. Test Setup .....                                     | 23        |

|        |                                                |    |
|--------|------------------------------------------------|----|
| 6.3.5. | Test Result.....                               | 24 |
| 6.4.   | Carrier Frequency Separation Measurement ..... | 29 |
| 6.4.1. | Test Limit .....                               | 29 |
| 6.4.2. | Test Procedure Used .....                      | 29 |
| 6.4.3. | Test Setting.....                              | 29 |
| 6.4.4. | Test Setup .....                               | 30 |
| 6.4.5. | Test Result.....                               | 31 |
| 6.5.   | Number of Hopping Channels Measurement .....   | 33 |
| 6.5.1. | Test Limit .....                               | 33 |
| 6.5.2. | Test Procedure Used .....                      | 33 |
| 6.5.3. | Test Settintg.....                             | 33 |
| 6.5.4. | Test Setup .....                               | 33 |
| 6.5.5. | Test Result.....                               | 34 |
| 6.6.   | Time of Occupancy Measurement.....             | 36 |
| 6.6.1. | Test Limit .....                               | 36 |
| 6.6.2. | Test Procedure Used .....                      | 36 |
| 6.6.3. | Test Settintg.....                             | 36 |
| 6.6.4. | Test Setup .....                               | 37 |
| 6.6.5. | Test Result.....                               | 38 |
| 6.7.   | Band-edge Compliance Measurement.....          | 41 |
| 6.7.1. | Test Limit .....                               | 41 |
| 6.7.2. | Test Procedure Used .....                      | 41 |
| 6.7.3. | Test Setting.....                              | 41 |
| 6.7.4. | Test Setup .....                               | 42 |
| 6.7.5. | Test Result.....                               | 43 |
| 6.8.   | Conducted Spurious Emissions Measurement.....  | 50 |
| 6.8.1. | Test Limit .....                               | 50 |
| 6.8.2. | Test Procedure Used .....                      | 50 |
| 6.8.3. | Test Setting.....                              | 50 |
| 6.8.4. | Test Setup .....                               | 51 |
| 6.8.5. | Test Result.....                               | 52 |
| 6.9.   | Radiated Spurious Emission Measurement .....   | 67 |
| 6.9.1. | Test Limit .....                               | 67 |
| 6.9.2. | Test Procedure Used .....                      | 67 |
| 6.9.3. | Test Setting.....                              | 68 |
| 6.9.4. | Test Setup .....                               | 70 |
| 6.9.5. | Test Result.....                               | 71 |
| 6.10.  | Radiated Restricted Band Edge Measurement..... | 82 |

---

|           |                                         |            |
|-----------|-----------------------------------------|------------|
| 6.10.1.   | Test Procedure Used .....               | 85         |
| 6.10.2.   | Test Setting.....                       | 85         |
| 6.10.3.   | Test Setup .....                        | 86         |
| 6.10.4.   | Test Result.....                        | 87         |
| 6.11.     | AC Conducted Emissions Measurement..... | 111        |
| 6.11.1.   | Test Limit .....                        | 111        |
| 6.11.2.   | Test Setup .....                        | 111        |
| 6.11.3.   | Test Result.....                        | 112        |
| <b>7.</b> | <b>CONCLUSION.....</b>                  | <b>114</b> |

## §2.1033 General Information

|                                |                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant:</b>              | kantiantech Inc.                                                                                                                |
| <b>Applicant Address:</b>      | NO.3 JinPin Street,Ya An Road,NanKai District.Tianjin China                                                                     |
| <b>Manufacturer:</b>           | kantiantech Inc.                                                                                                                |
| <b>Manufacturer Address:</b>   | NO.3 JinPin Street,Ya An Road,NanKai District.Tianjin China                                                                     |
| <b>Factory:</b>                | kantiantech Inc.                                                                                                                |
| <b>Factory Address:</b>        | NO.3 JinPin Street,Ya An Road,NanKai District.Tianjin China                                                                     |
| <b>Test Site:</b>              | Fanguang Inspection & Testing Co., Ltd.                                                                                         |
| <b>Test Site Address:</b>      | 200 Linghu Avenue, Xinwu District, Wuxi City, China                                                                             |
| <b>Test Device Serial No.:</b> | N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering |
| <b>FCC Classification:</b>     | FCC Part 15 Spread Spectrum Transmitter (DSS)                                                                                   |

## **1. INTRODUCTION**

### **1.1. Scope**

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### **1.2. MRT Test Location**

These measurement tests were performed at the Fangguang Inspection and testing Co.,LTD located at 200 Linghu Avenue, Xinwu District, Wuxi City. The detailed description of the measurement facility was found to be in compliance with the requirements of ANSI C63.4-2014.

## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

|                      |                                                                                                        |
|----------------------|--------------------------------------------------------------------------------------------------------|
| Product Name:        | WYZE SPRINKLER CONTROLLER                                                                              |
| Model Name:          | WSPRK1                                                                                                 |
| Input Voltage Range: | AC 24V~, 60Hz, 800mA                                                                                   |
| Wi-Fi Specification: | 802.11b/g/n-HT20/n-HT40                                                                                |
| Bluetooth Version:   | V3.0/4.0                                                                                               |
| Adapter Information: | Model: HMQ-SM2401<br>Rated Input: 120V~, 60Hz , Max. Input current: 800mA,<br>Rated Output: 24V~, 1.0A |

### 2.2. Product Specification Subjective to this Standard

|                      |                                               |
|----------------------|-----------------------------------------------|
| Operating Frequency: | 2402~2480MHz                                  |
| Channel Number:      | 79                                            |
| Type of modulation:  | GFSK, Pi/4 DQPSK, 8DPSK                       |
| Data Rate:           | 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) |
| Antenna Type:        | FPC Antenna                                   |
| Antenna Gain:        | 2.64dBi                                       |

The equipment under test (EUT) is the **WYZE SPRINKLER CONTROLLER**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.


### 2.3. Operation Frequency / Channel List

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 00      | 2402 MHz  | 01      | 2403 MHz  | 02      | 2404 MHz  |
| 03      | 2405 MHz  | 04      | 2406 MHz  | 05      | 2407 MHz  |
| 06      | 2408 MHz  | 07      | 2409 MHz  | 08      | 2410 MHz  |
| 09      | 2411 MHz  | 10      | 2412 MHz  | 11      | 2413 MHz  |
| 12      | 2414 MHz  | 13      | 2415 MHz  | 14      | 2416 MHz  |
| 15      | 2417 MHz  | 16      | 2418 MHz  | 17      | 2419 MHz  |
| 18      | 2420 MHz  | 19      | 2421 MHz  | 20      | 2422 MHz  |
| 21      | 2423 MHz  | 22      | 2424 MHz  | 23      | 2425 MHz  |
| 24      | 2426 MHz  | 25      | 2427 MHz  | 26      | 2428 MHz  |
| 27      | 2429 MHz  | 28      | 2430 MHz  | 29      | 2431 MHz  |
| 30      | 2432 MHz  | 31      | 2433 MHz  | 32      | 2434 MHz  |
| 33      | 2435 MHz  | 34      | 2436 MHz  | 35      | 2437 MHz  |
| 36      | 2438 MHz  | 37      | 2439 MHz  | 38      | 2440 MHz  |
| 39      | 2441 MHz  | 40      | 2442 MHz  | 41      | 2443 MHz  |
| 42      | 2444 MHz  | 43      | 2445 MHz  | 44      | 2446 MHz  |
| 45      | 2447 MHz  | 46      | 2448 MHz  | 47      | 2449 MHz  |
| 48      | 2450 MHz  | 49      | 2451 MHz  | 50      | 2452 MHz  |
| 51      | 2453 MHz  | 52      | 2454 MHz  | 53      | 2455 MHz  |
| 54      | 2456 MHz  | 55      | 2457 MHz  | 56      | 2458 MHz  |
| 57      | 2459 MHz  | 58      | 2460 MHz  | 59      | 2461 MHz  |
| 60      | 2462 MHz  | 61      | 2463 MHz  | 62      | 2464 MHz  |
| 63      | 2465 MHz  | 64      | 2466 MHz  | 65      | 2467 MHz  |
| 66      | 2468 MHz  | 67      | 2469 MHz  | 68      | 2470 MHz  |
| 69      | 2471 MHz  | 70      | 2472 MHz  | 71      | 2473 MHz  |
| 72      | 2474 MHz  | 73      | 2475 MHz  | 74      | 2476 MHz  |
| 75      | 2477 MHz  | 76      | 2478 MHz  | 77      | 2479 MHz  |
| 78      | 2480 MHz  | -       | -         | -       | -         |

## 2.4. Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 2.5. Device Capabilities

This device contains the following capabilities:

2.4GHz WLAN (DTS) & Bluetooth (v3.0/4.0)

**Note:** The maximum achievable duty cycle was determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

| Test Mode | Duty Cycle |
|-----------|------------|
| DH5       | 76.80%     |
| 2DH5      | 77.20%     |
| 3DH5      | 76.87%     |

## 2.6. Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

## 2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

## **2.8. Labeling Requirements**

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

### RSP-100 Issue 11 Section 3

The manufacturer, importer or distributor shall meet the labelling requirements set out in this section for every unit:

- (i) prior to marketing in Canada, for products manufactured in Canada
- (ii) prior to importation into Canada, for imported products

For information regarding the e-labelling option, see Notice 2014-DRS1003. The label for the certified product represents the manufacturer's or importer's compliance with Innovation, Science and Economic Development Canada's (ISED) regulatory requirements.

Please see attachment for IC label and label location.

### 3. DESCRIPTION of TEST

#### 3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the “Filing were used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

#### 3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. The turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beamwidth of horn antenna, the horn antenna should be always directed to the EUT when rising height.

## 4. ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the EUT is **permanently attached**.
- There are no provisions for connection to an external antenna.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions

| Instrument         | Manufacturer | Type No. | Asset No.       | Cali. Interval | Cali. Due Date |
|--------------------|--------------|----------|-----------------|----------------|----------------|
| EMI Test Receiver  | R&S          | ESR3     | FWXGJC-2016-181 | 1 year         | 2021/03/23     |
| Two-Line V-Network | R&S          | ENV 216  | FWXGJC-2016-182 | 1 year         | 2021/03/15     |
| AMN                | AFJ          | LT32C/10 | FWXGJC-2016-179 | 1 year         | 2021/05/29     |
| Thermohygrometer   | Yuhuaze      | HTC-1    | FWXDA-2016-385  | 1 year         | 2021/02/28     |

### Radiated Emission

| Instrument             | Manufacturer | Type No.        | Asset No.          | Cali. Interval | Cali. Due Date |
|------------------------|--------------|-----------------|--------------------|----------------|----------------|
| Loop Antenna           | Schwarzbeck  | FMZB 1519B      | FWXGJC-2018-015    | 1 year         | 2021/08/23     |
| Bi-Log Antenna         | R&S          | HL562E          | FWXGJC-2016-267-06 | 3 year         | 2021/03/21     |
| Broadband Horn Antenna | R&S          | HF907           | FWXGJC-2016-267-07 | 1 year         | 2021/04/06     |
| Broadband Horn Antenna | Schwarzbeck  | BBHA9170        | FWXGJC-2018-016    | 1 year         | 2021/08/19     |
| EMI Receiver           | R&S          | ESR26           | FWXGJC-2016-267-01 | 1 year         | 2021/03/23     |
| Pre-Amplifier          | R&S          | SCU-18D         | FWXGJC-2016-267-05 | 1 year         | 2021/03/15     |
| Pre-Amplifier          | R&S          | EMC184055<br>SE |                    |                | 2020/08/09     |
| Thermohygrometer       | Yuhuaze      | HTC-1           | FWXDA-2016-386     | 1 year         | 2021/02/28     |
| Anechoic Chamber       | Aimuke       | EMCCT-3         | FWXGJC-2016-270    | 1 year         | 2021/04/10     |

### Conducted Test Equipment

| Instrument          | Manufacturer | Type No. | Asset No.       | Cali. Interval | Cali. Due Date |
|---------------------|--------------|----------|-----------------|----------------|----------------|
| EXA Signal Analyzer | Keysight     | N9010B   | FWXGJC-2018-010 | 1 year         | 2021/05/29     |
| RF Control Unit     | Toncend      | JS0806-2 | FWXGJC-2018-013 | 1 year         | 2020/10/16     |
| Thermohygrometer    | Yuhuaze      | HTC-1    | FWXDA-2016-385  | 1 year         | 2021/02/28     |

| Test Software     | Manufacturer | Version | Asset No. | Function |
|-------------------|--------------|---------|-----------|----------|
| EMI Test Software | tonscend     | /       | /         | /        |

## 6. TEST RESULT

### 6.1. Summary

| FCC Part Section(s)    | IC Section(s)    | Test Description                                                                 | Test Limit                                                                     | Test Condition | Test Result | Reference                   |
|------------------------|------------------|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------|----------------|-------------|-----------------------------|
| 15.247(a)(1)           | RSS-247 [5.1]    | 20dB Bandwidth                                                                   | N/A                                                                            | Conducted      | PASS        | Section 7.2                 |
| 15.247(b)(1)           | RSS-247 [5.4(b)] | Peak Transmitter Output Power                                                    | <0.125 Watt if > 75 non- overlapping channels used                             |                | PASS        | Section 7.3                 |
| 15.247(a)(1)           | RSS-247 [5.1]    | Channel Separation                                                               | > 2/3 of 20 dB BW for systems with Output Power < 125mW                        |                | PASS        | Section 7.4                 |
| 15.247(a)(1)(i)<br>ii) | RSS-247 [5.1]    | Number of Channels                                                               | > 15 Channels                                                                  |                | PASS        | Section 7.5                 |
| 15.247(a)(1)(i)<br>ii) | RSS-247 [5.1]    | Time of Occupancy                                                                | < 0.4 sec in 31.6 sec period                                                   |                | PASS        | Section 7.6                 |
| 15.247(d)              | RSS-247 [5.5]    | Band Edge / out-of-Band Emissions                                                | Conducted $\geq$ 20dBc                                                         |                | PASS        | Section 7.7<br>Section 7.8  |
| 15.205,<br>15.209      | RSS-247 [5.5]    | General Field Strength Limits<br>(Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 | Radiated       | PASS        | Section 7.9<br>Section 7.10 |
| 15.207                 | RSS-Gen [8.8]    | AC Conducted Emissions<br>150kHz - 30MHz                                         | < FCC 15.207 limits                                                            | Line Conducted | Pass        | Section 7.11                |

#### Notes:

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.

## 6.2. 20dB Bandwidth Measurement

### 6.2.1. Test Limit

N/A


### 6.2.2. Test Procedure used

ANSI C63.10-2013 - Section 6.9.2

### 6.2.3. Test Setting


1. Set RBW  $\geq 1\%$  to 5% of the 20dB bandwidth
2. VBW = approximately three times RBW
3. Span = approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### 6.2.4. Test Setup





## 6.2.5. Test Result


| Test Mode | Antenna | Channel | 20db EBW[MHz] | FL[MHz]  | FH[MHz]  | 99% BW (MHz) | Verdict |
|-----------|---------|---------|---------------|----------|----------|--------------|---------|
| DH5       | Ant1    | 2402    | 1.062         | 2401.475 | 2402.537 | 0.83432      | PASS    |
|           |         | 2441    | 1.059         | 2440.472 | 2441.531 | 0.85273      | PASS    |
|           |         | 2480    | 1.056         | 2479.445 | 2480.501 | 0.83802      | PASS    |
| 2DH5      | Ant1    | 2402    | 1.374         | 2401.301 | 2402.675 | 1.1873       | PASS    |
|           |         | 2441    | 1.380         | 2440.298 | 2441.678 | 1.1932       | PASS    |
|           |         | 2480    | 1.368         | 2479.301 | 2480.669 | 1.1853       | PASS    |
| 3DH5      | Ant1    | 2402    | 1.389         | 2401.304 | 2402.693 | 1.1987       | PASS    |
|           |         | 2441    | 1.386         | 2440.313 | 2441.699 | 1.2047       | PASS    |
|           |         | 2480    | 1.392         | 2479.292 | 2480.684 | 1.1827       | PASS    |




### DH5\_Ant1\_2441




### DH5\_Ant1\_2480




## 2DH5\_Ant1\_2402




## 2DH5\_Ant1\_2441




## 2DH5\_Ant1\_2480




## 3DH5\_Ant1\_2402



## 3DH5\_Ant1\_2441



## 3DH5\_Ant1\_2480



## 6.3. Output Power Measurement

### 6.3.1. Test Limit

The maximum out power permissible output power is 0.125 Watt for all other frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.


### 6.3.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.5

### 6.3.3. Test Setting


1. Set RBW  $\geq$  the 20 dB bandwidth of the emission being measured.
2. VBW  $\geq$  RBW
3. Span = approximately five times the 20dB bandwidth, centered on a hopping channel
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss)

### 6.3.4. Test Setup



### 6.3.5.Test Result

| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5       | Ant1    | 2402    | 5.15        | <=21.00    | PASS    |
|           |         | 2441    | 6.02        | <=21.00    | PASS    |
|           |         | 2480    | 7.20        | <=21.00    | PASS    |
| 2DH5      | Ant1    | 2402    | 7.54        | <=21.00    | PASS    |
|           |         | 2441    | 8.16        | <=21.00    | PASS    |
|           |         | 2480    | 9.49        | <=21.00    | PASS    |
| 3DH5      | Ant1    | 2402    | 8.07        | <=21.00    | PASS    |
|           |         | 2441    | 8.65        | <=21.00    | PASS    |
|           |         | 2480    | 9.95        | <=21.00    | PASS    |



### DH5\_Ant1\_2441



### DH5\_Ant1\_2480



## 2DH5\_Ant1\_2402



## 2DH5\_Ant1\_2441




## 2DH5\_Ant1\_2480




## 3DH5\_Ant1\_2402



## 3DH5\_Ant1\_2441



## 3DH5\_Ant1\_2480



## **6.4. Carrier Frequency Separation Measurement**

### **6.4.1. Test Limit**

For BDR Mode, the minimum permissible channel separation for this system is the value of the 20dB BW. For EDR Mode, the minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.


### **6.4.2. Test Procedure Used**

ANSI C63.10-2013 - Section 7.8.2

### **6.4.3. Test Setting**

1. Span = wide enough to capture the peaks of two adjacent channels.
2. Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
3.  $VBW \geq RBW$
4. Sweep time = Auto couple
5. Detector = Peak
6. Trace mode = Max hold
7. Allowed the trace to stabilize
8. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

#### 6.4.4. Test Setup




### 6.4.5. Test Result

| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm]   | Verdict |
|-----------|---------|---------|-------------|--------------|---------|
| DH5       | Ant1    | Hop     | 1.06        | $\geq 0.708$ | PASS    |
| 2DH5      | Ant1    | Hop     | 0.966       | $\geq 0.920$ | PASS    |
| 3DH5      | Ant1    | Hop     | 1.148       | $\geq 0.928$ | PASS    |

#### DH5\_Ant1\_Hop



#### 2DH5\_Ant1\_Hop



## 3DH5\_Ant1\_Hop



## 6.5. Number of Hopping Channels Measurement

### 6.5.1. Test Limit

This frequency hopping system must employ a minimum of 15 hopping channels.


### 6.5.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.3

### 6.5.3. Test Setting

1. Span = the frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
2. To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3.  $VBW \geq RBW$
4. Sweep time = Auto couple
5. Detector = Peak
6. Trace mode = Max hold
7. Allow the trace to stabilize


### 6.5.4. Test Setup




### 6.5.5.Test Result

| Test Mode | Antenna | Channel | Result[Num] | Limit[Num] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| DH5       | Ant1    | Hop     | 79          | >=15       | PASS    |
| 2DH5      | Ant1    | Hop     | 79          | >=15       | PASS    |
| 3DH5      | Ant1    | Hop     | 79          | >=15       | PASS    |


#### DH5\_Ant1\_Hop



#### 2DH5\_Ant1\_Hop



#### 3DH5\_Ant1\_Hop



## **6.6. Time of Occupancy Measurement**

### **6.6.1. Test Limit**

The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.


### **6.6.2. Test Procedure Used**

ANSI C63.10-2013 - Section 7.8.4

### **6.6.3. Test Setting**

1. Span = zero span, centered on a hopping channel.
2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where T is the expected dwell time per channel.
3. VBW  $\geq$  RBW
4. Sweep time = as necessary to capture the entire dwell time per hopping channel
5. Detector = Peak
6. Trace mode = max hold
7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.



### 6.6.4. Test Setup




### 6.6.5. Test Result

| Test Mode | Antenna | Channel | BurstWidth<br>[ms] | TotalHops<br>[Num] | Result[s] | Limit[s] | Verdict |
|-----------|---------|---------|--------------------|--------------------|-----------|----------|---------|
| DH1       | Ant1    | Hop     | 0.38               | 110                | 0.041     | <=0.4    | PASS    |
| DH3       | Ant1    | Hop     | 1.63               | 130                | 0.212     | <=0.4    | PASS    |
| DH5       | Ant1    | Hop     | 2.88               | 80                 | 0.23      | <=0.4    | PASS    |

#### DH1\_Ant1\_Hop



#### DH3\_Ant1\_Hop



DH5\_Ant1\_Hop

