

JOYROOM



JOYROOM

User Manual

Auto Match Wireless Car Charger Holder


Parameters

Model	JZ25298
Name	Auto Match Wireless Car Charger Holder
Material	ABS+PC
Input	5V/2A 9V/2A 12V/2A
Output	5W/7.5W/10W/15W (MAX)
Input port	Type-C
Applicable phone size	4.5-6.7"

Indicator light

Bottom foot indicator light	Power on: constant blue light Charging: breathing blue light Standby: constant blue light POD: flashing blue light
Clamp arm indicator light	The light will turn on when the clamp arms open

Product diagram



Electric adjustment panel

Clamp arm

Button

Indicator light

Air vent clip

Operating steps (Air vent)

1. Put the universal ball into the nut first, then insert it into the socket on the back of the holder.

2. Fasten the nut clockwise to its position.

3. Loosen the knob and open the hook, insert the hook onto vent blade, then fasten the knob.

4. Use the Type-C charging cable in the package to connect the charger and the car holder, the clamp arms will automatically open.

5. Place your phone. The clamp arms will automatically lock and align with it to start charging.

6. Press the side button to open the clamp arms and take out your phone.

2. Fasten the nut clockwise to its position.

3. Loosen the knob and open the hook, insert the hook onto vent blade, then fasten the knob.

4. Use the Type-C charging cable in the package to connect the charger and the car holder, the clamp arms will automatically open.

5. Place your phone. The clamp arms will automatically lock and align with it to start charging.

6. Press the side button to open the clamp arms and take out your phone.

2. Fasten the nut clockwise to its position.

3. Loosen the knob and open the hook, insert the hook onto vent blade, then fasten the knob.

4. Use the Type-C charging cable in the package to connect the charger and the car holder, the clamp arms will automatically open.

5. Place your phone. The clamp arms will automatically lock and align with it to start charging.

6. Press the side button to open the clamp arms and take out your phone.

2. Fasten the nut clockwise to its position.

3. Loosen the knob and open the hook, insert the hook onto vent blade, then fasten the knob.

4. Use the Type-C charging cable in the package to connect the charger and the car holder, the clamp arms will automatically open.

5. Place your phone. The clamp arms will automatically lock and align with it to start charging.

6. Press the side button to open the clamp arms and take out your phone.

Warning

1. Do not disassemble or refit the product.

2. Do not store it in a wet environment.

3. Please keep the product away from heat and do not charge it near a heat source.

4. Please prevent water or other liquid from entering the product interface. Otherwise the product may be damaged.

5. Do not install the wireless car charger mount over an air bag cover or within the air bag deployment zone.

6. During charging, make sure to remove the metal/magnetic protective case or cards (like bank cards), etc. from your device.

7. During charging, the charger may heat up. This is a normal occurrence and won't affect its performance. If the charger or your phone is too hot, please disconnect the power supply and let it cool down before restarting the charging process.

8. Avoid using bent or damaged USB cables.

Warranty Card

Model:	Customer Name:
Purchase Date:	Tel:
Distributor:	Invoice Date:
User address (with postcode):	


Warranty

A. If there is performance failure on this product and it's not caused by human error damage, we will provide 3 months free warranty service for consumers from the date of purchase.

B. Warranty Exceptions:

- Human damage.
- Expired the warranty period.
- Failure to provide valid purchase certificate.
- Product damage caused by failure to follow the use, maintain and preserve instructions.
- Product damage caused by domestic fire or repair the product without authorization or immerse the product in water.
- Damage caused by other force majeure.

JOYROOM



JOYROOM

使用说明

滑动式车载无线充支架


产品规格

产品型号	JZ25298
产品名称	滑动式车载无线充支架
产品材质	ABS+PC
输入	5V/2A 9V/2A 12V/2A
输出	5W/7.5W/10W/15W (MAX)
输入接口	Type-C
适用尺寸	4.5-6.7英寸

指示灯

通电量灯长亮	
充电量灯闪烁	
充电量灯长亮	
充电量灯闪烁	
充电量灯长亮	

产品示意图



电动滑动面板

夹臂

按钮

指示灯

出风口夹子

产品使用

1. 将设备与配件连接到本产品, 将方向球穿过螺母插入到产品背部的螺栓型。

2. 顺时针方向拧紧螺母。

3. 旋转按钮打开夹臂, 插入出风口, 再旋转按钮, 夹住出风口扇叶叶片。

4. 使用包装内的Type-C充电线连接支架与车充, 夹臂自动张开, 机身滑动时后即可进行充电。

5. 放入手机, 夹臂自动夹紧, 机身滑动时后即可进行充电。

6. 按压侧开夹臂, 夹臂打开, 取出手机。

2. 顺时针方向拧紧螺母。

3. 旋转按钮打开夹臂, 插入出风口, 再旋转按钮, 夹住出风口扇叶叶片。

4. 使用包装内的Type-C充电线连接支架与车充, 夹臂自动张开, 机身滑动时后即可进行充电。

5. 放入手机, 夹臂自动夹紧, 机身滑动时后即可进行充电。

6. 按压侧开夹臂, 夹臂打开, 取出手机。

2. 顺时针方向拧紧螺母。

3. 旋转按钮打开夹臂, 插入出风口, 再旋转按钮, 夹住出风口扇叶叶片。

4. 使用包装内的Type-C充电线连接支架与车充, 夹臂自动张开, 机身滑动时后即可进行充电。

5. 放入手机, 夹臂自动夹紧, 机身滑动时后即可进行充电。

6. 按压侧开夹臂, 夹臂打开, 取出手机。

2. 顺时针方向拧紧螺母。

3. 旋转按钮打开夹臂, 插入出风口, 再旋转按钮, 夹住出风口扇叶叶片。

4. 使用包装内的Type-C充电线连接支架与车充, 夹臂自动张开, 机身滑动时后即可进行充电。

5. 放入手机, 夹臂自动夹紧, 机身滑动时后即可进行充电。

6. 按压侧开夹臂, 夹臂打开, 取出手机。

警告

1. 请勿自行拆卸或损坏本产品。

2. 请勿将本产品放在潮湿环境。

3. 请勿将本产品靠近热源或于热源附近充电。

4. 请勿将本产品或配件放入本产品包装盒内, 导致本产品损坏。

5. 不要将无线充电接收器安装在金属或金属保护壳或卡 (如银行卡等)。

6. 使用过程中可能产生热量, 此为正常现象, 并不会影响产品表现, 如感觉到手机或本产品过热请暂停充电, 待冷却后再继续使用。

7. 使用过程中可能产生热量, 此为正常现象, 并不会影响产品表现, 如感觉到手机或本产品过热请暂停充电, 待冷却后再继续使用。

8. 避免使用折曲或损坏的USB线材。

保修卡

产品型号:	用户姓名:
购买日期:	用户电话:
代理商:	发票日期:
用户地址 (含邮编):	

保修服务说明

凡在正常使用本产品过程中, 如果本产品出现非人为损坏的性能故障, 自购买之日起, 消费者享受免费保修服务。

保修期为12个月。

但有以下几种情况之一, 消费者不能享受免费保修权益:

- "人为损坏"
- "超出保修期"
- "不能提供有效的购买凭证"
- "未按说明书要求使用、维护、保养而造成产品损坏"
- "未经授权, 擅自拆卸、维修产品, 造成产品损坏"
- "其他不可抗力造成的损坏"

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.