Test Report (Bluetooth)

Applicant:	RION TECH (SHEN ZHEN) CO.,LTD.
Address of Applicant:	No.502,No.84,Langkou Village 1 District Langkou Community Dalang Street,Longhua District,Shenzhen,China
Manufacturer/Factory:	RION TECH (SHEN ZHEN) CO.,LTD.
Address of Manufacturer/Factory:	No.502,No.84,Langkou Village 1 District Langkou Community Dalang Street,Longhua District,Shenzhen,China

Equipment Under Test (EUT)

Product Name:	RWS Active Noise Reduction Earphone
Model No.:	T1-ANC
FCC ID:	2AWLN-T1ANC
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	June 03, 2020
Date of Test:	June 03-10, 2020
Date of report issued:	June 11, 2020
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*June 11, 2020*	*Original*

Prepared By: ***Date:*** *June 11, 2020*

Project Engineer

Check By: ***Date:*** *June 11, 2020*

Reviewer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 DESCRIPTION OF SUPPORT UNITS 7
5.4 DEVIATION FROM STANDARDS 7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS 7
5.6 TEST FACILITY 7
5.7 TEST LOCATION 7
5.8 ADDITIONAL INSTRUCTIONS 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED OUTPUT POWER 16
7.4 CHANNEL BANDWIDTH 18
7.5 POWER SPECTRAL DENSITY 20
7.6 BAND EDGES 22
7.6.1 Conducted Emission Method 22
7.6.2 Radiated Emission Method 24
7.7 SPURIOUS EMISSION 29
7.7.1 Conducted Emission Method 29
7.7.2 Radiated Emission Method 31

8 TEST SETUP PHOTO 44

9 EUT CONSTRUCTIONAL DETAILS 44

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remarks:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10:2013*

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	RWS Active Noise Reduction Earphone
Model No.:	T1-ANC
Test sample(s) ID:	GTS202006000050-1
Sample(s) Status:	Engineer sample
Serial No.:	T12020060200001
Hardware Version:	V3.0
Software Version:	V1.7.1.3
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	Microwave Multi-Layer Ceramic Antenna
Antenna Gain:	5.54dBi(declare by applicant)
Power Supply:	Charge box: Battery DC 3.7V, 400mAh Earphone: Battery DC 3.7V, 35mAh

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test,the test voltage was tuned from AC120V to AC240V, and found that the worst case was the AC120V. So the report just shows that condition's data.	

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
APPLE	USB Charger	A1399	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 26 2019	June. 25 2020
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 26 2019	June. 25 2020
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 26 2019	June. 25 2020
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 26 2019	June. 25 2020
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 26 2019	June. 25 2020
9	Coaxial Cable	GTS	N/A	GTS211	June. 26 2019	June. 25 2020
10	Coaxial cable	GTS	N/A	GTS210	June. 26 2019	June. 25 2020
11	Coaxial Cable	GTS	N/A	GTS212	June. 26 2019	June. 25 2020
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 26 2019	June. 25 2020
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 26 2019	June. 25 2020
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 26 2019	June. 25 2020
15	Band filter	Amindeon	82346	GTS219	June. 26 2019	June. 25 2020
16	Power Meter	Anritsu	ML2495A	GTS540	June. 26 2019	June. 25 2020
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 26 2019	June. 25 2020
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 26 2019	June. 25 2020
19	Splitter	Agilent	11636B	GTS237	June. 26 2019	June. 25 2020
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 26 2019	June. 25 2020
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 26 2019	June. 25 2020

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 26 2019	June. 25 2020
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 26 2019	June. 25 2020
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 26 2019	June. 25 2020
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 26 2019	June. 25 2020
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 26 2019	June. 25 2020

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 26 2019	June. 25 2020
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 26 2019	June. 25 2020
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 26 2019	June. 25 2020
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 26 2019	June. 25 2020
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 26 2019	June. 25 2020
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 26 2019	June. 25 2020
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 26 2019	June. 25 2020

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 26 2019	June. 25 2020
2	Barometer	ChangChun	DYM3	GTS255	June. 26 2019	June. 25 2020

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The antenna is Microwave Multi-Layer Ceramic antenna, the best case gain of the antenna is 5.54dBi, reference to the appendix II for details	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Class / Severity:	Class B
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2009 on conducted measurement.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data
Right earphone
Line:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.23	8.56	20.40	0.11	29.07	62.30	-33.23	QP
0.23	1.06	20.40	0.11	21.57	52.30	-30.73	Average
0.32	12.86	20.39	0.10	33.35	59.80	-26.45	QP
0.32	4.80	20.39	0.10	25.29	49.80	-24.51	Average
0.37	7.57	20.37	0.10	28.04	58.56	-30.52	QP
0.37	0.00	20.37	0.10	20.47	48.56	-28.09	Average
0.50	8.87	20.31	0.11	29.29	56.00	-26.71	QP
0.50	1.34	20.31	0.11	21.76	46.00	-24.24	Average
0.63	13.27	20.28	0.12	33.67	56.00	-22.33	QP
0.63	5.03	20.28	0.12	25.43	46.00	-20.57	Average
0.78	5.38	20.24	0.14	25.76	56.00	-30.24	QP
0.78	-2.83	20.24	0.14	17.55	46.00	-28.45	Average

Neutral:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.23	9.94	20.40	0.11	30.45	62.30	-31.85	QP
0.23	2.45	20.40	0.11	22.96	52.30	-29.34	Average
0.32	14.23	20.39	0.10	34.72	59.80	-25.08	QP
0.32	6.28	20.39	0.10	26.77	49.80	-23.03	Average
0.37	9.00	20.36	0.10	29.46	58.47	-29.01	QP
0.37	1.48	20.36	0.10	21.94	48.47	-26.53	Average
0.50	10.60	20.31	0.11	31.02	56.00	-24.98	QP
0.50	2.95	20.31	0.11	23.37	46.00	-22.63	Average
0.63	13.01	20.28	0.12	33.41	56.00	-22.59	QP
0.63	6.73	20.28	0.12	27.13	46.00	-18.87	Average
0.78	7.36	20.24	0.14	27.74	56.00	-28.26	QP
0.78	-1.06	20.24	0.14	19.32	46.00	-26.68	Average

Left earphone
Line:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.23	7.94	20.40	0.11	28.45	62.30	-33.85	QP
0.23	1.45	20.40	0.11	21.96	52.30	-30.34	Average
0.31	14.31	20.39	0.10	34.80	59.88	-25.08	QP
0.31	10.25	20.39	0.10	30.74	49.88	-19.14	Average
0.50	10.72	20.31	0.11	31.14	56.00	-24.86	QP
0.50	1.77	20.31	0.11	22.19	46.00	-23.81	Average
0.63	13.74	20.28	0.12	34.14	56.00	-21.86	QP
0.63	6.20	20.28	0.12	26.60	46.00	-19.40	Average
0.78	7.81	20.24	0.14	28.19	56.00	-27.81	QP
0.78	-1.94	20.24	0.14	18.44	46.00	-27.56	Average
2.31	4.99	20.20	0.18	25.37	56.00	-30.63	QP
2.31	-7.56	20.20	0.18	12.82	46.00	-33.18	Average

Neutral:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.23	12.01	20.40	0.11	32.52	62.30	-29.78	QP
0.23	3.36	20.40	0.11	23.87	52.30	-28.43	Average
0.32	12.81	20.39	0.10	33.30	59.80	-26.50	QP
0.32	8.79	20.39	0.10	29.28	49.80	-20.52	Average
0.37	9.10	20.36	0.10	29.56	58.47	-28.91	QP
0.37	5.76	20.36	0.10	26.22	48.47	-22.25	Average
0.50	8.48	20.31	0.11	28.90	56.00	-27.10	QP
0.50	2.52	20.31	0.11	22.94	46.00	-23.06	Average
0.63	15.32	20.28	0.12	35.72	56.00	-20.28	QP
0.63	6.12	20.28	0.12	26.52	46.00	-19.48	Average
0.78	10.02	20.24	0.14	30.40	56.00	-25.60	QP
0.78	-0.81	20.24	0.14	19.57	46.00	-26.43	Average

Notes:

1. *An initial pre-scan was performed on the line and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level =Receiver Read level + LISN Factor + Cable Loss*
4. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*

7.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	Peak Output Power (dBm)		Limit(dBm)	Result
	Right earphone	Left earphone		
Lowest	-1.42	-1.44	30.00	Pass
Middle	-1.34	-1.77		
Highest	-1.53	-1.89		

Test plot as follows:

Right earphone



Left earphone



Lowest channel





Middle channel





Highest channel

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	Channel Bandwidth (MHz)		Limit(KHz)	Result
	Right earphone	Left earphone		
Lowest	0.654	0.668	>500	Pass
Middle	0.678	0.665		
Highest	0.662	0.668		

Test plot as follows:

Right earphone



Left earphone



Lowest channel





Middle channel





Highest channel

7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	Power Spectral Density (dBm/3kHz)		Limit(dBm/3kHz)	Result
	Right earphone	Left earphone		
Lowest	-17.30	-17.29	8.00	Pass
Middle	-16.54	-16.86		
Highest	-17.90	-17.24		

Test plot as follows:

Right earphone



Left earphone



Lowest channel





Middle channel





Highest channel

7.6 Band edges

7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Right earphone



Lowest channel



Highest channel

Left earphone



Lowest channel



Highest channel

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10:2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	RMS	1MHz	3MHz	Average

Limit:

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data
Right earphone

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	40.49	27.91	5.30	24.64	49.06	74.00	-24.94	Horizontal
2390.00	43.93	27.59	5.38	24.71	52.19	74.00	-21.81	Horizontal
2400.00	45.61	27.41	5.39	24.72	53.69	74.00	-20.31	Horizontal
2310.00	40.81	27.91	5.30	24.64	49.38	74.00	-24.62	Vertical
2390.00	44.71	27.59	5.38	24.71	52.97	74.00	-21.03	Vertical
2400.00	45.92	27.41	5.39	24.72	54.00	74.00	-20.00	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	31.58	27.91	5.30	24.64	40.15	54.00	-13.85	Horizontal
2390.00	32.67	27.59	5.38	24.71	40.93	54.00	-13.07	Horizontal
2400.00	33.10	27.41	5.39	24.72	41.18	54.00	-12.82	Horizontal
2310.00	31.35	27.91	5.30	24.64	39.92	54.00	-14.08	Vertical
2390.00	33.09	27.59	5.38	24.71	41.35	54.00	-12.65	Vertical
2400.00	34.37	27.41	5.39	24.72	42.45	54.00	-11.55	Vertical

Test channel:	Highest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	42.31	27.53	5.47	24.80	50.51	74.00	-23.49	Horizontal
2500.00	41.93	27.55	5.49	24.86	50.11	74.00	-23.89	Horizontal
2483.50	42.75	27.53	5.47	24.80	50.95	74.00	-23.05	Vertical
2500.00	42.70	27.55	5.49	24.86	50.88	74.00	-23.12	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	32.38	27.53	5.47	24.80	40.58	54.00	-13.42	Horizontal
2500.00	32.72	27.55	5.49	24.86	40.90	54.00	-13.10	Horizontal
2483.50	33.72	27.53	5.47	24.80	41.92	54.00	-12.08	Vertical
2500.00	32.44	27.55	5.49	24.86	40.62	54.00	-13.38	Vertical

Left earphone

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	40.71	27.91	5.30	24.64	49.28	74.00	-24.72	Horizontal
2390.00	44.19	27.59	5.38	24.71	52.45	74.00	-21.55	Horizontal
2400.00	45.88	27.41	5.39	24.72	53.96	74.00	-20.04	Horizontal
2310.00	41.06	27.91	5.30	24.64	49.63	74.00	-24.37	Vertical
2390.00	45.00	27.59	5.38	24.71	53.26	74.00	-20.74	Vertical
2400.00	46.22	27.41	5.39	24.72	54.30	74.00	-19.70	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	31.75	27.91	5.30	24.64	40.32	54.00	-13.68	Horizontal
2390.00	32.86	27.59	5.38	24.71	41.12	54.00	-12.88	Horizontal
2400.00	33.33	27.41	5.39	24.72	41.41	54.00	-12.59	Horizontal
2310.00	31.54	27.91	5.30	24.64	40.11	54.00	-13.89	Vertical
2390.00	33.30	27.59	5.38	24.71	41.56	54.00	-12.44	Vertical
2400.00	34.57	27.41	5.39	24.72	42.65	54.00	-11.35	Vertical

Test channel:	Highest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	42.56	27.53	5.47	24.80	50.76	74.00	-23.24	Horizontal
2500.00	42.14	27.55	5.49	24.86	50.32	74.00	-23.68	Horizontal
2483.50	43.04	27.53	5.47	24.80	51.24	74.00	-22.76	Vertical
2500.00	42.94	27.55	5.49	24.86	51.12	74.00	-22.88	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	32.56	27.53	5.47	24.80	40.76	54.00	-13.24	Horizontal
2500.00	32.87	27.55	5.49	24.86	41.05	54.00	-12.95	Horizontal
2483.50	33.84	27.53	5.47	24.80	42.04	54.00	-11.96	Vertical
2500.00	32.61	27.55	5.49	24.86	40.79	54.00	-13.21	Vertical

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

7.7 Spurious Emission

7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Right earphone

Lowest channel



Left earphone



30MHz~25GHz

Middle channel





30MHz~25GHz

Highest channel





30MHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	30m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Remark:
Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

- **Below 1GHz**
- Pre-scan all test modes, found worst case at 2440MHz, and so only show the test result of 2440MHz

Right earphone
Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
35.128	37.25	11.33	0.61	35.36	13.83	40.00	-26.17	QP
41.567	38.04	12.22	0.68	35.75	15.19	40.00	-24.81	QP
47.826	36.11	12.28	0.75	36.08	13.06	40.00	-26.94	QP
98.487	33.71	12.00	1.18	36.71	10.18	43.50	-33.32	QP
162.041	35.23	8.34	1.64	37.14	8.07	43.50	-35.43	QP
219.075	35.67	11.13	1.95	37.35	11.40	46.00	-34.60	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
30.105	39.37	11.20	0.55	35.01	16.11	40.00	-23.89	QP
48.502	38.84	12.29	0.76	36.11	15.78	40.00	-24.22	QP
57.392	39.91	11.55	0.84	36.29	16.01	40.00	-23.99	QP
96.099	37.24	11.65	1.16	36.69	13.36	43.50	-30.14	QP
167.824	42.47	8.46	1.67	37.18	15.42	43.50	-28.08	QP
300.367	36.35	13.60	2.36	37.42	14.89	46.00	-31.11	QP

Left earphone
Horizontal:



	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	46.830	39.85	12.27	36.03	0.74	16.83	40.00	-23.17	QP
2	90.220	35.74	10.70	36.64	1.11	10.91	43.50	-32.59	QP
3	280.024	34.45	13.05	37.40	2.27	12.37	46.00	-33.63	QP
4	482.216	34.81	16.97	37.51	3.23	17.50	46.00	-28.50	QP
5	607.787	35.23	19.51	37.55	3.75	20.94	46.00	-25.06	QP
6	942.131	35.04	22.46	37.56	5.01	24.95	46.00	-21.05	QP

Vertical:



	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	40.135	38.47	12.20	35.67	0.66	15.66	40.00	-24.34	QP
2	72.084	40.54	7.48	36.46	0.96	12.52	40.00	-27.48	QP
3	155.910	41.42	8.05	37.11	1.60	13.96	43.50	-29.54	QP
4	216.024	36.85	11.02	37.35	1.93	12.45	46.00	-33.55	QP
5	510.044	35.92	17.52	37.51	3.35	19.28	46.00	-26.72	QP
6	887.610	35.22	22.20	37.60	4.80	24.62	46.00	-21.38	QP

■ **Above 1GHz**

Right earphone

Test channel:	Lowest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.20	31.78	8.60	32.09	43.49	74.00	-30.51	Vertical
7206.00	30.44	36.15	11.65	32.00	46.24	74.00	-27.76	Vertical
9608.00	30.23	37.95	14.14	31.62	50.70	74.00	-23.30	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	39.06	31.78	8.60	32.09	47.35	74.00	-26.65	Horizontal
7206.00	32.00	36.15	11.65	32.00	47.80	74.00	-26.20	Horizontal
9608.00	29.45	37.95	14.14	31.62	49.92	74.00	-24.08	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.41	31.78	8.60	32.09	32.70	54.00	-21.30	Vertical
7206.00	19.36	36.15	11.65	32.00	35.16	54.00	-18.84	Vertical
9608.00	18.57	37.95	14.14	31.62	39.04	54.00	-14.96	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	28.41	31.78	8.60	32.09	36.70	54.00	-17.30	Horizontal
7206.00	21.39	36.15	11.65	32.00	37.19	54.00	-16.81	Horizontal
9608.00	18.12	37.95	14.14	31.62	38.59	54.00	-15.41	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	35.34	31.85	8.67	32.12	43.74	74.00	-30.26	Vertical
7320.00	30.53	36.37	11.72	31.89	46.73	74.00	-27.27	Vertical
9760.00	30.31	38.35	14.25	31.62	51.29	74.00	-22.71	Vertical
12200.00	*					74.00		Vertical
14640.00	*					74.00		Vertical
4880.00	39.23	31.85	8.67	32.12	47.63	74.00	-26.37	Horizontal
7320.00	32.11	36.37	11.72	31.89	48.31	74.00	-25.69	Horizontal
9760.00	29.55	38.35	14.25	31.62	50.53	74.00	-23.47	Horizontal
12200.00	*					74.00		Horizontal
14640.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	24.53	31.85	8.67	32.12	32.93	54.00	-21.07	Vertical
7320.00	19.44	36.37	11.72	31.89	35.64	54.00	-18.36	Vertical
9760.00	18.64	38.35	14.25	31.62	39.62	54.00	-14.38	Vertical
12200.00	*					54.00		Vertical
14640.00	*					54.00		Vertical
4880.00	28.54	31.85	8.67	32.12	36.94	54.00	-17.06	Horizontal
7320.00	21.48	36.37	11.72	31.89	37.68	54.00	-16.32	Horizontal
9760.00	18.20	38.35	14.25	31.62	39.18	54.00	-14.82	Horizontal
12200.00	*					54.00		Horizontal
14640.00	*					54.00		Horizontal

Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.04	31.93	8.73	32.16	43.54	74.00	-30.46	Vertical
7440.00	30.33	36.59	11.79	31.78	46.93	74.00	-27.07	Vertical
9920.00	30.13	38.81	14.38	31.88	51.44	74.00	-22.56	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	38.87	31.93	8.73	32.16	47.37	74.00	-26.63	Horizontal
7440.00	31.89	36.59	11.79	31.78	48.49	74.00	-25.51	Horizontal
9920.00	29.34	38.81	14.38	31.88	50.65	74.00	-23.35	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.30	31.93	8.73	32.16	32.80	54.00	-21.20	Vertical
7440.00	19.28	36.59	11.79	31.78	35.88	54.00	-18.12	Vertical
9920.00	18.50	38.81	14.38	31.88	39.81	54.00	-14.19	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	28.28	31.93	8.73	32.16	36.78	54.00	-17.22	Horizontal
7440.00	21.31	36.59	11.79	31.78	37.91	54.00	-16.09	Horizontal
9920.00	18.04	38.81	14.38	31.88	39.35	54.00	-14.65	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

Left earphone

Test channel:	Lowest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.27	31.78	8.60	32.09	43.56	74.00	-30.44	Vertical
7206.00	30.48	36.15	11.65	32.00	46.28	74.00	-27.72	Vertical
9608.00	30.27	37.95	14.14	31.62	50.74	74.00	-23.26	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	39.14	31.78	8.60	32.09	47.43	74.00	-26.57	Horizontal
7206.00	32.05	36.15	11.65	32.00	47.85	74.00	-26.15	Horizontal
9608.00	29.50	37.95	14.14	31.62	49.97	74.00	-24.03	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.47	31.78	8.60	32.09	32.76	54.00	-21.24	Vertical
7206.00	19.40	36.15	11.65	32.00	35.20	54.00	-18.80	Vertical
9608.00	18.60	37.95	14.14	31.62	39.07	54.00	-14.93	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	28.47	31.78	8.60	32.09	36.76	54.00	-17.24	Horizontal
7206.00	21.43	36.15	11.65	32.00	37.23	54.00	-16.77	Horizontal
9608.00	18.16	37.95	14.14	31.62	38.63	54.00	-15.37	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	35.27	31.85	8.67	32.12	43.67	74.00	-30.33	Vertical
7320.00	30.48	36.37	11.72	31.89	46.68	74.00	-27.32	Vertical
9760.00	30.27	38.35	14.25	31.62	51.25	74.00	-22.75	Vertical
12200.00	*					74.00		Vertical
14640.00	*					74.00		Vertical
4880.00	39.14	31.85	8.67	32.12	47.54	74.00	-26.46	Horizontal
7320.00	32.06	36.37	11.72	31.89	48.26	74.00	-25.74	Horizontal
9760.00	29.50	38.35	14.25	31.62	50.48	74.00	-23.52	Horizontal
12200.00	*					74.00		Horizontal
14640.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	24.47	31.85	8.67	32.12	32.87	54.00	-21.13	Vertical
7320.00	19.40	36.37	11.72	31.89	35.60	54.00	-18.40	Vertical
9760.00	18.60	38.35	14.25	31.62	39.58	54.00	-14.42	Vertical
12200.00	*					54.00		Vertical
14640.00	*					54.00		Vertical
4880.00	28.48	31.85	8.67	32.12	36.88	54.00	-17.12	Horizontal
7320.00	21.44	36.37	11.72	31.89	37.64	54.00	-16.36	Horizontal
9760.00	18.16	38.35	14.25	31.62	39.14	54.00	-14.86	Horizontal
12200.00	*					54.00		Horizontal
14640.00	*					54.00		Horizontal

Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.09	31.93	8.73	32.16	43.59	74.00	-30.41	Vertical
7440.00	30.36	36.59	11.79	31.78	46.96	74.00	-27.04	Vertical
9920.00	30.16	38.81	14.38	31.88	51.47	74.00	-22.53	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	38.93	31.93	8.73	32.16	47.43	74.00	-26.57	Horizontal
7440.00	31.92	36.59	11.79	31.78	48.52	74.00	-25.48	Horizontal
9920.00	29.38	38.81	14.38	31.88	50.69	74.00	-23.31	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.35	31.93	8.73	32.16	32.85	54.00	-21.15	Vertical
7440.00	19.31	36.59	11.79	31.78	35.91	54.00	-18.09	Vertical
9920.00	18.53	38.81	14.38	31.88	39.84	54.00	-14.16	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	28.33	31.93	8.73	32.16	36.83	54.00	-17.17	Horizontal
7440.00	21.34	36.59	11.79	31.78	37.94	54.00	-16.06	Horizontal
9920.00	18.07	38.81	14.38	31.88	39.38	54.00	-14.62	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------