

RF Exposure Evaluation Report

Product : Good Night Light Remote
Trade mark : Novostella
Model/Type reference : BNL-01
Serial Number : N/A
Report Number : EED32M00164302
FCC ID : 2AWONBNL-01
Date of Issue : Aug. 04, 2020
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Test result : PASS

Prepared for:

Shenzhen Ustellar Technology Ltd.
Rm.201, A Bldg., No. A Qianhai 1st Rd., Shen' gang
Cooperation Zone, Qianhai, Shenzhen, CHINA 518000

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Smile Zhong

Smile Zhong

Reviewed by:

Jok Yang

Jok Yang

Approved by:

Sam Chuang

Sam Chuang

Date:

Aug. 04, 2020

Check No.:2447683068



2 Version

Version No.	Date	Description
00	Aug. 04, 2020	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Standard Requirement.....	6
5.1.2 Limits.....	6
5.1.3 EUT RF Exposure.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Shenzhen Ustellar Technology Ltd.
Address of Applicant:	Rm.201, A Bldg., No. A Qianhai 1st Rd., Shen' gang Cooperation Zone, Qianhai, Shenzhen, CHINA 518000
Manufacturer:	Shenzhen Ustellar Technology Ltd.
Address of Manufacturer:	Rm.201, A Bldg., No. A Qianhai 1st Rd., Shen' gang Cooperation Zone, Qianhai, Shenzhen, CHINA 518000
Factory:	Shenzhen Ustellar Technology Ltd.
Address of Factory:	Rm.201, A Bldg., No. A Qianhai 1st Rd., Shen' gang Cooperation Zone, Qianhai, Shenzhen, CHINA 518000

4.2 General Description of EUT

Product Name:	Good Night Light Remote
Model No.(EUT):	BNL-01
Trade Mark:	Novostella
EUT Supports Radios application:	433.92MHz

4.3 Product Specification subjective to this standard

Frequency Range:	433.92MHz	
Modulation Type:	ASK	
Test Power Grade:	Default	
Test Software of EUT:	Default	
Antenna Type:	PCB antenna	
Antenna Gain:	3dBi	
Power Supply:	Battery	AAA 1.5V*2
	Adapter	Model:HJ-0501000E1-US Input:100-240V~50/60Hz 0.2A Output:5V --- 1000mA
Max Conducted Peak Output Power:	68.76dBμV/m(-28.62dBm)	
	The Max Conducted Peak Output Power data refer to the reportEED32M00164301	
Sample Received Date:	Jun. 10, 2020	
Sample tested Date:	Jun. 10, 2020 to Jul. 17, 2020	
The tested sample(s) and the sample information are provided by the client.		

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The tune-up power is -28.5 dBm +/- 0.5dB, therefore the highest tune-up power is

-28.5 dBm (0.001 mW) @ 433.92 MHz

When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

So,

$$(0.001\text{mW} / 5\text{mm}) * (0.43392\text{GHz}^{\wedge}0.5) = 0.0001$$

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] = 0.0001 < 3.0$$

Therefore, standalone SAR measurements are not required for both head and body

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32M00164301 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.