Appendix Test Data

Project No.:	18220WC10104101	Test Date:	2021.6.17
Test Engineer:	Tony.He	Auditor:	Edward.Pan
Temperature:	24.3℃	Relative Humidity:	56 %
Pressure:	1012 hPa		

1. Duty Cycle

1.1 Ant1

1.1.1 Test Result

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	100.00	100.00	100.00	0.00	0.00
		2440	100.00	100.00	100.00	0.00	0.00
		2480	100.00	100.00	100.00	0.00	0.00
Note1: Only for Report Use							

1.1.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



2. Bandwidth

2.1 OBW

2.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Ant	99% Occupied Bandwidth (MHz)	Limit	Verdict
1M	SISO	2402	1	1.06	/	Note1
		2440	1	1.05	/	Note1
		2480	1	1.06	/	Note1
Note1: Only for Report Use						

2.1.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



2.2 XDB

2.2.1 Test Result

Mode	TX Type	Frequency (MHz)	Ant	6dB Bandwidth (MHz)	Limit	Verdict
1M	SISO	2402	1	0.71	>=0.5	Pass
		2440	1	0.70	>=0.5	Pass
		2480	1	0.72	>=0.5	Pass

2.2.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Power

3.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Measured Peak Output Power (dBm)	Limit (dBm)	Verdict
			Ant1		
1M	SISO	2402	4.70	<=30	Pass
		2440	4.56	<=30	Pass
		2480	3.87	<=30	Pass
Note1: Antenna Gain: 1: 2.65dBi;					

3.1.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



4. Maximum Power Spectral Density

4.1 PSD

4.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
			Ant1		
1M	SISO	2402	-6.27	<=8	Pass
		2440	-8.85	<=8	Pass
		2480	-9.00	<=8	Pass
Note1: Antenna Gain: 1: 2.65dBi;					

4.1.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Ref

5.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Ant	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	4.63	/	/
		2440	1	4.36	/	/
		2480	1	3.80	/	/
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level. Note2: Only for Report Use						

5.1.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



5.2 CSE

5.2.1 Test Result

Mode	TX Type	Frequency (MHz)	Ant	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	Refer To Test Graph	Refer To Test Graph	Note2
		2440	1	Refer To Test Graph	Refer To Test Graph	Note2
		2480	1	Refer To Test Graph	Refer To Test Graph	Note2
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level. Note2: Only for Report Use						

5.2.2 Test Graph

1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_LCH_2402MHz_DataRate=_Ant1_NTNV



1M_MCH_2440MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



1M_HCH_2480MHz_DataRate=_Ant1_NTNV



---End---