



TEST REPORT

Applicant : Mekotronics Co., Ltd
Address : Rm1103-1105, Hengrong Lifang Building, Baomin 2nd Rd, Baoan District, Shenzhen, Guangdong, China
Manufacturer : Mekotronics Co., Ltd
Address : Rm1103-1105, Hengrong Lifang Building, Baomin 2nd Rd, Baoan District, Shenzhen, Guangdong, China
Product Name : SparkBridge Media Player
Model Number : SR1AM201M
Trademark : N/A

FCC ID : 2AWPH-SR1AM201M

Test Date : Apr. 10, 2026 to Apr. 30, 2026

Date of Report : Apr. 30, 2026

Test Result : This device described above has been tested by BKC, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.

Test Procedure Used:

Standards : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2020+Cor1:2023

Prepared by(Test Engineer):
Sten Huang

Approved(Manager):
Casey Wang

Approved(Manager):
Jerry Liao

TABLE OF CONTENT

1. General Information	5
1.1. Description of Device (EUT)	5
1.2. Channel List	5
1.3. Summary of test result	5
1.4. Special Accessories and Auxiliary Equipment	6
1.5. Test mode	6
1.6. Block Diagram	7
1.7. Test Conditions	7
1.8. Measurement Uncertainty (95% confidence levels, k=2)	8
1.9. Test Facility	8
1.10. Test Equipment	9
2. Conducted emission at the mains terminals test	11
2.1. Limit	11
2.2. Test Setup	11
2.3. Test Procedure	11
2.4. Test Result	12
3. Radiated Spurious Emissions	14
3.1. Limit	14
3.2. Test Setup	15
3.3. Test Procedure	17
3.4. Test Result	18
4. Conducted Spurious Emissions	23
4.1. Limit	23
4.2. Test Setup	23
4.3. Test Procedure	23
4.4. Test Result	23
5. Band Edge Measurement	30
5.1. Limit	30
5.2. Test setup	30
5.3. Test Procedure	30
5.4. Test Result	30
6. -6 dB Bandwidth and 99% Bandwidth Measurement	35
6.1. Limit	35
6.2. Test Setup	35
6.3. Test Procedure	35
6.4. Test Result	35
7. Maximum Peak Output Power	42
7.1. Limit	42
7.2. Test Setup	42
7.3. Test Procedure	42
7.4. Test Result	43
8. Power Spectral Density	47
8.1. Limit	47
8.2. Test Setup	47
8.3. Test Procedure	47
8.4. Test Result	47
9. Duty Cycle Correction Factor (DCCF)	51
9.1. Limit	51
9.2. Test Setup	51
9.3. Test Procedure	51



9.4. Test Result	51
10. Antenna Requirement	55
11. Test Photographs	56



[illegible]

AC Power Line Conducted Emission	FCC part 15.207	PASS
Conducted Peak Output Power	FCC part 15.247 (b)(3)	PASS
Channel Bandwidth& 99% OCB	FCC part 15.247 (a)(2)	PASS
Power Spectral Density	FCC part 15.247 (e)	PASS
Band Edge	FCC part 15.247(d)	PASS
Spurious Emission	FCC part 15.205/15.209	PASS
Remark: N/A is an abbreviation for Not Applicable. Measurement Uncertainty is not taken into account for conformity statement		

1.4.Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Hardware Version	Software Version
Serial port board	/	/	/	/
Display	HP	271V8	/	/
Keyboard	HP	TPA-L001K	/	/
Mouse	HP	M260	/	/
USB flash drive	Ugreen	HS-1		

1.5.Test mode


The special RF test software was used to control EUT work in Continuous BLE TX mode, and select test channel, wireless mode.

Test mode	Low channel	Middle channel	High channel
GFSK	2402MHz	2440MHz	2480MHz


Note: Only the worst Data Record in the report

1.6.Block Diagram


AC Power Line Conducted Emission



Radiated Emission



RF Conducted Test



1.7.Test Conditions

Category	Normal Conditions	Extreme Conditions
Temperature range	15-35℃	N/A
Humidity range	20-75%	N/A
Pressure range	86-106kPa	N/A
Power supply	DC 5V	N/A
Note: N/A is an abbreviation for Not Applicable.		

1.8.Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for radio frequency	$\pm 7 \times 10^{-8}$	
Conducted Emissions (150kHz~30MHz)	$\pm 2.54\text{dB}$	
Radiated Emission(9KHz~30MHz)	$\pm 1.6\text{ dB}$	
Radiated Emission(30MHz~1GHz)	Vertical: $\pm 4.14\text{dB}$ Horizontal: $\pm 4.25\text{dB}$	
Radiated Emission(1GHz~6GHz)	$\pm 3.9\text{dB}$	
Radiated Emission(6GHz~18GHz)	$\pm 4.3\text{dB}$	
Radiated Emission(18GHz~40GHz)	$\pm 3.38\text{dB}$	
Uncertainty for conducted RF Power	$\pm 0.20\text{dB}$	
Conducted spurious emissions	$\pm 0.24\text{dB}$	
Uncertainty for temperature	0.6°C	
Uncertainty for humidity	1%	
Bandwidth	$\pm 1.5 \times 10^{-6}$	
Time	$\pm 2\%$	
Duty Cycle	$\pm 2\%$	
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%		

1.9.Test Facility

Site Description	
Name of Firm	: Shenzhen BKC Testing Co., Ltd.
Site Location	: Room 103, 1/F, Huaya Building, Huaya Industrial Park, Longhua Community, Longhua District, Shenzhen, Guangdong, China.
ISED CAB identifier	: CN0188
ISED Company Number	: 34333
FCC Designation Number	: CN1416
FCC Test Firm Registration Number	: 701543

1.10.Test Equipment

Conducted Test Site

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	102762	Mar. 10. 2026	Mar. 09. 2027
2	EMI Test Receiver	R&S	ESCI	101424	Mar. 10. 2026	Mar. 09. 2027
3	Rf cables	HTEC	HCE 2M-CE	N/A	Mar. 10. 2026	Mar. 09. 2027
4	Coupling/ Decoupling Network	Diamond	CX210	N/A	Mar. 10. 2026	Mar. 09. 2027
5	CE Testing software	EZ	EZ-EMC	N/A	N/A	N/A

Radiated Test Site(Below 1G and Above 1G)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Antenna	Schwarzbeck	VULB 9168	01321	Mar. 20. 2025	Mar. 19. 2028
2	EMI Test Receiver	R&S	ESRP	101478	Mar. 10. 2026	Mar. 09. 2027
3	Preamplifier	HP	8447D	2727A05345	Mar. 10. 2026	Mar. 09. 2027
4	Double Ridged Broadband	SCHWARZBECK	BBHA 9120D	02621	Mar. 10. 2025	Mar. 19. 2028
5	Preamplifier	Schwarzbeck	BBV 9718D	00041	Mar. 10. 2026	Mar. 09. 2027
6	Rf cables	HUBER+SUHNER	8M-RE	N/A	Mar. 10. 2026	Mar. 09. 2027
7	Rf cables	HUBER+SUHNER	1.5M-RE	N/A	Mar. 10. 2026	Mar. 09. 2027
8	Rf cables	HUBER+SUHNER	1.5M-AP-RE	N/A	Mar. 10. 2026	Mar. 09. 2027
9	Loop antenna	TESEQ	HLA6121	58357	Mar. 16. 2026	Mar. 15. 2027
10	Spectrum analyzer	R&S	FSP40	200061	Mar. 09. 2026	Mar. 10. 2027
11	Double Ridged Broadband Horn Antenna	COM-POWER	AH-1840	10100009	Mar. 10. 2026	Mar. 09. 2027
12	Spectrum	Agilent	N9020A	MY50510311	Mar. 10. 2026	Mar. 09. 2027
13	RE Testing software	EZ	EZ-EMC	N/A	N/A	N/A

RF Test Site

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum	Agilent	N9020A	MY50510311	Mar. 10. 2026	Mar. 09. 2027
2	Vector source	Agilent	N5182A	MY47420223	Mar. 10. 2026	Mar. 09. 2027
3	All instrument	Rohde & Schwarz	CMW 500	101131	Mar. 10. 2026	Mar. 09. 2027
4	RF Automatic Test System	TST	TSTRF562	MW200411BK-34	Mar. 09. 2026	Mar. 10. 2027
5	Spectrum analyzer	R&S	FSP40	200061	Mar. 09. 2026	Mar. 10. 2027

Test software

Software name	RF Testing software
---------------	---------------------




Software version	2.0.0.0
Software name	RE Testing software
Software version	EMEC-03A2 RE+
Software name	CE Testing software
Software version	EMEC-3A1+

Software Configuration Version

Software name	sscom
Software version	5.3.1

Power setting

Channel	Power Level
Lowest	Default
Middle	Default
Highest	Default



2. Conducted emission at the mains terminals test


2.1.Limit

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2020+Cor1:2023
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

2.2.Test Setup




2.3.Test Procedure

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. For the actual test configuration, please refer to the related Item - EUT Test Photos.


2.4.Test Result

Conducted Emission At The Mains Terminals Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Working



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1900	40.32	19.70	60.02	64.04	-4.02	QP
2	0.1900	23.91	19.70	43.61	54.04	-10.43	AVG
3	0.2860	35.82	19.68	55.50	60.64	-5.14	QP
4	0.2860	22.65	19.68	42.33	50.64	-8.31	AVG
5	0.5620	31.07	19.73	50.80	56.00	-5.20	QP
6	0.5620	19.06	19.73	38.79	46.00	-7.21	AVG
7	0.6220	29.50	19.80	49.30	56.00	-6.70	QP
8	0.6220	17.91	19.80	37.71	46.00	-8.29	AVG
9	1.2340	33.62	19.65	53.27	56.00	-2.73	peak
10	1.2340	19.04	19.65	38.69	46.00	-7.31	AVG
11 *	1.7020	34.15	19.69	53.84	56.00	-2.16	peak
12	1.7020	16.78	19.69	36.47	46.00	-9.53	AVG

Conducted Emission At The Mains Terminals Test Data			
Temperature:	25.1°C	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Working



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1883	42.59	19.70	62.29	64.11	-1.82	QP
2	0.1883	30.10	19.70	49.80	54.11	-4.31	AVG
3	0.2866	37.45	19.71	57.16	60.62	-3.46	QP
4	0.2866	27.12	19.71	46.83	50.62	-3.79	AVG
5	0.3806	31.95	19.73	51.68	58.27	-6.59	QP
6	0.3806	20.40	19.73	40.13	48.27	-8.14	AVG
7	0.4737	30.62	19.76	50.38	56.45	-6.07	QP
8 *	0.4737	25.43	19.76	45.19	46.45	-1.26	AVG
9	0.5686	30.79	19.77	50.56	56.00	-5.44	QP
10	0.5686	22.71	19.77	42.48	46.00	-3.52	AVG
11	0.7656	27.07	19.79	46.86	56.00	-9.14	QP
12	0.7656	20.94	19.79	40.73	46.00	-5.27	AVG

Note:1.Level = Reading + factor; Margin = Level - Limit

2.Have pre-scan all test channel, found CH00(GFSK-1M-2402) which it was worst case, so only show the worst case' s data on this report.

3. Radiated Spurious Emissions

3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2020+Cor1:2023
Test Result: PASS
Measurement Distance: 3m

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average


Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log(2400/F(\text{kHz})) + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log(24000/F(\text{kHz})) + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log(30) + 40$
30 ~ 88	100	3	100	$20\log(100)$
88 ~ 216	150	3	150	$20\log(150)$
216 ~ 960	200	3	200	$20\log(200)$
Above 960	500	3	500	$20\log(500)$


3.2.Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



3.3.Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high - pass filter is used during radiated emissions above 1GHz measurement.



3.4.Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.


Test Frequency : 30MHz ~ 1GHz

Radiation Emission Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Horizontal
Test Voltage :	DC 3.7V	Test Mode	BLE1M CH00



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	122.8340	35.16	-12.11	23.05	43.50	-20.45	QP
2	384.0118	50.56	-8.66	41.90	46.00	-4.10	QP
3	448.0322	50.04	-7.38	42.66	46.00	-3.34	QP
4	480.5276	45.64	-7.14	38.50	46.00	-7.50	QP
5	737.0712	38.49	-3.23	35.26	46.00	-10.74	QP
6	768.7481	41.42	-2.78	38.64	46.00	-7.36	QP

Radiation Emission Test Data			
Temperature:	25.1°C	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Vertical
Test Voltage :	DC 3.7V	Test Mode	BLE1M CH00



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.0245	39.87	-10.99	28.88	40.00	-11.12	QP
2	511.8352	43.84	-6.85	36.99	46.00	-9.01	QP
3	737.0714	40.21	-3.23	36.98	46.00	-9.02	QP
4	768.7481	41.14	-2.78	38.36	46.00	-7.64	QP
5	801.7863	38.75	-1.73	37.02	46.00	-8.98	QP
6	866.0879	39.09	-0.90	38.19	46.00	-7.81	QP

Note:

1.Level = Reading + factor; Margin = Level - Limit

2.Have pre-scan all test channel, found CH00(GFSK-1M-2402) which it was worst case, so only show the worst case' s data on this report.

1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	65.84	30.55	5.77	24.66	65.72	74.00	-8.28	Pk
V	4804.00	46.68	30.55	5.77	24.66	46.56	54.00	-7.44	AV
V	7206.00	66.65	30.33	6.32	24.55	67.19	74.00	-6.81	Pk
V	7206.00	46.06	30.33	6.32	24.55	46.60	54.00	-7.40	AV
V	9608.00	66.83	30.85	7.45	24.69	68.12	74.00	-5.88	Pk
V	9608.00	46.40	30.85	7.45	24.69	47.69	54.00	-6.31	AV
V	12010.00	65.87	31.02	8.99	25.57	69.41	74.00	-4.59	Pk
V	12010.00	46.97	31.02	8.99	25.57	50.51	54.00	-3.49	AV
H	4804.00	66.14	30.55	5.77	24.66	66.02	74.00	-7.98	Pk
H	4804.00	47.14	30.55	5.77	24.66	47.02	54.00	-6.98	AV
H	7206.00	66.77	30.33	6.32	24.55	67.31	74.00	-6.69	Pk
H	7206.00	46.41	30.33	6.32	24.55	46.95	54.00	-7.05	AV
H	9608.00	66.45	30.85	7.45	24.69	67.74	74.00	-6.26	Pk
H	9608.00	46.22	30.85	7.45	24.69	47.51	54.00	-6.49	AV
H	12010.00	66.42	31.02	8.99	25.57	69.96	74.00	-4.04	Pk
H	12010.00	46.17	31.02	8.99	25.57	49.71	54.00	-4.29	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2440MHz									
V	4880.00	66.27	30.55	5.77	24.66	66.15	74.00	-7.85	Pk
V	4880.00	45.94	30.55	5.77	24.66	45.82	54.00	-8.18	AV
V	7320.00	66.31	30.33	6.32	24.55	66.85	74.00	-7.15	Pk
V	7320.00	46.20	30.33	6.32	24.55	46.74	54.00	-7.26	AV
V	9760.00	66.09	30.85	7.45	24.69	67.38	74.00	-6.62	Pk
V	9760.00	46.57	30.85	7.45	24.69	47.86	54.00	-6.14	AV
V	12200.00	66.17	31.02	8.99	25.57	69.71	74.00	-4.29	Pk
V	12200.00	46.92	31.02	8.99	25.57	50.46	54.00	-3.54	AV
H	4880.00	66.44	30.55	5.77	24.66	66.32	74.00	-7.68	Pk
H	4880.00	46.16	30.55	5.77	24.66	46.04	54.00	-7.96	AV
H	7320.00	66.74	30.33	6.32	24.55	67.28	74.00	-6.72	Pk
H	7320.00	46.60	30.33	6.32	24.55	47.14	54.00	-6.86	AV
H	9760.00	66.77	30.85	7.45	24.69	68.06	74.00	-5.94	Pk
H	9760.00	46.25	30.85	7.45	24.69	47.54	54.00	-6.46	AV
H	12200.00	66.52	31.02	8.99	25.57	70.06	74.00	-3.94	Pk
H	12200.00	46.90	31.02	8.99	25.57	50.44	54.00	-3.56	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	66.28	30.55	5.77	24.66	66.16	74.00	-7.84	Pk
V	4960.00	46.07	30.55	5.77	24.66	45.95	54.00	-8.05	AV
V	7440.00	66.20	30.33	6.32	24.55	66.74	74.00	-7.26	Pk
V	7440.00	46.46	30.33	6.32	24.55	47.00	54.00	-7.00	AV
V	9920.00	66.23	30.85	7.45	24.69	67.52	74.00	-6.48	Pk
V	9920.00	46.74	30.85	7.45	24.69	48.03	54.00	-5.97	AV
V	12400.00	66.16	31.02	8.99	25.57	69.70	74.00	-4.30	Pk
V	12400.00	46.05	31.02	8.99	25.57	49.59	54.00	-4.41	AV
H	4960.00	66.06	30.55	5.77	24.66	65.94	74.00	-8.06	Pk
H	4960.00	46.22	30.55	5.77	24.66	46.10	54.00	-7.90	AV
H	7440.00	66.15	30.33	6.32	24.55	66.69	74.00	-7.31	Pk
H	7440.00	46.50	30.33	6.32	24.55	47.04	54.00	-6.96	AV
H	9920.00	66.00	30.85	7.45	24.69	67.29	74.00	-6.71	Pk
H	9920.00	46.37	30.85	7.45	24.69	47.66	54.00	-6.34	AV
H	12400.00	66.25	31.02	8.99	25.57	69.79	74.00	-4.21	Pk
H	12400.00	46.79	31.02	8.99	25.57	50.33	54.00	-3.67	AV

Note: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier;

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. Have pre-scan all test channel, found GFSK-1M which it was worst case, so only show the worst case' s data on this report.

Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
GFSK	Low Channel: 2402MHz									
	H	2310.00	65.94	30.22	4.85	23.98	64.55	74.00	PK	PASS
	H	2310.00	46.48	30.22	4.85	23.98	45.09	54.00	AV	PASS
	H	2390.00	63.56	30.22	4.85	23.98	62.17	74.00	PK	PASS
	H	2390.00	46.56	30.22	4.85	23.98	45.17	54.00	AV	PASS
	H	2400.00	65.21	30.22	4.85	23.98	63.82	74.00	PK	PASS
	H	2400.00	46.45	30.22	4.85	23.98	45.06	54.00	AV	PASS
	V	2310.00	66.80	30.22	4.85	23.98	65.41	74.00	PK	PASS
	V	2310.00	46.33	30.22	4.85	23.98	44.94	54.00	AV	PASS
	V	2390.00	58.92	30.22	4.85	23.98	57.53	74.00	PK	PASS
	V	2390.00	46.29	30.22	4.85	23.98	44.90	54.00	AV	PASS
	V	2400.00	61.40	30.22	4.85	23.98	60.01	74.00	PK	PASS
	V	2400.00	46.96	30.22	4.85	23.98	45.57	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	63.75	30.22	4.85	23.98	62.36	74.00	PK	PASS
	H	2483.50	46.97	30.22	4.85	23.98	45.58	54.00	AV	PASS
	H	2500.00	65.12	30.22	4.85	23.98	63.73	74.00	PK	PASS
	H	2500.00	45.99	30.22	4.85	23.98	44.60	54.00	AV	PASS
	V	2483.50	66.16	30.22	4.85	23.98	64.77	74.00	PK	PASS
	V	2483.50	46.71	30.22	4.85	23.98	45.32	54.00	AV	PASS
	V	2500.00	59.38	30.22	4.85	23.98	57.99	74.00	PK	PASS
	V	2500.00	46.68	30.22	4.85	23.98	45.29	54.00	AV	PASS
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier; Margin= Emission Level - Limit 2. Have pre-scan all test channel, found GFSK-1M which it was worst case, so only show the worst case' s data on this report.										

4. Conducted Spurious Emissions

4.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2020+Cor1:2023
Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.2.Test Setup




4.3.Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to ≈ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW $\approx [3 \times \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

4.4.Test Result


Mode	Frequency (MHz)	Max Value (dBm)	Limit (dBm)	Margin (dBm)	Verdict
BLE 1M	2402	-64.63	-26.53	-38.10	Pass
BLE 1M	2440	-65.12	-26.13	-38.99	Pass
BLE 1M	2480	-63.91	-26.48	-37.43	Pass
BLE 2M	2402	-65.17	-27.01	-38.16	Pass
BLE 2M	2440	-64.11	-26.72	-37.39	Pass
BLE 2M	2480	-61.75	-26.91	-34.84	Pass




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE2M 2440MHz Ant1 Ref




=

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission

5. Band Edge Measurement

5.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;

ANSI C63.10:2020+Cor1:2023

Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting

5.2.Test setup




5.3.Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

5.4.Test Result


Mode	Frequency (MHz)	Max Value (dBm)	Limit (dBm)	Verdict
BLE 1M	2402	-71.06	-26.53	Pass
BLE 1M	2480	-73.33	-26.48	Pass
BLE 2M	2402	-41.27	-27.01	Pass
BLE 2M	2480	-69.87	-26.91	Pass




Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission




Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




Band Edge NVNT BLE 2M 2402MHz Ant1 Ref



Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Band Edge NVNT BLE 2M 2480MHz Ant1 Ref



Band Edge NVNT BLE 2M 2480MHz Ant1 Emission

6. -6 dB Bandwidth and 99% Bandwidth Measurement

6.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019; ANSI C63.10:2020+Cor1:2023

6.2.Test Setup




6.3.Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. -6 dB Bandwidth: Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz;
3. 99% OBW:Set the spectrum analyzer: RBW = 1 % to 5 % of the OBW, VBW $\geq 3 \times$ RBW.

6.4.Test Result


Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	99% OBW (MHz)	Verdict
BLE 1M	2402	0.669	0.5	1.039	Pass
BLE 1M	2440	0.665	0.5	1.037	Pass
BLE 1M	2480	0.674	0.5	1.040	Pass
BLE 2M	2402	1.183	0.5	2.077	Pass
BLE 2M	2440	1.170	0.5	2.076	Pass
BLE 2M	2480	1.162	0.5	2.077	Pass




-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1




OBW NVNT BLE 1M 2402MHz Ant1




OBW NVNT BLE 1M 2440MHz Ant1




OBW NVNT BLE 1M 2480MHz Ant1



OBW NVNT BLE 2M 2402MHz Ant1



OBW NVNT BLE 2M 2440MHz Ant1



OBW NVNT BLE 2M 2480MHz Ant1

7. Maximum Peak Output Power


7.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2020+Cor1:2023

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2.Test Setup



7.3.Test Procedure

KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019

section 8.3.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq$ 3 RBW.
- Set span $\geq$ 3 x RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

section 8.3.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- Set the RBW = 1% to 5% of the OBW, not to exceed 1 MHz..
- Set the VBW $\geq$ 3 x RBW
- Set the span $\geq$ 1.5 x OBW.
- Detector = RMS.
- Sweep time = auto couple.
- trigger = free run..
- Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\geq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Trace average at least 100 traces in power averaging (rms) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.4.Test Result


Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Test Result
BLE 1M	2402	-6.17	30	PASS
BLE 1M	2440	-5.92	30	PASS
BLE 1M	2480	-6.11	30	PASS
BLE 2M	2402	-6.19	30	PASS
BLE 2M	2440	-6.00	30	PASS
BLE 2M	2480	-5.98	30	PASS

Note: ANT Gain =2.41 dBi.







Peak Power NVNT BLE 1M 2402MHz Ant1




Peak Power NVNT BLE 1M 2440MHz Ant1




Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2402MHz Ant1



Peak Power NVNT BLE 2M 2440MHz Ant1



Peak Power NVNT BLE 2M 2480MHz Ant1

8. Power Spectral Density

8.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019; ANSI C63.10:2020+Cor1:2023

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

8.2.Test Setup




8.3.Test Procedure

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017 section 10.2


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

8.4.Test Result


Mode	Frequency (MHz)	Total PSD (dBm/100KHz)	Limit (dBm/3KHz)	Verdict
BLE 1M	2402	-6.50	8	Pass
BLE 1M	2440	-6.19	8	Pass
BLE 1M	2480	-6.48	8	Pass
BLE 2M	2402	-6.98	8	Pass
BLE 2M	2440	-6.78	8	Pass
BLE 2M	2480	-6.90	8	Pass




PSD NVNT BLE 1M 2402MHz Ant1




PSD NVNT BLE 1M 2440MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2402MHz Ant1



PSD NVNT BLE 2M 2440MHz Ant1




PSD NVNT BLE 2M 2480MHz Ant1

9. Duty Cycle Correction Factor (DCCF)

9.1.Limit

-

9.2.Test Setup



9.3.Test Procedure


- 1.The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2.Set to the maximum power setting and enable the EUT transmit continuously
- 3.Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 8 MHz,
VBW $\geq$ RBW, Sweep = as necessary to capture the entire dwell time channel
Detector function = RMS, Trigger mode
Measure and record the duty cycle data

9.4.Test Result


Mode	TX Type	Frequency (MHz)	T _{on} (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	2.143	2.501	85.69	0.67	0.03
		2440	2.142	2.500	85.68	0.67	0.03
		2480	2.142	2.500	85.68	0.67	10.25
2M	SISO	2402	1.090	1.875	58.13	2.36	0.03
		2440	1.071	1.875	57.12	2.43	0.03
		2480	1.089	1.875	58.08	2.36	0.03

9.2 Test Graph


9.2.1 Ant1




1M HCH 2480MHz Ant1 NTN




2M LCH 2402MHz Ant1 NTN



2M MCH 2440MHz Ant1 NTV



2M HCH 2480MHz Ant1 NTV



10. Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfills the requirement of this section.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfills the requirement of this section.

This product has an Rubber Antenna, and the maximum antenna gain is 2.41 dBi, fulfills the requirement of this section.



11. Test Photographs

Please see the attachment for Test Photographs.

Appendix I: Photos of the EUT

Please see the attachment for External Photographs and Internal Photographs.

***** END OF REPORT *****

