# FCC TEST REPORT

| | | |
|---|---|---|
| Client Name | : | Parceltools Pty Ltd |
| Address | : | 18 Larkin St, Waverton, NSW, 2060, Australia |
| Product Name | : | Cubetape Dimensioning Products |
| Date | : | Jul. 06, 2020 |

## Shenzhen Anbotek Compliance Laboratory Limited

# Contents

1. General Information....5
1.1. Client Information....5
1.2. Description of Device (EUT)....5
1.3. Auxiliary Equipment Used During Test....5
1.4. Description of Test Modes....6
1.5. List of channels....7
1.6. Description Of Test Setup....8
1.7. Test Equipment List....9
1.8. Measurement Uncertainty....10
1.9. Description of Test Facility....10
2. Summary of Test Results....11
3. Conducted Emission Test....12
3.1. Test Standard and Limit....12
3.2. Test Setup....12
3.3. Test Procedure....12
3.4. Test Data....12
4. Radiation Spurious Emission and Band Edge....17
4.1. Test Standard and Limit....17
4.2. Test Setup....17
4.3. Test Procedure....18
4.4. Test Data....19
5. Maximum Peak Output Power Test....27
5.1. Test Standard and Limit....27
5.2. Test Setup....27
5.3. Test Procedure....27
5.4. Test Data....27
6. 20DB Occupy Bandwidth Test....31
6.1. Test Standard....31
6.2. Test Setup....31
6.3. Test Procedure....31
6.4. Test Data....31
7. Carrier Frequency Separation Test....35
7.1. Test Standard and Limit....35
7.2. Test Setup....35
7.3. Test Procedure....35
7.4. Test Data....35
8. Number of Hopping Channel Test....39
8.1. Test Standard and Limit....39

8.2. Test Setup....39
8.3. Test Procedure....39
8.4. Test Data....39
9. Dwell Time Test....41
9.1. Test Standard and Limit....41
9.2. Test Setup....41
9.3. Test Procedure....41
9.4. Test Data....41
10. 100kHz Bandwidth of Frequency Band Edge Requirement....45
10.1. Test Standard and Limit....45
10.2. Test Setup....45
10.3. Test Procedure....45
10.4. Test Data....45
11. Antenna Requirement....50
11.1. Test Standard and Requirement....50
11.2. Antenna Connected Construction....50
APPENDIX I -- TEST SETUP PHOTOGRAPH....51
APPENDIX II -- EXTERNAL PHOTOGRAPH....53
APPENDIX III -- INTERNAL PHOTOGRAPH....57

# TEST REPORT

| | | |
|---|---|---|
| Applicant | : | Parceltools Pty Ltd |
| Manufacturer | : | Parceltools Pty Ltd |
| Product Name | : | Cubetape Dimensioning Products |
| Model No. | : | C190DSK |
| Trade Mark | : | Cubetape |
| Rating(s) | : | Input: DC 5V, 500mA |
| **Test Standard(s)** | **:** | **FCC Part15 Subpart C 2019, Section 15.247** |
| **Test Method(s)** | **:** | **ANSI C63.10: 2013** |

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

| | |
|---|---|
| Date of receipt | Jun. 08, 2020 |
| Date of Test | Jun. 08~22, 2020 |

Prepared by

(Engineer / Dolly Mo)

Reviewer

(Supervisor / Bibo Zhang)

Approved & Authorized Signer

(Manager / Tom Chen)

# 1. General Information

## 1.1. Client Information

| | | |
|---|---|---|
| Applicant | : | Parceltools Pty Ltd |
| Address | : | 18 Larkin St, Waverton, NSW, 2060, Australia |
| Manufacturer | : | Parceltools Pty Ltd |
| Address | : | 18 Larkin St, Waverton, NSW, 2060, Australia |
| applicant | : | Parceltools Pty Ltd |
| Address | : | 18 Larkin St, Waverton, NSW, 2060, Australia |

## 1.2. Description of Device (EUT)

| | | | |
|---|---|---|---|
| Product Name | : | Cubetape Dimensioning Products | |
| Model No. | : | C190DSK | |
| Trade Mark | : | Cubetape | |
| Test Power Supply | : | AC 120V, 60Hz for adapter/ AC 240V, 60Hz for adapter | |
| Test Sample No. | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample) | |
| Product Description | : | Operation Frequency: | 2402~2480MHz |
| | | Transfer Rate: | 1/2/3 Mbits/s |
| | | Number of Channel: | 79 Channels |
| | | Modulation Type: | GFSK, π/4-DQPSK, 8-DPSK |
| | | Antenna Type: | PCB Antenna |
| | | Antenna Gain(Peak): | 0 dBi |
| Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. | | | |

## 1.3. Auxiliary Equipment Used During Test


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

| | | |
|---|---|---|
| Adapter | : | Manufacturer: ZTE<br>M/N: STC-A2050I1000USBA-C<br>S/N: 201202102100876<br>Input: 100-240V~ 50/60Hz, 0.3A<br>Output: DC 5V, 1000mA |

## 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

TEST MODE:

| | | | |
|---|---|---|---|
| Mode 1 | GFSK | CH00 | TX+ Charging Mode/TX Only |
| Mode 2 | | CH39 | |
| Mode 3 | | CH78 | |
| Mode 4 | π/4-DQPSK | CH00 | |
| Mode 5 | | CH39 | |
| Mode 6 | | CH78 | |
| Mode 7 | 8-DPSK | CH00 | |
| Mode 8 | | CH39 | |
| Mode 9 | | CH78 | |

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

## 1.5. List of channels

| Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|---|---|---|---|---|---|---|---|---|---|
| 00 | 2402 | 17 | 2419 | 34 | 2436 | 51 | 2453 | 68 | 2470 |
| 01 | 2403 | 18 | 2420 | 35 | 2437 | 52 | 2454 | 69 | 2471 |
| 02 | 2404 | 19 | 2421 | 36 | 2438 | 53 | 2455 | 70 | 2472 |
| 03 | 2405 | 20 | 2422 | 37 | 2439 | 54 | 2456 | 71 | 2473 |
| 04 | 2406 | 21 | 2423 | 38 | 2440 | 55 | 2457 | 72 | 2474 |
| 05 | 2407 | 22 | 2424 | 39 | 2441 | 56 | 2458 | 73 | 2475 |
| 05 | 2408 | 23 | 2425 | 40 | 2442 | 57 | 2459 | 74 | 2476 |
| 07 | 2409 | 24 | 2426 | 41 | 2443 | 58 | 2460 | 75 | 2477 |
| 08 | 2410 | 25 | 2427 | 42 | 2444 | 59 | 2461 | 76 | 2478 |
| 09 | 2411 | 26 | 2428 | 43 | 2445 | 60 | 2462 | 77 | 2479 |
| 10 | 2412 | 27 | 2429 | 44 | 2446 | 61 | 2463 | 78 | 2480 |
| 11 | 2413 | 28 | 2430 | 45 | 2447 | 62 | 2464 | | |
| 12 | 2414 | 29 | 2431 | 46 | 2448 | 63 | 2465 | | |
| 13 | 2415 | 30 | 2432 | 47 | 2449 | 64 | 2466 | | |
| 14 | 2416 | 31 | 2433 | 48 | 2450 | 65 | 2467 | | |
| 15 | 2417 | 32 | 2434 | 49 | 2451 | 66 | 2468 | | |
| 16 | 2418 | 33 | 2435 | 50 | 2452 | 67 | 2469 | | |

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

## 1.6. Description Of Test Setup

CE




RE



## 1.7. Test Equipment List

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|---|---|---|---|---|---|---|
| 1. | L.I.S.N. Artificial Mains Network | Rohde & Schwarz | ENV216 | 100055 | Nov. 04, 2019 | 1 Year |
| 2. | EMI Test Receiver | Rohde & Schwarz | ESPI3 | 101604 | Nov. 04, 2019 | 1 Year |
| 3. | RF Switching Unit | Compliance Direction | RSU-M2 | 38303 | Nov. 04, 2019 | 1 Year |
| 4. | MAX Spectrum Analysis | Agilent | N9020A | MY51170037 | Nov. 04, 2019 | 1 Year |
| 5. | Preamplifier | SKET Electronic | BK1G18G30D | KD17503 | Nov. 04, 2019 | 1 Year |
| 6. | Double Ridged Horn Antenna | Instruments corporation | GTH-0118 | 351600 | Nov. 01, 2019 | 1 Year |
| 7. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | VULB 9163-289 | Nov. 01, 2019 | 1 Year |
| 8. | Loop Antenna | Schwarzbeck | FMZB1519B | 00053 | Nov. 01, 2019 | 1 Year |
| 9. | Horn Antenna | A-INFO | LB-180400-KF | J211060628 | Nov. 01, 2019 | 1 Year |
| 10. | Pre-amplifier | SONOMA | 310N | 186860 | Nov. 04, 2019 | 1 Year |
| 11. | EMI Test Software EZ-EMC | SHURPLE | N/A | N/A | N/A | N/A |
| 12. | RF Test Control System | YIHENG | YH3000 | 2017430 | Nov. 04, 2019 | 1 Year |
| 13. | Power Sensor | DAER | RPR3006W | 15I00041SN045 | Nov. 04, 2019 | 1 Year |
| 14. | Power Sensor | DAER | RPR3006W | 15I00041SN046 | Nov. 04, 2019 | 1 Year |
| 15. | MXA Spectrum Analysis | Agilent | N9020A | MY51170037 | Nov. 04, 2019 | 1 Year |
| 16. | MXG RF Vector Signal Generator | Agilent | N5182A | MY48180656 | Nov. 04, 2019 | 1 Year |
| 17. | Signal Generator | Agilent | E4421B | MY41000743 | Nov. 04, 2019 | 1 Year |
| 18. | DC Power Supply | LW | TPR-6420D | 374470 | Nov. 04, 2019 | 1 Year |
| 19. | Constant Temperature Humidity Chamber | ZHONGJIAN | ZJ-KHWS80B | N/A | Nov. 04, 2019 | 1 Year |

## 1.8. Measurement Uncertainty

| | | |
|---|---|---|
| Radiation Uncertainty | : | Ur = 3.9 dB (Horizontal) |
| | | Ur = 3.8 dB (Vertical) |
| | | |
| Conduction Uncertainty | : | Uc = 3.4 dB |

## 1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 184111**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 27, 2019.

**ISED-Registration No.: 8058A**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, March 07, 2019.

**Test Location**

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

# 2. Summary of Test Results

| Standard Section | Test Item | Result |
|---|---|---|
| 15.203/15.247(c) | Antenna Requirement | PASS |
| 15.207 | Conducted Emission | PASS |
| 15.205/15.209 | Spurious Emission | PASS |
| 15.247(b)(1) | Conducted Peak Output Power | PASS |
| 15.247(a)(1) | 20dB Occupied Bandwidth | PASS |
| 15.247(a)(1) | Carrier Frequencies Separation | PASS |
| 15.247(a)(1) | Hopping Channel Number | PASS |
| 15.247(a)(1) | Dwell Time | PASS |
| 15.247(d) | Band Edge | PASS |
| **Remark:** “N/A” is an abbreviation for Not Applicable. | | |

# 3. Conducted Emission Test

## 3.1. Test Standard and Limit

| Test Standard | FCC Part15 Section 15.207 | | |
|---|---|---|---|
| Test Limit | Frequency | Maximum RF Line Voltage (dBuV) | |
| | | Quasi-peak Level | Average Level |
| | 150kHz~500kHz | 66 ~ 56 * | 56 ~ 46 * |
| | 500kHz~5MHz | 56 | 46 |
| | 5MHz~30MHz | 60 | 50 |
| **Remark:** (1) *Decreasing linearly with logarithm of the frequency.<br>(2) The lower limit shall apply at the transition frequency. | | | |

## 3.2. Test Setup




## 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

## 3.4. Test Data

During the test, pre-scan the GFSK, π/4QPSK, 8DPSK modulation, and found the GFSK modulation Low channel(TX+Charging Mode) which is the worst case, only the worst case is recorded in the report. Please to see the following pages.

**Conducted Emission Test Data**

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 25.3℃ Hum.: 60%




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.1700 | 25.26 | 19.90 | 45.16 | 64.96 | -19.80 | QP | |
| 2 | 0.3379 | 20.43 | 19.91 | 40.34 | 59.25 | -18.91 | QP | |
| 3 | 0.3379 | 7.06 | 19.91 | 26.97 | 49.25 | -22.28 | AVG | |
| 4 | 0.4980 | 17.81 | 19.98 | 37.79 | 56.03 | -18.24 | QP | |
| 5 | 0.5940 | 19.64 | 20.01 | 39.65 | 56.00 | -16.35 | QP | |
| 6 | 0.5940 | 5.46 | 20.01 | 25.47 | 46.00 | -20.53 | AVG | |
| 7 | 0.9260 | 3.10 | 20.10 | 23.20 | 46.00 | -22.80 | AVG | |
| 8 | 1.0220 | 18.81 | 20.12 | 38.93 | 56.00 | -17.07 | QP | |
| 9 | 1.2660 | 2.53 | 20.13 | 22.66 | 46.00 | -23.34 | AVG | |
| 10 | 1.6980 | 1.13 | 20.13 | 21.26 | 46.00 | -24.74 | AVG | |
| 11 | 2.0300 | 0.80 | 20.14 | 20.94 | 46.00 | -25.06 | AVG | |
| 12 | 2.6820 | 15.71 | 20.15 | 35.86 | 56.00 | -20.14 | QP | |

**Conducted Emission Test Data**

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 25.3℃ Hum.: 60%




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.1700 | 23.53 | 19.90 | 43.43 | 64.96 | -21.53 | QP | |
| 2 | 0.1740 | 8.05 | 19.90 | 27.95 | 54.76 | -26.81 | AVG | |
| 3 | 0.4060 | 3.09 | 19.94 | 23.03 | 47.73 | -24.70 | AVG | |
| 4 | 0.4860 | 14.50 | 19.97 | 34.47 | 56.24 | -21.77 | QP | |
| 5 | 0.5940 | 1.72 | 20.01 | 21.73 | 46.00 | -24.27 | AVG | |
| 6 | 0.7019 | 15.02 | 20.04 | 35.06 | 56.00 | -20.94 | QP | |
| 7 | 1.0060 | 13.11 | 20.12 | 33.23 | 56.00 | -22.77 | QP | |
| 8 | 1.0060 | 0.16 | 20.12 | 20.28 | 46.00 | -25.72 | AVG | |
| 9 | 1.3300 | 12.17 | 20.13 | 32.30 | 56.00 | -23.70 | QP | |
| 10 | 1.5180 | 0.08 | 20.13 | 20.21 | 46.00 | -25.79 | AVG | |
| 11 | 1.8300 | -1.07 | 20.14 | 19.07 | 46.00 | -26.93 | AVG | |
| 12 | 2.0579 | 13.48 | 20.14 | 33.62 | 56.00 | -22.38 | QP | |

**Conducted Emission Test Data**

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 25.3℃ Hum.: 60%




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.2260 | 24.31 | 19.89 | 44.20 | 62.59 | -18.39 | QP | |
| 2 | 0.3100 | 9.76 | 19.89 | 29.65 | 49.97 | -20.32 | AVG | |
| 3 | 0.3220 | 24.74 | 19.90 | 44.64 | 59.65 | -15.01 | QP | |
| 4 | 0.4500 | 19.82 | 19.96 | 39.78 | 56.87 | -17.09 | QP | |
| 5 | 0.4580 | 5.70 | 19.96 | 25.66 | 46.73 | -21.07 | AVG | |
| 6 | 0.8100 | 22.20 | 20.07 | 42.27 | 56.00 | -13.73 | QP | |
| 7 | 0.8100 | 6.55 | 20.07 | 26.62 | 46.00 | -19.38 | AVG | |
| 8 | 1.3540 | 21.07 | 20.13 | 41.20 | 56.00 | -14.80 | QP | |
| 9 | 1.3940 | 5.52 | 20.13 | 25.65 | 46.00 | -20.35 | AVG | |
| 10 | 1.9740 | 4.34 | 20.14 | 24.48 | 46.00 | -21.52 | AVG | |
| 11 | 2.0100 | 19.41 | 20.14 | 39.55 | 56.00 | -16.45 | QP | |
| 12 | 2.5780 | 3.26 | 20.15 | 23.41 | 46.00 | -22.59 | AVG | |

**Conducted Emission Test Data**

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 25.3℃ Hum.: 60%




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.3140 | 9.14 | 19.90 | 29.04 | 49.86 | -20.82 | AVG | |
| 2 | 0.3220 | 20.63 | 19.90 | 40.53 | 59.65 | -19.12 | QP | |
| 3 | 0.4140 | 5.91 | 19.94 | 25.85 | 47.57 | -21.72 | AVG | |
| 4 | 0.4500 | 17.69 | 19.96 | 37.65 | 56.87 | -19.22 | QP | |
| 5 | 0.8139 | 5.28 | 20.07 | 25.35 | 46.00 | -20.65 | AVG | |
| 6 | 0.8180 | 17.79 | 20.07 | 37.86 | 56.00 | -18.14 | QP | |
| 7 | 1.3619 | 17.19 | 20.13 | 37.32 | 56.00 | -18.68 | QP | |
| 8 | 1.4140 | 4.35 | 20.13 | 24.48 | 46.00 | -21.52 | AVG | |
| 9 | 1.9660 | 16.06 | 20.14 | 36.20 | 56.00 | -19.80 | QP | |
| 10 | 2.0180 | 3.71 | 20.14 | 23.85 | 46.00 | -22.15 | AVG | |
| 11 | 2.6420 | 14.85 | 20.15 | 35.00 | 56.00 | -21.00 | QP | |
| 12 | 3.2020 | 2.38 | 20.16 | 22.54 | 46.00 | -23.46 | AVG | |

# 4. Radiation Spurious Emission and Band Edge

## 4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 | | | | |
|---|---|---|---|---|---|
| Test Limit | Frequency (MHz) | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz~0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz~88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz~216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz~960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz~1000MHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1000MHz | 500 | 54.0 | Average | 3 |
| | | - | 74.0 | Peak | 3 |

**Remark:**
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

## 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

## 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

## 4.4. Test Data

**PASS**

During the test, pre-scan the GFSK, π/4QPSK, 8DPSK modulation, and found the GFSK modulation Middle channel(TX Only) which is the worst case, only the worst case is recorded in the report

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

**Test Results (30~1000MHz)**

Test Mode: Mode 2

Power Source: AC 120V, 60Hz for adapter

Polarization: Vertical

Temp.(℃)/Hum.(%RH): 25.7℃/49%RH




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 55.2207 | 42.38 | -16.51 | 25.87 | 40.00 | -14.13 | QP | 100 | 0 | |
| 2 | 63.3132 | 44.48 | -17.38 | 27.10 | 40.00 | -12.90 | QP | 100 | 360 | |
| 3 | 152.6640 | 44.00 | -19.78 | 24.22 | 43.50 | -19.28 | QP | 100 | 0 | |
| 4 | 219.0752 | 41.27 | -16.46 | 24.81 | 46.00 | -21.19 | QP | 100 | 360 | |
| 5 | 330.1949 | 39.79 | -12.55 | 27.24 | 46.00 | -18.76 | QP | 100 | 0 | |
| 6 | 601.4265 | 41.13 | -6.75 | 34.38 | 46.00 | -11.62 | QP | 100 | 360 | |

**Test Results (30~1000MHz)**

Test Mode: Mode 2

Power Source: AC 120V, 60Hz for adapter

Polarization: Horizontal

Temp.(℃)/Hum.(%RH): 25.7℃/49%RH




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Height (cm) | degree (deg) | Remark |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 92.1388 | 41.21 | -20.33 | 20.88 | 43.50 | -22.62 | QP | 100 | 360 | |
| 2 | 183.8440 | 53.87 | -20.65 | 33.22 | 43.50 | -10.28 | QP | 100 | 0 | |
| 3 | 210.7860 | 53.22 | -19.64 | 33.58 | 43.50 | -9.92 | QP | 100 | 360 | |
| 4 | 283.9791 | 50.19 | -15.75 | 34.44 | 46.00 | -11.56 | QP | 100 | 0 | |
| 5 | 400.4319 | 45.67 | -12.98 | 32.69 | 46.00 | -13.31 | QP | 100 | 360 | |
| 6 | 599.3212 | 37.75 | -6.76 | 30.99 | 46.00 | -15.01 | QP | 100 | 0 | |

**Test Results (1GHz-25GHz)**

| Test Mode: CH00 | | | | | Test channel: Lowest | | | |
|---|---|---|---|---|---|---|---|---|
| Peak Value | | | | | | | | |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4804.00 | 40.33 | 34.04 | 6.58 | 34.09 | 46.86 | 74.00 | -27.14 | V |
| 7206.00 | 33.83 | 37.11 | 7.73 | 34.50 | 44.17 | 74.00 | -29.83 | V |
| 9608.00 | 33.25 | 39.31 | 9.23 | 34.79 | 47.00 | 74.00 | -27.00 | V |
| 12010.00 | * | | | | | 74.00 | | V |
| 14412.00 | * | | | | | 74.00 | | V |
| 4804.00 | 45.23 | 34.04 | 6.58 | 34.09 | 51.76 | 74.00 | -22.24 | H |
| 7206.00 | 35.86 | 37.11 | 7.73 | 34.50 | 46.20 | 74.00 | -27.80 | H |
| 9608.00 | 32.96 | 39.31 | 9.23 | 34.79 | 46.71 | 74.00 | -27.29 | H |
| 12010.00 | * | | | | | 74.00 | | H |
| 14412.00 | * | | | | | 74.00 | | H |
| Average Value | | | | | | | | |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4804.00 | 28.57 | 34.04 | 6.58 | 34.09 | 35.10 | 54.00 | -18.90 | V |
| 7206.00 | 22.18 | 37.11 | 7.73 | 34.50 | 32.52 | 54.00 | -21.48 | V |
| 9608.00 | 21.07 | 39.31 | 9.23 | 34.79 | 34.82 | 54.00 | -19.18 | V |
| 12010.00 | * | | | | | 54.00 | | V |
| 14412.00 | * | | | | | 54.00 | | V |
| 4804.00 | 33.13 | 34.04 | 6.58 | 34.09 | 39.66 | 54.00 | -14.34 | H |
| 7206.00 | 24.55 | 37.11 | 7.73 | 34.50 | 34.89 | 54.00 | -19.11 | H |
| 9608.00 | 21.05 | 39.31 | 9.23 | 34.79 | 34.80 | 54.00 | -19.20 | H |
| 12010.00 | * | | | | | 54.00 | | H |
| 14412.00 | * | | | | | 54.00 | | H |


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

**Test Results (1GHz-25GHz)**

| Test Mode: CH39 | | | | | Test channel: Middle | | | |
|---|---|---|---|---|---|---|---|---|
| Peak Value | | | | | | | | |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4882.00 | 39.95 | 34.38 | 6.69 | 34.09 | 46.93 | 74.00 | -27.07 | V |
| 7323.00 | 33.59 | 37.22 | 7.78 | 34.53 | 44.06 | 74.00 | -29.94 | V |
| 9764.00 | 33.03 | 39.46 | 9.35 | 34.80 | 47.04 | 74.00 | -26.96 | V |
| 12205.00 | * | | | | | 74.00 | | V |
| 14646.00 | * | | | | | 74.00 | | V |
| 4882.00 | 44.78 | 34.38 | 6.69 | 34.09 | 51.76 | 74.00 | -22.24 | H |
| 7323.00 | 35.58 | 37.22 | 7.78 | 34.53 | 46.05 | 74.00 | -27.95 | H |
| 9764.00 | 32.71 | 39.46 | 9.35 | 34.80 | 46.72 | 74.00 | -27.28 | H |
| 12205.00 | * | | | | | 74.00 | | H |
| 14646.00 | * | | | | | 74.00 | | H |
| Average Value | | | | | | | | |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4882.00 | 28.29 | 34.38 | 6.69 | 34.09 | 35.27 | 54.00 | -18.73 | V |
| 7323.00 | 21.99 | 37.22 | 7.78 | 34.53 | 32.46 | 54.00 | -21.54 | V |
| 9764.00 | 20.90 | 39.46 | 9.35 | 34.80 | 34.91 | 54.00 | -19.09 | V |
| 12205.00 | * | | | | | 54.00 | | V |
| 14646.00 | * | | | | | 54.00 | | V |
| 4882.00 | 32.82 | 34.38 | 6.69 | 34.09 | 39.80 | 54.00 | -14.20 | H |
| 7323.00 | 24.34 | 37.22 | 7.78 | 34.53 | 34.81 | 54.00 | -19.19 | H |
| 9764.00 | 20.85 | 39.46 | 9.35 | 34.80 | 34.86 | 54.00 | -19.14 | H |
| 12205.00 | * | | | | | 54.00 | | H |
| 14646.00 | * | | | | | 54.00 | | H |


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

**Test Results (1GHz-25GHz)**

| Test Mode: CH78 | | | | | Test channel: Highest | | | |
|---|---|---|---|---|---|---|---|---|
| Peak Value | | | | | | | | |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4960.00 | 38.74 | 34.72 | 6.79 | 34.09 | 46.16 | 74.00 | -27.84 | V |
| 7440.00 | 32.78 | 37.34 | 7.82 | 34.57 | 43.37 | 74.00 | -30.63 | V |
| 9920.00 | 32.32 | 39.62 | 9.46 | 34.81 | 46.59 | 74.00 | -27.41 | V |
| 12400.00 | * | | | | | 74.00 | | V |
| 14880.00 | * | | | | | 74.00 | | V |
| 4960.00 | 43.32 | 34.72 | 6.79 | 34.09 | 50.74 | 74.00 | -23.26 | H |
| 7440.00 | 34.66 | 37.34 | 7.82 | 34.57 | 45.25 | 74.00 | -28.75 | H |
| 9920.00 | 31.88 | 39.62 | 9.46 | 34.81 | 46.15 | 74.00 | -27.85 | H |
| 12400.00 | * | | | | | 74.00 | | H |
| 14880.00 | * | | | | | 74.00 | | H |
| Average Value | | | | | | | | |
| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. |
| 4960.00 | 27.42 | 34.72 | 6.79 | 34.09 | 34.84 | 54.00 | -19.16 | V |
| 7440.00 | 21.40 | 37.34 | 7.82 | 34.57 | 31.99 | 54.00 | -22.01 | V |
| 9920.00 | 20.37 | 39.62 | 9.46 | 34.81 | 34.64 | 54.00 | -19.36 | V |
| 12400.00 | * | | | | | 54.00 | | V |
| 14880.00 | * | | | | | 54.00 | | V |
| 4960.00 | 31.82 | 34.72 | 6.79 | 34.09 | 39.24 | 54.00 | -14.76 | H |
| 7440.00 | 23.68 | 37.34 | 7.82 | 34.57 | 34.27 | 54.00 | -19.73 | H |
| 9920.00 | 20.24 | 39.62 | 9.46 | 34.81 | 34.51 | 54.00 | -19.49 | H |
| 12400.00 | * | | | | | 54.00 | | H |
| 14880.00 | * | | | | | 54.00 | | H |

Remark:

1. During the test, pre-scan the GFSK, π/4QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
2. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
3. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

**Radiated Band Edge:**

| Test Mode: CH00 | Test channel: Lowest |
|---|---|
|   |   |
| Average Value(Vertical) | Average Value(Horizontal) |
|   |   |
| Peak Value(Vertical) | Peak Value(Horizontal) |

| Test Mode: CH78 | Test channel: Highest |
|---|---|
|   |   |
| Average Value(Vertical) | Average Value(Horizontal) |
|   |   |
| Peak Value(Vertical) | Peak Value(Horizontal) |

Remark:

1. During the test, pre-scan the GFSK, π/4QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
2. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

# 5. Maximum Peak Output Power Test

## 5.1. Test Standard and Limit

| | |
|---|---|
| Test Standard | FCC Part15 C Section 15.247 (b)(3) |
| Test Limit | 125mW |

## 5.2. Test Setup




## 5.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
   RBW > the 20 dB bandwidth of the emission being measured
   Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold

## 5.4. Test Data

| | | | | | |
|---|---|---|---|---|---|
| Test Item | : | Max. peak output power | Test Mode | : | CH Low ~ CH High |
| Test Voltage | : | AC 120V, 60Hz for adapter | Temperature | : | 23.6° C |
| Test Result | : | PASS | Humidity | : | 49 % |

| Channel Frequency (MHz) | Peak Power output (dBm) | Limit (dBm) | Results | Modulation |
|---|---|---|---|---|
| 2402 | 0.199 | 20.96 | PASS | BDR |
| 2441 | -0.074 | 20.96 | PASS | BDR |
| 2480 | -0.908 | 20.96 | PASS | BDR |
| 2402 | **2.509** | 20.96 | PASS | EDR |
| 2441 | 2.284 | 20.96 | PASS | EDR |
| 2480 | 1.963 | 20.96 | PASS | EDR |
| Remark: The EDR was tested on (π/4QPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages. | | | | |




Test Mode: BDR---Low




Test Mode: BDR---Middle




Test Mode: BDR---High




Test Mode: EDR---Low




Test Mode: EDR---Middle




Test Mode: EDR---High

# 6. 20DB Occupy Bandwidth Test

## 6.1. Test Standard

| | |
|---|---|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |

## 6.2. Test Setup




## 6.3. Test Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

## 6.4. Test Data

| | | | | | |
|---|---|---|---|---|---|
| Test Item | : | 20dB BW | Test Mode | : | CH Low ~ CH High |
| Test Voltage | : | AC 120V, 60Hz for adapter | Temperature | : | 23.6° C |
| Test Result | : | PASS | Humidity | : | 49 % |

| Channel | Frequency(MHz) | 20dB Down BW(kHz) | Modulation Mode |
|---|---|---|---|
| Low | 2402 | 1021 | BDR |
| Middle | 2441 | 1027 | BDR |
| High | 2480 | 1025 | BDR |
| Low | 2402 | 1354 | EDR |
| Middle | 2441 | 1352 | EDR |
| High | 2480 | 1353 | EDR |
| Remark: The EDR was tested on (π/4QPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages. | | | |




Test Mode: BDR---Low




Test Mode: BDR---Middle




Test Mode: BDR---High




Test Mode: EDR---Low




Test Mode: EDR---Middle




Test Mode: EDR---High

# 7. Carrier Frequency Separation Test

## 7.1. Test Standard and Limit

| | |
|---|---|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |
| Test Limit | >25KHz or >two-thirds of the 20 dB bandwidth |

## 7.2. Test Setup




## 7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW = 30 kHz.
3. Set the VBW = 100 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

## 7.4. Test Data

| | | | | | |
|---|---|---|---|---|---|
| Test Item | : | Frequency Separation | Test Mode | : | CH Low ~ CH High |
| Test Voltage | : | AC 120V, 60Hz for adapter | Temperature | : | 23.6° C |
| Test Result | : | PASS | Humidity | : | 49 % |

| Channel | Frequency (MHz) | Separation Read Value (kHz) | Limit (kHz) | Modulation Mode |
|---|---|---|---|---|
| Low | 2402 | 1000 | 680.7 | BDR |
| Middle | 2441 | 1000 | 684.7 | BDR |
| High | 2480 | 1000 | 683.3 | BDR |
| Low | 2402 | 1000 | 902.7 | EDR |
| Middle | 2441 | 1000 | 901.3 | EDR |
| High | 2480 | 1000 | 902.0 | EDR |
| Remark: 1. The EDR was tested on (π/4QPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages.<br>2. The limit is 2/3 of 20dB BW. | | | | |




Test Mode: BDR---Low




Test Mode: BDR---Middle




Test Mode: BDR---High




Test Mode: EDR---Low




Test Mode: EDR---Middle




Test Mode: EDR---High

# 8. Number of Hopping Channel Test

## 8.1. Test Standard and Limit

| | |
|---|---|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |
| Test Limit | >15 channels |

## 8.2. Test Setup




## 8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = 100kHz.
3. Set the VBW = 300kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

## 8.4. Test Data

| | | | | | |
|---|---|---|---|---|---|
| Test Item | : | Number of Hopping Frequency | Test Mode | : | CH Low ~ CH High |
| Test Voltage | : | AC 120V, 60Hz for adapter | Temperature | : | 23.6° C |
| Test Result | : | PASS | Humidity | : | 49 % |

| Hopping Channel Frequency Range | Quantity of Hopping Channel | Quantity of Hopping Channel |
|---|---|---|
| 2402-2480MHz | 79 | ＞15 |
| Remark: The EDR was tested on (π/4QPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages. | | |




BDR Mode




EDR Mode

# 9. Dwell Time Test

## 9.1. Test Standard and Limit

| | |
|---|---|
| Test Standard | FCC Part15 C Section 15.247 (a)(1) |
| Test Limit | 0.4 sec |

## 9.2. Test Setup




## 9.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 1 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

## 9.4. Test Data

| | | | | | |
|---|---|---|---|---|---|
| Test Item | : | Time of Occupancy | Test Mode | : | CH Low ~ CH High |
| Test Voltage | : | AC 120V, 60Hz for adapter | Temperature | : | 23.6° C |
| Test Result | : | PASS | Humidity | : | 49 % |

| Package Type | Pulse width (ms) | Time slot length(ms) | Dwell time (ms) | Limit (s) | Modulation |
|---|---|---|---|---|---|
| DH1 | 0.378 | time slot length *1600/2 /79 * 31.6 | 120.96 | 0.4 | BDR |
| DH3 | 1.635 | time slot length *1600/4 /79 * 31.6 | 261.60 | 0.4 | BDR |
| DH5 | 2.888 | time slot length *1600/6 /79 * 31.6 | 308.05 | 0.4 | BDR |
| 3DH1 | 0.386 | time slot length *1600/2 /79 * 31.6 | 123.52 | 0.4 | EDR |
| 3DH3 | 1.635 | time slot length *1600/4 /79 * 31.6 | 261.60 | 0.4 | EDR |
| 3DH5 | 2.888 | time slot length *1600/6 /79 * 31.6 | 308.05 | 0.4 | EDR |
| Remark: The EDR was tested on (π/4QPSK, 8DPSK) modes, only the worst data of (8DPSK) is attached in the following pages. | | | | | |




Test Mode: BDR---DH1




Test Mode: BDR---DH3




Test Mode: BDR---DH5




Test Mode: EDR---3DH1




Test Mode: EDR---3DH3




Test Mode: EDR---3DH5

# 10. 100kHz Bandwidth of Frequency Band Edge Requirement

## 10.1. Test Standard and Limit

| | |
|---|---|
| Test Standard | FCC Part15 C Section 15.247 (d) |
| Test Limit | in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a). |

## 10.2. Test Setup




## 10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

## 10.4. Test Data

| | | | | | |
|---|---|---|---|---|---|
| Test Item | : | Band edge | Test Mode | : | CH Low ~ CH High |
| Test Voltage | : | AC 120V, 60Hz for adapter | Temperature | : | 23.6° C |
| Test Result | : | PASS | Humidity | : | 49 % |

Remark: The EDR was tested on (π/4QPSK, 8DPSK) modes, only the worst data of (π/4DQPSK) is attached in the following pages.

**For Hopping Mode**




BDR mode




EDR mode

**For Non-Hopping Mode**




BDR mode -- Lowest




BDR mode -- Highest

**For Non-Hopping Mode**




EDR mode -- Lowest




EDR mode -- Highest

Conducted Emission Method




Test Mode: BDR---Low




Test Mode: BDR---Mid




Test Mode: BDR---High




Test Mode: EDR---Low




Test Mode: EDR---Mid




Test Mode: EDR---High

# 11. Antenna Requirement

## 11.1. Test Standard and Requirement

| | |
|---|---|
| Test Standard | FCC Part15 Section 15.203 /247(c) |
| Requirement | 1) 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.<br>2) 15.247(c) (1)(i) requirement:<br>Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. |

## 11.2. Antenna Connected Construction

The antenna is PCB Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.



# APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement

Photo of Radiation Emission Test



# APPENDIX II -- EXTERNAL PHOTOGRAPH





DEVICE
BLUETOOTH
<98D331F4135F>

Anbotek
Product Safety

# APPENDIX III -- INTERNAL PHOTOGRAPH












---------- End of Report ----------