


FCC PART 15.247  
RSS-GEN ISSUE 5, MARCH 2019 AMENDMENT 1  
RSS-247, ISSUE 2, FEBRUARY 2017  
**TEST REPORT**

For

**Shenzhen Zhiyun IOT Co., LTD**

East Block 3 BLD 5. BLD.1, Tongfu Industrial Park Longgang District, Shenzhen, China

**FCC ID: 2AWRR-PRD**  
**IC: 26308-PRD**

|                                                                                                                                                                                                                                                                                                                     |                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                                                              | <b>Product Type:</b><br>Smart WiFi Security Camera                                              |
| <b>Report Number:</b> RSZ200710002                                                                                                                                                                                                                                                                                  |                                                                                                 |
| <b>Report Date:</b> 2021-05-08                                                                                                                                                                                                                                                                                      |                                                                                                 |
| <b>Reviewed By:</b> RF Engineer                                                                                                                                                                                                                                                                                     | Jacob Kong  |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>5F(B-West) ,6F,7F,the 3rd Phase of Wan Li Industrial<br>Building D,Shihua Rd, FuTian Free Trade Zone,<br>Shenzhen, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                                                                                 |

**Note:** This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

|                                                                                                                     |           |
|---------------------------------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                                                     | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                                            | 4         |
| OBJECTIVE .....                                                                                                     | 4         |
| TEST METHODOLOGY .....                                                                                              | 4         |
| MEASUREMENT UNCERTAINTY .....                                                                                       | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                                               | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                                             | 6         |
| EQUIPMENT MODIFICATIONS .....                                                                                       | 6         |
| EUT EXERCISE SOFTWARE .....                                                                                         | 6         |
| DUTY CYCLE .....                                                                                                    | 6         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                                            | 7         |
| EXTERNAL I/O CABLE.....                                                                                             | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                                                   | 7         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                                                | <b>8</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                                                                    | <b>9</b>  |
| <b>FCC §15.247 (i) &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>                                       | <b>10</b> |
| APPLICABLE STANDARD .....                                                                                           | 10        |
| RESULT .....                                                                                                        | 10        |
| <b>RSS-102 § 2.5.2 –EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION</b>                              | <b>11</b> |
| APPLICABLE STANDARD .....                                                                                           | 11        |
| <b>§15.203 &amp; RSS-Gen §6.8 ANTENNA REQUIREMENT .....</b>                                                         | <b>12</b> |
| APPLICABLE STANDARD .....                                                                                           | 12        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                                                | 13        |
| <b>§15.207 (a) &amp; RSS-GEN §8.8 AC LINE CONDUCTED EMISSIONS .....</b>                                             | <b>14</b> |
| APPLICABLE STANDARD .....                                                                                           | 14        |
| EUT SETUP .....                                                                                                     | 15        |
| EMI TEST RECEIVER SETUP.....                                                                                        | 15        |
| TEST PROCEDURE .....                                                                                                | 15        |
| CORRECTED FACTOR & MARGIN CALCULATION .....                                                                         | 16        |
| TEST DATA .....                                                                                                     | 16        |
| <b>§15.205, §15.209, §15.247(d) &amp; RSS-GEN § 8.10 &amp; RSS-247 § 5.5 SPURIOUS EMISSIONS .....</b>               | <b>19</b> |
| APPLICABLE STANDARD .....                                                                                           | 19        |
| EUT SETUP.....                                                                                                      | 19        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                                                   | 20        |
| TEST PROCEDURE .....                                                                                                | 20        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                                                      | 21        |
| TEST DATA .....                                                                                                     | 21        |
| <b>§15.247 (a)(2) &amp; RSS-Gen §6.7 RSS-247 §5.2 (a) 99% OCCUPIED BANDWIDTH &amp; 6 dB EMISSION BANDWIDTH.....</b> | <b>30</b> |
| APPLICABLE STANDARD .....                                                                                           | 30        |
| TEST PROCEDURE .....                                                                                                | 30        |
| TEST DATA .....                                                                                                     | 31        |

|                                                                                      |           |
|--------------------------------------------------------------------------------------|-----------|
| <b>§15.247(b)(3) &amp; RSS-247 § 5.4(d) MAXIMUM CONDUCTED OUTPUT POWER .....</b>     | <b>32</b> |
| APPLICABLE STANDARD .....                                                            | 32        |
| TEST PROCEDURE .....                                                                 | 32        |
| TEST DATA .....                                                                      | 33        |
| <b>§15.247(d) &amp; RSS-247 § 5.5 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE .....</b> | <b>34</b> |
| APPLICABLE STANDARD .....                                                            | 34        |
| TEST PROCEDURE .....                                                                 | 34        |
| TEST DATA .....                                                                      | 34        |
| <b>§15.247(e) &amp; RSS-247 § 5.2 (b) POWER SPECTRAL DENSITY .....</b>               | <b>35</b> |
| APPLICABLE STANDARD .....                                                            | 35        |
| TEST PROCEDURE .....                                                                 | 35        |
| TEST DATA .....                                                                      | 35        |
| <b>APPENDIX .....</b>                                                                | <b>36</b> |
| APPENDIX A: DTS BANDWIDTH .....                                                      | 36        |
| APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....                                         | 40        |
| APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER .....                                     | 44        |
| APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....                                     | 45        |
| APPENDIX E: BAND EDGE MEASUREMENTS.....                                              | 50        |
| APPENDIXG: DUTYCYCLE .....                                                           | 52        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                     |                                                                                                                                                                                                                                       |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                             | Smart WiFi Security Camera                                                                                                                                                                                                            |
| Tested Model                        | ZY-128                                                                                                                                                                                                                                |
| HVIN                                | HM0003                                                                                                                                                                                                                                |
| Multiple Models(FCC)                | Protect B2,Protect B3,Protect D1,Protect D2,Protect D3,Protect D4,HM202A,HM202A UG,HM311,HM311 UG,AP30, Nature-Univo1,Nature-Univo2, ZY101,ZY102,ZY103,ZY104,ZY105,ZY106,ZY107,ZY108,ZY109,ZY110, ZY111,ZY112,ZY113,ZY114,ZY115,ZY116 |
| Multiple Models(ISED)               | Protect B2, Protect D1, Protect D2, Protect D3                                                                                                                                                                                        |
| Models Differences                  | Please refer to the DoS letter                                                                                                                                                                                                        |
| Frequency Range                     | Wi-Fi: 2412~2472MHz                                                                                                                                                                                                                   |
| Maximum Conducted Peak Output Power | 16.99dBm(802.11b), 16.41dBm(802.11g), 16.63dBm(802.11n-HT20)                                                                                                                                                                          |
| Modulation Technique                | Wi-Fi: DSSS, OFDM                                                                                                                                                                                                                     |
| Antenna Specification*              | 5.0dBi (It is provided by the applicant)                                                                                                                                                                                              |
| Voltage Range                       | DC12.0V from adapter                                                                                                                                                                                                                  |
| Date of Test                        | 2020-07-20 to 2021-08-08                                                                                                                                                                                                              |
| Sample serial number                | RSZ200710002-RF-S1 (Assigned by BACL, Shenzhen)                                                                                                                                                                                       |
| Received date                       | 2020-07-10                                                                                                                                                                                                                            |
| Sample/EUT Status                   | Good condition                                                                                                                                                                                                                        |
| Adapter2 information                | Model:SAN-12010<br>Input: 100-240V, 50/60Hz, 0.4A<br>Output: DC12.0V, 1.0A                                                                                                                                                            |

### Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules and RSS-GEN Issue 5, March 2019 Amendment 1 and RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and RSS-GEN Issue 5, March 2019 Amendment 1 and RSS-247, Issue 2, February 2017.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

| Parameter                          |            | Uncertainty |
|------------------------------------|------------|-------------|
| Occupied Channel Bandwidth         |            | ±5%         |
| RF Output Power with Power meter   |            | ±0.73dB     |
| RF conducted test with spectrum    |            | ±1.6dB      |
| AC Power Lines Conducted Emissions |            | ±1.95dB     |
| Emissions,<br>Radiated             | Below 1GHz | ±4.75dB     |
|                                    | Above 1GHz | ±4.88dB     |
| Temperature                        |            | ±1 °C       |
| Humidity                           |            | ±6%         |
| Supply voltages                    |            | ±0.4%       |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) ,6F,7F,the 3rd Phase of Wan Li Industrial Building D,Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier : CN0023.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

#### Frequency List

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 8       | 2447            |
| 2       | 2417            | 9       | 2452            |
| 3       | 2422            | 10      | 2457            |
| 4       | 2427            | 11      | 2462            |
| 5       | 2432            | 12      | 2467            |
| 6       | 2437            | 13      | 2472            |
| 7       | 2442            | /       | /               |

For 802.11b/g/n20 mode, EUT was tested with Channel 1, 7 and 13.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

“REALTEK”\* software was used.

The device was tested with the worst case was performed as below:

| Mode         | Data rate | Power level* |         |         |         |
|--------------|-----------|--------------|---------|---------|---------|
|              |           | 2412MHz      | 2442MHz | 2467MHz | 2472MHz |
| 802.11b      | 1 Mbps    | 40           | 40      | /       | 41      |
| 802.11g      | 6 Mbps    | 45           | 46      | 46      | 28      |
| 802.11n-HT20 | MCS0      | 45           | 46      | 46      | 24      |

Note: the software and power level was provided by the applicant.

### Duty cycle

Test Result: Pass. Please refer to the Appendix.


### Support Equipment List and Details

| Manufacturer | Description | Model      | Serial Number |
|--------------|-------------|------------|---------------|
| HUAWEI       | Honor10     | BKL-AI20   | N/A           |
| HIKVISION    | Router      | DS-3WR03-E | 10021642429   |
| BULL         | Socket      | GN-415K    | 5503290068073 |

### External I/O Cable

| Cable Description                   | Length (m) | From Port | To      |
|-------------------------------------|------------|-----------|---------|
| Un-shielded un-detachable AC Cable  | 1.2        | socket    | mains   |
| Un-Shielding Un-Detachable DC Cable | 1.0        | EUT       | Adapter |
| Un-shielded Detachable RJ45 Cable   | 4.0        | EUT       | Router  |

### Block Diagram of Test Setup



## SUMMARY OF TEST RESULTS

| FCC Rules                    | RSS-247 & RSS-Gen Rules           | Description of Test                                                                                  | Result     |
|------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------|------------|
| §15.247 (i), §2.1091         | RSS-102 §2.5.2                    | Maximum Permissible Exposure(MPE) & Exemption Limits for Routine Evaluation – RF Exposure Evaluation | Compliance |
| §15.203                      | RSS-Gen §6.8                      | Antenna Requirement                                                                                  | Compliance |
| §15.207 (a)                  | RSS-Gen §8.8                      | AC Line Conducted Emissions                                                                          | Compliance |
| §15.205, §15.209, §15.247(d) | RSS-GEN §8.10 & RSS-247 §5.5      | Spurious Emissions                                                                                   | Compliance |
| §15.247 (a)(2)               | RSS- Gen §6.7<br>RSS-247 §5.2 (a) | 99% Occupied Bandwidth & 6 dB Emission Bandwidth                                                     | Compliance |
| §15.247(b)(3)                | RSS-247 §5.4(d)                   | Maximum Conducted Output Power                                                                       | Compliance |
| §15.247(d)                   | RSS-247 §5.5                      | 100 kHz Bandwidth of Frequency Band Edge                                                             | Compliance |
| §15.247(e)                   | RSS-247 §5.2 (b)                  | Power Spectral Density                                                                               | Compliance |

## TEST EQUIPMENT LIST

| Manufacturer                    | Description                  | Model           | Serial Number          | Calibration Date | Calibration Due Date |
|---------------------------------|------------------------------|-----------------|------------------------|------------------|----------------------|
| <b>Conducted Emissions Test</b> |                              |                 |                        |                  |                      |
| Rohde & Schwarz                 | EMI Test Receiver            | ESCI            | 101120                 | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                 | LISN                         | ENV216          | 101613                 | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                 | Transient Limitor            | ESH3Z2          | DE25985                | 2020/11/29       | 2021/11/28           |
| Unknown                         | CE Cable                     | CE Cable        | UF A210B-1-0720-504504 | 2020/11/29       | 2021/11/28           |
| Rohde & Schwarz                 | CE Test software             | EMC 32          | V8.53.0                | NCR              | NCR                  |
| <b>Radiated Emission Test</b>   |                              |                 |                        |                  |                      |
| R&S                             | EMI Test Receiver            | ESR3            | 102455                 | 2020/08/04       | 2021/08/03           |
| Sonoma instrument               | Pre-amplifier                | 310 N           | 186238                 | 2020/08/04       | 2021/08/03           |
| Sunol Sciences                  | Broadband Antenna            | JB1             | A040904-2              | 2020/12/22       | 2023/12/21           |
| Unknown                         | Cable                        | Chamber Cable 1 | F-03-EM236             | 2020/11/29       | 2021/11/28           |
| Unknown                         | Cable                        | Chamber Cable 4 | EC-007                 | 2020/11/29       | 2021/11/28           |
| Rohde & Schwarz                 | Auto test software           | EMC 32          | V9.10                  | NCR              | NCR                  |
| Rohde & Schwarz                 | Spectrum Analyzer            | FSV40-N         | 102259                 | 2020/08/04       | 2021/08/03           |
| COM-POWER                       | Pre-amplifier                | PA-122          | 181919                 | 2020/11/29       | 2021/11/28           |
| Quinstar                        | Amplifier                    | QLW-18405536-J0 | 15964001002            | 2019/11/29       | 2020/11/28           |
| Sunol Sciences                  | Horn Antenna                 | 3115            | 9107-3694              | 2021/01/15       | 2024/01/14           |
| Insulted Wire Inc.              | RF Cable                     | SPS-2503-3150   | 02222010               | 2020/11/29       | 2021/11/28           |
| Unknown                         | RF Cable                     | W1101-EQ1 OUT   | F-19-EM005             | 2020/11/29       | 2021/11/28           |
| MICRO-TRONICS                   | Passband filter              | HPM50111        | F-19-EM006             | 2020/04/20       | 2021/04/20           |
| Ducommun Technologies           | Horn antenna                 | ARH-4223-02     | 1007726-021304         | 2020/12/06       | 2023/12/05           |
| <b>RF Conducted Test</b>        |                              |                 |                        |                  |                      |
| Tonscend Corporation            | RF control Unit              | JS0806-2        | 19D8060154             | 2019/08/04       | 2020/08/03           |
| Tonscend Corporation            | RF control Unit              | JS0806-2        | 19D8060154             | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                 | Signal and Spectrum Analyzer | FSV40           | 101473                 | 2019/08/04       | 2020/08/03           |
| Rohde & Schwarz                 | Signal and Spectrum Analyzer | FSV40           | 101473                 | 2020/08/04       | 2021/08/03           |
| Unknown                         | RF Cable                     | Unknown         | 2301 276               | 2019/11/29       | 2020/11/28           |
| Unknown                         | RF Cable                     | Unknown         | 2301 276               | 2020/11/29       | 2021/11/28           |

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|-----------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                               | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (Minutes) |
| 0.3-1.34                                            | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                             | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                              | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                            | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000                                        | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density

### Result

#### Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

| Frequency (MHz) | Antenna Gain |           | Tune up conducted power |       | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|-----------------|--------------|-----------|-------------------------|-------|--------------------------|-------------------------------------|---------------------------------|
|                 | (dBi)        | (numeric) | (dBm)                   | (mW)  |                          |                                     |                                 |
| 2412-2472       | 5            | 3.16      | 17.5                    | 56.23 | 20                       | 0.035                               | 1                               |

Note: 1. The tune up conducted power was declared by the applicant

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Pass**

## **RSS-102 § 2.5.2 –EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION**

### **Applicable Standard**

According to RSS-102 §(2.5.2):

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance). In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

### **Calculated Data:**

The max tune-up conducted output power is 17.5 dBm, antenna gain is 5dBi.

Time-averaged maximum e.i.r.p. of the device is  $17.5\text{dBm} + 5\text{dBi} = 22.5\text{dBm} = 0.178\text{ W}$

The worst case is  $f = 2412\text{ MHz}$ :

The limit is  $1.31 \times 10^{-2} f^{0.6834} \text{ W} = 2.68\text{ W}$

$0.178\text{ W} < 2.68\text{ W}$

**So the RF Exposure evaluation can be exempted.**

---

## §15.203 & RSS-Gen §6.8 ANTENNA REQUIREMENT

---

### Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISSED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

**Antenna Connector Construction**

The EUT has an integral antenna arrangement for Wi-Fi which was permanently attached and the antenna gain is 5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

| Type     | Antenna Gain | Impedance |
|----------|--------------|-----------|
| Monopole | 5dBi         | 50Ω       |

**Result: Compliance**

## § 15.207 (a) & RSS-GEN §8.8 AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50  $\mu$ H / 50  $\Omega$  line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

| Table 4 - AC Power Lines Conducted Emission Limits |                              |                       |
|----------------------------------------------------|------------------------------|-----------------------|
| Frequency range<br>(MHz)                           | Conducted limit (dB $\mu$ V) |                       |
|                                                    | Quasi-Peak                   | Average               |
| 0.15 – 0.5                                         | 66 to 56 <sup>1</sup>        | 56 to 46 <sup>1</sup> |
| 0.5 – 5                                            | 56                           | 46                    |
| 5 – 30                                             | 60                           | 50                    |


**Note 1:** The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

## EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 & RSS-247/RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 65 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Haiguo Li on 2021-04-17.*


*EUT operation mode: Wi-Fi transmitting*

**AC 120V/60 Hz, Line****Final Result 1**

| Frequency (MHz) | QuasiPeak (dBμ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμ V) |
|-----------------|-------------------|-----------------|------|------------|-------------|---------------|
| 0.344750        | 43.5              | 9.000           | L1   | 19.9       | 15.6        | 59.1          |
| 0.383670        | 44.9              | 9.000           | L1   | 19.9       | 13.3        | 58.2          |
| 0.529930        | 50.5              | 9.000           | L1   | 19.8       | 5.5         | 56.0          |
| 0.529990        | 50.6              | 9.000           | L1   | 19.8       | 5.4         | 56.0          |
| 0.596970        | 38.2              | 9.000           | L1   | 19.8       | 17.8        | 56.0          |
| 0.695590        | 40.8              | 9.000           | L1   | 19.8       | 15.2        | 56.0          |

**Final Result 2**

| Frequency (MHz) | Average (dBμ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμ V) |
|-----------------|-----------------|-----------------|------|------------|-------------|---------------|
| 0.344750        | 28.1            | 9.000           | L1   | 19.9       | 21.0        | 49.1          |
| 0.383670        | 30.6            | 9.000           | L1   | 19.9       | 17.6        | 48.2          |
| 0.529930        | 36.8            | 9.000           | L1   | 19.8       | 9.2         | 46.0          |
| 0.529990        | 36.4            | 9.000           | L1   | 19.8       | 9.6         | 46.0          |
| 0.596970        | 24.2            | 9.000           | L1   | 19.8       | 21.8        | 46.0          |
| 0.695590        | 27.6            | 9.000           | L1   | 19.8       | 18.4        | 46.0          |

**AC 120V/60 Hz, Neutral****Final Result 1**

| Frequency (MHz) | QuasiPeak (dBμ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμ V) |
|-----------------|-------------------|-----------------|------|------------|-------------|---------------|
| 0.339010        | 43.8              | 9.000           | N    | 19.8       | 15.4        | 59.2          |
| 0.375550        | 48.2              | 9.000           | N    | 19.8       | 10.2        | 58.4          |
| 0.537930        | 49.4              | 9.000           | N    | 19.8       | 6.6         | 56.0          |
| 0.537950        | 49.4              | 9.000           | N    | 19.8       | 6.6         | 56.0          |
| 0.707230        | 41.7              | 9.000           | N    | 19.8       | 14.3        | 56.0          |
| 0.896410        | 40.7              | 9.000           | N    | 19.7       | 15.3        | 56.0          |

**Final Result 2**

| Frequency (MHz) | Average (dBμ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμ V) |
|-----------------|-----------------|-----------------|------|------------|-------------|---------------|
| 0.374000        | 36.9            | 9.000           | N    | 19.8       | 11.5        | 48.4          |
| 0.530000        | 42.1            | 9.000           | N    | 19.8       | 3.9         | 46.0          |
| 0.538000        | 42.6            | 9.000           | N    | 19.8       | 3.4         | 46.0          |
| 0.722000        | 32.5            | 9.000           | N    | 19.8       | 13.5        | 46.0          |
| 0.754000        | 32.4            | 9.000           | N    | 19.8       | 13.6        | 46.0          |
| 23.130000       | 38.0            | 9.000           | N    | 20.3       | 12.0        | 50.0          |

## §15.205, §15.209, §15.247(d) & RSS-GEN §8.10 & RSS-247 §5.5 SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


According to RSS-GEN §8.10 & RSS-247 §5.5


Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply: (a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD). (b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6. (c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### EUT Setup

Below 1 GHz:



**Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013 & RSS-Gen. The specification used was the FCC 15.209, and FCC 15.247 & RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W               | IF B/W  | Measurement |
|-------------------|---------|-------------------------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz                 | 120 kHz | QP          |
| Above 1 GHz       | 1MHz    | 3 MHz                   | /       | PK          |
|                   | 1MHz    | 10 Hz <sup>Note 1</sup> | /       | Average     |
|                   | 1MHz    | > 1/T <sup>Note 2</sup> | /       | Average     |

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Data


#### Environmental Conditions

|                           |                |
|---------------------------|----------------|
| <b>Temperature:</b>       | 26.8~28°C      |
| <b>Relative Humidity:</b> | 44~59 %        |
| <b>ATM Pressure:</b>      | 100.9~101.0kPa |

*The testing was performed by Zero Yan on 2021-04-17 for below 1GHz and by Alan He on 2021-04-19 for above 1GHz*

*EUT operation mode: Wi-Fi transmitting*

30 MHz~1 GHz: (worst case at 802.11b mode, low channel)



## Final\_Result

| Frequency (MHz) | QuasiPeak (dBμ V/m) | Limit (dBμ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|---------------------|-----------------|-------------|-------------|-----|---------------|--------------|
| 43.833750       | 27.38               | 40.00           | 12.62       | 220.0       | V   | 111.0         | -13.0        |
| 66.293250       | 35.37               | 40.00           | 4.63        | 242.0       | V   | 44.0          | -16.3        |

## Critical\_Freqs

| Frequency (MHz) | MaxPeak (dBμ) | Limit (dBμ) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|---------------|-------------|-------------|-------------|-----|---------------|--------------|
| 110.752500      | 31.55         | 43.50       | 11.95       | 300.0       | H   | 70.0          | -11.1        |
| 296.992500      | 32.63         | 46.00       | 13.37       | 200.0       | V   | 165.0         | -10.1        |
| 405.026250      | 36.37         | 46.00       | 9.63        | 300.0       | H   | 95.0          | -7.2         |
| 432.065000      | 34.66         | 46.00       | 11.34       | 300.0       | H   | 95.0          | -6.2         |

Note: the QP measurement will not performed when the peak value was more than 6dB lower than limit.

**1 GHz-25 GHz (Wi-Fi):****802.11b Mode:**

| Frequency<br>(MHz)       | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2387.62                  | 28.67             | PK         | 1                   | 2.4           | V              | 31.87                         | 60.54                              | 74                | 13.46          |
| 2387.62                  | 13.95             | Ave.       | 1                   | 2.4           | V              | 31.87                         | 45.82                              | 54                | 8.18           |
| 2485.17                  | 29.34             | PK         | 54                  | 2.0           | V              | 32.13                         | 61.47                              | 74                | 12.53          |
| 2485.17                  | 14.01             | Ave.       | 54                  | 2.0           | V              | 32.13                         | 46.14                              | 54                | 7.86           |
| 4824.00                  | 46.02             | PK         | 343                 | 1.0           | V              | 6.28                          | 52.30                              | 74                | 21.70          |
| 4824.00                  | 37.34             | Ave.       | 343                 | 1.0           | V              | 6.28                          | 43.62                              | 54                | 10.38          |
| Middle Channel (2442MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4884.00                  | 45.64             | PK         | 343                 | 1.3           | V              | 6.76                          | 52.40                              | 74                | 21.60          |
| 4884.00                  | 36.37             | Ave.       | 343                 | 1.3           | V              | 6.76                          | 43.13                              | 54                | 10.87          |
| High Channel (2472 MHz)  |                   |            |                     |               |                |                               |                                    |                   |                |
| 2386.37                  | 29.30             | PK         | 89                  | 2.3           | V              | 31.87                         | 61.17                              | 74                | 12.83          |
| 2386.37                  | 13.98             | Ave.       | 89                  | 2.3           | V              | 31.87                         | 45.85                              | 54                | 8.15           |
| 2484.49                  | 30.61             | PK         | 173                 | 1.9           | V              | 32.13                         | 62.74                              | 74                | 11.26          |
| 2484.49                  | 17.91             | Ave.       | 173                 | 1.9           | V              | 32.13                         | 50.04                              | 54                | 3.96           |
| 4944.00                  | 45.93             | PK         | 211                 | 2.2           | V              | 6.76                          | 52.69                              | 74                | 21.31          |
| 4944.00                  | 37.98             | Ave.       | 211                 | 2.2           | V              | 6.76                          | 44.74                              | 54                | 9.26           |

**802.11g Mode:**

| Frequency<br>(MHz)       | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2382.74                  | 28.87             | PK         | 54                  | 1.2           | V              | 31.87                         | 60.74                              | 74                | 13.26          |
| 2382.74                  | 14.16             | Ave.       | 54                  | 1.2           | V              | 31.87                         | 46.03                              | 54                | 7.97           |
| 2485.35                  | 28.72             | PK         | 270                 | 1.8           | V              | 32.13                         | 60.85                              | 74                | 13.15          |
| 2485.35                  | 14.18             | Ave.       | 270                 | 1.8           | V              | 32.13                         | 46.31                              | 54                | 7.69           |
| 4824.00                  | 43.69             | PK         | 258                 | 2.3           | V              | 6.28                          | 49.97                              | 74                | 24.03          |
| 4824.00                  | 29.35             | Ave.       | 258                 | 2.3           | V              | 6.28                          | 35.63                              | 54                | 18.37          |
| Middle Channel (2442MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4884.00                  | 43.37             | PK         | 93                  | 2.2           | V              | 6.76                          | 50.13                              | 74                | 23.87          |
| 4884.00                  | 29.16             | Ave.       | 93                  | 2.2           | V              | 6.76                          | 35.92                              | 54                | 18.08          |
| High Channel(2467 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2383.92                  | 28.69             | PK         | 38                  | 1.6           | V              | 31.87                         | 60.56                              | 74                | 13.44          |
| 2383.92                  | 13.81             | AV         | 38                  | 1.6           | V              | 31.87                         | 45.68                              | 54                | 8.32           |
| 2485.42                  | 30.75             | PK         | 83                  | 2.4           | V              | 32.13                         | 62.88                              | 74                | 11.12          |
| 2485.42                  | 16.12             | AV         | 83                  | 2.4           | V              | 32.13                         | 48.25                              | 54                | 5.75           |
| 4934.00                  | 43.32             | PK         | 324                 | 1.7           | V              | 6.76                          | 50.08                              | 74                | 23.92          |
| 4934.00                  | 28.52             | AV         | 324                 | 1.7           | V              | 6.76                          | 35.28                              | 54                | 18.72          |
| High Channel(2472 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2381.65                  | 28.58             | PK         | 192                 | 1.1           | V              | 31.87                         | 60.45                              | 74                | 13.55          |
| 2381.65                  | 13.78             | Ave.       | 192                 | 1.1           | V              | 31.87                         | 45.65                              | 54                | 8.35           |
| 2483.54                  | 38.69             | PK         | 248                 | 1.7           | V              | 32.13                         | 70.82                              | 74                | 3.18           |
| 2483.54                  | 17.85             | Ave.       | 248                 | 1.7           | V              | 32.13                         | 49.98                              | 54                | 4.02           |
| 4944.00                  | 42.64             | PK         | 102                 | 2.3           | V              | 6.76                          | 49.40                              | 74                | 24.60          |
| 4944.00                  | 28.94             | Ave.       | 102                 | 2.3           | V              | 6.76                          | 35.70                              | 54                | 18.30          |

**802.11n-HT20 Mode:**

| Frequency<br>(MHz)       | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2380.81                  | 28.97             | PK         | 308                 | 1.4           | V              | 31.87                         | 60.84                              | 74                | 13.16          |
| 2380.81                  | 14.21             | Ave.       | 308                 | 1.4           | V              | 31.87                         | 46.08                              | 54                | 7.92           |
| 2484.68                  | 28.65             | PK         | 144                 | 2.4           | V              | 32.13                         | 60.78                              | 74                | 13.22          |
| 2484.68                  | 14.11             | Ave.       | 144                 | 2.4           | V              | 32.13                         | 46.24                              | 54                | 7.76           |
| 4824.00                  | 44.15             | PK         | 16                  | 2.0           | V              | 6.28                          | 50.43                              | 74                | 23.57          |
| 4824.00                  | 29.28             | Ave.       | 16                  | 2.0           | V              | 6.28                          | 35.56                              | 54                | 18.44          |
| Middle Channel (2442MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4884.00                  | 42.73             | PK         | 284                 | 1.9           | V              | 6.76                          | 49.49                              | 74                | 24.51          |
| 4884.00                  | 29.04             | Ave.       | 284                 | 1.9           | V              | 6.76                          | 35.80                              | 54                | 18.20          |
| High Channel(2467 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2327.66                  | 28.50             | PK         | 311                 | 1.1           | V              | 31.64                         | 60.14                              | 74                | 13.86          |
| 2327.66                  | 13.80             | Ave.       | 311                 | 1.1           | V              | 31.64                         | 45.44                              | 54                | 8.56           |
| 2486.69                  | 30.71             | PK         | 327                 | 2.4           | V              | 32.13                         | 62.84                              | 74                | 11.16          |
| 2486.69                  | 16.03             | Ave.       | 327                 | 2.4           | V              | 32.13                         | 48.16                              | 54                | 5.84           |
| 4934.00                  | 43.24             | PK         | 319                 | 1.2           | V              | 6.76                          | 50.00                              | 74                | 24.00          |
| 4934.00                  | 28.60             | Ave.       | 319                 | 1.2           | V              | 6.76                          | 35.36                              | 54                | 18.64          |
| High Channel(2472 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2386.78                  | 28.91             | PK         | 211                 | 2.3           | V              | 31.87                         | 60.78                              | 74                | 13.22          |
| 2386.78                  | 14.18             | Ave.       | 211                 | 2.3           | V              | 31.87                         | 46.05                              | 54                | 7.95           |
| 2483.61                  | 38.62             | PK         | 269                 | 2.1           | V              | 32.13                         | 70.75                              | 74                | 3.25           |
| 2483.61                  | 17.09             | Ave.       | 269                 | 2.1           | V              | 32.13                         | 49.22                              | 54                | 4.78           |
| 4944.00                  | 42.39             | PK         | 186                 | 2.3           | V              | 6.76                          | 49.15                              | 74                | 24.85          |
| 4944.00                  | 28.77             | Ave.       | 186                 | 2.3           | V              | 6.76                          | 35.53                              | 54                | 18.47          |

**Note:**



Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


### Pre-scan with high channel in 802.11b Vertical



## Horizontal




Date: 19.APR.2021 10:55:57




Date: 19.APR.2021 11:42:11

## Vertical





Date: 19.APR.2021 10:51:03



Date: 19.APR.2021 11:36:22

## Horizontal



---

## **§15.247 (a)(2) & RSS-Gen §6.7 RSS-247 § 5.2 (a) 99% OCCUPIED BANDWIDTH & 6 dB EMISSION BANDWIDTH**

---

### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “6 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 6 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

### **Test Procedure**


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

The following conditions shall be observed for measuring the occupied bandwidth and 6 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 6 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 6 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong and Bravos Zhao from 2020-07-20 to 2021-04-22.*

*EUT operation mode: Transmitting*

### Test Result: Pass

*Please refer to the Appendix.*

## §15.247(b)(3) & RSS-247 § 5.4(d) MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

For DTSS employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 27 °C     |
| <b>Relative Humidity:</b> | 57 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by George Zhong and Bravos Zhao from 2020-07-20 to 2021-04-22.*

*EUT operation mode: Transmitting*

**Test Result: Pass**

*Please refer to the Appendix.*


## § 15.247(d) & RSS-247 §5.5 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong and Bravos Zhao from 2020-07-20 to 2021-04-22.*

*EUT operation mode: Transmitting*

**Test Result: Pass**

*Please refer to the Appendix.*

## §15.247(e) & RSS-247 § 5.2 (b) POWER SPECTRAL DENSITY


### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by George Zhong and Bravos Zhao from 2020-07-20 to 2021-05-08.*

*EUT operation mode: Transmitting*

#### Test Result: Pass


*Please refer to the Appendix.*

## APPENDIX


### Appendix A: DTS Bandwidth Test Result

| TestMode  | Antenna | Channel | DTS BW [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|--------------|------------|---------|
| 11B       | Ant1    | 2412    | 9.120        | 0.5        | PASS    |
|           |         | 2442    | 9.120        | 0.5        | PASS    |
|           |         | 2472    | 9.160        | 0.5        | PASS    |
| 11G       | Ant1    | 2412    | 16.680       | 0.5        | PASS    |
|           |         | 2442    | 16.680       | 0.5        | PASS    |
|           |         | 2472    | 16.680       | 0.5        | PASS    |
| 11N20SISO | Ant1    | 2412    | 17.840       | 0.5        | PASS    |
|           |         | 2442    | 17.840       | 0.5        | PASS    |
|           |         | 2472    | 17.800       | 0.5        | PASS    |

## Test Graphs




## 11G Ant1 2412




Date: 20.JUL.2020 20:48:21

## 11G Ant1 2442




Date: 20.JUL.2020 20:50:23

## 11G Ant1 2472




Date: 22.APR.2021 09:28:49

## 11N20SISO Ant1\_2412




Date: 20.JUL.2020 20:54:29

## 11N20SISO Ant1\_2442



Date: 20.JUL.2020 20:58:24

## 11N20SISO Ant1\_2472




Date: 22.APR.2021 09:30:35


**Appendix B: Occupied Channel Bandwidth  
Test Result**

| TestMode  | Antenna | Channel | OCB [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|-----------|------------|---------|
| 11B       | Ant1    | 2412    | 13.746    | ---        | PASS    |
|           |         | 2442    | 13.906    | ---        | PASS    |
|           |         | 2472    | 13.946    | ---        | PASS    |
| 11G       | Ant1    | 2412    | 17.463    | ---        | PASS    |
|           |         | 2442    | 17.502    | ---        | PASS    |
|           |         | 2472    | 17.423    | ---        | PASS    |
| 11N20SISO | Ant1    | 2412    | 18.302    | ---        | PASS    |
|           |         | 2442    | 18.342    | ---        | PASS    |
|           |         | 2472    | 18.222    | ---        | PASS    |


## Test Graphs




## 11G\_Ant1\_2412




## 11G\_Ant1\_2442



## 11G\_Ant1\_2472




## 11N20SISO Ant1 2412




Date: 20.JUL.2020 20:54:40

## 11N20SISO Ant1 2442



Date: 20.JUL.2020 20:58:35

## 11N20SISO Ant1 2472



Date: 22.APR.2021 09:30:45


**Appendix C: Maximum conducted output power  
Test Result**


| TestMode  | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| 11B       | Ant1    | 2412    | 16.99       | <=30       | PASS    |
|           |         | 2442    | 16.14       | <=30       | PASS    |
|           |         | 2472    | 15.34       | <=30       | PASS    |
| 11G       | Ant1    | 2412    | 15.74       | <=30       | PASS    |
|           |         | 2442    | 15.30       | <=30       | PASS    |
|           |         | 2467    | 16.41       | <=30       | PASS    |
|           |         | 2472    | 10.04       | <=30       | PASS    |
| 11N20SISO | Ant1    | 2412    | 16.63       | <=30       | PASS    |
|           |         | 2442    | 15.83       | <=30       | PASS    |
|           |         | 2467    | 16.05       | <=30       | PASS    |
|           |         | 2472    | 8.51        | <=30       | PASS    |


**Appendix D: Maximum power spectral density  
Test Result**


| TestMode  | Antenna | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|---------|------------------|-----------------|---------|
| 11B       | Ant1    | 2412    | -13.8            | <=8             | PASS    |
|           |         | 2442    | -15.16           | <=8             | PASS    |
|           |         | 2472    | -15.82           | <=8             | PASS    |
| 11G       | Ant1    | 2412    | -15.41           | <=8             | PASS    |
|           |         | 2442    | -16.61           | <=8             | PASS    |
|           |         | 2467    | -13.7            | <=8             | PASS    |
|           |         | 2472    | -24.28           | <=8             | PASS    |
| 11N20SISO | Ant1    | 2412    | -15.1            | <=8             | PASS    |
|           |         | 2442    | -15.83           | <=8             | PASS    |
|           |         | 2467    | -14.4            | <=8             | PASS    |
|           |         | 2472    | -24.32           | <=8             | PASS    |

## Test Graphs











## Appendix E: Band edge measurements

### Test Graphs




## 11G Ant1 High 2472




Date: 22.APR.2021 09:29:13

## 11N20SISO Ant1 Low 2412



Date: 20.JUL.2020 20:55:09

## 11N20SISO Ant1 High 2472




Date: 22.APR.2021 09:30:19

**AppendixG: DutyCycle  
Test Result**

| TestMode  | Antenna | Channel | TransmissionDuration<br>[ms] | Transmission<br>Period [ms] | Duty Cycle [%] |
|-----------|---------|---------|------------------------------|-----------------------------|----------------|
| 11B       | Ant1    | 2442    | 30.00                        | 30.00                       | 100.00         |
| 11G       | Ant1    | 2442    | 30.00                        | 30.00                       | 100.00         |
| 11N20SISO | Ant1    | 2442    | 30.00                        | 30.00                       | 100.00         |

## Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*