



Report No.: PTC21022000901E-FC02

FCC TEST REPORT

FCC ID: 2AWT7-RBX-S20

Product	:	WIFI SOLAR CAMERA
Model Name	:	RBX-S20, RBX-S10, RBX-S22, RBX-S30, RBX-B10, RBX-B20, RBX-A10, RBX-S40, RBX-S50
Brand	:	RUIBOXY
Report No.	:	PTC21022000901E-FC02
Prepared for		
Shenzhen Tian You Intelligence Co.,Ltd		
Room 301,Building 5, Lixin Xinwei Industrial Park, Xili North Road No.50, Licheng Community, Xili Street,Nanshan District, Shenzhen China		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



TEST RESULT CERTIFICATION

Applicant's name : SHENZHEN RUIBOSI ELECTRONIC CO., LTD.
Address : Room 501, Block 2th, Shabian Industrial Zone, Area 505, Bao'an Airport, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen City, Guangdong Province
Manufacture's name : SHENZHEN RUIBOSI ELECTRONIC CO., LTD.
Address : Room 501, Block 2th, Shabian Industrial Zone, Area 505, Bao'an Airport, Sanwei Community, Hangcheng Street, Baoan District, Shenzhen City, Guangdong Province
Product name : WIFI SOLAR CAMERA
Model name : RBX-S20, RBX-S10, RBX-S22, RBX-S30, RBX-B10, RBX-B20, RBX-A10, RBX-S40, RBX-S50
Test procedure : KDB 447498 D01 General RF Exposure Guidance v06
Test Date : Feb. 18, 2021 to Mar. 04, 2021
Date of Issue : Mar. 05, 2021
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Leo Yang" with a checkmark-like flourish at the end.

Leo Yang / Engineer

Technical Manager:

A handwritten signature in black ink that appears to read "Chris Du" in a stylized, cursive font.

Chris Du / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



Report No.: PTC21022000901E-FC02

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	WIFI SOLAR CAMERA
Model Name	:	RBX-S20, RBX-S10, RBX-S22, RBX-S30, RBX-B10, RBX-B20, RBX-A10, RBX-S40, RBX-S50
Additional model		Note: The appearance and color of the product are different, and the electrical principle is the same. The main test model is RBX-S20
Specification	:	802.11b/g/n HT20/HT40
Operation Frequency	:	2412-2462MHz for 802.11b/g/ n(HT20) 2422-2452MHz for 802.11n(HT40)
Number of Channel	:	11 channels for 802.11b/g/ n(HT20) 7 channels for 802.11 n(HT40)
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	WIFI SOLAR CAMERA
Antenna Gain	:	3 dBi
Power supply	:	Input: AC120V 60HZ, DC 5V Battery: 3.7V 14400mAh
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : FCC Part 2.1091

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mw)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2412	2	14.62	29	0.0115	1	Pass

*****THE END REPORT*****