

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

FCC ID: 2AWUU60B4901
IC: 26271-60B4901

Page: 1 / 62
Rev.: 00

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

INDUSTRY CANADA RSS-247

Test Standard	FCC Part 15.247 IC RSS-247 issue 4 and IC RSS-GEN issue 5
Product name	Two-Channel Network Audio Player
Brand Name	Verkada
Model No.	NP21-HW
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10-2020 (FCC), ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024 (IC) and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.(Wugu Laboratory)

Approved by:



Kevin Tsai
Asst. Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 2 / 62
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	September 7, 2026	Initial Issue	ALL	Peggy Tsai

Table of contents

1.	GENERAL INFORMATION	4
1.1	EUT INFORMATION	4
1.2	EUT CHANNEL INFORMATION	5
1.3	ANTENNA INFORMATION	5
1.4	MEASUREMENT UNCERTAINTY.....	6
1.5	FACILITIES AND TEST LOCATION	6
1.6	INSTRUMENT CALIBRATION	7
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	9
1.8	TEST SET UP DIAGRAM	10
1.9	TEST PROGRAM	10
1.10	TEST METHODOLOGY AND APPLIED STANDARDS	10
2.	TEST SUMMERY	11
3.	DESCRIPTION OF TEST MODES.....	12
3.1	THE WORST MODE OF OPERATING CONDITION	12
3.2	THE WORST MODE OF MEASUREMENT	13
3.3	EUT DUTY CYCLE	14
4.	TEST RESULT	15
4.1	AC POWER LINE CONDUCTED EMISSION	15
4.2	6DB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)	20
4.3	OUTPUT POWER MEASUREMENT	25
4.4	POWER SPECTRAL DENSITY	29
4.5	CONDUCTED BAND EDGE AND SPURIOUS EMISSION	32
4.6	RADIATION BANDEDGE AND SPURIOUS EMISSION	36
APPENDIX A - PHOTOGRAPHS OF EUT		

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	FCC: Verkada Inc 405 E. 4th Ave. San Mateo California United States 94401 IC: Verkada, Inc. 405 E. 4th Ave. San Mateo CA 94401 United States Of America (Excluding The States Of Alaska)
Manufacturer	Verkada Inc 405 E. 4th Ave. San Mateo California United States 94401
Equipment	Two-Channel Network Audio Player
Model No. / HVIN	NP21-HW
Model Discrepancy	N/A
Trade Name	Verkada
Received Date	July 3, 2026
Date of Test	July 8 ~ 13, 2026
Power Operation	1. Powered from POE (Not for sell) Brand / Model: Verkada / POE60U-BTB I/P: 100-240Vac, 1.5A, 50-60Hz O/P Pair 1: 56Vdc, 0.535A, 30W, max PIN 3,6+PIN 1,2 Return O/P Pair 2: 56Vdc, 0.535A, 30W, max PIN 4,5+PIN 7,8 Return 2. Powered from AC 120V
PMN	NP21-HW
EUT Serial #	MFJN-R76L-EP73
HW Version	B3
SW Version	20002

Remark:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 EUT CHANNEL INFORMATION

Frequency Range	2402MHz-2480MHz
Modulation Type	GFSK for BLE 1 Mbps GFSK for BLE 2 Mbps
Number of channel	40 Channels

Remark:

Refer as ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC) and RSS-GEN for test channels.

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Type	☐ PIFA ☒ PCB ☐ Dipole ☐ FPC Antenna
Antenna Gain	Ant 1: 3.90 dBi Ant 2: 3.69 dBi
Antenna Connector	N/A

Notes:

- 1.The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203 and RSS-GEN 6.8.
2. The device is equipped with two antenna paths, ANT1 and ANT2. Based on verification results, ANT1 represents the worst-case condition and is therefore used for subsequent testing and compliance evaluation.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	±2.654dB
Channel Bandwidth	±0.216dB
RF output power (Spectrum)	±0.884dB
RF output power (Power Meter + Power sensor)	±0.442dB
Power Spectral density	±2.105dB
Conducted Bandedge	±2.104dB
Conducted Spurious Emission	±2.104dB
Radiated Emission_9kHz-30MHz	±2.998dB
Radiated Emission_30MHz-200MHz	±3.308dB
Radiated Emission_200MHz-1GHz	±3.506dB
Radiated Emission_1GHz-6GHz	±4.068dB
Radiated Emission_6GHz-18GHz	±4.120dB
Radiated Emission_18GHz-26GHz	±3.411dB
Radiated Emission_26GHz-40GHz	±3.410dB

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	Ben Yang	-
Radiation	Ben Yang	-
RF Conducted	Jerry Chang	-

Remark: The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC pubic Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

1.6 INSTRUMENT CALIBRATION

Conducted_FCC/IC/NCC (All)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
PXA Signal Analyzer	Keysight	N9030B	MY62291089	2025-09-24	2026-09-23
Power Sensor	Anritsu	MA2411B	1911387	2025-08-21	2026-08-20
Power Sensor	Anritsu	MA2411B	1911386	2026-06-23	2027-06-22
Power Meter	Anritsu	ML2496A	2136002	2026-06-23	2027-06-22
DC Blocks	Marvelous Microwave	MVE6411	MVE-001	2025-08-06	2026-08-05
Software	Radio Test Software Ver. 21				

966A_Radiated					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Signal Analyzer	Agilent	N9010A	MY52220817	2026-03-13	2027-03-12
Active Loop Antenna	COM-POWER	AL-130	121051	2026-02-04	2027-02-03
Thermo-Hygro Meter	HTC	HTC-1	HTC-D06	2026-05-19	2027-05-18
Bi-Log Antenna	Sunol Sciences	JB3	A030105&532	2026-06-18	2027-06-17
Preamplifier	EMEC	EM330	060609	2026-02-13	2027-02-12
Cable	Huber+Suhner	104PEA	20995+21000+182330	2025-08-06	2026-08-05
Horn Antenna	ETC	MCTD 1209	DRH13M02003	2025-12-19	2026-12-18
Preamplifier	HP	8449B	3008A00965	2025-12-17	2026-12-16
Cable	EMCI	EMC101G	1508S0193+230205+250412	2026-01-14	2027-01-13
Attenuator	Mini-Circuits	BW-S9W5	BWS9W5-09-966A-01	2026-02-05	2027-02-04
High Pass Filters	Titan Microwave	T04H30001800070S01	22011402-4	2026-06-01	2027-05-31
Pre-Amplifier	EMC	EMC184045SE	980860	2025-11-19	2026-11-18
Horn Antenna	SCHWARZBECK	BBHA9170	1047	2025-12-09	2026-12-08
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Software	e3 V9-210616c				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 8 / 62
Rev.: 00

AC Mains Conduction					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EMI Test Receiver	R&S	ESCI	100064	2026-05-21	2027-05-20
LISN	TESEQ	LN2-16N	22012	2026-02-04	2027-02-03
Cable	Woken	RFC-SMA-100-NMR-084SFL402	MFR-2Y194	2026-03-20	2027-03-19
Software	e3 V9-210616c				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT


EUT Accessories Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
	N/A					

Support Equipment (Conducted)						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	NB(K)	Lenovo	ThinkPad X260	N/A	N/A	N/A
A	Test kit	N/A	N/A	N/A	N/A	N/A

Support Equipment (RSE)						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	NB(D)	Lenovo	ThinkPad X260	N/A	N/A	N/A
2	Adapter	Lenovo	ADLX45DLC3A	N/A	N/A	N/A
3	Micro USB Cable	Philips	DLC4562U	N/A	N/A	N/A
4	RJ45	atake	AC6-FL10	N/A	N/A	N/A
A	Test Board	N/A	N/A	N/A	N/A	N/A
B	POE	Verkada	POE60U-BTB	N/A	N/A	N/A

Support Equipment (Conduction)						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	NB(D)	Lenovo	ThinkPad X260	N/A	N/A	N/A
2	Micro USB Cable	Philips	DLC4562U	N/A	N/A	N/A
3	RJ45	atake	AC6-FL10	N/A	N/A	N/A
A	Test Board	N/A	N/A	N/A	N/A	N/A
B	POE	Verkada	POE60U-BTB	N/A	N/A	N/A

1.8 TEST SET UP DIAGRAM



1.9 TEST PROGRAM

This EUT use Simplicity Studio software to set the frequency, modulation and power to allow continuous transmission of the sample.

Simplicity Studio v5.11.0

1.10 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC), FCC Part 2, FCC Part 15.247, KDB 558074, RSS-247 Issue 4 and RSS-GEN Issue 5.

2. TEST SUMMERY

FCC Standard Section	IC Standard Section	Report Section	Test Item	Result
15.203	-	1.3	Antenna Requirement	Pass
15.207(a)	RSS-GEN 8.8	4.1	AC Conducted Emission	Pass
15.247(a)(2)	RSS-247(6.3.1)(a)	4.2	6 dB Bandwidth	Pass
-	RSS-GEN 6.7	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	RSS-247(6.3.2)	4.3	Output Power Measurement	Pass
15.247(e)	RSS-247(6.3.1)(b)	4.4	Power Spectral Density	Pass
15.247(d)	RSS-247(6.6)	4.5	Conducted Band Edge	Pass
15.247(d)	RSS-247(6.6)	4.5	Conducted Spurious Emission	Pass
15.247(d) 15.205, 15.209	RSS-GEN 8.9, 8.10	4.6	Radiation Band Edge	Pass
15.247(d) 15.205, 15.209	RSS-GEN 8.9, 8.10	4.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	BLE Mode (1Mbps) BLE Mode (2Mbps)
Test Channel Frequencies	1.Lowest Channel : 2402MHz 2.Middle Channel : 2442MHz 3.Highest Channel : 2480MHz

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conduction Emission	
Test Condition	AC Power line conduction emission for line and neutral
Power supply Mode	Mode 1: EUT power by POE Mode 2: EUT power by AC 120V
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by POE
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by POE Mode 2: EUT power by AC 120V
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. AC power line conducted emission were performed the EUT transmit at the highest output power channel as worse case.
3. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.

3.3 EUT DUTY CYCLE


Temperature: 23.6°C

Test date: July 13, 2026


Humidity: 55% RH

Tested by: Jerry Chang

Mode	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) = 10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
BLE 1M	62.40	2.05	2.56	3.00
BLE 2M	33.60	4.74	4.76	5.00



BLE 1M 2402MHz



BLE 2M 2402MHz

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC),

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup




Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 16 / 62
Rev: 00

4.1.4 Test Result

Project No : TM-2606000431P
Operation Band : BLE
Test Chamber : Conduction
Probe : Line
Note :

Test Date : 2026-07-08
Temp./Humi. : 25°C / 65%
Engineer : Ben.Yang
Test Voltage : AC 120V/60Hz



Trace:						
Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.155	48.19	0.11	48.30	65.74	-17.44	QP
0.155	31.86	0.11	31.97	55.74	-23.77	Average
0.219	38.22	0.09	38.31	62.84	-24.53	QP
0.219	22.24	0.09	22.33	52.84	-30.51	Average
0.595	40.36	0.08	40.44	56.00	-15.56	QP
0.595	33.87	0.08	33.95	46.00	-12.05	Average
9.808	46.74	0.25	46.99	60.00	-13.01	QP
9.808	40.81	0.25	41.06	50.00	-8.94	Average
10.631	42.22	0.26	42.48	60.00	-17.52	QP
10.631	35.55	0.26	35.81	50.00	-14.19	Average
22.737	47.87	0.40	48.27	60.00	-11.73	QP
22.737	43.08	0.40	43.48	50.00	-6.52	Average

Note: 1. Actual FS= Spectrum Read Level + Factor


Note: 2. Margin= Actual FS - Limit

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 17 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE
Test Chamber : Conduction
Probe : Neutral
Note :

Test Date : 2026-07-08
Temp./Humi. : 25°C / 65%
Engineer : Ben.Yang
Test Voltage : AC 120V/60Hz



Trace:						
Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.159	47.15	0.12	47.27	65.50	-18.23	QP
0.159	29.42	0.12	29.54	55.50	-25.96	Average
0.217	38.01	0.11	38.12	62.95	-24.83	QP
0.217	22.02	0.11	22.13	52.95	-30.82	Average
0.602	41.26	0.10	41.36	56.00	-14.64	QP
0.602	34.76	0.10	34.86	46.00	-11.14	Average
2.093	28.32	0.14	28.46	56.00	-27.54	QP
2.093	20.58	0.14	20.72	46.00	-25.28	Average
10.012	46.14	0.25	46.39	60.00	-13.61	QP
10.012	39.95	0.25	40.20	50.00	-9.80	Average
22.829	48.43	0.39	48.82	60.00	-11.18	QP
22.829	42.95	0.39	43.34	50.00	-6.66	Average

Note: 1. Actual FS= Spectrum Read Level + Factor


Note: 2. Margin= Actual FS - Limit

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 18 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE
Test Chamber : Conduction
Probe : Line
Note :

Test Date : 2026-07-08
Temp./Humi. : 25°C / 65%
Engineer : Ben.Yang
Test Voltage : AC 230V/60Hz



Trace:						
Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.153	47.95	0.11	48.06	65.82	-17.76	QP
0.153	31.73	0.11	31.84	55.82	-23.98	Average
0.186	42.58	0.10	42.68	64.22	-21.54	QP
0.186	25.91	0.10	26.01	54.22	-28.21	Average
0.589	40.32	0.08	40.40	56.00	-15.60	QP
0.589	34.27	0.08	34.35	46.00	-11.65	Average
1.757	28.78	0.12	28.90	56.00	-27.10	QP
1.757	21.57	0.12	21.69	46.00	-24.31	Average
9.809	46.50	0.25	46.75	60.00	-13.25	QP
9.809	40.27	0.25	40.52	50.00	-9.48	Average
22.789	49.72	0.40	50.12	60.00	-9.88	QP
22.789	45.70	0.40	46.10	50.00	-3.90	Average

Note: 1. Actual FS= Spectrum Read Level + Factor


Note: 2. Margin= Actual FS - Limit

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 19 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE
Test Chamber : Conduction
Probe : Neutral
Note :

Test Date : 2026-07-08
Temp./Humi. : 25°C / 65%
Engineer : Ben.Yang
Test Voltage : AC 230V/60Hz



Trace:						
Freq	Read Level	Factor	Actual FS	Limit	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV	dBuV	dB	PK/QP/AV
0.153	47.83	0.12	47.95	65.82	-17.87	QP
0.153	31.06	0.12	31.18	55.82	-24.64	Average
0.168	43.32	0.12	43.44	65.04	-21.60	QP
0.168	25.25	0.12	25.37	55.04	-29.67	Average
0.603	41.05	0.10	41.15	56.00	-14.85	QP
0.603	34.48	0.10	34.58	46.00	-11.42	Average
1.906	28.12	0.14	28.26	56.00	-27.74	QP
1.906	20.09	0.14	20.23	46.00	-25.77	Average
9.942	46.65	0.25	46.90	60.00	-13.10	QP
9.942	40.19	0.25	40.44	50.00	-9.56	Average
22.821	48.66	0.39	49.05	60.00	-10.95	QP
22.821	42.67	0.39	43.06	50.00	-6.94	Average

Note: 1. Actual FS= Spectrum Read Level + Factor

Note: 2. Margin= Actual FS - Limit

4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH(99%)

4.2.1 Test Limit

According to §15.247(a)(2) and RSS-247 section 6.3.1 (a),

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

FCC:

Test method Refer as KDB 558074 D01 and ANSI C63.10-2020,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. In the test report.

IC:

Test method Refer as KDB 558074 D01 and ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth and 6 dB Bandwidth.
4. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. In the test report.

4.2.3 Test Setup

Refer to section 1.8.

4.2.4 Test Result

Temperature: 23.6°C
Humidity: 55% RH

Test date: July 13, 2026
Tested by: Jerry Chang

6dB BANDWIDTH

BLE 1M mode

Frequency (MHz)	6dB BW (MHz)	Required BW (MHz)	Result
2402	0.7195	≥ 0.5	PASS
2442	0.7167	≥ 0.5	PASS
2480	0.7096	≥ 0.5	PASS

BLE 2M mode

Frequency (MHz)	6dB BW (MHz)	Required BW (MHz)	Result
2402	1.095	≥ 0.5	PASS
2442	1.095	≥ 0.5	PASS
2480	1.093	≥ 0.5	PASS

BANDWIDTH 99%

BLE 1M mode

Frequency (MHz)	99%Bandwidth (MHz)
2402	1.0291
2442	1.0294
2480	1.0190

BLE 2M mode


Frequency (MHz)	99%Bandwidth (MHz)
2402	2.0666
2442	2.0709
2480	2.0732

Test Data

6dB BANDWIDTH



OBW 6dB BLE 1M 2402MHz



OBW 6dB BLE 1M 2442MHz




OBW 6dB BLE 1M 2480MHz



OBW 6dB BLE 2M 2402MHz



OBW 6dB BLE 2M 2442MHz



OBW 6dB BLE 2M 2480MHz

BANDWIDTH 99%



OBW 99% BLE 1M 2402MHz



OBW 99% BLE 1M 2442MHz



OBW 99% BLE 1M 2480MHz



OBW 99% BLE 2M 2402MHz



OBW 99% BLE 2M 2442MHz



OBW 99% BLE 2M 2480MHz

4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b)(3) and RSS-247 section 6.3.2,

Peak output power :

FCC

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

IC

For DTS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W, and the e.i.r.p. shall not exceed 4 W, except as provided in section 6.5 a) and b).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power.

Limit	☒ Antenna not exceed 6 dBi : 30dBm ☐ Antenna with DG greater than 6 dBi [Limit = 30 – (DG – 6)] ☐ Point-to-point operation
-------	---

Average output power : For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as KDB 558074 D01

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup

Refer to section 1.8.

4.3.4 Test Result

Temperature: 23.6°C

Test date: July 13, 2026

Humidity: 55% RH

Tested by: Jerry Chang

Peak & Average output power :

BLE 1M mode:

CH	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	Required Limit (dBm)
0	2402	10	7.40	30
20	2442	10	7.30	30
39	2480	10	7.25	30
CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Required Limit (dBm)
0	2402	10	7.34	30
20	2442	10	7.24	30
39	2480	10	7.19	30

***Note:**

1.Measured by power meter, path loss 0.94 dB + Duty cycle factor has been offseted to the power meter for Avg. power and path loss has been offseted for Peak power measurement.

BLE 2M mode:

CH	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	Required Limit (dBm)
0	2402	10	7.40	30
20	2442	10	7.30	30
39	2480	10	7.25	30
CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Required Limit (dBm)
0	2402	10	7.24	30
20	2442	10	7.15	30
39	2480	10	7.09	30

***Note:**

1.Measured by power meter, path loss 0.94 dB + Duty cycle factor has been offseted to the power meter for Avg. power and path loss has been offseted for Peak power measurement.

EIRP Power:

EIRP BLE 1M mode

CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit
0	2402	10	7.34	3.90	11.24	4W= 36 dBm
20	2442	10	7.24	3.90	11.14	4W= 36 dBm
39	2480	10	7.19	3.90	11.09	4W= 36 dBm

* **Note:** EIRP = Average Power + Gain

EIRP BLE 2M mode

CH	Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit
0	2402	10	7.24	3.90	11.14	4W= 36 dBm
20	2442	10	7.15	3.90	11.05	4W= 36 dBm
39	2480	10	7.09	3.90	10.99	4W= 36 dBm

* **Note:** EIRP = Average Power + Gain

4.4 POWER SPECTRAL DENSITY

4.4.1 Test Limit

According to §15.247(e) and RSS-247 section 6.3.1 (b),

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	☒ Antenna not exceed 6 dBi : 8dBm ☐ Antenna with DG greater than 6 dBi [Limit = 8 – (DG – 6)] ☐ Point-to-point operation :
-------	---

4.4.2 Test Procedure

Test method Refer as KDB 558074 D01

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss was compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

4.4.3 Test Setup

Refer to section 1.8.

4.4.4 Test Result

Temperature: 23.6°C
Humidity: 55% RH

Test date: July 13, 2026
Tested by: Jerry Chang

BLE 1M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-6.62	8	PASS
2442	-6.68	8	PASS
2480	-6.62	8	PASS

***Note:**

1.path loss as 0.94 dB that offsets in the spectrum


BLE 2M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-8.26	8	PASS
2442	-8.36	8	PASS
2480	-8.39	8	PASS

***Note:**

1.path loss as 0.94 dB that offsets in the spectrum

Test Data



4.5 CONDUCTED BAND EDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d) and RSS-247 section 6.6,

FCC: In any 100 kHz bandwidth outside the authorized frequency band, Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

IC: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement – provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

4.5.2 Test Procedure

Test method Refer as KDB 558074 D01

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup

Refer to section 1.8.

4.5.4 Test Result


Temperature: 23.6°C

Test date: July 13, 2026

Humidity: 55% RH

Tested by: Jerry Chang

Test Data Reference Level




Reference Level BLE 1M 2402MHz



Reference Level BLE 1M 2442MHz




Reference Level BLE 1M 2480MHz



Reference Level BLE 2M 2402MHz





Reference Level BLE 2M 2442MHz



Reference Level BLE 2M 2480MHz

Band Edge



Spurious Emission



4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

IC according to RSS-Gen, Section 8.9 and 8.10

RSS-Gen Table 3 and Table 5 – General Field Strength Limits for Transmitters and Receivers at Frequencies Above 30 MHz ^(Note)

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Note: Measurements for compliance with the limits in table 3 may be performed at distances other than 3 metres, in accordance with Section 6.6.

RSS-Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)

Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement Distance (m)
9-490 kHz ^{Note}	6.37/F (F in kHz)	300
490-1,705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

4.6.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC), and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9KHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

4. No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz).

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-ane choic chamber, the measurements correspond to those obtained at an open-field test site. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

5. The SA setting following :

(1) Below 30MHz :

(1.1) 9KHz-490KHz : RBW=200Hz / VBW=1kHz / Sweep=AUTO

(1.2) 490KHz-30MHz : RBW=10kHz / VBW=30kHz / Sweep=AUTO

(2) 30MHz to 1GHz : RBW = 100kHz, VBW $\geq 3 \times$ RBW, Sweep = Auto,

Detector = Peak, Trace = Max hold.

(3) Above 1GHz :

(3.1) For Peak measurement : RBW = 1MHz, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(3.2) For Average measurement : RBW = 1MHz, VBW

·If Duty Cycle $\geq 98\%$, VBW=10Hz.

·If Duty Cycle $< 98\%$, VBW=1/T.


6. Data result :

Actual FS=Spectrum Reading Level + Factor


Margin=Actual FS- Limit

4.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz



Above 1 GHz




4.6.4 Test Result

Band Edge Test Data

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : Vertical
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2381.94	33.51	6.20	39.71	54.00	-14.29	Average
2382.44	47.62	6.20	53.82	74.00	-20.18	Peak
2402.00	96.81	6.11	102.92	--	--	Peak
2402.00	96.29	6.11	102.40	--	--	Average
2490.35	43.02	6.56	49.58	74.00	-24.42	Peak
2496.84	33.02	6.57	39.59	54.00	-14.41	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 42 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2381.44	34.22	6.20	40.42	54.00	-13.58	Average
2381.94	49.68	6.20	55.88	74.00	-18.12	Peak
2402.00	98.15	6.11	104.26	--	--	Peak
2402.00	97.60	6.11	103.71	--	--	Average
2493.35	43.30	6.56	49.86	74.00	-24.14	Peak
2496.84	33.17	6.57	39.74	54.00	-14.26	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 43 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2339.48	33.00	6.28	39.28	54.00	-14.72	Average
2347.97	43.76	6.22	49.98	74.00	-24.02	Peak
2480.00	98.43	6.44	104.87	--	--	Peak
2480.00	97.73	6.44	104.17	--	--	Average
2483.85	41.69	6.49	48.18	54.00	-5.82	Average
2489.85	53.59	6.56	60.15	74.00	-13.85	Peak

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 44 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2327.99	33.18	6.18	39.36	54.00	-14.64	Average
2337.98	43.14	6.27	49.41	74.00	-24.59	Peak
2480.00	96.09	6.44	102.53	--	--	Peak
2480.00	95.54	6.44	101.98	--	--	Average
2483.85	39.88	6.49	46.37	54.00	-7.63	Average
2489.85	51.69	6.56	58.25	74.00	-15.75	Peak

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 45 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2381.44	33.43	6.20	39.63	54.00	-14.37	Average
2381.94	47.63	6.20	53.83	74.00	-20.17	Peak
2402.00	96.59	6.11	102.70	--	--	Peak
2402.00	94.27	6.11	100.38	--	--	Average
2493.84	42.80	6.56	49.36	74.00	-24.64	Peak
2497.84	32.74	6.57	39.31	54.00	-14.69	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 46 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2381.94	49.21	6.20	55.41	74.00	-18.59	Peak
2381.94	33.68	6.20	39.88	54.00	-14.12	Average
2402.00	97.89	6.11	104.00	--	--	Peak
2402.00	95.59	6.11	101.70	--	--	Average
2492.85	42.65	6.56	49.21	74.00	-24.79	Peak
2497.84	32.88	6.57	39.45	54.00	-14.55	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 47 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2312.00	32.90	6.24	39.14	54.00	-14.86	Average
2362.96	43.66	6.13	49.79	74.00	-24.21	Peak
2480.00	98.11	6.44	104.55	--	--	Peak
2480.00	95.77	6.44	102.21	--	--	Average
2483.85	53.72	6.49	60.21	74.00	-13.79	Peak
2483.85	44.03	6.49	50.52	54.00	-3.48	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 48 / 62
Rev: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A



Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
2311.00	43.03	6.24	49.27	74.00	-24.73	Peak
2314.50	32.83	6.22	39.05	54.00	-14.95	Average
2480.00	95.66	6.44	102.10	--	--	Peak
2480.00	93.31	6.44	99.75	--	--	Average
2483.85	51.49	6.49	57.98	74.00	-16.02	Peak
2483.85	42.54	6.49	49.03	54.00	-4.97	Average


Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 49 / 62
Rev.: 00

TX Test Data

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : E2
Setting :

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
38.49	46.88	-9.10	37.78	40.00	-2.22	Peak
189.69	52.98	-11.76	41.22	43.50	-2.28	Peak
316.03	46.37	-8.98	37.39	46.00	-8.61	Peak
365.50	45.02	-7.64	37.38	46.00	-8.62	Peak
695.42	37.08	-1.18	35.90	46.00	-10.10	Peak
757.86	40.80	-0.31	40.49	46.00	-5.51	Peak

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 50 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : E2
Setting :

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
189.57	50.94	-11.79	39.15	43.50	-4.35	Peak
264.01	44.92	-10.12	34.80	46.00	-11.20	Peak
315.91	51.11	-8.98	42.13	46.00	-3.87	Peak
694.94	41.94	-1.19	40.75	46.00	-5.25	Peak
758.59	41.62	-0.30	41.32	46.00	-4.68	Peak
821.16	34.75	0.93	35.68	46.00	-10.32	Peak

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 51 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	49.48	2.34	51.82	74.00	-22.18	Peak
4804.00	46.28	2.34	48.62	54.00	-5.38	Average
7206.00	33.45	9.08	42.53	74.00	-31.47	Peak
7206.00	28.42	9.08	37.50	54.00	-16.50	Average
17685.00	34.78	25.76	60.54	74.00	-13.46	Peak
17685.00	24.09	25.76	49.85	54.00	-4.15	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 52 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	47.83	2.34	50.17	74.00	-23.83	Peak
4804.00	42.76	2.34	45.10	54.00	-8.90	Average
7206.00	34.62	9.08	43.70	74.00	-30.30	Peak
7206.00	26.77	9.08	35.85	54.00	-18.15	Average
17694.00	33.37	25.90	59.27	74.00	-14.73	Peak
17694.00	24.19	25.90	50.09	54.00	-3.91	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 53 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	50.74	2.57	53.31	74.00	-20.69	Peak
4884.00	48.95	2.57	51.52	54.00	-2.48	Average
7326.00	34.37	9.11	43.48	74.00	-30.52	Peak
7326.00	28.60	9.11	37.71	54.00	-16.29	Average
17837.00	33.61	25.35	58.96	74.00	-15.04	Peak
17837.00	24.27	25.35	49.62	54.00	-4.38	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 54 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	47.18	2.57	49.75	74.00	-24.25	Peak
4884.00	44.97	2.57	47.54	54.00	-6.46	Average
7326.00	34.40	9.11	43.51	74.00	-30.49	Peak
7326.00	27.83	9.11	36.94	54.00	-17.06	Average
17719.00	34.06	25.46	59.52	74.00	-14.48	Peak
17719.00	24.18	25.46	49.64	54.00	-4.36	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 55 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	48.49	3.40	51.89	74.00	-22.11	Peak
4960.00	45.21	3.40	48.61	54.00	-5.39	Average
7440.00	34.82	9.07	43.89	74.00	-30.11	Peak
7440.00	27.68	9.07	36.75	54.00	-17.25	Average
17605.00	33.36	25.43	58.79	74.00	-15.21	Peak
17605.00	24.16	25.43	49.59	54.00	-4.41	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 56 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_1M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	42.76	3.40	46.16	74.00	-27.84	Peak
4960.00	41.23	3.40	44.63	54.00	-9.37	Average
7440.00	33.84	9.07	42.91	74.00	-31.09	Peak
7440.00	24.24	9.07	33.31	54.00	-20.69	Average
17683.00	33.00	25.73	58.73	74.00	-15.27	Peak
17683.00	24.06	25.73	49.79	54.00	-4.21	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 57 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	48.34	2.34	50.68	74.00	-23.32	Peak
4804.00	42.39	2.34	44.73	54.00	-9.27	Average
7206.00	32.47	9.08	41.55	74.00	-32.45	Peak
7206.00	28.19	9.08	37.27	54.00	-16.73	Average
17781.00	33.92	25.19	59.11	74.00	-14.89	Peak
17781.00	24.19	25.19	49.38	54.00	-4.62	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 58 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2402 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4804.00	44.67	2.34	47.01	74.00	-26.99	Peak
4804.00	40.26	2.34	42.60	54.00	-11.40	Average
7206.00	33.68	9.08	42.76	74.00	-31.24	Peak
7206.00	27.65	9.08	36.73	54.00	-17.27	Average
17601.00	34.35	25.45	59.80	74.00	-14.20	Peak
17601.00	24.13	25.45	49.58	54.00	-4.42	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 59 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	51.77	2.57	54.34	74.00	-19.66	Peak
4884.00	45.61	2.57	48.18	54.00	-5.82	Average
7326.00	34.29	9.11	43.40	74.00	-30.60	Peak
7326.00	27.35	9.11	36.46	54.00	-17.54	Average
17596.00	33.64	25.43	59.07	74.00	-14.93	Peak
17596.00	24.01	25.43	49.44	54.00	-4.56	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 60 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2442 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4884.00	44.90	2.57	47.47	74.00	-26.53	Peak
4884.00	42.08	2.57	44.65	54.00	-9.35	Average
7326.00	34.22	9.11	43.33	74.00	-30.67	Peak
7326.00	26.18	9.11	35.29	54.00	-18.71	Average
17461.00	34.17	25.25	59.42	74.00	-14.58	Peak
17461.00	24.07	25.25	49.32	54.00	-4.68	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 61 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	47.74	3.40	51.14	74.00	-22.86	Peak
4960.00	41.99	3.40	45.39	54.00	-8.61	Average
7440.00	34.08	9.07	43.15	74.00	-30.85	Peak
7440.00	28.53	9.07	37.60	54.00	-16.40	Average
17691.00	33.19	25.84	59.03	74.00	-14.97	Peak
17691.00	24.16	25.84	50.00	54.00	-4.00	Average

Project No: TM-2606000431P
Report No.: TMWK2606003010KR

Page: 62 / 62
Rev.: 00

Project No : TM-2606000431P
Operation Band : BLE_2M
Frequency : 2480 MHz
Operation Mode : TX
EUT Pol : E2
Setting : 10

Test Date : 2026-07-08
Temp./Humi. : 25.7/52
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A



Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4960.00	43.35	3.40	46.75	74.00	-27.25	Peak
4960.00	40.06	3.40	43.46	54.00	-10.54	Average
7440.00	34.75	9.07	43.82	74.00	-30.18	Peak
7440.00	26.20	9.07	35.27	54.00	-18.73	Average
17699.00	34.15	25.97	60.12	74.00	-13.88	Peak
17699.00	24.26	25.97	50.23	54.00	-3.77	Average

- End of Test Report -