

Project No: TM-2508000452P  
Report No.: TMWK2508003623KS FCC ID: 2AWUU60B5801

Page 1 / 14  
Rev.: 00

# RF Exposure Evaluation Report

**FCC 47 CFR § 2.1091**

for

**Wireless Universal Transmitter Sensor**

**Model Name.: QT11-W-HW**

Prepared for:

**Verkada Inc  
405 E. 4th Ave., San Mateo, California, United States, 94401**

Prepared by

**Compliance Certification Services Inc.  
Wugu Laboratory  
No.11, Wugong 6th Rd., Wugu Dist.,  
New Taipei City, Taiwan.  
Issue Date: October 9, 2025**

**Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.**

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 2 / 14  
Rev.: 00

Revision History

| Rev. | Issue Date      | Revisions     | Effect Page | Revised By |
|------|-----------------|---------------|-------------|------------|
| 00   | October 9, 2025 | Initial Issue | ALL         | Peggy Tsai |



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 3 / 14  
Rev.: 00

Table of Contents

1 ATTESTATION OF TEST RESULTS ..... 4

2 ACCREDITATION ..... 5

3 TEST SPECIFICATION, METHODS AND PROCEDURES ..... 6

4 DEVICE UNDER TEST (DUT) INFORMATION ..... 7

    4.1 DUT DESCRIPTION ..... 7

    4.2 WIRELESS TECHNOLOGIES ..... 8

5 MEASUREMENT UNCERTAINTY..... 9

6 MAXIMUM PERMISSIBLE EXPOSURE..... 10

    6.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) ..... 10

    6.2 MPE CALCULATION METHOD..... 11

    6.3 MPE EXEMPTION ..... 12

    6.4 MULTIPLE RF SOURCES ..... 13

7 MPE EXEMPTION OPTION B ..... 14



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 4 / 14  
Rev.: 00

1 Attestation of Test Results

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Applicant Name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Verkada Inc                                                                                               |
| Model Name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | QT11-W-HW                                                                                                 |
| Applicable Standards                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | FCC 47 CFR § 2.1091<br>FCC 47 CFR § 1.1307<br>FCC 47 CFR § 1.1310<br>Published RF exposure KDB procedures |
| Receive EUT Date:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | August 27, 2025                                                                                           |
| Date of Test:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | September 25, 2025                                                                                        |
| Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report. |                                                                                                           |
| Approved & Released By:<br>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Tested by:<br>        |
| Sky Zhou<br>Asst. Section Manager<br>Compliance Certification Services Inc.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | KW Huang<br>Engineer<br>Compliance Certification Services Inc.                                            |



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 5 / 14  
Rev.: 00

## 2 Accreditation

|                          |                                                             |
|--------------------------|-------------------------------------------------------------|
| Test Laboratory Name:    | Compliance Certification Services Inc. Wugu Laboratory      |
| Test Laboratory Address: | No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. |
| FCC Registration No. :   | 444940                                                      |
| MRA:                     | APEC TEL                                                    |



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 6 / 14  
Rev.: 00

### **3 Test Specification, Methods and Procedures**

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 7 / 14  
Rev.: 00

## 4 Device Under Test (DUT) Information

### 4.1 DUT Description

|                   |                                       |
|-------------------|---------------------------------------|
| Product           | Wireless Universal Transmitter Sensor |
| Trade Name        | Verkada                               |
| Model No.         | QT11-W-HW                             |
| Model Discrepancy | N/A                                   |
| Hardware Version  | Rev.0                                 |
| Software Version  | Rev.0                                 |
| Sample Stage      | Identical prototype                   |

## 4.2 Wireless Technologies

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |              |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|--------------|
| <b>Frequency bands</b>         | <input type="checkbox"/> Bluetooth: 2402MHz-2480MHz<br><input type="checkbox"/> 802.11b/g/n HT20: 2412MHz ~ 2462 MHz<br><input type="checkbox"/> 802.11n HT40: 2422MHz ~ 2452 MHz<br><input type="checkbox"/> 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz<br><input type="checkbox"/> 802.11n HT40: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795MHz<br><input type="checkbox"/> 802.11ac VHT20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz<br><input type="checkbox"/> 802.11ac VHT40: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795MHz<br><input type="checkbox"/> 802.11ac VHT80: 5210 MHz / 5290 MHz / 5530 MHz / 5775 MHz<br><input checked="" type="checkbox"/> Others: 915.0 MHz ~ 915.7 MHz |              |           |              |
| <b>Exposure classification</b> | <input type="checkbox"/> Occupational/Controlled exposure<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |              |           |              |
| <b>Antenna Specification</b>   | <p><b>Type:</b> PCB Antenna<br/> <b>Model:</b> Pippin<br/> <b>Manufacturer:</b> N/A<br/> <b>Gain:</b> 2.0 dBi</p> <p>Gain :      2.00 dBi    (Numeric gain: 1.58)      Worst</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |              |           |              |
| <b>Maximum tune up power</b>   | <table border="1"> <tr> <td>915MHz:</td> <td>20.00 dBm</td> <td>(100.000 mW)</td> </tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 915MHz:      | 20.00 dBm | (100.000 mW) |
| 915MHz:                        | 20.00 dBm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (100.000 mW) |           |              |

### Notes:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
- The tune up power referred the AVG power of the test report TMTN2508000940NR for RF Exposure assessment purpose.



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 9 / 14  
Rev.: 00

## 5 Measurement Uncertainty

| PARAMETER                                    | UNCERTAINTY  |
|----------------------------------------------|--------------|
| AC Powerline Conducted Emission              | +/- 2.21 dB  |
| Channel Bandwidth                            | +/- 2.87 %   |
| RF output power (Spectrum)                   | +/- 2.88 dB  |
| RF output power (Power Meter & Power sensor) | +/- 0.243 dB |
| Power Density                                | +/- 2.87 dB  |
| Conducted Bandedge                           | +/- 2.87 dB  |
| Conducted Spurious Emission                  | +/- 2.88 dB  |
| Channel Separation                           | +/- 2.87 dB  |
| In-Band Emission (Channel Mask)              | +/- 2.88 dB  |
| Frequency Stability                          | +/- 0.03 ppm |



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 10 / 14  
Rev.: 00

## 6 Maximum Permissible Exposure

### 6.1 Limits for Maximum Permissible Exposure (MPE)

**Table 1 - Limits for Maximum Permissible Exposure (MPE)**

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure         |                               |                               |                                     |                          |
| 0.3-3.0                                                 | 614                           | 1.63                          | * 100                               | 6                        |
| 3.0-30                                                  | 1842/f                        | 4.89/f                        | * 900/f <sup>2</sup>                | 6                        |
| 30-300                                                  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500                                               |                               |                               | f/300                               | 6                        |
| 1,500-100,000                                           |                               |                               | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3-1.34                                                | 614                           | 1.63                          | * 100                               | 30                       |
| 1.34-30                                                 | 824/f                         | 2.19/f                        | * 180/f <sup>2</sup>                | 30                       |
| 30-300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500                                               |                               |                               | f/1500                              | 30                       |
| <b><u>1,500-100,000</u></b>                             |                               |                               | 1.0                                 | 30                       |

## 6.2 MPE Calculation Method

### Calculation

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm<sup>2</sup>

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

### 6.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

| Single RF Sources Subject to Routine Environmental Evaluation |                       |
|---------------------------------------------------------------|-----------------------|
| RF Source frequency (MHz)                                     | Threshold ERP (watts) |
| 0.3-1.34                                                      | $1,920 R^2$ .         |
| 1.34-30                                                       | $3,450 R^2/f^2$ .     |
| 30-300                                                        | $3.83 R^2$ .          |
| 300-1,500                                                     | $0.0128 R^2 f$ .      |
| 1,500-100,000                                                 | $19.2 R^2$ .          |
| Note: R is in meters, f is in MHz.                            |                       |

#### 6.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



Project No: TM-2508000452P  
Report No.: TMWK2508003623KS

Page 14 / 14  
Rev.: 00

7 MPE Exemption Option B

| Frequency (MHz) | R(m) | Max Tune-up power (dBm) | G(dBi) | Max Tune-up EIRP (dBm) | Max Tune-up ERP (dBm) | Max Tune-up ERP (mW) | ERP Threshold (mW) | MPE Exemption |
|-----------------|------|-------------------------|--------|------------------------|-----------------------|----------------------|--------------------|---------------|
| 915             | 0.2  | 20.0                    | 2.00   | 22.00                  | 19.85                 | 96.605               | 1867               | Complies      |

END OF REPORT