



Project No: TM-2412000476P
Report No.: TMWK2501000094KS

FCC ID: 2AWUU68B2701

Page 1 / 16
Rev.: 00

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for
Outdoor Wi-Fi Gateway

Model: GW31-E-HW

Prepared for:

Verkada Inc

405 E. 4th Ave. San Mateo California United States 94401

Prepared by

Compliance Certification Services Inc.

Wugu Laboratory

No.11, Wugong 6th Rd., Wugu Dist.,

New Taipei City, Taiwan

Issued Date: February 26, 2025

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No: TM-2412000476P
Report No.: TMWK2501000094KS

Page 2 / 16
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	February 26, 2025	Initial Issue	ALL	Peggy Tsai

Table of Contents

1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES	5
3	DEVICE UNDER TEST (DUT) INFORMATION	6
3.1	DUT DESCRIPTION	6
3.2	WIRELESS TECHNOLOGIES	7
4	MAXIMUM PERMISSIBLE EXPOSURE	10
4.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
4.2	MPE CALCULATION METHOD	11
4.3	MPE EXEMPTION	12
4.4	MULTIPLE RF SOURCES	13
5	MPE EXEMPTION OPTION B	14
6	SIMULTANEOUS TRANSMISSION ANALYSIS	15
6.1	SUM OF THE WIFI 2.4GHZ + BLUETOOTH	15
6.2	SUM OF THE WIFI 5GHZ + BLUETOOTH	15
7	FACILITIES	16



Project No: TM-2412000476P
Report No.: TMWK2501000094KS

Page 4 / 16
Rev.: 00

1 Attestation of Test Results

Applicant	Verkada Inc 405 E. 4th Ave. San Mateo California United States 94401
Manufacturer	Verkada Inc 405 E. 4th Ave. San Mateo California United States 94401
Model Name	GW31-E-HW
Applicable Standards	FCC 47 CFR § 2.1091 FCC 47 CFR § 1.1307 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures
Receive EUT Date:	January 2, 2025
Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.	
Approved & Released By: 	
Sky Zhou Asst. Section Manager	

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Project No: TM-2412000476P
Report No.: TMWK2501000094KS

Page 6 / 16
Rev.: 00

3 Device Under Test (DUT) Information

3.1 DUT Description

Product	Outdoor Wi-Fi Gateway
Trade Name	Verkada
Model No.	GW31-E-HW
Model Discrepancy	N/A
EUT Serial #	68B2701-DVT01
Software Version	0.1
Hardware Version	0.1
Sample Stage	Identical prototype

3.2 Wireless Technologies

Frequency bands	☒ Bluetooth: 2402MHz-2480MHz ☒ 802.11b/g/n HT20/ac VHT20/ax HE20: 2412MHz ~ 2462 MHz ☒ 802.11n HT40/ac VHT40/ax HE40: 2422MHz ~ 2452MHz ☒ 802.11a/n HT20: 5180MHz ~ 5240MHz / 5745MHz ~ 5825MHz ☒ 802.11ac VHT20: 5180MHz ~ 5240MHz / 5745MHz ~ 5825MHz ☒ 802.11ax HE20: 5180MHz ~ 5240MHz / 5745MHz ~ 5825MHz ☒ 802.11n HT40: 5190MHz ~ 5230MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT40: 5190MHz ~ 5230MHz / 5755MHz ~ 5795MHz ☒ 802.11ax HE40: 5190MHz ~ 5230MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT80: 5210MHz / 5775MHz ☒ 802.11ax HE80: 5210MHz / 5775MHz ☐ Others:
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure

Antenna Specification

Type: Dipole Antenna
Brand / Model: Senao / 7102A1338000

Bluetooth: Gain: 2.38 dBi

WIFI 2.4G:

Ant 1: Gain: 2.79 dBi

Ant 2: Gain: 2.38 dBi

Direction gain: Gain: 5.6 dBi

WIFI 5G:

Band1:

Ant 1: Gain: 5.07 dBi

Ant 2: Gain: 4.96 dBi

Direction gain: Gain: 8.03 dBi

Band4:

Ant 1: Gain: 4.85 dBi

Ant 2: Gain: 5.03 dBi

Direction gain: Gain: 7.95 dBi

Bluetooth:	Antenna Gain :	2.38 dBi	(Numeric gain: 1.73)	Worst
2.4GHz:				
Ant 1:	Antenna Gain:	2.79 dBi	(Numeric gain: 1.90)	Worst
Ant 2:	Antenna Gain:	2.38 dBi	(Numeric gain: 1.73)	Worst
Direction gain:	Antenna Gain:	5.60 dBi	(Numeric gain: 3.63)	Worst
5GHz(Band 1):				
Ant 1:	Antenna Gain:	5.07 dBi	(Numeric gain: 3.21)	Worst
Ant 2:	Antenna Gain:	4.96 dBi	(Numeric gain: 3.13)	Worst
Direction gain:	Antenna Gain:	8.03 dBi	(Numeric gain: 6.35)	Worst
5GHz(Band 4):				
Ant 1:	Antenna Gain:	4.85 dBi	(Numeric gain: 3.05)	Worst
Ant 2:	Antenna Gain:	5.03 dBi	(Numeric gain: 3.18)	Worst
Direction gain:	Antenna Gain:	7.95 dBi	(Numeric gain: 6.24)	Worst

**Maximum
Tune up
power**

BLE	5.00 dBm	(3.16 mW)
2.4GHz		
IEEE 802.11b_Ch0	24.50 dBm	(281.838 mW)
IEEE 802.11b_Ch1	25.50 dBm	(354.813 mW)
IEEE 802.11g_Ch0	19.50 dBm	(89.13 mW)
IEEE 802.11g_Ch1	19.50 dBm	(89.13 mW)
IEEE 802.11n HT 20 (MIMO)	21.00 dBm	(125.89 mW)
IEEE 802.11n HT 40 (MIMO)	18.00 dBm	(63.10 mW)
IEEE 802.11ac VHT 20 (MIMO)	21.00 dBm	(125.89 mW)
IEEE 802.11ac VHT 40 (MIMO)	18.00 dBm	(63.10 mW)
IEEE 802.11ax HE 20 (MIMO)	20.00 dBm	(100.00 mW)
IEEE 802.11ax HE 40 (MIMO)	18.00 dBm	(63.10 mW)
5GHz (U-NII-1)		
IEEE 802.11a_Ch0	26.00 dBm	(398.107 mW)
IEEE 802.11a_Ch1	26.00 dBm	(398.107 mW)
IEEE 802.11n HT 20 (MIMO)	26.00 dBm	(398.11 mW)
IEEE 802.11n HT 40 (MIMO)	20.50 dBm	(112.20 mW)
IEEE 802.11ac VHT 20 (MIMO)	26.00 dBm	(398.11 mW)
IEEE 802.11ac VHT 40 (MIMO)	20.50 dBm	(112.20 mW)
IEEE 802.11ac VHT 80 (MIMO)	20.50 dBm	(112.20 mW)
IEEE 802.11ax HE 20 (MIMO)	25.50 dBm	(354.81 mW)
IEEE 802.11ax HE 40 (MIMO)	20.50 dBm	(112.20 mW)
IEEE 802.11ax HE 80 (MIMO)	20.00 dBm	(100.00 mW)
5GHz (U-NII-3)		
IEEE 802.11a_Ch0	26.00 dBm	(398.11 mW)
IEEE 802.11a_Ch1	25.50 dBm	(354.81 mW)
IEEE 802.11n HT20 (MIMO)	27.00 dBm	(501.19 mW)
IEEE 802.11n HT40 (MIMO)	27.50 dBm	(562.34 mW)
IEEE 802.11ac VHT20 (MIMO)	27.00 dBm	(501.19 mW)
IEEE 802.11ac VHT40 (MIMO)	27.50 dBm	(562.34 mW)
IEEE 802.11ac VHT80 (MIMO)	24.50 dBm	(281.84 mW)
IEEE 802.11ax HE20 (MIMO)	26.50 dBm	(446.68 mW)
IEEE 802.11ax HE40 (MIMO)	27.00 dBm	(501.19 mW)
IEEE 802.11ax HE80 (MIMO)	24.50 dBm	(281.84 mW)

Notes:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. The power referred the Tune up power of the test report TMWK2412004833KR, TMWK2412004834KR and TMWK2412004835KR for RF Exposure assessment purpose.

4 Maximum Permissible Exposure

4.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

4.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

4.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	

4.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



Project No: TM-2412000476P
Report No.: TMWK2501000094KS

Page 14 / 16
Rev.: 00

5 MPE Exemption Option B

BLE

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
BLE	2402	0.2	5.0	2.38	7.38	5.23	3.334	3060	Complies

WIFI 2.4GHz (DTS)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11b_Ch0	2412	0.2	24.5	2.38	26.88	24.73	297.167	3060	Complies
IEEE 802.11b_Ch1	2412	0.2	25.5	2.79	28.29	26.14	411.150	3060	Complies
IEEE 802.11g_Ch0	2412	0.2	19.5	2.38	21.88	19.73	93.972	3060	Complies
IEEE 802.11g_Ch1	2412	0.2	19.5	2.79	22.29	20.14	103.276	3060	Complies
IEEE 802.11n HT 20 (MIMO)	2412	0.2	21.0	5.60	26.60	24.45	278.612	3060	Complies
IEEE 802.11n HT 40 (MIMO)	2422	0.2	18.0	5.60	23.60	21.45	139.637	3060	Complies
IEEE 802.11ac VHT 20 (MIMO)	2412	0.2	21.0	5.60	26.60	24.45	278.612	3060	Complies
IEEE 802.11ac VHT 40 (MIMO)	2422	0.2	18.0	5.60	23.60	21.45	139.637	3060	Complies
IEEE 802.11ax HE 20 (MIMO)	2412	0.2	20.0	5.60	25.60	23.45	221.309	3060	Complies
IEEE 802.11ax HE 40 (MIMO)	2422	0.2	18.0	5.60	23.60	21.45	139.637	3060	Complies

WIFI 5.2GHz (U-NII 1)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a_Ch0	5220	0.2	26.0	5.07	31.07	28.92	779.830	3060	Complies
IEEE 802.11a_Ch1	5220	0.2	26.0	4.96	30.96	28.81	760.326	3060	Complies
IEEE 802.11n HT 20 (MIMO)	5220	0.2	26.0	8.03	34.03	31.88	1541.700	3060	Complies
IEEE 802.11n HT 40 (MIMO)	5190	0.2	20.5	8.03	28.53	26.38	434.510	3060	Complies
IEEE 802.11ac VHT 20 (MIMO)	5220	0.2	26.0	8.03	34.03	31.88	1541.700	3060	Complies
IEEE 802.11ac VHT 40 (MIMO)	5190	0.2	20.5	8.03	28.53	26.38	434.510	3060	Complies
IEEE 802.11ac VHT 80 (MIMO)	5210	0.2	20.5	8.03	28.53	26.38	434.510	3060	Complies
IEEE 802.11ax HE 20 (MIMO)	5220.00	0.2	25.5	8.03	33.53	31.38	1374.042	3060	Complies
IEEE 802.11ax HE 40 (MIMO)	5190.00	0.2	20.5	8.03	28.53	26.38	434.510	3060	Complies
IEEE 802.11ax HE 80 (MIMO)	5210.00	0.2	20.0	8.03	28.03	25.88	387.258	3060	Complies

WIFI 5.8GHz (U-NII 3)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a_Ch0	5745	0.2	26.0	4.85	30.85	28.70	741.310	3060	Complies
IEEE 802.11a_Ch1	5745	0.2	25.5	5.03	30.53	28.38	688.652	3060	Complies
IEEE 802.11n HT20 (MIMO)	5745	0.2	27.0	7.95	34.95	32.80	1905.461	3060	Complies
IEEE 802.11n HT40 (MIMO)	5755	0.2	27.5	7.95	35.45	33.30	2137.962	3060	Complies
IEEE 802.11ac VHT20 (MIMO)	5745	0.2	27.0	7.95	34.95	32.80	1905.461	3060	Complies
IEEE 802.11ac VHT40 (MIMO)	5755	0.2	27.5	7.95	35.45	33.30	2137.962	3060	Complies
IEEE 802.11ac VHT80 (MIMO)	5775	0.2	24.5	7.95	32.45	30.30	1071.519	3060	Complies
IEEE 802.11ax HE20 (MIMO)	5745	0.2	26.5	7.95	34.45	32.30	1698.244	3060	Complies
IEEE 802.11ax HE40 (MIMO)	5755	0.2	27.0	7.95	34.95	32.80	1905.461	3060	Complies
IEEE 802.11ax HE80 (MIMO)	5775	0.2	24.5	7.95	32.45	30.30	1071.519	3060	Complies

6 Simultaneous Transmission Analysis

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

6.1 Sum of the WiFi 2.4GHz + Bluetooth

WiFi 2.4GHz +Bluetooth

Mode	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WiFi 2.4GHz	411.150	3060	0.135	≤ 1
Bluetooth	3.334	3060		

6.2 Sum of the WiFi 5GHz + Bluetooth

WiFi 5GHz + Bluetooth

Mode	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WiFi 5GHz	2137.962	3060	0.700	≤ 1
Bluetooth	3.334	3060		

Project No: TM-2412000476P
Report No.: TMWK2501000094KS

Page 16 / 16
Rev.: 00

7 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

--End of Test Report--