


10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
 - Centre Frequency: The centre frequency of the middle hopping channel.
 - Resolution BW: 10 MHz.
 - Video BW: 10 MHz.
 - Span: Zero span.
 - Detector: Peak.
 - Trace Mode: Clear Write.
 - Sweep: Video Trigger
- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

10.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	23.8-24.5℃,33.8-44.0%RH	Test Date:	2026.01.13-2026.01.20
Test Power Supply:	Battery	Sample Number:	S25111111-062

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
2.4G SRD_1M	Ant1	2402	2.13	2.51	84.86	0.71
	Ant2	2402	2.13	2.51	84.86	0.71
	Ant1	2440	2.13	2.51	84.86	0.71
	Ant2	2440	2.13	2.51	84.86	0.71
	Ant1	2480	2.13	2.51	84.86	0.71
	Ant2	2480	2.13	2.51	84.86	0.71
2.4G SRD_2M	Ant1	2404	1.07	1.25	85.60	0.68
	Ant2	2404	1.07	1.25	85.60	0.68
	Ant1	2440	1.07	1.25	85.60	0.68
	Ant2	2440	1.07	1.25	85.60	0.68
	Ant1	2478	1.07	1.25	85.60	0.68
	Ant2	2478	1.07	1.25	85.60	0.68

10.5. Test graphs









11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

11.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


12. Radiated Emission

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT	
MHz	Meters	uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m(Peak)	
		54.0 dBuV/m(Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\log(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According to ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the Trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.


Test result

PASS. (See below detailed test result)

12.6. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-01-14 **Tested By:** Li Xiongbin
Test Mode: ANT1 2.4G SRD 1M TX Mode **Power Supply:** Battery
Condition: Temp:24.1°C;Humi:42.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\5
Memo: Sample Number:S25111111-059




Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.084	35.69	10.48	3.78	17.65	40.00	22.35	QP	Horizontal
2	35.823	28.53	11.79	3.86	11.88	40.00	28.12	QP	Horizontal
3	53.913	26.12	13.38	4.01	11.21	40.00	28.79	QP	Horizontal
4	97.707	26.42	10.98	4.29	9.39	43.50	34.11	QP	Horizontal
5	111.084	26.25	11.91	4.36	10.21	43.50	33.29	QP	Horizontal
6	887.631	27.61	21.55	7.09	24.28	46.00	21.72	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-01-14**Tested By:** Li Xiongbin**Test Mode:** ANT1 2.4G SRD 1M TX Mode**Power Supply:** Battery**Condition:** Temp:24.1°C;Humi:42.5%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\6**Memo:** Sample Number:S25111111-059**Final Data List**


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.000	32.67	10.50	3.78	14.65	40.00	25.35	QP	Vertical
2	35.974	28.01	11.88	3.86	11.45	40.00	28.55	QP	Vertical
3	54.217	28.02	13.25	4.01	12.98	40.00	27.02	QP	Vertical
4	96.009	28.18	11.19	4.28	11.35	43.50	32.15	QP	Vertical
5	370.256	26.13	15.56	5.58	14.80	46.00	31.20	QP	Vertical
6	898.275	27.03	21.73	7.11	23.96	46.00	22.04	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-01-14 **Tested By:** Li Xiongbin
Test Mode: ANT1 2.4G SRD 2M TX Mode **Power Supply:** Battery
Condition: Temp:24.1°C;Humi:42.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\7
Memo: Sample Number:S25111111-059

**Final Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.042	34.97	10.49	3.78	16.94	40.00	23.06	QP	Horizontal
2	41.303	26.84	12.82	3.93	11.29	40.00	28.71	QP	Horizontal
3	54.065	26.9	13.35	4.01	11.96	40.00	28.04	QP	Horizontal
4	109.230	25.4	12.13	4.35	9.57	43.50	33.93	QP	Horizontal
5	595.612	26.57	19.15	6.38	19.26	46.00	26.74	QP	Horizontal
6	904.595	27.45	22.27	7.12	24.97	46.00	21.03	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 2M TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\8

Memo:

Sample Number:S25111111-059



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.021	32.55	10.50	3.78	14.53	40.00	25.47	QP	Vertical
2	36.025	28.57	11.91	3.86	12.04	40.00	27.96	QP	Vertical
3	55.021	27.84	12.71	4.02	12.27	40.00	27.73	QP	Vertical
4	95.942	26.64	11.14	4.28	9.76	43.50	33.74	QP	Vertical
5	652.912	27.64	19.09	6.52	20.27	46.00	25.73	QP	Vertical
6	906.500	26.87	22.21	7.13	24.35	46.00	21.65	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 1M TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\9

Memo:

Sample Number:S25111111-059



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.169	32.69	10.47	3.78	14.64	40.00	25.36	QP	Horizontal
2	42.897	26.99	13.64	3.94	12.27	40.00	27.73	QP	Horizontal
3	54.636	27.81	12.95	4.02	12.48	40.00	27.52	QP	Horizontal
4	99.504	26.24	11.70	4.30	9.94	43.50	33.56	QP	Horizontal
5	109.691	25.22	11.99	4.36	9.26	43.50	34.24	QP	Horizontal
6	968.940	26.77	22.03	7.28	24.59	54.00	29.41	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 1M TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\10

Memo:

Sample Number:S25111111-059



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.000	32.93	10.50	3.78	14.91	40.00	25.09	QP	Vertical
2	35.949	29.27	11.87	3.86	12.70	40.00	27.30	QP	Vertical
3	44.583	26.6	13.40	3.95	11.65	40.00	28.35	QP	Vertical
4	54.141	28.47	13.30	4.01	13.48	40.00	26.52	QP	Vertical
5	106.507	26.27	10.95	4.34	9.25	43.50	34.25	QP	Vertical
6	984.693	26.38	22.58	7.32	24.89	54.00	29.11	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 2M TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\11

Memo:

Sample Number:S25111111-059



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.317	31.87	10.44	3.78	13.79	40.00	26.21	QP	Horizontal
2	35.899	29.83	11.84	3.86	13.23	40.00	26.77	QP	Horizontal
3	48.293	25.82	13.32	3.97	10.81	40.00	29.19	QP	Horizontal
4	62.030	25.6	12.59	4.08	9.97	40.00	30.03	QP	Horizontal
5	98.325	25.86	11.33	4.29	9.18	43.50	34.32	QP	Horizontal
6	989.538	26.15	22.24	7.33	24.36	54.00	29.64	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbn

Test Mode:

ANT2 2.4G SRD 2M TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Below 1G\12

Memo:

Sample Number:S25111111-059



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.000	32.63	10.50	3.78	14.61	40.00	25.39	QP	Vertical
2	35.974	28.34	11.88	3.86	11.78	40.00	28.22	QP	Vertical
3	53.989	28.08	13.40	4.01	13.19	40.00	26.81	QP	Vertical
4	62.117	26.87	12.58	4.08	11.23	40.00	28.77	QP	Vertical
5	99.504	25.72	11.70	4.30	9.42	43.50	34.08	QP	Vertical
6	952.771	26.8	22.00	7.24	24.46	46.00	21.54	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 1M 2480MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\1

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3789.700	45.84	30.67	4.54	-39.62	41.43	74.00	32.57	PK	Horizontal
2	4377.900	46.31	31.63	4.83	-39.74	43.03	74.00	30.97	PK	Horizontal
3	7465.100	42.82	36.69	5.78	-39.85	45.44	74.00	28.56	PK	Horizontal
4	9051.200	41.72	38.88	6.79	-38.66	48.73	74.00	25.27	PK	Horizontal
5	9919.900	45.90	38.34	6.68	-39.61	51.31	-	-	PK	Horizontal
6	11436.300	41.59	39.44	7.58	-39.60	49.01	74.00	24.99	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 1M 2480MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\2

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3799.900	46.40	30.90	4.54	-39.62	42.22	74.00	31.78	PK	Vertical
2	4554.700	45.58	32.03	4.95	-39.76	42.80	74.00	31.20	PK	Vertical
3	7441.300	45.03	36.62	5.77	-39.86	47.56	74.00	26.44	PK	Vertical
4	9398.000	43.75	38.70	6.75	-39.04	50.16	74.00	23.84	PK	Vertical
5	9918.200	44.69	38.34	6.68	-39.61	50.10	-	-	PK	Vertical
6	10851.500	40.96	39.31	7.30	-39.61	47.96	74.00	26.04	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 1M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\3

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3827.100	46.37	30.57	4.55	-39.63	41.86	74.00	32.14	PK	Horizontal
2	4350.700	46.46	31.31	4.81	-39.74	42.84	74.00	31.16	PK	Horizontal
3	5005.200	44.89	33.01	5.25	-39.80	43.35	74.00	30.65	PK	Horizontal
4	7453.200	43.16	36.62	5.78	-39.85	45.71	74.00	28.29	PK	Horizontal
5	9384.400	41.60	38.73	6.75	-39.02	48.06	74.00	25.94	PK	Horizontal
6	11419.300	41.68	39.61	7.58	-39.60	49.27	74.00	24.73	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 1M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\4

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3820.300	46.41	30.66	4.55	-39.63	41.99	74.00	32.01	PK	Vertical
2	4959.300	44.47	33.08	5.22	-39.80	42.97	74.00	31.03	PK	Vertical
3	7318.900	42.67	37.00	5.73	-39.87	45.53	74.00	28.47	PK	Vertical
4	9187.200	41.94	38.55	6.78	-38.81	48.46	74.00	25.54	PK	Vertical
5	9758.400	45.53	37.98	6.70	-39.43	50.78	-	-	PK	Vertical
6	12298.200	41.42	39.40	7.81	-39.36	49.27	74.00	24.73	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbin

Test Mode:

ANT1 2.4G SRD 1M 2402MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\5

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO .	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3839.000	45.85	30.43	4.55	-39.64	41.19	74.00	32.81	PK	Horizontal
2	4855.600	44.68	32.92	5.15	-39.79	42.96	74.00	31.04	PK	Horizontal
3	7517.800	43.20	36.65	5.80	-39.85	45.80	74.00	28.20	PK	Horizontal
4	9607.100	44.84	38.13	6.72	-39.27	50.42	-	-	PK	Horizontal
5	11429.500	40.66	39.51	7.58	-39.60	48.15	74.00	25.85	PK	Horizontal
6	12340.700	41.02	39.28	7.81	-39.33	48.78	74.00	25.22	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbin

Test Mode:

ANT1 2.4G SRD 1M 2402MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\6

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4073.600	46.18	31.15	4.62	-39.71	42.24	74.00	31.76	PK	Vertical
2	4847.100	44.27	32.85	5.15	-39.78	42.49	74.00	31.51	PK	Vertical
3	7517.800	43.95	36.65	5.80	-39.85	46.55	74.00	27.45	PK	Vertical
4	9044.400	42.99	38.86	6.79	-38.65	49.99	74.00	24.01	PK	Vertical
5	9608.800	44.25	38.14	6.72	-39.27	49.84	-	-	PK	Vertical
6	11410.800	40.63	39.69	7.57	-39.60	48.29	74.00	25.71	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 2M 2404MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\7

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3798.200	46.38	30.86	4.54	-39.62	42.16	74.00	31.84	PK	Horizontal
2	4879.400	44.31	33.02	5.17	-39.79	42.71	74.00	31.29	PK	Horizontal
3	7398.800	43.02	36.71	5.76	-39.86	45.63	74.00	28.37	PK	Horizontal
4	9161.700	41.76	38.86	6.78	-38.78	48.62	74.00	25.38	PK	Horizontal
5	11434.600	42.04	39.45	7.58	-39.60	49.47	74.00	24.53	PK	Horizontal
6	12213.200	41.08	39.23	7.81	-39.43	48.69	74.00	25.31	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 2M 2404MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\8

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3772.700	46.50	30.30	4.54	-39.61	41.73	74.00	32.27	PK	Vertical
2	4872.600	45.06	32.99	5.16	-39.79	43.42	74.00	30.58	PK	Vertical
3	7526.300	42.67	36.53	5.80	-39.85	45.15	74.00	28.85	PK	Vertical
4	9063.100	43.28	38.66	6.79	-38.67	50.06	74.00	23.94	PK	Vertical
5	10686.600	41.72	39.46	7.18	-39.63	48.73	74.00	25.27	PK	Vertical
6	11398.900	40.65	39.79	7.57	-39.60	48.41	74.00	25.59	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbin

Test Mode:

ANT1 2.4G SRD 2M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\9

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3789.700	45.81	30.67	4.54	-39.62	41.40	74.00	32.60	PK	Horizontal
2	5051.100	44.63	33.09	5.27	-39.79	43.20	74.00	30.80	PK	Horizontal
3	7369.900	42.85	36.88	5.75	-39.86	45.62	74.00	28.38	PK	Horizontal
4	9163.400	41.69	38.84	6.78	-38.78	48.53	74.00	25.47	PK	Horizontal
5	10691.700	40.89	39.48	7.18	-39.63	47.92	74.00	26.08	PK	Horizontal
6	11400.600	40.88	39.79	7.57	-39.60	48.64	74.00	25.36	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 2M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\10

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4102.500	46.08	31.12	4.64	-39.71	42.13	74.00	31.87	PK	Vertical
2	4376.200	46.41	31.61	4.83	-39.74	43.11	74.00	30.89	PK	Vertical
3	4869.200	44.65	32.98	5.16	-39.79	43.00	74.00	31.00	PK	Vertical
4	7519.500	43.37	36.63	5.80	-39.85	45.95	74.00	28.05	PK	Vertical
5	11448.200	41.30	39.32	7.59	-39.60	48.61	74.00	25.39	PK	Vertical
6	12301.600	40.93	39.40	7.81	-39.36	48.78	74.00	25.22	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbin

Test Mode:

ANT1 2.4G SRD 2M 2478MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\11

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4376.200	46.82	31.61	4.83	-39.74	43.52	74.00	30.48	PK	Horizontal
2	5059.600	45.15	32.98	5.27	-39.79	43.61	74.00	30.39	PK	Horizontal
3	7327.400	42.90	37.00	5.73	-39.87	45.76	74.00	28.24	PK	Horizontal
4	9379.300	42.44	38.74	6.75	-39.02	48.91	74.00	25.09	PK	Horizontal
5	9909.700	44.38	38.32	6.68	-39.60	49.78	-	-	PK	Horizontal
6	11988.800	41.58	38.94	7.81	-39.60	48.73	74.00	25.27	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-15

Tested By:

Li Xiongbín

Test Mode:

ANT1 2.4G SRD 1M 2478MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\12

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4097.400	47.22	31.11	4.64	-39.71	43.26	74.00	30.74	PK	Vertical
2	5027.300	44.76	33.05	5.26	-39.79	43.28	74.00	30.72	PK	Vertical
3	7432.800	43.81	36.63	5.77	-39.86	46.35	74.00	27.65	PK	Vertical
4	9180.400	41.49	38.64	6.78	-38.80	48.11	74.00	25.89	PK	Vertical
5	9909.700	44.69	38.32	6.68	-39.60	50.09	-	-	PK	Vertical
6	11451.600	42.83	39.28	7.59	-39.60	50.10	74.00	23.90	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbin

Test Mode:

ANT2 2.4G SRD 1M 2402MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\17

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3776.100	48.15	30.37	4.54	-39.61	43.45	74.00	30.55	PK	Horizontal
2	4733.200	45.40	31.90	5.07	-39.77	42.60	74.00	31.40	PK	Horizontal
3	7378.400	43.23	36.83	5.75	-39.86	45.95	74.00	28.05	PK	Horizontal
4	9160.000	41.35	38.88	6.78	-38.78	48.23	74.00	25.77	PK	Horizontal
5	9607.100	56.99	38.13	6.72	-39.27	62.57	-	-	PK	Horizontal
6	11412.500	41.59	39.68	7.58	-39.60	49.25	74.00	24.75	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 1M 2402MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\18

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4381.300	46.05	31.68	4.83	-39.74	42.82	74.00	31.18	PK	Vertical
2	5022.200	44.48	33.04	5.26	-39.80	42.98	74.00	31.02	PK	Vertical
3	7522.900	42.95	36.58	5.80	-39.85	45.48	74.00	28.52	PK	Vertical
4	9122.600	41.93	38.45	6.78	-38.73	48.43	74.00	25.57	PK	Vertical
5	9607.100	57.10	38.13	6.72	-39.27	62.68	-	-	PK	Vertical
6	10679.800	41.46	39.44	7.17	-39.63	48.44	74.00	25.56	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 1M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\19

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4049.800	45.74	31.20	4.60	-39.70	41.84	74.00	32.16	PK	Horizontal
2	4925.300	45.05	33.10	5.20	-39.79	43.56	74.00	30.44	PK	Horizontal
3	7681.000	43.10	36.81	5.86	-39.83	45.94	74.00	28.06	PK	Horizontal
4	9758.400	55.71	37.98	6.70	-39.43	60.96	-	-	PK	Horizontal
5	11419.300	41.08	39.61	7.58	-39.60	48.67	74.00	25.33	PK	Horizontal
6	12225.100	41.46	39.25	7.81	-39.42	49.10	74.00	24.90	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbin

Test Mode:

ANT2 2.4G SRD 1M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\20

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4376.200	46.82	31.61	4.83	-39.74	43.52	74.00	30.48	PK	Vertical
2	4855.600	44.77	32.92	5.15	-39.79	43.05	74.00	30.95	PK	Vertical
3	7320.600	43.89	37.00	5.73	-39.87	46.75	74.00	27.25	PK	Vertical
4	9758.400	56.89	37.98	6.70	-39.43	62.14	-	-	PK	Vertical
5	11392.100	40.81	39.71	7.57	-39.60	48.49	74.00	25.51	PK	Vertical
6	12301.600	41.22	39.40	7.81	-39.36	49.07	74.00	24.93	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 1M 2480MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\21

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4094.000	45.94	31.11	4.63	-39.71	41.97	74.00	32.03	PK	Horizontal
2	4991.600	44.80	33.02	5.24	-39.80	43.26	74.00	30.74	PK	Horizontal
3	7441.300	44.92	36.62	5.77	-39.86	47.45	74.00	26.55	PK	Horizontal
4	9049.500	42.19	38.90	6.79	-38.65	49.23	74.00	24.77	PK	Horizontal
5	9921.600	55.37	38.34	6.68	-39.61	60.78	-	-	PK	Horizontal
6	12342.400	41.96	39.27	7.81	-39.33	49.71	74.00	24.29	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 1M 2480MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\22

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3776.100	47.22	30.37	4.54	-39.61	42.52	74.00	31.48	PK	Vertical
2	4818.200	44.99	32.39	5.13	-39.78	42.73	74.00	31.27	PK	Vertical
3	7439.600	46.28	36.62	5.77	-39.86	48.81	74.00	25.19	PK	Vertical
4	9061.400	41.63	38.69	6.79	-38.67	48.44	74.00	25.56	PK	Vertical
5	9919.900	58.94	38.34	6.68	-39.61	64.35	-	-	PK	Vertical
6	11438.000	40.84	39.42	7.59	-39.60	48.25	74.00	25.75	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 2M 2478MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\23

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4376.200	46.87	31.61	4.83	-39.74	43.57	74.00	30.43	PK	Horizontal
2	7434.500	44.38	36.63	5.77	-39.86	46.92	74.00	27.08	PK	Horizontal
3	8401.800	42.00	37.68	6.30	-39.32	46.66	74.00	27.34	PK	Horizontal
4	9081.800	43.22	38.33	6.79	-38.69	49.65	74.00	24.35	PK	Horizontal
5	9909.700	55.65	38.32	6.68	-39.60	61.05	-	-	PK	Horizontal
6	12048.300	41.67	39.24	7.81	-39.56	49.16	74.00	24.84	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 2M 2478MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\24

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4376.200	45.94	31.61	4.83	-39.74	42.64	74.00	31.36	PK	Vertical
2	5013.700	44.60	33.03	5.26	-39.80	43.09	74.00	30.91	PK	Vertical
3	7436.200	44.57	36.63	5.77	-39.86	47.11	74.00	26.89	PK	Vertical
4	9032.500	41.29	38.76	6.80	-38.64	48.21	74.00	25.79	PK	Vertical
5	9909.700	58.39	38.32	6.68	-39.60	63.79	-	-	PK	Vertical
6	12094.200	41.12	39.47	7.81	-39.52	48.88	74.00	25.12	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 2M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\25

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4094.000	46.38	31.11	4.63	-39.71	42.41	74.00	31.59	PK	Horizontal
2	4393.200	46.25	31.82	4.84	-39.74	43.17	74.00	30.83	PK	Horizontal
3	4908.300	44.20	33.10	5.19	-39.79	42.70	74.00	31.30	PK	Horizontal
4	7516.100	43.37	36.67	5.80	-39.85	45.99	74.00	28.01	PK	Horizontal
5	9758.400	55.30	37.98	6.70	-39.43	60.55	-	-	PK	Horizontal
6	11917.400	42.28	38.59	7.78	-39.60	49.05	74.00	24.95	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbin

Test Mode:

ANT2 2.4G SRD 2M 2440MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\26

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4090.600	46.16	31.12	4.63	-39.71	42.20	74.00	31.80	PK	Vertical
2	4384.700	45.20	31.72	4.83	-39.74	42.01	74.00	31.99	PK	Vertical
3	4896.400	44.23	33.09	5.18	-39.79	42.71	74.00	31.29	PK	Vertical
4	7500.800	42.58	36.89	5.80	-39.85	45.42	74.00	28.58	PK	Vertical
5	9758.400	56.19	37.98	6.70	-39.43	61.44	-	-	PK	Vertical
6	11455.000	41.38	39.25	7.59	-39.60	48.62	74.00	25.38	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 2M 2404MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\27

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4102.500	46.03	31.12	4.64	-39.71	42.08	74.00	31.92	PK	Horizontal
2	4865.800	45.36	32.96	5.16	-39.79	43.69	74.00	30.31	PK	Horizontal
3	7397.100	42.62	36.72	5.76	-39.86	45.24	74.00	28.76	PK	Horizontal
4	9438.800	42.71	38.31	6.74	-39.08	48.68	74.00	25.32	PK	Horizontal
5	9613.900	55.64	38.16	6.72	-39.28	61.24	-	-	PK	Horizontal
6	11434.600	41.46	39.45	7.58	-39.60	48.89	74.00	25.11	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-16

Tested By:

Li Xiongbín

Test Mode:

ANT2 2.4G SRD 2M 2404MHz TX Mode

Power Supply:

Battery

Condition:

Temp:24.1°C;Humi:42.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25111111-3E\FCC Above 1G 2.4G SRD\28

Memo:

Sample Number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3776.100	47.39	30.37	4.54	-39.61	42.69	74.00	31.31	PK	Vertical
2	4852.200	45.59	32.91	5.15	-39.79	43.86	74.00	30.14	PK	Vertical
3	7443.000	43.14	36.61	5.78	-39.86	45.67	74.00	28.33	PK	Vertical
4	9017.200	42.57	38.64	6.80	-38.62	49.39	74.00	24.61	PK	Vertical
5	9613.900	55.85	38.16	6.72	-39.28	61.45	-	-	PK	Vertical
6	11393.800	41.32	39.73	7.57	-39.60	49.02	74.00	24.98	PK	Vertical

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2404MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\53

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.050	42.37	27.43	-27.81	0.00	41.99	74.00	32.01	PK	Horizontal
2	2390.000	40.18	27.43	-27.80	0.00	39.81	74.00	34.19	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2404MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\54

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2377.400	41.45	27.39	-27.88	0.00	40.96	74.00	33.04	PK	Vertical
2	2390.000	40.26	27.43	-27.80	0.00	39.89	74.00	34.11	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2478MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\55

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	43.24	27.70	-27.66	0.00	43.28	74.00	30.72	PK	Horizontal
2	2484.649	45.85	27.71	-27.66	0.00	45.90	74.00	28.10	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2478MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\56

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	42.28	27.70	-27.66	0.00	42.32	74.00	31.68	PK	Vertical
2	2483.989	46.05	27.70	-27.66	0.00	46.09	74.00	27.91	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2480MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\57

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	49.55	27.70	-27.66	0.00	49.59	74.00	24.41	PK	Horizontal
2	2484.724	49.36	27.71	-27.66	0.00	49.41	74.00	24.59	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2480MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\58

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	47.54	27.70	-27.66	0.00	47.58	74.00	26.42	PK	Vertical
2	2484.199	48.86	27.70	-27.66	0.00	48.90	74.00	25.10	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2402MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\59

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.080	42.10	27.42	-27.82	0.00	41.70	74.00	32.30	PK	Horizontal
2	2390.000	39.82	27.43	-27.80	0.00	39.45	74.00	34.55	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2402MHz ANT1 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\60

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2381.160	43.12	27.41	-27.86	0.00	42.67	74.00	31.33	PK	Vertical
2	2390.000	40.32	27.43	-27.80	0.00	39.95	74.00	34.05	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2402MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\83

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.700	42.81	27.42	-27.82	0.00	42.41	74.00	31.59	PK	Horizontal
2	2390.000	41.60	27.43	-27.80	0.00	41.23	74.00	32.77	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2402MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\84

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2387.970	41.02	27.43	-27.81	0.00	40.64	74.00	33.36	PK	Vertical
2	2390.000	38.70	27.43	-27.80	0.00	38.33	74.00	35.67	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2480MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\89

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	47.07	27.70	-27.66	0.00	47.11	74.00	26.89	PK	Horizontal
2	2484.931	48.49	27.71	-27.66	0.00	48.54	74.00	25.46	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD1M 2480MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\90

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	47.15	27.70	-27.66	0.00	47.19	74.00	26.81	PK	Vertical
2	2485.816	46.69	27.71	-27.65	0.00	46.75	74.00	27.25	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2478MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\91

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	44.01	27.70	-27.66	0.00	44.05	74.00	29.95	PK	Horizontal
2	2484.490	45.41	27.71	-27.66	0.00	45.46	74.00	28.54	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2478MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\92

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	42.32	27.70	-27.66	0.00	42.36	74.00	31.64	PK	Vertical
2	2484.628	45.46	27.71	-27.66	0.00	45.51	74.00	28.49	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2404MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\99

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2386.480	42.87	27.42	-27.82	0.00	42.47	74.00	31.53	PK	Horizontal
2	2390.000	40.24	27.43	-27.80	0.00	39.87	74.00	34.13	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-01-14

Tested By:

Nan Zhong

Test Mode:

TX SRD2M 2404MHz ANT2 Mode

Power Supply:

Battery

Condition:

Temp:24.2°C;Humi:45.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 test date\Q25111111-3E\FCC ABOVE 1G BLE\100

Memo:

Sample number:S25111111-059



Suspected Data List										
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2385.730	41.40	27.42	-27.83	0.00	40.99	74.00	33.01	PK	Vertical
2	2390.000	38.99	27.43	-27.80	0.00	38.62	74.00	35.38	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Power Line Conducted Emissions

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI Test Receiver	R&S	ESCI 3	DDT-ZC01972	2026/03/28
Two Line V-Network	R&S	ENV216	DDT-ZC00586	2026/07/06
Pulse Limiter	R&S	KH43101	DDT-ZC00747	2026/03/28
Coaxial signal signal cable	H&S	RG214-5	DDT-ZC01817	2026/03/28
Conducted Radiated Software	Audix	e3	DDT-ZC00562	/
Two Line V-Network	R&S	ENV216	DDT-ZC02058	2026/07/06

14.2. Block diagram of test setup



14.3. Limits

Frequency	Quasi-Peak Level	Average Level
	dB(μV)	dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Adapter	Apple	A1882	Apple 30W fast charge - 1#/2# Venue	Input: 100-240V~ 50-60Hz, 0.75A, Output: DC 5V/3A or 9V/3A or 15V/2A or 20V/1.5A

14.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means Peak detection; "----" means Average detection.


Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

14.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room D:\2025 report data\Q25111111\0116 CE.EM6
Test Date : 2026-01-16 Tested By : Jiahao Yang
Power Supply : AC120V/60Hz Test Mode : SRD1M mode
Condition : Temp:22.4°C,Humi:56.8% LISN : 2025 2# 216/LINE
Memo : SAMPLE NUMBER:S25111111-059

Data: 26



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Margin	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.16	14.95	9.47	0.05	10.21	34.68	65.43	30.75	QP	LINE
2	0.16	9.45	9.47	0.05	10.21	29.18	65.43	36.25	Average	LINE
3	0.30	13.80	9.48	0.07	10.25	33.60	60.32	26.72	QP	LINE
4	0.30	8.70	9.48	0.07	10.25	28.50	60.32	31.82	Average	LINE
5	0.55	14.72	9.50	0.11	10.33	34.66	56.00	21.34	QP	LINE
6	0.55	8.73	9.50	0.11	10.33	28.67	56.00	27.33	Average	LINE
7	0.78	15.35	9.51	0.14	10.37	35.37	56.00	20.63	QP	LINE
8	0.78	10.92	9.51	0.14	10.37	30.94	56.00	25.06	Average	LINE
9	1.42	10.47	9.50	0.19	10.39	30.55	56.00	25.45	QP	LINE
10	1.42	5.02	9.50	0.19	10.39	25.10	56.00	30.90	Average	LINE
11	3.94	9.69	9.53	0.23	10.29	29.74	56.00	26.26	QP	LINE
12	3.94	1.98	9.53	0.23	10.29	22.03	56.00	33.97	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2025 report data\Q25111111\0116 CE.EM6

Test Date : 2026-01-16

Tested By : Jiahao Yang

Power Supply : AC120V/60Hz


Test Mode : SRD1M mode

Condition : Temp:22.4°C,Humi:56.8%

LISN : 2025 2# 216/NEUTRAL

Memo : SAMPLE NUMBER:S25111111-059

Data: 28



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Margin (dB)	Detector	Phase
1	0.24	14.22	9.48	0.06	10.23	33.99	61.95	27.96	QP	NEUTRAL
2	0.24	8.96	9.48	0.06	10.23	28.73	61.95	33.22	Average	NEUTRAL
3	0.52	16.65	9.48	0.10	10.33	36.56	56.00	19.44	QP	NEUTRAL
4	0.52	9.89	9.48	0.10	10.33	29.80	56.00	26.20	Average	NEUTRAL
5	0.78	15.27	9.48	0.14	10.37	35.26	56.00	20.74	QP	NEUTRAL
6	0.78	11.08	9.48	0.14	10.37	31.07	56.00	24.93	Average	NEUTRAL
7	1.42	10.48	9.50	0.19	10.39	30.56	56.00	25.44	QP	NEUTRAL
8	1.42	5.04	9.50	0.19	10.39	25.12	56.00	30.88	Average	NEUTRAL
9	3.86	8.38	9.52	0.23	10.30	28.43	56.00	27.57	QP	NEUTRAL
10	3.86	2.05	9.52	0.23	10.30	22.10	56.00	33.90	Average	NEUTRAL
11	4.70	9.16	9.53	0.24	10.27	29.20	56.00	26.80	QP	NEUTRAL
12	4.70	-1.56	9.53	0.24	10.27	18.48	56.00	37.52	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2025 report data\Q25111111\0116 CE.EM6

Test Date : 2026-01-16

Tested By : Jiahao Yang

Power Supply : AC120V/60Hz


Test Mode : SRD2M mode

Condition : Temp:22.4°C,Humi:56.8%

LISN : 2025 2# 216/NEUTRAL

Memo : SAMPLE NUMBER:S25111111-059

Data: 30



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Margin	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.22	14.69	9.49	0.06	10.21	34.45	62.83	28.38	QP	NEUTRAL
2	0.22	9.15	9.49	0.06	10.21	28.91	62.83	33.92	Average	NEUTRAL
3	0.53	16.47	9.48	0.10	10.33	36.38	56.00	19.62	QP	NEUTRAL
4	0.53	9.17	9.48	0.10	10.33	29.08	56.00	26.92	Average	NEUTRAL
5	0.78	15.25	9.48	0.14	10.37	35.24	56.00	20.76	QP	NEUTRAL
6	0.78	10.91	9.48	0.14	10.37	30.90	56.00	25.10	Average	NEUTRAL
7	0.89	12.19	9.48	0.16	10.39	32.22	56.00	23.78	QP	NEUTRAL
8	0.89	7.05	9.48	0.16	10.39	27.08	56.00	28.92	Average	NEUTRAL
9	3.94	7.59	9.52	0.23	10.29	27.63	56.00	28.37	QP	NEUTRAL
10	3.94	2.05	9.52	0.23	10.29	22.09	56.00	33.91	Average	NEUTRAL
11	4.67	9.20	9.53	0.24	10.27	29.24	56.00	26.76	QP	NEUTRAL
12	4.67	-0.87	9.53	0.24	10.27	19.17	56.00	36.83	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).


4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room
Test Date : 2026-01-16
Power Supply : AC120V/60Hz
Condition : Temp:22.4°C,Humi:56.8%
Memo : SAMPLE NUMBER:S25111111-059

D:\2025 report data\Q25111111\0116 CE.EM6
Tested By : Jiahao Yang
Test Mode : SRD2M mode
LISN : 2025 2# 216/LINE

Data: 32



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Margin (dB)	Detector	Phase
1	0.17	14.64	9.48	0.05	10.20	34.37	64.99	30.62	QP	LINE
2	0.17	9.55	9.48	0.05	10.20	29.28	64.99	35.71	Average	LINE
3	0.21	14.64	9.46	0.05	10.21	34.36	63.23	28.87	QP	LINE
4	0.21	9.42	9.46	0.05	10.21	29.14	63.23	34.09	Average	LINE
5	0.52	16.10	9.49	0.10	10.32	36.01	56.00	19.99	QP	LINE
6	0.52	9.75	9.49	0.10	10.32	29.66	56.00	26.34	Average	LINE
7	0.78	15.45	9.51	0.14	10.37	35.47	56.00	20.53	QP	LINE
8	0.78	10.99	9.51	0.14	10.37	31.01	56.00	24.99	Average	LINE
9	1.40	10.45	9.50	0.19	10.40	30.54	56.00	25.46	QP	LINE
10	1.40	5.16	9.50	0.19	10.40	25.25	56.00	30.75	Average	LINE
11	3.94	9.10	9.53	0.23	10.29	29.15	56.00	26.85	QP	LINE
12	3.94	1.36	9.53	0.23	10.29	21.41	56.00	34.59	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

16. Photos of the EUT

Please refer to DDT-Q25111111-3E appendix I

-----End Report-----