**RF EXPOSURE EVALUATION METHOD**

**SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation
Distances are illustrated in the following Table.

| MHz | 5 | 10 | 15 | 20 | 25 | mm |
|---|---|---|---|---|---|---|
| 150 | 39 | 77 | 116 | 155 | 194 | SAR Test Exclusion Threshold (mW) |
| 300 | 27 | 55 | 82 | 110 | 137 | |
| 450 | 22 | 45 | 67 | 89 | 112 | |
| 835 | 16 | 33 | 49 | 66 | 82 | |
| 900 | 16 | 32 | 47 | 63 | 79 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | |

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation
The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

**BT5.0 The Worst Case**

| | |
|---|---|
| Mode | 2402-2480MHz |
| Detector | PEAK |
| GFSK | 3.5±1dBm |
| π/4-DQPSK | 4±1dBm |
| 8-DPSK | 5±1dBm |

Remark: The worst case gain of the antenna is 2.92Bi.

0Bi logarithmic terms convert to numeric result is nearly 1.96

| **Mode** | **Frequency (GHz)** | **Maxinum Peak Conducted Output Power (dBm)** | **Tune up Power (dBm)** | **Tune up Power (mW)** | **Result** | **Limit** |
|---|---|---|---|---|---|---|
| GFSK | 2.402 | 4.31 | 4.5 | 2.818 | 0.874 | 3 |
| π/4-DQPSK | 2.402 | 4.96 | 5 | 3.162 | 0.980 | 3 |
| 8-DPSK | 2.402 | 5.77 | 6 | 3.981 | 1.234 | 3 |

Threshold at which no SAR required is 1.234 ≤ 3.0for 1-g SAR, Separation distance is 5mm.