FCC RF Test Report

APPLICANT	:	Rolling Wireless S.a r.l.
EQUIPMENT	:	5G Module
BRAND NAME	:	Rolling Wireless
MODEL NAME	:	RW135R-GL
FCC ID	:	2AX2URW135RGL
STANDARD	:	47 CFR Part 27
CLASSIFICATION	:	PCS Licensed Transmitter (PCB)
TEST DATE(S)	:	Apr. 28, 2026 ~ May 14, 2026

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang

ACCREDITED
Cert #5145.01

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 5
1.6 Maximum EIRP Power and Emission Designator 6
1.7 Testing Site 6
1.8 Test Software 6
1.9 Applied Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 10
3 CONDUCTED TEST ITEMS **11**
3.1 Measuring Instruments 11
3.2 Test Setup 11
3.3 Test Result of Conducted Test 11
3.4 Conducted Output Power Measurement 12
3.5 Peak-to-Average Ratio 13
3.6 EIRP 14
3.7 Occupied Bandwidth 15
3.8 Conducted Band Edge Measurement 16
3.9 Conducted Spurious Emission Measurement 17
3.10 Frequency Stability Measurement 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Radiated Spurious Emission Measurement 21
5 LIST OF MEASURING EQUIPMENT **22**
6 MEASUREMENT UNCERTAINTY **23**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG642201E	Rev. 01	Initial issue of report	Jun. 18, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	—	Report Only	-
3.5	-	Peak-to-Average Ratio	—	Report Only	
3.6	§27.50 (a)(3)	EIRP	EIRP < 250mW/5MHz	PASS	-
3.7	§2.1049	Occupied Bandwidth	—	Report Only	-
3.8	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.9	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	-
3.10	§2.1055	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	Under limit 11.88 dB at 9241.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Rolling Wireless S.a r.l.
8-10, rue Mathias Hardt 1717, Luxembourg

1.2 Manufacturer

Rolling Wireless S.a r.l.
8-10, rue Mathias Hardt 1717, Luxembourg

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	5G Module
Brand Name	Rolling Wireless
Model Name	RW135R-GL
FCC ID	2AX2URW135RGL
IMEI Code	Conducted: 359200990000278 Radiation: 359200990002126
EUT Stage	Identical Prototype

Remark: There are two types of EUT. For details, please refer to the RW135R-GL_Operational Description of Product Equality Declaration exhibit separately. After evaluation, the differences will not affect RF performance, so we choose the Sample1 to full test, and Sample2 to verify the worst case for RSE, which is recorded in another report(FG642201F).

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx Frequency	LTE Band 30 : 2305 MHz ~ 2315 MHz
Rx Frequency	LTE Band 30 : 2350 MHz ~ 2360 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	LTE Band 30 : 22.65 dBm
Antenna Gain	LTE Band 30 : 1.0 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power and Emission Designator

LTE Band 30		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
5	2307.5 ~ 2312.5	0.1828	4M50G7D	0.1486	4M47W7D
10	2310.0	0.1841	9M03G7D	0.1510	9M01W7D

Note: All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-SZ 03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 27(D)
- ANSI C63.26-2015
- FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01
-

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Z Plane)

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	V		-	-	V	V	V	V	V	V	V	V	V	V
		-	-		V	-	-	V	V	V	V	V	V	V		V	
Peak-to-Average Ratio	30	-	-		V	-	-	V	V	V				V		V	
E.I.R.P	30	-	-	V		-	-	V	V	V	V	V	V	V	V	V	V
		-	-		V	-	-	V	V	V	V	V	V	V		V	
26dB and 99% Bandwidth	30	-	-	V	V	-	-	V	V					V		V	
Conducted Band Edge	30	-	-	V	V	-	-	V	V	V		V		V	V		V
Conducted Spurious Emission	30	-	-	V		-	-	V				V			V	V	V
		-	-		V	-	-	V				V				V	
Frequency Stability	30	-	-	V		-	-	V						V		V	
Radiated Spurious Emission	30	-	-	V		-	-	V				V			V	V	V
					V			V				V				V	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power.																

2.2 Connection Diagram of Test System



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC power supply	N/A	N/A	N/A	N/A	N/A
3.	WWAN Antenna	N/A	N/A	N/A	N/A	N/A
4.	Test Jig	N/A	N/A	N/A	N/A	N/A
5.	Earphone	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.0 + 10 = 15.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth ,Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

   P_T = transmitter output power in dBm

   G_T = gain of the transmitting antenna in dBi

   L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

27.53 (a)(4)

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300 MHz, 61 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz;

(iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Mar. 26, 2026	Apr. 28, 2026	Mar. 25, 2027	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V，3A	Oct. 13, 2025	Apr. 28, 2026	Oct. 12, 2026	Conducted (TH01-SZ)
Power Divider	Titan	P02N005180	923402	0.4GHz~26.5GHz	Nov. 07, 2025	Apr. 28, 2026	Nov. 06, 2026	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 02, 2025	Apr. 28, 2026	Jul. 01, 2026	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	May 14, 2026	Jul. 02, 2026	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 25, 2025	May 14, 2026	Dec. 24, 2026	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Dec. 23, 2025	May 14, 2026	Dec. 22, 2027	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	May 14, 2026	Jul. 04, 2026	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	May 14, 2026	Jul. 03, 2026	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 03, 2025	May 14, 2026	Apr. 02, 2027	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 25, 2025	May 14, 2026	Dec. 24, 2026	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 13, 2025	May 14, 2026	Oct. 12, 2026	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 13, 2025	May 14, 2026	Oct. 12, 2026	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	May 14, 2026	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	May 14, 2026	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.47 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.31 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.72 dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Lorenzo Liu	Temperature :	24~26℃
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and EIRP

LTE Band 30:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W)		
Channel				27710					
Frequency (MHz)				2310				M	
10	QPSK	1	0		22.63			0.2307	
10	QPSK	1	25		22.65			0.2317	
10	QPSK	1	49		22.40			0.2188	
10	QPSK	25	0		21.40			0.1738	
10	QPSK	25	12		21.41			0.1742	
10	QPSK	25	25		21.46			0.1762	
10	QPSK	50	0		21.42			0.1746	
10	16QAM	1	0		21.79			0.1901	
10	16QAM	1	25		21.64			0.1837	
10	16QAM	1	49		21.65			0.1841	
10	16QAM	25	0		20.22			0.1324	
10	16QAM	25	12		20.27			0.1340	
10	16QAM	25	25		20.28			0.1343	
10	16QAM	50	0		20.21			0.1321	
10	64QAM	1	0		20.45			0.1396	
10	64QAM	1	25		20.53			0.1422	
10	64QAM	1	49		20.32			0.1355	
10	64QAM	25	0		19.22			0.1052	
10	64QAM	25	12		19.16			0.1038	
10	64QAM	25	25		19.19			0.1045	
10	64QAM	50	0		19.17			0.1040	
10	256QAM	1	0		17.85			0.0767	
10	256QAM	1	25		17.82			0.0762	
10	256QAM	1	49		17.83			0.0764	
10	256QAM	25	0		17.75			0.0750	
10	256QAM	25	12		17.78			0.0755	
10	256QAM	25	25		17.74			0.0748	
10	256QAM	50	0		17.77			0.0753	
Channel				27685	27710	27735	EIRP(W)		
Frequency (MHz)				2307.5	2310	2312.5	L	M	H

5	QPSK	1	0	22.48	22.55	22.47	0.2228	0.2265	0.2223
5	QPSK	1	12	22.62	22.60	22.56	0.2301	0.2291	0.2270
5	QPSK	1	24	22.31	22.32	22.27	0.2143	0.2148	0.2123
5	QPSK	12	0	21.29	21.32	21.31	0.1694	0.1706	0.1702
5	QPSK	12	7	21.29	21.39	21.37	0.1694	0.1734	0.1726
5	QPSK	12	13	21.30	21.38	21.29	0.1698	0.1730	0.1694
5	QPSK	25	0	21.30	21.37	21.38	0.1698	0.1726	0.1730
5	16QAM	1	0	21.66	21.72	21.64	0.1845	0.1871	0.1837
5	16QAM	1	12	21.56	21.59	21.46	0.1803	0.1816	0.1762
5	16QAM	1	24	21.57	21.64	21.52	0.1807	0.1837	0.1786
5	16QAM	12	0	20.20	20.12	20.13	0.1318	0.1294	0.1297
5	16QAM	12	7	20.14	20.23	20.18	0.1300	0.1327	0.1312
5	16QAM	12	13	20.22	20.21	20.19	0.1324	0.1321	0.1315
5	16QAM	25	0	20.06	20.19	20.12	0.1276	0.1315	0.1294
5	64QAM	1	0	20.41	20.35	20.39	0.1384	0.1365	0.1377
5	64QAM	1	12	20.45	20.50	20.41	0.1396	0.1413	0.1384
5	64QAM	1	24	20.23	20.26	20.15	0.1327	0.1337	0.1303
5	64QAM	12	0	19.07	19.20	19.14	0.1016	0.1047	0.1033
5	64QAM	12	7	19.04	19.06	19.05	0.1009	0.1014	0.1012
5	64QAM	12	13	19.12	19.11	19.09	0.1028	0.1026	0.1021
5	64QAM	25	0	19.10	19.16	19.02	0.1023	0.1038	0.1005
5	256QAM	1	0	17.67	17.83	17.81	0.0736	0.0764	0.0760
5	256QAM	1	12	17.68	17.81	17.74	0.0738	0.0760	0.0748
5	256QAM	1	24	17.73	17.74	17.77	0.0746	0.0748	0.0753
5	256QAM	12	0	17.65	17.69	17.63	0.0733	0.0740	0.0729
5	256QAM	12	7	17.69	17.76	17.69	0.0740	0.0752	0.0740
5	256QAM	12	13	17.70	17.71	17.62	0.0741	0.0743	0.0728
5	256QAM	25	0	17.64	17.76	17.64	0.0731	0.0752	0.0731

LTE Band 30

Peak-to-Average Ratio

Mode	LTE Band 30 / 10MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	5.33	6.26	6.64	PASS

LTE Band 30 / 10MHz / QPSK	LTE Band 30 / 10MHz / 16QAM
Middle Channel / Full RB	**Middle Channel / Full RB**
	
LTE Band 30 / 10MHz / 64QAM	
Middle Channel / Full RB	
	

26dB Bandwidth

Mode	LTE Band 30 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	-	-	-	-	5.10	5.09	10.07	10.11	-	-	-	-

LTE Band 30

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 30 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	-	-	-	-	4.50	4.47	9.03	9.01	-	-	-	-

LTE Band 30

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Conducted Band Edge

LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Lowest Band Edge / 1 RB / Lower zoom in

Highest Band Edge / 1 RB / Lower zoom in



LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29586 GHz	-39.45 dBm	-8.45 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29973 GHz	-33.38 dBm	-8.38 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30397 GHz	-25.81 dBm	-12.81 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	7.81 dBm*	20.81 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30822 GHz	5.25 dBm	-24.75 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31003 GHz*	8.34 dBm*	21.34 dB*
2.311 GHz	2.320 GHz	1.000 MHz	2.31105 GHz	-27.65 dBm	-14.65 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32007 GHz	-39.46 dBm	-14.46 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32417 GHz	-41.98 dBm	-10.98 dB

Date: 28.APR.2026 15:01:50

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29596 GHz	-42.07 dBm	-11.07 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29961 GHz	-40.44 dBm	-15.44 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30887 GHz	-26.47 dBm	-13.47 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30999 GHz*	8.21 dBm*	21.21 dB*
2.310 GHz	2.315 GHz	100.000 kHz	2.31044 GHz	5.13 dBm	-24.87 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	8.22 dBm*	21.22 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31605 GHz	-26.37 dBm	-13.37 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32213 GHz	-32.40 dBm	-7.40 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32423 GHz	-38.37 dBm	-7.37 dB

Date: 28.APR.2026 15:19:17

Lowest Band Edge / Full RB / Lower zoom in



Date: 28.APR.2026 15:04:26

Highest Band Edge / Full RB / Lower zoom in



Date: 28.APR.2026 15:20:27

Lowest Band Edge / Full RB / Upper zoom in



Date: 28.APR.2026 15:04:47

Highest Band Edge / Full RB / Upper zoom in



Date: 28.APR.2026 15:20:50

LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29549 GHz	-42.16 dBm	-11.16 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29898 GHz	-37.09 dBm	-12.09 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-33.45 dBm	-20.45 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30498 GHz*	20.98 dBm*	33.98 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30531 GHz	17.90 dBm	-12.10 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31055 GHz	-36.11 dBm	-23.11 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31285 GHz	-36.54 dBm	-23.54 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32244 GHz	-42.27 dBm	-17.27 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32457 GHz	-42.26 dBm	-11.26 dB

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29466 GHz	-41.95 dBm	-10.95 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29702 GHz	-42.31 dBm	-17.31 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30845 GHz	-36.77 dBm	-23.77 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30998 GHz	-34.38 dBm	-21.38 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31464 GHz	17.89 dBm	-12.11 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31501 GHz*	21.18 dBm*	34.18 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31899 GHz	-33.28 dBm	-20.28 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32313 GHz	-33.02 dBm	-8.02 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32413 GHz	-40.85 dBm	-9.85 dB

Lowest Band Edge / 1 RB / Lower zoom in

Highest Band Edge / 1 RB / Lower zoom in



LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29597 GHz	-39.26 dBm	-8.26 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29981 GHz	-32.42 dBm	-7.42 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30377 GHz	-25.53 dBm	-12.53 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	6.98 dBm*	19.98 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30791 GHz	3.95 dBm	-26.05 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31002 GHz*	7.48 dBm*	20.48 dB*
2.311 GHz	2.320 GHz	1.000 MHz	2.31118 GHz	-26.73 dBm	-13.73 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32003 GHz	-40.33 dBm	-15.33 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32735 GHz	-42.10 dBm	-11.10 dB

Date: 28.APR.2026 15:05:50

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29386 GHz	-42.19 dBm	-11.19 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29995 GHz	-40.87 dBm	-15.87 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30893 GHz	-26.10 dBm	-13.10 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.31000 GHz*	7.33 dBm*	20.33 dB*
2.310 GHz	2.315 GHz	100.000 kHz	2.31074 GHz	4.10 dBm	-25.90 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31503 GHz*	7.30 dBm*	20.30 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31634 GHz	-25.09 dBm	-12.09 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32036 GHz	-32.40 dBm	-7.40 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32409 GHz	-39.55 dBm	-8.55 dB

Date: 28.APR.2026 15:18:12

Lowest Band Edge / Full RB / Lower zoom in



Date: 28.APR.2026 15:06:29

Highest Band Edge / Full RB / Lower zoom in



Date: 28.APR.2026 15:18:35

Lowest Band Edge / Full RB / Upper zoom in



Date: 28.APR.2026 15:06:41

Highest Band Edge / Full RB / Upper zoom in



Date: 28.APR.2026 15:18:46

LTE Band 30 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29226 GHz	-42.11 dBm	-11.11 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29859 GHz	-42.18 dBm	-17.18 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30397 GHz	-36.99 dBm	-23.99 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30498 GHz*	20.11 dBm*	33.11 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30534 GHz	17.31 dBm	-12.69 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31032 GHz	-41.94 dBm	-28.94 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31465 GHz	-42.41 dBm	-29.41 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32045 GHz	-42.22 dBm	-17.22 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32588 GHz	-42.17 dBm	-11.17 dB

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29261 GHz	-42.23 dBm	-11.23 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29734 GHz	-42.22 dBm	-17.22 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30886 GHz	-42.07 dBm	-29.07 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30984 GHz	-41.07 dBm	-28.07 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31470 GHz	16.65 dBm	-13.35 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31503 GHz*	19.93 dBm*	32.93 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31604 GHz	-36.64 dBm	-23.64 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32382 GHz	-41.70 dBm	-16.70 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32575 GHz	-42.17 dBm	-11.17 dB

Lowest Band Edge / 1 RB / Lower zoom in

Highest Band Edge / 1 RB / Lower zoom in



LTE Band 30 / 5MHz / 64QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29581 GHz	-41.05 dBm	-10.05 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29991 GHz	-34.58 dBm	-9.58 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30391 GHz	-26.70 dBm	-13.70 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	6.54 dBm*	19.54 dB*
2.305 GHz	2.310 GHz	100.000 kHz	2.30731 GHz	3.14 dBm	-26.86 dB
2.310 GHz	2.311 GHz	1.000 MHz	2.31002 GHz*	6.33 dBm*	19.33 dB*
2.311 GHz	2.320 GHz	1.000 MHz	2.31102 GHz	-27.98 dBm	-14.98 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32012 GHz	-41.15 dBm	-16.15 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32549 GHz	-42.10 dBm	-11.10 dB

Date: 28.APR.2026 15:07:19

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29553 GHz	-42.22 dBm	-11.22 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29997 GHz	-41.45 dBm	-16.45 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30898 GHz	-27.21 dBm	-14.21 dB
2.309 GHz	2.310 GHz	1.000 MHz	2.30997 GHz*	5.67 dBm*	18.67 dB*
2.310 GHz	2.315 GHz	100.000 kHz	2.31224 GHz	3.34 dBm	-26.66 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	6.25 dBm*	19.25 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31625 GHz	-26.40 dBm	-13.40 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32031 GHz	-33.77 dBm	-8.77 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32427 GHz	-40.52 dBm	-9.52 dB

Date: 28.APR.2026 15:17:04

Lowest Band Edge / Full RB / Lower zoom in



Date: 28.APR.2026 15:14:18

Highest Band Edge / Full RB / Lower zoom in



Date: 28.APR.2026 15:17:32

Lowest Band Edge / Full RB / Upper zoom in



Date: 28.APR.2026 15:09:01

Highest Band Edge / Full RB / Upper zoom in



Date: 28.APR.2026 15:17:43

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29551 GHz	-51.50 dBm	-20.50 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29951 GHz	-48.29 dBm	-23.29 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30400 GHz	-37.20 dBm	-24.20 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	8.57 dBm*	21.57 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.30561 GHz	19.03 dBm	-10.97 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31507 GHz	-50.61 dBm	-37.61 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31828 GHz	-50.82 dBm	-37.82 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32005 GHz	-51.80 dBm	-26.80 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32498 GHz	-52.04 dBm	-21.04 dB

Date: 28.APR.2026 15:43:11

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29494 GHz	-52.19 dBm	-21.19 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29822 GHz	-51.95 dBm	-26.95 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30128 GHz	-51.40 dBm	-38.40 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30453 GHz	-51.20 dBm	-38.20 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31444 GHz	18.53 dBm	-11.47 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	10.32 dBm*	23.32 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31607 GHz	-36.48 dBm	-23.48 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32010 GHz	-47.83 dBm	-22.83 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32418 GHz	-51.19 dBm	-20.19 dB

Date: 28.APR.2026 15:47:42

Lowest Band Edge / 1 RB / Lower zoom in



Date: 28.APR.2026 15:43:50

Highest Band Edge / 1 RB / Lower zoom in



Date: 28.APR.2026 15:47:56

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29586 GHz	-35.78 dBm	-4.78 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29898 GHz	-31.57 dBm	-6.57 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30381 GHz	-27.99 dBm	-14.99 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	-9.58 dBm*	3.42 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.31430 GHz	2.13 dBm	-27.87 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	-7.71 dBm*	5.29 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31617 GHz	-28.49 dBm	-15.49 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32153 GHz	-30.64 dBm	-5.64 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32421 GHz	-35.00 dBm	-4.00 dB

Lowest Band Edge / Full RB / Lower zoom in



Lowest Band Edge / Full RB / Upper zoom in



LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29533 GHz	-47.30 dBm	-16.30 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29742 GHz	-47.60 dBm	-22.60 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30342 GHz	-33.93 dBm	-20.93 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	9.73 dBm*	22.73 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.30563 GHz	17.85 dBm	-12.15 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31571 GHz	-43.33 dBm	-30.33 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31834 GHz	-40.02 dBm	-27.02 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32040 GHz	-50.93 dBm	-25.93 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32649 GHz	-51.98 dBm	-20.98 dB

Date: 28.APR.2026 15:44:20

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29460 GHz	-52.16 dBm	-21.16 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29985 GHz	-51.55 dBm	-26.55 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30121 GHz	-43.03 dBm	-30.03 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30423 GHz	-42.94 dBm	-29.94 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31444 GHz	17.67 dBm	-12.33 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	9.60 dBm*	22.60 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31678 GHz	-33.39 dBm	-20.39 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32238 GHz	-42.13 dBm	-17.13 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32479 GHz	-39.71 dBm	-8.71 dB

Date: 28.APR.2026 15:46:53

Lowest Band Edge / 1 RB / Lower zoom in



Date: 28.APR.2026 15:44:35

Highest Band Edge / 1 RB / Lower zoom in



Date: 28.APR.2026 15:47:13

LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29597 GHz	-36.80 dBm	-5.80 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29986 GHz	-32.12 dBm	-7.12 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30373 GHz	-27.61 dBm	-14.61 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	-9.99 dBm*	3.01 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.31200 GHz	0.95 dBm	-29.05 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	-8.65 dBm*	4.35 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31611 GHz	-28.12 dBm	-15.12 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32015 GHz	-31.16 dBm	-6.16 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32430 GHz	-35.60 dBm	-4.60 dB

Lowest Band Edge / Full RB / Lower zoom in



Lowest Band Edge / Full RB / Upper zoom in



LTE Band 30 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29587 GHz	-51.78 dBm	-20.78 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29979 GHz	-49.77 dBm	-24.77 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30396 GHz	-41.43 dBm	-28.43 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	7.13 dBm*	20.13 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.30560 GHz	17.61 dBm	-12.39 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31510 GHz	-47.97 dBm	-34.97 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31852 GHz	-51.77 dBm	-38.77 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32203 GHz	-51.93 dBm	-26.93 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32417 GHz	-52.03 dBm	-21.03 dB

Date: 28.APR.2026 15:45:03

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29223 GHz	-51.94 dBm	-20.94 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29794 GHz	-52.11 dBm	-27.11 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30179 GHz	-48.35 dBm	-35.35 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30431 GHz	-49.61 dBm	-36.61 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31440 GHz	16.71 dBm	-13.29 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	8.33 dBm*	21.33 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31603 GHz	-39.65 dBm	-26.65 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32012 GHz	-49.28 dBm	-24.28 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32447 GHz	-51.55 dBm	-20.55 dB

Date: 28.APR.2026 15:45:50

Lowest Band Edge / 1 RB / Lower zoom in



Date: 28.APR.2026 15:45:17

Highest Band Edge / 1 RB / Lower zoom in



Date: 28.APR.2026 15:46:08

LTE Band 30 / 10MHz / 64QAM

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29517 GHz	-38.04 dBm	-7.04 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29989 GHz	-32.92 dBm	-7.92 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30285 GHz	-29.57 dBm	-16.57 dB
2.304 GHz	2.305 GHz	1.000 MHz	2.30500 GHz*	-11.54 dBm*	1.46 dB*
2.305 GHz	2.315 GHz	100.000 kHz	2.31379 GHz	0.08 dBm	-29.92 dB
2.315 GHz	2.316 GHz	1.000 MHz	2.31500 GHz*	-8.88 dBm*	4.12 dB*
2.316 GHz	2.320 GHz	1.000 MHz	2.31657 GHz	-29.71 dBm	-16.71 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32021 GHz	-32.48 dBm	-7.48 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32413 GHz	-37.41 dBm	-6.41 dB

Lowest Band Edge / Full RB / Lower zoom in



Lowest Band Edge / Full RB / Upper zoom in



Conducted Spurious Emission

LTE Band 30 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	30.24238 MHz	-53.11 dBm	-13.11 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29092 GHz	-61.14 dBm	-21.14 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.54938 GHz	-61.04 dBm	-21.04 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61084 GHz	-56.46 dBm	-16.46 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.01825 GHz	-57.06 dBm	-17.06 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.97575 GHz	-55.87 dBm	-15.87 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.55606 GHz	-50.82 dBm	-10.82 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.69961 GHz	-52.63 dBm	-12.63 dB

Date: 28.APR.2026 15:50:33

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	30.24238 MHz	-50.89 dBm	-10.89 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29049 GHz	-61.56 dBm	-21.56 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.32847 GHz	-61.16 dBm	-21.16 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61604 GHz	-56.81 dBm	-16.81 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.00625 GHz	-57.22 dBm	-17.22 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.98975 GHz	-55.65 dBm	-15.65 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.54606 GHz	-50.83 dBm	-10.83 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.68361 GHz	-52.88 dBm	-12.88 dB

Date: 28.APR.2026 15:51:46

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	30.24238 MHz	-52.42 dBm	-12.42 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.20482 GHz	-61.89 dBm	-21.89 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.32820 GHz	-60.85 dBm	-20.85 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.97740 GHz	-56.92 dBm	-16.92 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.01775 GHz	-57.12 dBm	-17.12 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.96075 GHz	-55.86 dBm	-15.86 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.55006 GHz	-50.84 dBm	-10.84 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.70111 GHz	-52.55 dBm	-12.55 dB

Date: 28.APR.2026 15:53:00

LTE Band 30 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	30.24238 MHz	-52.21 dBm	-12.21 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29178 GHz	-61.46 dBm	-21.46 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.51189 GHz	-60.88 dBm	-20.88 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.61164 GHz	-56.36 dBm	-16.36 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.02775 GHz	-57.11 dBm	-17.11 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.93176 GHz	-55.83 dBm	-15.83 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.53306 GHz	-50.85 dBm	-10.85 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.74960 GHz	-52.58 dBm	-12.58 dB

Date: 28.APR.2026 15:42:51

Frequency Stability

Test Conditions		LTE Band 30 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 5MHz	Note 2.
		Frequency Offset (△f) (Hz)	Result
50	Normal Voltage	3.2	PASS
40	Normal Voltage	5.1	
30	Normal Voltage	4.3	
20(Ref.)	Normal Voltage	4.4	
10	Normal Voltage	3.2	
0	Normal Voltage	4.8	
-10	Normal Voltage	4.7	
-20	Normal Voltage	5.0	
-30	Normal Voltage	4.2	
20	Maximum Voltage	4.9	
20	Normal Voltage	4.4	
20	Minimum Voltage	5.3	

Note:

1. Normal Voltage = 3.3 V.; Minimum Voltage = 3.135 V.; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.

|MAX(△f)| = 5.3Hz

Frequency Stability	Frequency (MHz)	Limit Line	Result
f_L – |MAX(△f)|	2305.252195	≧ 2305 MHz	PASS
f_H + |MAX(△f)|	2314.757705	≦ 2315 MHz	

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	LiangPing Zhou	Temperature :	22~25℃
		Relative Humidity :	48~52%

LTE Band 30 / 5MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4610.50	-61.42	-40	-21.42	-49.10	-67.67	6.30	12.55	H
	6915.75	-58.17	-40	-18.17	-50.28	-61.57	8.25	11.65	H
	9221.00	-52.29	-40	-12.29	-51.38	-54.64	9.50	11.85	H
	4610.50	-56.25	-40	-16.25	-44.31	-62.50	6.30	12.55	V
	6915.75	-57.56	-40	-17.56	-50.15	-60.96	8.25	11.65	V
	9221.00	-53.05	-40	-13.05	-51.32	-55.40	9.50	11.85	V
Middle	4615.50	-61.43	-40	-21.43	-49.12	-67.68	6.45	12.70	H
	6923.25	-58.20	-40	-18.20	-50.30	-61.60	8.40	11.80	H
	9231.00	-52.36	-40	-12.36	-51.46	-54.71	9.65	12.00	H
	4615.50	-55.95	-40	-15.95	-44.02	-62.20	6.45	12.70	V
	6923.25	-57.48	-40	-17.48	-50.06	-60.88	8.40	11.80	V
	9231.00	-53.11	-40	-13.11	-51.39	-55.46	9.65	12.00	V
Highest	4620.50	-61.33	-40	-21.33	-49.02	-67.58	6.61	12.86	H
	6930.75	-57.97	-40	-17.97	-50.20	-61.35	8.56	11.94	H
	9241.00	-51.88	-40	-11.88	-51.03	-54.23	9.81	12.16	H
	4620.50	-53.82	-40	-13.82	-41.89	-60.07	6.61	12.86	V
	6930.75	-57.26	-40	-17.26	-49.96	-60.64	8.56	11.94	V
	9241.00	-52.76	-40	-12.76	-51.07	-55.11	9.81	12.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 30 / 10MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4611.00	-61.67	-40	-21.67	-49.35	-67.92	6.45	12.70	H
	6916.50	-58.29	-40	-18.29	-50.40	-61.69	8.40	11.80	H
	9222.00	-52.31	-40	-12.31	-51.40	-54.66	9.65	12.00	H
	4611.00	-56.11	-40	-16.11	-44.17	-62.36	6.45	12.70	V
	6916.50	-57.93	-40	-17.93	-50.52	-61.33	8.40	11.80	V
	9222.00	-53.01	-40	-13.01	-51.28	-55.36	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.