FCC RF Test Report

APPLICANT	:	Rolling Wireless S.a r.l.
EQUIPMENT	:	5G Module
BRAND NAME	:	Rolling Wireless
MODEL NAME	:	RW135R-GL
FCC ID	:	2AX2URW135RGL
STANDARD	:	47 CFR Part 90(S)
CLASSIFICATION	:	PCS Licensed Transmitter (PCB)
TEST DATE(S)	:	Apr. 27, 2026 ~ May 13, 2026

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang

ACCREDITED
Cert #5145.01

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 5
1.6 Maximum Conducted Power and Emission Designator 6
1.7 Testing Site 6
1.8 Test Software 6
1.9 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 10

3 TEST RESULT **11**

3.1 Conducted Output Power Measurement 11
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement 12
3.3 Emissions Mask Measurement 13
3.4 Emissions Mask – Out Of Band Emissions Measurement 15
3.5 Field Strength of Spurious Radiation Measurement 16
3.6 Frequency Stability Measurement 19

4 LIST OF MEASURING EQUIPMENT **21**

5 MEASUREMENT UNCERTAINTY **22**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG642201D	Rev. 01	Initial issue of report	Jun. 18, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	—	Report only	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	—	Report only	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< 50+10log$_{10}$(P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< 43+10log$_{10}$(P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< 43+10log$_{10}$(P[Watts])	PASS	Under limit 47.90 dB at 3258.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Rolling Wireless S.a r.l.
8-10, rue Mathias Hardt 1717, Luxembourg

1.2 Manufacturer

Rolling Wireless S.a r.l.
8-10, rue Mathias Hardt 1717, Luxembourg

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	5G Module
Brand Name	Rolling Wireless
Model Name	RW135R-GL
FCC ID	2AX2URW135RGL
IMEI Code	Conducted: 359200990000278 Radiation: 359200990002126
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT. For details, please refer to the RW135R-GL_Operational Description of Product Equality Declaration exhibit separately. After evaluation, the differences will not affect RF performance, so we choose the Sample1 to full test, and Sample2 to verify the worst case for RSE, which is recorded in another report(FG642201F).

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814 ~ 824 MHz
Rx Frequency	859 ~ 869 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	24.52 dBm
Antenna Gain	3.0 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power and Emission Designator

LTE Band 26		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
1.4	814.7 ~ 823.3	0.2735	1M09G7D	0.2377	1M10W7D
3	815.5 ~ 822.5	0.2793	2M77G7D	0.2339	2M73W7D
5	816.5 ~ 821.5	0.2780	4M50G7D	0.2360	4M49W7D
10	819.0	0.2831	8M93G7D	0.2382	8M97W7D
15	824	0.2704	13M4G7D	0.2350	13M4W7D

Note: All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-SZ 03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16 QAM	64 QAM	256 QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v					v		v	
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v		v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v				v			v	v	v
Frequency Stability	26	v					-	v						v		v	
Radiated Spurious Emission	26			v	v	v	-	v				v			v	v	v
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. 4. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power.																

2.2 Connection Diagram of Test System



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC power supply	N/A	N/A	N/A	N/A	N/A
3.	WWAN Antenna	N/A	N/A	N/A	N/A	N/A
4.	Test Jig	N/A	N/A	N/A	N/A	N/A
5.	Earphone	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.0 + 10 = 14.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
15	Channel	-	-	26790
	Frequency	-	-	824
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 $Log_{10}(f/6.1)$ decibels or 50 + 10 $Log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + $10Log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[\text{Watts}])$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
4. battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	May 13, 2026	Jul. 02, 2026	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 25, 2025	May 13, 2026	Dec. 24, 2026	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Dec. 23, 2025	May 13, 2026	Dec. 22, 2027	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	May 13, 2026	Jul. 04, 2026	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 25, 2025	May 13, 2026	Dec. 24, 2026	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 13, 2025	May 13, 2026	Oct. 12, 2026	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 13, 2025	May 13, 2026	Oct. 12, 2026	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	May 13, 2026	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	May 13, 2026	NCR	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Mar. 26, 2026	Apr. 27, 2026~ Apr. 28, 2026	Mar. 25, 2027	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V，3A	Oct. 13, 2025	Apr. 27, 2026~ Apr. 28, 2026	Oct. 12, 2026	Conducted (TH01-SZ)
Power Divider	Titan	P02N005180	923402	0.4GHz~26.5GHz	Nov. 07, 2025	Apr. 27, 2026~ Apr. 28, 2026	Nov. 06, 2026	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 02, 2025	Apr. 27, 2026~ Apr. 28, 2026	Jul. 01, 2026	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 1 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.47 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.31 dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Lorenzo Liu	Temperature :	24~26℃
		Relative Humidity :	50~53%

Conducted Output Power (Average power)

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
Channel						26790
Frequency (MHz)						824
15	QPSK	1	0			24.13
15	QPSK	1	37			24.32
15	QPSK	1	74			24.27
15	QPSK	36	0			23.40
15	QPSK	36	20			23.44
15	QPSK	36	39			23.44
15	QPSK	75	0			23.45
15	16QAM	1	0			23.66
15	16QAM	1	37			23.71
15	16QAM	1	74			23.62
15	16QAM	36	0			22.40
15	16QAM	36	20			22.46
15	16QAM	36	39			22.47
15	16QAM	75	0			22.47
15	64QAM	1	0			22.57
15	64QAM	1	37			22.55
15	64QAM	1	74			22.69
15	64QAM	36	0			21.41
15	64QAM	36	20			21.51
15	64QAM	36	39			21.41
15	64QAM	75	0			21.46
15	256QAM	1	0			18.71
15	256QAM	1	37			18.84
15	256QAM	1	74			18.73
15	256QAM	36	0			18.77
15	256QAM	36	20			18.67
15	256QAM	36	39			18.69
15	256QAM	75	0			18.69
Channel					26740	
Frequency (MHz)					819	
10	QPSK	1	0		24.34	
10	QPSK	1	25		24.52	
10	QPSK	1	49		24.42	

10	QPSK	25	0		23.44	
10	QPSK	25	12		23.37	
10	QPSK	25	25		23.36	
10	QPSK	50	0		23.35	
10	16QAM	1	0		23.76	
10	16QAM	1	25		23.77	
10	16QAM	1	49		23.65	
10	16QAM	25	0		22.42	
10	16QAM	25	12		22.43	
10	16QAM	25	25		22.41	
10	16QAM	50	0		22.44	
10	64QAM	1	0		22.50	
10	64QAM	1	25		22.70	
10	64QAM	1	49		22.56	
10	64QAM	25	0		21.40	
10	64QAM	25	12		21.43	
10	64QAM	25	25		21.42	
10	64QAM	50	0		21.42	
10	256QAM	1	0		19.13	
10	256QAM	1	25		19.22	
10	256QAM	1	49		19.10	
10	256QAM	25	0		18.97	
10	256QAM	25	12		19.08	
10	256QAM	25	25		19.03	
10	256QAM	50	0		19.12	
Channel				26715	26740	26765
Frequency (MHz)				816.5	819	821.5
5	QPSK	1	0	24.10	24.13	24.09
5	QPSK	1	12	24.42	24.44	24.39
5	QPSK	1	24	24.29	24.33	24.30
5	QPSK	12	0	23.33	23.40	23.34
5	QPSK	12	7	23.33	23.34	23.23
5	QPSK	12	13	23.26	23.27	23.31
5	QPSK	25	0	23.21	23.33	23.24
5	16QAM	1	0	23.70	23.73	23.69
5	16QAM	1	12	23.64	23.69	23.70
5	16QAM	1	24	23.62	23.55	23.52
5	16QAM	12	0	22.34	22.36	22.29
5	16QAM	12	7	22.37	22.41	22.26
5	16QAM	12	13	22.29	22.32	22.36
5	16QAM	25	0	22.40	22.42	22.27
5	64QAM	1	0	22.43	22.45	22.38
5	64QAM	1	12	22.58	22.62	22.59
5	64QAM	1	24	22.52	22.46	22.51
5	64QAM	12	0	21.28	21.38	21.26

5	64QAM	12	7	21.38	21.35	21.34
5	64QAM	12	13	21.33	21.35	21.34
5	64QAM	25	0	21.27	21.33	21.30
5	256QAM	1	0	18.98	19.11	19.03
5	256QAM	1	12	19.08	19.15	19.13
5	256QAM	1	24	19.00	19.08	19.07
5	256QAM	12	0	18.85	18.96	18.82
5	256QAM	12	7	19.01	19.01	19.01
5	256QAM	12	13	18.95	18.98	18.85
5	256QAM	25	0	19.02	19.02	18.98
Channel				26705	26740	26775
Frequency (MHz)				815.5	819	822.5
3	QPSK	1	0	24.11	24.21	24.12
3	QPSK	1	8	24.41	24.46	24.38
3	QPSK	1	14	24.30	24.34	24.29
3	QPSK	8	0	23.27	23.40	23.33
3	QPSK	8	4	23.28	23.27	23.22
3	QPSK	8	7	23.31	23.34	23.32
3	QPSK	15	0	23.25	23.26	23.30
3	16QAM	1	0	23.69	23.69	23.67
3	16QAM	1	8	23.66	23.69	23.62
3	16QAM	1	14	23.53	23.64	23.54
3	16QAM	8	0	22.33	22.40	22.31
3	16QAM	8	4	22.36	22.41	22.30
3	16QAM	8	7	22.25	22.34	22.32
3	16QAM	15	0	22.38	22.36	22.31
3	64QAM	1	0	22.45	22.47	22.42
3	64QAM	1	8	22.59	22.62	22.66
3	64QAM	1	14	22.51	22.53	22.43
3	64QAM	8	0	21.29	21.30	21.26
3	64QAM	8	4	21.32	21.36	21.36
3	64QAM	8	7	21.31	21.37	21.31
3	64QAM	15	0	21.29	21.35	21.31
3	256QAM	1	0	18.97	19.05	19.02
3	256QAM	1	8	19.14	19.15	19.16
3	256QAM	1	14	19.03	19.03	18.99
3	256QAM	8	0	18.79	18.90	18.84
3	256QAM	8	4	18.92	19.05	18.97
3	256QAM	8	7	18.91	19.00	18.88
3	256QAM	15	0	19.01	19.04	18.99
Channel				26697	26740	26783
Frequency (MHz)				814.7	819	823.3
1.4	QPSK	1	0	24.08	24.19	24.09
1.4	QPSK	1	3	24.37	24.37	24.30
1.4	QPSK	1	5	24.27	24.36	24.29

1.4	QPSK	3	0	23.34	23.40	23.41
1.4	QPSK	3	1	23.27	23.31	23.23
1.4	QPSK	3	3	23.24	23.32	23.25
1.4	QPSK	6	0	23.24	23.34	23.27
1.4	16QAM	1	0	23.63	23.68	23.66
1.4	16QAM	1	3	23.65	23.76	23.62
1.4	16QAM	1	5	23.58	23.61	23.51
1.4	16QAM	3	0	22.33	22.38	22.30
1.4	16QAM	3	1	22.29	22.39	22.28
1.4	16QAM	3	3	22.29	22.40	22.37
1.4	16QAM	6	0	22.40	22.35	22.29
1.4	64QAM	1	0	22.40	22.40	22.44
1.4	64QAM	1	3	22.51	22.69	22.60
1.4	64QAM	1	5	22.45	22.50	22.42
1.4	64QAM	3	0	21.22	21.39	21.26
1.4	64QAM	3	1	21.37	21.36	21.36
1.4	64QAM	3	3	21.32	21.41	21.28
1.4	64QAM	6	0	21.29	21.32	21.32
1.4	256QAM	1	0	19.01	19.03	18.98
1.4	256QAM	1	3	19.12	19.20	19.20
1.4	256QAM	1	5	18.98	19.02	19.08
1.4	256QAM	3	0	18.80	18.91	18.86
1.4	256QAM	3	1	19.01	19.01	18.94
1.4	256QAM	3	3	18.95	18.94	18.90
1.4	256QAM	6	0	19.00	19.04	19.00

LTE Band 26_Part 90S

26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.34	1.35	3.04	2.99	4.93	5.11	9.77	9.83	-	-	-	-
High CH	-	-	-	-	-	-	-	-	14.33	14.42	-	-

LTE Band 26

Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



High Channel / 15MHz / QPSK



High Channel / 15MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.09	1.10	2.77	2.73	4.50	4.49	8.93	8.97	-	-	-	-
High CH	-	-	-	-	-	-	-	-	13.40	13.43	-	-

LTE Band 26

Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



High Channel / 15MHz / QPSK



High Channel / 15MHz / 16QAM



Emission masks – In-band emissions

LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None

Tx Power 24.19 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95554 MHz	-13.27 dBm	-37.45 dB	-0.27 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	813.99839 MHz	-31.58 dBm	-55.76 dB	-11.58 dB
700.000 kHz	737.500 kHz	300.000 Hz	815.42304 MHz	-68.14 dBm	-92.32 dB	-48.14 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.44018 MHz	-43.27 dBm	-67.45 dB	-30.27 dB

Date: 28.APR.2026 14:35:08

Highest Band Edge / 1RB



Spectrum Emission Mask Standard: None

Tx Power 24.27 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55768 MHz	-44.73 dBm	-69.00 dB	-31.73 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	822.59518 MHz	-67.89 dBm	-92.16 dB	-47.89 dB
700.000 kHz	737.500 kHz	300.000 Hz	824.00696 MHz	-33.09 dBm	-57.36 dB	-13.09 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.03804 MHz*	-11.27 dBm*	-35.54 dB*	1.73 dB*

Date: 28.APR.2026 14:40:16

Lowest Band Edge / 1RB-CP



Date: 28.APR.2026 14:35:32

Highest Band Edge / 1RB-CP



Date: 28.APR.2026 14:40:53

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.96089 MHz	-17.19 dBm	-40.47 dB	-4.19 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	813.99304 MHz	-39.91 dBm	-63.19 dB	-19.91 dB
700.000 kHz	737.500 kHz	300.000 Hz	815.41125 MHz	-40.54 dBm	-63.82 dB	-20.54 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.43804 MHz	-16.57 dBm	-39.85 dB	-3.57 dB

Date: 28.APR.2026 14:39:07

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55125 MHz	-15.62 dBm	-38.94 dB	-2.62 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	822.59304 MHz	-39.22 dBm	-62.54 dB	-19.22 dB
700.000 kHz	737.500 kHz	300.000 Hz	824.01125 MHz	-40.39 dBm	-63.71 dB	-20.39 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04875 MHz	-16.65 dBm	-39.97 dB	-3.65 dB

Date: 28.APR.2026 14:45:30

-

-

Highest Band Edge / Full RB-CP



Date: 28.APR.2026 14:47:23

LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 23.67 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.96196 MHz	-14.38 dBm	-38.05 dB	-1.38 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	813.99732 MHz	-34.74 dBm	-58.40 dB	-14.74 dB
700.000 kHz	737.500 kHz	300.000 Hz	815.42196 MHz	-69.23 dBm	-92.90 dB	-49.23 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.62122 MHz	-44.48 dBm	-68.15 dB	-31.48 dB

Date: 28.APR.2026 14:31:08

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 23.50 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.32522 MHz	-45.27 dBm	-68.77 dB	-32.27 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	822.56732 MHz	-70.01 dBm	-93.51 dB	-50.01 dB
700.000 kHz	737.500 kHz	300.000 Hz	824.00696 MHz	-36.01 dBm	-59.51 dB	-16.01 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.03911 MHz*	-8.67 dBm*	-32.17 dB*	4.33 dB*

Date: 28.APR.2026 14:41:30

Lowest Band Edge / 1 RB-CP



Date: 28.APR.2026 14:34:14

Highest Band Edge / 1 RB-CP



Date: 28.APR.2026 14:42:00

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None

Tx Power 22.22 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95125 MHz	-17.04 dBm	-39.25 dB	-4.04 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	813.99304 MHz	-40.96 dBm	-63.18 dB	-20.96 dB
700.000 kHz	737.500 kHz	300.000 Hz	815.40804 MHz	-41.43 dBm	-63.64 dB	-21.43 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.43804 MHz	-16.84 dBm	-39.05 dB	-3.84 dB

Date: 27.APR.2026 18:44:06

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None

Tx Power 22.32 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.56196 MHz	-18.34 dBm	-40.66 dB	-5.34 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	822.59518 MHz	-40.43 dBm	-62.74 dB	-20.43 dB
700.000 kHz	737.500 kHz	300.000 Hz	824.00804 MHz	-41.10 dBm	-63.42 dB	-21.10 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04232 MHz	-17.16 dBm	-39.48 dB	-4.16 dB

Date: 28.APR.2026 14:43:18

LTE Band 26 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Lowest Band Edge / 1 RB-CP



-

-

Lowest Band Edge / Full RB	Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.11 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.96196 MHz	-19.70 dBm	-40.81 dB	-6.70 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	813.99518 MHz	-42.15 dBm	-63.26 dB	-22.15 dB
700.000 kHz	737.500 kHz	300.000 Hz	815.40911 MHz	-42.50 dBm	-63.62 dB	-22.50 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.45518 MHz	-20.85 dBm	-41.96 dB	-7.85 dB

Date: 27.APR.2026 18:43:21



Spectrum Emission Mask Standard: None
Tx Power 21.05 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.53518 MHz	-21.68 dBm	-42.73 dB	-8.68 dB
-737.500 kHz	-700.000 kHz	300.000 Hz	822.59518 MHz	-42.65 dBm	-63.70 dB	-22.65 dB
700.000 kHz	737.500 kHz	300.000 Hz	824.00911 MHz	-43.52 dBm	-64.57 dB	-23.52 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.05518 MHz	-21.03 dBm	-42.09 dB	-8.03 dB

Date: 27.APR.2026 18:51:23

LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.54 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95982 MHz	-16.21 dBm	-39.75 dB	-3.21 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	813.99196 MHz	-38.06 dBm	-61.60 dB	-18.06 dB
1.500 MHz	1.538 MHz	300.000 Hz	817.01518 MHz	-73.59 dBm	-97.13 dB	-53.59 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.09375 MHz	-47.46 dBm	-71.00 dB	-34.46 dB

Date: 27.APR.2026 18:55:27

Highest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.98 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.76518 MHz	-49.20 dBm	-73.18 dB	-36.20 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	820.99018 MHz	-74.39 dBm	-98.36 dB	-54.39 dB
1.500 MHz	1.538 MHz	300.000 Hz	824.01339 MHz	-38.06 dBm	-62.04 dB	-18.06 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.03839 MHz	-14.33 dBm	-38.31 dB	-1.33 dB

Date: 28.APR.2026 14:58:40

-

-

Highest Band Edge / 1RB-CP



Date: 28.APR.2026 14:59:09

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 22.96 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.96161 MHz	-20.83 dBm	-43.79 dB	-7.83 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	813.99911 MHz	-43.53 dBm	-66.49 dB	-23.53 dB
1.500 MHz	1.538 MHz	300.000 Hz	817.00268 MHz	-42.74 dBm	-65.70 dB	-22.74 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04732 MHz	-19.31 dBm	-42.27 dB	-6.31 dB

Date: 27.APR.2026 18:59:13

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 23.01 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95982 MHz	-17.63 dBm	-40.64 dB	-4.63 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	820.99911 MHz	-41.52 dBm	-64.53 dB	-21.52 dB
1.500 MHz	1.538 MHz	300.000 Hz	824.00089 MHz	-41.96 dBm	-64.97 dB	-21.96 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04554 MHz	-17.66 dBm	-40.67 dB	-4.66 dB

Date: 27.APR.2026 19:07:17

LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Lowest Band Edge / 1 RB-CP



Highest Band Edge / 1 RB-CP



Lowest Band Edge / Full RB	Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None

Tx Power 22.01 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95982 MHz	-21.16 dBm	-43.17 dB	-8.16 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	813.99911 MHz	-44.86 dBm	-66.87 dB	-24.86 dB
1.500 MHz	1.538 MHz	300.000 Hz	817.00446 MHz	-42.93 dBm	-64.94 dB	-22.93 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04911 MHz	-22.43 dBm	-44.44 dB	-9.43 dB

Date: 27.APR.2026 18:58:28



Spectrum Emission Mask Standard: None

Tx Power 22.00 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95268 MHz	-20.36 dBm	-42.37 dB	-7.36 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	820.99732 MHz	-43.97 dBm	-65.97 dB	-23.97 dB
1.500 MHz	1.538 MHz	300.000 Hz	824.00446 MHz	-43.98 dBm	-65.99 dB	-23.98 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04196 MHz	-19.72 dBm	-41.72 dB	-6.72 dB

Date: 27.APR.2026 19:06:32

LTE Band 26 / 3MHz / 64QAM

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.96161 MHz	-19.00 dBm	-41.00 dB	-6.00 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	813.99911 MHz	-41.99 dBm	-64.00 dB	-21.99 dB
1.500 MHz	1.538 MHz	300.000 Hz	817.02946 MHz	-78.63 dBm	-100.63 dB	-58.63 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.06339 MHz	-50.03 dBm	-72.03 dB	-37.03 dB

Date: 27.APR.2026 18:56:58

Highest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	819.87054 MHz	-52.79 dBm	-74.80 dB	-39.79 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	820.99554 MHz	-78.73 dBm	-100.73 dB	-58.73 dB
1.500 MHz	1.538 MHz	300.000 Hz	824.00446 MHz	-41.70 dBm	-63.71 dB	-21.70 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.03839 MHz	-16.66 dBm	-38.67 dB	-3.66 dB

Date: 27.APR.2026 19:05:02

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.94375 MHz	-25.20 dBm	-46.21 dB	-12.20 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	813.99911 MHz	-45.56 dBm	-66.57 dB	-25.56 dB
1.500 MHz	1.538 MHz	300.000 Hz	817.00268 MHz	-44.55 dBm	-65.56 dB	-24.55 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04196 MHz	-21.97 dBm	-42.98 dB	-8.97 dB

Date: 27.APR.2026 18:57:43

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95268 MHz	-20.43 dBm	-41.49 dB	-7.43 dB
-1.538 MHz	-1.500 MHz	300.000 Hz	820.99911 MHz	-44.46 dBm	-65.52 dB	-24.46 dB
1.500 MHz	1.538 MHz	300.000 Hz	824.00268 MHz	-44.98 dBm	-66.04 dB	-24.98 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04196 MHz	-21.69 dBm	-42.76 dB	-8.69 dB

Date: 27.APR.2026 19:05:47

LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.49 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.96116 MHz	-20.65 dBm	-44.14 dB	-7.65 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	813.99866 MHz	-41.78 dBm	-65.27 dB	-21.78 dB
2.500 MHz	2.538 MHz	300.000 Hz	819.02545 MHz	-79.00 dBm	-102.49 dB	-59.00 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.60958 MHz	-52.45 dBm	-75.94 dB	-39.45 dB

Date: 27.APR.2026 19:09:51

Highest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.36 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.37166 MHz	-53.42 dBm	-76.78 dB	-40.42 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	818.99598 MHz	-79.36 dBm	-102.72 dB	-59.36 dB
2.500 MHz	2.538 MHz	300.000 Hz	824.00134 MHz	-41.55 dBm	-64.91 dB	-21.55 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.03884 MHz	-18.91 dBm	-42.27 dB	-5.91 dB

Date: 27.APR.2026 19:17:53

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 22.92 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.94508 MHz	-23.75 dBm	-46.66 dB	-10.75 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	813.98527 MHz	-48.92 dBm	-71.84 dB	-28.92 dB
2.500 MHz	2.538 MHz	300.000 Hz	819.00134 MHz	-46.83 dBm	-69.74 dB	-26.83 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.07903 MHz	-22.25 dBm	-45.17 dB	-9.25 dB

Date: 27.APR.2026 19:13:35

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 22.99 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.95580 MHz	-22.77 dBm	-45.76 dB	-9.77 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	818.98795 MHz	-47.00 dBm	-69.98 dB	-27.00 dB
2.500 MHz	2.538 MHz	300.000 Hz	824.00134 MHz	-46.85 dBm	-69.84 dB	-26.85 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04152 MHz	-21.05 dBm	-44.04 dB	-8.05 dB

Date: 27.APR.2026 19:21:37

LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 23.11 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.92097 MHz	-20.51 dBm	-43.62 dB	-7.51 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	813.99866 MHz	-43.20 dBm	-66.31 dB	-23.20 dB
2.500 MHz	2.538 MHz	300.000 Hz	819.01205 MHz	-77.82 dBm	-100.93 dB	-57.82 dB
2.538 MHz	7.500 MHz	100.000 kHz	820.76982 MHz	-45.78 dBm	-68.89 dB	-32.78 dB

Date: 27.APR.2026 19:10:36

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 22.62 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.87809 MHz	-48.81 dBm	-71.43 dB	-35.81 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	818.98795 MHz	-78.15 dBm	-100.77 dB	-58.15 dB
2.500 MHz	2.538 MHz	300.000 Hz	824.00134 MHz	-42.24 dBm	-64.85 dB	-22.24 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.03884 MHz	-19.16 dBm	-41.77 dB	-6.16 dB

Date: 27.APR.2026 19:18:38

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 22.03 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.96116 MHz	-26.09 dBm	-48.12 dB	-13.09 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	813.98795 MHz	-49.48 dBm	-71.51 dB	-29.48 dB
2.500 MHz	2.538 MHz	300.000 Hz	819.00134 MHz	-47.32 dBm	-69.35 dB	-27.32 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.07099 MHz	-23.81 dBm	-45.84 dB	-10.81 dB

Date: 27.APR.2026 19:12:50

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.98 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.94508 MHz	-23.75 dBm	-45.73 dB	-10.75 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	818.98795 MHz	-48.72 dBm	-70.70 dB	-28.72 dB
2.500 MHz	2.538 MHz	300.000 Hz	824.00134 MHz	-47.73 dBm	-69.71 dB	-27.73 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04688 MHz	-23.39 dBm	-45.37 dB	-10.39 dB

Date: 27.APR.2026 19:20:52

LTE Band 26 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 22.12 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95848 MHz	-23.53 dBm	-45.65 dB	-10.53 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	813.99866 MHz	-44.88 dBm	-67.00 dB	-24.88 dB
2.500 MHz	2.538 MHz	300.000 Hz	819.03616 MHz	-79.23 dBm	-101.35 dB	-59.23 dB
2.538 MHz	7.500 MHz	100.000 kHz	822.69105 MHz	-53.05 dBm	-75.17 dB	-40.05 dB

Date: 27.APR.2026 19:11:21

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.82 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.51100 MHz	-53.28 dBm	-75.10 dB	-40.28 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	818.98527 MHz	-79.12 dBm	-100.94 dB	-59.12 dB
2.500 MHz	2.538 MHz	300.000 Hz	824.00134 MHz	-43.48 dBm	-65.30 dB	-23.48 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.03884 MHz	-20.59 dBm	-42.41 dB	-7.59 dB

Date: 27.APR.2026 19:19:23

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.01 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.96116 MHz	-25.33 dBm	-46.34 dB	-12.33 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	813.99866 MHz	-50.74 dBm	-71.75 dB	-30.74 dB
2.500 MHz	2.538 MHz	300.000 Hz	819.00134 MHz	-48.80 dBm	-69.81 dB	-28.80 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.03884 MHz	-24.97 dBm	-45.98 dB	-11.97 dB

Date: 27.APR.2026 19:12:06

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.94 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.95580 MHz	-26.51 dBm	-47.45 dB	-13.51 dB
-2.538 MHz	-2.500 MHz	300.000 Hz	818.98795 MHz	-50.36 dBm	-71.30 dB	-30.36 dB
2.500 MHz	2.538 MHz	300.000 Hz	824.00134 MHz	-49.94 dBm	-70.88 dB	-29.94 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.05760 MHz	-26.50 dBm	-47.44 dB	-13.50 dB

Date: 27.APR.2026 19:20:08

LTE Band 26 / 10MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.43 dBm Tx Bandwidth 10.000 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.93928 MHz	-32.82 dBm	-56.25 dB	-19.82 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-53.69 dBm	-77.12 dB	-33.69 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-79.39 dBm	-102.82 dB	-59.39 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.86816 MHz	-53.19 dBm	-76.62 dB	-40.19 dB

Date: 27.APR.2026 19:24:12

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.31 dBm Tx Bandwidth 10.000 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	811.13470 MHz	-53.53 dBm	-76.85 dB	-40.53 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-79.58 dBm	-102.89 dB	-59.58 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-53.80 dBm	-77.12 dB	-33.80 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.03929 MHz	-29.14 dBm	-52.45 dB	-16.14 dB

Date: 27.APR.2026 19:27:56

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 23.01 dBm Tx Bandwidth 10.000 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.93570 MHz	-30.57 dBm	-53.58 dB	-17.57 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-55.64 dBm	-78.65 dB	-35.64 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-54.20 dBm	-77.21 dB	-34.20 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.15361 MHz	-29.69 dBm	-52.70 dB	-16.69 dB

Date: 27.APR.2026 19:28:41

LTE Band 26 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask — Standard: None
Tx Power 22.63 dBm — Tx Bandwidth 10.000 MHz — RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.96071 MHz	-28.04 dBm	-50.68 dB	-15.04 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-52.97 dBm	-75.61 dB	-32.97 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.00937 MHz	-79.29 dBm	-101.93 dB	-59.29 dB
5.038 MHz	10.000 MHz	100.000 kHz	827.48696 MHz	-47.89 dBm	-70.52 dB	-34.89 dB

Date: 27.APR.2026 19:24:56

Lowest Band Edge / 1 RB



Spectrum Emission Mask — Standard: None
Tx Power 22.80 dBm — Tx Bandwidth 10.000 MHz — RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	810.62023 MHz	-52.34 dBm	-75.14 dB	-39.34 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.98312 MHz	-79.54 dBm	-102.33 dB	-59.54 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-53.97 dBm	-76.76 dB	-33.97 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.03929 MHz	-30.94 dBm	-53.73 dB	-17.94 dB

Date: 27.APR.2026 19:27:11

Lowest Band Edge / Full RB



Spectrum Emission Mask — Standard: None
Tx Power 21.96 dBm — Tx Bandwidth 10.000 MHz — RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.96071 MHz	-31.92 dBm	-53.89 dB	-18.92 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-57.33 dBm	-79.29 dB	-37.33 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.01688 MHz	-55.30 dBm	-77.26 dB	-35.30 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.06072 MHz	-30.93 dBm	-52.89 dB	-17.93 dB

Date: 27.APR.2026 19:29:26

LTE Band 26 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.96071 MHz	-31.76 dBm	-53.28 dB	-18.76 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-55.59 dBm	-77.11 dB	-35.59 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.02437 MHz	-79.31 dBm	-100.83 dB	-59.31 dB
5.038 MHz	10.000 MHz	100.000 kHz	826.76169 MHz	-53.23 dBm	-74.75 dB	-40.23 dB

Date: 27.APR.2026 19:25:42

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.52127 MHz	-53.53 dBm	-75.12 dB	-40.53 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.98688 MHz	-79.66 dBm	-101.25 dB	-59.66 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-56.68 dBm	-78.27 dB	-36.68 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.05715 MHz	-35.98 dBm	-57.57 dB	-22.98 dB

Date: 27.APR.2026 19:26:26

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-10.000 MHz	-5.038 MHz	100.000 kHz	813.88569 MHz	-33.11 dBm	-54.09 dB	-20.11 dB
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-58.73 dBm	-79.72 dB	-38.73 dB
5.000 MHz	5.038 MHz	300.000 Hz	824.02813 MHz	-57.01 dBm	-78.00 dB	-37.01 dB
5.038 MHz	10.000 MHz	100.000 kHz	824.09288 MHz	-31.77 dBm	-52.75 dB	-18.77 dB

Date: 27.APR.2026 19:30:55

LTE Band 26 / 15MHz

Highest Band Edge / 1RB QPSK



Spectrum Emission Mask Standard: None
Tx Power -37.54 dBm Tx Bandwidth 3.840 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-15.000 MHz	-7.538 MHz	100.000 kHz	816.45982 MHz	-31.39 dBm	6.15 dB	-18.39 dB
-7.538 MHz	-7.500 MHz	300.000 Hz	816.49732 MHz	-53.46 dBm	-15.91 dB	-33.46 dB
7.500 MHz	7.538 MHz	300.000 Hz	831.51339 MHz	-79.51 dBm	-41.97 dB	-59.51 dB
7.538 MHz	15.000 MHz	100.000 kHz	832.72946 MHz	-48.26 dBm	-10.71 dB	-35.26 dB

Date: 27.APR.2026 19:41:13

Highest Band Edge / Full RB QPSK



Spectrum Emission Mask Standard: None
Tx Power 17.81 dBm Tx Bandwidth 3.840 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-15.000 MHz	-7.538 MHz	100.000 kHz	816.30446 MHz	-33.73 dBm	-51.54 dB	-20.73 dB
-7.538 MHz	-7.500 MHz	300.000 Hz	816.49732 MHz	-57.81 dBm	-75.62 dB	-37.81 dB
7.500 MHz	7.538 MHz	300.000 Hz	831.52411 MHz	-58.14 dBm	-75.95 dB	-38.14 dB
7.538 MHz	15.000 MHz	100.000 kHz	831.54018 MHz	-32.60 dBm	-50.41 dB	-19.60 dB

Date: 27.APR.2026 19:37:31

Highest Band Edge / 1 RB 16QAM



Spectrum Emission Mask Standard: None
Tx Power -37.81 dBm Tx Bandwidth 3.840 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-15.000 MHz	-7.538 MHz	100.000 kHz	816.32054 MHz	-32.11 dBm	5.71 dB	-19.11 dB
-7.538 MHz	-7.500 MHz	300.000 Hz	816.49732 MHz	-54.28 dBm	-16.47 dB	-34.28 dB
7.500 MHz	7.538 MHz	300.000 Hz	831.53482 MHz	-79.61 dBm	-41.80 dB	-59.61 dB
7.538 MHz	15.000 MHz	100.000 kHz	832.72411 MHz	-48.58 dBm	-10.77 dB	-35.58 dB

Date: 27.APR.2026 19:40:29

Highest Band Edge / Full RB 16QAM



Spectrum Emission Mask Standard: None
Tx Power 16.80 dBm Tx Bandwidth 3.840 MHz RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-15.000 MHz	-7.538 MHz	100.000 kHz	816.45982 MHz	-35.32 dBm	-52.12 dB	-22.32 dB
-7.538 MHz	-7.500 MHz	300.000 Hz	816.49732 MHz	-59.67 dBm	-76.46 dB	-39.67 dB
7.500 MHz	7.538 MHz	300.000 Hz	831.50804 MHz	-59.81 dBm	-76.61 dB	-39.81 dB
7.538 MHz	15.000 MHz	100.000 kHz	831.55625 MHz	-34.24 dBm	-51.03 dB	-21.24 dB

Date: 27.APR.2026 19:38:15

LTE Band 26 / 15MHz

Highest Band Edge / 1 RB 64QAM



Spectrum Emission Mask — Standard: None

Tx Power -37.99 dBm — Tx Bandwidth 3.840 MHz — RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-15.000 MHz	-7.538 MHz	100.000 kHz	816.44375 MHz	-32.54 dBm	5.45 dB	-19.54 dB
-7.538 MHz	-7.500 MHz	300.000 Hz	816.49732 MHz	-55.40 dBm	-17.41 dB	-35.40 dB
7.500 MHz	7.538 MHz	300.000 Hz	831.53482 MHz	-79.67 dBm	-41.68 dB	-59.67 dB
7.538 MHz	15.000 MHz	100.000 kHz	832.67054 MHz	-49.28 dBm	-11.29 dB	-36.28 dB

Highest Band Edge / Full RB 64QAM



Spectrum Emission Mask — Standard: None

Tx Power 15.75 dBm — Tx Bandwidth 3.840 MHz — RBW 100.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-15.000 MHz	-7.538 MHz	100.000 kHz	816.45982 MHz	-37.89 dBm	-53.64 dB	-24.89 dB
-7.538 MHz	-7.500 MHz	300.000 Hz	816.46518 MHz	-63.29 dBm	-79.03 dB	-43.29 dB
7.500 MHz	7.538 MHz	300.000 Hz	831.51875 MHz	-62.44 dBm	-78.19 dB	-42.44 dB
7.538 MHz	15.000 MHz	100.000 kHz	831.58839 MHz	-37.51 dBm	-53.25 dB	-24.51 dB

Emission masks – Out of band emissions

LTE Band 26 / 1.4MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	636.73005 MHz	-53.34 dBm	-40.34 dB
839.000 MHz	1.000 GHz	100.000 kHz	973.81034 MHz	-52.79 dBm	-39.79 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.55486 GHz	-42.37 dBm	-29.37 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.92626 GHz	-37.90 dBm	-24.90 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00625 GHz	-38.27 dBm	-25.27 dB

Date: 27.APR.2026 18:45:57

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	769.29783 MHz	-53.27 dBm	-40.27 dB
839.000 MHz	1.000 GHz	100.000 kHz	967.53448 MHz	-52.79 dBm	-39.79 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.63334 GHz	-42.24 dBm	-29.24 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.91926 GHz	-37.74 dBm	-24.74 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00025 GHz	-38.13 dBm	-25.13 dB

Date: 27.APR.2026 18:47:04

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	800.79667 MHz	-53.38 dBm	-40.38 dB
839.000 MHz	1.000 GHz	100.000 kHz	968.01724 MHz	-52.78 dBm	-39.78 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.50887 GHz	-42.50 dBm	-29.50 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.93576 GHz	-37.87 dBm	-24.87 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.01325 GHz	-38.24 dBm	-25.24 dB

Date: 27.APR.2026 18:53:59

LTE Band 26 / 3MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	794.17558 MHz	-53.21 dBm	-40.21 dB
839.000 MHz	1.000 GHz	100.000 kHz	959.24713 MHz	-52.38 dBm	-39.38 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.98825 GHz	-42.35 dBm	-29.35 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.96425 GHz	-37.81 dBm	-24.81 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.02124 GHz	-38.17 dBm	-25.17 dB

Date: 27.APR.2026 19:00:20

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	807.07696 MHz	-53.60 dBm	-40.60 dB
839.000 MHz	1.000 GHz	100.000 kHz	979.84483 MHz	-52.95 dBm	-39.95 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.48038 GHz	-42.40 dBm	-29.40 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.90276 GHz	-37.83 dBm	-24.83 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.02024 GHz	-38.33 dBm	-25.33 dB

Date: 27.APR.2026 19:01:26

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	804.74011 MHz	-53.27 dBm	-40.27 dB
839.000 MHz	1.000 GHz	100.000 kHz	980.08621 MHz	-52.87 dBm	-39.87 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.52437 GHz	-42.34 dBm	-29.34 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.93926 GHz	-38.02 dBm	-25.02 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.01075 GHz	-38.01 dBm	-25.01 dB

Date: 27.APR.2026 19:08:24

LTE Band 26 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	807.41776 MHz	-53.65 dBm	-40.65 dB
839.000 MHz	1.000 GHz	100.000 kHz	943.87931 MHz	-52.80 dBm	-39.80 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.63234 GHz	-42.29 dBm	-29.29 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99575 GHz	-37.83 dBm	-24.83 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.01975 GHz	-38.24 dBm	-25.24 dB

Date: 27.APR.2026 19:14:42

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	787.65187 MHz	-53.32 dBm	-40.32 dB
839.000 MHz	1.000 GHz	100.000 kHz	977.18966 MHz	-52.76 dBm	-39.76 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.63834 GHz	-42.38 dBm	-29.38 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98775 GHz	-37.90 dBm	-24.90 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00075 GHz	-38.13 dBm	-25.13 dB

Date: 27.APR.2026 19:15:48

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	763.99122 MHz	-53.52 dBm	-40.52 dB
839.000 MHz	1.000 GHz	100.000 kHz	947.82184 MHz	-52.84 dBm	-39.84 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.47238 GHz	-42.41 dBm	-29.41 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.92476 GHz	-37.82 dBm	-24.82 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.01025 GHz	-38.28 dBm	-25.28 dB

Date: 27.APR.2026 19:22:44

LTE Band 26 / 10MHz
Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	739.55162 MHz	-53.70 dBm	-40.70 dB
839.000 MHz	1.000 GHz	100.000 kHz	985.55747 MHz	-52.92 dBm	-39.92 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.63084 GHz	-42.48 dBm	-29.48 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.92188 GHz	-37.91 dBm	-24.91 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00575 GHz	-38.16 dBm	-25.16 dB

Date: 27.APR.2026 19:34:44

LTE Band 26 / 15MHz
Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	809.000 MHz	100.000 kHz	636.58399 MHz	-53.27 dBm	-40.27 dB
839.000 MHz	1.000 GHz	100.000 kHz	970.10920 MHz	-53.07 dBm	-40.07 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.47438 GHz	-42.42 dBm	-29.42 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.90476 GHz	-37.69 dBm	-24.69 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.02574 GHz	-38.00 dBm	-25.00 dB

Date: 27.APR.2026 19:42:08

Frequency Stability

Test Conditions		LTE Band 26 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 1.4MHz	≤2.5ppm
		Deviation (ppm)	Result
50	Normal Voltage	0.0018	PASS
40	Normal Voltage	0.0083	
30	Normal Voltage	0.0087	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0088	
0	Normal Voltage	0.0095	
-10	Normal Voltage	0.0088	
-20	Normal Voltage	0.0093	
-30	Normal Voltage	0.0084	
20	Maximum Voltage	0.0022	
20	Normal Voltage	0.0000	
20	Minimum Voltage	0.0094	

Note:

1. Normal Voltage = 3.3 V. ; Minimum Voltage = 3.135 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Wenbo Xiao	Temperature :	22~25℃
		Relative Humidity :	48~52%

LTE Band 26 / 10MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1628.3	-65.87	-13	-52.87	-75.36	-69.10	3.98	9.36	H
	2442.45	-62.73	-13	-49.73	-76.73	-66.28	4.85	10.55	H
	3256.6	-61.16	-13	-48.16	-77.50	-66.09	5.50	12.58	H
	1628.3	-65.37	-13	-52.37	-74.76	-68.60	3.98	9.36	V
	2442.45	-62.76	-13	-49.76	-76.74	-66.31	4.85	10.55	V
	3256.6	-61.11	-13	-48.11	-77.31	-66.04	5.50	12.58	V
Middle	1635.3	-65.62	-13	-52.62	-75.11	-68.87	4.00	9.40	H
	2452.95	-62.37	-13	-49.37	-76.37	-65.94	4.88	10.60	H
	3270.6	-61.06	-13	-48.06	-77.26	-65.99	5.52	12.60	H
	1635.3	-65.97	-13	-52.97	-75.36	-69.22	4.00	9.40	V
	2452.95	-62.27	-13	-49.27	-76.25	-65.84	4.88	10.60	V
	3270.6	-61.58	-13	-48.58	-77.61	-66.51	5.52	12.60	V
Highest	1642.3	-65.87	-13	-52.87	-75.38	-69.04	4.10	9.42	H
	2463.45	-63.07	-13	-50.07	-77.02	-66.65	4.90	10.63	H
	3284.6	-61.58	-13	-48.58	-77.81	-66.50	5.55	12.62	H
	1642.3	-65.72	-13	-52.72	-74.97	-68.89	4.10	9.42	V
	2463.45	-62.87	-13	-49.87	-76.79	-66.45	4.90	10.63	V
	3284.6	-61.92	-13	-48.92	-77.98	-66.84	5.55	12.62	V

LTE Band 26 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1629	-65.19	-13	-52.19	-74.68	-68.44	4.00	9.40	H
	2443.5	-62.65	-13	-49.65	-76.65	-66.22	4.88	10.60	H
	3258	-60.90	-13	-47.90	-77.27	-65.83	5.52	12.60	H
	1629	-65.50	-13	-52.50	-74.89	-68.75	4.00	9.40	V
	2443.5	-62.58	-13	-49.58	-76.56	-66.15	4.88	10.60	V
	3258	-61.14	-13	-48.14	-77.37	-66.07	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 15MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1634.5	-65.38	-13	-52.38	-74.87	-68.55	4.10	9.42	H
	2451.75	-62.84	-13	-49.84	-76.84	-66.42	4.90	10.63	H
	3269	-61.48	-13	-48.48	-77.85	-66.40	5.55	12.62	H
	1634.5	-65.94	-13	-52.94	-75.33	-69.11	4.10	9.42	V
	2451.75	-62.91	-13	-49.91	-76.89	-66.49	4.90	10.63	V
	3269	-61.22	-13	-48.22	-77.45	-66.14	5.55	12.62	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.