

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093) and
IEEE Std 1528-2013**

Product Name: Smart Phone

Model No.: Blade20 Turbo

Serial Model: Refer to page 8

Brand Name: DOOGEE

Report No.: AiTSZ-250220046FW1

FCC ID: 2AX4Y-BLADE20TURBO

Prepared for

Shenzhen DOOGEE Hengtong Technology CO.,LTD
B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No. 22, Dafu Industrial Zone,
Guanlan Aobei Community, Guanlan Street, Longhua New District,
Shenzhen, Guangdong China

Prepared by

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai
Street, Bao'an District, Shenzhen, Guangdong, China
Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen DOOGEE Hengtong Technology CO.,LTD
 B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No.
Address : 22, Dafu Industrial Zone, Guanlan Aobei Community, Guanlan
 Street, Longhua New District, Shenzhen, Guangdong China
Manufacturer's Name : Shenzhen DOOGEE Hengtong Technology CO.,LTD
 B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No.
Address : 22, Dafu Industrial Zone, Guanlan Aobei Community, Guanlan
 Street, Longhua New District, Shenzhen, Guangdong China

Product description

Product name : Smart Phone
Trademark : DOOGEE
Model and/or type reference : Blade20 Turbo
Serial Model..... : Refer to page 8
 FCC 47 CFR Part 2(2.1093)

Standards : IEEE Std 1528-2013
 Published RF exposure KDB procedures

This device described above has been tested by Guangdong Asia Hongke Test Technology Limited. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited, this document may be altered or revised by Guangdong Asia Hongke Test Technology Limited, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... : Feb. 10, 2025 ~ Feb. 19, 2025
Date of Issue..... : Mar. 25, 2025
Test Result..... : **Pass**

Reviewed by: 
 Simba Huang

Approved by: 
 Seal.chen



※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Mar. 25, 2025	Seal.chen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits	6
1.2. Statement of Compliance.....	7
1.3. EUT Description	8
1.4. Test specification(s)	10
1.5. Ambient Condition	10
2. SAR Measurement System	11
2.1. SATIMO SAR Measurement Set-up Diagram	11
2.2. Robot	12
2.3. Probe	13
2.3.1. E-Field Probe Calibration.....	13
2.4. Phantoms	14
2.5. Technical Data	15
2.6. Device Holder	16
2.7. Test Equipment List	17
3. SAR Measurement Procedures	19
3.1. Power Reference.....	19
3.2. Area scan & Zoom scan	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure.....	22
4.1. Tissue Verification.....	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR measurement variabilit.....	26
6. SAR Measurement Uncertainty.....	27
7. RF Exposure Positions	28
7.1. Ear and handset reference point	28
7.2. Definition of the cheek position	28
7.3. Definition of the tilt position	30
7.4. Body Worn Accessory.....	30
7.5. Wireless Router Devices	31
8. RF Output Power	32
8.1. GSM Conducted Power	32
8.2. WCDMA Conducted Power.....	33
8.3. LTE Conducted Power.....	36
8.4. Wi-Fi & BT Output Power	54

9. Antenna Location.....	56
10. Stand-alone SAR test exclusion	57
11. SAR Measurement Results.....	58
12. Simultaneous Transmission Analysis.....	81
Appendix A. Photo documentation	82
Appendix B. System Check Plots	83
Appendix C. SAR Test Plots.....	98
Appendix D. Calibration Certificate	184

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
HEAD AND TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing as follows.

Band	Max SAR Value Reported(W/kg)		
	1-g Head (Separation distance of 0mm)	1-g Body&Hotspot (Separation distance of 10mm)	Max SAR Summation
GSM850	0.351	0.307	Head: 1.550 Body: 1.333 Hotspot: 1.333
GSM1900	0.304	0.255	
WCDMA Band II	0.082	0.377	
WCDMA Band IV	0.128	0.400	
WCDMA Band V	0.288	0.294	
LTE band 2	0.456	0.406	
LTE band 4	0.465	0.469	
LTE band 5	0.305	0.274	
LTE band 7	0.297	0.540	
LTE band 25	0.615	0.510	
LTE band 26a	0.156	0.184	
LTE band 26b	0.093	0.105	
LTE band 38	0.236	0.480	
LTE band 41	0.388	0.647	
LTE band 66	0.069	0.418	
2.4GHz WLAN ANT1	0.267	0.255	
2.4GHz WLAN ANT2	0.262	0.205	
5.2GHz WLAN ANT1	0.564	0.563	
5.2GHz WLAN ANT2	0.371	0.105	
5.8GHz WLAN ANT1	0.580	0.580	
5.8GHz WLAN ANT2	0.252	0.106	

NOTE: The Max SAR Summation is calculated based on the same configuration and test position.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093), and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	Smart Phone		
Model Name	Blade20 Turbo		
Family Model	Blade20 Max, Blade20 Play, Blade20 Pro Max, Blade20 Power, Blade20 Plus, Blade20 Energy, Blade20 Pro Energy, Blade20 Ultra Energy, Blade20 Max Energy, Blade20 Play Energy, Blade20 X		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna Type	PIFA Antenna		
Power rating:	DC 3.87V 10300mAh 39.86Wh Rechargeable Li-ion battery		
Hardware version	M1703-MUB-V2		
Software version	DOOGEE-Blade20 Turbo-EEA-Android15.0-20250221		
Device Operating Configurations			
Supporting Mode(s)	GSM850/1900,WCDMABand2/4/5,LTEBand2/4/5/7/25/26a/26b/38/41/66, WLAN 2.4G/5.2G/5.8G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 25	1850-1915	1930-1995
	LTE Band 26a	814-824	859-869
	LTE Band 26b	824-849	869-894
	LTE Band 38	2570-2620	
	LTE Band 41	2535-2655	
	LTE Band 66	1710-1780	2110-2200
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	

GPRS Multislot Class(12)	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
EGPRS Multislot Class(12)	Max Number of Timeslots in Uplink	4
	Max Number of Timeslots in Downlink	4
	Max Total Timeslot	5
Power Class	4, tested with power level 5(GSM 850)	
	1, tested with power level 0(GSM 1900)	
	3, tested with power control "all 1"(WCDMA Band 2)	
	3, tested with power control "all 1"(WCDMA Band 4)	
	3, tested with power control "all 1"(WCDMA Band 5)	
	3, tested with power control all Max.(LTE Band 2)	
	3, tested with power control all Max.(LTE Band 4)	
	3, tested with power control all Max.(LTE Band 5)	
	3, tested with power control all Max.(LTE Band 7)	
	3, tested with power control all Max.(LTE Band 25)	
	3, tested with power control all Max.(LTE Band 26a)	
	3, tested with power control all Max.(LTE Band 26b)	
	3, tested with power control all Max.(LTE Band 38)	
	3, tested with power control all Max.(LTE Band 41)	
	3, tested with power control all Max.(LTE Band 66)	

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe EPGO 0523-403 with following specifications is used.



- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within $\pm 0.25\text{dB}$. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. Phantoms


For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



SAM

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.6. Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

2.7. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	EPGO 0523-403	Sep. 11, 2024	Sep. 10, 2025
☐	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DI P 0G900-348	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Feb. 21, 2024	Feb. 20, 2027
☐	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Feb. 21, 2024	Feb. 20, 2027
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	Jul. 01, 2024	Jun. 30, 2025
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	Jul. 01, 2024	Jun. 30, 2025
☒	R&S	Universal radio communication tester	CMU200	117858	Jul. 01, 2024	Jun. 30, 2025
☒	R&S	Wideband radio communication tester	CMW500	116581	Jul. 01, 2024	Jun. 30, 2025
☒	HP	Network Analyzer	8753D	3410J01136	Jul. 01, 2024	Jun. 30, 2025

☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power meter	E4419B	MY45102538	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power meter	E4419B	MY45102140	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power meter	E4419B	MY45102215	Jul. 01, 2024	Jun. 30, 2025
☒	JFW	attenuator	50FPE-006	4360846-494-4	Jul. 01, 2024	Jun. 30, 2025
☒	JFW	attenuator	50FPE-006	4360846-492-1	Jul. 01, 2024	Jun. 30, 2025
☒	JFW	attenuator	50FPE-006	4360846-490-6	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power sensor	E9301A	MY41495644	Jul. 01, 2024	Jun. 30, 2025
☒	Agilent	Power sensor	E9301A	US39212148	Jul. 01, 2024	Jun. 30, 2025
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2024	Jul. 16, 2027
☒	MVG	SAR Phantom	SSM2	SN 24/11 SAM87	NCR	NCR
☒	MVG	Device Holder	SMPPD	SN 24/11 MSH73	NCR	NCR

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For Wi-Fi/BT power measurement, use engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure Wi-Fi/BT output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan

above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx _{Area} , Δy _{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx _{Zoom} , Δy _{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz _{Zoom} (n)		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	Δz _{Zoom} (1): between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		Δz _{Zoom} (n>1): between subsequent points	≤ 1.5 · Δz _{Zoom} (n-1)	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine these highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists of a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scans to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
	750	835	900	1800	1900	2000	2450	2600	5200	5800
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.



4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	$\sigma \text{ (S/m)} (\pm 5\%)$	ϵ_r	$\sigma \text{ (S/m)}$		
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	42.01	0.94	21.1 °C	Feb. 10, 2025
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.61	1.41	21.2 °C	Feb. 12, 2025
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	41.42	1.39	21.4 °C	Feb. 14, 2025
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	40.41	1.82	21.6 °C	Feb. 16, 2025
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	39.43	1.99	21.5 °C	Feb. 17, 2025
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	37.40	4.51	21.0 °C	Feb. 18, 2025
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	35.30	5.27	21.3 °C	Feb. 19, 2025

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Power fed to reference dipole (mW)	Measured SAR Value		Measured SAR (Normalized to 1W)		Target SAR Value (1W)		Deviation (%)		Test Date
		1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	
835MHz	100	1.011	0.612	10.11	6.12	9.40	6.28	7.55%	-2.55%	Feb. 10, 2025
1800MHz	100	3.832	2.025	38.32	20.25	37.06	20.01	3.40%	1.20%	Feb. 12, 2025
1900MHz	100	4.154	2.153	41.54	21.53	39.69	20.92	4.66%	2.92%	Feb. 14, 2025
2450MHz	100	5.184	2.359	51.84	23.59	50.05	23.80	3.58%	-0.88%	Feb. 16, 2025
2600MHz	100	5.433	2.523	54.33	25.23	54.16	24.85	0.31%	1.53%	Feb. 17, 2025
5200MHz	100	14.712	5.212	147.12	52.12	162.59	56.21	-9.51%	-7.28%	Feb. 18, 2025
5800MHz	100	16.421	5.623	164.21	56.23	182.2	61.32	-9.87%	-8.30%	Feb. 19, 2025

5. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.

3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

6. SAR Measurement Uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

7. RF Exposure Positions

7.1. Ear and handset reference point

Figure 7.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 7.1.1 Front, back, and side views of SAM phantom

7.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 7.2.1 and Figure 7.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 7.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 7.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 7.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line

passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 7.2.3. The actual rotation angles should be documented in the test report.




Fig 7.2.1 Handset vertical and horizontal reference lines—fixed case




Fig 7.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 7.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

7.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 7.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 7.3.1 – Tilt position of the wireless device on the left side of SAM

7.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 7.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do

not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 7.4.1 – Test positions for body-worn devices

7.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The —Portable Hotspot|| feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

8. RF Output Power

8.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Factor	Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	128	189	251		Tune-up	128	189	251
Frequency (MHz)		824.2	836.4	848.8			824.2	836.4	848.8
GSM (GMSK)	33.50	32.92	33.04	32.88	/	/	/	/	/
GPRS(GMSK,1 Tx slot)	33.50	32.92	33.03	32.87	-9.03	24.47	23.89	24.00	23.84
GPRS(GMSK,2 Tx slot)	32.50	32.06	32.18	32.01	-6.02	26.48	26.04	26.16	25.99
GPRS(GMSK,3 Tx slot)	30.50	30.13	30.24	30.05	-4.26	26.24	25.87	25.98	25.79
GPRS(GMSK,4 Tx slot)	29.50	29.06	29.17	28.98	-3.01	26.49	26.05	26.16	25.97
GPRS(EDGE,1 Tx slot)	27.50	26.09	26.74	27.05	-9.03	18.47	17.06	17.71	18.02
GPRS(EDGE,2 Tx slot)	26.00	24.94	25.66	25.90	-6.02	19.98	18.92	19.64	19.88
GPRS(EDGE,3 Tx slot)	24.00	22.86	23.51	23.76	-4.26	19.74	18.60	19.25	19.50
GPRS(EDGE,4 Tx slot)	23.00	21.82	22.37	22.68	-3.01	19.99	18.81	19.36	19.67

Band GSM1900	Burst-Averaged output Power (dBm)				Factor	Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	512	661	810		Tune-up	512	661	810
Frequency (MHz)		1850.2	1880	1909.8			1850.2	1880	1909.8
GSM (GMSK)	31.00	30.43	30.70	30.46	/	/	/	/	/
GPRS(GMSK,1 Tx slot)	31.00	30.44	30.71	30.48	-9.03	21.97	21.41	21.68	21.45
GPRS(GMSK,2 Tx slot)	30.00	29.39	29.66	29.42	-6.02	23.98	23.37	23.64	23.40
GPRS(GMSK,3 Tx slot)	28.00	27.26	27.53	27.25	-4.26	23.74	23.00	23.27	22.99
GPRS(GMSK,4 Tx slot)	26.50	26.17	26.49	26.16	-3.01	23.49	23.16	23.48	23.15
GPRS(EDGE,1 Tx slot)	26.00	25.23	25.53	25.23	-9.03	16.97	16.20	16.50	16.20
GPRS(EDGE,2 Tx slot)	25.00	24.29	24.62	24.32	-6.02	18.98	18.27	18.60	18.30
GPRS(EDGE,3 Tx slot)	23.00	22.51	22.76	22.39	-4.26	18.74	18.25	18.50	18.13
GPRS(EDGE,4 Tx slot)	22.00	21.56	21.78	21.39	-3.01	18.99	18.55	18.77	18.38

Note:

Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme.

Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link

Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link

Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link

SAR testing was performed on the maximum frame-averaged power mode.

The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum

Burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB

Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB

Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB

Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB

8.2. WCDMA Conducted Power

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

1. Release99 Setup Configuration

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm1
	β_c/β_d	8/15

2. HSDPA Setup Configuration

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs} = \beta_{hs}/\beta_c$	30/15			

3. HSUPA Setup Configuration

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm1				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	15/15
	β_{ec}	209/225	12/15	30/15	2/15	24/15
	β_c/β_d	11/15	6/15	15/9	2/15	15/15
	β_{hs}	22/15	12/15	30/15	4/15	30/15
	β_{ed}	1309/225	94/75	47/15 47/15	56/75	134/15
	CM (dB)	1.0	3.0	2.0	3.0	1.0
HSDPA Specific Settings	D_{ACK}	8				
	D_{NAK}	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				

HSUPA Specific Settings	CQI Repetition Factor (Table 5.2B.4)	2				
	Ahs = β_{hs}/β_c	30/15				
	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9

4. WCDMA Conducted Power Results

Choose the highest output power mode RMC 12.2Kbps for Band VIII/I at middle channel to test SAR and determine the worst configuration for further high/low channel test.

WCDMA Band II	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC12.2K	20.00	19.90	19.68	18.57
HSDPA Sub 1	19.50	19.19	19.12	17.80
HSDPA Sub 2	19.00	18.65	18.47	17.33
HSDPA Sub 3	19.00	18.54	18.29	17.15
HSDPA Sub 4	18.50	18.48	18.29	17.18
HSUPA Sub 1	18.00	17.63	17.43	16.32
HSUPA Sub 2	18/20/20	17.38	19.70	19.80
HSUPA Sub 3	21.50	20.70	21.05	20.43
HSUPA Sub 4	20.00	18.88	19.75	19.50
HSUPA Sub 5	21.50	20.81	21.11	20.86

WCDMA Band IV	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC12.2K	23.00	22.85	22.84	22.52
HSDPA Sub 1	22.50	22.02	22.03	21.76
HSDPA Sub 2	21.50	21.42	21.47	21.20
HSDPA Sub 3	21.50	21.36	21.36	21.11
HSDPA Sub 4	21.50	21.35	21.39	21.07
HSUPA Sub 1	20.50	20.46	20.43	19.24
HSUPA Sub 2	19.50	19.46	19.24	18.97
HSUPA Sub 3	20.50	20.00	20.21	20.06
HSUPA Sub 4	17.50	17.43	17.47	17.20
HSUPA Sub 5	20.50	20.33	20.25	19.96

WCDMA Band V	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	21.50	21.34	21.44	21.39
HSDPA Sub 1	22.50	21.91	21.81	22.04
HSDPA Sub 2	21.50	21.39	21.39	21.43
HSDPA Sub 3	21.50	21.19	21.24	21.34
HSDPA Sub 4	21.50	21.12	21.18	21.25
HSUPA Sub 1	20.50	20.24	20.32	20.36
HSUPA Sub 2	20.50	20.04	20.00	20.10
HSUPA Sub 3	21.00	20.85	20.87	20.93
HSUPA Sub 4	20.00	19.49	19.51	19.60
HSUPA Sub 5	21.50	20.96	21.01	21.00

8.3. LTE Conducted Power

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 36.521-1 specification. A summary of these configurations are illustrated below:

Test Parameters for Channel Bandwidths				
Ch BW	Downlink Configuration	Mod'n	Uplink Configuration	
	N/A for Max UE output power testing		RB allocation	
			FDD	TDD
1.4MHz		QPSK	1	1
1.4MHz		QPSK	5	5
3MHz		QPSK	1	1
3MHz		QPSK	4	4
5MHz		QPSK	1	1
5MHz		QPSK	8	8
10MHz		QPSK	1	1
10MHz		QPSK	12	12
15MHz		QPSK	1	1
15MHz		QPSK	16	16
20MHz		QPSK	1	1
20MHz		QPSK	18	18

Note 1: Test Channel Bandwidths are checked separately for each E-UTRA band, the applicable channel bandwidths are specified in Table 5.4.2.1-1.

Note 2: For E-UTRA bands not applied with Note 2 in Table 6.2.2.3-1:

- The 1 RB allocation shall be tested at RB#0 for low and mid range, RB #max for high range test frequency.
- The RBstart of non-1RB allocation shall be RB #0 for low and mid range, RB# (max +1 - RB allocation) for high range test frequency.

Note 3: For E-UTRA bands applied with Note 2 in Table 6.2.2.3-1:

- If the test channel bandwidth is larger than 4MHz, then the 1 RB allocation shall be tested at both RB #0 and RB #max.
- If the test channel bandwidth is smaller or equal to 4MHz, then the 1 RB allocation shall be tested at RB #0.
- If the test channel bandwidth = (FUL_high - FUL_low) specified by the operating band, then only one frequency range shall be tested and the 1 RB allocation shall be tested at RB #0, RB # $\left\lceil N_{RB}^{UL} / 2 \right\rceil$ and RB #max.
- For non-1RB allocation, test frequency is middle range, and the RBstart shall be RB #0.

2. LTE Conducted Power Results

LTE output list

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	22.50	22.05	22.14	21.41
			1	2	22.50	22.03	22.06	21.35
			1	5	22.50	22.08	22.02	21.33
			3	0	22.50	22.32	22.33	21.61
			3	1	22.50	22.32	22.37	21.59
			3	2	22.50	22.30	22.23	21.53
			6	0	21.50	21.40	21.35	20.65
		16QAM	1	0	21.50	21.23	21.31	20.57
			1	2	21.50	21.23	21.27	20.54
			1	5	21.50	21.24	21.19	20.51
			3	0	21.50	21.38	21.42	20.65
			3	1	21.50	21.37	21.37	20.70
			3	2	21.50	21.36	21.34	20.62
			6	0	21.00	20.59	20.60	19.93
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	22.50	22.18	22.31	21.67
			1	7	22.50	22.20	22.12	21.57
			1	14	22.50	22.25	22.04	21.43
			8	0	22.00	21.63	21.68	21.07
			8	4	22.00	21.62	21.65	21.07
			8	7	22.00	21.72	21.57	20.99
			15	0	22.00	21.65	21.67	21.04
		16QAM	1	0	22.00	21.38	21.53	20.91
			1	7	22.00	21.43	21.37	20.81
			1	14	22.00	21.44	21.32	20.72
			8	0	21.00	20.88	20.95	20.35
			8	4	21.00	20.88	20.97	20.32
			8	7	21.00	20.94	20.87	20.19
			15	0	21.00	20.97	20.95	20.34
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	23.00	22.24	22.69	22.08
			1	12	23.00	22.56	22.47	21.90
			1	24	23.00	22.60	22.28	21.77
			12	0	22.00	21.82	21.93	21.43
			12	6	22.00	21.77	21.96	21.38
			12	11	22.00	21.87	21.66	21.11
			25	0	22.00	21.87	21.82	21.25
		16QAM	1	0	22.00	21.61	21.81	21.23
			1	12	22.00	21.69	21.64	21.04
			1	24	22.00	21.72	21.47	20.96
			12	0	21.50	20.99	21.17	20.61

			12	6	21.50	20.98	21.18	20.62
			12	11	21.50	21.12	20.90	20.37
			25	0	21.50	21.11	21.10	20.55
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.00	22.48	22.81	22.33
			1	24	23.00	22.56	22.43	21.97
			1	49	23.00	22.74	22.07	21.76
			25	0	22.50	21.82	22.07	21.69
			25	12	22.50	21.83	22.09	21.70
			25	24	22.50	22.11	21.61	21.13
			50	0	22.50	22.05	21.90	21.51
		16QAM	1	0	22.50	21.74	22.06	21.59
			1	24	22.50	21.84	21.72	21.29
			1	49	22.50	21.96	21.38	21.03
			25	0	21.50	21.06	21.34	20.96
			25	12	21.50	21.09	21.33	20.98
			25	24	21.50	21.32	20.85	20.46
			50	0	21.50	21.26	21.15	20.78
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	23.00	22.46	22.86	22.14
			1	37	23.00	22.65	22.38	22.17
			1	74	23.00	22.87	21.96	21.71
			36	0	22.50	21.71	22.17	21.39
			36	18	22.50	21.88	21.64	21.45
			36	37	22.50	22.12	21.23	21.00
			75	0	22.00	21.99	21.77	21.38
		16QAM	1	0	22.50	21.73	22.16	21.35
			1	37	22.50	21.86	21.59	21.43
			1	74	22.50	22.09	21.23	21.06
			36	0	22.50	21.72	22.10	21.38
			36	18	22.50	21.85	21.64	21.44
			36	37	22.50	22.08	21.21	21.02
			75	0	21.50	21.16	20.97	20.61
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.00	22.08	22.86	21.92
			1	49	23.00	22.42	22.40	22.28
			1	99	23.00	22.61	21.61	21.71
			50	0	22.50	21.49	22.39	21.28
			50	24	22.50	21.48	22.42	21.28
			50	49	22.50	22.01	21.57	21.22
			100	0	22.00	21.77	21.98	21.19
		16QAM	1	0	22.00	21.24	21.94	21.27
			1	49	22.00	21.53	21.47	21.63
			1	99	22.00	21.68	20.98	21.11
			50	0	22.00	20.69	21.61	20.60

			50	24	22.00	20.67	21.63	20.61
			50	49	22.00	21.21	20.83	20.48
			100	0	21.50	21.01	21.22	20.50

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.50	22.82	23.08	22.83
			1	2	23.50	22.77	23.01	22.85
			1	5	23.50	22.78	23.04	22.81
			3	0	23.50	22.98	23.27	22.98
			3	1	23.50	22.96	23.25	23.02
			3	2	23.50	22.96	23.22	22.96
			6	0	22.50	22.06	22.36	22.10
		16QAM	1	0	22.50	21.96	22.22	21.83
			1	2	22.50	21.98	22.23	21.94
			1	5	22.50	21.92	22.17	21.87
			3	0	22.50	22.02	22.31	22.03
			3	1	22.50	22.06	22.29	22.04
			3	2	22.50	22.02	22.24	22.01
			6	0	22.00	21.31	21.60	21.11
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.50	22.85	23.06	22.75
			1	7	23.50	22.78	23.04	22.77
			1	14	23.50	22.76	22.98	22.79
			8	0	23.00	22.21	22.47	22.16
			8	4	23.00	22.21	22.46	22.16
			8	7	23.00	22.19	22.51	22.13
			15	0	22.50	22.24	22.47	22.23
		16QAM	1	0	22.50	21.91	22.30	21.85
			1	7	22.50	21.85	22.27	21.81
			1	14	22.50	21.77	22.25	21.81
			8	0	22.00	21.47	21.75	21.40
			8	4	22.00	21.50	21.78	21.40
			8	7	22.00	21.46	21.71	21.41
			15	0	22.00	21.42	21.77	21.40
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.50	22.96	23.36	22.92
			1	12	23.50	22.92	23.30	23.01
			1	24	23.50	22.92	23.23	22.93
			12	0	23.00	22.33	22.59	22.32
			12	6	23.00	22.29	22.60	22.31
			12	11	23.00	22.28	22.64	22.28
			25	0	23.00	22.31	22.60	22.34
		16QAM	1	0	22.50	22.31	22.48	22.24
			1	12	22.50	22.24	22.45	22.29
			1	24	22.50	22.23	22.41	22.24

			12	0	22.00	21.56	21.82	21.58
			12	6	22.00	21.62	21.80	21.61
			12	11	22.00	21.61	21.82	21.58
			25	0	22.00	21.60	21.90	21.55
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	23.50	22.92	23.40	23.09
			1	24	23.50	22.88	23.26	22.96
			1	49	23.50	23.02	23.25	23.04
			25	0	23.00	22.16	22.63	22.37
			25	12	23.00	22.18	22.66	22.38
			25	24	23.00	22.20	22.66	22.30
			50	0	23.00	22.39	22.67	22.37
		16QAM	1	0	23.00	22.01	22.66	22.16
			1	24	23.00	21.96	22.50	22.14
			1	49	23.00	22.16	22.48	22.09
			25	0	22.00	21.49	21.88	21.64
			25	12	22.00	21.45	21.91	21.67
			25	24	22.00	21.53	21.96	21.59
			50	0	22.00	21.70	21.89	21.64
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.50	22.95	23.35	23.09
			1	37	23.50	22.98	23.30	22.92
			1	74	23.50	23.12	23.13	22.92
			36	0	23.00	22.33	22.60	22.44
			36	18	23.00	22.37	22.51	22.31
			36	37	23.00	22.51	22.38	22.34
			75	0	23.00	22.38	22.55	22.29
		16QAM	1	0	23.00	22.34	22.57	22.47
			1	37	23.00	22.38	22.49	22.29
			1	74	23.00	22.55	22.41	22.33
			36	0	23.00	22.32	22.58	22.48
			36	18	23.00	22.36	22.55	22.28
			36	37	23.00	22.54	22.43	22.30
			75	0	22.00	21.63	21.71	21.58
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.50	22.98	23.24	23.23
			1	49	23.50	23.26	23.31	23.10
			1	99	23.50	23.29	23.11	22.97
			50	0	23.00	22.49	22.67	22.48
			50	24	23.00	22.52	22.66	22.46
			50	49	23.00	22.65	22.69	22.33
			100	0	23.00	22.52	22.68	22.36
		16QAM	1	0	23.00	22.34	22.41	22.54
			1	49	23.00	22.55	22.35	22.36
			1	99	23.00	22.60	22.22	22.29

			50	0	22.00	21.76	21.99	21.73
			50	24	22.00	21.79	21.96	21.74
			50	49	22.00	21.89	21.95	21.64
			100	0	22.00	21.82	21.94	21.63

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	23.50	23.12	23.00	22.85
			1	2	23.50	23.13	23.01	22.78
			1	5	23.50	23.11	23.02	22.78
			3	0	23.50	23.37	23.20	23.07
			3	1	23.50	23.42	23.17	23.08
			3	2	23.50	23.39	23.22	22.97
			6	0	22.50	22.46	22.23	22.16
		16QAM	1	0	22.50	22.29	22.04	21.98
			1	2	22.50	22.30	22.01	21.99
			1	5	22.50	22.30	22.10	21.95
			3	0	22.50	22.43	22.28	22.05
			3	1	22.50	22.41	22.23	22.09
			3	2	22.50	22.40	22.28	22.05
			6	0	22.00	21.81	21.26	21.30
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	23.50	23.15	22.91	22.91
			1	7	23.50	23.21	22.98	22.90
			1	14	23.50	23.22	22.94	22.84
			8	0	23.00	22.55	22.39	22.29
			8	4	23.00	22.53	22.35	22.33
			8	7	23.00	22.62	22.43	22.29
			15	0	23.00	22.63	22.41	22.33
		16QAM	1	0	22.50	22.25	22.18	22.00
			1	7	22.50	22.25	22.19	21.93
			1	14	22.50	22.26	22.20	21.89
			8	0	22.00	21.80	21.60	21.53
			8	4	22.00	21.82	21.61	21.51
			8	7	22.00	21.82	21.66	21.52
			15	0	22.00	21.83	21.69	21.50
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	23.50	23.36	23.23	23.15
			1	12	23.50	23.43	23.29	23.10
			1	24	23.50	23.25	23.23	23.01
			12	0	23.00	22.66	22.51	22.44
			12	6	23.00	22.67	22.49	22.48
			12	11	23.00	22.69	22.57	22.35
			25	0	23.00	22.75	22.50	22.47
		16QAM	1	0	23.00	22.65	22.36	22.47
			1	12	23.00	22.75	22.40	22.43
			1	24	23.00	22.61	22.40	22.33

			12	0	22.00	21.96	21.73	21.72
			12	6	22.00	21.98	21.71	21.73
			12	11	22.00	21.97	21.76	21.61
			25	0	22.00	21.99	21.77	21.68
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band 5	10MHz	QPSK	1	0	23.50	23.00	23.21	23.30
			1	24	23.50	23.29	23.17	23.22
			1	49	23.50	23.19	23.21	23.08
			25	0	23.00	22.72	22.52	22.59
			25	12	23.00	22.73	22.47	22.64
			25	24	23.00	22.57	22.59	22.38
			50	0	23.00	22.68	22.55	22.53
		16QAM	1	0	22.50	22.43	22.46	22.30
			1	24	22.50	22.39	22.37	22.33
			1	49	22.50	22.21	22.45	22.12
			25	0	22.50	22.00	21.69	21.87
			25	12	22.50	22.02	21.76	21.86
			25	24	22.50	21.83	21.80	21.67
			50	0	22.00	21.95	21.79	21.82

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.00	22.46	22.71	22.11
			1	12	23.00	22.53	22.74	21.92
			1	24	23.00	22.58	22.73	21.69
			12	0	21/23/20	20.15	22.06	19.48
			12	6	21/23/20	20.18	22.15	19.44
			12	11	21/23/20	20.25	22.06	19.39
			25	0	21/23/20	20.25	22.14	19.47
		16QAM	1	0	21/22/21	20.04	21.86	20.88
			1	12	21/22/21	20.14	21.90	19.63
			1	24	21/22/21	20.13	21.88	19.35
			12	0	20.00	19.38	19.60	18.71
			12	6	20.00	19.40	19.61	18.72
			12	11	20.00	19.49	19.66	18.65
			25	0	20.00	19.45	19.68	18.68
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.00	22.50	22.38	21.96
			1	24	23.00	22.52	22.26	21.76
			1	49	23.00	22.32	22.33	21.80
			25	0	20.50	19.83	20.09	19.65
			25	12	20.50	19.85	20.11	19.64
			25	24	20.50	19.99	20.04	19.52
			50	0	20.50	19.93	20.07	19.62
		16QAM	1	0	20.50	20.00	19.99	19.45
			1	24	20.50	19.91	20.03	19.35

			1	49	20.50	19.77	20.00	19.23
			25	0	19.50	19.10	19.32	18.83
			25	12	19.50	19.12	19.34	18.88
			25	24	19.50	19.30	19.28	18.77
			50	0	19.50	19.21	19.36	18.85
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	22.50	22.45	22.35	22.02
			1	37	22.50	22.31	22.26	21.72
			1	74	22.50	22.19	22.32	21.69
			36	0	20.00	19.86	20.00	19.71
			36	18	20.00	19.97	19.99	19.58
			36	37	20.00	20.00	19.96	19.44
			75	0	20.50	19.91	20.04	19.57
		16QAM	1	0	20.50	20.22	19.99	19.74
			1	37	20.50	20.12	20.03	19.56
			1	74	20.50	20.00	19.92	19.43
			36	0	20.50	19.84	20.01	19.74
			36	18	20.50	19.98	20.04	19.61
			36	37	20.50	19.97	19.92	19.47
			75	0	19.50	19.16	19.17	18.76
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.00	22.45	22.32	22.21
			1	49	23.00	22.64	22.35	21.88
			1	99	23.00	22.62	22.25	21.73
			50	0	20.50	19.92	20.13	19.90
			50	24	20.50	19.95	20.11	19.86
			50	49	20.50	20.07	20.06	19.59
			100	0	20.50	19.97	20.10	19.70
		16QAM	1	0	20.50	20.19	19.86	19.91
			1	49	20.50	20.39	19.98	19.71
			1	99	20.50	20.33	19.78	19.46
			50	0	19.50	19.18	19.37	19.10
			50	24	19.50	19.18	19.34	19.08
			50	49	19.50	19.31	19.31	18.81
			100	0	19.50	19.23	19.31	18.94

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26047/1850.7	26365/1882.5	26683/1914.3
LTE Band 25	1.4MHz	QPSK	1	0	16/23/23	15.52	22.39	22.13
			1	2	16/23/23	15.52	22.31	22.10
			1	5	16/23/23	15.57	22.30	22.19
			3	0	23.00	22.60	22.59	22.34
			3	1	23.00	22.60	22.54	22.33
			3	2	23.00	22.57	22.51	22.38
			6	0	22.00	21.62	21.66	21.54
		16QAM	1	0	15/22/22	14.72	21.52	21.24

			1	2	15/22/22	14.66	21.47	21.28
			1	5	22.00	21.46	21.47	21.30
			3	0	22.00	21.62	21.61	21.32
			3	1	22.00	21.63	21.60	21.34
			3	2	22.00	21.64	21.55	21.41
			6	0	21.00	20.73	20.90	20.74
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26055/1851.5	26365/1882.5	26675/1913.5
LTE Band 25	3MHz	QPSK	1	0	22.50	22.37	22.44	21.97
			1	7	22.50	22.42	22.33	22.18
			1	14	22.50	22.40	22.30	22.28
			8	0	22.00	21.79	21.80	21.48
			8	4	22.00	21.79	21.82	21.45
			8	7	22.00	21.86	21.77	21.65
			15	0	22.00	21.86	21.83	21.57
		16QAM	1	0	22.00	21.61	21.66	21.18
			1	7	22.00	21.65	21.59	21.35
			1	14	22.00	21.62	21.56	21.54
			8	0	21.50	21.07	21.11	20.73
			8	4	21.50	21.07	21.11	20.72
			8	7	21.50	21.10	21.08	20.88
			15	0	21.50	21.15	21.10	20.86
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26065/1852.5	26365/1882.5	26665/1912.5
LTE Band 25	5MHz	QPSK	1	0	23.00	22.67	22.81	22.20
			1	12	23.00	22.74	22.67	22.32
			1	24	23.00	22.74	22.51	22.56
			12	0	22.50	21.92	21.98	21.39
			12	6	22.50	21.95	22.03	21.39
			12	11	22.50	22.06	21.88	21.75
			25	0	22.50	22.01	21.97	21.58
		16QAM	1	0	22.00	21.79	21.90	21.29
			1	12	22.00	21.87	21.77	21.45
			1	24	22.00	21.84	21.67	21.66
			12	0	21.50	21.14	21.26	20.63
			12	6	21.50	21.15	21.24	20.65
			12	11	21.50	21.26	21.09	20.98
			25	0	21.50	21.31	21.22	20.89
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26090/1855	26365/1882.5	26640/1910
LTE Band 25	10MHz	QPSK	1	0	23.50	22.65	22.91	22.44
			1	24	23.50	22.71	22.58	22.07
			1	49	23.50	23.01	22.39	22.48
			25	0	22.50	21.96	22.15	21.65
			25	12	22.50	21.93	22.15	21.64
			25	24	22.50	22.31	21.82	21.77
			50	0	22.50	22.18	22.03	21.78
		16QAM	1	0	22.50	21.91	22.15	21.72

			1	24	22.50	21.93	21.78	21.29
			1	49	22.50	22.23	21.69	21.69
			25	0	22.00	21.17	21.43	20.89
			25	12	22.00	21.22	21.42	20.93
			25	24	22.00	21.57	21.15	21.04
			50	0	21.50	21.45	21.34	21.00
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26115/1857.5	26365/1882.5	26615/1907.5
LTE Band 25	15MHz	QPSK	1	0	23.50	22.67	23.06	22.62
			1	37	23.50	22.91	22.57	22.23
			1	74	23.50	23.19	22.38	22.42
			36	0	22.50	21.91	22.29	21.82
			36	18	22.50	22.17	21.79	21.50
			36	37	22.50	22.41	21.59	21.67
			75	0	22.50	22.21	21.92	21.74
		16QAM	1	0	22.50	21.92	22.32	21.83
			1	37	22.50	22.13	21.82	21.51
			1	74	22.50	22.41	21.59	21.65
			36	0	22.50	21.93	22.29	21.85
			36	18	22.50	22.15	21.80	21.52
			36	37	22.50	22.37	21.60	21.65
			75	0	21.50	21.39	21.16	20.91
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26140/1860	26365/1882.5	26590/1905
LTE Band 25	20MHz	QPSK	1	0	23.50	22.63	23.19	22.40
			1	49	23.50	23.11	22.60	22.54
			1	99	23.50	23.27	22.35	22.35
			50	0	23.00	22.03	22.53	22.14
			50	24	23.00	21.98	22.50	22.13
			50	49	23.00	22.64	21.99	21.72
			100	0	22.50	22.37	22.23	21.89
		16QAM	1	0	22.50	21.74	22.33	21.58
			1	49	22.50	22.20	21.76	21.67
			1	99	22.50	22.37	21.44	21.50
			50	0	22.00	21.22	21.76	21.36
			50	24	22.00	21.24	21.77	21.35
			50	49	22.00	21.88	21.23	21.00
			100	0	22.00	21.62	21.48	21.13

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26697/814.7	26740/819	26783/823.3
LTE Band 26a	1.4MHz	QPSK	1	0	24.00	22.57	23.59	23.48
			1	2	24.00	22.11	23.50	23.49
			1	5	24.00	22.32	23.57	23.43
			3	0	24.00	22.39	23.75	23.70
			3	1	24.00	22.80	23.74	23.73
			3	2	24.00	22.67	23.72	23.69
			6	0	23.00	22.46	22.89	22.79
		16QAM	1	0	23.00	22.41	22.52	22.63

			1	2	23.00	22.72	22.46	22.61
			1	5	23.00	22.15	22.49	22.60
			3	0	23.00	22.46	22.73	22.77
			3	1	23.00	22.34	22.68	22.69
			3	2	23.00	22.88	22.67	22.72
			6	0	24.00	23.96	22.06	22.96
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26705/818.5	26740/819	26775/822.5
LTE Band 26a	3MHz	QPSK	1	0	22/24/24	21.49	23.10	23.48
			1	7	22/24/24	21.76	23.15	23.48
			1	14	23/24/24	22.32	23.37	23.42
			8	0	17/23/23	16.07	22.87	22.87
			8	4	17/23/23	16.33	22.58	22.88
			8	7	23.00	22.03	22.97	22.97
			15	0	21/24/23	20.02	23.03	22.94
		16QAM	1	0	21/23/23	20.65	22.11	22.67
			1	7	21/23/23	20.92	22.10	22.68
			1	14	22/23/23	21.82	22.23	22.68
			8	0	16/22/23	15.18	21.88	22.17
			8	4	16/22/23	15.22	21.97	22.17
			8	7	22/23/23	21.73	22.19	22.16
			15	0	20/23/23	19.38	22.05	22.19
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26715/816.5	26740/819	26765/821.5
LTE Band 26a	5MHz	QPSK	1	0	25.00	24.28	24.25	24.28
			1	12	25.00	24.38	24.30	24.50
			1	24	25.00	24.24	24.30	24.34
			12	0	23.50	23.19	23.36	23.31
			12	6	23.50	23.22	23.32	23.31
			12	11	23.50	23.11	23.24	23.35
			25	0	23.50	23.22	23.35	23.36
		16QAM	1	0	23.50	23.18	23.25	23.21
			1	12	23.50	23.35	23.45	23.30
			1	24	23.50	23.18	23.33	23.21
			12	0	22.50	22.18	22.38	22.32
			12	6	22.50	22.20	22.40	22.31
			12	11	22.50	22.12	22.25	22.37
			25	0	22.50	22.24	22.33	22.38
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		/	26740/819	/
LTE Band 26a	10MHz	QPSK	1	0	24.00	/	24.31	/
			1	24	24.00	/	24.41	/
			1	49	24.00	/	24.38	/
			25	0	22.00	/	23.35	/
			25	12	22.00	/	23.40	/
			25	24	22.00	/	23.28	/
			50	0	21.50	/	23.33	/
		16QAM	1	0	23.50	/	23.13	/
			1	24	23.50	/	23.24	/
			1	49	23.50	/	23.15	/

			25	0	22.00	/	22.38	/
			25	12	22.00	/	22.42	/
			25	24	22.00	/	22.31	/
			50	0	21.50	/	22.40	/

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26797/824.7	26915/836.5	27033/848.3
LTE Band 26b	1.4MHz	QPSK	1	0	23.50	23.48	23.26	23.11
			1	2	23.50	23.45	23.22	23.06
			1	5	23.50	23.43	23.25	23.05
			3	0	24.00	23.71	23.41	23.35
			3	1	24.00	23.70	23.38	23.31
			3	2	24.00	23.64	23.43	23.30
			6	0	23.00	22.79	22.48	22.37
		16QAM	1	0	23.00	22.62	22.23	22.12
			1	2	23.00	22.61	22.28	22.11
			1	5	23.00	22.60	22.28	22.04
			3	0	23.00	22.73	22.46	22.33
			3	1	23.00	22.73	22.45	22.33
			3	2	23.00	22.67	22.41	22.26
			6	0	22.00	21.98	21.59	21.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26805/825.5	26915/836.5	27025/847.5
LTE Band 26b	3MHz	QPSK	1	0	24.00	23.48	23.15	23.17
			1	7	24.00	23.50	23.17	23.13
			1	14	24.00	23.42	23.15	23.06
			8	0	23.00	22.83	22.61	22.54
			8	4	23.00	22.81	22.62	22.51
			8	7	23.00	22.88	22.63	22.50
			15	0	23.00	22.90	22.66	22.54
		16QAM	1	0	23.00	22.57	22.33	22.25
			1	7	23.00	22.49	22.39	22.21
			1	14	23.00	22.48	22.39	22.11
			8	0	22.50	22.08	21.86	21.78
			8	4	22.50	22.10	21.88	21.77
			8	7	22.50	22.05	21.88	21.67
			15	0	22.50	22.02	21.93	21.73
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26815/826.5	26915/836.5	27015/846.5
LTE Band 26b	5MHz	QPSK	1	0	24.00	23.68	23.48	23.46
			1	12	24.00	23.69	23.54	23.38
			1	24	24.00	23.54	23.45	23.26
			12	0	23.00	22.98	22.70	22.75
			12	6	23.00	22.95	22.73	22.76
			12	11	23.00	22.90	22.71	22.59
			25	0	23.00	22.97	22.75	22.70
		16QAM	1	0	23.00	22.98	22.61	22.72
			1	12	23.00	22.95	22.61	22.70
			1	24	23.00	22.83	22.64	22.49

			12	0	22.50	22.29	21.92	22.05
			12	6	22.50	22.26	21.93	22.06
			12	11	22.50	22.18	21.96	21.89
			25	0	22.50	22.27	22.00	21.97
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26840/829	26915/836.5	26990/844
LTE Band 26b	10MHz	QPSK	1	0	24.00	23.69	23.51	23.50
			1	24	24.00	23.55	23.36	23.52
			1	49	24.00	23.41	23.47	23.33
			25	0	23.00	22.92	22.75	22.85
			25	12	23.00	22.96	22.71	22.83
			25	24	23.00	22.79	22.75	22.71
		16QAM	50	0	23.00	22.91	22.82	22.84
			1	0	23.00	22.91	22.64	22.53
			1	24	23.00	22.79	22.58	22.54
			1	49	23.00	22.63	22.69	22.39
			25	0	22.50	22.17	21.95	22.12
			25	12	22.50	22.17	21.99	22.13
			25	24	22.50	22.05	22.01	21.94
			50	0	22.50	22.17	22.07	22.09
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		26865/831.5	26915/836.5	26965/841.5
LTE Band 26b	15MHz	QPSK	1	0	24.00	23.69	23.55	23.39
			1	37	24.00	23.46	23.44	23.47
			1	74	24.00	23.42	23.45	23.24
			36	0	23.00	22.90	22.78	22.68
			36	18	23.00	22.66	22.64	22.77
			36	37	23.00	22.63	22.69	22.56
			75	0	23.00	22.77	22.65	22.70
		16QAM	1	0	23.00	22.92	22.78	22.71
			1	37	23.00	22.67	22.64	22.80
			1	74	23.00	22.64	22.66	22.60
			36	0	23.00	22.93	22.79	22.76
			36	18	23.00	22.68	22.68	22.75
			36	37	23.00	22.60	22.69	22.58
			75	0	22.00	21.95	21.88	21.89

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37775/2572.5	38000/2595	38225/2617.5
LTE Band 38	5MHz	QPSK	1	0	20/19/21	19.14	18.74	20.38
			1	12	20/19/21	19.14	18.69	20.45
			1	24	20/19/21	19.03	18.56	20.52
			12	0	19.00	18.50	18.04	18.22
			12	6	19.00	18.52	18.05	18.21
			12	11	19.00	18.43	18.02	18.22
			25	0	18.50	18.48	18.08	18.20
		16QAM	1	0	19.00	18.77	18.07	18.12
			1	12	19.00	18.76	18.06	18.21
			1	24	19.00	18.67	17.94	18.19

			12	0	18.00	17.74	17.33	17.40
			12	6	18.00	17.73	17.35	17.40
			12	11	18.00	17.71	17.30	17.39
			25	0	18.00	17.74	17.35	17.43
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37800/2575	38000/2595	38200/2615
LTE Band 38	10MHz	QPSK	1	0	20.50	19.24	18.96	20.31
			1	24	20.50	19.08	18.77	20.32
			1	49	20.50	19.09	18.67	20.47
			25	0	18.50	18.46	18.17	18.07
			25	12	18.50	18.46	18.15	18.06
			25	24	18.50	18.40	18.04	18.23
		16QAM	50	0	18.50	18.48	18.15	18.20
			1	0	19.00	18.67	18.40	17.65
			1	24	19.00	18.48	18.21	17.72
			1	49	19.00	18.54	18.09	17.80
			25	0	18.00	17.82	17.51	17.32
			25	12	18.00	17.80	17.50	17.30
			25	24	18.00	17.76	17.37	17.44
			50	0	18.00	17.74	17.44	17.42
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37825/2577.5	38000/2595	38175/2615
LTE Band 38	15MHz	QPSK	1	0	20/19/21	19.13	18.98	20.36
			1	37	20/19/21	19.04	18.71	20.31
			1	74	20/19/21	19.03	18.45	20.51
			36	0	18.50	18.28	17.96	18.00
			36	18	18.50	18.32	17.97	18.00
			36	37	18.50	18.31	17.98	17.98
		16QAM	75	0	18.50	18.27	18.00	17.98
			1	0	19.00	18.55	18.40	17.73
			1	37	19.00	18.47	18.10	17.79
			1	74	19.00	18.45	17.84	17.90
			36	0	18.50	18.28	18.01	17.98
			36	18	18.50	18.29	17.95	17.96
			36	37	18.50	18.27	17.98	17.97
			75	0	18.00	17.57	17.23	17.24
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37850/2580	38000/2595	38150/2610
LTE Band 38	20MHz	QPSK	1	0	20/19/19	19.07	18.98	18.43
			1	49	20/19/21	19.10	18.78	20.10
			1	99	19/21/21	18.84	20.10	20.30
			50	0	18.50	18.43	18.21	17.88
			50	24	18.50	18.45	18.24	17.89
			50	49	18.50	18.41	18.02	18.19
			100	0	18.50	18.41	18.10	18.06
		16QAM	1	0	18.50	18.36	18.29	17.25
			1	49	18.50	18.32	18.03	17.45
			1	99	18.50	18.08	17.77	17.55
			50	0	18.00	17.74	17.51	17.17
			50	24	18.00	17.73	17.51	17.17

			50	49	18.00	17.71	17.29	17.48
			100	0	18.00	17.66	17.37	17.31

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39675/2498.5	40620/2593	41565/2687.5
LTE Band 41	5MHz	QPSK	1	0	20.00	19.52	18.93	19.96
			1	12	20.00	19.58	18.91	19.93
			1	24	20.00	19.52	18.75	19.91
			12	0	20.00	19.80	18.24	19.46
			12	6	20.00	19.84	18.23	19.48
			12	11	20.00	19.99	18.17	19.35
			25	0	20.00	19.97	18.23	19.45
		16QAM	1	0	20.00	19.83	18.51	19.54
			1	12	20.00	19.88	18.50	19.53
			1	24	20.00	19.83	18.33	19.52
			12	0	18.50	18.02	17.48	16.98
			12	6	18.50	18.03	17.46	16.98
			12	11	18.50	18.21	17.39	16.90
			25	0	18.50	18.20	17.48	17.02
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39700/2501	40620/2593	41540/2685
LTE Band 41	10MHz	QPSK	1	0	20.50	19.62	19.16	20.20
			1	24	20.50	19.02	19.03	19.95
			1	49	20.50	19.75	18.83	20.03
			25	0	20.00	19.80	18.35	19.62
			25	12	20.00	19.80	18.35	19.63
			25	24	20.00	19.32	18.22	19.41
			50	0	20.00	19.99	18.38	19.56
		16QAM	1	0	20/19/20	19.08	18.04	19.37
			1	24	20/19/20	19.11	17.83	19.24
			1	49	20/19/20	19.90	17.73	19.26
			25	0	20/18/18	19.19	17.61	17.18
			25	12	20/18/18	19.19	17.60	17.19
			25	24	20/18/18	19.40	17.48	16.98
			50	0	20/18/18	19.25	17.64	17.11
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39725/2503.5	40620/2593	41515/2682.5
LTE Band 41	15MHz	QPSK	1	0	20.50	19.59	19.18	20.39
			1	37	20.50	19.62	19.05	20.05
			1	74	20.50	19.05	18.76	20.03
			36	0	19.50	19.18	18.21	19.44
			36	18	19.50	19.18	18.20	19.45
			36	37	19.50	19.20	18.22	19.48
			75	0	19.50	19.20	18.22	19.46
		16QAM	1	0	20/19/20	19.07	18.23	19.62
			1	37	20/19/20	19.75	18.01	19.27
			1	74	20/19/20	19.20	17.74	19.24
			36	0	19.50	19.17	18.21	19.44
			36	18	19.50	19.18	18.17	19.45
			36	37	19.50	19.19	18.18	19.46

			75	0	20/18/18	19.14	17.45	17.09
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39750/2506	40620/2593	41490/2680
LTE Band 41	20MHz	QPSK	1	0	20.50	18.51	19.04	20.49
			1	49	20.50	18.88	18.89	20.07
			1	99	20.50	18.80	20.17	19.98
			50	0	19.50	18.83	18.41	18.19
			50	24	19.50	18.83	18.44	18.22
			50	49	19.50	18.95	18.20	19.42
			100	0	20.00	18.40	18.27	19.68
		16QAM	1	0	19/18/18	18.78	17.86	17.87
			1	49	19/18/20	18.87	17.76	19.02
			1	99	19/18/19	18.78	17.38	18.92
			50	0	19/18/18	18.04	17.75	17.45
			50	24	19/18/18	18.06	17.73	17.42
			50	49	19/18/18	18.92	17.51	16.91
			100	0	18.50	18.34	17.57	17.26

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131979/1710.7	132322/1745	132665/1779.3
LTE Band 66	1.4MHz	QPSK	1	0	23.50	22.95	23.12	23.37
			1	2	23.50	22.90	23.21	23.28
			1	5	23.50	22.94	23.17	23.35
			3	0	24.00	23.12	23.40	23.47
			3	1	24.00	23.04	23.40	23.47
			3	2	24.00	23.05	23.32	23.52
			6	0	23.00	22.25	22.48	22.52
		16QAM	1	0	22.50	22.06	22.33	22.34
			1	2	22.50	22.07	22.33	22.36
			1	5	22.50	21.89	22.27	22.35
			3	0	23.00	22.18	22.40	22.51
			3	1	23.00	22.11	22.40	22.53
			3	2	23.00	21.96	22.36	22.54
			6	0	22.00	21.55	21.74	21.70
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131987/1711.5	132322/1745	132657/1778.5
LTE Band 66	3MHz	QPSK	1	0	23.50	22.78	23.46	23.05
			1	7	23.50	22.85	23.11	23.04
			1	14	23.50	23.27	23.06	22.88
			8	0	23.00	22.24	22.51	22.52
			8	4	23.00	22.25	22.52	22.53
			8	7	23.00	22.30	22.56	22.57
			15	0	23.00	22.33	22.57	22.56
		16QAM	1	0	22.50	21.87	21.95	22.11
			1	7	22.50	21.85	22.33	22.11
			1	14	22.50	22.38	22.28	22.17
			8	0	22.00	21.46	21.77	21.78
			8	4	22.00	21.46	21.79	21.76

			8	7	22.00	21.57	21.81	21.73
			15	0	22.00	21.45	21.83	21.71
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		131997/1712.5	132322/1745	132647/1777.5
LTE Band 66	5MHz	QPSK	1	0	23.50	23.16	23.40	23.28
			1	12	23.50	23.20	23.40	23.33
			1	24	23.50	23.19	23.31	23.39
			12	0	23.00	22.42	22.66	22.63
			12	6	23.00	22.45	22.64	22.64
			12	11	23.00	22.49	22.66	22.63
			25	0	23.00	22.46	22.69	22.68
		16QAM	1	0	23.00	22.26	22.59	22.56
			1	12	23.00	22.36	22.54	21.82
			1	24	23.00	22.35	22.48	22.63
			12	0	22.00	21.67	21.89	21.92
			12	6	22.00	21.68	21.86	21.91
			12	11	22.00	21.70	21.85	21.91
			25	0	22.00	21.71	21.91	21.90
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132022/1715	132322/1745	132622/1775
LTE Band 66	10MHz	QPSK	1	0	23.50	23.08	23.46	23.36
			1	24	23.50	23.17	23.34	23.28
			1	49	23.50	23.26	23.33	23.37
			25	0	23.00	22.42	22.69	22.68
			25	12	23.00	22.45	22.65	22.67
			25	24	23.00	22.53	22.63	22.60
			50	0	23.00	22.53	22.71	22.67
		16QAM	1	0	23.00	22.34	22.65	22.56
			1	24	23.00	22.39	22.52	22.53
			1	49	23.00	22.48	22.57	22.64
			25	0	22.00	21.70	21.90	21.90
			25	12	22.00	21.73	21.89	21.88
			25	24	22.00	21.80	21.90	21.87
			50	0	22.00	21.78	21.92	21.86
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132047/1717.5	132322/1745	132597/1772.5
LTE Band 66	15MHz	QPSK	1	0	24.00	23.11	23.44	23.31
			1	37	24.00	23.84	23.32	23.26
			1	74	24.00	23.35	23.22	23.70
			36	0	23.00	22.33	22.64	22.64
			36	18	23.00	21.94	22.56	22.53
			36	37	23.00	22.62	22.53	22.57
			75	0	23.00	22.50	22.63	22.54
		16QAM	1	0	23.50	22.71	22.70	22.56
			1	37	23.50	23.05	22.56	22.50
			1	74	23.50	22.59	22.49	22.56
			36	0	23.00	22.34	22.71	22.57
			36	18	23.00	22.61	22.55	22.48

			36	37	23.00	22.65	22.49	22.55
			75	0	22.00	21.72	21.80	21.71
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		132072/1720	132322/1745	132572/1770
LTE Band 66	20MHz	QPSK	1	0	24.00	23.13	23.53	23.28
			1	49	24.00	23.28	23.42	23.37
			1	99	24.00	23.49	23.22	23.24
			50	0	23.00	22.58	22.73	22.58
			50	24	23.00	22.62	22.72	22.59
			50	49	23.00	22.80	22.64	22.53
			100	0	23.00	22.70	22.66	22.57
		16QAM	1	0	23.00	21.47	22.60	22.38
			1	49	23.00	22.42	22.53	22.39
			1	99	23.00	22.58	22.37	22.42
			50	0	22.50	21.87	21.95	21.85
			50	24	22.50	21.87	21.95	21.82
			50	49	22.50	22.08	21.88	21.80
			100	0	22.00	21.93	21.90	21.78

8.4. Wi-Fi & BT Output Power

Mode	Channel	Frequency (MHz)	Output Power (dBm)ANT1	Tune-Up	Output Power (dBm)ANT2	Tune-Up	Output Power (dBm)MIMO	Tune-Up
802.11b	1	2412	11.16	11±1	12.23	12±1	/	/
	6	2437	9.25	9±1	12.10	12±1	/	/
	11	2462	10.89	10±1	11.30	11±1	/	/
802.11g	1	2412	9.90	9±1	10.41	10±1	/	/
	6	2437	10.05	10±1	9.64	9±1	/	/
	11	2462	9.04	9±1	9.20	9±1	/	/
802.11n (HT20)	1	2412	10.06	10±1	10.18	10±1	13.13	13±1
	6	2437	9.85	9±1	10.11	10±1	12.99	12±1
	11	2462	9.08	9±1	8.99	8±1	12.05	12±1
802.11n (H40)	3	2422	9.56	9±1	9.46	9±1	12.52	12±1
	6	2437	9.33	9±1	9.16	9±1	12.26	12±1
	9	2452	8.70	8±1	8.35	8±1	11.54	11±1

Mode	Frequency (MHz)	Output Power (dBm)ANT1	Tune-Up	Output Power (dBm)ANT2	Tune-Up	Output Power (dBm)MIMO	Tune-Up
802.11A	5180	9.56	9±1	9.52	9±1	/	/
	5200	9.24	9±1	9.54	9±1	/	/
	5240	8.53	8±1	9.06	9±1	/	/
802.11N20SISO	5180	7.90	7±1	7.35	7±1	10.64	10±1
	5200	8.00	8±1	6.80	6±1	10.45	10±1
	5240	7.90	7±1	6.99	6±1	10.48	10±1
802.11N40SISO	5190	5.38	5±1	8.22	8±1	10.04	10±1
	5230	3.59	3±1	7.02	7±1	8.65	8±1
802.11AC20SISO	5180	6.88	6±1	6.74	6±1	9.82	9±1
	5200	6.95	6±1	6.97	6±1	9.97	9±1
	5240	5.71	5±1	7.22	7±1	9.54	9±1
802.11AC40SISO	5190	6.73	6±1	8.69	8±1	10.83	10±1
	5230	6.07	6±1	8.33	8±1	10.36	10±1
802.11AC80SISO	5210	7.37	7±1	8.42	8±1	10.94	10±1


Mode	Frequency (MHz)	Output Power (dBm)ANT1	Tune-Up	Output Power (dBm)ANT2	Tune-Up	Output Power (dBm)MIMO	Tune-Up
802.11A	5745	10.29	10±1	9.68	9±1	/	/
	5785	10.51	10±1	10.47	10±1	/	/
	5825	10.42	10±1	10.82	10±1	/	/
802.11N20SISO	5745	10.26	10±1	8.02	8±1	12.29	12±1
	5785	9.84	9±1	8.96	8±1	12.43	12±1
	5825	9.62	9±1	9.70	9±1	12.67	12±1
802.11N40SISO	5755	9.82	9±1	7.87	7±1	11.96	11±1
	5795	10.79	10±1	8.86	8±1	12.94	12±1
802.11AC20SISO	5745	9.44	9±1	8.17	8±1	11.86	11±1
	5785	9.47	9±1	9.03	9±1	12.27	12±1
	5825	9.30	9±1	10.25	10±1	12.81	12±1
802.11AC40SISO	5755	9.09	9±1	8.92	8±1	12.02	12±1
	5795	9.97	9±1	9.36	9±1	12.69	12±1
802.11AC80SISO	5775	10.28	10±1	9.12	9±1	12.75	12±1

BR+EDR	Output Power (dBm)				
	Channel	Tune-up (dBm)	Data Rates		
			1M	2M	3M
	0CH	4.00	3.73	3.61	3.68
	39CH	4.00	3.82	2.90	2.73
	78CH	5.00	4.78	3.91	3.90

Mode	Channel	Tune-up (dBm)	Output Power (dBm)
BLE1M	CH00	-8.00	-8.55
	CH19	-7.00	-7.10
	CH39	-8.00	-8.35

Mode	Channel	Tune-up (dBm)	Output Power (dBm)
BLE2M	CH00	-8.00	-8.52
	CH19	-7.00	-7.40
	CH39	-8.00	-8.34

9. Antenna Location



Antenna information:

Distance of The Antenna to the EUT surface and edge (mm)						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
BT/WLAN	≤25mm	≤25mm	≤25mm	>25mm	≤25mm	>25mm
WWAN	≤25mm	≤25mm	≤25mm	≤25mm	>25mm	≤25mm

Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
BT/WLAN	Yes	Yes	Yes	NO	Yes	NO
WWAN	Yes	Yes	Yes	Yes	NO	Yes

10. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Pmax (dBm)	Pmax (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	5.00	3.16	5	2.480	1.0	3	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \leq 7.5$ W/kg for test separation distances ≤ 50 mm, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	Pmax (dBm)	Pmax (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/kg)
Bluetooth	Head	5.00	3.16	5	2.48	7.5	0.132
Bluetooth	Body	5.00	3.16	10	2.48	7.5	0.066
Bluetooth	Hotspot	5.00	3.16	10	2.48	7.5	0.066

NOTE: Estimated SAR calculation for Bluetooth

< GSM 850>

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.198	0.108	-2.42	29.17	29.50	0.214	2025/2/10	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.285	0.163	0.55	29.17	29.50	0.307	2025/2/10	2#
Left Side	189/836.4	GPRS(GMSK 4TS)	0.097	0.054	-1.10	29.17	29.50	0.105	2025/2/10	
Right Side	189/836.4	GPRS(GMSK 4TS)	0.099	0.055	-2.43	29.17	29.50	0.107	2025/2/10	
Bottom Side	189/836.4	GPRS(GMSK 4TS)	0.160	0.089	-2.53	29.17	29.50	0.173	2025/2/10	

Test Position	Test channel /Freq.	Test Mode	SAR Value		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date	Plot
			(W/kg)							
			1g	10g						

								(W/Kg)		
Left Cheek	661/1880	GPRS(GMSK 2TS)	0.281	0.119	1.54	29.66	30.00	0.304	2025/2/14	3#
Left Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.168	0.071	2.64	29.66	30.00	0.182	2025/2/14	
Right Cheek	661/1880	GPRS(GMSK 2TS)	0.248	0.102	2.71	29.66	30.00	0.268	2025/2/14	
Right Tilt 15 Degree	661/1880	GPRS(GMSK 2TS)	0.131	0.055	1.31	29.66	30.00	0.142	2025/2/14	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	661/1880	GPRS(GMSK 2TS)	0.162	0.095	2.97	29.66	30.00	0.175	2025/2/14	
Back Side	661/1880	GPRS(GMSK 2TS)	0.236	0.145	-1.02	29.66	30.00	0.255	2025/2/14	4#
Left Side	661/1880	GPRS(GMSK 2TS)	0.072	0.044	1.94	29.66	30.00	0.078	2025/2/14	
Right Side	661/1880	GPRS(GMSK 2TS)	0.074	0.042	0.07	29.66	30.00	0.080	2025/2/14	
Bottom Side	661/1880	GPRS(GMSK 2TS)	0.130	0.079	-2.04	29.66	30.00	0.141	2025/2/14	

< WCDMA Band 2>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	9400/1880	RMC12.2K	0.076	0.047	1.23	19.68	20.00	0.082	2025/2/14	5#
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.041	0.024	3.83	19.68	20.00	0.044	2025/2/14	
Right	9400/1880	RMC12.2K	0.066	0.040	-0.74	19.68	20.00	0.071	2025/2/14	

Cheek										
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.035	0.021	-1.85	19.68	20.00	0.038	2025/2/14	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	9400/1880	RMC12.2K	0.222	0.125	-3.30	19.68	20.00	0.239	2025/2/14	
Back Side	9400/1880	RMC12.2K	0.350	0.199	1.45	19.68	20.00	0.377	2025/2/14	6#
Left Side	9400/1880	RMC12.2K	0.108	0.058	-0.99	19.68	20.00	0.116	2025/2/14	
Right Side	9400/1880	RMC12.2K	0.114	0.062	-3.04	19.68	20.00	0.123	2025/2/14	
Bottom Side	9400/1880	RMC12.2K	0.175	0.100	-2.63	19.68	20.00	0.188	2025/2/14	

< WCDMA Band 4 >

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	1413/1732.6	RMC12.2K	0.123	0.078	-3.54	22.84	23.00	0.128	2025/2/12	7#
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.070	0.043	-0.84	22.84	23.00	0.073	2025/2/12	
Right Cheek	1413/1732.6	RMC12.2K	0.105	0.067	0.05	22.84	23.00	0.109	2025/2/12	
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.051	0.032	-3.03	22.84	23.00	0.053	2025/2/12	

Test Position	Test channel	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR	Date	Plot
------------------	-----------------	-----------	---------------------	----------------	--------------------	------------------	---------------	------	------

of Hotspot with 10mm	/Freq.		1g	10g	(±5%)	(dBm)	(dBm)	1g (W/Kg)		
Front Side	1413/1732.6	RMC12.2K	0.246	0.157	2.60	22.84	23.00	0.255	2025/2/12	
Back Side	1413/1732.6	RMC12.2K	0.386	0.260	-1.25	22.84	23.00	0.400	2025/2/12	8#
Left Side	1413/1732.6	RMC12.2K	0.123	0.083	3.65	22.84	23.00	0.128	2025/2/12	
Right Side	1413/1732.6	RMC12.2K	0.126	0.085	-0.72	22.84	23.00	0.131	2025/2/12	
Bottom Side	1413/1732.6	RMC12.2K	0.205	0.133	2.46	22.84	23.00	0.213	2025/2/12	

< WCDMA Band 5>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	4182/836.4	RMC12.2K	0.284	0.185	1.52	21.44	21.50	0.288	2025/2/10	9#
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.151	0.094	0.11	21.44	21.50	0.153	2025/2/10	
Right Cheek	4182/836.4	RMC12.2K	0.261	0.170	1.91	21.44	21.50	0.265	2025/2/10	
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.123	0.079	-3.42	21.44	21.50	0.125	2025/2/10	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	4182/836.4	RMC12.2K	0.192	0.111	0.99	21.44	21.50	0.195	2025/2/10	
Back	4182/836.4	RMC12.2K	0.290	0.170	1.36	21.44	21.50	0.294	2025/2/10	10#

with 10mm										
1RB										
Front Side	18900/1880	20M QPSK(1,0)	0.252	0.154	-2.51	22.86	23.00	0.260	2025/2/14	
Back Side	18900/1880	20M QPSK(1,0)	0.393	0.243	2.65	22.86	23.00	0.406	2025/2/14	18#
Left Side	18900/1880	20M QPSK(1,0)	0.125	0.074	3.27	22.86	23.00	0.129	2025/2/14	
Right Side	18900/1880	20M QPSK(1,0)	0.123	0.075	-1.52	22.86	23.00	0.127	2025/2/14	
Bottom Side	18900/1880	20M QPSK(1,0)	0.220	0.133	3.49	22.86	23.00	0.227	2025/2/14	
50%RB										
Front Side	18900/1880	20M QPSK(50,24)	0.129	0.077	3.63	22.42	22.50	0.131	2025/2/14	
Back Side	18900/1880	20M QPSK(50,24)	0.202	0.130	-4.17	22.42	22.50	0.206	2025/2/14	
Left Side	18900/1880	20M QPSK(50,24)	0.074	0.043	0.01	22.42	22.50	0.075	2025/2/14	
Right Side	18900/1880	20M QPSK(50,24)	0.069	0.040	-1.13	22.42	22.50	0.070	2025/2/14	
Bottom Side	18900/1880	20M QPSK(50,24)	0.118	0.075	-0.94	22.42	22.50	0.120	2025/2/14	

< LTE Band 4>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	20175/1732.5	20M QPSK(1,49)	0.445	0.292	2.01	23.31	23.50	0.465	2025/2/12	19#
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.236	0.153	0.68	23.31	23.50	0.247	2025/2/12	
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.408	0.254	-0.72	23.31	23.50	0.426	2025/2/12	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.222	0.144	2.66	23.31	23.50	0.232	2025/2/12	

50%RB										
Left Cheek	20175/1732.5	20M QPSK(50,49)	0.264	0.169	-2.69	22.69	23.00	0.284	2025/2/12	
Left Tilt 15 Degree	20175/1732.5	20M QPSK(50,49)	0.126	0.085	4.22	22.69	23.00	0.135	2025/2/12	
Right Cheek	20175/1732.5	20M QPSK(50,49)	0.218	0.136	-3.99	22.69	23.00	0.234	2025/2/12	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(50,49)	0.115	0.085	0.48	22.69	23.00	0.124	2025/2/12	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.288	0.177	-0.13	23.31	23.50	0.301	2025/2/12	
Back Side	20175/1732.5	20M QPSK(1,49)	0.449	0.281	-3.57	23.31	23.50	0.469	2025/2/12	20#
Left Side	20175/1732.5	20M QPSK(1,49)	0.138	0.084	1.77	23.31	23.50	0.144	2025/2/12	
Right Side	20175/1732.5	20M QPSK(1,49)	0.140	0.086	2.29	23.31	23.50	0.146	2025/2/12	
Bottom Side	20175/1732.5	20M QPSK(1,49)	0.230	0.143	2.03	23.31	23.50	0.240	2025/2/12	
50%RB										
Front Side	20175/1732.5	20M QPSK(50,49)	0.145	0.090	4.69	22.69	23.00	0.156	2025/2/12	
Back Side	20175/1732.5	20M QPSK(50,49)	0.248	0.153	-4.44	22.69	23.00	0.266	2025/2/12	
Left Side	20175/1732.5	20M QPSK(50,49)	0.082	0.044	3.28	22.69	23.00	0.088	2025/2/12	
Right Side	20175/1732.5	20M QPSK(50,49)	0.084	0.051	0.01	22.69	23.00	0.090	2025/2/12	
Bottom Side	20175/1732.5	20M QPSK(50,49)	0.136	0.085	1.97	22.69	23.00	0.146	2025/2/12	

< LTE Band 5>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	20525/836.5	10M QPSK(1,0)	0.285	0.190	-3.91	23.21	23.50	0.305	2025/2/10	21#
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,0)	0.146	0.095	2.89	23.21	23.50	0.156	2025/2/10	
Right Cheek	20525/836.5	10M QPSK(1,0)	0.257	0.164	-1.15	23.21	23.50	0.275	2025/2/10	
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,0)	0.125	0.083	1.98	23.21	23.50	0.134	2025/2/10	
50%RB										
Left Cheek	20525/836.5	10M QPSK(25,12)	0.155	0.106	4.87	22.47	23.00	0.175	2025/2/10	
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,12)	0.074	0.057	4.91	22.47	23.00	0.084	2025/2/10	
Right Cheek	20525/836.5	10M QPSK(25,12)	0.146	0.082	-2.22	22.47	23.00	0.165	2025/2/10	
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,12)	0.064	0.044	4.86	22.47	23.00	0.072	2025/2/10	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20525/836.5	10M QPSK(1,0)	0.162	0.100	3.43	23.21	23.50	0.173	2025/2/10	
Back Side	20525/836.5	10M QPSK(1,0)	0.256	0.163	-1.08	23.21	23.50	0.274	2025/2/10	22#
Left	20525/836.5	10M OPSK(1,0)	0.081	0.049	-0.23	23.21	23.50	0.087	2025/2/10	

Side										
Right Side	20525/836.5	10M QPSK(1,0)	0.078	0.048	1.88	23.21	23.50	0.083	2025/2/10	
Bottom Side	20525/836.5	10M QPSK(1,0)	0.130	0.079	-0.43	23.21	23.50	0.139	2025/2/10	
50%RB										
Front Side	20525/836.5	10M QPSK(25,12)	0.085	0.055	-2.23	22.47	23.00	0.096	2025/2/10	
Back Side	20525/836.5	10M QPSK(25,12)	0.143	0.089	0.82	22.47	23.00	0.162	2025/2/10	
Left Side	20525/836.5	10M QPSK(25,12)	0.043	0.028	-4.30	22.47	23.00	0.049	2025/2/10	
Right Side	20525/836.5	10M QPSK(25,12)	0.046	0.028	-0.76	22.47	23.00	0.052	2025/2/10	
Bottom Side	20525/836.5	10M QPSK(25,12)	0.071	0.047	4.94	22.47	23.00	0.080	2025/2/10	

< LTE Band 7 >

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	21100/2535	20M QPSK(1,49)	0.256	0.191	3.62	22.35	23.00	0.297	2025/2/17	23#
Left Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.140	0.103	-3.84	22.35	23.00	0.163	2025/2/17	
Right Cheek	21100/2535	20M QPSK(1,49)	0.232	0.164	3.75	22.35	23.00	0.269	2025/2/17	
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.120	0.090	-2.26	22.35	23.00	0.139	2025/2/17	
50%RB										
Left Cheek	21100/2535	20M QPSK(50,0)	0.145	0.111	-0.70	20.13	20.50	0.158	2025/2/17	
Left Tilt 15 Degree	21100/2535	20M QPSK(50,0)	0.074	0.058	0.96	20.13	20.50	0.081	2025/2/17	
Right	21100/2535	20M QPSK(50,0)	0.120	0.096	2.67	20.13	20.50	0.131	2025/2/17	

Cheek										
Right Tilt 15 Degree	21100/2535	20M QPSK(50,0)	0.062	0.046	3.82	20.13	20.50	0.068	2025/2/17	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	21100/2535	20M QPSK(1,49)	0.282	0.171	-2.96	22.35	23.00	0.328	2025/2/17	
Back Side	21100/2535	20M QPSK(1,49)	0.465	0.296	-1.35	22.35	23.00	0.540	2025/2/17	24#
Left Side	21100/2535	20M QPSK(1,49)	0.150	0.091	1.43	22.35	23.00	0.174	2025/2/17	
Right Side	21100/2535	20M QPSK(1,49)	0.144	0.089	0.92	22.35	23.00	0.167	2025/2/17	
Bottom Side	21100/2535	20M QPSK(1,49)	0.240	0.148	-1.48	22.35	23.00	0.279	2025/2/17	
50%RB										
Front Side	21100/2535	20M QPSK(50,0)	0.160	0.092	-0.38	20.13	20.50	0.174	2025/2/17	
Back Side	21100/2535	20M QPSK(50,0)	0.274	0.168	-2.84	20.13	20.50	0.298	2025/2/17	
Left Side	21100/2535	20M QPSK(50,0)	0.085	0.052	3.64	20.13	20.50	0.093	2025/2/17	
Right Side	21100/2535	20M QPSK(50,0)	0.078	0.048	-1.55	20.13	20.50	0.085	2025/2/17	
Bottom Side	21100/2535	20M QPSK(50,0)	0.120	0.082	0.35	20.13	20.50	0.131	2025/2/17	

< LTE Band 25>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										

Left Cheek	26365/1882.5	20M QPSK(1,99)	0.472	0.300	0.87	22.35	23.50	0.615	2025/2/14	25#
Left Tilt 15 Degree	26365/1882.5	20M QPSK(1,99)	0.278	0.168	-3.56	22.35	23.50	0.362	2025/2/14	
Right Cheek	26365/1882.5	20M QPSK(1,99)	0.421	0.260	-0.59	22.35	23.50	0.549	2025/2/14	
Right Tilt 15 Degree	26365/1882.5	20M QPSK(1,99)	0.194	0.122	-0.78	22.35	23.50	0.253	2025/2/14	
50%RB										
Left Cheek	26365/1882.5	20M QPSK(50,0)	0.252	0.175	-4.10	22.53	23.00	0.281	2025/2/14	
Left Tilt 15 Degree	26365/1882.5	20M QPSK(50,0)	0.148	0.092	-3.67	22.53	23.00	0.165	2025/2/14	
Right Cheek	26365/1882.5	20M QPSK(50,0)	0.230	0.150	4.40	22.53	23.00	0.256	2025/2/14	
Right Tilt 15 Degree	26365/1882.5	20M QPSK(50,0)	0.114	0.063	-3.33	22.53	23.00	0.127	2025/2/14	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	26365/1882.5	20M QPSK(1,99)	0.240	0.146	-2.39	22.35	23.50	0.313	2025/2/14	
Back Side	26365/1882.5	20M QPSK(1,99)	0.391	0.245	0.87	22.35	23.50	0.510	2025/2/14	26#
Left Side	26365/1882.5	20M QPSK(1,99)	0.123	0.077	0.55	22.35	23.50	0.160	2025/2/14	
Right Side	26365/1882.5	20M QPSK(1,99)	0.125	0.075	0.89	22.35	23.50	0.163	2025/2/14	
Bottom Side	26365/1882.5	20M QPSK(1,99)	0.210	0.128	-0.37	22.35	23.50	0.274	2025/2/14	
50%RB										
Front	26365/1882.5	20M	0.120	0.074	4.08	22.53	23.00	0.134	2025/2/14	

Side		QPSK(50,0)								
Back Side	26365/1882.5	20M QPSK(50,0)	0.234	0.137	2.02	22.53	23.00	0.261	2025/2/14	
Left Side	26365/1882.5	20M QPSK(50,0)	0.066	0.039	1.05	22.53	23.00	0.074	2025/2/14	
Right Side	26365/1882.5	20M QPSK(50,0)	0.070	0.045	-0.87	22.53	23.00	0.078	2025/2/14	
Bottom Side	26365/1882.5	20M QPSK(50,0)	0.111	0.074	0.75	22.53	23.00	0.124	2025/2/14	

< LTE Band 26a>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	26740/819	10M QPSK(1,24)	0.153	0.117	1.20	24.41	24.50	0.156	2025/2/10	33#
Left Tilt 15 Degree	26740/819	10M QPSK(1,24)	0.083	0.062	-1.47	24.41	24.50	0.085	2025/2/10	
Right Cheek	26740/819	10M QPSK(1,24)	0.135	0.098	1.03	24.41	24.50	0.138	2025/2/10	
Right Tilt 15 Degree	26740/819	10M QPSK(1,24)	0.067	0.050	-1.11	24.41	24.50	0.068	2025/2/10	
50%RB										
Left Cheek	26740/819	10M QPSK(25,12)	0.078	0.059	-2.67	23.40	23.50	0.080	2025/2/10	
Left Tilt 15 Degree	26740/819	10M QPSK(25,12)	0.042	0.037	4.85	23.40	23.50	0.043	2025/2/10	
Right Cheek	26740/819	10M QPSK(25,12)	0.077	0.051	-4.36	23.40	23.50	0.079	2025/2/10	
Right Tilt 15 Degree	26740/819	10M QPSK(25,12)	0.036	0.027	0.72	23.40	23.50	0.037	2025/2/10	

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift	Conducted power	Tune-up power	Scaled SAR	Date	Plot
---------------	---------------------	-----------	------------------	--	-------------	-----------------	---------------	------------	------	------

of Hotspot with 10mm			1g	10g	(±5%)	(dBm)	(dBm)	1g (W/Kg)		
1RB										
Front Side	26740/819	10M QPSK(1,24)	0.126	0.079	-0.46	24.41	24.50	0.129	2025/2/10	
Back Side	26740/819	10M QPSK(1,24)	0.180	0.113	1.65	24.41	24.50	0.184	2025/2/10	34#
Left Side	26740/819	10M QPSK(1,24)	0.060	0.037	1.40	24.41	24.50	0.061	2025/2/10	
Right Side	26740/819	10M QPSK(1,24)	0.066	0.040	3.58	24.41	24.50	0.067	2025/2/10	
Bottom Side	26740/819	10M QPSK(1,24)	0.100	0.063	-0.48	24.41	24.50	0.102	2025/2/10	
50%RB										
Front Side	26740/819	10M QPSK(25,12)	0.063	0.040	-0.18	23.40	23.50	0.064	2025/2/10	
Back Side	26740/819	10M QPSK(25,12)	0.101	0.062	-2.15	23.40	23.50	0.103	2025/2/10	
Left Side	26740/819	10M QPSK(25,12)	0.034	0.022	-3.96	23.40	23.50	0.035	2025/2/10	
Right Side	26740/819	10M QPSK(25,12)	0.036	0.023	-4.64	23.40	23.50	0.037	2025/2/10	
Bottom Side	26740/819	10M QPSK(25,12)	0.054	0.034	1.45	23.40	23.50	0.055	2025/2/10	

< LTE Band 26b>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	26865/831.5	15M QPSK(1,0)	0.084	0.066	3.69	23.55	24.00	0.093	2025/2/10	35#
Left Tilt 15 Degree	26865/831.5	15M QPSK(1,0)	0.045	0.034	0.20	23.55	24.00	0.050	2025/2/10	
Right Cheek	26865/831.5	15M QPSK(1,0)	0.073	0.057	-1.58	23.55	24.00	0.081	2025/2/10	

Right Tilt 15 Degree	26865/831.5	15M QPSK(1,0)	0.039	0.029	0.04	23.55	24.00	0.043	2025/2/10	
50%RB										
Left Cheek	26865/831.5	15M QPSK(36,0)	0.044	0.034	4.35	22.78	23.00	0.046	2025/2/10	
Left Tilt 15 Degree	26865/831.5	15M QPSK(36,0)	0.026	0.020	2.69	22.78	23.00	0.027	2025/2/10	
Right Cheek	26865/831.5	15M QPSK(36,0)	0.042	0.033	0.21	22.78	23.00	0.044	2025/2/10	
Right Tilt 15 Degree	26865/831.5	15M QPSK(36,0)	0.023	0.016	-0.84	22.78	23.00	0.024	2025/2/10	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	26865/831.5	15M QPSK(1,0)	0.060	0.038	-1.79	23.55	24.00	0.067	2025/2/10	
Back Side	26865/831.5	15M QPSK(1,0)	0.095	0.062	4.32	23.55	24.00	0.105	2025/2/10	36#
Left Side	26865/831.5	15M QPSK(1,0)	0.033	0.021	1.06	23.55	24.00	0.037	2025/2/10	
Right Side	26865/831.5	15M QPSK(1,0)	0.032	0.020	-1.08	23.55	24.00	0.035	2025/2/10	
Bottom Side	26865/831.5	15M QPSK(1,0)	0.055	0.035	3.64	23.55	24.00	0.061	2025/2/10	
50%RB										
Front Side	26865/831.5	15M QPSK(36,0)	0.030	0.020	-3.25	22.78	23.00	0.032	2025/2/10	
Back Side	26865/831.5	15M QPSK(36,0)	0.050	0.036	-1.78	22.78	23.00	0.053	2025/2/10	
Left Side	26865/831.5	15M QPSK(36,0)	0.019	0.011	4.18	22.78	23.00	0.020	2025/2/10	
Right	26865/831.5	15M QPSK(36,0)	0.017	0.010	4.22	22.78	23.00	0.018	2025/2/10	

Side										
Bottom Side	26865/831.5	15M QPSK(36,0)	0.029	0.021	-2.45	22.78	23.00	0.031	2025/2/10	

< LTE Band 38>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	38000/2595	20M QPSK(1,99)	0.192	0.147	0.21	20.10	21.00	0.236	2025/2/17	43#
Left Tilt 15 Degree	38000/2595	20M QPSK(1,99)	0.104	0.079	1.83	20.10	21.00	0.128	2025/2/17	
Right Cheek	38000/2595	20M QPSK(1,99)	0.181	0.133	2.10	20.10	21.00	0.223	2025/2/17	
Right Tilt 15 Degree	38000/2595	20M QPSK(1,99)	0.089	0.068	-2.37	20.10	21.00	0.109	2025/2/17	
50%RB										
Left Cheek	38000/2595	20M QPSK(50,24)	0.104	0.078	-2.45	18.24	18.50	0.110	2025/2/17	
Left Tilt 15 Degree	38000/2595	20M QPSK(50,24)	0.061	0.041	-4.72	18.24	18.50	0.065	2025/2/17	
Right Cheek	38000/2595	20M QPSK(50,24)	0.096	0.068	1.18	18.24	18.50	0.102	2025/2/17	
Right Tilt 15 Degree	38000/2595	20M QPSK(50,24)	0.050	0.041	-4.28	18.24	18.50	0.053	2025/2/17	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front	38000/2595	20M OPSK(1.99)	0.234	0.144	2.58	20.10	21.00	0.288	2025/2/17	

Side										
Back Side	38000/2595	20M QPSK(1,99)	0.390	0.253	0.23	20.10	21.00	0.480	2025/2/17	44#
Left Side	38000/2595	20M QPSK(1,99)	0.129	0.084	-0.06	20.10	21.00	0.159	2025/2/17	
Right Side	38000/2595	20M QPSK(1,99)	0.132	0.085	-3.81	20.10	21.00	0.162	2025/2/17	
Bottom Side	38000/2595	20M QPSK(1,99)	0.210	0.131	-3.91	20.10	21.00	0.258	2025/2/17	
50%RB										
Front Side	38000/2595	20M QPSK(50,24)	0.131	0.081	-4.15	18.24	18.50	0.139	2025/2/17	
Back Side	38000/2595	20M QPSK(50,24)	0.208	0.127	-0.90	18.24	18.50	0.221	2025/2/17	
Left Side	38000/2595	20M QPSK(50,24)	0.070	0.048	-3.57	18.24	18.50	0.074	2025/2/17	
Right Side	38000/2595	20M QPSK(50,24)	0.072	0.050	3.27	18.24	18.50	0.076	2025/2/17	
Bottom Side	38000/2595	20M QPSK(50,24)	0.105	0.071	-2.27	18.24	18.50	0.111	2025/2/17	

< LTE Band 41>

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Left Cheek	40620/2593	20M QPSK(1,0)	0.277	0.204	0.65	19.04	20.50	0.388	2025/2/17	29#
Left Tilt 15 Degree	40620/2593	20M QPSK(1,0)	0.166	0.120	-4.00	19.04	20.50	0.232	2025/2/17	
Right Cheek	40620/2593	20M QPSK(1,0)	0.247	0.180	-2.79	19.04	20.50	0.346	2025/2/17	
Right Tilt 15 Degree	40620/2593	20M QPSK(1,0)	0.124	0.090	0.60	19.04	20.50	0.174	2025/2/17	
50%RB										
Left Cheek	40620/2593	20M QPSK(50,49)	0.139	0.114	-3.15	18.20	19.50	0.188	2025/2/17	

Left Tilt 15 Degree	40620/2593	20M QPSK(50,49)	0.095	0.065	-2.74	18.20	19.50	0.128	2025/2/17	
Right Cheek	40620/2593	20M QPSK(50,49)	0.132	0.091	0.44	18.20	19.50	0.178	2025/2/17	
Right Tilt 15 Degree	40620/2593	20M QPSK(50,49)	0.074	0.049	2.82	18.20	19.50	0.100	2025/2/17	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	40620/2593	20M QPSK(1,0)	0.282	0.174	-1.72	19.04	20.50	40620/2593	2025/2/17	
Back Side	40620/2593	20M QPSK(1,0)	0.462	0.291	-4.63	19.04	20.50	40620/2593	2025/2/17	30#
Left Side	40620/2593	20M QPSK(1,0)	0.150	0.094	-2.94	19.04	20.50	40620/2593	2025/2/17	
Right Side	40620/2593	20M QPSK(1,0)	0.141	0.084	-0.88	19.04	20.50	40620/2593	2025/2/17	
Bottom Side	40620/2593	20M QPSK(1,0)	0.245	0.147	-2.39	19.04	20.50	40620/2593	2025/2/17	
50%RB										
Front Side	40620/2593	20M QPSK(50,49)	0.149	0.097	-0.80	18.20	19.50	0.201	2025/2/17	
Back Side	40620/2593	20M QPSK(50,49)	0.242	0.174	4.73	18.20	19.50	0.326	2025/2/17	
Left Side	40620/2593	20M QPSK(50,49)	0.087	0.052	2.43	18.20	19.50	0.117	2025/2/17	
Right Side	40620/2593	20M QPSK(50,49)	0.077	0.050	0.69	18.20	19.50	0.104	2025/2/17	
Bottom Side	40620/2593	20M QPSK(50,49)	0.125	0.084	1.48	18.20	19.50	0.169	2025/2/17	

< LTE Band 66 >

Test	Test channel	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled	Date	Plot
------	--------------	-----------	-----------	-------	-----------	---------	--------	------	------

Position	/Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)		
			1g	10g						
1RB										
Left Cheek	132322/1745	20M QPSK(1,0)	0.062	0.043	0.21	23.53	24.00	0.069	2025/2/12	31#
Left Tilt 15 Degree	132322/1745	20M QPSK(1,0)	0.032	0.022	0.72	23.53	24.00	0.036	2025/2/12	
Right Cheek	132322/1745	20M QPSK(1,0)	0.054	0.036	1.79	23.53	24.00	0.060	2025/2/12	
Right Tilt 15 Degree	132322/1745	20M QPSK(1,0)	0.029	0.020	-2.20	23.53	24.00	0.032	2025/2/12	
50%RB										
Left Cheek	132322/1745	20M QPSK(50,49)	0.035	0.026	2.54	22.64	23.00	0.038	2025/2/12	
Left Tilt 15 Degree	132322/1745	20M QPSK(50,49)	0.019	0.011	2.36	22.64	23.00	0.021	2025/2/12	
Right Cheek	132322/1745	20M QPSK(50,49)	0.032	0.018	-4.17	22.64	23.00	0.035	2025/2/12	
Right Tilt 15 Degree	132322/1745	20M QPSK(50,49)	0.017	0.010	-2.69	22.64	23.00	0.018	2025/2/12	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	132322/1745	20M QPSK(1,0)	0.246	0.141	-2.73	23.53	24.00	0.274	2025/2/12	
Back Side	132322/1745	20M QPSK(1,0)	0.375	0.222	1.27	23.53	24.00	0.418	2025/2/12	32#
Left Side	132322/1745	20M QPSK(1,0)	0.120	0.070	-2.56	23.53	24.00	0.134	2025/2/12	

Right Side	132322/1745	20M QPSK(1,0)	0.126	0.072	1.22	23.53	24.00	0.140	2025/2/12	
Bottom Side	132322/1745	20M QPSK(1,0)	0.210	0.124	-0.17	23.53	24.00	0.234	2025/2/12	
50%RB										
Front Side	132322/1745	20M QPSK(50,49)	0.130	0.077	-3.77	22.64	23.00	0.141	2025/2/12	
Back Side	132322/1745	20M QPSK(50,49)	0.195	0.125	4.87	22.64	23.00	0.212	2025/2/12	
Left Side	132322/1745	20M QPSK(50,49)	0.072	0.036	-3.14	22.64	23.00	0.078	2025/2/12	
Right Side	132322/1745	20M QPSK(50,49)	0.075	0.040	0.21	22.64	23.00	0.081	2025/2/12	
Bottom Side	132322/1745	20M QPSK(50,49)	0.110	0.065	1.62	22.64	23.00	0.120	2025/2/12	

< WiFi 2.4G> ANT1

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	1/2412	802.11b	0.247	0.171	1.06	11.16	11.50	0.267	2025/2/16	15#
Left Cheek	1/2412	802.11b	0.135	0.091	-2.60	11.16	11.50	0.146	2025/2/16	
Left Tilt 15 Degree	1/2412	802.11b	0.228	0.155	-2.14	11.16	11.50	0.247	2025/2/16	
Right Cheek	1/2412	802.11b	0.103	0.070	-2.91	11.16	11.50	0.111	2025/2/16	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	1/2412	802.11b	0.162	0.106	-2.35	11.16	11.50	0.175	2025/2/16	
Back	1/2412	802.11b	0.236	0.156	3.26	11.16	11.50	0.255	2025/2/16	16#

Side										
Left Side	1/2412	802.11b	0.075	0.048	3.53	11.16	11.50	0.081	2025/2/16	
Top Side	1/2412	802.11b	0.081	0.051	-1.19	11.16	11.50	0.088	2025/2/16	

< WiFi 5.2G> ANT1

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	36/5180	802.11a	0.510	0.415	2.31	9.56	10.00	0.564	2025/2/18	11#
Left Tilt 15 Degree	36/5180	802.11a	0.292	0.233	-2.48	9.56	10.00	0.323	2025/2/18	
Right Cheek	36/5180	802.11a	0.460	0.363	-1.97	9.56	10.00	0.509	2025/2/18	
Right Tilt 15 Degree	36/5180	802.11a	0.232	0.179	0.34	9.56	10.00	0.257	2025/2/18	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	36/5180	802.11a	0.318	0.230	-1.83	9.56	10.00	0.352	2025/2/18	
Back Side	36/5180	802.11a	0.509	0.380	1.11	9.56	10.00	0.563	2025/2/18	13#
Left Side	36/5180	802.11a	0.159	0.119	-3.15	9.56	10.00	0.176	2025/2/18	
Top Side	36/5180	802.11a	0.153	0.114	1.83	9.56	10.00	0.169	2025/2/18	

< WiFi 5.8G> ANT1

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR	Date	Plot
---------------	---------------------	-----------	------------------	-------------	-----------------	---------------	------------	------	------

			1g	10g	(±5%)	(dBm)	(dBm)	1g (W/Kg)		
Left Cheek	159/5795	802.11N40	0.553	0.458	3.02	10.79	11.00	0.580	2025/2/19	12#
Left Tilt 15 Degree	159/5795	802.11N40	0.317	0.263	-2.78	10.79	11.00	0.333	2025/2/19	
Right Cheek	159/5795	802.11N40	0.499	0.401	-1.20	10.79	11.00	0.524	2025/2/19	
Right Tilt 15 Degree	159/5795	802.11N40	0.227	0.186	0.11	10.79	11.00	0.238	2025/2/19	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	159/5795	802.11N40	0.354	0.270	0.80	10.79	11.00	0.372	2025/2/19	
Back Side	159/5795	802.11N40	0.553	0.430	2.01	10.79	11.00	0.580	2025/2/19	14#
Left Side	159/5795	802.11N40	0.171	0.133	-3.10	10.79	11.00	0.179	2025/2/19	
Top Side	159/5795	802.11N40	0.180	0.136	-2.92	10.79	11.00	0.189	2025/2/19	

< WiFi 2.4G> ANT2

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	1/2412	802.11b	0.246	0.170	2.54	12.23	12.50	0.262	2025/2/16	41#
Left Cheek	1/2412	802.11b	0.133	0.089	0.59	12.23	12.50	0.142	2025/2/16	
Left Tilt 15 Degree	1/2412	802.11b	0.233	0.161	-1.42	12.23	12.50	0.248	2025/2/16	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	1/2412	802.11b	0.132	0.063	2.57	12.23	12.50	0.140	2025/2/16	
Back Side	1/2412	802.11b	0.193	0.093	0.12	12.23	12.50	0.205	2025/2/16	42#
Left Side	1/2412	802.11b	0.060	0.028	2.82	12.23	12.50	0.064	2025/2/16	
Top Side	1/2412	802.11b	0.069	0.033	-1.34	12.23	12.50	0.073	2025/2/16	

Test Position of Hotspot with	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						

10mm										
Front Side	40/5200	802.11a	0.078	0.046	-3.64	9.54	10.00	0.087	2025/2/18	
Back Side	40/5200	802.11a	0.094	0.055	0.57	9.54	10.00	0.105	2025/2/18	39#
Left Side	40/5200	802.11a	0.042	0.024	0.79	9.54	10.00	0.047	2025/2/18	
Top Side	40/5200	802.11a	0.033	0.019	0.60	9.54	10.00	0.037	2025/2/18	

< WiFi 5.8G> ANT2

Test Position	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Left Cheek	165/5825	802.11a	0.242	0.084	1.45	10.82	11.00	0.252	2025/2/19	38#
Left Tilt 15 Degree	165/5825	802.11a	0.156	0.050	0.97	10.82	11.00	0.163	2025/2/19	
Right Cheek	165/5825	802.11a	0.201	0.065	2.34	10.82	11.00	0.210	2025/2/19	
Right Tilt 15 Degree	165/5825	802.11a	0.132	0.041	3.69	10.82	11.00	0.138	2025/2/19	

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	165/5825	802.11a	0.084	0.046	-1.58	10.82	11.00	0.088	2025/2/19	
Back Side	165/5825	802.11a	0.102	0.058	3.02	10.82	11.00	0.106	2025/2/19	40#
Left Side	165/5825	802.11a	0.042	0.024	2.60	10.82	11.00	0.044	2025/2/19	
Top Side	165/5825	802.11a	0.033	0.018	3.05	10.82	11.00	0.034	2025/2/19	

12. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

1) Scalar SAR summation < 1.6W/kg.

2) SPLSR = $\frac{(SAR_1 + SAR_2)^{1.5}}{r}$ / (min. separation distance, mm), and the peak separation distance is

determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where

(x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.

If SPLSR ≤ 0.04, simultaneously transmission SAR measurement is not necessary.

No.	Simultaneous Tx	Head	Body-worn	Hotspot
1	WWAN+WLAN	Yes	Yes	Yes
2	WWAN+Bluetooth	Yes	Yes	Yes

Note : WiFi and Bluetooth use the same antenna and cannot be transmitted at the same time.

Exposure Position		WWAN Band	NII/DTSS/DSS ANT1+ANT2	Simultaneous Tx SAR(W/Kg)
		SAR(W/Kg)	SAR(W/Kg)	
Head	Left Cheek	0.615	0.935	1.550
	Left Tilt 15 Degree	0.362	0.631	0.993
	Right Cheek	0.549	0.856	1.405
	Right Tilt 15 Degree	0.253	0.489	0.742
Body&Hotspot	Front Side	0.395	0.460	0.855
	Back Side	0.647	0.686	1.333
	Left Side	0.210	0.223	0.433
	Right Side	0.197	/	0.197
	Top Side	/	0.223	0.223
	Bottom Side	0.343	/	0.343

Note : The Simultaneous Tx is calculated based on the same configuration and test position.

Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 850MHz
MEASUREMENT 2 System Performance Check - 1800MHz
MEASUREMENT 3 System Performance Check - 1900MHz
MEASUREMENT 4 System Performance Check - 2450MHz
MEASUREMENT 5 System Performance Check - 2600MHz
MEASUREMENT 6 System Performance Check - 5200MHz
MEASUREMENT 7 System Performance Check - 5800MHz

MEASUREMENT 1


Date of measurement: 10/2/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.66</u>

B. SAR Measurement Results


Frequency (MHz)	835.000000
Relative permittivity (real part)	42.012031
Relative permittivity (imaginary part)	19.131021
Conductivity (S/m)	0.941030
Variation (%)	0.310000



Maximum location: X=2.00, Y=2.00

SAR Peak: 1.87 W/kg

SAR 10g (W/Kg)	0.612031
SAR 1g (W/Kg)	1.011231



MEASUREMENT 2


Date of measurement: 12/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results


Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.606403
Relative permittivity (imaginary part)	14.067180
Conductivity (S/m)	1.406718
Variation (%)	-0.140000



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.024557
SAR 1g (W/Kg)	3.832112



MEASUREMENT 3


Date of measurement:14/2/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.05</u>

B. SAR Measurement Results


Frequency (MHz)	1900.000000
Relative permittivity (real part)	41.420140
Relative permittivity (imaginary part)	12.570123
Conductivity (S/m)	1.390503
Variation (%)	-0.440000



Maximum location: X=1.00, Y=2.00

SAR Peak: 7.65 W/kg

SAR 10g (W/Kg)	2.153165
SAR 1g (W/Kg)	4.153568



MEASUREMENT 4


Date of measurement: 16/2/2025

A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2450</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.38</u>

B. SAR Measurement Results


Frequency (MHz)	2450.000000
Relative permittivity (real part)	40.408511
Relative permittivity (imaginary part)	13.399264
Conductivity (S/m)	1.823789
Variation (%)	-1.250000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.359425
SAR 1g (W/Kg)	5.183642



MEASUREMENT 5


Date of measurement: 17/2/2025

A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.35</u>

B. SAR Measurement Results



Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.432362
Relative permittivity (imaginary part)	13.768602
Conductivity (S/m)	1.988798
Variation (%)	-3.980000



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.523157
SAR 1g (W/Kg)	5.432595

3D screen shot	Hot spot position
	

MEASUREMENT 6


Date of measurement: 18/2/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5200</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	37.400000
Relative permittivity (imaginary part)	16.129999
Conductivity (S/m)	4.510778
Variation (%)	-4.570000



Maximum location: X=0.00, Y=1.00

SAR Peak: 15.14 W/kg

SAR 10g (W/Kg)	5.212361
SAR 1g (W/Kg)	14.712032

3D screen shot	Hot spot position
	

MEASUREMENT 7


Date of measurement: 19/2/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>2.27</u>

B. SAR Measurement Results



Frequency (MHz)	5800.000000
Relative permittivity (real part)	35.299999
Relative permittivity (imaginary part)	16.360001
Conductivity (S/m)	5.271556
Variation (%)	-2.480000



Maximum location: X=-1.00, Y=2.00

SAR Peak: 17.07 W/kg

SAR 10g (W/Kg)	5.623106
SAR 1g (W/Kg)	16.421035

3D screen shot	Hot spot position
	

Appendix C. SAR Test Plots

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WALN 5.2G Head ANT1
MEASUREMENT 12 WALN 5.8G Head ANT1
MEASUREMENT 13 WALN 5.2G Body ANT1
MEASUREMENT 14 WALN 5.8G Body ANT1
MEASUREMENT 15 WALN 2.4G Head ANT1
MEASUREMENT 16 WALN 2.4G Body ANT1
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 25 Head
MEASUREMENT 26 LTE Band 25 Body
MEASUREMENT 29 LTE Band 41 Head
MEASUREMENT 30 LTE Band 41 Body
MEASUREMENT 31 LTE Band 66 Head
MEASUREMENT 32 LTE Band 66 Body
MEASUREMENT 33 LTE Band 26a Head
MEASUREMENT 34 LTE Band 26a Body
MEASUREMENT 35 LTE Band 26b Head
MEASUREMENT 36 LTE Band 26b Body
MEASUREMENT 37 WALN 5.2G Head ANT2
MEASUREMENT 38 WALN 5.8G Head ANT2
MEASUREMENT 39 WALN 5.2G Body ANT2

MEASUREMENT 40 WALN 5.8G Body ANT2
MEASUREMENT 41 WALN 2.4G Head ANT2
MEASUREMENT 42 WALN 2.4G Body ANT2
MEASUREMENT 43 LTE Band 38 Head
MEASUREMENT 44 LTE Band 38 Body

MEASUREMENT 1


Date of measurement: 10/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.400024
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901453
Variation (%)	0.210000



Maximum location: X=-66.00, Y=-50.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.239675
SAR 1g (W/Kg)	0.324748

3D screen shot	Hot spot position
	

MEASUREMENT 2


Date of measurement: 10/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.400024
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901453
Variation (%)	0.549999



Maximum location: X=-10.00, Y=-38.00

SAR Peak: 0.50 W/kg

SAR 10g (W/Kg)	0.163201
SAR 1g (W/Kg)	0.285410

3D screen shot	Hot spot position
	

MEASUREMENT 3


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.408000
Conductivity (S/m)	1.400391
Variation (%)	1.540000



Maximum location: X=-72.00, Y=-65.00

SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.118777
SAR 1g (W/Kg)	0.281267

3D screen shot	Hot spot position
	

MEASUREMENT 4


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results


Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.408000
Conductivity (S/m)	1.400391
Variation (%)	-1.020002



Maximum location: X=17.00, Y=-32.00

SAR Peak: 0.55 W/kg

SAR 10g (W/Kg)	0.144543
SAR 1g (W/Kg)	0.236040



MEASUREMENT 5


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.408000
Conductivity (S/m)	1.400391
Variation (%)	1.230000



Maximum location: X=-51.00, Y=-51.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.047270
SAR 1g (W/Kg)	0.076228

3D screen shot	Hot spot position
	

MEASUREMENT 6


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results


Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.408000
Conductivity (S/m)	1.400391
Variation (%)	1.450000



Maximum location: X=20.00, Y=-30.00

SAR Peak: 0.54 W/kg

SAR 10g (W/Kg)	0.199237
SAR 1g (W/Kg)	0.350144



MEASUREMENT 7


Date of measurement: 12/2/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>Band4 WCDMA1700</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1732.600000
Relative permittivity (real part)	40.116364
Relative permittivity (imaginary part)	14.137455
Conductivity (S/m)	1.360337
Variation (%)	-3.540000



Maximum location: X=-52.00, Y=-52.00

SAR Peak: 0.18 W/kg

SAR 10g (W/Kg)	0.078245
SAR 1g (W/Kg)	0.122665

3D screen shot	Hot spot position
	

MEASUREMENT 8


Date of measurement: 12/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1732.600000
Relative permittivity (real part)	40.116364
Relative permittivity (imaginary part)	14.137455
Conductivity (S/m)	1.360337
Variation (%)	-1.250000



Maximum location: X=-9.00, Y=-39.00

SAR Peak: 0.68 W/kg

SAR 10g (W/Kg)	0.260321
SAR 1g (W/Kg)	0.386450

3D screen shot	Hot spot position
	

MEASUREMENT 9


Date of measurement: 10/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.400024
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901453
Variation (%)	1.520000



Maximum location: X=-39.00, Y=-53.00

SAR Peak: 0.40 W/kg

SAR 10g (W/Kg)	0.185210
SAR 1g (W/Kg)	0.284026

3D screen shot	Hot spot position
	

MEASUREMENT 10


Date of measurement: 10/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.400024
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901453
Variation (%)	1.360000



Maximum location: X=-9.00, Y=-38.00

SAR Peak: 0.50 W/kg

SAR 10g (W/Kg)	0.170274
SAR 1g (W/Kg)	0.290139

3D screen shot	Hot spot position
	

MEASUREMENT 11


Date of measurement: 18/2/2025

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11a U-NII</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.a (Crest factor: 1.0)</u>
ConvF	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5180.000000
Relative permittivity (real part)	36.000000
Relative permittivity (imaginary part)	16.129999
Conductivity (S/m)	4.641855
Variation (%)	2.310000



Maximum location: X=-38.00, Y=-57.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.415102
SAR 1g (W/Kg)	0.510120

3D screen shot	Hot spot position
	

MEASUREMENT 12


Date of measurement: 19/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11n U-NII</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>IEEE802.n (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.27</u>

B. SAR Measurement Results



Frequency (MHz)	5795.000000
Relative permittivity (real part)	35.301200
Relative permittivity (imaginary part)	16.355245
Conductivity (S/m)	5.265480
Variation (%)	3.020000



Maximum location: X=-35.00, Y=-27.00

SAR Peak: 1.65 W/kg

SAR 10g (W/Kg)	0.458402
SAR 1g (W/Kg)	0.553205

3D screen shot	Hot spot position
	

MEASUREMENT 13


Date of measurement: 18/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.a (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.30</u>

B. SAR Measurement Results



Frequency (MHz)	5180.000000
Relative permittivity (real part)	36.000000
Relative permittivity (imaginary part)	16.129999
Conductivity (S/m)	4.641855
Variation (%)	1.110000



Maximum location: X=-19.00, Y=-33.00

SAR Peak: 1.10 W/kg

SAR 10g (W/Kg)	0.380223
SAR 1g (W/Kg)	0.509412

3D screen shot	Hot spot position
	

MEASUREMENT 14


Date of measurement: 19/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11n U-NII</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>IEEE802.n (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.27</u>

B. SAR Measurement Results



Frequency (MHz)	5795.000000
Relative permittivity (real part)	35.301200
Relative permittivity (imaginary part)	16.355245
Conductivity (S/m)	5.265480
Variation (%)	2.010000



Maximum location: X=-1.00, Y=-31.00

SAR Peak: 1.04 W/kg

SAR 10g (W/Kg)	0.430214
SAR 1g (W/Kg)	0.553254

3D screen shot	Hot spot position
	

MEASUREMENT 15


Date of measurement: 16/2/2025

A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11b ISM</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.b (Crest factor: 1.0)</u>
ConvF	<u>2.38</u>

B. SAR Measurement Results



Frequency (MHz)	2412.000000
Relative permittivity (real part)	39.226002
Relative permittivity (imaginary part)	13.207000
Conductivity (S/m)	1.769738
Variation (%)	1.060000



Maximum location: X=-38.00, Y=-50.00

SAR Peak: 0.44 W/kg

SAR 10g (W/Kg)	0.170845
SAR 1g (W/Kg)	0.247412

3D screen shot	Hot spot position
	

MEASUREMENT 16


Date of measurement: 16/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.b (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.38</u>

B. SAR Measurement Results



Frequency (MHz)	2412.000000
Relative permittivity (real part)	39.226002
Relative permittivity (imaginary part)	13.207000
Conductivity (S/m)	1.769738
Variation (%)	3.260000



Maximum location: X=-15.00, Y=-36.00

SAR Peak: 0.41 W/kg

SAR 10g (W/Kg)	0.156210
SAR 1g (W/Kg)	0.236324

3D screen shot	Hot spot position
	

MEASUREMENT 17


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1879.500000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.411700
Conductivity (S/m)	1.400405
Variation (%)	2.140000



Maximum location: X=-51.00, Y=-21.00

SAR Peak: 0.70 W/kg

SAR 10g (W/Kg)	0.320221
SAR 1g (W/Kg)	0.441962

3D screen shot	Hot spot position
	

MEASUREMENT 18


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1879.500000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.411700
Conductivity (S/m)	1.400405
Variation (%)	2.650001



Maximum location: X=-10.00, Y=-39.00

SAR Peak: 0.67 W/kg

SAR 10g (W/Kg)	0.243215
SAR 1g (W/Kg)	0.393058

3D screen shot	Hot spot position
	

MEASUREMENT 19


Date of measurement: 12/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1732.500000
Relative permittivity (real part)	40.115910
Relative permittivity (imaginary part)	14.136136
Conductivity (S/m)	1.360603
Variation (%)	2.010000



Maximum location: X=-37.00, Y=-53.00

SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.292028
SAR 1g (W/Kg)	0.445102

3D screen shot	Hot spot position
	

MEASUREMENT 20


Date of measurement: 12/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results


Frequency (MHz)	1732.500000
Relative permittivity (real part)	40.115910
Relative permittivity (imaginary part)	14.136136
Conductivity (S/m)	1.360603
Variation (%)	-3.570000



Maximum location: X=-5.00, Y=-15.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.280727
SAR 1g (W/Kg)	0.449078



MEASUREMENT 21


Date of measurement: 10/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.500000
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901561
Variation (%)	-3.909999



Maximum location: X=-38.00, Y=-54.00

SAR Peak: 0.39 W/kg

SAR 10g (W/Kg)	0.189542
SAR 1g (W/Kg)	0.285327

3D screen shot	Hot spot position
	

MEASUREMENT 22


Date of measurement: 10/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.66</u>

B. SAR Measurement Results



Frequency (MHz)	836.500000
Relative permittivity (real part)	41.500000
Relative permittivity (imaginary part)	19.400000
Conductivity (S/m)	0.901561
Variation (%)	-1.079999



Maximum location: X=-10.00, Y=-40.00

SAR Peak: 0.41 W/kg

SAR 10g (W/Kg)	0.163002
SAR 1g (W/Kg)	0.256314

3D screen shot	Hot spot position
	

MEASUREMENT 23


Date of measurement: 17/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.086666
Relative permittivity (imaginary part)	13.418333
Conductivity (S/m)	1.889749
Variation (%)	3.620001



Maximum location: X=-36.00, Y=-49.00

SAR Peak: 0.51 W/kg

SAR 10g (W/Kg)	0.190547
SAR 1g (W/Kg)	0.256048

3D screen shot	Hot spot position
	

MEASUREMENT 24


Date of measurement: 17/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.086666
Relative permittivity (imaginary part)	13.418333
Conductivity (S/m)	1.889749
Variation (%)	-1.350001



Maximum location: X=-5.00, Y=-35.00

SAR Peak: 0.80 W/kg

SAR 10g (W/Kg)	0.295512
SAR 1g (W/Kg)	0.465473

3D screen shot	Hot spot position
	

MEASUREMENT 25


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 25</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1882.500000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.393200
Conductivity (S/m)	1.400333
Variation (%)	0.870000



Maximum location: X=-38.00, Y=-57.00

SAR Peak: 0.72 W/kg

SAR 10g (W/Kg)	0.300120
SAR 1g (W/Kg)	0.472140

3D screen shot	Hot spot position
	

MEASUREMENT 26


Date of measurement: 14/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 25</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1882.500000
Relative permittivity (real part)	40.000000
Relative permittivity (imaginary part)	13.393200
Conductivity (S/m)	1.400333
Variation (%)	0.870001



Maximum location: X=-10.00, Y=-41.00

SAR Peak: 0.61 W/kg

SAR 10g (W/Kg)	0.245402
SAR 1g (W/Kg)	0.391336

3D screen shot	Hot spot position
	

MEASUREMENT 29


Date of measurement: 17/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 41</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	2593.000000
Relative permittivity (real part)	39.009335
Relative permittivity (imaginary part)	13.553667
Conductivity (S/m)	1.952481
Variation (%)	0.650000



Maximum location: X=-45.00, Y=-60.00

SAR Peak: 0.54 W/kg

SAR 10g (W/Kg)	0.203845
SAR 1g (W/Kg)	0.277203

3D screen shot	Hot spot position
	

MEASUREMENT 30


Date of measurement: 17/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 41</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	2593.000000
Relative permittivity (real part)	39.009335
Relative permittivity (imaginary part)	13.553667
Conductivity (S/m)	1.952481
Variation (%)	-4.630000



Maximum location: X=-12.00, Y=-36.00

SAR Peak: 0.92 W/kg

SAR 10g (W/Kg)	0.291254
SAR 1g (W/Kg)	0.462103

3D screen shot	Hot spot position
	

MEASUREMENT 31


Date of measurement: 12/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>CUSTOM (LTEBand66)</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results



Frequency (MHz)	1745.000000
Relative permittivity (real part)	40.104546
Relative permittivity (imaginary part)	14.103182
Conductivity (S/m)	1.367225
Variation (%)	0.210000



Maximum location: X=-51.00, Y=-51.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.043214
SAR 1g (W/Kg)	0.062060

3D screen shot	Hot spot position
 A 3D perspective view of a grey, bowl-shaped structure on a light blue surface. A small, rectangular area on the right side of the bowl is highlighted with a grid of green and yellow dots, indicating the hot spot position.	 A 3D visualization of the hot spot position. It shows a green, irregularly shaped volume with a yellow and red core, indicating the intensity of the hot spot. The volume is positioned over a grey, bowl-shaped structure on a light blue surface.

MEASUREMENT 32


Date of measurement: 12/2/2025

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>CUSTOM (LTEBand66)</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.05</u>

B. SAR Measurement Results


Frequency (MHz)	1745.000000
Relative permittivity (real part)	40.104546
Relative permittivity (imaginary part)	14.103182
Conductivity (S/m)	1.367225
Variation (%)	1.270000



Maximum location: X=-9.00, Y=-31.00

SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)	0.222364
SAR 1g (W/Kg)	0.374754



MEASUREMENT 33


Date of measurement: 10/2/2025

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>CUSTOM (LTEBand26A)</u>
Channels	<u>Middle</u>
Signal	<u>(Crest factor: 1.0)</u>
ConvF	<u>1.66</u>

B. SAR Measurement Results

Frequency (MHz)	819.000000
Relative permittivity (real part)	41.575294
Relative permittivity (imaginary part)	19.768942
Conductivity (S/m)	0.899487
Variation (%)	1.200000



Maximum location: X=-52.00, Y=-27.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.117201
SAR 1g (W/Kg)	0.153326