



RF TEST REPORT

Report No.:SHATBL2512025W05

Applicant : Shenzhen DOOGEE Hengtong Technology CO.,LTD

Product Name : Smart Phone

Brand Name : DOOGEE

Model Name : S300 Plus

Series Model : S300,S300 Pro,S300 Plus Thermal,S300 Ultra,S300 Max,
S300 Pro Max,V MAX 2 ,V MAX 2 Pro,V Max 2 Plus,
V Max 2 Ultra,V Max 2 SE

FCC ID : 2AX4YS300PLUS

Test Standard : 47 CFR Part 2, Part 24E, Part 22H

Date of Sample Arrival : Nov.24, 2025

Date of Test : Nov.24, 2025~Feb.11, 2026

Issue Date : Feb.11, 2026

Report Prepared by :

Emily

(Emily)

Report Approved by :

Guozheng Li

(Guozheng Li)

Authorized Signatory :

Terry Yang

(Terry Yang)



"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

Tel:+86(0)21-51298625

Web:www.atbl-lab.com

Email:atbl@atbl-lab.com

TABLE OF CONTENTS

REVISION HISTORY	3
DECLARATION OF REPORT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Factory	5
1.4. General Information of EUT	6
1.5. Environmental conditions	7
1.6. Modification of EUT	7
1.7. Laboratory Information	7
1.8. Applicable Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1. Test Mode	8
2.2. Summary of Test Results	8
2.3. Connection Diagram of Test System	9
2.4. Support Unit used in test configuration and system	9
2.5. Equipment List	10
2.6. Measurement Uncertainty	12
3. TEST RESULT	13
3.1. Conducted Output Power	13
3.2. Effective Radiated Power and Effective Isotropic Radiated Power	14
3.3. Peak-to-Average Ratio	16
3.4. Occupied Bandwidth	17
3.5. Conducted Band Edge	19
3.6. Conducted Spurious Emission	21
3.7. Frequency Stability	22
3.8. Radiated Spurious Emission	23
4. TEST SETUP PHOTOGRAPHS	41
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	41

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
00	Feb.11, 2026	Initial Release	

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2, Part 24E, Part 22H. And it is applicable only to the tested sample identified in the report.

2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.

3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.

4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.

1. GENERAL DESCRIPTION

1.1. Applicant

Name : Shenzhen DOOGEE Hengtong Technology CO.,LTD
Address : B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No.22,Longhua New District Shenzhen China

1.2. Manufacturer

Name : Shenzhen DOOGEE Hengtong Technology CO.,LTD
Address : B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No.22,Longhua New District Shenzhen China

1.3. Factory

Name : Shenzhen DOOGEE Hengtong Technology CO.,LTD
Address : B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No.22,Longhua New District Shenzhen China

1.4. General Information of EUT

Test Sample	202512024007	
Product Name:	Smart Phone	
Brand Name	DOOGEE	
Model Name	S300 Plus	
Series Model	S300,S300 Pro,S300 Plus Thermal,S300 Ultra,S300 Max, S300 Pro Max,V MAX 2 ,V MAX 2 Pro,V Max 2 Plus,V Max 2 Ultra, V Max 2 SE	
Model Difference	Only the model name, appearance color, and memory different.	
Hardware Version:	M1805-MUB-V3-BOM1	
Software Version:	DOOGEE-S300 Plus-EEA-Android15.0-20251213	
Support Networks:	GSM, GPRS, EDGE	
Frequency Bands:	☒ GPRS 850 ☒ PCS1900 (U.S. Bands) ☐ GSM 900 ☐ DCS 1800 (Non-U.S. Bands)	
Type of Modulation:	GMSK,8PSK Modulation For GSM/GPRS/EDGE	
Frequency Range:	GSM/GPRS/EDGE 850: 824.2MHz-848.8 MHz	
	GSM/GPRS/EDGE 1900: 1850.2MHz-1909.8 MHz	
Emission Designator:	GSM/GPRS 850:	243KGXW
	EDGE 850:	243KG7W
	GSM/GPRS 1900:	243KGXW
	EDGE 1900:	243KG7W
Antenna Type:	FPC Antenna	
Antenna gain:	GSM850:-2.0dBi	PCS1900: 1.39dBi
Power supply	DC 7.7V	
Adapter	Input:AC100-240V~50/60Hz 2.2A Max Output:5.0V== 3.0A 15.0W;9.0V== 3.0A 27.0W;12.0V== 3.0A 36.0W;15.0V== 3.0A 45.0W;20.0V== 5.0A 100.0W PPS:3.3-20.0V== 6.0A Power:120W Max	
Battery	DC 7.7V 11000mAh	
SIM Card Description:	The prototype supports dual cards	
Connecting I/O Port(s)	Refer to the remark below.	

Remark:

The above information of EUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5. Environmental conditions

Temperature	Normal Temperature(NT):	25°C
	High Temperature(HT):	55°C
	Low Temperature(LT):	-10°C
Voltage	Normal Voltage(NV):	7.7V
	High Voltage(HV):	7.32V
	Low Voltage(LV):	8.47V
Other	Relative Humidity	55 %
	Air Pressure	101 kPa

1.6. Modification of EUT

No modifications are made to the EUT during all test items.

1.7. Laboratory Information

Company Name	:	Shanghai ATBL Technology Co., Ltd.
Address	:	Building 8, No.160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	:	+86(0)21-51298625
FCC-Registration Number	:	485917
Designation Number	:	CN1306
A2LA Number	:	6184.01
CNAS Number	:	CNAS L14531
ISED Designation Number	:	27371
CAB identifier	:	CN0116

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

47 CFR Part 2, 22(H), 24(E)

ANSI C63.26-2015

FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST

2.1. Test Mode

Bands	Tx/Rx Frequency	RF Channel		
		Low(L)	Middle(M)	High(H)
GSM/GPRS/ EDGE850	TX (824 MHz ~ 849 MHz)	Channel 128	Channel 190	Channel 251
		824.2 MHz	836.6 MHz	848.8 MHz

Bands	Tx/Rx Frequency	RF Channel		
		Low(L)	Middle(M)	High(H)
GSM/GPRS/ EDGE1900	TX (1850 MHz-1910 MHz)	Channel 512	Channel 661	Channel 810
		1850.2 MHz	1880.0 MHz	1909.8 MHz

Pre-scan all bandwidth and RB, find worse case mode are chosen to the report, the worse mode applicability and tested channel detail as below:

Band	Radiatd	Conducted
GSM/GPRS/ EDGE850/1900	GSM (GMSK, 1Tx-slot) Link GPRS (GMSK, 1Tx-slot) Link EDGE (8PSK, 1Tx-slot) Link	GSM (GMSK, 1Tx-slot) Link GPRS (GMSK, 1Tx-slot) Link EDGE (8PSK, 1Tx-slot) Link

2.2. Summary of Test Results


Conducted Test:

Item	Test Description	FCC Rules	Result
1	Occupied Bandwidth	§2.1049	Pass
2	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal	§2.1051, §22.917(a), §24.238(a)	Pass
5	Conducted Output Power	§2.1046	Pass
6	Frequency stability / variation of ambient temperature	§2.1055, § 22.355, §24.235	Pass
7	Peak- to- Average Ratio	§24.232(d)	Pass

Radiated Test:

Item	Test Description	FCC Rules	Result
1	Effective Radiated Power	§22.913(a)(5)	Pass
2	Equivalent Isotropic Radiated Power	§24.232(c)	Pass
3	Radiated Spurious and Harmonic Emissions	§2.1053, §22.917(a), §24.238(a),	Pass

2.3. Connection Diagram of Test System



Remarks:

The Signal Analyzer could be connected to a Monopole antenna or directly connected to the EUT, if the EUT has already employing an antenna connector.

2.4. Support Unit used in test configuration and system

NO.	Unit	Brand	Model	Description
1	--	--	--	--
2	--	--	--	--

2.5. Equipment List

2.5.1. For Conducted Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	Calibrated due until	Cal. Interval
Power sensor-Card reader	Cesheng	smu 1003	16I00054SN016	2025.03.19	2026.03.18	1 year
Adjustable Attenuator	Agilent	8494B	MY42144015	2025.07.28	2026.07.27	1 year
Adjustable Attenuator	Agilent	8496B	MY42143776	2025.07.28	2026.07.27	1 year
Environmental Test Chamber	KSON	THS-B6C-150	9159K	2025.03.17	2026.03.16	1 year
Signal analyzer	Keysight	N9020A	MY50510136	2025.07.18	2026.07.17	1 year
Vector signal generator	Agilent	N5182A	MY48180764	2025.07.18	2026.07.17	1 year
Analog signal generator	Keysight	N5182B	MY57300196	2025.07.18	2026.07.17	1 year
Wideband radio communication tester	R&S	CMW500	101331	2025.07.28	2026.07.27	1 year
Switch Box	Cesheng	smu 1003	WCS20221215	2025.03.19	2026.03.18	1 year
Thermometer	DeLi	N/A	N/A	2025.08.01	2026.07.31	1 year
Test Software	Cesheng	WCS-WC N	N/A	N/A	N/A	N/A

2.5.2. For Radiated Spurious Emission

Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	Calibrated due until	Cal. Interval
Signal analyzer	Agilent	N9020A	MY50200811	2025.03.17	2026.03.16	1 year
Amplifier	JPT	JPA0118-5 5-303A	1910001800055 000	2025.03.24	2026.03.23	1 year
Amplifier	JPT	JPA-10M1 G32	2101010003500 1	2025.03.17	2026.03.16	1 year
Antenna/Turn table Controller	Brilliant	N/A	N/A	N/A	N/A	N/A
Loop Antenna(9kHz-30MHz)	Daze	ZN30900C	20077	2025.05.13	2026.05.12	1 year
Bilog Antenna	SCHWAR ZBECK	VULB 9168	01174	2025.05.20	2026.05.19	1 year
Broad-band Horn Antenna	SCHWAR ZBECK	BBHA 9120D	02334	2025.05.20	2026.05.19	1 year
Horn Antenna	COM-PO WER	PAM-1840	10100008	2025.07.27	2026.07.26	1 year
Thermometer	DeLi	N/A	N/A	2025.08.01	2026.07.31	1 year
Test Software	FALA	EMC-RI(V er.4A2)	N/A	N/A	N/A	N/A
Wideband radio communication tester	R&S	CMW500	101331	2025.07.28	2026.07.27	1 year
Spectrum analyzer	R&S	FSV40-N	101761	2025.07.28	2026.07.27	1 year
Vector signal generator	Keysight	N5182B	MY50200811	2025.07.28	2026.07.27	1 year
Alternative Horn Antenna	Schwarzbe ck	BBHA 9120D	2802	2025.07.28	2026.07.27	1 year
Filter Box	XingBo	EZSVFU1 &EZSVFU 2	N/A	2025.07.28	2026.07.27	1 year
Substitute antenna Bilog Antenna	SCHWAR ZBECK	VULB 9168	1449	2025.05.20	2026.05.19	1 year
Substitute antenna Broad-band Horn Antenna	SCHWAR ZBECK	BBHA 9120D	2659	2025.05.20	2026.05.19	1 year

2.5.3. For AC Power-Line Conducted Emission

Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	Calibrated due until	Cal. Interval
EMI Test Receiver	R&S	ESPI	100679	2025.03.17	2026.03.16	1 year
LISN	R&S	ENV216	101300	2025.03.17	2026.03.16	1 year
LISN	R&S	ENV216	100333	2025.03.17	2026.03.16	1 year
CE Cable	Chuangce xing	2M	EMI0014	N/A	N/A	N/A
Temperature & Humidity	Deli	Deli	EMI0015	2025.08.01	2026.07.31	1 year
Testing Software	FALA	EZ-EMC(Ve r.EMC-CON 3A1.1)	EMI0044	N/A	N/A	N/A
Wideband radio communication tester	R&S	CMW500	101331	2025.07.28	2026.07.27	1 year

2.6. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Occupied Channel Bandwidth	$\pm 4\%$
2	Transmitter power conducted	$\pm 0.56 \text{ dB}$
3	Transmitter power Radiated	$\pm 2.20 \text{ dB}$
4	Conducted spurious emission	$\pm 1.60 \text{ dB}$
5	Radiated spurious emission	$\pm 2.20 \text{ dB}$
6	Temperature	$\pm 0.6^\circ\text{C}$
7	Humidity	$\pm 2\%$
8	DC and low frequency voltages	$\pm 0.05\%$
9	Radio frequency error	$\pm 3 \times 10^{-8}$

3. TEST RESULT

3.1. Conducted Output Power

3.1.1. Test Setup



3.1.2. Test Procedures

- 1.The testing follows ANSI C63.26 Section 5.2.
- 2.The transmitter output port was connected to the system simulator.
- 3.Set EUT at maximum power through the system simulator.
- 4.Select lowest, middle, and highest channels for each band and different modulation.
- 5.Measure and record the power level from the system simulator.

3.1.3. Test Result

Please refer to the Appendix F1.


3.2. Effective Radiated Power and Effective Isotropic Radiated Power

3.2.1. Test Limit


The substitution method, in ANSI/TIA-603-E-2016, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v03. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

3.2.2. Test Setup

Test site-up for radiated ERP and/or EIRP measurements



Substitution method set-up for radiated emission



3.2.3. Test Procedures

1. The measurements procedures specified in ANSI/TIA-603-E-2016 were applied.

In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.

2. The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$ERP/EIRP = SGLevel - P_{cl} + G_a$$

where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as SGLevel, typically dBW or dBm);

SGLevel = Signal generator output power or PSD, in dBm or dBW;

G_a = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

P_{cl} = signal attenuation in the connecting cable between the transmitter and antenna.

The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.

From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.

3. The EUT is then put into continuously transmitting mode at its maximum power level. Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step 1 is added to this result.

This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).

ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ dBi}$.


4. Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.4. Test Result

Please refer to the Appendix F1.

3.3. Peak-to-Average Ratio

3.3.1. Test Setup



3.3.2. Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.3. Test Procedures


- 1.The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
- 2.The EUT was connected to spectrum and system simulator via a power divider.
- 3.Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- 4.The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
- 5.Record the deviation as Peak to Average Ratio.

3.3.4. Test Result of Peak-to-Average Ratio

Please refer to the Appendix F2.

3.4. Occupied Bandwidth

3.4.1. Test Setup



3.4.2. Description of Occupied Bandwidth Measurement

1. The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.
2. The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.3. Test Procedures


1. The testing follows ANSI C63.26 Section 5.4.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.4.4. Test Result of Occupied Bandwidth

Please refer to the Appendix F3.

3.5. Conducted Band Edge

3.5.1. Test Setup



3.5.2. Description of Conducted Band Edge Measurement

22.917(a):

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a):

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (g):

For operations in the 600MHz band and 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53 (h):

For operations in the 1710 – 1755 MHz and 1710 – 1780 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.5.3. Test Procedures

- 1.The testing follows ANSI C63.26 section 5.7
- 2.The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 3.The band edges of low and high channels for the highest RF powers were measured.
- 4.Set RBW $\geq$ 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
- 5.Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
- 6.Set spectrum analyzer with RMS detector.
- 7.The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 8.Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}$$


- 9.When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.

3.5.4. Test Result of Conducted Band Edge

Please refer to the Appendix F4.

3.6. Conducted Spurious Emission

3.6.1. Test Setup



3.6.2. Description of Conducted Spurious Emission Measurement

- 1.The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.
- 2.It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.3. Test Procedures


- 1.The testing follows ANSI C63.26 section 5.7
- 2.The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 3.The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4.The middle channel for the highest RF power within the transmitting frequency was measured.
- 5.The conducted spurious emission for the whole frequency range was taken.
- 6.Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
- 7.Set spectrum analyzer with RMS detector.
- 8.Taking the record of maximum spurious emission.
- 9.The RF fundamental frequency should be excluded against the limit line in the operating frequency band
- 10The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)} = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$

3.6.4. Test Result of Conducted Spurious Emission

Please refer to the Appendix F5.

3.7. Frequency Stability

3.7.1. Test Setup



3.7.2. Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.3. Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.4. Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20 \pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


3.7.5. Test Result of Frequency Stability

Please refer to the Appendix F6.


3.8. Radiated Spurious Emission

3.8.1. Test Setup


3.8.1.1. For radiated test below 30MHz



3.8.1.2. For radiated test from 30MHz to 1GHz



3.8.1.3. For radiated test above 1GHz



3.8.2. Description of Radiated Spurious Emission

- 1.The radiated spurious emission was measured by substitution method according to ANSI C63.26.
- 2.The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.
- 3.The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.3. Test Procedures


- 1.The testing follows ANSI C63.26 Section 5.5
- 2.The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
- 3.The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
- 4.The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 5.The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
- 6.During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
- 7.Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 8.A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 9.Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 10.EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
- 11.ERP (dBm) = EIRP - 2.15
- 12.The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.8.4. Test Result of Radiated Spurious Emission

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

For frequencies above 30 MHz, the test results are as follows


Test Results**Radiated spurious emissions - MS allocated a channel****Below 1GHz:****Only the worst model is shown**




Above1GHz:

Test Mode	GSM850_Traffic Mode_Mid CH_Main antenna
-----------	---


Horizontal



Mk.	Freq. (MHz)	Level (dB m)	Limit (dB m)	Margin (dB)	Deg. (deg.)	Hi. (cm)	Factor (dB)	Pol.
Peak:								
1	3016.000	-53.7	-13.0	40.7	0	150	-8.2	H
2	9045.000	-42.3	-13.0	29.3	359.7	150	4.3	H
3	16069.500	-35.6	-13.0	22.6	359.7	150	13.9	H





Test Mode	GSM850_Traffic Mode_High CH_Main antenna
-----------	--




Test Summary Result

Mk.	Freq. (MHz)	Level (dB m)	Limit (dB m)	Margin (dB)	Deg. (deg.)	Hi. (cm)	Factor (dB)	Pol.
Peak:								
1	2544.000	-49.0	-13.0	36.0	359.92	150	-11.5	H
2	9058.500	-42.3	-13.0	29.3	359.92	150	4.3	H
3	12231.000	-40.5	-13.0	27.5	359.92	150	8.1	H









Below 1GHz:
Only the worst model is shown

Test Mode	GSM1900_Traffic Mode_Mid CH_Main antenna
-----------	--




Mk.	Freq. (MHz)	Level (dB m)	Limit (dB m)	Margin (dB)	Deg. (deg.)	Hi. (cm)	Factor (dB)	Pol.
Peak:								
1	42.900	-64.4	-13.0	51.4	342.07	150	-42.0	H
2	50.409	-63.8	-13.0	50.8	106.57	150	-42.4	H
3	68.872	-69.7	-13.0	56.7	7.56	150	-45.3	H
4	94.428	-69.0	-13.0	56.0	181.12	150	-41.0	H
5	102.001	-68.0	-13.0	55.0	75.47	150	-39.3	H
6	147.921	-69.4	-13.0	56.4	44.52	150	-34.7	H




Above1GHz:


Test Mode	GSM1900_Traffic Mode_Mid CH_Main antenna
-----------	--


Horizontal





Mk.	Freq. (MHz)	Level (dB m)	Limit (dB m)	Margin (dB)	Deg. (deg.)	Hi. (cm)	Factor (dB)	Pol.
Peak:								
1	2548.000	-50.9	-13.0	37.9	100.92	150	-11.4	H
2	8116.000	-43.8	-13.0	30.8	166.67	150	4.1	H
3	13504.500	-38.7	-13.0	25.7	359.42	150	10.0	H











4. TEST SETUP PHOTOGRAPHS

Please refer to the Appendix J_Test Setup Template.

5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

External Photos Please refer to the Appendix K_ External Photos of the EUT.

Internal Photos Please refer to the Appendix K_ Internal Photos of the EUT.

※※※※※END OF THE REPORT※※※※※