


TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\92
Memo: 11AX40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.76	4.36	33.45	-30.81	50.76	68.20	17.44	PK	Vertical
2	5727.51	46.35	4.36	33.46	-30.81	53.36	68.20	14.84	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\127
Memo: 11BE40MIMO 5670

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.02	7.34	33.45	-30.81	54.00	68.20	14.20	PK	Horizontal
2	5728.31	46.79	7.35	33.46	-30.81	56.79	68.20	11.41	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\128
Memo: 11BE40MIMO 5670

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	45.62	7.34	33.45	-30.81	55.60	68.20	12.60	PK	Vertical
2	5733.48	46.51	7.36	33.47	-30.81	56.53	68.20	11.67	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\159
Memo: 11BE40MIMO 5670 RU56+RU13

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.84	7.34	33.45	-30.81	53.82	68.20	14.38	PK	Horizontal
2	5735.66	46.45	7.36	33.47	-30.81	56.47	68.20	11.73	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\162
Memo: 11BE40MIMO 5670 RU56+RU13

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.72	7.34	33.45	-30.81	53.70	68.20	14.50	PK	Vertical
2	5742.96	46.80	7.38	33.49	-30.80	56.87	68.20	11.33	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\93
Memo: 11A 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.71	4.36	33.45	-30.81	50.71	68.20	17.49	PK	Horizontal
2	5740.62	46.14	4.36	33.48	-30.80	53.18	68.20	15.02	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\94
Memo: 11A 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.11	4.36	33.45	-30.81	50.11	68.20	18.09	PK	Vertical
2	5736.79	46.46	4.36	33.47	-30.81	53.48	68.20	14.72	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\95
Memo: 11N20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.04	4.36	33.45	-30.81	50.04	68.20	18.16	PK	Horizontal
2	5727.19	46.24	4.36	33.45	-30.81	53.24	68.20	14.96	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\96
Memo: 11N20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	44.66	4.36	33.45	-30.81	51.66	68.20	16.54	PK	Vertical
2	5728.87	47.17	4.36	33.46	-30.81	54.18	68.20	14.02	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\97
Memo: 11AC20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	47.89	4.36	33.45	-30.81	54.89	68.20	13.31	PK	Horizontal
2	5725.58	53.95	4.36	33.45	-30.81	60.95	68.20	7.25	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\98
Memo: 11AC20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	46.41	4.36	33.45	-30.81	53.41	68.20	14.79	PK	Vertical
2	5728.01	47.75	4.36	33.46	-30.81	54.76	68.20	13.44	PK	Vertical

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\99
Memo: 11AX20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	51.80	4.36	33.45	-30.81	58.80	68.20	9.40	PK	Horizontal
2	5725.81	56.72	4.36	33.45	-30.81	63.72	68.20	4.48	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-03-08
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\100
Memo: 11AX20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	51.59	4.36	33.45	-30.81	58.59	68.20	9.61	PK	Vertical
2	5726.38	55.38	4.36	33.45	-30.81	62.38	68.20	5.82	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\129
Memo: 11BE20MIMO 5700

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.30	7.34	33.45	-30.81	53.28	68.20	14.92	PK	Horizontal
2	5729.71	47.50	7.35	33.46	-30.81	57.50	68.20	10.70	PK	Horizontal

Note:


- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\130
Memo: 11BE20MIMO 5700

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.86	7.34	33.45	-30.81	53.84	68.20	14.36	PK	Vertical
2	5725.92	46.91	7.34	33.45	-30.81	56.89	68.20	11.31	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\145
Memo: 11BE20MIMO 5700 RU39+RU7

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.73	7.34	33.45	-30.81	53.71	68.20	14.49	PK	Horizontal
2	5733.99	47.25	7.36	33.47	-30.81	57.27	68.20	10.93	PK	Horizontal


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\146
Memo: 11BE20MIMO 5700 RU39+RU7

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	43.06	7.34	33.45	-30.81	53.04	68.20	15.16	PK	Vertical
2	5734.33	46.72	7.36	33.47	-30.81	56.74	68.20	11.46	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\179
Memo: 11AX160MIMO 5250

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5148.15	47.58	6.21	32.90	-31.04	55.65	74.00	18.35	PK	Horizontal
2	5150.00	44.83	6.21	32.90	-31.04	52.90	68.20	15.30	PK	Horizontal
3	5350.00	43.09	6.61	32.90	-30.96	51.64	74.00	22.36	PK	Horizontal
4	5364.21	46.07	6.63	32.90	-30.95	54.65	74.00	19.35	PK	Horizontal

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5148.15	35.44	6.21	32.90	-31.04	43.51	54.00	10.49	AV	Horizontal
2	5150.00	35.97	6.21	32.90	-31.04	44.04	54.00	9.96	AV	Horizontal
3	5350.00	34.82	6.61	32.90	-30.96	43.37	54.00	10.63	AV	Horizontal
4	5364.21	36.17	6.63	32.90	-30.95	44.75	54.00	9.25	AV	Horizontal


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\180
Memo: 11AX160MIMO 5250

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5116.14	46.72	6.15	32.90	-31.05	54.72	74.00	19.28	PK	Vertical
2	5150.00	45.33	6.21	32.90	-31.04	53.40	68.20	14.80	PK	Vertical
3	5350.00	44.53	6.61	32.90	-30.96	53.08	74.00	20.92	PK	Vertical
4	5394.21	46.90	6.69	32.90	-30.94	55.55	74.00	18.45	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5116.14	35.87	6.15	32.90	-31.05	43.87	54.00	10.13	AV	Vertical
2	5150.00	35.28	6.21	32.90	-31.04	43.35	54.00	10.65	AV	Vertical
3	5350.00	35.64	6.61	32.90	-30.96	44.19	54.00	9.81	AV	Vertical
4	5394.21	35.28	6.69	32.90	-30.94	43.93	54.00	10.07	AV	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\181
Memo: 11BE160MIMO 5250

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5135.43	46.72	6.19	32.90	-31.05	54.76	74.00	19.24	PK	Horizontal
2	5150.00	43.61	6.21	32.90	-31.04	51.68	68.20	16.52	PK	Horizontal
3	5350.00	43.72	6.61	32.90	-30.96	52.27	74.00	21.73	PK	Horizontal
4	5355.87	46.02	6.62	32.90	-30.96	54.58	74.00	19.42	PK	Horizontal

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5135.43	35.43	6.19	32.90	-31.05	43.47	54.00	10.53	AV	Horizontal
2	5150.00	35.49	6.21	32.90	-31.04	43.56	54.00	10.44	AV	Horizontal
3	5350.00	35.39	6.61	32.90	-30.96	43.94	54.00	10.06	AV	Horizontal
4	5355.87	35.42	6.62	32.90	-30.96	43.98	54.00	10.02	AV	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\182
Memo: 11BE160MIMO 5250

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5118.39	46.95	6.15	32.90	-31.05	54.95	74.00	19.05	PK	Vertical
2	5150.00	44.34	6.21	32.90	-31.04	52.41	68.20	15.79	PK	Vertical
3	5350.00	43.70	6.61	32.90	-30.96	52.25	74.00	21.75	PK	Vertical
4	5389.02	46.41	6.68	32.90	-30.94	55.05	74.00	18.95	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5118.39	35.82	6.15	32.90	-31.05	43.82	54.00	10.18	AV	Vertical
2	5150.00	35.47	6.21	32.90	-31.04	43.54	54.00	10.46	AV	Vertical
3	5350.00	35.29	6.61	32.90	-30.96	43.84	54.00	10.16	AV	Vertical
4	5389.02	35.38	6.68	32.90	-30.94	44.02	54.00	9.98	AV	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\183
Memo: 11AX160MIMO 5570

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5419.36	46.69	6.74	32.90	-30.93	55.40	74.00	18.60	PK	Horizontal
2	5460.00	44.27	6.82	32.90	-30.92	53.07	68.20	15.13	PK	Horizontal
3	5725.00	42.85	7.34	33.45	-30.81	52.83	68.20	15.37	PK	Horizontal
4	5746.92	46.19	7.38	33.49	-30.80	56.26	68.20	11.94	PK	Horizontal

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5419.36	35.64	6.74	32.90	-30.93	44.35	54.00	9.65	AV	Horizontal
2	5460.00	35.87	6.82	32.90	-30.92	44.67	54.00	9.33	AV	Horizontal


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\184
Memo: 11AX160MIMO 5570

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.80	47.03	6.81	32.90	-30.92	55.82	74.00	18.18	PK	Vertical
2	5460.00	43.12	6.82	32.90	-30.92	51.92	68.20	16.28	PK	Vertical
3	5725.00	43.44	7.34	33.45	-30.81	53.42	68.20	14.78	PK	Vertical
4	5749.37	46.22	7.39	33.50	-30.80	56.31	68.20	11.89	PK	Vertical

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.80	35.87	6.81	32.90	-30.92	44.66	54.00	9.34	AV	Vertical
2	5460.00	35.86	6.82	32.90	-30.92	44.66	54.00	9.34	AV	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\185
Memo: 11BE160MIMO 5570

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5415.65	47.21	6.73	32.90	-30.93	55.91	74.00	18.09	PK	Horizontal
2	5460.00	43.15	6.82	32.90	-30.92	51.95	68.20	16.25	PK	Horizontal
3	5725.00	42.86	7.34	33.45	-30.81	52.84	68.20	15.36	PK	Horizontal
4	5735.41	45.97	7.36	33.47	-30.81	55.99	68.20	12.21	PK	Horizontal

Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5415.65	35.87	6.73	32.90	-30.93	44.57	54.00	9.43	AV	Horizontal
2	5460.00	35.39	6.82	32.90	-30.92	44.19	54.00	9.81	AV	Horizontal


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-19 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\186
Memo: 11BE160MIMO 5570

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.81	46.59	6.81	32.90	-30.92	55.38	74.00	18.62	PK	Vertical
2	5460.00	43.30	6.82	32.90	-30.92	52.10	68.20	16.10	PK	Vertical
3	5725.00	43.59	7.34	33.45	-30.81	53.57	68.20	14.63	PK	Vertical
4	5741.95	46.40	7.37	33.48	-30.80	56.45	68.20	11.75	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.81	35.67	6.81	32.90	-30.92	44.46	54.00	9.54	AV	Vertical
2	5460.00	35.99	6.82	32.90	-30.92	44.79	54.00	9.21	AV	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\187
Memo: 11A 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5461.97	51.10	6.83	32.90	-40.92	49.91	68.20	18.29	PK	Horizontal
2	5470.00	46.59	6.84	32.90	-40.91	45.42	68.20	22.78	PK	Horizontal
3	5850.00	46.91	7.59	33.80	-40.76	47.54	68.20	20.66	PK	Horizontal
4	5889.74	49.04	7.66	33.88	-40.74	49.84	68.20	18.36	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\188
Memo: 11A 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.36	50.30	6.81	32.90	-40.92	49.09	74.00	24.91	PK	Vertical
2	5470.00	47.35	6.84	32.90	-40.91	46.18	68.20	22.02	PK	Vertical
3	5850.00	46.61	7.59	33.80	-40.76	47.24	68.20	20.96	PK	Vertical
4	5875.70	48.78	7.64	33.85	-40.75	49.52	68.20	18.68	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\189
Memo: 11N20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5459.14	49.49	6.82	32.90	-40.92	48.29	74.00	25.71	PK	Horizontal
2	5470.00	46.93	6.84	32.90	-40.91	45.76	68.20	22.44	PK	Horizontal
3	5850.00	46.40	7.59	33.80	-40.76	47.03	68.20	21.17	PK	Horizontal
4	5877.46	49.56	7.64	33.85	-40.75	50.30	68.20	17.90	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\190
Memo: 11N20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5455.81	48.96	6.81	32.90	-40.92	47.75	74.00	26.25	PK	Vertical
2	5470.00	46.83	6.84	32.90	-40.91	45.66	68.20	22.54	PK	Vertical
3	5850.00	46.26	7.59	33.80	-40.76	46.89	68.20	21.31	PK	Vertical
4	5862.74	49.00	7.61	33.83	-40.75	49.69	68.20	18.51	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\191
Memo: 11AC20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5464.36	49.30	6.83	32.90	-40.91	48.12	68.20	20.08	PK	Horizontal
2	5470.00	47.32	6.84	32.90	-40.91	46.15	68.20	22.05	PK	Horizontal
3	5850.00	46.75	7.59	33.80	-40.76	47.38	68.20	20.82	PK	Horizontal
4	5864.59	48.99	7.61	33.83	-40.75	49.68	68.20	18.52	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\192
Memo: 11AC20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.28	50.70	6.81	32.90	-40.92	49.49	74.00	24.51	PK	Vertical
2	5470.00	46.30	6.84	32.90	-40.91	45.13	68.20	23.07	PK	Vertical
3	5850.00	45.48	7.59	33.80	-40.76	46.11	68.20	22.09	PK	Vertical
4	5869.18	49.18	7.62	33.84	-40.75	49.89	68.20	18.31	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\193
Memo: 11AX20MIMO 5720

Test Graph



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5463.86	50.07	6.83	32.90	-40.91	48.89	68.20	19.31	PK	Horizontal
2	5470.00	46.69	6.84	32.90	-40.91	45.52	68.20	22.68	PK	Horizontal
3	5850.00	46.30	7.59	33.80	-40.76	46.93	68.20	21.27	PK	Horizontal
4	5869.22	49.97	7.62	33.84	-40.75	50.68	68.20	17.52	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\194
Memo: 11AX20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5452.25	49.84	6.81	32.90	-40.92	48.63	74.00	25.37	PK	Vertical
2	5470.00	46.23	6.84	32.90	-40.91	45.06	68.20	23.14	PK	Vertical
3	5850.00	46.03	7.59	33.80	-40.76	46.66	68.20	21.54	PK	Vertical
4	5887.04	49.11	7.66	33.87	-40.75	49.89	68.20	18.31	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\195
Memo: 11BE20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5457.83	49.49	6.82	32.90	-40.92	48.29	74.00	25.71	PK	Horizontal
2	5470.00	47.00	6.84	32.90	-40.91	45.83	68.20	22.37	PK	Horizontal
3	5850.00	45.59	7.59	33.80	-40.76	46.22	68.20	21.98	PK	Horizontal
4	5879.44	50.14	7.64	33.86	-40.75	50.89	68.20	17.31	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\196
Memo: 11BE20MIMO 5720

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5462.56	49.07	6.83	32.90	-40.91	47.89	68.20	20.31	PK	Vertical
2	5470.00	47.13	6.84	32.90	-40.91	45.96	68.20	22.24	PK	Vertical
3	5850.00	45.89	7.59	33.80	-40.76	46.52	68.20	21.68	PK	Vertical
4	5873.36	50.06	7.63	33.85	-40.75	50.79	68.20	17.41	PK	Vertical


Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\197
Memo: 11N40MIMO 5710

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5450.86	49.25	6.80	32.90	-40.92	48.03	74.00	25.97	PK	Horizontal
2	5470.00	46.93	6.84	32.90	-40.91	45.76	68.20	22.44	PK	Horizontal
3	5850.00	46.49	7.59	33.80	-40.76	47.12	68.20	21.08	PK	Horizontal
4	5859.14	49.83	7.60	33.82	-40.76	50.49	68.20	17.71	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\198
Memo: 11N40MIMO 5710

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5452.79	49.25	6.81	32.90	-40.92	48.04	74.00	25.96	PK	Vertical
2	5470.00	46.42	6.84	32.90	-40.91	45.25	68.20	22.95	PK	Vertical
3	5850.00	46.26	7.59	33.80	-40.76	46.89	68.20	21.31	PK	Vertical
4	5896.31	49.68	7.68	33.89	-40.74	50.51	68.20	17.69	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\199
Memo: 11AC40MIMO 5710

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.11	49.33	6.81	32.90	-40.92	48.12	74.00	25.88	PK	Horizontal
2	5470.00	48.62	6.84	32.90	-40.91	47.45	68.20	20.75	PK	Horizontal
3	5850.00	46.68	7.59	33.80	-40.76	47.31	68.20	20.89	PK	Horizontal
4	5861.21	49.80	7.61	33.82	-40.76	50.47	68.20	17.73	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\200
Memo: 11AC40MIMO 5710

Test Graph



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.23	49.18	6.81	32.90	-40.92	47.97	74.00	26.03	PK	Vertical
2	5470.00	46.45	6.84	32.90	-40.91	45.28	68.20	22.92	PK	Vertical
3	5850.00	46.78	7.59	33.80	-40.76	47.41	68.20	20.79	PK	Vertical
4	5890.10	50.16	7.66	33.88	-40.74	50.96	68.20	17.24	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\201
Memo: 11AX40MIMO 5710

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5451.08	49.26	6.80	32.90	-40.92	48.04	74.00	25.96	PK	Horizontal
2	5470.00	45.94	6.84	32.90	-40.91	44.77	68.20	23.43	PK	Horizontal
3	5850.00	46.35	7.59	33.80	-40.76	46.98	68.20	21.22	PK	Horizontal
4	5868.50	49.35	7.62	33.84	-40.75	50.06	68.20	18.14	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\202
Memo: 11AX40MIMO 5710

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5453.74	48.77	6.81	32.90	-40.92	47.56	74.00	26.44	PK	Vertical
2	5470.00	46.57	6.84	32.90	-40.91	45.40	68.20	22.80	PK	Vertical
3	5850.00	46.24	7.59	33.80	-40.76	46.87	68.20	21.33	PK	Vertical
4	5872.96	49.29	7.63	33.85	-40.75	50.02	68.20	18.18	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\203
Memo: 11BE40MIMO 5710

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5468.99	49.59	6.84	32.90	-40.91	48.42	68.20	19.78	PK	Horizontal
2	5470.00	45.70	6.84	32.90	-40.91	44.53	68.20	23.67	PK	Horizontal
3	5850.00	45.49	7.59	33.80	-40.76	46.12	68.20	22.08	PK	Horizontal
4	5864.99	49.03	7.62	33.83	-40.75	49.73	68.20	18.47	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\204
Memo: 11BE40MIMO 5710

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5457.38	49.27	6.82	32.90	-40.92	48.07	74.00	25.93	PK	Vertical
2	5470.00	48.67	6.84	32.90	-40.91	47.50	68.20	20.70	PK	Vertical
3	5850.00	47.26	7.59	33.80	-40.76	47.89	68.20	20.31	PK	Vertical
4	5884.43	49.22	7.65	33.87	-40.75	49.99	68.20	18.21	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\205
Memo: 11AC80MIMO 5690

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5454.01	49.71	6.81	32.90	-40.92	48.50	74.00	25.50	PK	Horizontal
2	5470.00	45.89	6.84	32.90	-40.91	44.72	68.20	23.48	PK	Horizontal
3	5850.00	45.74	7.59	33.80	-40.76	46.37	68.20	21.83	PK	Horizontal
4	5887.27	49.27	7.66	33.87	-40.75	50.05	68.20	18.15	PK	Horizontal

Note:


1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09
EUT: Wireless Access Point
Test Mode: TX Mode
Condition: Temp:22.2°C;Humi:56.7%
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\206
Memo: 11AC80MIMO 5690

Tested By: Bairong
Model Number: RG-RAP73HD
Power Supply: AC 120V/60Hz
Test Site: DDT 3# Chamber

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5456.89	48.87	6.82	32.90	-40.92	47.67	74.00	26.33	PK	Vertical
2	5470.00	45.54	6.84	32.90	-40.91	44.37	68.20	23.83	PK	Vertical
3	5850.00	44.98	7.59	33.80	-40.76	45.61	68.20	22.59	PK	Vertical
4	5887.36	49.73	7.66	33.87	-40.75	50.51	68.20	17.69	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\207
Memo: 11AX80MIMO 5690

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5458.78	49.97	6.82	32.90	-40.92	48.77	74.00	25.23	PK	Horizontal
2	5470.00	44.93	6.84	32.90	-40.91	43.76	68.20	24.44	PK	Horizontal
3	5850.00	46.26	7.59	33.80	-40.76	46.89	68.20	21.31	PK	Horizontal
4	5899.64	48.74	7.68	33.90	-40.74	49.58	68.20	18.62	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\208
Memo: 11AX80MIMO 5690

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5459.81	49.33	6.82	32.90	-40.92	48.13	74.00	25.87	PK	Vertical
2	5470.00	47.03	6.84	32.90	-40.91	45.86	68.20	22.34	PK	Vertical
3	5850.00	45.59	7.59	33.80	-40.76	46.22	68.20	21.98	PK	Vertical
4	5877.23	49.40	7.64	33.85	-40.75	50.14	68.20	18.06	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\209
Memo: 11BE80MIMO 5690

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5461.07	49.28	6.82	32.90	-40.92	48.08	68.20	20.12	PK	Horizontal
2	5470.00	47.07	6.84	32.90	-40.91	45.90	68.20	22.30	PK	Horizontal
3	5850.00	45.60	7.59	33.80	-40.76	46.23	68.20	21.97	PK	Horizontal
4	5878.85	49.69	7.64	33.86	-40.75	50.44	68.20	17.76	PK	Horizontal


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-05-09 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G\210
Memo: 11BE80MIMO 5690

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5464.67	49.01	6.83	32.90	-40.91	47.83	68.20	20.37	PK	Vertical
2	5470.00	46.09	6.84	32.90	-40.91	44.92	68.20	23.28	PK	Vertical
3	5850.00	45.09	7.59	33.80	-40.76	45.72	68.20	22.48	PK	Vertical
4	5859.23	49.13	7.60	33.82	-40.76	49.79	68.20	18.41	PK	Vertical


Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2023-04-13 **Tested By:** Bairong
EUT: Wireless Access Point **Model Number:** RG-RAP73HD
Test Mode: TX Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.2°C;Humi:56.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2023 report data\Q23032214 RG-RAP73HD\FCC ABOVE 1G 5.8G7
Memo: 11A MIMO 5745

Test Graph



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Cable Loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5725.00	58.00	7.34	33.45	-40.81	57.98	125.30	67.32	PK	Horizontal
2	5740.03	103.23	7.37	33.48	-40.80	103.28	125.30	22.02	PK	Horizontal
3	5850.00	47.22	7.59	33.80	-40.76	47.85	125.27	77.42	PK	Horizontal

Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.