

GPWL-AS-A33-20-800-01-A1WG
120V , 60Hz ,20W
FCC ID: 2AX70-GPWL-MAAS
IC: 32571-GPWLMAAS
Factory ID: DGO DATE: XXXXXX
GLOBE ELECTRIC COMPANY INC.
CONFORMS TO UL STD 1598
CONFORME À UL STD 1598
CERTIFIED TO CSA STD C22.2 No.250.0
CERTIFIÉ CSA STD C22.2 No.250.0
SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
CAUTION – RISK OF FIRE
ATTENTION - RISQUE D'INCENDIE


C UL LISTED US
Intertek
5003628


Size: 54*38mm

GPWL-RA-A35-14-800-01-A1WG
120V , 60Hz ,20W
FCC ID: 2AX70-GPWL-MAAS
IC: 32571-GPWLMAAS
Factory ID: DGO DATE: XXXXXX
GLOBE ELECTRIC COMPANY INC.
CONFORMS TO UL STD 1598
CONFORME À UL STD 1598
CERTIFIED TO CSA STD C22.2 No.250.0
CERTIFIÉ CSA STD C22.2 No.250.0
SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
CAUTION – RISK OF FIRE
ATTENTION - RISQUE D'INCENDIE


C UL LISTED US
Intertek
5003628


Size: 54*38mm



Size: 10*10mm

WALL MOUNT ONLY
INSTALLATION MURALE
SEULEMENT
MOUNTING ORIENTATION ↑
SENS DE MONTAGE ↑

Size: 50*30mm

SUITABLE FOR OPERATION IN AMBIENT NOT EXCEEDING 40 °C
CONVIENT POUR UN FONCTIONNEMENT DANS UN AMBIANT NE DÉPASSANT PAS 40°C
MIN 90 °C SUPPLY CONDUCTORS
CONDUCTEURS D'ALIMENTATION MIN 90°C
MADE IN MALAYSIA FABRIQUÉ EN MALAISIE
CAN ICES(B)/NMB(B)

Size: 78*16mm

60000151
120V , 60Hz ,20W
FCC ID: 2AX70-GPWL-MAAS
IC: 32571-GPWLMAAS
Factory ID: DGO DATE: XXXXXX
GLOBE ELECTRIC COMPANY INC.
CONFORMS TO UL STD 1598
CONFORME À UL STD 1598
CERTIFIED TO CSA STD C22.2 No.250.0
CERTIFIÉ CSA STD C22.2 No.250.0
SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
CAUTION – RISK OF FIRE
ATTENTION - RISQUE D'INCENDIE


C US
Intertek
5003628


Size: 54*38mm

60000150
120V , 60Hz ,20W
FCC ID: 2AX70-GPWL-MAAS
IC: 32571-GPWLMAAS
Factory ID: DGO DATE: XXXXXX
GLOBE ELECTRIC COMPANY INC.
CONFORMS TO UL STD 1598
CONFORME À UL STD 1598
CERTIFIED TO CSA STD C22.2 No.250.0
CERTIFIÉ CSA STD C22.2 No.250.0
SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
CAUTION – RISK OF FIRE
ATTENTION - RISQUE D'INCENDIE


C US
Intertek
5003628


Size: 54*38mm



Size: 10*10mm

WALL MOUNT ONLY
INSTALLATION MURALE
SEULEMENT
MOUNTING ORIENTATION ↑
SENS DE MONTAGE ↑

Size: 50*30mm

SUITABLE FOR OPERATION IN AMBIENT NOT EXCEEDING 40 °C
CONVIENT POUR UN FONCTIONNEMENT DANS UN AMBIANT NE DÉPASSANT PAS 40°C
MIN 90 °C SUPPLY CONDUCTORS
CONDUCTEURS D'ALIMENTATION MIN 90°C
MADE IN MALAYSIA FABRIQUÉ EN MALAISIE
CAN ICES(B)/NMB(B)

Size: 78*16mm

60000150

60000151

