FCC Test Report

(PART 24)

Report No.: RFBGSN-WTW-P20070580-1

FCC ID: 2AX8C-3544

Test Model: FL44TE

Received Date: Jul. 29, 2020

Test Date: Aug. 05, 2020 ~ Nov. 25, 2020

Issued Date: Nov. 30, 2020

Applicant: Amazon.com Services LLC

Address: 410 Terry Ave N Seattle, WA 98109 650 694 8333

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / Designation Number: 788550 / TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record **4**

1 Certificate of Conformity **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Test Site and Instruments 7

3 General Information **8**

3.1 General Description of EUT 8
3.2 Configuration of System under Test 10
3.2.1 Description of Support Units 10
3.3 Test Mode Applicability and Tested Channel Detail 11
3.4 EUT Operating Conditions 16
3.5 General Description of Applied Standards and references 16

4 Test Types and Results **17**

4.1 Output Power Measurement 17
4.1.1 Limits of Output Power Measurement 17
4.1.2 Test Procedures 17
4.1.3 Test Setup 18
4.1.4 Test Results 19
4.2 Modulation Characteristics Measurement 28
4.2.1 Limits of Modulation Characteristics 28
4.2.2 Test Setup 28
4.2.3 Test Procedure 28
4.2.4 Test Results 29
4.3 Frequency Stability Measurement 30
4.3.1 Limits of Frequency Stability Measurement 30
4.3.2 Test Procedure 30
4.3.3 Test Setup 30
4.3.4 Test Results 31
4.4 Occupied Bandwidth Measurement 44
4.4.1 Test Procedure 44
4.4.2 Test Setup 44
4.4.3 Test Result 44
4.5 Band Edge Measurement 51
4.5.1 Limits of Band Edge Measurement 51
4.5.2 Test Setup 51
4.5.3 Test Procedures 51
4.5.4 Test Results 52
4.6 Peak to Average Ratio 64
4.6.1 Limits of Peak to Average Ratio Measurement 64
4.6.2 Test Setup 64
4.6.3 Test Procedures 64
4.6.4 Test Results 64
4.7 Conducted Spurious Emissions 71
4.7.1 Limits of Conducted Spurious Emissions Measurement 71
4.7.2 Test Setup 71
4.7.3 Test Procedure 71
4.7.4 Test Results 72
4.8 Radiated Emission Measurement 85
4.8.1 Limits of Radiated Emission Measurement 85
4.8.2 Test Procedure 85
4.8.3 Deviation from Test Standard 85
4.8.4 Test Setup 86
4.8.5 Test Results 87

5 Pictures of Test Arrangements **129**

Appendix – Information of the Testing Laboratories **130**

Release Control Record

Issue No.	Description	Date Issued
RFBGSN-WTW-P20070580-1	Original Release	Nov. 30, 2020

1 Certificate of Conformity

Product: Fleet Edge

Brand: N/A

Test Model: FL44TE

Sample Status: Engineering Sample

Applicant: Amazon.com Services LLC

Test Date: Aug. 05, 2020 ~ Nov. 25, 2020

Standards: FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang , **Date:** Nov. 30, 2020

Vera Huang / Specialist

Approved by : , **Date:** Nov. 30, 2020

Dylan Chiou / Senior Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	**Test Item**	**Result**	**Remarks**
2.1046 24.232	Effective Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement.
24.232(d)	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
24.238	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -2.87 dB at 35.82 MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.04 dB
	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Mar. 18, 2020	Mar. 17, 2021
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 12, 2019	Dec. 11, 2020
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-969	Nov. 24, 2019	Nov. 23, 2020
			Nov. 22, 2020	Nov. 21, 2021
BILOG Antenna SCHWARZBECK	VULB 9168	9168-472	Nov. 08, 2019	Nov. 07, 2020
			Nov. 06, 2020	Nov. 05, 2021
Fixed Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	Apr. 14, 2020	Apr. 13, 2021
BILOG Antenna SCHWARZBECK	VULB 9168	9168-160	Nov. 07, 2019	Nov. 06, 2020
			Nov. 06, 2020	Nov. 05, 2021
HORN Antenna SCHWARZBECK	9120D	9120D-1169	Nov. 24, 2019	Nov. 23, 2020
			Nov. 22, 2020	Nov. 21, 2021
MXG Vector signal generator Agilent	N5182B	MY53050162	Jan. 14, 2020	Jan. 14, 2021
Preamplifier EMCI	EMC001340	980201	Oct. 14, 2019	Oct. 13, 2020
			Oct. 21, 2020	Oct. 20, 2021
Preamplifier EMCI	EMC 012645	980115	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
Preamplifier EMCI	EMC 330H	980112	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
RF Coaxial Cable EMCI	EMC104-SM-SM-8000	180409	Jan. 18, 2020	Jan. 17, 2021
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM-1000(140807)	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
RF Coaxial Cable WOKEN	8D-FB	Cable-Ch10-01	Oct. 08, 2019	Oct. 07, 2020
			Oct. 07, 2020	Oct. 06, 2021
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer Anritsu	MT8821C	6201462755	Feb. 13, 2020	Feb. 12, 2021
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 19, 2019	Aug. 18, 2021
Temperature & Humidity Chamber GIANT FORCE	GTH-120-40-CP-AR	MAA1306-019	Sep. 09, 2020	Sep. 08, 2021
DC power supply Keysight	U8002A	MY56330015	NA	NA
Digital Multimeter Fluke	87-III	70360742	Jun. 23, 2020	Jun. 22, 2021

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 10.

3 General Information

3.1 General Description of EUT

Product	Fleet Edge	
Brand	N/A	
Test Model	FL44TE	
Status of EUT	Engineering Sample	
Power Supply Rating	12 Vdc (Power Supply)	
Modulation Type	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range	WCDMA II	1852.4 ~ 1907.6 MHz
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz
	LTE Band 25 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1914.3 MHz
	LTE Band 25 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1913.5 MHz
	LTE Band 25 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1912.5 MHz
	LTE Band 25 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1910.0 MHz
	LTE Band 25 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1907.5 MHz
	LTE Band 25 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1905.0 MHz
Max. EIRP Power	WCDMA II	216.77 mW
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	204.17 mW
	LTE Band 2 (Channel Bandwidth: 3 MHz)	207.97 mW
	LTE Band 2 (Channel Bandwidth: 5 MHz)	210.86 mW
	LTE Band 2 (Channel Bandwidth: 10 MHz)	215.28 mW
	LTE Band 2 (Channel Bandwidth: 15 MHz)	218.78 mW
	LTE Band 2 (Channel Bandwidth: 20 MHz)	221.82 mW
	LTE Band 25 (Channel Bandwidth: 1.4 MHz)	174.18 mW
	LTE Band 25 (Channel Bandwidth: 3 MHz)	177.42 mW
	LTE Band 25 (Channel Bandwidth: 5 MHz)	180.72 mW
	LTE Band 25 (Channel Bandwidth: 10 MHz)	183.65 mW
	LTE Band 25 (Channel Bandwidth: 15 MHz)	189.23 mW
	LTE Band 25 (Channel Bandwidth: 20 MHz)	193.20 mW

Emission Designator	WCDMA II	4M17F9W
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1M09D7W
	LTE Band 2 (Channel Bandwidth: 3 MHz)	2M70G7D
	LTE Band 2 (Channel Bandwidth: 5 MHz)	4M49D7W
	LTE Band 2 (Channel Bandwidth: 10 MHz)	8M97D7W
	LTE Band 2 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 2 (Channel Bandwidth: 20 MHz)	18M0D7W
	LTE Band 25 (Channel Bandwidth: 1.4 MHz)	1M09D7W
	LTE Band 25 (Channel Bandwidth: 3 MHz)	2M70G7D
	LTE Band 25 (Channel Bandwidth: 5 MHz)	4M49D7W
	LTE Band 25 (Channel Bandwidth: 10 MHz)	8M99D7W
	LTE Band 25 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 25 (Channel Bandwidth: 20 MHz)	18M0D7W
Antenna Type	Refer to Note as below	
Accessory Device	N/A	
Data Cable Supplied	N/A	

Note:

1. The information of module collocated in this EUT is listed as below.

Product	Brand	Model
BT/WLAN Module	Intel	9560NGW
WWAN Module	Quectel	EM06-A

2. The antenna information is listed as below.

Ant.	Brand	Model	Antenna Type	Antenna Gain (dBi)		Remark
				WCDMA 2 / LTE 2	LTE 25	
1	TAOGLAS	MA491.A.BICG.005.gb	Multiband Antennas	-0.4	-0.4	Main Antenna
2	TAOGLAS	MA491.A.BICG.005.gb	Multiband Antennas	-0.1	-0.1	Diversity Antenna

3. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Keyboard	DELL	RT7D50	CN-0J4624-37172-44T-000M	FCC DOC Approved	--
B	Mouse	DELL	MS111-L	N/A	N/A	--
C	Monitor	ViewSonic	VX2457-MHD	UG0182942333	N/A	--
D	Communication Tester	R&S	CMU200	123295	N/A	For WCDMA
		ANRITSU	MT8821C	6201502978	NA	For LTE
E	Power Supply	NA	NA	NA	NA	--
F	WLAN&WWAN Antenna	TAOGLAS	MA491.A.BICG.005.gb	NA	NA	Provided by client
G	GPS Antenna	NA	NA	NA	NA	Provided by client

Note:
1. All power cords of the above support units are non-shielded (1.8m).
2. Item D acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	HDMI Cable	1	2	N	0	-
2.	RF Cable	1	0.5	N	0	-
3.	RF Cable	1	0.5	N	0	-
4.	RF Cable	1	0.5	N	0	-
5.	USB Cable	1	2.4	N	0	-
6.	USB Cable	1	2.2	N	0	-
7.	DC power Cable	1	1.2	N	0	-
8.	Power Cord	1	1.8	N	0	-

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.
The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	EIRP	Radiated Emission
WCDMA	Z-plane	Z-plane
LTE Band 2	Z-plane	Z-plane
LTE Band 25	Z-plane	Z-plane

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
-	Modulation Characteristics	9262 to 9538	9400	WCDMA
-	Frequency Stability	9262 to 9538	9262, 9538	WCDMA
-	Occupied Bandwidth	9262 to 9538	9262, 9400, 9538	WCDMA
-	Band Edge	9262 to 9538	9262, 9538	WCDMA
-	Peak to Average Ratio	9262 to 9538	9262, 9400, 9538	WCDMA
-	Conducted Emission	9262 to 9538	9262, 9400, 9538	WCDMA
-	Radiated Emission	9262 to 9538	9262, 9400, 9538	WCDMA

Note: For radiated emissions below 1 GHz, select the worst radiated emission channel for final testing.

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Modulation Characteristics	18700 to 19100	18900	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Frequency Stability	18607 to 19193	18607, 19193	1.4 MHz	QPSK	6 RB / 0 RB Offset
		18615 to 19185	18615, 19185	3 MHz	QPSK	15 RB / 0 RB Offset
		18625 to 19175	18625, 19175	5 MHz	QPSK	25 RB / 0 RB Offset
		18650 to 19150	18650, 19150	10 MHz	QPSK	50 RB / 0 RB Offset
		18675 to 19125	18675, 19125	15 MHz	QPSK	75 RB / 0 RB Offset
		18700 to 19100	18700, 19100	20 MHz	QPSK	100 RB / 0 RB Offset
-	Occupied Bandwidth	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	18607 to 19193	18607	1.4 MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			19193	1.4 MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		18615 to 19185	18615	3 MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			19185	3 MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		18625 to 19175	18625	5 MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			19175	5 MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		18650 to 19150	18650	10 MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			19150	10 MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
		18675 to 19125	18675	15 MHz	QPSK	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			19125	15 MHz	QPSK	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		18700 to 19100	18700	20 MHz	QPSK	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			19100	20 MHz	QPSK	1 RB / 99 RB Offset
						100 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset

Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation. Therefore, only EIRP, modulation characteristics, occupied bandwidth and peak to average ratio items had been tested under QPSK, 16QAM mode, the other items were performed under QPSK mode only.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.
3. For radiated emissions below 1 GHz, select the worst radiated emission channel (above 1GHz) for final testing.

LTE Band 25

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	26047 to 26683	26047, 26365, 26683	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26090 to 26640	26090, 26365, 26640	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Modulation Characteristics	26090 to 26640	26365	10 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Frequency Stability	26047 to 26683	26047, 26683	1.4 MHz	QPSK	6 RB / 0 RB Offset
		26055 to 26675	26055, 26675	3 MHz	QPSK	15 RB / 0 RB Offset
		26065 to 26665	26065, 26665	5 MHz	QPSK	25 RB / 0 RB Offset
		26090 to 26640	26090, 26640	10 MHz	QPSK	50 RB / 0 RB Offset
		26115 to 26615	26115, 26615	15 MHz	QPSK	75 RB / 0 RB Offset
		26140 to 26590	26140, 26590	20 MHz	QPSK	100 RB / 0 RB Offset
-	Occupied Bandwidth	26047 to 26683	26047, 26365, 26683	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		26090 to 26640	26090, 26365, 26640	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	26047 to 26683	26047, 26365, 26683	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26090 to 26640	26090, 26365, 26640	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	26047 to 26683	26047	1.4 MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			26683	1.4 MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		26055 to 26675	26055	3 MHz	QPSK	1 RB / 0 RB Offset
						1 RB / 0 RB Offset
			26675	3 MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		26065 to 26665	26065	5 MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			26665	5 MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		26090 to 26640	26090	10 MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			26640	10 MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
		26115 to 26615	26115	15 MHz	QPSK	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			26615	15 MHz	QPSK	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		26140 to 26590	26140	20 MHz	QPSK	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			26590	20 MHz	QPSK	1 RB / 99 RB Offset
						100 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	26047 to 26683	26047, 26365, 26683	1.4 MHz	QPSK	1 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3 MHz	QPSK	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5 MHz	QPSK	1 RB / 0 RB Offset
		26090 to 26640	26090, 26365, 26640	10 MHz	QPSK	1 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15 MHz	QPSK	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	26047 to 26683	26047, 26365, 26683	1.4 MHz	QPSK	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5 MHz	QPSK	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20 MHz	QPSK	1 RB / 0 RB Offset

Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation. Therefore, only EIRP, modulation characteristics, occupied bandwidth and peak to average ratio items had been tested under QPSK, 16QAM mode, the other items were performed under QPSK mode only.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.
3. For radiated emissions below 1 GHz, select the worst radiated emission channel (above 1GHz) for final testing.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	25 deg. C, 65 % RH	12 Vdc	Cyril Chen / Getaz Yang
Modulation Characteristics	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Frequency Stability	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Occupied Bandwidth	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Band Edge	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Peak to Average Ratio	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Conducted Emission	25 deg. C, 65 % RH	12 Vdc	Getaz Yang
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Cyril Chen / Getaz Yang

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:
FCC 47 CFR Part 2
FCC 47 CFR Part 24
ANSI 63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

References Test Guidance:
KDB 971168 D01 Power Meas License Digital Systems v03r01
ANSI/TIA/EIA-603-E 2016

NOTE: All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

EIRP / ERP Measurement:

a. All measurements were done at low, middle and high operational frequency range. RBW is 5 MHz for WCDMA, and 1.4 MHz、3 MHz、5 MHz、10 MHz、15 MHz、 20 MHz for LTE mode, and VBW ≥ 3 x RBW.
b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.
d. Correction Factor (includes EIRP and ERP unit conversion factor) = Antenna gain of substitution horn. – Tx cable loss. Measurement method refers to ANSI C63.26 section 5.2.7 & 5.2.4.

Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup

EIRP / ERP Measurement:
<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:

4.1.4 Test Results

Conducted Output Power (dBm)

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	23.73	23.98	23.22

LTE Band 2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100	
		Frequency (MHz)		1860.0	1880.0	1900.0	
20M	QPSK	1	0	23.98	23.38	23.45	0
		1	50	23.87	23.22	23.32	0
		1	99	23.73	23.10	23.10	0
		50	0	22.83	22.28	22.33	1
		50	25	22.61	22.10	22.15	1
		50	50	22.60	22.04	22.07	1
		100	0	22.79	22.21	22.23	1
	16QAM	1	0	22.94	22.29	22.39	1
		1	50	22.80	22.16	22.29	1
		1	99	22.68	22.05	22.07	1
		50	0	21.64	21.18	21.32	2
		50	25	21.54	21.04	21.11	2
		50	50	21.57	20.99	21.05	2
		100	0	21.70	21.15	21.19	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18675	18900	19125	
		Frequency (MHz)		1857.5	1880.0	1902.5	
15M	QPSK	1	0	23.95	23.35	23.38	0
		1	37	23.83	23.14	23.28	0
		1	74	23.66	23.02	23.06	0
		36	0	22.77	22.22	22.27	1
		36	19	22.53	22.06	22.07	1
		36	39	22.54	21.97	21.99	1
		75	0	22.72	22.15	22.18	1
	16QAM	1	0	22.94	22.31	22.29	1
		1	37	22.76	22.13	22.27	1
		1	74	22.63	21.93	21.97	1
		36	0	21.57	21.07	21.17	2
		36	19	21.47	20.97	21.03	2
		36	39	21.53	20.96	20.95	2
		75	0	21.71	21.06	21.11	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18650	18900	19150	
		Frequency (MHz)		1855.0	1880.0	1905.0	
10M	QPSK	1	0	23.87	23.28	23.30	0
		1	24	23.80	23.09	23.20	0
		1	49	23.60	22.94	23.02	0
		25	0	22.74	22.17	22.22	1
		25	12	22.46	22.00	22.02	1
		25	25	22.47	21.89	21.91	1
		50	0	22.69	22.08	22.14	1
	16QAM	1	0	22.81	22.21	22.24	1
		1	24	22.72	22.02	22.15	1
		1	49	22.54	21.90	21.96	1
		25	0	21.62	20.99	21.18	2
		25	12	21.45	20.91	20.93	2
		25	25	21.41	20.82	20.84	2
		50	0	21.68	20.99	21.06	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18625	18900	19175	
		Frequency (MHz)		1852.5	1880.0	1907.5	
5M	QPSK	1	0	23.82	23.24	23.24	0
		1	12	23.72	23.06	23.13	0
		1	24	23.57	22.90	22.99	0
		12	0	22.67	22.10	22.18	1
		12	6	22.38	21.93	21.99	1
		12	13	22.40	21.85	21.88	1
		25	0	22.64	22.01	22.07	1
	16QAM	1	0	22.74	22.23	22.23	1
		1	12	22.68	22.04	22.04	1
		1	24	22.49	21.88	21.97	1
		12	0	21.65	21.00	21.04	2
		12	6	21.36	20.85	20.94	2
		12	13	21.32	20.78	20.84	2
		25	0	21.47	20.91	20.92	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18615	18900	19185	
		Frequency (MHz)		1851.5	1880.0	1908.5	
3M	QPSK	1	0	23.78	23.17	23.19	0
		1	7	23.69	23.00	23.09	0
		1	14	23.49	22.82	22.92	0
		8	0	22.64	22.05	22.11	1
		8	3	22.34	21.86	21.91	1
		8	7	22.33	21.80	21.81	1
		15	0	22.57	21.97	22.00	1
	16QAM	1	0	22.73	22.13	22.11	1
		1	7	22.67	21.93	22.03	1
		1	14	22.45	21.78	21.86	1
		8	0	21.57	20.83	21.05	2
		8	3	21.27	20.83	20.90	2
		8	7	21.32	20.71	20.80	2
		15	0	21.46	20.80	20.91	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18607	18900	19193	
		Frequency (MHz)		1850.7	1880.0	1909.3	
1.4M	QPSK	1	0	23.73	23.12	23.14	0
		1	2	23.68	23.05	23.09	0
		1	5	23.60	22.99	23.06	0
		3	0	23.54	22.91	23.03	0
		3	1	23.51	22.84	22.96	0
		3	3	23.43	22.76	22.90	0
		6	0	22.51	21.91	21.95	1
	16QAM	1	0	22.65	22.11	22.06	1
		1	2	22.64	21.98	22.07	1
		1	5	22.53	21.96	22.00	1
		3	0	22.46	21.87	22.02	1
		3	1	22.45	21.75	21.88	1
		3	3	22.38	21.67	21.86	1
		6	0	21.49	20.89	20.90	2

LTE Band 25

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26140	26365	26590	
		Frequency (MHz)		1860.0	1882.5	1905.0	
20M	QPSK	1	0	23.22	23.14	23.35	0
		1	50	23.11	22.98	23.23	0
		1	99	22.93	22.84	23.01	0
		50	0	22.06	22.04	22.25	1
		50	25	21.89	21.83	22.03	1
		50	50	21.72	21.77	21.98	1
		100	0	22.01	21.93	22.14	1
	16QAM	1	0	22.14	22.05	22.28	1
		1	50	22.04	21.97	22.20	1
		1	99	21.92	21.80	21.98	1
		50	0	20.90	20.94	21.14	2
		50	25	20.84	20.78	20.94	2
		50	50	20.64	20.71	20.93	2
		100	0	21.00	20.91	21.08	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26115	26365	26615	
		Frequency (MHz)		1857.5	1882.5	1907.5	
15M	QPSK	1	0	23.17	23.08	23.30	0
		1	37	23.07	22.96	23.15	0
		1	74	22.93	22.71	23.06	0
		36	0	22.01	21.95	22.22	1
		36	19	21.79	21.78	21.98	1
		36	39	21.74	21.66	21.88	1
		75	0	21.99	21.93	22.19	1
	16QAM	1	0	22.15	22.04	22.25	1
		1	37	22.02	21.90	22.13	1
		1	74	21.84	21.65	22.00	1
		36	0	20.88	20.73	21.18	2
		36	19	20.70	20.75	20.90	2
		36	39	20.70	20.65	20.87	2
		75	0	20.92	20.86	21.16	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26090	26365	26640	
		Frequency (MHz)		2855.0	1882.5	1910.0	
10M	QPSK	1	0	23.16	23.04	23.25	0
		1	24	22.94	22.89	23.09	0
		1	49	22.89	22.82	22.85	0
		25	0	21.91	21.83	22.11	1
		25	12	21.76	21.65	21.94	1
		25	25	21.65	21.63	21.84	1
		50	0	21.94	21.85	22.09	1
	16QAM	1	0	22.11	21.97	22.22	1
		1	24	21.87	21.88	22.02	1
		1	49	21.85	21.77	21.79	1
		25	0	20.74	20.82	21.02	2
		25	12	20.74	20.62	20.88	2
		25	25	20.64	20.56	20.79	2
		50	0	20.90	20.80	21.08	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26065	26365	26665	
		Frequency (MHz)		1852.5	1882.5	1912.5	
5M	QPSK	1	0	23.09	22.97	23.17	0
		1	12	22.89	22.93	23.11	0
		1	24	22.87	22.74	23.00	0
		12	0	21.93	21.80	22.00	1
		12	6	21.80	21.60	21.87	1
		12	13	21.66	21.46	21.67	1
		25	0	21.91	21.76	22.05	1
	16QAM	1	0	22.04	21.92	22.13	1
		1	12	21.83	21.92	22.03	1
		1	24	21.84	21.69	21.96	1
		12	0	20.76	20.79	20.92	2
		12	6	20.79	20.59	20.78	2
		12	13	20.65	20.40	20.66	2
		25	0	20.70	20.56	21.01	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26055	26365	26675	
		Frequency (MHz)		1851.5	1882.5	1913.5	
3M	QPSK	1	0	22.98	22.92	23.11	0
		1	7	22.95	22.79	23.00	0
		1	14	22.67	22.60	22.75	0
		8	0	21.83	21.83	21.94	1
		8	3	21.66	21.61	21.82	1
		8	7	21.62	21.49	21.68	1
		15	0	21.89	21.77	22.04	1
	16QAM	1	0	21.96	21.91	22.06	1
		1	7	21.86	21.73	21.94	1
		1	14	21.64	21.54	21.71	1
		8	0	20.79	20.76	20.80	2
		8	3	20.60	20.57	20.75	2
		8	7	20.61	20.43	20.66	2
		15	0	20.85	20.67	20.87	2

BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26047	26365	26683	
		Frequency (MHz)		1850.7	1882.5	1914.3	
1.4M	QPSK	1	0	22.89	22.83	23.04	0
		1	2	22.84	22.77	22.98	0
		1	5	22.81	22.70	22.95	0
		3	0	22.77	22.64	22.90	0
		3	1	22.73	22.61	22.83	0
		3	3	22.66	22.58	22.79	0
		6	0	21.79	21.74	21.82	1
	16QAM	1	0	21.88	21.77	21.99	1
		1	2	21.77	21.68	21.96	1
		1	5	21.77	21.62	21.91	1
		3	0	21.75	21.59	21.89	1
		3	1	21.66	21.56	21.82	1
		3	3	21.63	21.54	21.70	1
		6	0	20.78	20.69	20.77	2

EIRP Power (dBm)

WCDMA							
Plane	**Channel**	**Frequency (MHz)**	**Reading (dBm)**	**Correction Factor (dB)**	**EIRP (dBm)**	**EIRP (mW)**	**Polarization (H/V)**
Z	9262	1852.4	-13.56	36.57	23.01	199.99	H
	9400	1880.0	-13.86	37.22	23.36	216.77	
	9538	1907.6	-14.01	37.18	23.17	207.49	
	9262	1852.4	-19.39	37.65	18.26	66.99	V
	9400	1880.0	-18.73	37.58	18.85	76.74	
	9538	1907.6	-18.95	37.48	18.53	71.29	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	**Channel**	**Frequency (MHz)**	**Reading (dBm)**	**Correction Factor (dB)**	**EIRP (dBm)**	**EIRP (mW)**	**Polarization (H/V)**
Z	18607	1850.7	-13.47	36.57	23.10	204.17	H
	18900	1880.0	-14.78	37.22	22.44	175.39	
	19193	1909.3	-14.61	37.18	22.57	180.72	
	18607	1850.7	-18.62	37.65	19.03	79.98	V
	18900	1880.0	-19.34	37.58	18.24	66.68	
	19193	1909.3	-19.12	37.48	18.36	68.55	
Channel Bandwidth: 1.4 MHz / 16QAM							
Z	18607	1850.7	-14.58	36.57	21.99	158.12	H
	18900	1880.0	-15.93	37.22	21.29	134.59	
	19193	1909.3	-15.78	37.18	21.40	138.04	
	18607	1850.7	-19.59	37.65	18.06	63.97	V
	18900	1880.0	-20.17	37.58	17.41	55.08	
	19193	1909.3	-19.98	37.48	17.50	56.23	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18615	1851.5	-13.39	36.57	23.18	207.97	H
	18900	1880.0	-14.71	37.22	22.51	178.24	
	19185	1908.5	-14.57	37.18	22.61	182.39	
	18615	1851.5	-18.55	37.65	19.10	81.28	V
	18900	1880.0	-19.27	37.58	18.31	67.76	
	19185	1908.5	-19.06	37.48	18.42	69.50	
Channel Bandwidth: 3 MHz / 16QAM							
Z	18615	1851.5	-14.51	36.57	22.06	160.69	H
	18900	1880.0	-15.84	37.22	21.38	137.40	
	19185	1908.5	-15.71	37.18	21.47	140.28	
	18615	1851.5	-19.49	37.65	18.16	65.46	V
	18900	1880.0	-20.08	37.58	17.50	56.23	
	19185	1908.5	-19.89	37.48	17.59	57.41	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18625	1852.5	-13.33	36.57	23.24	210.86	H
	18900	1880.0	-14.65	37.22	22.57	180.72	
	19175	1907.5	-14.48	37.18	22.70	186.21	
	18625	1852.5	-18.48	37.65	19.17	82.60	V
	18900	1880.0	-19.20	37.58	18.38	68.87	
	19175	1907.5	-18.98	37.48	18.50	70.79	
Channel Bandwidth: 5 MHz / 16QAM							
Z	18625	1852.5	-14.43	36.57	22.14	163.68	H
	18900	1880.0	-15.76	37.22	21.46	139.96	
	19175	1907.5	-15.65	37.18	21.53	142.23	
	18625	1852.5	-19.40	37.65	18.25	66.83	V
	18900	1880.0	-20.00	37.58	17.58	57.28	
	19175	1907.5	-19.82	37.48	17.66	58.34	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18650	1855.0	-13.24	36.57	23.33	215.28	H
	18900	1880.0	-14.60	37.22	22.62	182.81	
	19150	1905.0	-14.42	37.18	22.76	188.80	
	18650	1855.0	-18.41	37.65	19.24	83.95	V
	18900	1880.0	-19.12	37.58	18.46	70.15	
	19150	1905.0	-18.90	37.48	18.58	72.11	
Channel Bandwidth: 10 MHz / 16QAM							
Z	18650	1855.0	-14.36	36.57	22.21	166.34	H
	18900	1880.0	-15.69	37.22	21.53	142.23	
	19150	1905.0	-15.54	37.18	21.64	145.88	
	18650	1855.0	-19.33	37.65	18.32	67.92	V
	18900	1880.0	-19.93	37.58	17.65	58.21	
	19150	1905.0	-19.73	37.48	17.75	59.57	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18675	1857.5	-13.17	36.57	23.40	218.78	H
	18900	1880.0	-14.50	37.22	22.72	187.07	
	19125	1902.5	-14.34	37.18	22.84	192.31	
	18675	1857.5	-18.34	37.65	19.31	85.31	V
	18900	1880.0	-19.05	37.58	18.53	71.29	
	19125	1902.5	-18.83	37.48	18.65	73.28	
Channel Bandwidth: 15 MHz / 16QAM							
Z	18675	1857.5	-14.29	36.57	22.28	169.04	H
	18900	1880.0	-15.58	37.22	21.64	145.88	
	19125	1902.5	-15.45	37.18	21.73	148.94	
	18675	1857.5	-19.25	37.65	18.40	69.18	V
	18900	1880.0	-19.85	37.58	17.73	59.29	
	19125	1902.5	-19.64	37.48	17.84	60.81	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18700	1860.0	-13.11	36.57	23.46	221.82	H
	18900	1880.0	-14.42	37.22	22.80	190.55	
	19100	1900.0	-14.29	37.18	22.89	194.54	
	18700	1860.0	-18.28	37.65	19.37	86.50	V
	18900	1880.0	-18.95	37.58	18.63	72.95	
	19100	1900.0	-18.77	37.48	18.71	74.30	
Channel Bandwidth: 20 MHz / 16QAM							
Z	18700	1860.0	-14.24	36.57	22.33	171.00	H
	18900	1880.0	-15.49	37.22	21.73	148.94	
	19100	1900.0	-15.37	37.18	21.81	151.71	
	18700	1860.0	-19.18	37.65	18.47	70.31	V
	18900	1880.0	-19.76	37.58	17.82	60.53	
	19100	1900.0	-19.58	37.48	17.90	61.66	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 25							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	26047	1850.7	-14.27	36.57	22.30	169.82	H
	26365	1882.5	-15.07	37.22	22.15	164.06	
	26683	1914.3	-16.68	39.09	22.41	174.18	
	26047	1850.7	-19.47	37.65	18.18	65.77	V
	26365	1882.5	-19.65	37.58	17.93	62.09	
	26683	1914.3	-19.62	37.92	18.30	67.61	
Channel Bandwidth: 1.4 MHz / 16QAM							
Z	26047	1850.7	-15.38	36.57	21.19	131.52	H
	26365	1882.5	-16.30	37.22	20.92	123.59	
	26683	1914.3	-17.75	39.09	21.34	136.14	
	26047	1850.7	-20.59	37.65	17.06	50.82	V
	26365	1882.5	-20.71	37.58	16.87	48.64	
	26683	1914.3	-20.69	37.92	17.23	52.84	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 25							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	26055	1851.5	-14.19	36.57	22.38	172.98	H
	26365	1882.5	-15.00	37.22	22.22	166.72	
	26675	1913.5	-16.62	39.11	22.49	177.42	
	26055	1851.5	-19.38	37.65	18.27	67.14	V
	26365	1882.5	-19.57	37.58	18.01	63.24	
	26675	1913.5	-19.55	37.93	18.38	68.87	
Channel Bandwidth: 3 MHz / 16QAM							
Z	26055	1851.5	-15.28	36.57	21.29	134.59	H
	26365	1882.5	-16.21	37.22	21.01	126.18	
	26675	1913.5	-17.68	39.11	21.43	139.00	
	26055	1851.5	-20.50	37.65	17.15	51.88	V
	26365	1882.5	-20.64	37.58	16.94	49.43	
	26675	1913.5	-20.60	37.93	17.33	54.08	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 25							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	26065	1852.5	-14.11	36.57	22.46	176.20	H
	26365	1882.5	-14.90	37.22	22.32	170.61	
	26665	1912.5	-15.54	38.11	22.57	180.72	
	26065	1852.5	-19.29	37.65	18.36	68.55	V
	26365	1882.5	-19.47	37.58	18.11	64.71	
	26665	1912.5	-19.49	37.96	18.47	70.31	
Channel Bandwidth: 5 MHz / 16QAM							
Z	26065	1852.5	-15.20	36.57	21.37	137.09	H
	26365	1882.5	-16.12	37.22	21.10	128.82	
	26665	1912.5	-16.57	38.11	21.54	142.56	
	26065	1852.5	-20.39	37.65	17.26	53.21	V
	26365	1882.5	-20.57	37.58	17.01	50.23	
	26665	1912.5	-20.52	37.96	17.44	55.46	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 25							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	26090	1855.0	-14.04	36.57	22.53	179.06	H
	26365	1882.5	-14.83	37.22	22.39	173.38	
	26640	1910.0	-15.55	38.19	22.64	183.65	
	26090	1855.0	-19.22	37.65	18.43	69.66	V
	26365	1882.5	-19.36	37.58	18.22	66.37	
	26640	1910.0	-19.56	38.15	18.59	72.28	
Channel Bandwidth: 10 MHz / 16QAM							
Z	26090	1855.0	-15.13	36.57	21.44	139.32	H
	26365	1882.5	-16.03	37.22	21.19	131.52	
	26640	1910.0	-16.56	38.19	21.63	145.55	
	26090	1855.0	-20.30	37.65	17.35	54.33	V
	26365	1882.5	-20.49	37.58	17.09	51.17	
	26640	1910.0	-20.62	38.15	17.53	56.62	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 25							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	26115	1857.5	-13.95	36.57	22.62	182.81	H
	26365	1882.5	-14.75	37.22	22.47	176.60	
	26615	1907.5	-15.46	38.23	22.77	189.23	
	26115	1857.5	-19.06	37.65	18.59	72.28	V
	26365	1882.5	-19.26	37.58	18.32	67.92	
	26615	1907.5	-19.56	38.22	18.66	73.45	
Channel Bandwidth: 15 MHz / 16QAM							
Z	26115	1857.5	-15.04	36.57	21.53	142.23	H
	26365	1882.5	-15.95	37.22	21.27	133.97	
	26615	1907.5	-16.47	38.23	21.76	149.97	
	26115	1857.5	-20.22	37.65	17.43	55.34	V
	26365	1882.5	-20.41	37.58	17.17	52.12	
	26615	1907.5	-20.60	38.22	17.62	57.81	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 25							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	26140	1860.0	-13.89	36.57	22.68	185.35	H
	26365	1882.5	-14.69	37.22	22.53	179.06	
	26590	1905.0	-15.86	38.72	22.86	193.20	
	26140	1860.0	-19.00	37.65	18.65	73.28	V
	26365	1882.5	-19.17	37.58	18.41	69.34	
	26590	1905.0	-18.79	37.56	18.77	75.34	
Channel Bandwidth: 20 MHz / 16QAM							
Z	26140	1860.0	-14.95	36.57	21.62	145.21	H
	26365	1882.5	-15.87	37.22	21.35	136.46	
	26590	1905.0	-16.84	38.72	21.88	154.17	
	26140	1860.0	-20.14	37.65	17.51	56.36	V
	26365	1882.5	-20.34	37.58	17.24	52.97	
	26590	1905.0	-19.78	37.56	17.78	59.98	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

4.2 Modulation Characteristics Measurement

4.2.1 Limits of Modulation Characteristics

N/A

4.2.2 Test Setup

4.2.3 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector. The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

4.2.4 Test Results

Spectrum Plot of Measurement
WCDMA
Channel 9400

Spectrum Plot of Measurement	
LTE Band 2	
Channel 18900	
QPSK	16QAM



Spectrum Plot of Measurement	
LTE Band 25	
Channel 26365	
QPSK	16QAM



4.3 Frequency Stability Measurement

4.3.1 Limits of Frequency Stability Measurement

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.3.2 Test Procedure

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.3.3 Test Setup



4.3.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	WCDMA			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1852.400004	0.002	1907.600002	0.001
10.2	1852.400002	0.001	1907.600003	0.002
13.8	1852.400002	0.001	1907.600003	0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	WCDMA			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1852.400002	0.001	1907.600003	0.002
-20	1852.400001	0.001	1907.600002	0.001
-10	1852.400002	0.001	1907.600002	0.001
0	1852.400002	0.001	1907.600004	0.002
10	1852.399998	-0.001	1907.599998	-0.001
20	1852.399998	-0.001	1907.599997	-0.002
30	1852.399999	-0.001	1907.599996	-0.002
40	1852.399996	-0.002	1907.599997	-0.001
50	1852.399998	-0.001	1907.599998	-0.001
60	1852.399998	-0.001	1907.599998	-0.001
70	1852.399997	-0.002	1907.599998	-0.001
80	1852.399999	-0.001	1907.599997	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1850.700001	0.001	1909.300000	-0.001
10.2	1850.700004	0.002	1909.299998	-0.001
13.8	1850.700002	0.001	1909.299998	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 2			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1850.700003	0.002	1909.300003	0.001
-20	1850.700002	0.001	1909.300001	0.001
-10	1850.700002	0.001	1909.300003	0.002
0	1850.700002	0.001	1909.300001	0.001
10	1850.699998	-0.001	1909.300002	0.001
20	1850.699998	-0.001	1909.300001	0.001
30	1850.699999	-0.001	1909.300001	0.001
40	1850.699998	-0.001	1909.299997	-0.002
50	1850.699999	-0.001	1909.299997	-0.002
60	1850.699999	-0.001	1909.299998	-0.001
70	1850.699999	-0.001	1909.299996	-0.002
80	1850.699997	-0.001	1909.299996	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1851.500003	0.002	1908.499999	-0.001
10.2	1851.500003	0.002	1908.499998	-0.001
13.8	1851.500003	0.002	1908.499996	-0.002

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 2			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1851.500001	0.001	1908.500003	0.002
-20	1851.500002	0.001	1908.500002	0.001
-10	1851.500004	0.002	1908.500004	0.002
0	1851.500002	0.001	1908.500003	0.002
10	1851.499998	-0.001	1908.500003	0.002
20	1851.499998	-0.001	1908.500002	0.001
30	1851.499998	-0.001	1908.500004	0.002
40	1851.499998	-0.001	1908.499998	-0.001
50	1851.499997	-0.002	1908.499999	-0.001
60	1851.499997	-0.002	1908.499997	-0.001
70	1851.499997	-0.002	1908.499998	-0.001
80	1851.499999	-0.001	1908.499998	-0.001

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1852.500004	0.002	1907.499999	-0.001
10.2	1852.500003	0.002	1907.499999	-0.001
13.8	1852.500002	0.001	1907.499998	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 2			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1852.500001	0.001	1907.500002	0.001
-20	1852.500002	0.001	1907.500002	0.001
-10	1852.500002	0.001	1907.500003	0.002
0	1852.500001	0.001	1907.500003	0.001
10	1852.499998	-0.001	1907.500004	0.002
20	1852.499996	-0.002	1907.500004	0.002
30	1852.499999	-0.001	1907.500002	0.001
40	1852.499997	-0.001	1907.499999	-0.001
50	1852.499999	-0.001	1907.499996	-0.002
60	1852.499996	-0.002	1907.499998	-0.001
70	1852.499997	-0.002	1907.499997	-0.002
80	1852.499999	-0.001	1907.499998	-0.001

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1855.000001	0.001	1904.999998	-0.001
10.2	1855.000001	0.001	1904.999996	-0.002
13.8	1855.000003	0.002	1904.999997	-0.002

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 2			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1855.000003	0.002	1905.000004	0.002
-20	1855.000002	0.001	1905.000002	0.001
-10	1855.000003	0.001	1905.000002	0.001
0	1855.000002	0.001	1905.000003	0.002
10	1854.999999	-0.001	1905.000004	0.002
20	1854.999998	-0.001	1905.000002	0.001
30	1854.999996	-0.002	1905.000002	0.001
40	1854.999999	-0.001	1904.999998	-0.001
50	1854.999999	-0.001	1904.999998	-0.001
60	1854.999998	-0.001	1904.999996	-0.002
70	1854.999999	-0.001	1904.999998	-0.001
80	1854.999998	-0.001	1904.999997	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1857.500002	0.001	1902.499999	-0.001
10.2	1857.500003	0.002	1902.499997	-0.002
13.8	1857.500002	0.001	1902.499998	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 2			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1857.500003	0.001	1902.500002	0.001
-20	1857.500002	0.001	1902.500003	0.002
-10	1857.500002	0.001	1902.500003	0.002
0	1857.500004	0.002	1902.500002	0.001
10	1857.499999	-0.001	1902.500002	0.001
20	1857.499997	-0.002	1902.500002	0.001
30	1857.499996	-0.002	1902.500003	0.001
40	1857.499996	-0.002	1902.499997	-0.001
50	1857.499997	-0.002	1902.499998	-0.001
60	1857.499999	-0.001	1902.499996	-0.002
70	1857.499999	-0.001	1902.499996	-0.002
80	1857.499998	-0.001	1902.499997	-0.001

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1860.000001	0.001	1899.999998	-0.001
10.2	1860.000002	0.001	1899.999996	-0.002
13.8	1860.000004	0.002	1899.999997	-0.002

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 2			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1860.000004	0.002	1900.000004	0.002
-20	1860.000001	0.001	1900.000003	0.001
-10	1860.000003	0.001	1900.000002	0.001
0	1860.000003	0.001	1900.000003	0.001
10	1859.999998	-0.001	1900.000001	0.001
20	1859.999996	-0.002	1900.000002	0.001
30	1859.999998	-0.001	1900.000004	0.002
40	1859.999996	-0.002	1899.999997	-0.002
50	1859.999999	-0.001	1899.999999	-0.001
60	1859.999998	-0.001	1899.999998	-0.001
70	1859.999996	-0.002	1899.999998	-0.001
80	1859.999998	-0.001	1899.999998	-0.001

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 25			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1850.700002	0.001	1914.299997	-0.002
10.2	1850.700003	0.002	1914.299998	-0.001
13.8	1850.700002	0.001	1914.299998	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 25			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1850.700003	0.002	1914.300002	0.001
-20	1850.700003	0.002	1914.300003	0.002
-10	1850.700001	0.001	1914.300001	0.001
0	1850.700003	0.002	1914.300003	0.002
10	1850.699998	-0.001	1914.300002	0.001
20	1850.699997	-0.002	1914.300001	0.001
30	1850.699998	-0.001	1914.300002	0.001
40	1850.699997	-0.002	1914.299997	-0.001
50	1850.699998	-0.001	1914.299997	-0.001
60	1850.699999	-0.001	1914.299998	-0.001
70	1850.699998	-0.001	1914.299999	-0.001
80	1850.699996	-0.002	1914.299998	-0.001

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 25			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1851.500004	0.002	1913.499998	-0.001
10.2	1851.500003	0.002	1913.499998	-0.001
13.8	1851.500003	0.002	1913.499996	-0.002

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 25			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1851.500002	0.001	1913.500003	0.002
-20	1851.500002	0.001	1913.500002	0.001
-10	1851.500003	0.001	1913.500002	0.001
0	1851.500003	0.002	1913.500002	0.001
10	1851.499999	-0.001	1913.500003	0.002
20	1851.499997	-0.002	1913.500003	0.002
30	1851.499998	-0.001	1913.500004	0.002
40	1851.499997	-0.002	1913.499998	-0.001
50	1851.499997	-0.002	1913.499999	-0.001
60	1851.499997	-0.002	1913.499998	-0.001
70	1851.499997	-0.002	1913.499996	-0.002
80	1851.499997	-0.002	1913.499996	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 25			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1852.500003	0.002	1912.499999	-0.001
10.2	1852.500004	0.002	1912.499998	-0.001
13.8	1852.500004	0.002	1912.499999	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 25			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1852.500001	0.001	1912.500002	0.001
-20	1852.500002	0.001	1912.500003	0.002
-10	1852.500001	0.001	1912.500003	0.001
0	1852.500001	0.001	1912.500004	0.002
10	1852.499997	-0.001	1912.500004	0.002
20	1852.499998	-0.001	1912.500004	0.002
30	1852.499996	-0.002	1912.500003	0.001
40	1852.499998	-0.001	1912.499997	-0.002
50	1852.499999	-0.001	1912.499998	-0.001
60	1852.499996	-0.002	1912.499999	-0.001
70	1852.499999	-0.001	1912.499997	-0.002
80	1852.499997	-0.001	1912.499997	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 25			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1855.000004	0.002	1909.999999	-0.001
10.2	1855.000002	0.001	1909.999998	-0.001
13.8	1855.000003	0.001	1909.999997	-0.002

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 25			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1855.000004	0.002	1910.000003	0.002
-20	1855.000002	0.001	1910.000002	0.001
-10	1855.000001	0.001	1910.000004	0.002
0	1855.000002	0.001	1910.000003	0.001
10	1854.999998	-0.001	1910.000002	0.001
20	1854.999997	-0.001	1910.000002	0.001
30	1854.999997	-0.001	1910.000002	0.001
40	1854.999999	-0.001	1909.999998	-0.001
50	1854.999997	-0.002	1909.999996	-0.002
60	1854.999997	-0.002	1909.999997	-0.001
70	1854.999998	-0.001	1909.999997	-0.002
80	1854.999997	-0.002	1909.999998	-0.001

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 25			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1857.500002	0.001	1907.499999	-0.001
10.2	1857.500002	0.001	1907.499996	-0.002
13.8	1857.500002	0.001	1907.499998	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 25			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1857.500002	0.001	1907.500002	0.001
-20	1857.500003	0.001	1907.500002	0.001
-10	1857.500004	0.002	1907.500004	0.002
0	1857.500002	0.001	1907.500003	0.002
10	1857.499997	-0.001	1907.500003	0.002
20	1857.499996	-0.002	1907.500003	0.002
30	1857.499997	-0.002	1907.500004	0.002
40	1857.499997	-0.001	1907.499999	-0.001
50	1857.499999	-0.001	1907.499999	-0.001
60	1857.499997	-0.002	1907.499998	-0.001
70	1857.499996	-0.002	1907.499996	-0.002
80	1857.499996	-0.002	1907.499996	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 25			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	1860.000002	0.001	1904.999997	-0.001
10.2	1860.000004	0.002	1904.999997	-0.002
13.8	1860.000001	0.001	1904.999998	-0.001

Note: The applicant defined the normal working voltage of the battery is from 10.2 Vdc to 13.8 Vdc.

Frequency Error vs. Temperature

Temp. (℃)	LTE Band 25			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	1860.000001	0.001	1905.000002	0.001
-20	1860.000003	0.002	1905.000004	0.002
-10	1860.000002	0.001	1905.000003	0.002
0	1860.000004	0.002	1905.000001	0.001
10	1859.999998	-0.001	1905.000002	0.001
20	1859.999998	-0.001	1905.000001	0.001
30	1859.999999	-0.001	1905.000002	0.001
40	1859.999999	-0.001	1904.999997	-0.002
50	1859.999998	-0.001	1904.999997	-0.002
60	1859.999998	-0.001	1904.999998	-0.001
70	1859.999996	-0.002	1904.999997	-0.001
80	1859.999996	-0.002	1904.999997	-0.002

Note:

1. The applicant declared that the normal operating temperature of the EUT is from -30˚C to 80˚C.
2. The EUT would shut down automatically as below -30˚C.

4.4 Occupied Bandwidth Measurement

4.4.1 Test Procedure

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Measurement method, please refer to section 5.4.4 of ANSI C63.26. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

For the 26dBc bandwidth measurement method, please refer to section 5.4.3 of ANSI C63.26.

4.4.2 Test Setup



4.4.3 Test Result

WCDMA			
Channel	**Frequency (MHz)**	**99 % Occupied Bandwidth (MHz)**	**26 dB Bandwidth (MHz)**
9262	1852.4	4.16	4.76
9400	1880.0	4.16	4.74
9538	1907.6	4.17	4.75

Spectrum Plot of Worst Value	
99 % Occupied Bandwidth	**26 dB Bandwidth**
WCDMA	
	

LTE Band 2					
Channel Bandwidth: 1.4 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18607	1850.7	1.09	1.09	1.23	1.21
18900	1880.0	1.09	1.09	1.22	1.21
19193	1909.3	1.09	1.09	1.22	1.22
Channel Bandwidth: 3 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18615	1851.5	2.70	2.70	2.92	2.94
18900	1880.0	2.70	2.70	2.93	2.93
19185	1908.5	2.70	2.70	2.94	2.91

Spectrum Plot of Worst Value

99 % Occupied Bandwidth

1.4 MHz / 16QAM

26 dB Bandwidth

1.4 MHz / QPSK

3 MHz / QPSK

3 MHz / 16QAM

LTE Band 2					
Channel Bandwidth: 5 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18625	1852.5	4.49	4.49	4.80	4.80
18900	1880.0	4.49	4.49	4.81	4.81
19175	1907.5	4.49	4.49	4.81	4.80
Channel Bandwidth: 10 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18650	1855.0	8.97	8.97	9.50	9.53
18900	1880.0	8.96	8.96	9.51	9.52
19150	1905.0	8.96	8.95	9.50	9.50

Spectrum Plot of Worst Value

99 % Occupied Bandwidth	26 dB Bandwidth
5 MHz / 16QAM	5 MHz / QPSK

10 MHz / 16QAM	10 MHz / 16QAM

LTE Band 2					
Channel Bandwidth: 15 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18675	1857.5	13.48	13.46	14.28	14.28
18900	1880.0	13.46	13.44	14.25	14.24
19125	1902.5	13.43	13.42	14.24	14.22
Channel Bandwidth: 20 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18700	1860.0	17.95	17.97	19.05	19.06
18900	1880.0	17.91	17.93	19.02	19.02
19100	1900.0	17.89	17.90	19.01	19.00

Spectrum Plot of Worst Value	
99 % Occupied Bandwidth	26 dB Bandwidth
15 MHz / QPSK	15 MHz / QPSK
20 MHz / 16QAM	20 MHz / 16QAM

LTE Band 25					
Channel Bandwidth: 1.4 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26047	1850.7	1.09	1.09	1.22	1.22
26365	1882.5	1.09	1.09	1.23	1.22
26683	1914.3	1.09	1.09	1.25	1.23
Channel Bandwidth: 3 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26055	1851.5	2.70	2.70	2.93	2.93
26365	1882.5	2.70	2.70	2.94	2.93
26675	1913.5	2.70	2.70	2.95	2.94

Spectrum Plot of Worst Value

99 % Occupied Bandwidth	26 dB Bandwidth
1.4 MHz / 16QAM	1.4 MHz / QPSK

3 MHz / QPSK	3 MHz / QPSK

LTE Band 25					
Channel Bandwidth: 5 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26065	1852.5	4.49	4.49	4.79	4.81
26365	1882.5	4.49	4.49	4.79	4.81
26665	1912.5	4.49	4.49	4.82	4.83
Channel Bandwidth: 10 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26090	1855.0	8.97	8.97	9.51	9.52
26365	1882.5	8.96	8.96	9.52	9.51
26640	1910.0	8.99	8.99	9.54	9.52

Spectrum Plot of Worst Value

99 % Occupied Bandwidth

5 MHz / 16QAM

26 dB Bandwidth

5 MHz / 16QAM

10 MHz / 16QAM

10 MHz / QPSK

LTE Band 25					
Channel Bandwidth: 15 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26115	1857.5	13.48	13.47	14.28	14.27
26365	1882.5	13.47	13.45	14.28	14.25
26615	1907.5	13.49	13.47	14.31	14.25
Channel Bandwidth: 20 MHz					
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		26 dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
26140	1860.0	17.95	17.97	19.04	19.04
26365	1882.5	17.93	17.95	19.01	19.01
26590	1905.0	17.92	17.94	19.05	19.01

Spectrum Plot of Worst Value

99 % Occupied Bandwidth	26 dB Bandwidth
15 MHz / QPSK	15 MHz / QPSK

20 MHz / 16QAM	20 MHz / QPSK

4.5 Band Edge Measurement

4.5.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.5.2 Test Setup



4.5.3 Test Procedures

a. All measurements were done at low and high operational frequency range.
b. The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 51 kHz and VB of the spectrum is 160 kHz (WCDMA).
c. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 15 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
d. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
e. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 51 kHz and VB of the spectrum is 160 kHz (LTE Bandwidth 5 MHz).
f. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 10 MHz).
g. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
h. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 200 kHz and VB of the spectrum is 1 MHz (LTE Bandwidth 20 MHz).
i. Record the max trace plot into the test report.

4.5.4 Test Results

WCDMA			
Channel	9262	Channel	9538

LTE Band 2					
Channel Bandwidth: 1.4 MHz					
Channel	18607	1 RB	Channel	19193	1 RB





Channel	18607	6 RB	Channel	19193	6 RB





LTE Band 2					
Channel Bandwidth: 3 MHz					
Channel	18615	1 RB	Channel	19185	1 RB
					
Channel	18615	15 RB	Channel	19185	15 RB
					

LTE Band 2					
Channel Bandwidth: 5 MHz					
Channel	18625	1 RB	Channel	19175	1 RB
					
Channel	18625	25 RB	Channel	19175	25 RB
					

LTE Band 2					
Channel Bandwidth: 10 MHz					
Channel	18650	1 RB	Channel	19150	1 RB
					
Channel	18650	50 RB	Channel	19150	50 RB
					

LTE Band 2					
Channel Bandwidth: 15 MHz					
Channel	18675	1 RB	Channel	19125	1 RB
					
Channel	18675	75 RB	Channel	19125	75 RB
					

LTE Band 2					
Channel Bandwidth: 20 MHz					
Channel	18700	1 RB	Channel	19100	1 RB
					
Channel	18700	100 RB	Channel	19100	100 RB
					

LTE Band 25					
Channel Bandwidth: 1.4 MHz					
Channel	26047	1 RB	Channel	26683	1 RB
					
Channel	26047	6 RB	Channel	26683	6 RB
					

LTE Band 25					
Channel Bandwidth: 3 MHz					
Channel	26055	1 RB	Channel	26675	1 RB
				
Channel	26055	15 RB	Channel	26675	15 RB
				

LTE Band 25					
Channel Bandwidth: 5 MHz					
Channel	26065	1 RB	Channel	26665	1 RB
					
Channel	26065	25 RB	Channel	26665	25 RB
					

LTE Band 25					
Channel Bandwidth: 10 MHz					
Channel	26090	1 RB	Channel	26640	1 RB
					
Channel	26090	50 RB	Channel	26640	50 RB
					

LTE Band 25					
Channel Bandwidth: 15 MHz					
Channel	26115	1 RB	Channel	26615	1 RB
					
Channel	26115	75 RB	Channel	26615	75 RB
					

LTE Band 25					
Channel Bandwidth: 20 MHz					
Channel	26140	1 RB	Channel	26590	1 RB
					
Channel	26140	100 RB	Channel	26590	100 RB
					

4.6 Peak to Average Ratio

4.6.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.6.2 Test Setup



4.6.3 Test Procedures

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.6.4 Test Results

Channel	Frequency (MHz)	Peak to Average Ratio (dB)
		WCDMA
9262	1852.4	2.83
9400	1880.0	2.84
9538	1907.6	2.81

Spectrum Plot of Worst Value

WCDMA

LTE Band 2							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	3.60	4.29	18615	1851.5	3.45	4.21
18900	1880.0	3.59	4.28	18900	1880.0	3.45	4.09
19193	1909.3	3.51	4.27	19185	1908.5	3.32	4.05

Spectrum Plot of Worst Value	
1.4 MHz / 16QAM	3 MHz / 16QAM

LTE Band 2							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	3.39	4.12	18650	1855.0	3.34	4.07
18900	1880.0	3.33	4.10	18900	1880.0	3.39	4.06
19175	1907.5	3.22	4.00	19150	1905.0	3.32	4.13

Spectrum Plot of Worst Value	
5 MHz / 16QAM	10 MHz / 16QAM

LTE Band 2							
Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	3.39	3.94	18700	1860.0	3.25	3.92
18900	1880.0	3.53	4.08	18900	1880.0	3.27	4.06
19125	1902.5	3.46	4.15	19100	1900.0	3.30	4.04

Spectrum Plot of Worst Value	
15 MHz / 16QAM	20 MHz / 16QAM

LTE Band 25							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
26047	1850.7	3.53	4.16	26055	1851.5	3.27	4.01
26365	1882.5	3.64	4.18	26365	1882.5	3.51	4.10
26683	1914.3	3.39	4.11	26675	1913.5	3.28	3.99

Spectrum Plot of Worst Value	
1.4 MHz / 16QAM	3 MHz / 16QAM

LTE Band 25							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
26065	1852.5	3.34	4.00	26090	1855.0	3.15	3.90
26365	1882.5	3.22	4.07	26365	1882.5	3.19	3.91
26665	1912.5	3.27	4.00	26640	1910.0	3.05	3.79

Spectrum Plot of Worst Value	
5 MHz / 16QAM	10 MHz / 16QAM

LTE Band 25							
Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
26115	1857.5	3.20	3.84	26140	1860.0	3.21	3.92
26365	1882.5	3.19	3.86	26365	1882.5	3.20	3.94
26615	1907.5	3.13	3.87	26590	1905.0	3.25	3.94

Spectrum Plot of Worst Value	
15 MHz / 16QAM	20 MHz / 16QAM

4.7 Conducted Spurious Emissions

4.7.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to -13 dBm.

4.7.2 Test Setup



4.7.3 Test Procedure

a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
b. Measuring frequency range is from 9 kHz to 1 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz is used for conducted emission measurement.
c. Measuring frequency range is from 1 GHz to 20 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz is used for conducted emission measurement.

4.7.4 Test Results

WCDMA	
Channel 9262	
Frequency Range: 9 kHz ~ 1 GHz	**Frequency Range: 1 GHz ~ 20 GHz**
	
Channel 9400	
Frequency Range: 9 kHz ~ 1 GHz	**Frequency Range: 1 GHz ~ 20 GHz**
	
Channel 9538	
Frequency Range: 9 kHz ~ 1 GHz	**Frequency Range: 1 GHz ~ 20 GHz**
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 2	
Channel Bandwidth: 1.4 MHz	
Channel 18607	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 18900	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 19193	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 2	
Channel Bandwidth: 3 MHz	
Channel 18615	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 18900	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 19185	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 2	
Channel Bandwidth: 5 MHz	
Channel 18625	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 18900	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 19175	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 2	
Channel Bandwidth: 10 MHz	
Channel 18650	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 18900	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 19150	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 2	
Channel Bandwidth: 15 MHz	
Channel 18675	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 18900	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 19125	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 2	
Channel Bandwidth: 20 MHz	
Channel 18700	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 18900	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 19100	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 25	
Channel Bandwidth: 1.4 MHz	
Channel 26047	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26365	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26683	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 25	
Channel Bandwidth: 3 MHz	
Channel 26055	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
.Channel 26365	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26675	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 25	
Channel Bandwidth: 5 MHz	
Channel 26065	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26365	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26665	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 25	
Channel Bandwidth: 10 MHz	
Channel 26090	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26365	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26640	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 25	
Channel Bandwidth: 15 MHz	
Channel 26115	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26365	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26615	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

LTE Band 25	
Channel Bandwidth: 20 MHz	
Channel 26140	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26365	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	
Channel 26590	
Frequency Range: 9 kHz ~ 1 GHz	Frequency Range: 1 GHz ~ 20 GHz
	

Note: The signal over the limit in 9 kHz is from spectrum analyzer.

4.8 Radiated Emission Measurement

4.8.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit is equal to -13 dBm.

4.8.2 Test Procedure

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
b. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn. Correction Factor (includes EIRP and ERP unit conversion factor) = Antenna gain of substitution horn. – Tx cable loss. Measurement method refers to ANSI C63.26 section 5.5.3.2.
c. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

4.8.3 Deviation from Test Standard

No deviation.

4.8.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.8.5 Test Results

WCDMA:

Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : WCDMA B2 Link_L-CH
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3704.80	-55.50	-48.57	-13.00	-6.93	-42.50	Peak

Data: 4



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : WCDMA B2 Link_L-CH
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3700.40	-56.34	-49.41	-13.00	-6.93	-43.34	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : WCDMA B2 Link_M-CH
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	97.90	-31.98	-21.31	-13.00	-10.67	-18.98	Peak
2	306.45	-44.84	-37.93	-13.00	-6.91	-31.84	Peak
3	402.48	-53.49	-47.56	-13.00	-5.93	-40.49	Peak
4	571.26	-56.18	-54.22	-13.00	-1.96	-43.18	Peak
5	724.52	-58.28	-58.66	-13.00	0.38	-45.28	Peak
6	836.07	-61.68	-62.09	-13.00	0.41	-48.68	Peak
7	3760.00	-54.63	-47.98	-13.00	-6.65	-41.63	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : WCDMA B2 Link_M-CH
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	72.68	-28.24	-19.17	-13.00	-9.07	-15.24	Peak
2	217.21	-48.37	-41.05	-13.00	-7.32	-35.37	Peak
3	353.01	-61.11	-54.89	-13.00	-6.22	-48.11	Peak
4	412.18	-60.46	-54.61	-13.00	-5.85	-47.46	Peak
5	476.20	-62.84	-57.78	-13.00	-5.06	-49.84	Peak
6	485.90	-61.46	-56.58	-13.00	-4.88	-48.46	Peak
7	3760.00	-54.53	-47.88	-13.00	-6.65	-41.53	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : WCDMA B2 Link_H-CH
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3815.20	-56.26	-49.86	-13.00	-6.40	-43.26	Peak

Data: 4



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : WCDMA B2 Link_H-CH
Tested by: Cyril Chen

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3815.20	-55.19	-48.79	-13.00	-6.40	-42.19	Peak

LTE Band 2
Channel Bandwidth: 1.4 MHz / QPSK
Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_1.4M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3710.40	-56.13	-49.26	-13.00	-6.87	-43.13	Peak

Data: 4



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_1.4M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3701.40	-56.22	-49.29	-13.00	-6.93	-43.22	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_1.4M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3760.00	-56.24	-49.59	-13.00	-6.65	-43.24	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_1.4M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3760.00	-55.74	-49.09	-13.00	-6.65	-42.74	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_1.4M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3818.60	-55.33	-48.93	-13.00	-6.40	-42.33	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_1.4M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3818.60	-54.98	-48.58	-13.00	-6.40	-41.98	Peak

Channel Bandwidth: 5 MHz / QPSK
Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_5M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3705.00	-55.80	-48.87	-13.00	-6.93	-42.80	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_5M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3705.00	-55.46	-48.53	-13.00	-6.93	-42.46	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_5M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3760.00	-55.42	-48.77	-13.00	-6.65	-42.42	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_5M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3760.00	-54.47	-47.82	-13.00	-6.65	-41.47	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_5M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3815.00	-55.13	-48.73	-13.00	-6.40	-42.13	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_5M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3815.00	-54.55	-48.15	-13.00	-6.40	-41.55	Peak

Channel Bandwidth: 20 MHz / QPSK
Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_20M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	34.85	-27.68	-25.61	-13.00	-2.07	-14.68	Peak
2	108.57	-30.98	-20.63	-13.00	-10.35	-17.98	Peak
3 pp	168.71	-25.10	-19.64	-13.00	-5.46	-12.10	Peak
4	224.00	-41.88	-34.83	-13.00	-7.05	-28.88	Peak
5	385.02	-53.02	-46.99	-13.00	-6.03	-40.02	Peak
6	746.83	-52.10	-52.92	-13.00	0.82	-39.10	Peak
7	3720.00	-54.03	-47.21	-13.00	-6.82	-41.03	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_20M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	35.82	-15.87	-14.34	-13.00	-1.53	-2.87	Peak
2	68.80	-27.57	-19.25	-13.00	-8.32	-14.57	Peak
3	87.23	-34.67	-23.63	-13.00	-11.04	-21.67	Peak
4	108.57	-36.59	-26.24	-13.00	-10.35	-23.59	Peak
5	169.68	-36.66	-31.13	-13.00	-5.53	-23.66	Peak
6	279.29	-54.71	-48.12	-13.00	-6.59	-41.71	Peak
7	3720.00	-52.81	-45.99	-13.00	-6.82	-39.81	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_20M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3760.00	-54.36	-47.71	-13.00	-6.65	-41.36	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_20M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3760.00	-53.08	-46.43	-13.00	-6.65	-40.08	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 2 QPSK_20M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3800.00	-54.41	-47.98	-13.00	-6.43	-41.41	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 2 QPSK_20M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3800.00	-53.90	-47.47	-13.00	-6.43	-40.90	Peak

LTE Band 25
Channel Bandwidth: 1.4 MHz / QPSK
Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_1.4M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3701.40	-55.88	-48.95	-13.00	-6.93	-42.88	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_1.4M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3701.40	-56.23	-49.30	-13.00	-6.93	-43.23	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_1.4M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3765.00	-55.64	-49.04	-13.00	-6.60	-42.64	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_1.4M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3765.00	-54.97	-48.37	-13.00	-6.60	-41.97	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_1.4M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3828.60	-55.76	-49.39	-13.00	-6.37	-42.76	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_1.4M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3828.60	-54.79	-48.42	-13.00	-6.37	-41.79	Peak

Channel Bandwidth: 5 MHz / QPSK
Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_5M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3705.00	-55.51	-48.58	-13.00	-6.93	-42.51	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_5M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3705.00	-55.62	-48.69	-13.00	-6.93	-42.62	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_5M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3765.00	-55.35	-48.75	-13.00	-6.60	-42.35	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

Data: 4



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_5M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3765.00	-54.61	-48.01	-13.00	-6.60	-41.61	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_5M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3825.00	-55.26	-48.89	-13.00	-6.37	-42.26	Peak

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_5M Link_H-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3825.00	-53.15	-46.78	-13.00	-6.37	-40.15	Peak

Channel Bandwidth: 20 MHz / QPSK
Low Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_20M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3720.00	-54.42	-47.60	-13.00	-6.82	-41.42	Peak

Data: 4



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_20M Link_L-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3720.00	-54.56	-47.74	-13.00	-6.82	-41.56	Peak

Middle Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_20M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3765.00	-54.55	-47.95	-13.00	-6.60	-41.55	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_20M Link_M-CH
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	3765.00	-53.02	-46.42	-13.00	-6.60	-40.02	Peak

High Channel

Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch



Site : 966 Chamber 5
Condition: PART22/24 HORIZONTAL
Remak : LTE Band 25 QPSK_20M Link_
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	83.35	-43.43	-32.48	-13.00	-10.95	-30.43	Peak
2	203.63	-45.09	-37.23	-13.00	-7.86	-32.09	Peak
3	309.36	-47.21	-40.35	-13.00	-6.86	-34.21	Peak
4	385.99	-55.74	-49.71	-13.00	-6.03	-42.74	Peak
5	485.90	-61.94	-57.06	-13.00	-4.88	-48.94	Peak
6	642.07	-63.53	-62.67	-13.00	-0.86	-50.53	Peak
7	3810.00	-54.70	-48.30	-13.00	-6.40	-41.70	Peak



Site : 966 Chamber 5
Condition: PART22/24 VERTICAL
Remak : LTE Band 25 QPSK_20M Link_
Tested by: Getaz Yang

	Freq	Level	Read Level	Limit Line	Factor	Over Limit	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	71.71	-28.62	-19.77	-13.00	-8.85	-15.62	Peak
2	143.49	-41.99	-33.73	-13.00	-8.26	-28.99	Peak
3	307.42	-54.02	-47.13	-13.00	-6.89	-41.02	Peak
4	465.53	-60.99	-55.73	-13.00	-5.26	-47.99	Peak
5	656.62	-63.65	-62.87	-13.00	-0.78	-50.65	Peak
6	746.83	-58.70	-59.52	-13.00	0.82	-45.70	Peak
7	3810.00	-52.49	-46.09	-13.00	-6.40	-39.49	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---