

45

15

electrify home

PRODUCT NAME: HomeStation
 PRODUCT NUMBER: EAZR040JPA10-00
 FOR USE WITH ELECTRIC VEHICLES.
 TYPE 3R.
 INDOOR/OUTDOOR USE
 VENTILATION NOT REQUIRED.
 MADE IN XXXXX.
 OPERATING TEMP: -22 F to 122 F.
 INPUT: 208-240V~, 40A, 60Hz.
 SINGLE PHASE
 OUTPUT: 208-240V~, 40A, 60Hz
 EIAW-UBKSSUTC03
 REV:XX DATE CODE: YYWW
 S/N: PPPPYWWSSSSXXX
 (BARCODE)

CAUTION: Do not use this product if there is any damage to the unit, Risk of electric shock. Do not remove cover or attempt to open the enclosure. No user serviceable parts inside, Refer servicing to qualified service personnel. To reduce the risk of electric shock and fire - Do not connect to a circuit operating at more than 150 volts to ground.

WARNING: To avoid a risk of fire or electric shock, do not use this device with an extension cord, Risk of explosion. This equipment has arcing or sparking parts that should not be exposed to flammable vapors. This equipment should be located at least 18 inches (460 mm) above the floor. This device is intended only for charging vehicles not requiring ventilation during charging.

This device complies with Part 15 of the FCC Rules.
 Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: 2AX85EAR040JPA1000

XXXXX: MANUFACTURER:
 (1) DCWP: CHINA
 (2) DEIC: TAIWAN
 (3) Pingzhen: TAIWAN P.J

REV: RR
 PLEASE REFER BOM REVISION IN SAP.
 FOR EXAMPLE: S0, S1... OR 00.

DATE CODE: YY WW
 # 2 CODE FOR WEEK
 # 2 CODE FOR YEAR, 2011 IS 11, 2012 IS 12 ...

PPPP YY WW SSSSS X X
 # 1 CODE MODEL STAYUS (P:Porotype, E:EVT, D:DVT, 0:MP)
 # 1 CODE MANUFACTURE (A:Chungli, B:Tainan, C:Dongguan, D:Deltagreentech, P:Pingzhen, W:Wujiang)
 # 5 CODE S/N: 00001~99999
 (Numeric Base 10, resets to 00001 once it reaches 99999)
 # 2 CODE FOR WEEK
 # 2 CODE FOR YEAR, 2011 IS 11, 2012 IS 12 ...
 # 3 CODE FOR PRODUCT ID

CAUTION, WARNING Text Type: Tahoma, Size: 3.2mm.
 Other Text Type: Arial, Size: 1.6mm.

Text Type: Arial, Size: 2.4mm.

Other Text Type: Arial, Size: 1.6mm.

R3.0

NOTE:

1. BLANK LABEL P/N: 32639701XX.
2. TEXT COLOR: BLACK.
3. LABEL PRINTING MUST BE CLEAR & COMPLETE.
4. BARCODE:
 - a. CODE: USE CODE 128.
 - b. SETUP 2PINS FOR BARCODE PRINTING.
 - c. MINIMUM RESOLUTION: 300 dpi.
 - d. BARCODE HEIGHT: 3.0 mm
5. RIBBON: SONY 4070, B110C, B110CR OR EQUIVALENT.

台達電子工業股份有限公司 DELTA ELECTRONICS, INC.				Drawn: 2020/08/07 JOHNNY.K.HUANG		Design: 2020/08/07 JOHNNY.K.HUANG																																													
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION. DIMENSIONAL TOLERANCES HOLES: ±0.06 ANGLES: ±0.6° <table><tr><td>0-10</td><td>±0.25</td><td>DECIMALS</td><td>100-150</td><td>±0.2</td><td>250-300</td><td>±0.4</td><td>UP-500</td><td>±1.0</td></tr><tr><td>10-100</td><td>±0.35</td><td>XX</td><td>±0.3</td><td>100-150</td><td>±0.75</td><td>300-350</td><td>±0.6</td><td>500-600</td><td>±0.4</td></tr><tr><td>100-150</td><td>±0.4</td><td>XX</td><td>±0.2</td><td>150-200</td><td>±0.8</td><td>200-250</td><td>±0.6</td><td>250-300</td><td>±0.5</td></tr><tr><td>150-200</td><td>±0.5</td><td>XX</td><td>±0.1</td><td>200-250</td><td>±0.5</td><td>250-300</td><td>±0.4</td><td>300-OVER</td><td>±0.1</td></tr></table> <table><tr><td>SCALE</td><td>0.000</td><td>UNIT</td><td>MM</td><td>USE ON</td></tr></table>				0-10	±0.25	DECIMALS	100-150	±0.2	250-300	±0.4	UP-500	±1.0	10-100	±0.35	XX	±0.3	100-150	±0.75	300-350	±0.6	500-600	±0.4	100-150	±0.4	XX	±0.2	150-200	±0.8	200-250	±0.6	250-300	±0.5	150-200	±0.5	XX	±0.1	200-250	±0.5	250-300	±0.4	300-OVER	±0.1	SCALE	0.000	UNIT	MM	USE ON	THIRD ANGLE PROJECTION Description: SPEC LABEL (US)			
				0-10	±0.25	DECIMALS	100-150	±0.2	250-300	±0.4	UP-500	±1.0																																							
10-100	±0.35	XX	±0.3	100-150	±0.75	300-350	±0.6	500-600	±0.4																																										
100-150	±0.4	XX	±0.2	150-200	±0.8	200-250	±0.6	250-300	±0.5																																										
150-200	±0.5	XX	±0.1	200-250	±0.5	250-300	±0.4	300-OVER	±0.1																																										
SCALE	0.000	UNIT	MM	USE ON																																															
A3 SIZE				Part No. EIAW-U9KSSU7C03		REV.																																													
						00																																													
				SHEET 1 OF 1		ISSUE DATE: 2020/08/07																																													