

FCC 47 CFR MPE REPORT

Anhui Grizzly Vision Technology Co.,Ltd

75" ULTRA HD SMART TV(ATSC TUNER)

Model Number: RWOSU7549

Additional Model: RWOSU7547, PLED7538-C-UHDSM, RNSMU7536,
RQSM7527

FCC ID: 2AXAQ-RCA-HX-75

Prepared for:	Anhui Grizzly Vision Technology Co.,Ltd
	High-tech Industrial Park,High-tech Zone,Huainan,Anhui,China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2109136
Date of Test:	Jul. 29~Sep. 07, 2021
Date of Report:	Sep. 10, 2021



Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Antenna	Mode (MHz)	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)
0	GFSK 1M-BLE	2480	3.26	2.1184	3±1
0	GFSK-2M-BLE	2480	3.28	2.1281	3±1
0	GFSK-BT	2480	3.30	2.1380	3±1
0	8-DPSK-BT	2480	6.19	4.1591	6±1
1	IEEE 802.11b	2412	17.39	54.8277	16±1
1	IEEE 802.11g	2412	21.04	127.0574	20±1
1	IEEE 802.11n HT20 (2.4G)	2462	19.34	85.9014	18±1
1	IEEE 802.11n HT40 (2.4G)	2422	19.58	90.7821	19±1
1	IEEE 802.11a	5240	13.21	20.9411	13±1
1	IEEE 802.11n HT20 (5G)	5240	11.80	15.1356	11±1
1	IEEE 802.11ac VHT20 (5G)	5240	11.55	14.2889	11±1
1	IEEE 802.11n HT40 (5G)	5230	11.73	14.8936	11±1
1	IEEE 802.11acVHT40 (5G)	5230	11.47	14.0281	11±1
1	IEEE 802.11acVHT80 (5G)	5210	10.73	11.8304	10±1
2	IEEE 802.11b	2462	18.17	65.6145	18±1
2	IEEE 802.11g	2462	21.75	149.6236	21±1
2	IEEE 802.11n HT20 (2.4G)	2462	20.82	120.7814	20±1
2	IEEE 802.11n HT40 (2.4G)	2437	21.05	127.3503	21±1
2	IEEE 802.11a	5785	12.06	16.0694	12±1
2	IEEE 802.11n HT20 (5G)	5785	10.98	12.5314	10±1

2	IEEE 802.11ac VHT20(5G)	5785	10.64	11.5878	10±1
2	IEEE 802.11n HT40 (5G)	5795	10.79	11.9950	10±1
2	IEEE 802.11acVHT40 (5G)	5795	10.07	10.1625	10±1
2	IEEE 802.11acVHT80 (5G)	5775	9.60	9.1201	9±1

3. Calculated Result and Limit

Bluetooth Antenna 0

Mode	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
BLE	4	2	1.585	0.0008	1	Complies
BT	7	2	1.585	0.0016	1	Complies

W-Fi Antenna 1

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	17	2	1.585	0.0158	1	Complies
IEEE 802.11g	21	2	1.585	0.0397	1	Complies
IEEE 802.11n HT20	19	2	1.585	0.0250	1	Complies
IEEE 802.11n HT40	20	2	1.585	0.0315	1	Complies
5G Band						
IEEE 802.11a	14	2	1.585	0.0079	1	Complies
IEEE 802.11n HT20	12	2	1.585	0.0050	1	Complies
IEEE 802.11ac VHT20	12	2	1.585	0.0050	1	Complies
IEEE 802.11n HT40	12	2	1.585	0.0050	1	Complies
IEEE 802.11ac VHT40	12	2	1.585	0.0050	1	Complies
IEEE 802.11ac VHT80	11	2	1.585	0.0040	1	Complies

Wi-Fi Antenna 2

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	19	2	1.585	0.0250	1	Complies
IEEE 802.11g	22	2	1.585	0.0500	1	Complies
IEEE 802.11n HT20	21	2	1.585	0.0397	1	Complies
IEEE 802.11n HT40	22	2	1.585	0.0500	1	Complies
5G Band						
IEEE 802.11a	13	2	1.585	0.0063	1	Complies
IEEE 802.11n HT20	11	2	1.585	0.0040	1	Complies
IEEE 802.11ac VHT20	11	2	1.585	0.0040	1	Complies
IEEE 802.11n HT40	11	2	1.585	0.0040	1	Complies
IEEE 802.11ac VHT40	11	2	1.585	0.0040	1	Complies
IEEE 802.11ac VHT80	10	2	1.585	0.0032	1	Complies

Wi-Fi Antenna 1+2

Mode	Power Density (S) (mW/cm ²) Antenna 1	Power Density (S) (mW/cm ²) Antenna 2	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
2.4G Band					
IEEE 802.11n HT20	0.0250	0.0397	0.0647	1	Complies
IEEE 802.11n HT40	0.0315	0.0500	0.0815	1	Complies
5G Band					
IEEE 802.11n HT20	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11ac VHT20	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11n HT40	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11ac VHT40	0.0050	0.0040	0.0090	1	Complies
IEEE 802.11ac VHT80	0.0040	0.0032	0.0072	1	Complies

Bluetooth+2.4G Wi-Fi+5G Wi-Fi

MAX Power Density (S) (mW/cm ²) Bluetooth	MAX Power Density (S) (mW/cm ²) 2.4G WiFi ANT1+ANT2	MAX Power Density (S) (mW/cm ²) 5G WiFi ANT1+ANT2	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
0.0016	0.0815	0.0090	0.0921	1	Complies

Note: 2.4 and 5GHz bands are share an antenna, Can't both the 2.4 and 5 GHz bands operate simultaneously.

End of Test Report