FCC RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.

FOR

Realfit GoPods E5

ISSUED TO
Zhi Mei Shang Pin Technology(shenzhen) Co., Ltd.

Room A802, Building G4, TCL International E City, Shuguang Community, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tested by: Ye Hongji
Ye Hongji
Date Sep. 30, 2020

Approved by:
Wei Yanquan
(Chief Engineer)
Date Sep. 30, 2020

Report No.:	BL-SZ2090475-602
EUT Name:	Realfit GoPods E5
Model Name:	RT02
Brand Name:	Realfit
Test Standard:	47 CFR Part 15 Subpart C
FCC ID:	2AXBT-RT02R
Test conclusion:	Pass
Test Date:	Sep. 17, 2020 ~ Sep. 25, 2020
Date of Issue:	Sep. 30, 2020

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055
TEL: +86-755-66850100, FAX: +86-755-61824271
Email: qc@baluntek.com
www.baluntek.com

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Sep. 30, 2020	Initial Issue

TABLE OF CONTENTS

1 ADMINISTRATIVE DATA (GENERAL INFORMATION) 5

1.1 Identification of the Testing Laboratory 5

1.2 Identification of the Responsible Testing Location 5

1.3 Laboratory Condition 5

1.4 Announce 6

2 PRODUCT INFORMATION 7

2.1 Applicant Information 7

2.2 Manufacturer Information 7

2.3 Factory Information 7

2.4 General Description for Equipment under Test (EUT) 7

2.5 Technical Information 8

2.6 Additional Instructions 9

3 SUMMARY OF TEST RESULTS 10

3.1 Test Standards 10

3.2 Verdict 10

4 GENERAL TEST CONFIGURATIONS 11

4.1 Test Environments 11

4.2 Test Equipment List 11

4.3 Measurement Uncertainty 12

4.4 Description of Test Setup 13

4.4.1 For Antenna Port Test 13

4.4.2 For AC Power Supply Port Test 13

4.4.3 For Radiated Test (Below 30 MHz) 14

4.4.4 For Radiated Test (30 MHz-1 GHz) 14

4.4.5 For Radiated Test (Above 1 GHz) 15

4.5 Measurement Results Explanation Example 16

4.5.1 For conducted test items: 16

5 TEST ITEMS 17
5.1 Antenna Requirements 17
5.1.1 Relevant Standards 17
5.1.2 Antenna Anti-Replacement Construction 17
5.1.3 Antenna Gain 17
5.2 Frequency Hopping Systems 18
5.2.1 Relevant Standards 18
5.2.2 Description of the systems 18
5.3 Number of Hopping Frequencies 20
5.3.1 Limit 20
5.3.2 Test Setup 20
5.3.3 Test Procedure 20
5.3.4 Test Result 20
5.4 Peak Output Power and E.I.R.P 21
5.4.1 Test Limit 21
5.4.2 Test Setup 21
5.4.3 Test Procedure 21
5.4.4 Test Result 21
5.5 Occupied Bandwidth 22
5.5.1 Limit 22
5.5.2 Test Setup 22
5.5.3 Test Procedure 22
5.5.4 Test Result 22
5.6 Carrier Frequency Separation 23
5.6.1 Limit 23
5.6.2 Test Setup 23
5.6.3 Test Procedure 23
5.6.4 Test Result 23
5.7 Time of Occupancy (Dwell time) 24
5.7.1 Limit 24
5.7.2 Test Setup 24
5.7.3 Test Procedure 24
5.7.4 Test Result 25

5.8 Conducted Spurious Emission & Authorized-band band-edge 26
5.8.1 Limit 26
5.8.2 Test Setup 26
5.8.3 Test Procedure 26
5.8.4 Test Result 26
5.9 Conducted Emission 27
5.9.1 Limit 27
5.9.2 Test Setup 27
5.9.3 Test Procedure 27
5.9.4 Test Result 27
5.10 Radiated Spurious Emission 28
5.10.1 Limit 28
5.10.2 Test Setup 28
5.10.3 Test Procedure 28
5.10.4 Test Result 29
5.11 Band Edge (Restricted-band band-edge) 30
5.11.1 Limit 30
5.11.2 Test Setup 30
5.11.3 Test Procedure 30
5.11.4 Test Result 30
ANNEX A TEST RESULT 31
A.1 Number of Hopping Frequency 31
A.2 Peak Output Power and E.I.R.P 32
A.3 20 dB and 99% bandwidth 35
A.4 Hopping Frequency Separation 40
A.5 Average Time of Occupancy 41
A.6 Conducted Spurious Emissions & Authorized-band band-edge 44
A.7 Conducted Emissions 51
A.8 Radiated Spurious Emission 53
A.9 Band Edge (Restricted-band band-edge) 71
ANNEX B TEST SETUP PHOTOS 75
ANNEX C EUT EXTERNAL PHOTOS 75
ANNEX D EUT INTERNAL PHOTOS 75

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20℃ to 25℃
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

(1) The test report reference to the report template version v5.7.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.

(5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.

(6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Zhi Mei Shang Pin Technology(shenzhen) Co., Ltd.
Address	Room A802, Building G4, TCL International E City, Shuguang Community, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

2.2 Manufacturer Information

Manufacturer	Zhi Mei Shang Pin Technology(shenzhen) Co., Ltd.
Address	Room A802, Building G4, TCL International E City, Shuguang Community, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

2.3 Factory Information

Factory	Realfit (Shenzhen) Intelligent Technology Co., Ltd.
Address	701, Block B, Building G4, TCL International E City Nanshan District, Shenzhen, Guangdong, China.

2.4 General Description for Equipment under Test (EUT)

EUT Name	Realfit GoPods E5
Model Name Under Test	RT02
Series Model Name	RT02-000R
Description of Model name differentiation	N/A
Hardware Version	RF02_E1_V1.4_R_0722
Software Version	E5.1.0.113
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth 5.0 (BR+EDR)

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, ∏/4-DQPSK, 8-DPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	FPC Antenna
Antenna Gain	-3.77 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	**2402**	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	**78**	**2480**
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	**39**	**2441**	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

2.6 Additional Instructions

EUT Software Settings:

Mode	☒ Bluetooth test mode loop back enabled. EUT is controlled over CBT / CMW.

Power level setup in software			
Test Software Version	BQB		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	TX LEVEL is built-in set parameters and cannot be changed and selected.
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-17 Edition)	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note [1]
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	ANNEX A.1	Pass	Note [2]
3	Peak Output Power and E.I.R.P	15.247(b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.3	Pass	Note [2]
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	ANNEX A.4	Pass	Note [2]
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	ANNEX A.5	Pass	Note [2]
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Low/Middle/High	ANNEX A.6	Pass	Note [2]
8	Conducted Emission	15.207	Low/Middle/High	ANNEX A.7	Pass	Note [2]
9	Radiated Spurious Emission	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.8	Pass	Note [2]
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.9	Pass	Note [2]
11	Receiver Spurious Emissions	--	--	--	N/A	Note [3]

Note [1]: Please refer to section 5.1

Note [2]: Π/4-DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in Π/4-DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note [3]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	3.7 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2020.06.08	2021.06.07
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2020.06.08	2021.06.07
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2020.06.09	2021.06.08
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2020.06.09	2021.06.08
LISN	SCHWARZBECK	NSLK 8127	8127-687	2020.06.09	2021.06.08
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2020.06.08	2021.06.07
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW270	100607	2020.06.08	2021.06.07
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2020.06.08	2021.06.07
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2020.06.08	2021.06.07
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2020.06.08	2021.06.07
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
Temperature Chamber	AHK	SP20	1412	2020.06.10	2021.06.09
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2021.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2021.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2019.01.06	2021.01.05
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2021.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2020.06.08	2021.06.07
Power Amplifier	OPHIR RF	5225F	1037	2020.02.19	2021.02.18
Power Amplifier	OPHIR RF	5273F	1016	2020.02.19	2021.02.18
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Sound Level Meter	B&K	NL-20	00844023	2019.11.12	2020.11.11
Ear Simulator	B&K	4185	2409449	2019.11.12	2020.11.11

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Ear Simulator	B&K	4195	2418189	2019.11.12	2020.11.11
Audio analyzer	B&K	UPL 16	100129	2019.11.12	2020.11.11

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%

4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:
Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

4.4.2 For AC Power Supply Port Test



(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.
Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).
Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.
Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.
For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.
Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwith and transmitted bandwith are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (d)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power and E.I.R.P

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (b)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span

Video (or Average) Bandwidth (VBW) ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a); RSS-247, 5.1 (d)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
Span: Zero span, centered on a hopping channel
RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel
Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel
Detector function: Peak
Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:
For GFSK and 8-DPSK:
For DH1 package type

{Total of Dwell} = {Pulse Time} * (1600 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} * (1600 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} * (1600 / 6) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For AFH Mode:
For DH1 package type

{Total of Dwell} = {Pulse Time} * (800 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} * (800 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} * (800 / 6) / {Number of Hopping Frequency} * {Period}

{Period} = 0.4 s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5.

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz
VBW = 300 kHz
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW

Sweep = auto
Detector function = peak
Trace = max hold
For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT

A.1 Number of Hopping Frequency

Test Data

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots

GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power and E.I.R.P

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK		dBm	mW	
	dBm	mW			
Low	4.70	2.95	21	125	Pass
Middle	4.30	2.69			Pass
High	4.18	2.62			Pass

Channel	Measured Output Peak Power				Limit		Verdict
	∏/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW			
Low	4.58	2.87	4.61	2.89	21	125	Pass
Middle	4.31	2.70	4.31	2.70			Pass
High	4.20	2.63	4.19	2.62			Pass

Test plots

GFSK LOW CHANNEL



Date: 18.SEP.2020 20:17:26

GFSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:19:46

GFSK HIGH CHANNEL



Date: 18.SEP.2020 20:21:39

Π/4-DQPSK LOW CHANNEL



Date: 18.SEP.2020 20:24:09

Π/4-DQPSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:25:08

Π/4-DQPSK HIGH CHANNEL



Date: 18.SEP.2020 20:26:33

8-DPSK LOW CHANNEL



Date: 18.SEP.2020 20:27:39

8-DPSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:29:54

8-DPSK HIGH CHANNEL



Date: 18.SEP.2020 20:31:48

A.3 20 dB and 99% bandwidth

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.978271	0.855282
Middle	1.013184	0.881331
High	1.000000	0.876990
∏/4-DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.282471	1.202605
Middle	1.312988	1.224313
High	1.312988	1.211288
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.286865	1.211288
Middle	1.299805	1.224313
High	1.299805	1.219971

Test plots

20 dB Bandwidth

GFSK LOW CHANNEL



Date: 18.SEP.2020 20:17:42

GFSK MIDDLE CHANNEL

Date: 18.SEP.2020 20:20:01

GFSK HIGH CHANNEL



Date: 18.SEP.2020 20:21:55

Π/4-DQPSK LOW CHANNEL



Date: 18.SEP.2020 20:24:25

Π/4-DQPSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:25:24

Π/4-DQPSK HIGH CHANNEL

Date: 18.SEP.2020 20:26:48

8-DPSK LOW CHANNEL



Date: 18.SEP.2020 20:27:55

8-DPSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:30:09

8-DPSK HIGH CHANNEL



Date: 18.SEP.2020 20:32:04

99% Bandwidth

GFSK LOW CHANNEL



Date: 18.SEP.2020 20:17:57

GFSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:20:17

GFSK HIGH CHANNEL



Date: 18.SEP.2020 20:22:10

Π/4-DQPSK LOW CHANNEL



Date: 18.SEP.2020 20:24:40

Π/4-DQPSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:25:40

Π/4-DQPSK HIGH CHANNEL

Date: 18.SEP.2020 20:27:04

8-DPSK LOW CHANNEL



Date: 18.SEP.2020 20:28:10

8-DPSK MIDDLE CHANNEL



Date: 18.SEP.2020 20:30:25

8-DPSK HIGH CHANNEL



Date: 18.SEP.2020 20:32:20

A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	Max 2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.0033	0.675456	Pass
8-DPSK	1.0033	0.866537	Pass

Test Plots

GFSK



8-DPSK



A.5 Average Time of Occupancy

Test Data

GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38600	123.520	0.4	Pass
DH 3	1.62183	259.493	0.4	Pass
DH 5	2.87500	306.667	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.39383	126.026	0.4	Pass
DH 3	1.62492	259.987	0.4	Pass
DH 5	2.88500	307.733	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38933	62.293	0.4	Pass
DH 3	1.63100	130.480	0.4	Pass
DH 5	2.87530	153.349	0.4	Pass

Test Plots

GFSK DH1



Date: 18.SEP.2020 20:43:59

GFSK DH3



Date: 18.SEP.2020 20:44:25

GFSK DH5



Date: 18.SEP.2020 20:44:54

8-DPSK DH1



Date: 18.SEP.2020 20:47:16

8-DPSK DH3



Date: 18.SEP.2020 20:47:47

8-DPSK DH5



Date: 18.SEP.2020 20:48:16

AFH Mode DH1



Date: 18.SEP.2020 20:45:30

AFH Mode DH3



Date: 18.SEP.2020 20:45:57

AFH Mode DH5



Date: 18.SEP.2020 20:46:23

A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-27.24	4.44	-15.56	Pass
Middle	-27.42	4.12	-15.88	Pass
High	-27.40	4.01	-15.99	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-26.93	4.46	-15.54	Pass
Middle	-27.48	4.15	-15.85	Pass
High	-26.92	4.02	-15.98	Pass

Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-27.29	4.43	-15.57	Pass
8-DPSK	-27.15	4.25	-15.75	Pass

Test Plots

GFSK LOW CHANNEL, CARRIER LEVEL



Date: 18.SEP.2020 20:18:09

GFSK LOW CHANNEL, BAND EDGE



Date: 18.SEP.2020 20:19:18

GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:18:35

GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.SEP.2020 20:18:48

GFSK MIDDLE CHANNEL, CARRIER LEVEL



Date: 18.SEP.2020 20:20:28

GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:20:50

GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.SEP.2020 20:21:02

GFSK HIGH CHANNEL, CARRIER LEVEL



Date: 18.SEP.2020 20:22:25

GFSK HIGH CHANNEL, BAND EDGE

Date: 18.SEP.2020 20:23:44

GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:23:05

GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.SEP.2020 20:23:16

8-DPSK LOW CHANNEL, CARRIER LEVEL



Date: 18.SEP.2020 20:28:24

8-DPSK LOW CHANNEL, BAND EDGE



Date: 18.SEP.2020 20:29:32

8-DPSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:28:49

8-DPSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.SEP.2020 20:29:03

8-DPSK MIDDLE CHANNEL, CARRIER LEVEL



Date: 18.SEP.2020 20:30:38

8-DPSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:31:07

8-DPSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.SEP.2020 20:31:21

8-DPSK HIGH CHANNEL, CARRIER LEVEL



Date: 18.SEP.2020 20:32:31

8-DPSK HIGH CHANNEL, BAND EDGE



Date: 18.SEP.2020 20:33:37

8-DPSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:32:55

8-DPSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.SEP.2020 20:33:08

GFSK HOPPING, CARRIER LEVEL



GFSK HOPPING BAND EDGE (LOW)



GFSK HOPPING BAND EDGE (HIGH)



GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



GFSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



8-DPSK HOPPING, CARRIER LEVEL



Date: 18.SEP.2020 20:40:42

8-DPSK Hopping BAND EDGE (LOW)



Date: 18.SEP.2020 20:42:27

8-DPSK Hopping BAND EDGE (HIGH)



Date: 18.SEP.2020 20:42:51

8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.SEP.2020 20:41:36

8-DPSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



Date: 18.SEP.2020 20:41:58

A.7 Conducted Emissions

Note [1]: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.
Note [2]: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.
Note [3]: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.162	43.23	10.40	65.36	-22.13	Peak	L	Pass
1**	0.162	28.46	10.40	55.36	-26.90	AV	L	Pass
2	0.196	41.32	10.38	63.78	-22.46	Peak	L	Pass
2**	0.196	27.34	10.38	53.78	-26.44	AV	L	Pass
3	0.224	39.89	10.37	62.67	-22.78	Peak	L	Pass
3**	0.224	26.73	10.37	52.67	-25.94	AV	L	Pass
4	0.280	38.42	10.34	60.82	-22.40	Peak	L	Pass
4**	0.280	25.00	10.34	50.82	-25.82	AV	L	Pass
5	0.770	37.48	10.26	56.00	-18.52	Peak	L	Pass
5**	0.770	24.23	10.26	46.00	-21.77	AV	L	Pass
6	1.664	36.38	10.26	56.00	-19.62	Peak	L	Pass
6**	1.664	23.21	10.26	46.00	-22.79	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	44.81	10.41	66.00	-21.19	Peak	N	Pass
1**	0.150	29.13	10.41	56.00	-26.87	AV	N	Pass
2	0.178	42.44	10.39	64.58	-22.14	Peak	N	Pass
2**	0.178	27.91	10.39	54.58	-26.67	AV	N	Pass
3	0.242	39.34	10.34	62.03	-22.69	Peak	N	Pass
3**	0.242	25.82	10.34	52.03	-26.21	AV	N	Pass
4	0.626	35.69	10.28	56.00	-20.31	Peak	N	Pass
4**	0.626	25.02	10.28	46.00	-20.98	AV	N	Pass
5	1.034	35.50	10.23	56.00	-20.50	Peak	N	Pass
5**	1.034	23.76	10.23	46.00	-22.24	AV	N	Pass
6	1.766	36.08	10.26	56.00	-19.92	Peak	N	Pass
6**	1.766	23.84	10.26	46.00	-22.16	AV	N	Pass

A.8 Radiated Spurious Emission

Test Data and Plots

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.

Note [4]: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.624	26.75	-22.51	40.0	-13.25	Peak	146.00	100	Horizontal	Pass
2	53.959	15.60	-22.97	40.0	-24.40	Peak	291.10	200	Horizontal	Pass
3	95.766	14.82	-24.77	43.5	-28.68	Peak	263.90	100	Horizontal	Pass
4	119.434	14.20	-25.81	43.5	-29.30	Peak	349.20	100	Horizontal	Pass
5	201.544	18.44	-23.86	43.5	-25.06	Peak	141.90	100	Horizontal	Pass
6	273.518	27.51	-22.29	46.0	-18.49	Peak	217.70	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.624	27.02	-22.51	40.0	-12.98	Peak	291.50	200	Vertical	Pass
2	64.144	23.06	-24.96	40.0	-16.94	Peak	360.00	200	Vertical	Pass
3	149.989	19.06	-28.19	43.5	-24.44	Peak	360.00	200	Vertical	Pass
4	167.206	19.73	-26.99	43.5	-23.77	Peak	269.60	100	Vertical	Pass
5	205.085	18.67	-23.78	43.5	-24.83	Peak	55.80	200	Vertical	Pass
6	278.078	20.12	-21.90	46.0	-25.88	Peak	360.00	200	Vertical	Pass

Test Data and Plots (1 GHz ~ 10th Harmonic)

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1775.400	46.64	-16.97	74.0	-27.36	Peak	0.00	150	Horizontal	Pass
1**	1775.400	36.27	-16.97	54.0	-17.73	AV	0.00	150	Horizontal	Pass
2	2401.800	101.66	-12.26	74.0	27.66	Peak	84.00	150	Horizontal	N/A
2**	2401.800	99.97	-12.26	54.0	45.97	AV	84.00	150	Horizontal	N/A
3	4792.400	49.64	-2.68	74.0	-24.36	Peak	324.00	150	Horizontal	Pass
3**	4792.400	39.35	-2.68	54.0	-14.65	AV	324.00	150	Horizontal	Pass
4	6297.600	51.99	-0.73	74.0	-22.01	Peak	184.00	150	Horizontal	Pass
4**	6297.600	42.24	-0.73	54.0	-11.76	AV	184.00	150	Horizontal	Pass
5	12012.562	50.99	1.10	74.0	-23.01	Peak	190.00	150	Horizontal	Pass
5**	12012.562	41.34	1.10	54.0	-12.66	AV	190.00	150	Horizontal	Pass
6	15746.962	53.95	0.98	74.0	-20.05	Peak	131.00	150	Horizontal	Pass
6**	15746.962	45.00	0.98	54.0	-9.00	AV	131.00	150	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1776.600	53.71	-16.94	74.0	-20.29	Peak	41.00	150	Vertical	Pass
1**	1776.600	37.76	-16.94	54.0	-16.24	AV	41.00	150	Vertical	Pass
2	2401.900	98.89	-12.26	74.0	24.89	Peak	152.00	150	Vertical	N/A
2**	2401.900	97.71	-12.26	54.0	43.71	AV	152.00	150	Vertical	N/A
3	3944.400	47.10	-5.26	74.0	-26.90	Peak	207.00	150	Vertical	Pass
3**	3944.400	36.56	-5.26	54.0	-17.44	AV	207.00	150	Vertical	Pass
4	6272.200	52.21	-0.24	74.0	-21.79	Peak	343.00	150	Vertical	Pass
4**	6272.200	42.80	-0.24	54.0	-11.20	AV	343.00	150	Vertical	Pass
5	11956.500	50.45	1.09	74.0	-23.55	Peak	121.00	150	Vertical	Pass
5**	11956.500	40.73	1.09	54.0	-13.27	AV	121.00	150	Vertical	Pass
6	15811.537	54.13	2.13	74.0	-19.87	Peak	188.00	150	Vertical	Pass
6**	15811.537	44.64	2.13	54.0	-9.36	AV	188.00	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1705.200	45.42	-17.21	74.0	-28.58	Peak	0.00	150	Horizontal	Pass
1**	1705.200	32.02	-17.21	54.0	-21.98	AV	0.00	150	Horizontal	Pass
2	2440.800	99.01	-12.79	74.0	25.01	Peak	92.00	150	Horizontal	N/A
2**	2440.800	97.81	-12.79	54.0	43.81	AV	92.00	150	Horizontal	N/A
3	5089.800	49.71	-2.46	74.0	-24.29	Peak	332.00	150	Horizontal	Pass
3**	5089.800	40.93	-2.46	54.0	-13.07	AV	332.00	150	Horizontal	Pass
4	6676.600	52.84	-0.59	74.0	-21.16	Peak	360.00	150	Horizontal	Pass
4**	6676.600	45.11	-0.59	54.0	-8.89	AV	360.00	150	Horizontal	Pass
5	12105.425	51.00	0.60	74.0	-23.00	Peak	216.00	150	Horizontal	Pass
5**	12105.425	40.88	0.60	54.0	-13.12	AV	216.00	150	Horizontal	Pass
6	15780.563	53.74	1.57	74.0	-20.26	Peak	347.00	150	Horizontal	Pass
6**	15780.563	45.33	1.57	54.0	-8.67	AV	347.00	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1793.800	53.18	-16.81	74.0	-20.82	Peak	43.00	150	Vertical	Pass
1**	1793.800	35.60	-16.81	54.0	-18.40	AV	43.00	150	Vertical	Pass
2	2440.800	97.27	-12.79	74.0	23.27	Peak	157.00	150	Vertical	N/A
2**	2440.800	95.29	-12.79	54.0	41.29	AV	157.00	150	Vertical	N/A
3	3953.000	46.28	-4.64	74.0	-27.72	Peak	360.00	150	Vertical	Pass
3**	3953.000	39.62	-4.64	54.0	-14.38	AV	360.00	150	Vertical	Pass
4	6283.400	52.00	-0.22	74.0	-22.00	Peak	255.00	150	Vertical	Pass
4**	6283.400	44.11	-0.22	54.0	-9.89	AV	255.00	150	Vertical	Pass
5	12454.737	51.81	1.88	74.0	-22.19	Peak	111.00	150	Vertical	Pass
5**	12454.737	41.48	1.88	54.0	-12.52	AV	111.00	150	Vertical	Pass
6	17182.839	54.79	2.59	74.0	-19.21	Peak	75.00	150	Vertical	Pass
6**	17182.839	45.55	2.59	54.0	-8.45	AV	75.00	150	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1317.100	46.53	-17.38	74.0	-27.47	Peak	0.00	150	Horizontal	Pass
1**	1317.100	46.07	-17.38	54.0	-7.93	AV	0.00	150	Horizontal	Pass
2	2479.800	97.57	-12.43	74.0	23.57	Peak	86.00	150	Horizontal	N/A
2**	2479.800	95.41	-12.43	54.0	41.41	AV	86.00	150	Horizontal	N/A
3	4291.600	47.50	-5.03	74.0	-26.50	Peak	186.00	150	Horizontal	Pass
3**	4291.600	37.90	-5.03	54.0	-16.10	AV	186.00	150	Horizontal	Pass
4	6690.800	52.17	-0.29	74.0	-21.83	Peak	321.00	150	Horizontal	Pass
4**	6690.800	43.12	-0.29	54.0	-10.88	AV	321.00	150	Horizontal	Pass
5	10938.174	50.00	-0.04	74.0	-24.00	Peak	57.00	150	Horizontal	Pass
5**	10938.174	41.17	-0.04	54.0	-12.83	AV	57.00	150	Horizontal	Pass
6	17469.225	54.70	2.91	74.0	-19.30	Peak	360.00	150	Horizontal	Pass
6**	17469.225	45.52	2.91	54.0	-8.48	AV	360.00	150	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1992.000	54.17	-15.54	74.0	-19.83	Peak	23.00	150	Vertical	Pass
1**	1992.000	43.35	-15.54	54.0	-10.65	AV	23.00	150	Vertical	Pass
2	2479.900	93.39	-12.43	74.0	19.39	Peak	150.00	150	Vertical	N/A
2**	2479.900	92.96	-12.43	54.0	38.96	AV	150.00	150	Vertical	N/A
3	4923.400	48.94	-2.56	74.0	-25.06	Peak	81.00	150	Vertical	Pass
3**	4923.400	39.76	-2.56	54.0	-14.24	AV	81.00	150	Vertical	Pass
4	6983.000	53.45	0.78	74.0	-20.55	Peak	208.00	150	Vertical	Pass
4**	6983.000	43.81	0.78	54.0	-10.19	AV	208.00	150	Vertical	Pass
5	11194.050	49.79	-0.38	74.0	-24.21	Peak	171.00	150	Vertical	Pass
5**	11194.050	40.77	-0.38	54.0	-13.23	AV	171.00	150	Vertical	Pass
6	17428.802	54.21	3.49	74.0	-19.79	Peak	85.00	150	Vertical	Pass
6**	17428.802	46.05	3.49	54.0	-7.95	AV	85.00	150	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1995.500	49.88	-15.55	74.0	-24.12	Peak	357.00	150	Horizontal	Pass
1**	1995.500	31.23	-15.55	54.0	-22.77	AV	357.00	150	Horizontal	Pass
2	2402.100	100.75	-12.26	74.0	26.75	Peak	71.00	150	Horizontal	N/A
2**	2402.100	100.21	-12.26	54.0	46.21	AV	71.00	150	Horizontal	N/A
3	4699.400	48.89	-3.85	74.0	-25.11	Peak	344.00	150	Horizontal	Pass
3**	4699.400	38.44	-3.85	54.0	-15.56	AV	344.00	150	Horizontal	Pass
4	6673.800	52.66	-0.72	74.0	-21.34	Peak	316.00	150	Horizontal	Pass
4**	6673.800	43.37	-0.72	54.0	-10.63	AV	316.00	150	Horizontal	Pass
5	10537.687	50.14	-0.66	74.0	-23.86	Peak	-1.00	150	Horizontal	Pass
5**	10537.687	42.31	-0.66	54.0	-11.69	AV	-1.00	150	Horizontal	Pass
6	17423.550	54.62	3.66	74.0	-19.38	Peak	170.00	150	Horizontal	Pass
6**	17423.550	47.03	3.66	54.0	-6.97	AV	170.00	150	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1947.500	40.85	-15.87	74.0	-33.15	Peak	24.00	150	Vertical	Pass
1**	1947.500	49.95	-15.87	54.0	-4.05	AV	24.00	150	Vertical	Pass
2	2401.800	95.46	-12.26	74.0	21.46	Peak	152.00	150	Vertical	N/A
2**	2401.800	93.25	-12.26	54.0	39.25	AV	152.00	150	Vertical	N/A
3	4966.000	49.48	-3.14	74.0	-24.52	Peak	4.00	150	Vertical	Pass
3**	4966.000	39.52	-3.14	54.0	-14.48	AV	4.00	150	Vertical	Pass
4	6611.800	52.33	0.19	74.0	-21.67	Peak	107.00	150	Vertical	Pass
4**	6611.800	43.01	0.19	54.0	-10.99	AV	107.00	150	Vertical	Pass
5	11143.162	49.80	-0.93	74.0	-24.20	Peak	-3.00	150	Vertical	Pass
5**	11143.162	41.41	-0.93	54.0	-12.59	AV	-3.00	150	Vertical	Pass
6	17468.699	55.17	2.90	74.0	-18.83	Peak	253.00	150	Vertical	Pass
6**	17468.699	46.34	2.90	54.0	-7.66	AV	253.00	150	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1991.200	51.29	-15.51	74.0	-22.71	Peak	0.00	150	Horizontal	Pass
1**	1991.200	30.98	-15.51	54.0	-23.02	AV	0.00	150	Horizontal	Pass
2	2440.900	98.54	-12.80	74.0	24.54	Peak	80.00	150	Horizontal	N/A
2**	2440.900	97.72	-12.80	54.0	43.72	AV	80.00	150	Horizontal	N/A
3	4006.200	47.01	-5.14	74.0	-26.99	Peak	360.00	150	Horizontal	Pass
3**	4006.200	37.37	-5.14	54.0	-16.63	AV	360.00	150	Horizontal	Pass
4	6736.800	52.54	-0.32	74.0	-21.46	Peak	58.00	150	Horizontal	Pass
4**	6736.800	43.75	-0.32	54.0	-10.25	AV	58.00	150	Horizontal	Pass
5	10856.237	49.47	0.07	74.0	-24.53	Peak	-1.00	150	Horizontal	Pass
5**	10856.237	39.37	0.07	54.0	-14.63	AV	-1.00	150	Horizontal	Pass
6	17472.901	55.02	2.86	74.0	-18.98	Peak	206.00	150	Horizontal	Pass
6**	17472.901	46.95	2.86	54.0	-7.05	AV	206.00	150	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1995.400	57.16	-15.55	74.0	-16.84	Peak	16.00	150	Vertical	Pass
1**	1995.400	49.93	-15.55	54.0	-4.07	AV	16.00	150	Vertical	Pass
2	2441.000	94.16	-12.82	74.0	20.16	Peak	68.00	150	Vertical	N/A
2**	2441.000	93.54	-12.82	54.0	39.54	AV	68.00	150	Vertical	N/A
3	4034.200	46.67	-5.01	74.0	-27.33	Peak	30.00	150	Vertical	Pass
3**	4034.200	37.00	-5.01	54.0	-17.00	AV	30.00	150	Vertical	Pass
4	6738.600	52.68	-0.18	74.0	-21.32	Peak	224.00	150	Vertical	Pass
4**	6738.600	43.13	-0.18	54.0	-10.87	AV	224.00	150	Vertical	Pass
5	11269.375	50.12	-0.27	74.0	-23.88	Peak	107.00	150	Vertical	Pass
5**	11269.375	40.53	-0.27	54.0	-13.47	AV	107.00	150	Vertical	Pass
6	17425.650	54.78	3.60	74.0	-19.22	Peak	286.00	150	Vertical	Pass
6**	17425.650	45.62	3.60	54.0	-8.38	AV	286.00	150	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1994.700	49.14	-15.58	74.0	-24.86	Peak	0.00	150	Horizontal	Pass
1**	1994.700	30.93	-15.58	54.0	-23.07	AV	0.00	150	Horizontal	Pass
2	2479.900	96.59	-12.43	74.0	22.59	Peak	65.00	150	Horizontal	N/A
2**	2479.900	93.39	-12.43	54.0	39.39	AV	65.00	150	Horizontal	N/A
3	4584.400	49.28	-3.67	74.0	-24.72	Peak	285.00	150	Horizontal	Pass
3**	4584.400	39.23	-3.67	54.0	-14.77	AV	285.00	150	Horizontal	Pass
4	6687.000	52.72	-0.22	74.0	-21.28	Peak	84.00	150	Horizontal	Pass
4**	6687.000	44.04	-0.22	54.0	-9.96	AV	84.00	150	Horizontal	Pass
5	12018.312	51.07	0.96	74.0	-22.93	Peak	-1.00	150	Horizontal	Pass
5**	12018.312	40.58	0.96	54.0	-13.42	AV	-1.00	150	Horizontal	Pass
6	16079.813	53.74	1.64	74.0	-20.26	Peak	363.00	150	Horizontal	Pass
6**	16079.813	44.09	1.64	54.0	-9.91	AV	363.00	150	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1993.200	47.63	-15.62	74.0	-26.37	Peak	5.00	150	Vertical	Pass
1**	1993.200	50.46	-15.62	54.0	-3.54	AV	5.00	150	Vertical	Pass
2	2480.000	92.47	-12.43	74.0	18.47	Peak	58.00	150	Vertical	N/A
2**	2480.000	90.71	-12.43	54.0	36.71	AV	58.00	150	Vertical	N/A
3	4720.200	49.25	-3.81	74.0	-24.75	Peak	166.00	150	Vertical	Pass
3**	4720.200	40.05	-3.81	54.0	-13.95	AV	166.00	150	Vertical	Pass
4	6611.400	52.42	0.19	74.0	-21.58	Peak	5.00	150	Vertical	Pass
4**	6611.400	42.71	0.19	54.0	-11.29	AV	5.00	150	Vertical	Pass
5	11074.450	49.35	-1.24	74.0	-24.65	Peak	-1.00	150	Vertical	Pass
5**	11074.450	41.09	-1.24	54.0	-12.91	AV	-1.00	150	Vertical	Pass
6	17421.976	54.29	3.70	74.0	-19.71	Peak	363.00	150	Vertical	Pass
6**	17421.976	46.62	3.70	54.0	-7.38	AV	363.00	150	Vertical	Pass

Hopping Mode:

GFSK MODE 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1749.200	48.79	-17.34	74.0	-25.21	Peak	360.00	150	Horizontal	Pass
1**	1749.200	30.24	-17.34	54.0	-23.76	AV	360.00	150	Horizontal	Pass
2	2401.900	92.00	-12.26	74.0	18.00	Peak	188.00	150	Horizontal	N/A
2**	2401.900	90.60	-12.26	54.0	36.60	AV	188.00	150	Horizontal	N/A
3	2480.600	90.66	-12.42	74.0	16.66	Peak	314.00	150	Horizontal	N/A
3**	2480.600	90.05	-12.42	54.0	36.05	AV	314.00	150	Horizontal	N/A
4	6667.400	52.61	-0.87	74.0	-21.39	Peak	3.00	150	Horizontal	Pass
4**	6667.400	42.81	-0.87	54.0	-11.19	AV	3.00	150	Horizontal	Pass
5	11587.350	50.24	-0.26	74.0	-23.76	Peak	171.00	150	Horizontal	Pass
5**	11587.350	40.97	-0.26	54.0	-13.03	AV	171.00	150	Horizontal	Pass
6	16901.175	54.59	1.12	74.0	-19.41	Peak	130.00	150	Horizontal	Pass
6**	16901.175	45.20	1.12	54.0	-8.80	AV	130.00	150	Horizontal	Pass

GFSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1992.100	54.95	-15.55	74.0	-19.05	Peak	24.00	150	Vertical	Pass
1**	1992.100	36.99	-15.55	54.0	-17.01	AV	24.00	150	Vertical	Pass
2	2402.200	91.59	-12.26	74.0	17.59	Peak	332.00	150	Vertical	N/A
2**	2402.200	90.46	-12.26	54.0	36.46	AV	332.00	150	Vertical	N/A
3	2479.300	89.53	-12.44	74.0	15.53	Peak	101.00	150	Vertical	N/A
3**	2479.300	90.47	-12.44	54.0	36.47	AV	101.00	150	Vertical	N/A
4	6606.200	53.06	0.13	74.0	-20.94	Peak	163.00	150	Vertical	Pass
4**	6606.200	43.50	0.13	54.0	-10.50	AV	163.00	150	Vertical	Pass
5	11030.750	49.52	-0.61	74.0	-24.48	Peak	26.00	150	Vertical	Pass
5**	11030.750	40.55	-0.61	54.0	-13.45	AV	26.00	150	Vertical	Pass
6	17420.136	54.26	3.75	74.0	-19.74	Peak	363.00	150	Vertical	Pass
6**	17420.136	45.71	3.75	54.0	-8.29	AV	363.00	150	Vertical	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1992.900	48.83	-15.60	74.0	-25.17	Peak	92.00	150	Horizontal	Pass
1**	1992.900	33.97	-15.60	54.0	-20.03	AV	92.00	150	Horizontal	Pass
2	2401.700	90.78	-12.26	74.0	16.78	Peak	304.00	150	Horizontal	N/A
2**	2401.700	87.79	-12.26	54.0	33.79	AV	304.00	150	Horizontal	N/A
3	2480.600	91.36	-12.42	74.0	17.36	Peak	92.00	150	Horizontal	N/A
3**	2480.600	89.36	-12.42	54.0	35.36	AV	92.00	150	Horizontal	N/A
4	3783.000	46.98	-6.39	74.0	-27.02	Peak	360.00	150	Horizontal	Pass
4**	3783.000	40.13	-6.39	54.0	-13.87	AV	360.00	150	Horizontal	Pass
5	6612.800	52.82	0.19	74.0	-21.18	Peak	58.00	150	Horizontal	Pass
5**	6612.800	42.74	0.19	54.0	-11.26	AV	58.00	150	Horizontal	Pass
6	17178.636	54.55	2.63	74.0	-19.45	Peak	358.00	150	Horizontal	Pass
6**	17178.636	45.79	2.63	54.0	-8.21	AV	358.00	150	Horizontal	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1317.100	50.15	-17.38	74.0	-23.85	Peak	360.00	150	Vertical	Pass
1**	1317.100	49.44	-17.38	54.0	-4.56	AV	360.00	150	Vertical	Pass
2	2402.400	90.87	-12.27	74.0	16.87	Peak	183.00	150	Vertical	N/A
2**	2402.400	86.20	-12.27	54.0	32.20	AV	183.00	150	Vertical	N/A
3	2478.600	87.03	-12.46	74.0	13.03	Peak	360.00	150	Vertical	N/A
3**	2478.600	82.45	-12.46	54.0	28.45	AV	360.00	150	Vertical	N/A
4	4500.200	48.16	-4.46	74.0	-25.84	Peak	0.00	150	Vertical	Pass
4**	4500.200	42.88	-4.46	54.0	-11.12	AV	0.00	150	Vertical	Pass
5	10348.225	50.20	0.03	74.0	-23.80	Peak	361.00	150	Vertical	Pass
5**	10348.225	40.14	0.03	54.0	-13.86	AV	361.00	150	Vertical	Pass
6	17470.011	55.53	2.91	74.0	-18.47	Peak	218.00	150	Vertical	Pass
6**	17470.011	46.71	2.91	54.0	-7.29	AV	218.00	150	Vertical	Pass

A.9 Band Edge (Restricted-band band-edge)

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.
Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.
Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
Note [4]: The Level (dBuV/m) has been corrected by factor.

Test Data

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390.00	54.553	32.61	74	19.447	PEAK	Pass
		2390.00	46.121	32.61	54	7.879	AVERAGE	Pass
GFSK	HIGH	2483.50	53.273	32.54	74	20.727	PEAK	Pass
		2483.50	N/A	N/A	54	N/A	AVERAGE	Pass
8-DPSK	Low	2390.00	55.181	32.61	74	18.819	PEAK	Pass
		2390.00	46.002	32.61	54	7.998	AVERAGE	Pass
8-DPSK	HIGH	2483.50	53.096	32.54	74	20.904	PEAK	Pass
		2483.50	N/A	N/A	54	N/A	AVERAGE	Pass
GFSK(Hopping)	Low	2390.00	54.012	32.61	74	19.988	PEAK	Pass
		2390.00	44.705	32.61	54	9.295	AVERAGE	Pass
GFSK(Hopping)	HIGH	2483.50	53.450	32.54	74	20.550	PEAK	Pass
		2483.50	N/A	N/A	54	N/A	AVERAGE	Pass
8-DPSK (Hopping)	Low	2390.00	53.886	32.61	74	20.114	PEAK	Pass
		2390.00	N/A	N/A	54	N/A	AVERAGE	Pass
8-DPSK (Hopping)	HIGH	2483.50	54.980	32.54	74	19.020	PEAK	Pass
		2483.50	44.660	32.54	54	9.340	AVERAGE	Pass

Test Plots

GFSK LOW CHANNEL, PEAK



GFSK LOW CHANNEL, AV



GFSK HIGH CHANNEL, PEAK



8-DPSK LOW CHANNEL, PEAK



8-DPSK LOW CHANNEL, AV



8-DPSK HIGH CHANNEL, PEAK



Hopping Mode:

GFSK LOW FREQUENCY BAND, PEAK



GFSK LOW FREQUENCY BAND, AV



GFSK HIGH FREQUENCY BAND, PEAK



8-DPSK LOW FREQUENCY BAND, PEAK



8-DPSK HIGH FREQUENCY BAND, PEAK



8-DPSK HIGH FREQUENCY BAND, AV



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2090475-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2090475-AW-3.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2090475-AI-3.PDF”.

--END OF REPORT--