

Product Name: K330w Plus Wireless Mechanical Keyboard	Report No: FCC022022-05618RF3
Product Model: K330w Plus	Security Classification: Open
Version: V1.0	Total Page: 5

TIRT Testing Report



Prepared By:	Checked By:	Approved By:	A circular blue stamp with the text "Beijing TIRT Technology Service Co., Ltd." around the perimeter and "TIRT Shenzhen" in the center.
Stone Tang	Randy Lv	Daniel Chen	
Stone Tang	Randy Lv	Daniel chen	

FCC RF EXPOSURE REPORT

FCC ID: 2AXCA-K330WPLUS

Project No. : 2022-05618
Equipment : K330w Plus Wireless Mechanical Keyboard
Brand Name : DURGOD
Test Model : K330w Plus
Series Model : N/A
Applicant : Zhuhai Hoksi Technology CO.,LTD
Address : Room803,No.3 BLDG,No.6, Pingbei 1 Rd., Nanping Technology & Industry Park,Xiangzhou St.,ZhuHai,China
Manufacturer : Zhuhai Hoksi Technology CO.,LTD
Address : Room803,No.3 BLDG,No.6, Pingbei 1 Rd., Nanping Technology & Industry Park,Xiangzhou St.,ZhuHai,China
Factory : Zhuhai Hengchang Electronic Technology Co.,Ltd
Address : 3rd floor, A building, No. 7 of 3rd pingxi Road, Nanping Technical industry park, Zhuhai, China
Date of Receipt : 2022.10.17
Date of Test : 2022.10.17-2022.10.27
Issued Date : 2022.10.27
Report Version : V1.0
Test Sample : Engineering Sample No.: 20221026018937
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091

- The test result referred exclusively to the presented test model /sample.
- Without written approval of TIRT Inc. the test report shall not reproduced except in full.

Lab: Beijing TIRT Technology Service Co.,Ltd Shenzhen
Add: 101, 3 # Factory Building, Gongjin Electronics, Shatin Community, KengziStreet, Pingshan District, Shenzhen City, Guangdong province, China
TEL: +86-0755-27087573

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
FCC022022-05618RF3	V1.0	Original Report	2022.10.27	Valid

1. TEST FACILITY

Company:	Beijing TIRT Technology Service Co.,Ltd Shenzhen
Address:	101, 3 # Factory Building, Gongjin Electronics, Shatin Community, KengziStreet, Pingshan District, Shenzhen City, Guangdong province, China
CNAS Registration Number:	CNAS L14158
A2LA Registration Number	6049.01
Telephone:	+86-0755-27087573

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

For LE :

Antenna Specification:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		RFPCA430816IM AB301	PCB	IPEX Compatible (Gold)	3.12

Note: The antenna gain is provided by the manufacturer.

3. TEST RESULTS

For LE:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.12	2.05	-3.84	0.413	0.001685	1	Complies

For SRD 2.4G:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.12	2.05	-0.64	0.863	0.00352	1	Complies

Note:

1. Only the worst case recorded.
2. The calculated distance is 20 cm.

End of Test Report