

[illegible]

XIBERIA

Instruction manual

Wearing a wireless headset

G01

Headset specifications

- Model: G01
- Headset battery capacity: 180mAh battery 3.7V/100mAh
- Working time: about 8 hours (70% volume)
- Charging time: about 4 hours
- Standby time: about 200 hours
- Head charging standard: USB TYPE-C, DC5V/2A
- Frequency response: 20Hz-20KHz
- Impedance: 16Ω ± 5dB (1kHz)
- SNR sensitivity: 30 ± 3dB (1kHz)
- Effective distance: 10m (line of sight)
- Effective distance: 10m (line of sight)

Headset connection

Headset adjustment of the wearing position

Headset connection

Headset charging

Recommend charging the battery before using it for the first time.

When the charging cable is connected, the red light on the ear cup will return to the charging state.

Headset pairing

The headset and USB wireless adapter are paired and ready to use at the factory. If the headset connecting your smartphone or PC by following the steps below (it is recommended to contact technical support before pairing to determine if it is necessary):

1. Turn off the headset.
2. Unplug the USB wireless transmitter and receiver.
3. Turn on the headset according to the headset mode.
4. Seeing that the headset LED is on, indicating that the connection is successful.

Headset connection control

The headset can be used as a wired headset with the included 3.5 mm audio cable. To wear the headset in wired mode, the headset will be automatically connected.

Note: If this is your first time using this headset, you will need to set the headset as a power input and output device.

Headset connection and configuration

1. Right-click the speaker icon on the taskbar and select 'Play Devices'.

2. Click on the 'Recording' tab, then 'Right-click on 'XIBERIA G01' and select 'Set as default device'.

3. Right-click on 'XIBERIA G01' device, configure the PCM (Wave) device as follows:

- 1. Navigate to the Settings menu and select it.
- 2. Highlight the Device menu option and select it.
- 3. Select 'Device' in the 'XIBERIA G01' headset.
- 4. Set the 'Output Device' to the XIBERIA G01 Wireless Headset.
- 5. Select 'Output Device' in the XIBERIA G01 Wireless Headset.
- 6. Select 'Output Device' and select 'XIBERIA G01'.

4. Set the 'Output Device' to the XIBERIA G01 Wireless Headset.

5. Select 'Output Device' and select 'XIBERIA G01'.

6. Select 'Output Device' and select 'XIBERIA G01'.

7. Select 'Output Device' and select 'XIBERIA G01'.

8. Select 'Output Device' and select 'XIBERIA G01'.

9. Select 'Output Device' and select 'XIBERIA G01'.

10. Select 'Output Device' and select 'XIBERIA G01'.

11. Select 'Output Device' and select 'XIBERIA G01'.

12. Select 'Output Device' and select 'XIBERIA G01'.

13. Select 'Output Device' and select 'XIBERIA G01'.

14. Select 'Output Device' and select 'XIBERIA G01'.

15. Select 'Output Device' and select 'XIBERIA G01'.

16. Select 'Output Device' and select 'XIBERIA G01'.

17. Select 'Output Device' and select 'XIBERIA G01'.

18. Select 'Output Device' and select 'XIBERIA G01'.

19. Select 'Output Device' and select 'XIBERIA G01'.

20. Select 'Output Device' and select 'XIBERIA G01'.

21. Select 'Output Device' and select 'XIBERIA G01'.

22. Select 'Output Device' and select 'XIBERIA G01'.

23. Select 'Output Device' and select 'XIBERIA G01'.

24. Select 'Output Device' and select 'XIBERIA G01'.

25. Select 'Output Device' and select 'XIBERIA G01'.

26. Select 'Output Device' and select 'XIBERIA G01'.

27. Select 'Output Device' and select 'XIBERIA G01'.

28. Select 'Output Device' and select 'XIBERIA G01'.

29. Select 'Output Device' and select 'XIBERIA G01'.

30. Select 'Output Device' and select 'XIBERIA G01'.

31. Select 'Output Device' and select 'XIBERIA G01'.

32. Select 'Output Device' and select 'XIBERIA G01'.

33. Select 'Output Device' and select 'XIBERIA G01'.

34. Select 'Output Device' and select 'XIBERIA G01'.

35. Select 'Output Device' and select 'XIBERIA G01'.

36. Select 'Output Device' and select 'XIBERIA G01'.

37. Select 'Output Device' and select 'XIBERIA G01'.

38. Select 'Output Device' and select 'XIBERIA G01'.

39. Select 'Output Device' and select 'XIBERIA G01'.

40. Select 'Output Device' and select 'XIBERIA G01'.

41. Select 'Output Device' and select 'XIBERIA G01'.

42. Select 'Output Device' and select 'XIBERIA G01'.

43. Select 'Output Device' and select 'XIBERIA G01'.

44. Select 'Output Device' and select 'XIBERIA G01'.

45. Select 'Output Device' and select 'XIBERIA G01'.

46. Select 'Output Device' and select 'XIBERIA G01'.

47. Select 'Output Device' and select 'XIBERIA G01'.

48. Select 'Output Device' and select 'XIBERIA G01'.

49. Select 'Output Device' and select 'XIBERIA G01'.

50. Select 'Output Device' and select 'XIBERIA G01'.

51. Select 'Output Device' and select 'XIBERIA G01'.

52. Select 'Output Device' and select 'XIBERIA G01'.

53. Select 'Output Device' and select 'XIBERIA G01'.

54. Select 'Output Device' and select 'XIBERIA G01'.

55. Select 'Output Device' and select 'XIBERIA G01'.

56. Select 'Output Device' and select 'XIBERIA G01'.

57. Select 'Output Device' and select 'XIBERIA G01'.

58. Select 'Output Device' and select 'XIBERIA G01'.

59. Select 'Output Device' and select 'XIBERIA G01'.

60. Select 'Output Device' and select 'XIBERIA G01'.

61. Select 'Output Device' and select 'XIBERIA G01'.

62. Select 'Output Device' and select 'XIBERIA G01'.

63. Select 'Output Device' and select 'XIBERIA G01'.

64. Select 'Output Device' and select 'XIBERIA G01'.

65. Select 'Output Device' and select 'XIBERIA G01'.

66. Select 'Output Device' and select 'XIBERIA G01'.

67. Select 'Output Device' and select 'XIBERIA G01'.

68. Select 'Output Device' and select 'XIBERIA G01'.

69. Select 'Output Device' and select 'XIBERIA G01'.

70. Select 'Output Device' and select 'XIBERIA G01'.

71. Select 'Output Device' and select 'XIBERIA G01'.

72. Select 'Output Device' and select 'XIBERIA G01'.

73. Select 'Output Device' and select 'XIBERIA G01'.

74. Select 'Output Device' and select 'XIBERIA G01'.

75. Select 'Output Device' and select 'XIBERIA G01'.

76. Select 'Output Device' and select 'XIBERIA G01'.

77. Select 'Output Device' and select 'XIBERIA G01'.

78. Select 'Output Device' and select 'XIBERIA G01'.

79. Select 'Output Device' and select 'XIBERIA G01'.

80. Select 'Output Device' and select 'XIBERIA G01'.

81. Select 'Output Device' and select 'XIBERIA G01'.

82. Select 'Output Device' and select 'XIBERIA G01'.

83. Select 'Output Device' and select 'XIBERIA G01'.

84. Select 'Output Device' and select 'XIBERIA G01'.

85. Select 'Output Device' and select 'XIBERIA G01'.

86. Select 'Output Device' and select 'XIBERIA G01'.

87. Select 'Output Device' and select 'XIBERIA G01'.

88. Select 'Output Device' and select 'XIBERIA G01'.

89. Select 'Output Device' and select 'XIBERIA G01'.

90. Select 'Output Device' and select 'XIBERIA G01'.

91. Select 'Output Device' and select 'XIBERIA G01'.

92. Select 'Output Device' and select 'XIBERIA G01'.

93. Select 'Output Device' and select 'XIBERIA G01'.

94. Select 'Output Device' and select 'XIBERIA G01'.

95. Select 'Output Device' and select 'XIBERIA G01'.

96. Select 'Output Device' and select 'XIBERIA G01'.

97. Select 'Output Device' and select 'XIBERIA G01'.

98. Select 'Output Device' and select 'XIBERIA G01'.

99. Select 'Output Device' and select 'XIBERIA G01'.

100. Select 'Output Device' and select 'XIBERIA G01'.

101. Select 'Output Device' and select 'XIBERIA G01'.

102. Select 'Output Device' and select 'XIBERIA G01'.

103. Select 'Output Device' and select 'XIBERIA G01'.

104. Select 'Output Device' and select 'XIBERIA G01'.

105. Select 'Output Device' and select 'XIBERIA G01'.

106. Select 'Output Device' and select 'XIBERIA G01'.

107. Select 'Output Device' and select 'XIBERIA G01'.

108. Select 'Output Device' and select 'XIBERIA G01'.

109. Select 'Output Device' and select 'XIBERIA G01'.

110. Select 'Output Device' and select 'XIBERIA G01'.

111. Select 'Output Device' and select 'XIBERIA G01'.

112. Select 'Output Device' and select 'XIBERIA G01'.

113. Select 'Output Device' and select 'XIBERIA G01'.

114. Select 'Output Device' and select 'XIBERIA G01'.

115. Select 'Output Device' and select 'XIBERIA G01'.

116. Select 'Output Device' and select 'XIBERIA G01'.

117. Select 'Output Device' and select 'XIBERIA G01'.

118. Select 'Output Device' and select 'XIBERIA G01'.

119. Select 'Output Device' and select 'XIBERIA G01'.

120. Select 'Output Device' and select 'XIBERIA G01'.

121. Select 'Output Device' and select 'XIBERIA G01'.

122. Select 'Output Device' and select 'XIBERIA G01'.

123. Select 'Output Device' and select 'XIBERIA G01'.

124. Select 'Output Device' and select 'XIBERIA G01'.

125. Select 'Output Device' and select 'XIBERIA G01'.

126. Select 'Output Device' and select 'XIBERIA G01'.

127. Select 'Output Device' and select 'XIBERIA G01'.

128. Select 'Output Device' and select 'XIBERIA G01'.

129. Select 'Output Device' and select 'XIBERIA G01'.

130. Select 'Output Device' and select 'XIBERIA G01'.

131. Select 'Output Device

FCC Warning Statement Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.