

# FCC RF Exposure

EUT Description: **tablet case with keyboard**

Model No.: **ATFS6L10409**

FCC ID: **2AXD9-ATFS6L10409**

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mW

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

### 2.4G

| Frequency | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power mW | Min test separation distance mm | Result | Limit | SAR Test Exclusion |
|-----------|--------------------|---------------------|----------------------|---------------------------------|--------|-------|--------------------|
| 2402MHz   | -8.573             | -8 $\pm$ 1(-7)      | 0.2                  | 5                               | 0.062  | 3.0   | Pass               |

Note:

PK Output power = conducted power.

Conducted power see the test report **HK2008112352-E**

antenna gain = 1.5dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.062 which is  $\leq 3$ , SAR testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm