

Test Report

No. 1-2711-26-01-06_TR1-R01

August 19. 2026

Applicant	WSAUD A/S
Product	RF Module for hearing instruments
Model	RF Module 15
Tested Technology	Bluetooth LE, NFMI
Test Standard	FCC 47 CFR Part 2
FCC ID	2AXDT-RFM015

Verdict **TEST EXEMPTION FULFILLED**

The test results apply only to the equipment specified in this document.

This test report is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.



Digitally signed by
Alexander.Hnatovskiy@cetec
omadvanced.com
Date: 2026.08.19 07:05:43

authorized by

Alexander Hnatovskiy
Coordinator Area
Regulatory Services Radio



Digitally signed by
Eric.Tuettmann@cetecomadv
anced.com
Date: 2026.08.19 05:11:06

created by

Eric Tuettmann
Testing Manager
Regulatory Services Radio

Table of Contents

1. Disclaimer	3
2. Document history.....	4
2.1. Current release	4
2.2. Previous releases	4
3. Test laboratory.....	5
3.1. Contact information	5
3.2. Involved test locations.....	5
3.3. Subcontracted laboratories.....	5
3.4. Laboratory listings and recognitions	5
4. Client information	6
4.1. Applicant.....	6
4.2. Manufacturer.....	6
5. Test sample information	7
5.1. General Information	7
5.1.1. General Data of Main EUT as Declared by Applicant.....	7
6. Measurement details	8
6.1. Test methodology.....	8
7. SAR test exclusion (KDB 447498 D01 General RF Exposure Guidance v06)	9
7.0.1. 4.3.1. Standalone SAR test exclusion considerations	9
7.0.2. Results.....	11
8. Simultaneous Transmission	12
8.1. KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.2.1:.....	12
8.1.1. Results.....	13
8.1.2. TechnologyShare of LimitNFMI0.06%Bluetooth LE14.74%Sum14.80%	13

1. Disclaimer

The test results of this test report relate exclusively to the test item specified in chapter "Test sample information". cetecom advanced does not assume responsibility for any conclusions and generalizations drawn from the test results regarding other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced.

The testing service provided by cetecom advanced has been rendered under the current "General Terms and Conditions for cetecom advanced".

cetecom advanced will not be liable for any loss or damage resulting from false, inaccurate, inappropriate, or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced test report include or imply any product or service warranties from cetecom advanced, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced.

All rights and remedies regarding vendor's products and services for which cetecom advanced has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. Public keys for verification of the electronic signatures can be requested at the testing laboratory.

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at cetecom advanced.

2. Document history

2.1. Current release

Release No.: R01
Date of release: August 19. 2026
Applied changes: Initial release

2.2. Previous releases

Version	Applied change	Date of release
n/a		

3. Test laboratory

3.1. Contact information

cetecom advanced GmbH
Untertuerkheimer Str. 6-10
66117 Saarbruecken
Germany

3.2. Involved test locations

Saarbrücken Lab

Untertürkheimer Strasse 6 – 10
66117 Saarbrücken
Germany

3.3. Subcontracted laboratories

None.

3.4. Laboratory listings and recognitions

	Saarbrücken	Essen
FCC	DE0002	DE0003
ISED	DE0001 3462C	DE0001 3462D

4. Client information

4.1. Applicant

Name: WSAUD A/S
Address: DENMARK, DK-3540 Lynge, Nymøllevej 6
Contact Person: Carsten Quaade Jensen
Contact Person's Email: carsten.jensen@wsa.com

4.2. Manufacturer

Name: WSAUD A/S
Address: DENMARK, DK-3540 Lynge, Nymøllevej 6
Contact Person: Carsten Quaade Jensen
Contact Person's Email: carsten.jensen@wsa.com

5. Test sample information

The data about the test samples is given/supplied by the customer and not under control by cetecom advanced GmbH.

5.1. General Information

5.1.1. General Data of Main EUT as Declared by Applicant

FCC ID

2AXDT-RFM015

6. Measurement details

6.1. Test methodology

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number D-PL-12047-01-00.

Test method, standard, rule	Description
FCC 47 CFR Part 2	Federal Communications Commission, 47 code of federal regulations, Part 2: General Rules & Regulations for Equipment Authorisation

7. SAR test exclusion (KDB 447498 D01 General RF Exposure Guidance v06)

7.0.1. 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops and tablets, etc.

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

1) $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f_{(\text{MHz})}/150)]\}$ mW, for 100 MHz to 1500 MHz

2) $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$ mW, for > 1500 MHz and ≤ 6 GHz

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f_{(\text{MHz})})]$

For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and

100 MHz is multiplied by ½

SAR measurement procedures are not established below 100 MHz.

MHz	5	10	15	20	25	mm
150	49	77	116	155	194	
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

7.0.2. Results

customer declared minimum safety distance: 5 mm

Technology	Note	Frequency [MHz]	Threshold 1g, 10g	Threshold 100 MHz, 50mm	Powerlimit [mW]	P _{max} [dBm]	P _{max} [mW]	Limit [%]
BT LE	A	2450.00	3	-/-	9.58	1.50	1.41	14.74%
NFMI	B	10.60	3	474.34	468.34	-5.20	0.3	0.06%

Value	Explanation
Output Power	The larger of the maximum conducted power or equivalent isotropic radiated power (EIRP), source-based and time-averaged.
Limit	SAR-based threshold in mW.
Limit %	Output Power / Limit

Notes & References

#	Document	Document Type	Additional Information
A	1-2711-26-01-03_TR1-R01	cetecom advanced test report	pg 24, 1.5 dBm cond.
B	-/-	customer declaration	-/-

8. Simultaneous Transmission

8.1. KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.2.1:

As discussed in § 1.1307(b)(3)(ii)(A), the 1-mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

When maximum available power each individual transmitting antenna within the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.

When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time-averaging period. This exemption may not be combined with any other exemption.

KDB 447498 D04 Interim General RF Exposure Guidance v01, section 2.1.2:

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of Formula (4) (see section 7.1) is satisfied.

For these test exemptions to apply, the maximum output power, duty factor, and other applicable parameters used in the standalone ERP determination tests, must be the same, or corresponding to a more conservative choice, than those required for simultaneous transmission.

The power level of the standalone SAR used to qualify for SAR test exemption, or additional test exemption, must be clearly explained in the SAR report. When simultaneous transmission SAR- based test exemptions, or when the SPLSR test exemption cannot be applied, enlarged zoom scan SAR measurements must be performed at the maximum output power required for the applicable simultaneous transmission scenarios. This power level shall account for the tune-up tolerance requirements of all transmitters, but not more than

2 dB lower than the maximum tune-up tolerance limit.

KDB 447498 D04 Interim General RF Exposure Guidance v01, Appendix C.:

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) shall be used to determine exemption for simultaneous transmission according to Formula 4 [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated}{Exposure Limit_k} \leq 1 \quad (4)$$

where:

- | | |
|---|---|
| a | number of fixed, mobile, or portable RF sources claiming exemption using the § 1.1307(b)(3)(i)(B) formula for P _{th} , including existing exempt transmitters and those being added. |
| b | number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added. |

c	number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.
P _i	the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).
P _{th,i}	the exemption threshold power (P _{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i.
ERP _j	the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j.
ERP _{th,j}	exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question
Evaluated _j	the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.
Exposure Limit _{th,j}	either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE shall be less than 1, to determine simultaneous transmission exposure compliance.

8.1.1. Results

8.1.2.

Technology	Share of Limit
NFMI	0.06%
Bluetooth LE	14.74%
Sum	14.80%

End of document