FCC RADIO TEST REPORT

FCC ID	:	**2AXFL-4269**
Equipment	:	**Digital Media Receiver**
Model Name	:	**H6Y2A5**
Applicant	:	**Orthoclase Feldspar LLC 1202 NE McClain Road Bentonville, AR 72712**
Standard	:	**FCC Part 15 Subpart E §15.407**

The product was received on May 11, 2021 and testing was started from May 21, 2021 and completed on Jun. 25, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 5
1.3 Modification of EUT 6
1.4 Testing Location 6
1.5 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency and Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 10
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 11
3.2 Maximum Conducted Output Power Measurement 14
3.3 Power Spectral Density Measurement 15
3.4 Unwanted Emissions Measurement 18
3.5 AC Conducted Emission Measurement 23
3.6 Automatically Discontinue Transmission 25
3.7 Antenna Requirements 27
4 List of Measuring Equipment **28**
5 Uncertainty of Evaluation **30**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Appendix E. Duty Cycle Plots

History of this test report

Report No.	Version	Description	Issued Date
FR120234-01E	01	Initial issue of report	Jul. 07, 2021

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.403(i)	6dB & 26dB Bandwidth	Pass
3.1	2.1049	99% Occupied Bandwidth	Reporting only
3.2	15.407(a)	Maximum Conducted Output Power	Pass
3.3	15.407(a)	Power Spectral Density	Pass
3.4	15.407(b)	Unwanted Emissions	Pass
3.5	15.207	AC Conducted Emission	Pass
3.6	15.407(c)	Automatically Discontinue Transmission	Pass
3.7	15.203 15.407(a)	Antenna Requirement	Pass

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Alan Liu

Report Producer: Lucy Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	H6Y2A5
FCC ID	2AXFL-4269
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	**MIMO<Ant. 1 + 2>** 802.11a: 20.06 dBm / 0.1014 W 802.11n HT20: 19.96 dBm / 0.0991 W 802.11n HT40: 18.61 dBm / 0.0727 W 802.11ac VHT20: 19.86 dBm / 0.0968 W 802.11ac VHT40: 18.51 dBm / 0.0710 W 802.11ac VHT80: 17.32 dBm / 0.0540 W
99% Occupied Bandwidth	**MIMO<Ant. 1>** 802.11a: 17.83 MHz 802.11n HT20: 18.53 MHz 802.11n HT40: 36.46 MHz 802.11ac VHT80: 75.28 MHz **MIMO<Ant. 2>** 802.11a: 17.48 MHz 802.11n HT20: 18.33 MHz 802.11n HT40: 36.46 MHz 802.11ac VHT80: 75.28 MHz
Antenna Type / Gain	Ant. 1: PCB Dipole Antenna with gain 3.0 dBi Ant. 2: PCB Dipole Antenna with gain 5.5 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Antenna Function for Transmitter	

	Ant. 1	Ant. 2
802.11 a/n/ac MIMO	V	V

Remark:

1. MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2
2. The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH02-HY, CO05-HY, DFS02-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH12-HY (TAF Code: 3786)
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z plane as worst plane.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "#" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Idle with Controller + MPEG4 + Adapter + Bluetooth Link with Speaker
Remark: For Radiated Test Cases, the tests were performed with Adapter.	

Ch. #		Band IV：5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

Remark: For radiation spurious emission, the final modulation and the worst data rate was reference the max RF conducted power.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Speaker	JAWBONE	MINIJAMBOX	N/A	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth controller	N/A	N/A	2AVZA-2374	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “Compliance tool 1.0.1.4” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW ≥ 3 x RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



Maximum 26dB Bandwidth



Maximum 99% Occupied Bandwidth



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

 # Method SA-3 #

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time ≤ (number of points in sweep) × T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
  Detector = power averaging (rms).
- Trace mode = max hold.
- Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
   Method (c): Measure and add 10 log(N_{ANT}) dB.
   With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity 10 log(N_{ANT}) dB is added to each spectrum value before comparing to the emission limit. The addition of 10 log(N_{ANT}) dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{ANT}$ th of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/MHz) for MIMO Ant. 1



Worst Case Power Density (dBm/MHz) for MIMO Ant. 2



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of −27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

EUT is verified this characteristic during the function check of normal sample associated with an access point:

A. Information start: make EUT supply information to the access point.

B. Information stop: stop supplying information to the access point.

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving.

C. Information start: make EUT supply information to the access point again.

The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5745MHz



Note: The control / signaling information during the period B is precluded.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = 10 log(NANT/NSS=1) dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain “DG” is calculated as following table.

<CDD Modes>						
			DG for Power	**DG for PSD**	**Power Limit Reduction**	**PSD Limit Reduction**
	Ant. 1 (dBi)	**Ant. 2 (dBi)**				
Band IV	3.00	5.50	5.50	7.35	0.00	1.35

Power Limit Reduction = DG(Power) – 6dBi, (min = 0)

PSD Limit Reduction = DG(PSD) – 6dBi, (min = 0)

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 04, 2021	May 26, 2021~ Jun. 16, 2021	Jan. 03, 2022	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	37059 & 01	30MHz~1GHz	Oct. 11, 2020	May 26, 2021~ Jun. 16, 2021	Oct. 10, 2021	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 8	1GHz~18GHz	Nov. 23, 2020	May 26, 2021~ Jun. 16, 2021	Nov. 22, 2021	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	00993	18GHz~40GHz	Nov. 19, 2020	May 26, 2021~ Jun. 16, 2021	Nov. 18, 2021	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 24, 2021	May 26, 2021~ Jun. 16, 2021	Mar. 23, 2022	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY572801 20	1GHz~26.5GHz	Jul. 20, 2020	May 26, 2021~ Jun. 16, 2021	Jul. 19, 2021	Radiation (03CH12-HY)
Preamplifier	E-INSTRUME NT TECH LTD.	ERA-100M-18 G-56-01-A70	EC190024 9	1GHz-18GHz	Dec. 05, 2020	May 26, 2021~ Jun. 16, 2021	Dec. 04, 2021	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 11, 2020	May 26, 2021~ Jun. 16, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Jan. 15, 2021	May 26, 2021~ Jun. 16, 2021	Jan. 14, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz~30MHz	Mar. 11, 2021	May 26, 2021~ Jun. 16, 2021	Mar. 10, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 11, 2020	May 26, 2021~ Jun. 16, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 22, 2021	May 26, 2021~ Jun. 16, 2021	Feb. 21, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 22, 2021	May 26, 2021~ Jun. 16, 2021	Feb. 21, 2022	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	May 26, 2021~ Jun. 16, 2021	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	May 26, 2021~ Jun. 16, 2021	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-00098 9	N/A	N/A	May 26, 2021~ Jun. 16, 2021	N/A	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-1 2SS	SN2	1.2GHz Low Pass Filter	Mar. 17, 2021	May 26, 2021~ Jun. 16, 2021	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000 -40ST	SN2	6.75GHz High Pass Filter	Mar. 17, 2021	May 26, 2021~ Jun. 16, 2021	Mar. 16, 2022	Radiation (03CH12-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 03, 2021	May 31 2021~ Jun. 11, 2021	Mar. 02, 2022	Conducted (TH02-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO10	10MHz~6GHz	Dec. 16, 2020	May 31 2021~ Jun. 11, 2021	Dec. 15, 2021	Conducted (TH02-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	May 31 2021~ Jun. 11, 2021	Jul. 21, 2021	Conducted (TH02-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2021	May 31 2021~ Jun. 11, 2021	Mar. 16, 2022	Conducted (TH02-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 25, 2021	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 30, 2020	Jun. 25, 2021	Nov. 29, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 18, 2020	Jun. 25, 2021	Nov. 17, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 01, 2020	Jun. 25, 2021	Nov. 30, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 25, 2021	N/A	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Feb. 25, 2021	Jun. 25, 2021	Feb. 24, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 31, 2020	Jun. 25, 2021	Dec. 30, 2021	Conduction (CO05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV3044	101048	10Hz~44GHz	Apr. 20, 2021	May 21, 2021	Apr. 19, 2022	DFS (DFS02-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.9 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.6 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.9 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Ching Chen / Hank Hsu	Temperature:	21~25	°C
Test Date:	2021/5/31~2021/6/11	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	149	5745	17.63	17.38	21.25	21.25	16.30	16.35	0.5	Pass
11a	6Mbps	2	157	5785	17.68	17.48	21.15	21.00	16.30	16.30	0.5	Pass
11a	6Mbps	2	165	5825	17.83	17.48	21.20	21.10	16.30	16.35	0.5	Pass
HT20	MCS0	2	149	5745	18.48	18.33	21.40	21.25	17.60	17.60	0.5	Pass
HT20	MCS0	2	157	5785	18.53	18.33	21.50	21.05	17.60	17.60	0.5	Pass
HT20	MCS0	2	165	5825	18.43	18.28	23.25	21.25	17.55	17.55	0.5	Pass
HT40	MCS0	2	151	5755	36.46	36.36	41.58	41.40	36.27	36.27	0.5	Pass
HT40	MCS0	2	159	5795	36.36	36.46	41.58	41.58	36.36	36.36	0.5	Pass
VHT80	MCS0	2	155	5775	75.28	75.28	81.76	80.64	76.48	76.48	0.5	Pass

Report Number : FR120234-01E

TEST RESULTS DATA
Average Power Table

Band IV MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	16.40	16.70	19.56	30.00		5.50		Pass
11a	6Mbps	2	157	5785	16.40	17.00	19.72	30.00		5.50		Pass
11a	6Mbps	2	165	5825	17.00	17.10	20.06	30.00		5.50		Pass
HT20	MCS0	2	149	5745	16.40	16.90	19.67	30.00		5.50		Pass
HT20	MCS0	2	157	5785	16.20	16.90	19.57	30.00		5.50		Pass
HT20	MCS0	2	165	5825	16.90	17.00	19.96	30.00		5.50		Pass
HT40	MCS0	2	151	5755	15.40	15.80	18.61	30.00		5.50		Pass
HT40	MCS0	2	159	5795	15.20	15.90	18.57	30.00		5.50		Pass
VHT20	MCS0	2	149	5745	16.30	16.80	19.57	30.00		5.50		Pass
VHT20	MCS0	2	157	5785	16.10	16.80	19.47	30.00		5.50		Pass
VHT20	MCS0	2	165	5825	16.80	16.90	19.86	30.00		5.50		Pass
VHT40	MCS0	2	151	5755	15.30	15.70	18.51	30.00		5.50		Pass
VHT40	MCS0	2	159	5795	15.10	15.80	18.47	30.00		5.50		Pass
VHT80	MCS0	2	155	5775	14.00	14.60	17.32	30.00		5.50		Pass

Report Number : FR120234-01E

TEST RESULTS DATA
Power Spectral Density

Band IV MIMO															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	2.22		4.41	4.89	7.90	28.65		7.35		Pass
11a	6Mbps	2	157	5785	2.22		4.27	5.00	8.01	28.65		7.35		Pass
11a	6Mbps	2	165	5825	2.22		5.02	5.08	8.09	28.65		7.35		Pass
HT20	MCS0	2	149	5745	2.22		4.10	4.58	7.59	28.65		7.35		Pass
HT20	MCS0	2	157	5785	2.22		3.97	4.86	7.87	28.65		7.35		Pass
HT20	MCS0	2	165	5825	2.22		4.75	5.32	8.33	28.65		7.35		Pass
HT40	MCS0	2	151	5755	2.22		0.29	0.71	3.72	28.65		7.35		Pass
HT40	MCS0	2	159	5795	2.22		-0.13	0.92	3.93	28.65		7.35		Pass
VHT80	MCS0	2	155	5775	2.22		-4.11	-2.91	0.10	28.65		7.35		Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	**Temperature :**	23~26℃
		Relative Humidity :	40~50%

EUT Information

Report NO :	120234-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	33.81	55.88	22.07	L1	OFF	19.5
0.152250	47.90	---	65.88	17.98	L1	OFF	19.5
0.233250	---	33.03	52.33	19.30	L1	OFF	19.5
0.233250	36.18	---	62.33	26.15	L1	OFF	19.5
0.498750	---	30.98	46.02	15.04	L1	OFF	19.7
0.498750	34.39	---	56.02	21.63	L1	OFF	19.7
0.568500	---	25.87	46.00	20.13	L1	OFF	19.7
0.568500	29.06	---	56.00	26.94	L1	OFF	19.7
3.732000	---	24.91	46.00	21.09	L1	OFF	19.9
3.732000	26.29	---	56.00	29.71	L1	OFF	19.9
20.573250	---	26.88	50.00	23.12	L1	OFF	20.4
20.573250	29.02	---	60.00	30.98	L1	OFF	20.4

EUT Information

Report NO :	120234-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	33.43	55.88	22.45	N	OFF	19.5
0.152250	47.34	---	65.88	18.54	N	OFF	19.5
0.235500	---	32.50	52.25	19.75	N	OFF	19.5
0.235500	35.75	---	62.25	26.50	N	OFF	19.5
0.501000	---	31.90	46.00	14.10	N	OFF	19.7
0.501000	34.57	---	56.00	21.43	N	OFF	19.7
0.633750	---	24.34	46.00	21.66	N	OFF	19.8
0.633750	26.37	---	56.00	29.63	N	OFF	19.8
2.366250	---	24.20	46.00	21.80	N	OFF	20.0
2.366250	25.57	---	56.00	30.43	N	OFF	20.0
21.158250	---	28.24	50.00	21.76	N	OFF	20.6
21.158250	30.86	---	60.00	29.14	N	OFF	20.6

Appendix C. Radiated Spurious Emission

Test Engineer :	Jack Cheng, Lance Chiang and Chuan Chu	Temperature :	23.8~26.2°C
		Relative Humidity :	56.5~68.6%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5647.2	50.25	-17.95	68.2	41.44	31.6	10.5	33.29	311	245	P	H
		5691.4	53.89	-44.97	98.86	44.91	31.77	10.52	33.31	311	245	P	H
		5717.8	60.77	-49.41	110.18	51.68	31.87	10.53	33.31	311	245	P	H
		5723.2	66.12	-51.98	118.1	57.02	31.89	10.53	33.32	311	245	P	H
	*	5745	114.4	-	-	105.2	31.98	10.54	33.32	311	245	P	H
	*	5745	107.29	-	-	98.09	31.98	10.54	33.32	311	245	A	H
		5624.4	49.28	-18.92	68.2	40.47	31.6	10.49	33.28	109	183	P	V
		5696.2	52.95	-49.45	102.4	43.96	31.78	10.52	33.31	109	183	P	V
		5716.4	60.59	-49.2	109.79	51.5	31.87	10.53	33.31	109	183	P	V
		5723.2	65.74	-52.36	118.1	56.64	31.89	10.53	33.32	109	183	P	V
	*	5745	112.55	-	-	103.35	31.98	10.54	33.32	109	183	P	V
	*	5745	105.08	-	-	95.88	31.98	10.54	33.32	109	183	A	V

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5630	51.72	-16.48	68.2	42.91	31.6	10.49	33.28	100	303	P	H
		5697.8	52.71	-50.87	103.58	43.71	31.79	10.52	33.31	100	303	P	H
		5713	54.63	-54.21	108.84	45.56	31.85	10.53	33.31	100	303	P	H
		5722.8	54.61	-62.57	117.18	45.51	31.89	10.53	33.32	100	303	P	H
	*	5785	115.09	-	-	105.81	32.07	10.55	33.34	100	303	P	H
	*	5785	106.49	-	-	97.21	32.07	10.55	33.34	100	303	A	H
		5854.2	51.21	-61.41	112.62	41.72	32.22	10.63	33.36	100	303	P	H
		5857.8	52	-58.01	110.01	42.49	32.23	10.64	33.36	100	303	P	H
		5883.2	51.78	-47.33	99.11	42.15	32.33	10.67	33.37	100	303	P	H
		5929.4	52.33	-15.87	68.2	42.59	32.4	10.73	33.39	100	303	P	H
		5639.2	50.73	-17.47	68.2	41.92	31.6	10.5	33.29	200	346	P	V
		5680.8	51.61	-39.42	91.03	42.68	31.72	10.51	33.3	200	346	P	V
		5711	51.82	-56.46	108.28	42.77	31.84	10.52	33.31	200	346	P	V
		5724	53.42	-66.5	119.92	44.31	31.9	10.53	33.32	200	346	P	V
	*	5785	111.67	-	-	102.39	32.07	10.55	33.34	200	346	P	V
	*	5785	104.32	-	-	95.04	32.07	10.55	33.34	200	346	A	V
		5853	52	-63.36	115.36	42.52	32.21	10.63	33.36	200	346	P	V
		5871	51.27	-55.05	106.32	41.7	32.28	10.66	33.37	200	346	P	V
		5915	50.98	-24.59	75.57	41.24	32.4	10.72	33.38	200	346	P	V
		5933.8	51.37	-16.83	68.2	41.62	32.4	10.74	33.39	200	346	P	V

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	113.24	-	-	103.85	32.15	10.59	33.35	152	323	P	H
	*	5825	105.8	-	-	96.41	32.15	10.59	33.35	152	323	A	H
		5851	65.29	-54.63	119.92	55.82	32.2	10.63	33.36	152	323	P	H
		5855	56.57	-54.23	110.8	47.08	32.22	10.63	33.36	152	323	P	H
		5882.6	53.74	-45.82	99.56	44.11	32.33	10.67	33.37	152	323	P	H
		5926.6	51.81	-16.39	68.2	42.07	32.4	10.73	33.39	152	323	P	H
	*	5825	111.29	-	-	101.9	32.15	10.59	33.35	150	356	P	V
	*	5825	104.1	-	-	94.71	32.15	10.59	33.35	150	356	A	V
		5851.4	60.32	-58.69	119.01	50.84	32.21	10.63	33.36	150	356	P	V
		5856.6	56.74	-53.61	110.35	47.23	32.23	10.64	33.36	150	356	P	V
		5879.8	51.91	-49.72	101.63	42.29	32.32	10.67	33.37	150	356	P	V
		5934.8	50.57	-17.63	68.2	40.82	32.4	10.74	33.39	150	356	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	49.86	-24.14	74	59.01	39.98	16.96	66.09	100	0	P	H
		17235	52.46	-15.74	68.2	58.69	40.24	20.36	66.83	100	0	P	H
		17989	61.94	-12.06	74	60.57	50.08	20.73	69.44	100	0	P	H
		17989	50.66	-3.34	54	49.29	50.08	20.73	69.44	100	0	A	H
		11490	49.06	-24.94	74	58.21	39.98	16.96	66.09	100	0	P	V
		17235	51.06	-17.14	68.2	57.29	40.24	20.36	66.83	100	0	P	V
		17978	61.88	-12.12	74	60.79	49.76	20.73	69.4	100	0	P	V
		17978	50.39	-3.61	54	49.3	49.76	20.73	69.4	100	0	A	V
802.11a CH 157 5785MHz		11570	49.91	-24.09	74	59.2	39.72	17.03	66.04	100	0	P	H
		17355	51.3	-16.9	68.2	57.04	41	20.42	67.16	100	0	P	H
		17989	60.91	-13.09	74	59.54	50.08	20.73	69.44	100	0	P	H
		17989	50.77	-3.23	54	49.4	50.08	20.73	69.44	100	0	A	H
		11570	49.43	-24.57	74	58.72	39.72	17.03	66.04	100	0	P	V
		17355	51.29	-16.91	68.2	57.03	41	20.42	67.16	100	0	P	V
		17989	60.64	-13.36	74	59.27	50.08	20.73	69.44	100	0	P	V
		17989	50.6	-3.4	54	49.23	50.08	20.73	69.44	100	0	A	V
802.11a CH 165 5825MHz		11650	48.61	-25.39	74	58.22	39.3	17.09	66	100	0	P	H
		17475	54.88	-13.32	68.2	60.2	41.7	20.47	67.49	100	0	P	H
		17978	61.73	-12.27	74	60.64	49.76	20.73	69.4	100	0	P	H
		17978	50.45	-3.55	54	49.36	49.76	20.73	69.4	100	0	A	H
		11650	49.25	-24.75	74	58.86	39.3	17.09	66	100	0	P	V
		17475	53.52	-14.68	68.2	58.84	41.7	20.47	67.49	100	0	P	V
		17989	61.4	-12.6	74	60.03	50.08	20.73	69.44	100	0	P	V
		17989	50.65	-3.35	54	49.28	50.08	20.73	69.44	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5641.6	50.42	-17.78	68.2	41.61	31.6	10.5	33.29	311	245	P	H
		5697.2	54.66	-48.48	103.14	45.66	31.79	10.52	33.31	311	245	P	H
		5719.6	64.59	-46.1	110.69	55.49	31.88	10.53	33.31	311	245	P	H
		5723	69.67	-47.97	117.64	60.57	31.89	10.53	33.32	311	245	P	H
	*	5745	114.34	-	-	105.14	31.98	10.54	33.32	311	245	P	H
	*	5745	107.15	-	-	97.95	31.98	10.54	33.32	311	245	A	H
		5647.8	50.2	-18	68.2	41.39	31.6	10.5	33.29	108	183	P	V
		5688.6	52.52	-44.27	96.79	43.55	31.75	10.52	33.3	108	183	P	V
		5718	62.27	-47.97	110.24	53.18	31.87	10.53	33.31	108	183	P	V
		5724.2	65.77	-54.61	120.38	56.66	31.9	10.53	33.32	108	183	P	V
	*	5745	112.33	-	-	103.13	31.98	10.54	33.32	108	183	P	V
	*	5745	105.09	-	-	95.89	31.98	10.54	33.32	108	183	A	V

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5647.6	50.37	-17.83	68.2	41.56	31.6	10.5	33.29	100	303	P	H
		5691.2	51.94	-46.77	98.71	42.97	31.76	10.52	33.31	100	303	P	H
		5701	55.82	-49.66	105.48	46.81	31.8	10.52	33.31	100	303	P	H
		5723.6	53.45	-65.56	119.01	44.35	31.89	10.53	33.32	100	303	P	H
	*	5785	112.87	-	-	103.59	32.07	10.55	33.34	100	303	P	H
	*	5785	105.06	-	-	95.78	32.07	10.55	33.34	100	303	A	H
		5851.8	52.21	-65.89	118.1	42.73	32.21	10.63	33.36	100	303	P	H
		5856.2	52.6	-57.86	110.46	43.1	32.22	10.64	33.36	100	303	P	H
		5887.2	52.75	-43.39	96.14	43.09	32.35	10.68	33.37	100	303	P	H
		5949.2	50.99	-17.21	68.2	41.22	32.4	10.76	33.39	100	303	P	H
		5625	50.18	-18.02	68.2	41.37	31.6	10.49	33.28	400	164	P	V
		5671.6	51.39	-32.83	84.22	42.49	31.69	10.51	33.3	400	164	P	V
		5702.2	52.13	-53.69	105.82	43.11	31.81	10.52	33.31	400	164	P	V
		5723	52.13	-65.51	117.64	43.03	31.89	10.53	33.32	400	164	P	V
	*	5785	111.16	-	-	101.88	32.07	10.55	33.34	400	164	P	V
	*	5785	104.05	-	-	94.77	32.07	10.55	33.34	400	164	A	V
		5850.6	50.38	-70.45	120.83	40.91	32.2	10.63	33.36	400	164	P	V
		5857.6	52.52	-57.55	110.07	43.01	32.23	10.64	33.36	400	164	P	V
		5891.8	52.25	-40.48	92.73	42.57	32.37	10.68	33.37	400	164	P	V
		5943.6	51.12	-17.08	68.2	41.36	32.4	10.75	33.39	400	164	P	V

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	113.35	-	-	103.96	32.15	10.59	33.35	190	295	P	H
	*	5825	105.83	-	-	96.44	32.15	10.59	33.35	190	295	A	H
		5852.2	60.59	-56.59	117.18	51.11	32.21	10.63	33.36	190	295	P	H
		5856.8	58.09	-52.21	110.3	48.58	32.23	10.64	33.36	190	295	P	H
		5882	53.21	-46.79	100	43.58	32.33	10.67	33.37	190	295	P	H
		5925.6	50.41	-17.79	68.2	40.66	32.4	10.73	33.38	190	295	P	H
	*	5825	111.53	-	-	102.14	32.15	10.59	33.35	148	354	P	V
	*	5825	104.39	-	-	95	32.15	10.59	33.35	148	354	A	V
		5854.6	61.04	-50.67	111.71	51.55	32.22	10.63	33.36	148	354	P	V
		5855.2	56.03	-54.71	110.74	46.54	32.22	10.63	33.36	148	354	P	V
		5887.4	52.43	-43.56	95.99	42.77	32.35	10.68	33.37	148	354	P	V
		5936.4	51.62	-16.58	68.2	41.87	32.4	10.74	33.39	148	354	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	49.79	-24.21	74	58.94	39.98	16.96	66.09	100	0	P	H
		17235	52.21	-15.99	68.2	58.44	40.24	20.36	66.83	100	0	P	H
		17978	60.73	-13.27	74	59.64	49.76	20.73	69.4	100	0	P	H
		17978	50.43	-3.57	54	49.34	49.76	20.73	69.4	100	0	A	H
		11490	49.24	-24.76	74	58.39	39.98	16.96	66.09	100	0	P	V
		17235	50.51	-17.69	68.2	56.74	40.24	20.36	66.83	100	0	P	V
		17978	60	-14	74	58.91	49.76	20.73	69.4	100	0	P	V
		17978	49.87	-4.13	54	48.78	49.76	20.73	69.4	100	0	A	V
802.11n HT20 CH 157 5785MHz		11570	49.9	-24.1	74	59.19	39.72	17.03	66.04	100	0	P	H
		17355	52.7	-15.5	68.2	58.44	41	20.42	67.16	100	0	P	H
		17978	60.65	-13.35	74	59.56	49.76	20.73	69.4	100	0	P	H
		17978	50.43	-3.57	54	49.34	49.76	20.73	69.4	100	0	A	H
		11570	49.21	-24.79	74	58.5	39.72	17.03	66.04	100	0	P	V
		17355	51.39	-16.81	68.2	57.13	41	20.42	67.16	100	0	P	V
		17978	60.41	-13.59	74	59.32	49.76	20.73	69.4	100	0	P	V
		17978	50.21	-3.79	54	49.12	49.76	20.73	69.4	100	0	A	V
802.11n HT20 CH 165 5825MHz		11650	49.5	-24.5	74	59.11	39.3	17.09	66	100	0	P	H
		17475	55.39	-12.81	68.2	60.71	41.7	20.47	67.49	100	0	P	H
		17967	60.73	-13.27	74	59.92	49.44	20.72	69.35	100	0	P	H
		17967	49.93	-4.07	54	49.12	49.44	20.72	69.35	100	0	A	H
		11650	48.85	-25.15	74	58.46	39.3	17.09	66	100	0	P	V
		17475	52.69	-15.51	68.2	58.01	41.7	20.47	67.49	100	0	P	V
		17989	60.49	-13.51	74	59.12	50.08	20.73	69.44	100	0	P	V
		17989	50.26	-3.74	54	48.89	50.08	20.73	69.44	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5644.2	50.3	-17.9	68.2	41.49	31.6	10.5	33.29	298	248	P	H
		5699.6	56.01	-48.9	104.91	47	31.8	10.52	33.31	298	248	P	H
		5717.2	65.87	-44.15	110.02	56.78	31.87	10.53	33.31	298	248	P	H
		5722.4	69.46	-46.81	116.27	60.36	31.89	10.53	33.32	298	248	P	H
	*	5755	111.68	-	-	102.46	32.01	10.54	33.33	298	248	P	H
	*	5755	103.13	-	-	93.91	32.01	10.54	33.33	298	248	A	H
		5850.4	51.44	-69.85	121.29	41.97	32.2	10.63	33.36	298	248	P	H
		5860.8	50.69	-58.48	109.17	41.17	32.24	10.64	33.36	298	248	P	H
		5911	50.97	-27.56	78.53	41.24	32.4	10.71	33.38	298	248	P	H
		5934.8	50.97	-17.23	68.2	41.22	32.4	10.74	33.39	298	248	P	H
		5624.8	49.17	-19.03	68.2	40.36	31.6	10.49	33.28	114	183	P	V
		5698.8	57.71	-46.61	104.32	48.7	31.8	10.52	33.31	114	183	P	V
		5718.2	64.03	-46.27	110.3	54.94	31.87	10.53	33.31	114	183	P	V
		5723	65.94	-51.7	117.64	56.84	31.89	10.53	33.32	114	183	P	V
	*	5755	108.79	-	-	99.57	32.01	10.54	33.33	114	183	P	V
	*	5755	100.97	-	-	91.75	32.01	10.54	33.33	114	183	A	V
		5854.6	49.77	-61.94	111.71	40.28	32.22	10.63	33.36	114	183	P	V
		5874.2	50.61	-54.81	105.42	41.02	32.3	10.66	33.37	114	183	P	V
		5917.4	52.8	-21	73.8	43.06	32.4	10.72	33.38	114	183	P	V
		5948.4	52.08	-16.12	68.2	42.31	32.4	10.76	33.39	114	183	P	V

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5645.6	49.97	-18.23	68.2	41.16	31.6	10.5	33.29	100	302	P	H
		5675	52.32	-34.42	86.74	43.41	31.7	10.51	33.3	100	302	P	H
		5716.6	54.22	-55.63	109.85	45.13	31.87	10.53	33.31	100	302	P	H
		5723.8	54.18	-65.28	119.46	45.07	31.9	10.53	33.32	100	302	P	H
	*	5795	110.45	-	-	101.14	32.09	10.56	33.34	100	302	P	H
	*	5795	102.86	-	-	93.55	32.09	10.56	33.34	100	302	A	H
		5852	54.06	-63.58	117.64	44.58	32.21	10.63	33.36	100	302	P	H
		5856.8	53.96	-56.34	110.3	44.45	32.23	10.64	33.36	100	302	P	H
		5881.6	51.91	-48.39	100.3	42.28	32.33	10.67	33.37	100	302	P	H
		5929.8	52.64	-15.56	68.2	42.89	32.4	10.74	33.39	100	302	P	H
		5648.6	50.54	-17.66	68.2	41.73	31.6	10.5	33.29	200	143	P	V
		5671	50.4	-33.38	83.78	41.51	31.68	10.51	33.3	200	143	P	V
		5719.8	51.39	-59.35	110.74	42.29	31.88	10.53	33.31	200	143	P	V
		5723.6	51.61	-67.4	119.01	42.51	31.89	10.53	33.32	200	143	P	V
	*	5795	108.47	-	-	99.16	32.09	10.56	33.34	200	143	P	V
	*	5795	100.45	-	-	91.14	32.09	10.56	33.34	200	143	A	V
		5851.6	53.02	-65.53	118.55	43.54	32.21	10.63	33.36	200	143	P	V
		5855.2	53.49	-57.25	110.74	44	32.22	10.63	33.36	200	143	P	V
		5921	51.03	-20.12	71.15	41.29	32.4	10.72	33.38	200	143	P	V
		5940.2	51.65	-16.55	68.2	41.89	32.4	10.75	33.39	200	143	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	49.89	-24.11	74	59.03	39.96	16.97	66.07	100	0	P	H
		17265	50.2	-18	68.2	56.39	40.36	20.37	66.92	100	0	P	H
		17978	62.03	-11.97	74	60.94	49.76	20.73	69.4	100	0	P	H
		17978	50.43	-3.57	54	49.34	49.76	20.73	69.4	100	0	A	H
		11510	49.86	-24.14	74	59	39.96	16.97	66.07	100	0	P	V
		17265	50.44	-17.76	68.2	56.63	40.36	20.37	66.92	100	0	P	V
		17967	60.83	-13.17	74	60.02	49.44	20.72	69.35	100	0	P	V
		17967	49.96	-4.04	54	49.15	49.44	20.72	69.35	100	0	A	V
802.11n HT40 CH 159 5795MHz		11590	49.26	-24.74	74	58.6	39.64	17.05	66.03	100	0	P	H
		17385	51.43	-16.77	68.2	56.98	41.26	20.43	67.24	100	0	P	H
		17967	60.85	-13.15	74	60.04	49.44	20.72	69.35	100	0	P	H
		17967	50.44	-3.56	54	49.63	49.44	20.72	69.35	100	0	A	H
		11590	49.51	-24.49	74	58.85	39.64	17.05	66.03	100	0	P	V
		17385	51.24	-16.96	68.2	56.79	41.26	20.43	67.24	100	0	P	V
		17978	60.58	-13.42	74	59.49	49.76	20.73	69.4	100	0	P	V
		17978	50.33	-3.67	54	49.24	49.76	20.73	69.4	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5647.8	50.87	-17.33	68.2	42.06	31.6	10.5	33.29	308	244	P	H
		5698.8	60.32	-44	104.32	51.31	31.8	10.52	33.31	308	244	P	H
		5719.2	65.19	-45.39	110.58	56.09	31.88	10.53	33.31	308	244	P	H
		5723.8	64.58	-54.88	119.46	55.47	31.9	10.53	33.32	308	244	P	H
	*	5775	107.17	-	-	97.9	32.05	10.55	33.33	308	244	P	H
	*	5775	98.8	-	-	89.53	32.05	10.55	33.33	308	244	A	H
		5850.8	54.88	-65.5	120.38	45.41	32.2	10.63	33.36	308	244	P	H
		5856	55.13	-55.39	110.52	45.63	32.22	10.64	33.36	308	244	P	H
		5890	51.47	-42.6	94.07	41.8	32.36	10.68	33.37	308	244	P	H
		5942.8	50.42	-17.78	68.2	40.66	32.4	10.75	33.39	308	244	P	H
		5638.2	49.83	-18.37	68.2	41.02	31.6	10.5	33.29	400	162	P	V
		5697.2	58.55	-44.59	103.14	49.55	31.79	10.52	33.31	400	162	P	V
		5716.2	61.88	-47.86	109.74	52.8	31.86	10.53	33.31	400	162	P	V
		5722	62.08	-53.28	115.36	52.98	31.89	10.53	33.32	400	162	P	V
	*	5775	103.78	-	-	94.51	32.05	10.55	33.33	400	162	P	V
	*	5775	95.91	-	-	86.64	32.05	10.55	33.33	400	162	A	V
		5852.2	52.45	-64.73	117.18	42.97	32.21	10.63	33.36	400	162	P	V
		5858.4	52.58	-57.27	109.85	43.07	32.23	10.64	33.36	400	162	P	V
		5899.8	51.77	-35.04	86.81	42.06	32.4	10.69	33.38	400	162	P	V
		5948.2	51.82	-16.38	68.2	42.05	32.4	10.76	33.39	400	162	P	V

Remark

1. No other spurious found.
2. All results are PASS against Peak and Average limit line.

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	49.68	-24.32	74	58.92	39.8	17.01	66.05	100	0	P	H
		17325	50.86	-17.34	68.2	56.82	40.72	20.4	67.08	100	0	P	H
		17967	60.19	-13.81	74	59.38	49.44	20.72	69.35	100	0	P	H
		17967	50.04	-3.96	54	49.23	49.44	20.72	69.35	100	0	A	H
		11550	49.33	-24.67	74	58.57	39.8	17.01	66.05	100	0	P	V
		17325	50.7	-17.5	68.2	56.66	40.72	20.4	67.08	100	0	P	V
		17967	59.73	-14.27	74	58.92	49.44	20.72	69.35	100	0	P	V
		17967	49.59	-4.41	54	48.78	49.44	20.72	69.35	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission above 18GHz

WIFI 802.11a (SHF @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz SHF		22972	45.31	-28.69	74	47.54	38.91	12.37	53.51	150	0	P	H
		22972	45.33	-28.67	74	47.56	38.91	12.37	53.51	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line. 3. Super High Frequency (SHF)												

Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a LF		30	26.13	-13.87	40	30.5	24.46	0.81	29.64	-	-	P	H
		131.85	30.06	-13.44	43.5	40.46	17.52	1.7	29.62	-	-	P	H
		576.11	35.57	-10.43	46	34.72	26.15	3.56	28.86	-	-	P	H
		746.83	35.94	-10.06	46	32.14	28.29	4.12	28.61	-	-	P	H
		925.31	36.96	-9.04	46	30.85	29.64	4.63	28.16	100	0	P	H
		989.33	37.94	-16.06	54	30.75	30.41	4.83	28.05	-	-	P	H
		30	31.34	-8.66	40	35.71	24.46	0.81	29.64	-	-	P	V
		112.45	31.58	-11.92	43.5	42.57	17.06	1.58	29.63	-	-	P	V
		264.74	25.37	-20.63	46	32.6	19.74	2.4	29.37	-	-	P	V
		455.83	30.59	-15.41	46	33.14	23.37	3.17	29.09	-	-	P	V
		576.11	34.25	-11.75	46	33.4	26.15	3.56	28.86	-	-	P	V
		903.97	38.97	-7.03	46	33.49	29.08	4.59	28.19	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Jack Cheng, Lance Chiang and Chuan Chu	Temperature :	23.8~26.2°C
		Relative Humidity :	56.5~68.6%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Vertical	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Vertical	Fundamental
Peak		

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Vertical	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Vertical	Fundamental
Peak		

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak		
Peak		Left blank

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNII) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank

Band 4 - 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.		

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNII) 3m HORN_9120D_1328 HORIZONTAL	 Site : 03CH12-HY Condition : PEAK(UNII) 3m HORN_9120D_1328 VERTICAL

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.		

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNII) 3m HORN_9120D_1328 HORIZONTAL	 Site : 03CH12-HY Condition : PEAK(UNII) 3m HORN_9120D_1328 VERTICAL

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Vertical
Peak Avg.		

Emission above 18GHz

5GHz WIFI 802.11a (SHF)

WIFI	5GHz WIFI	
ANT	802.11a CH165 Super High Frequency (SHF)	
1+2	Horizontal	Vertical
Peak Avg.		

Emission below 1GHz

5GHz WIFI 802.11a (LF)

WIFI	5GHz WIFI	
ANT	802.11a LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m BILO6_6111D_37059 HORIZONTAL	 Site : 03CH12-HY Condition : QP 3m BILO6_6111D_37059 VERTICAL

Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1+2	5GHz 802.11a	100.00	-	-	10Hz	0.00
1+2	5GHz 802.11n HT20	100.00	-	-	10Hz	0.00
1+2	5GHz 802.11n HT40	100.00	-	-	10Hz	0.00
1+2	5GHz 802.11ac VHT80	100.00	-	-	10Hz	0.00

MIMO <Ant. 1+2>

5GHz 802.11a



5GHz 802.11n HT20



5GHz 802.11n HT40



5GHz 802.11ac VHT80



———THE END———