

## 14 RF Exposure

### General SAR test reduction & exclusion guidance

#### KDB 447498

#### Section 4.3 General SAR test reduction and exclusion guidance

For Standalone SAR exclusion consideration, when SAR Exclusion Threshold requirement in KDB 447498 is satisfied, standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

The SAR Test Exclusion Threshold for frequencies in the range 100 MHz to 6 GHz, and for test separation distance of  $\leq 50$  mm, is determined as follows.

$$\text{SAR Exclusion Threshold (SARET)} = (\text{NT} \times \text{TSD}_A) / \sqrt{f_{\text{GHz}}}$$

Where,

NT = Numeric Threshold (3.0 for 1-g SAR and 7.5 for 10-g SAR)

TSD<sub>A</sub> = Minimum Test separation distance or 50 mm (whichever is lower)

f<sub>GHz</sub> = Transmit frequency in GHz

| <i>Channel Frequency<br/>(MHz)</i> | <i>Maximum<br/>Conducted Power<br/>(mW)</i> | <i>SAR Exclusion<br/>Threshold at 10 mm<br/>(mW)</i> | <i>SAR Evaluation</i> |
|------------------------------------|---------------------------------------------|------------------------------------------------------|-----------------------|
| 915                                | 15.7                                        | 31.4                                                 | Not Required          |

Therefore standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.