RF MEASUREMENT REPORT

FCC ID	:	2AXJ4AX80
Applicant	:	TP-Link Corporation Limited
Application Type	:	Certification
Product	:	AX6000 8-Stream Wi-Fi 6 Router
Model No.	:	Archer AX80
Brand Name	:	tp-link
FCC Classification	:	Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s)	:	Part15 Subpart E (Section 15.407)
Received Date	:	June 28 ,2022
Test Date	:	July 7~28 ,2022

Test By : Owen Tsai
(Owen Tsai)

Reviewed By : Paddy Chen
(Paddy Chen)

Approved By : Chenz Ker
(Chenz Ker)

Testing Laboratory
3261

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v02r01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2206TW0119-U2	V1.0	Original Report	2022-08-31	Valid

CONTENTS

Description Page

General Information **6**

1. INTRODUCTION **7**

1.1. Scope 7
1.2. MRT Test Location 7

2. PRODUCT INFORMATION **8**

2.1. Equipment Description 8
2.2. Product Specification Subjective to this Report 8
2.3. Working Frequencies for this report 9
2.4. Description of Available Antennas 10
2.5. Test Mode 11
2.6. Configuration of Test System 12
2.7. Test System Details 13
2.8. Description of Test Software 13
2.9. Applied Standards 13
2.10. Duty Cycle 14
2.11. Test Configuration 16
2.12. EMI Suppression Device(s)/Modifications 16
2.13. Labeling Requirements 16

3. DESCRIPTION OF TEST **17**

3.1. Evaluation Procedure 17
3.2. AC Line Conducted Emissions 17
3.3. Radiated Emissions 18

4. ANTENNA REQUIREMENTS **19**

5. TEST EQUIPMENT CALIBRATION DATE **20**

6. MEASUREMENT UNCERTAINTY **21**

7. TEST RESULT **22**

7.1. Summary 22
7.2. 26dB Bandwidth Measurement 23
7.2.1. Test Limit 23
7.2.2. Test Procedure used 23
7.2.3. Test Setting 23
7.2.4. Test Setup 24
7.2.5. Test Result 25

7.3. 6dB Bandwidth Measurement 40
7.3.1. Test Limit 40
7.3.2. Test Procedure used 40
7.3.3. Test Setting 40
7.3.4. Test Setup 40
7.3.5. TestResult 41
7.4. Output Power Measurement 45
7.4.1. Test Limit 45
7.4.2. Test Procedure Used 45
7.4.3. Test Setting 45
7.4.4. Test Setup 45
7.4.5. Test Result 46
7.5. Transmit Power Control 52
7.5.1. Test Limit 52
7.5.2. Test Procedure Used 52
7.5.3. Test Setting 52
7.5.4. Test Setup 52
7.5.5. Test Result 52
7.6. Power Spectral Density Measurement 53
7.6.1. Test Limit 53
7.6.2. Test Procedure Used 53
7.6.3. Test Setting 53
7.6.4. Test Setup 54
7.6.5. Test Result 55
7.7. Radiated Spurious Emission Measurement 107
7.7.1. Test Limit 107
7.7.2. Test Procedure Used 107
7.7.3. Test Setting 107
7.7.4. Test Setup 109
7.7.5. Test Result 110
7.8. Radiated Restricted Band Edge Measurement 264
7.8.1. Test Limit 264
7.8.2. Test Procedure Used 265
7.8.3. Test Setting 265
7.8.4. Test Setup 266
7.8.5. Test Result 267
7.9. AC Conducted Emissions Measurement 401
7.9.1. Test Limit 401
7.9.2. Test Procedure 401

7.9.3. Test Setup 402
7.9.4. Test Result..... 403

8. CONCLUSION..... 407

Appendix A : Test Setup Photograph 408

Appendix B : External Photograph..... 409

Appendix C : Internal Photograph 410

General Information

Applicant	TP-Link Corporation Limited
Applicant Address	Room 901, 9/F., New East Ocean Centre, 9 Science Museum Road, Tsim Sha Tsui, Kowloon, Hongkong
Manufacturer	TP-Link Corporation Limited
Manufacturer Address	Room 901, 9/F., New East Ocean Centre, 9 Science Museum Road, Tsim Sha Tsui, Kowloon, Hongkong
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.407

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.

1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	AX6000 8-Stream Wi-Fi 6 Router
Model No.:	Archer AX80
Brand Name:	tp-link
Wi-Fi Specification:	802.11a/b/g/n/ac/ax
EUT Identification No.:	#1-1 (Conducted) #1-2 (Radiated)
Adapter	BRAND: MASS POWER MODEL: S042-1A120330VU INPUT: 100 - 240V ~ 50/60Hz 1.0A OUTPUT: DC 12.0V 3.3A

2.2. Product Specification Subjective to this Report

Frequency Range:	For 802.11a/n-HT20/ac-VHT20/ax-HE20: 5180~5240MHz, 5260~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40: 5190~5230MHz, 5270~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80: 5210MHz, 5290MHz, 5530MHz, 5610 MHz, 5690MHz, 5775MHz For 802.11ac-VHT160/ax-HE160: 5250MHz, 5570MHz
Type of Modulation:	802.11a/n/ac: OFDM 802.11ax: OFDMA
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps 802.11ac: up to 3466.7Mbps 802.11ax: up to 4804Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11a/n-HT20/ac-VHT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

802.11ac-VHT160/ax-HE160

Channel	Frequency	Channel	Frequency	Channel	Frequency
50	5250MHz	114	5570 MHz	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	T_X Paths	Max Antenna Gain (dBi)	Beamforming Directional Gain (dBi)	CDD Directional Gain (dBi)	
					For Power	For PSD
Dipole Antenna	2412 ~ 2462	4	1.97	7.99	1.97	7.99
	5150 ~ 5250	4	3.00	9.02	3.00	9.02
	5250 ~ 5350	4	2.43	8.45	2.43	8.45
	5470 ~ 5725	4	2.89	8.91	2.89	8.91
	5725 ~ 5850	4	2.96	8.98	2.96	8.98

Remark:

1. The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

   If all antennas have the same gain, G_{ANT}, Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

   - For power spectral density (PSD) measurements on all devices,

   Array Gain = 10 log(N_{ANT}/ N_{SS}) dB;

   - For power measurements on IEEE 802.11 devices,

   Array Gain = 0 dB for $N_{ANT} \leq 4$;

2. The EUT also supports Beam Forming mode, and the Beam Forming support 802.11ac/ax, not include 802.11a/b/g/n. BF Directional gain = G_{ANT} + 10 log (N_{ANT}).
3. All messages of antenna were declared by manufacturer.

Test Mode	T_X Paths	CDD Mode	Beamforming Mode
802.11b/g/n (DTS)	4	√	X
802.11ax (DTS)	4	√	√
802.11a/n (NII)	4	√	X
802.11ac/ax (NII)	4	√	√

2.5. Test Mode

CDD Mode
Mode 1: Transmit by 802.11a_Nss=1 (6Mbps) (CDD mode)
Mode 2: Transmit by 802.11ac-VHT20_Nss=1 (MCS0) (CDD mode)
Mode 3: Transmit by 802.11ac-VHT40_Nss=1 (MCS0) (CDD mode)
Mode 4: Transmit by 802.11ac-VHT80_Nss=1 (MCS0) (CDD mode)
Mode 5: Transmit by 802.11ac-VHT160_Nss=1 (MCS0) (CDD mode)
Mode 6: Transmit by 802.11ax-HE20_Nss=1 (MCS0) (CDD mode)
Mode 7: Transmit by 802.11ax-HE40_Nss=1 (MCS0) (CDD mode)
Mode 8: Transmit by 802.11ax-HE80_Nss=1 (MCS0) (CDD mode)
Mode 9: Transmit by 802.11ax-HE160_Nss=1 (MCS0) (CDD mode)
Beamforming Mode
Mode 10: Transmit by 802.11ac-VHT20_Nss=1 (MCS0) (Beam-Forming mode)
Mode 11: Transmit by 802.11ac-VHT40_Nss=1 (MCS0) (Beam-Forming mode)
Mode 12: Transmit by 802.11ac-VHT80_Nss=1 (MCS0) (Beam-Forming mode)
Mode 13: Transmit by 802.11ac-VHT160_Nss=1 (MCS0) (Beam-Forming mode)
Mode 14: Transmit by 802.11ax-HE20_Nss=1 (MCS0) (Beam-Forming mode)
Mode 15: Transmit by 802.11ax-HE40_Nss=1 (MCS0) (Beam-Forming mode)
Mode 16: Transmit by 802.11ax-HE80_Nss=1 (MCS0) (Beam-Forming mode)
Mode 17: Transmit by 802.11ax-HE160_Nss=1 (MCS0) (Beam-Forming mode)
Remark: 1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. This device supports 4 N_{SS} and power level of 4 NSS is less than or equal to the power of 1 N_{SS}. The worst case is N_{SS}=1. 3. Due to the same modulation between 802.11n and 802.11ac, so 802.11n-HT20 and HT40 are covered by 802.11ac-VHT20 and VHT40 in this report, meanwhile, power level for 802.11n-HT20 and HT40 will not be greater than 802.11ac-VHT20 and VHT40. 4. Due to CDD mode was the worst mode, so all test items were evaluated in this report. The beamforming mode only evaluated the RF output power. 5. EUT supports one configuration only in 802.11ax full RU mode.

2.6. Configuration of Test System

The device was tested per the guidance ANSI C63.10: 2013was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram



Signal Cable Type		Signal Cable Description
A	LAN Cable	Non-Shielded, 10.0m

2.7. Test System Details

N/A

2.8. Description of Test Software

The test utility software used during testing was “QATool”, the version is ver0.0.2.88.

Note: Final power setting please refer to operational description.

2.9. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 789033 D02v02r01,
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.10. Duty Cycle

5GHz (NII) operation is possible in 20MHz, 40MHz, 80MHz and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
802.11a	96.90%
802.11ac-VHT20	96.06%
802.11ac-VHT40	91.69%
802.11ac-VHT80	85.07%
802.11ac-VHT160	76.45%
802.11ax-HE20	84.72%
802.11ax-HE40	84.86%
802.11ax-HE80	84.85%
802.11ax-HE160	85.29%

Duty Cycle (T = Transmission Duration)

802.11a



802.11ac-VHT20



802.11ac-VHT40



802.11ac-VHT80



Duty Cycle (T = Transmission Duration)	
802.11ac-VHT160	802.11ax-HE20
	
802.11ax-HE40	802.11ax-HE80
	
802.11ax-HE160	
	

2.11. Test Configuration

The device was tested per the guidance of KDB 789033 D02v02r01.ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.12. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.13. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 789033 D02v02r01 were used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2023/3/7
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2023/4/20
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2023/5/9
Temperature/Humidity Meter	TFA	35.1078.10.IT	MRTTWA00050	1 year	2023/6/16

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2022/10/4
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2023/3/9
Acitve Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2023/5/24
Broadband Horn antenna	RFSPIN	DRH18-E	MRTTWA00087	1 year	2022/8/31
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2023/3/29
Broadband Preamplifier	EMC Instruments corporation	EMC118A45SE	MRTTWA00088	1 year	2022/8/31
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2023/3/30
Cable	HUBERSUHNER	SF106	MRTTWE00034	1 year	2023/6/27

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2023/4/20
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2022/10/18
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2023/7/19
Attenuator	WTI	218FS-20	MRTTWE00026	1 year	2022/11/18
Attenuator	WTI	218FS-10	MRTTWE00027	1 year	2023/6/15
Temperature & Humidity Chamber	TEN BILLION	TTH-B3UP	MRTTWA00036	1 year	2023/6/14
DIVA PLUS Funk-Wetterstation	TFA	35.1083	MRTTWA00050	1 year	2023/06/16

Software	**Version**	**Function**
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 150kHz~30MHz: ± 2.53dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 9kHz ~ 1GHz: ± 4.25dB 1GHz ~ 40GHz: ± 4.45dB
Conducted Power (Carrier Power / Power Density)
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ± 0.84dB
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):± 2.65 dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ± 3.3%
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ±0.82°C/ ±3%
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): ±78.4Hz

7. TEST RESULT

7.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section7.2
15.407(e)	6dB Bandwidth	≥ 500kHz		Pass	Section 7.3
15.407(a)(1)(ii), (2), (3)	Maximum Conducted Output Power	Refer to section 7.4		Pass	Section 7.4
15.407(h)(1)	Transmit Power Control	≤ 24 dBm		Pass	Section 7.5
15.407(a)(1)(ii), (2), (3), (12)	Peak Power Spectral Density	Refer to section 7.6		Pass	Section 7.6
15.407(g)	Frequency Stability	± 20 ppm		Pass	Section 7.7
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Refer to Section 7.8	Radiated	Pass	Section 7.8& 7.9
15.205, 15.209 15.407(b)(7), (8), (9)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in15.209		Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.10

Notes:

1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part ofthe system to connect the EUT to the analyzer at all frequencies of interest.
3) Output power test was verified over all data rates of each mode (data refers to operational description), and then choose the maximum power output (low data rate) for final test of each channel.
4) For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

7.2. 26dB Bandwidth Measurement

7.2.1.Test Limit

N/A

7.2.2.Test Procedure used

KDB 789033 D02v02r01- Section II)C)1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

7.2.3.Test Setting

26dB Bandwidth

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth
2. RBW = approximately 1% of the emission bandwidth.
3. VBW > RBW
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

99% Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 1% to 5% of the OBW
3. VBW ≥ 3 × RBW
4. Span = 1.5 times to 5 times the OBW
5. Detector = peak
6. Trace mode = max hold
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument.

7.2.4.Test Setup



7.2.5.Test Result

Product	AX6000 8-Stream Wi-Fi 6 Router	Test Engineer	Jay
Test Site	SR5	Test Date	2022/7/21~2022/7/25

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11a	6Mbps	36	5180	20.410	16.393
802.11a	6Mbps	44	5220	19.250	16.338
802.11a	6Mbps	48	5240	19.100	16.371
802.11a	6Mbps	52	5260	19.560	16.332
802.11a	6Mbps	60	5300	21.640	16.381
802.11a	6Mbps	64	5320	21.300	16.446
802.11a	6Mbps	100	5500	19.760	16.421
802.11a	6Mbps	116	5580	19.270	16.364
802.11a	6Mbps	140	5700	19.470	16.377
802.11a	6Mbps	144	5720	20.260	16.352
802.11a	6Mbps	149	5745	19.570	16.379
802.11a	6Mbps	157	5785	20.810	16.424
802.11a	6Mbps	165	5825	21.950	16.462
802.11ac-VHT20	MCS0	36	5180	21.130	17.618
802.11ac-VHT20	MCS0	44	5220	20.640	17.592
802.11ac-VHT20	MCS0	48	5240	19.200	17.598
802.11ac-VHT20	MCS0	52	5260	20.540	17.606
802.11ac-VHT20	MCS0	60	5300	21.450	17.625
802.11ac-VHT20	MCS0	64	5320	21.910	17.619
802.11ac-VHT20	MCS0	100	5500	21.580	17.614
802.11ac-VHT20	MCS0	116	5580	20.540	17.578
802.11ac-VHT20	MCS0	140	5700	21.040	17.618
802.11ac-VHT20	MCS0	144	5720	20.340	17.565
802.11ac-VHT20	MCS0	149	5745	23.790	17.660
802.11ac-VHT20	MCS0	157	5785	22.120	17.672
802.11ac-VHT20	MCS0	165	5825	21.350	17.674

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11ac-VHT40	MCS0	38	5190	39.670	35.889
802.11ac-VHT40	MCS0	46	5230	39.420	35.886
802.11ac-VHT40	MCS0	54	5270	39.090	35.808
802.11ac-VHT40	MCS0	62	5310	39.590	35.841
802.11ac-VHT40	MCS0	102	5510	39.880	35.936
802.11ac-VHT40	MCS0	110	5550	39.510	35.782
802.11ac-VHT40	MCS0	134	5670	40.360	35.921
802.11ac-VHT40	MCS0	142	5710	39.490	35.805
802.11ac-VHT40	MCS0	151	5755	45.370	35.896
802.11ac-VHT40	MCS0	159	5795	46.290	35.994
802.11ac-VHT80	MCS0	42	5210	79.020	75.130
802.11ac-VHT80	MCS0	58	5290	85.560	75.148
802.11ac-VHT80	MCS0	106	5530	84.850	75.002
802.11ac-VHT80	MCS0	122	5610	79.000	74.818
802.11ac-VHT80	MCS0	138	5690	78.820	75.052
802.11ac-VHT80	MCS0	155	5775	81.400	75.121
802.11ac-VHT160	MCS0	50	5250	160.400	153.790
802.11ac-VHT160	MCS0	114	5570	160.300	153.450
802.11ax-HE20	MCS0	36	5180	20.890	18.869
802.11ax-HE20	MCS0	44	5220	20.980	18.843
802.11ax-HE20	MCS0	48	5240	19.720	18.836
802.11ax-HE20	MCS0	52	5260	20.560	18.816
802.11ax-HE20	MCS0	60	5300	20.740	18.852
802.11ax-HE20	MCS0	64	5320	21.220	18.877
802.11ax-HE20	MCS0	100	5500	20.950	18.850
802.11ax-HE20	MCS0	116	5580	20.810	18.830
802.11ax-HE20	MCS0	140	5700	21.230	18.843
802.11ax-HE20	MCS0	144	5720	20.720	18.903
802.11ax-HE20	MCS0	149	5745	20.720	18.877
802.11ax-HE20	MCS0	157	5785	21.640	18.852
802.11ax-HE20	MCS0	165	5825	21.770	18.923

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
Ant 0					
802.11ax-HE40	MCS0	38	5190	39.190	37.430
802.11ax-HE40	MCS0	46	5230	39.400	37.351
802.11ax-HE40	MCS0	54	5270	39.220	37.447
802.11ax-HE40	MCS0	62	5310	39.340	37.544
802.11ax-HE40	MCS0	102	5510	39.310	37.402
802.11ax-HE40	MCS0	110	5550	39.110	37.457
802.11ax-HE40	MCS0	134	5670	39.300	37.396
802.11ax-HE40	MCS0	142	5710	39.230	37.499
802.11ax-HE40	MCS0	151	5755	39.160	37.436
802.11ax-HE40	MCS0	159	5795	39.410	37.487
802.11ax-HE80	MCS0	42	5210	79.870	76.762
802.11ax-HE80	MCS0	58	5290	79.710	76.652
802.11ax-HE80	MCS0	106	5530	79.740	76.560
802.11ax-HE80	MCS0	122	5610	79.710	76.315
802.11ax-HE80	MCS0	138	5690	79.840	76.414
802.11ax-HE80	MCS0	155	5775	81.130	76.757
802.11ax-HE160	MCS0	50	5250	161.200	155.150
802.11ax-HE160	MCS0	114	5570	161.300	155.300

802.11a 26dB Bandwidth & 99% Bandwidth

Channel 36 (5180MHz)



Channel 44 (5220MHz)

Channel 48 (5240MHz)

Channel 52 (5260MHz)



Channel 60 (5300MHz)



Channel 64 (5320MHz)

Channel 100 (5500MHz)



Channel 116 (5580MHz)



Channel 140 (5700MHz)



Channel 144 (5720MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)



Channel 165 (5825MHz)



802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth

Channel 36 (5180MHz)



Channel 44 (5220MHz)

Channel 48 (5240MHz)



Channel 52 (5260MHz)



Channel 60 (5300MHz)

Channel 64 (5320MHz)



Channel 100 (5500MHz)

Channel 116 (5580MHz)



Channel 140 (5700MHz)



Channel 144 (5720MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)



Channel 165 (5825MHz)



802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth

Channel 38 (5190MHz)

Channel 46 (5230MHz)

Channel 54 (5270MHz)



Channel 62 (5310MHz)

Channel 102 (5510MHz)

Channel 110 (5550MHz)



Channel 134 (5670MHz)



Channel 142 (5710MHz)



Channel 151 (5755MHz)	Channel 159 (5795MHz)
	

802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth

Channel 42 (5210MHz)

Channel 58 (5290MHz)

Channel 106 (5530MHz)



Channel 122 (5610MHz)



Channel 138 (5690MHz)



Channel 155 (5775MHz)



802.11ac-VHT160 26dB Bandwidth & 99% Bandwidth

Channel 50 (5250MHz)



Channel 114 (5570MHz)



802.11ax-HE20 26dB Bandwidth & 99% Bandwidth

Channel 36 (5180MHz)

Channel 44 (5220MHz)

Channel 48 (5240MHz)



Channel 52 (5260MHz)

Channel 60 (5300MHz)



Channel 64 (5320MHz)

Channel 100 (5500MHz)



Channel 116 (5580MHz)



Channel 140 (5700MHz)



Channel 144 (5720MHz)



Channel 149 (5745MHz)



Channel 144 (5785MHz)



Channel 144 (5825MHz)



802.11ax-HE40 26dB Bandwidth & 99% Bandwidth

Channel 38 (5190MHz)

Channel 46 (5230MHz)



Channel 54 (5270MHz)



Channel 62 (5310MHz)

Channel 102 (5510MHz)



Channel 110 (5550MHz)



Channel 134 (5670MHz)



Channel 142 (5710MHz)



Channel 151 (5755MHz)	Channel 159 (5795MHz)