



User Guide

EAP Controller Software

CONTENTS

1 Quick Start	1
1.1 Determine the Network Topology	2
1.1.1 Management in the Same Subnet	2
1.1.2 Management in Different Subnets	3
1.2 Install the EAP Controller	3
1.2.1 Installation on Windows Host	3
1.2.2 Installation on Linux Host	4
1.3 Inform the EAPs of the Controller Host's Address	5
1.4 Start and Log in to the EAP Controller	6
1.4.1 Launch the EAP Controller	6
1.4.2 Do the Basic Configurations	7
1.4.3 Log in to the Management Interface	9
1.5 Create Sites and Adopt EAPs	9
1.5.1 Create Sites	9
1.5.2 Adopt the EAPs	10
1.6 Monitor and Manage the EAPs	11
2 Monitor and Manage the Network	12
2.1 Monitor the Network with the Map	13
2.1.1 Add a Map	13
2.1.2 Monitor the EAPs on the Map	15
2.2 View the Statistics of the Network	16
2.2.1 View the Client Distribution on SSID	16
2.2.2 Have a Quick Look at EAPs and Clients	16
2.2.3 View Current Usage-Top EAPs	17
2.2.4 View Recent Activities	17
2.3 Monitor and Manage the EAPs	18
2.3.1 Manage the EAPs in Different Status	18

2.3.2	View the Detailed Information of EAPs.....	19
2.3.3	Manage the EAPs in the Action Column	19
2.4	Monitor and Manage Clients	20
2.4.1	View the Current Information of Clients	20
2.4.2	Manage Clients in the Action Column.....	20
2.5	View Clients Statistics During the Specified Period	21
2.5.1	Select a Specified Period	21
2.5.2	View the History Information of Clients	21
2.5.3	Manage Clients in the Action Column.....	22
2.6	Manage the Rogue APs List	22
2.6.1	Manage the Untrusted Rogue APs List	22
2.6.2	Manage the Trusted Rogue APs List.....	23
2.7	View Past Guest Authorization.....	24
2.8	View Logs.....	24
2.9	View Alerts.....	25
3	Configure the EAPs Globally	26
3.1	Wireless Network.....	27
3.1.1	Add Wireless Networks	27
3.1.2	Configure Advanced Wireless Parameters	32
3.1.3	Configure Band Steering	33
3.2	Access Control	34
3.3	Portal Authentication.....	35
3.3.1	No Authentication.....	36
3.3.2	Simple Password	40
3.3.3	Local User.....	43
3.3.4	Voucher.....	50
3.3.5	SMS.....	57
3.3.6	Facebook.....	61
3.3.7	External RADIUS Server	62

3.3.8	External Portal Server	66
3.4	Free Authentication Policy	67
3.5	MAC Filter	67
3.6	Scheduler	69
3.7	QoS.....	71
3.8	System	74
3.8.1	Reboot Schedule	74
3.8.2	Log Setting.....	74
3.8.3	Device Account.....	76
3.8.4	LED.....	76
3.8.5	SSH	77
3.8.6	Management VLAN.....	77
3.8.7	Backup&Restore	78
3.8.8	Batch Upgrade.....	78

4 Configure the EAPs Separately 79

4.1	View the Information of the EAP	80
4.1.1	Overview	80
4.1.2	LAN.....	80
4.1.3	Radio.....	81
4.2	View Clients Connecting to the EAP	81
4.2.1	User.....	81
4.2.2	Guest	82
4.3	Configure the EAP	82
4.3.1	Basic Config.....	82
4.3.2	IP Setting.....	83
4.3.3	Radio.....	83
4.3.4	Load Balance.....	85
4.3.5	WLANs	85
4.3.6	Trunk Settings.....	86

4.3.7	Rouge AP Detection	86
4.3.8	Forget this AP	87
4.3.9	Local LAN Port VLAN Settings	87
5	Manage the EAP Controller	88
5.1	Information About the Software	89
5.2	User Account	89
5.3	Controller Settings	90
5.3.1	Configure Controller Hostname/IP	90
5.3.2	Configure Mail Server	90
6	Application Example	92
6.1	Basic Configuration	93
6.2	Advanced Settings	93
6.2.1	Monitor the EAPs with Map	93
6.2.2	Configure Portal Authentication	94
6.2.3	Create a SSID for the Employees	95
6.2.4	Configure Scheduler	96

1 Quick Start

The EAP Controller is a management software for the TP-Link EAP devices. It allows you to centrally manage your EAP devices using a web browser. You can configure EAPs in batches and conduct real-time monitoring of each EAP in the network.

Follow the steps below to complete the basic settings of the EAP Controller.

- 1. Determine the Network Topology*
- 2. Install the EAP Controller*
- 3. Inform the EAPs of the Controller Host's Address*
- 4. Start and Log in to the EAP Controller*
- 5. Create Sites and Adopt the EAPs*
- 6. Monitor and Manage the EAPs*

1.1 Determine the Network Topology

There are two kinds of network topologies to centrally manage EAPs via the EAP Controller:


- The EAP Controller and EAPs are in the same subnet.
- The EAP Controller and EAPs are in different subnets.

Determine your management method according to your need and refer to the following introductions to build your network topology.

1.1.1 Management in the Same Subnet

If your EAP Controller and EAPs are in the same subnet, refer to the following network topology.

A router acts as a DHCP server to assign IP addresses to EAPs and clients. EAP Controller should be installed on one host, which is called as Controller Host. The other hosts in the same LAN can access the Controller Host to manage the network. Taking the following topology as an example, you can enter "192.168.0.100:8043" in a web browser on Host B to visit the EAP Controller interface on Host A. It's recommended to set a static IP address to the Controller Host for the convenient login to the EAP Controller interface.




Note:

- The EAP Controller must be running all the time when you manage the network.
- The EAP Controller can be running on only one host in a LAN. When other users in the LAN try to launch EAP Controller on their own hosts, they will be redirected to the host that is already running EAP Controller.

1.1.2 Management in Different Subnets

If your EAP Controller and EAPs are in different subnets, refer to the following topology.

A router acts as the gateway of the network. A layer 3 switch acts as a DHCP server to assign IP addresses to EAPs and clients. The Controller Host and the EAPs are connected to the switch's different network segments. To help the EAPs find the Controller Host, EAP Discover Utility should be installed on Host B which is in the same subnet with the EAPs. For how to use EAP Discovery Utility, refer to [1.3 Inform the EAPs the Controller Host's Address](#) for detailed instructions.



1.2 Install the EAP Controller

We provide EAP Controller for both Windows and Linux operating systems. Determine your operation system and follow the introductions below to install EAP Controller.

1.2.1 Installation on Windows Host

Make sure your PC meets the following system requirements and then properly install the EAP Controller software.

System Requirements

Operating System: Microsoft Windows XP/Vista/7/8/10.

Web Browser: Mozilla Firefox 32 (or above), Google Chrome 37 (or above), Opera 24 (or above), or Microsoft Internet Explorer 11 (or above).

Note:

We recommend that you deploy the EAP controller on a 64-bit operating system to guarantee the software stability.

Install the EAP Controller

Download the installation file of EAP Controller from the website <http://www.tp-link.com/en/download/EAP-Controller.html>. Then follow the instructions to properly install the EAP Controller software. After successful installation, a shortcut icon  of the EAP Controller will be created on your desktop.

1.2.2 Installation on Linux Host

Make sure your PC meets the following system requirements and then install the EAP Controller software.

System Requirements

Operating System: 64-bit Linux operating system, including Ubuntu 14.04/16.04/17.04, CentOS 6.x/7.x and Fedora 20 (or above).

Web Browser: Mozilla Firefox 32 (or above), Google Chrome 37 (or above), Opera 24 (or above), or Microsoft Internet Explorer 11 (or above).

Install the EAP Controller

Download the installation file of EAP Controller from our website <http://www.tp-link.com/en/download/EAP-Controller.html>.

Follow the steps below to install EAP Controller on your Linux PC:

1. Make sure your PC is running in root mode. You can use this command to enter root mode:

```
sudo
```

2. Extract the tar.gz file using the command:

```
tar zxvf EAP_Controller_v2.5.3_linux_x64.tar.gz
```

3. Install EAP Controller using the command:

```
sudo ./install.sh
```

Tips:

- To uninstall EAP Controller, go to the installation path: /opt/tplink/EAPController, and run the command: `sudo ./uninstall.sh`.
- During uninstallation, you can choose whether to backup the database. The backup folder is /opt/tplink/eap_db_backup.
- During installation, you will be asked whether to restore the database if there is any backup database in the folder /opt/tplink/eap_db_backup.

1.3 Inform the EAPs of the Controller Host's Address

If your Controller Host and EAPs are in the same network segment, you can skip this section.

If your Controller Host and EAPs are in different subnets, you need to install EAP Discovery Utility on a host that is in the same network segment with the EAPs. EAP Discovery Utility can help the EAPs find the Controller Host.

System Requirements


WinXP/Vista/7/8/8.1/10/Server2008/Server2012

Mac OS X 10.7/10.8/10.9/10.10/10.11


Install and Use EAP Discovery Utility

Follow the steps below to install EAP Discovery Utility and use it to inform the EAPs of the Controller host's IP address:

1. Download the installation file from our website http://www.tp-link.com/en/download/EAP-Controller.html#EAP_Discovery_Tool. Then follow the instructions to properly install EAP Discovery Utility.
2. Open the EAP Discovery Utility and the following window will pop up. This window shows the information of all EAPs in the same LAN.



3. Click **manage** in the **Action** column or select multiple EAPs and click **Batch Setting**.



The 'Device Information' dialog box displays the following fields and values:

- Status: Pending
- Model: EAP110
- IP Address: 192.168.1.100
- MAC Address: 00:0a:eb:13:7b:00
- Controller Hostname/IP:
- Username:
- Password:

At the bottom, there are 'Apply' and 'Cancel' buttons.

4. Enter the hostname or IP address of the Controller Host.
5. Enter the EAP's username and password (both are admin by default).
6. Click **Apply** to inform the EAP of the Controller's hostname or IP address. And then the connection can be established between the EAP and the Controller Host.


1.4 Start and Log in to the EAP Controller

Launch the software on the Controller Host and follow the instructions to complete the basic configurations, and then you can log in to the management interface.

1.4.1 Launch the EAP Controller

Launch EAP Controller on Windows Host

To launch EAP Controller on a Windows host, double click the icon  and the following window will pop up. You can click **Hide** to hide this window but do not close it. After a while, your web browser will automatically open.



Note:

- If your browser does not open automatically, click **Launch a Browser to Manage Wireless Network**. You can also launch a web browser and enter `http://127.0.0.1:8088` in the address bar.
- If your web browser opens but prompts a problem with the website's security certificate, click **Continue**.

Launch EAP Controller on Linux Host

To launch EAP Controller on a Linux host, follow the steps below:

1. Start the EAP Controller service using the command: **`tpeap start`**.
2. Launch a web browser and enter `http://127.0.0.1:8088` in the address bar to visit the web page of EAP Controller.

Tips:

You can also use the following commands to stop the service or view the service status:

- To stop the service: **`tpeap stop`**
- To view the service status: **`tpeap status`**

1.4.2 Do the Basic Configurations

In the web browser you can see the configuration page. Follow the setup wizard to complete the basic settings for EAP Controller.

1. The EAP Controller displays all the detected EAPs in the network. Select the one or more EAPs to be managed and click **Next**.

The screenshot shows a web interface for configuring the EAP Controller. At the top, there is a progress bar with four steps: 1. Select Devices (highlighted in blue), 2. Wireless Settings, 3. User Account, and 4. Summary. Below the progress bar, the text "Please select the devices you would like to configure" is displayed. A table lists detected devices with columns for Name/MAC Address, IP Address, and Model. Two devices are listed: one with MAC address ec:08:6b:d4:e9:bc and IP 192.168.0.4 (model EAP330), and another with MAC address 50:c7:bf:0b:be:00 and IP 192.168.0.5 (model EAP225). Both devices have a checked checkbox in the first column. Below the table, there are navigation buttons: "<<", "<", "1", ">", ">>". To the right of these buttons, it says "A total of 1 page(s) Page to" followed by a text input field and a "GO" button. At the bottom right, there are two large buttons: "Skip" and "Next".

☒	↕ Name/MAC Address	↕ IP Address	↕ Model
☒	ec:08:6b:d4:e9:bc	192.168.0.4	EAP330
☒	50:c7:bf:0b:be:00	192.168.0.5	EAP225

<< < 1 > >> A total of 1 page(s) Page to GO

Skip Next

2. Set the SSID name (wireless network name) and password for the EAPs to be managed. The EAP Controller will create two wireless networks, a 2.4GHz one and a 5GHz one both encrypted in the WPA2-PSK mode. Click **Next**.

1 Select Devices 2 Wireless Settings 3 User Account 4 Summary

Create a wireless network

SSID: (1-32 characters)

Password: (WPA2-PSK)

Back Next

3. Specify a username and a password to create an administrator account. Specify the email address to receive the notification emails and reset your password if necessary. Click **Next**.

1 Select Devices 2 Wireless Settings 3 User Account 4 Summary

Set up your login account for the EAP Controller

Username: (4-32 characters)

Password: (6-32 characters, only numbers and letters.)

Confirm Password:

Email Address: (You can reset your password with this email)

Back Next

Note:

After logging into the EAP Controller, please set a mail server so that you can receive the notification emails and reset your password in case that you forget the password. Please refer to [Configure Mail Server](#).

4. Review your settings and click **Finish**.

1 Select Devices 2 Wireless Settings 3 User Account 4 Summary

Please confirm your information

SSID Name: SSID1

Password: 12345678

Admin Name: administrator

Email Address: administrator@tp-link.com

Back Finish

1.4.3 Log in to the Management Interface

Once the basic configuration is finished, the browser will be redirected to the following page. Log in to the management interface of EAP Controller with the username and password you have set in the basic configuration.



Note::

In addition to the Controller Host, other hosts in the same LAN can also manage EAP devices via remote access to the Controller Host. For example, when the IP address of the Controller Host is 192.168.0.100 and the EAP Controller is running normally on this host, you can enter <https://192.168.0.100:8043/login>, or <https://192.168.0.100:8043>, or <http://192.168.0.100:8088> in the web browser of other hosts in the same LAN to log into the management interface and manage EAP devices.


1.5 Create Sites and Adopt EAPs

The EAP Controller can manage multiple EAP networks, which are called sites. Multiple sites are logically separated, and each site has its own configurations. There is an initial site named **Default**. If you have no need to manage EAPs with different sites, you can use the default site and skip the **Create Sites** section. However, **Adopt the EAPs** is a necessary step to manage the EAPs.


1.5.1 Create Sites

Follow the steps below to add sites.

1. Click **Sites: Default** in the top left corner of the page and select **Add/Edit Site**, and then the following window will pop up.



2. Click **+ Add** and set a name for the site.




3. Click **Apply** to create the site.

1.5.2 Adopt the EAPs

The EAP Controller can discover all EAP devices currently connected in the network and display their connection statuses. All the EAPs are in **Pending** status when first discovered by the EAP Controller. To manage the EAPs, you need to adopt them. In the quick setup process, the EAP Controller will automatically adopt the selected EAPs using the default username and password (both are admin). However, if you have changed the username or password of your EAPs before, the EAP Controller cannot automatically adopt the them.

To ensure that all EAPs are adopted, follow the steps below:


1. Select a site and go to **Access Points > Pending**. The table displays all the EAPs that have not been adopted.



The screenshot shows the TP-Link EAP Controller web interface. The top navigation bar includes 'Map', 'Statistics', 'Access Points', 'Clients', 'Insight', and 'Log'. The 'Access Points' tab is active, showing a table of pending EAPs. The table has columns for Name/MAC Address, IP Address, Status, Model, Hardware Version, Firmware Version, Num of Clients, Download, Upload, and Action. One EAP is listed with IP 192.168.0.22 and status 'Pending'. The 'Action' column for this EAP has a 'Retry' button.

Name/MAC Address	IP Address	Status	Model	Hardware Version	Firmware Version	Num of Clients	Download	Upload	Action
ec:5b:4f:ad:bc	192.168.0.22	Pending	EAP330	2.0	1.1.0 Build 20170508 Rel. 63715	0	0 Bytes	0 Bytes	Retry

2. Click the **Retry** button in the **Action** column and enter the current username and password of the EAP. Click **Apply**.



The modal dialog box is titled 'AP username and password required'. It contains a note: 'Note: The username and password have been changed for this AP. The EAP Controller cannot adopt it automatically. Please manually enter the correct username and password.' Below the note are two input fields: 'Username:' and 'Password:'. At the bottom is an 'Apply' button.

Tips:

- If you have a new discovered EAP, you can click the **Adopt** button in the **Action** column to adopt the EAP. The EAP Controller will automatically adopt the EAP using the default username and password (both are admin).
- If you have multiple new discovered EAPs, and all of them have the default username and password (both are admin), you can click the **Batch Adopt** button to adopt them all at once. But if there are any EAPs with the **Retry** button, it means that the username and password of these EAPs have been changed. You need to first adopt them before batch adopt the rest EAPs.


3. Wait for a moment, the EAPs will be adopted and the status will change to **Connected**. All the EAPs' username and password will become the same as those of the Controller's administrator account you created in the [Basic Configuration](#).

Tips:

If you want to change the EAPs' username and password, please refer to [Device Account](#).

1.6 Monitor and Manage the EAPs

When all the configurations above are finished, you can centrally monitor and manage the EAPs via the EAP Controller's management interface. The management interface is mainly divided into three sections as the following screen.



Section A	In Section A, you can check the status of EAPs and clients in the network. Also, you can click  to refresh the current page, click  to globally configure the wireless network, and click  to sign out from the management interface. Furthermore, the Sites allows you to group your EAPs and manage them in batches. To configure sites, refer to Create Sites.
Section B	In Section B, you can centrally monitor and manage the EAPs and clients.
Section C	In Section C, you can globally configure the wireless network. The global configurations will take effect on all the adopted EAPs.


2 **Monitor and Manage the Network**

With the EAP Controller you can monitor the EAP devices and centrally manage your wireless network. This chapter includes the following sections:

- *Monitor the Network with the Map*
- *View the Statistics of the Network*
- *Monitor and Manage the EAPs*
- *Monitor and Manage Clients*
- *View Clients Statistics during the Specified Period*
- *Manage the Rogue APs List*
- *View Past Guest Authorization*
- *View Logs*
- *View Alerts*

2.1 Monitor the Network with the Map

You can upload your local map images and monitor the status and coverage range of each EAP with the map. When you initially launch the EAP Controller, a default map is displayed as the following figure shows. Follow the instructions below to add your own map and manage the EAPs via the map.




2.1.1 Add a Map

Prepare a map image in .jpg, .gif, or .png format. And then follow the steps below to add the map to the EAP Controller.

1. Click **Configure Maps** on the upper right corner of map and click **Add**.




2. Enter the map description, select your map image, and click **Create**.




3. Select your local map from the drop-down list on the upper right corner of map area.

Map: ▼

- Click . Draw a line on the map and enter the distance the line represents. Then the EAP Controller will compute and generate the map scale automatically based on your configuration.



- Drag the EAPs from the **Unplaced APs** list to the appropriate locations on the map according to their actual locations.



You can click  to reveal additional options:



Lock the selected EAP in the current location on the map.

	Unlock the selected EAP and you can drag it to another location.
	Display the EAP's details and configure the wireless parameters. Refer to Configure the EAPs Separately .
	Remove the selected EAP back into the Unplaced APs list.

2.1.2 Monitor the EAPs on the Map


Click any of the following options to display EAP Label, Details, and Coverage on the map.

Label | **Details** | **Coverage**

Label	Display the EAP's name. The default name is the MAC address of the EAP.
Details	Display the EAP's name, MAC address, IP address, transmitting/receiving channel, number of connected users, and number of connected guests.
Coverage	Display a visual representation of the wireless range covered by EAPs. The actual signal coverage may be smaller than the visual coverage on the map because the obstacles around the EAPs will weaken the signal.


2.2 View the Statistics of the Network

The EAP Controller collects all statistics of the managed EAPs and displays the statistical information via graphs, pie charts and tables, providing an overview of your wireless network.



2.2.1 View the Client Distribution on SSID

A visual pie chart represents the client distribution on each SSID. For example, the ssid_211 has one client, which occupies 50% of all the clients.



2.2.2 Have a Quick Look at EAPs and Clients

This tab displays the **Most Active AP**, the **Most Active Clients** and the **All-Time Top Client**. You can click the MAC address of the EAP or the client to see more details.

Quick Look	
■ Most Active AP:	00:14:78:b8:c0:02 Download: 4.69 G Upload: 4.00 G
■ Most Active Client:	EC-DF-3A-D5-6A-94 Download: 36.00 K Upload: 103.94 K
■ All-time Top Client:	EC-DF-3A-D5-6A-94 Duration: 29m 57s Download: 47.45 K Upload: 88.42 K

Most Active AP	The current connected AP with the maximum traffic.
Most Active Client	The current connected client with the maximum traffic.
All-time Top Client	The client with the maximum traffic among all the clients that have ever accessed the EAP network.

2.2.3 View Current Usage-Top EAPs

This tab lists the hostname, the number of connected clients and the data traffic condition of the ten APs with the most traffic currently.


Current Usage - Top APs					1-5	6-10
AP	Clients	%Clients	Traffic(MB)	%Traffic		
00:14:78:b8:c0:02	2	100.0%	8894.80	100.0%		
00:14:78:c0:a8:7b	0	0.0%	0.27	0.0%		

Clients	The amount of clients connected to this EAP.
%Clients	The proportion of current connected clients to the Top EAPs' total client amount.
Traffic	The total amount of data transmitted by this EAP, which equals the sum of the transmission traffic of all the current clients that connect to the AP.
%Traffic	The proportion of the EAP's current data transmission amount to the Top EAPs' total transmission amount.

2.2.4 View Recent Activities


The **Recent Activities** statistics can be toggled between a view for the past specific 24 hours and one for the past specific 30 days.

The left ordinate axis indicates the traffic and the right one represents the number of the clients. The abscissa axis shows the selected time period. **Traffic** indicates a visual graph of the network traffic during the selected time period. **Client** indicates a visual graph of the number of the connected clients during the selected time period. For example, the statistics information at 10:00 indicates the traffic size and client number from 9:00 to 10:00. In the following figure, at 10 o'clock, the traffic is about 8 and there is 1 client connected to the AP.



2.3 Monitor and Manage the EAPs

The EAP Controller can discover all the EAP devices currently connected to the network and display the information about them on the **Access Points** page.



2.3.1 Manage the EAPs in Different Status

According to their connection status, all the EAPs are divided into three categories: connected, disconnected and pending. You can view the EAPs in different status on different pages:

[All](#) | [Connected](#) | [Disconnected](#) | [Pending](#)

All

Displays the information of all the EAPs in different status.

Pending

Displays the pending EAPs.

All the EAPs are in pending state by default when first discovered by the EAP Controller, and only after they are adopted and connected, you can monitor and manage them. To adopt pending EAPs, please refer to [Adopt EAPs](#).

Connected	Displays the connected EAPs. Only connected EAPs can be managed. After you adopt a pending EAP, its status will become provisioning and then connected. A connected EAP will turn into a pending one after you forget this EAP. You can refer to Forget this AP to forget a EAP or click Forget All on the page to forget all the connected EAPs.
Disconnected	Displays the disconnected EAPs. If a connected or pending EAP powers off, it will be disconnected. When a disconnected EAP is reset to factory default settings or you forget it, it will turn into a pending one again. You can refer to Forget this AP to forget a EAP or click Forget All on the page to forget all the disconnected EAPs.

2.3.2 View the Detailed Information of EAPs


You can click **Overview**, **Config**, and **Performance** tab to view different detailed information of EAPs.



Overview	Overview displays the EAP's name/MAC address, IP address, status, model, software version, number of connected clients and download/upload bytes.
Config	Config displays the EAP's name/MAC address, IP address, status, model, software version, WLAN Group bounded with the 2G and 5G of the EAP, and radio of the 2G and 5G.
Performance	Performance displays the EAP's name/MAC address, IP address, status, model, software version, number of connected 2G clients and 5G clients, TX(Downloaded Traffic), RX(Uploaded Traffic), TX 2G and TX 5G.

2.3.3 Manage the EAPs in the Action Column

You can execute the corresponding operation to the EAP by clicking an icon in the **Action** column.



	Locate the EAP in the map.
	Reboot the EAP.



Upgrade the EAP.

Click **Browse** to locate and choose the upgrade file in your computer, then click **Upgrade** to install the latest EAP firmware. The Status will appear as **Upgrading** until the process is complete and the EAP reconnects to the EAP Controller.

Upgrade(00:14:78:c0:a8:7b)

Model:

EAP115-Wall

Upgrade File:

Browse

Upgrade

Note:

- Only managed EAPs can be rebooted or upgraded.
- If you want to login to the EAP's own management interface, you need to forget the EAP before that.

2.4 Monitor and Manage Clients

The **Clients** tab displays the clients connected to the EAP network.

tp-link

Sites: Default

APs: 2 Connected, 0 Disconnected, 0 Pending

Stations: 2 Users, 0 Guests

Map, Statistics, Access Points, Clients, Insight, Log

All Clients | Users | Guests

MAC, Name, IP, AP, SSID

MAC Address	Hostname	IP Address	Access Point	SSID	User/Guest	2G/5G	Download	Upload	Rate(Mbps)	Active Time	Signal	Action
EC:DE:3A:D5:6A:94	android-506a80335f19d762	192.168.0.103	00:14:78:b8:c0:02	ssid_211	User	2G	67.29 K	183.92 K	13.0	7m 59s		
58:A2:B5:E2:E9:89	android-4814cd2ba1fa66b1	192.168.0.107	00:14:78:b8:c0:02	ssid_111	User	5G	28.52 K	63.69 K	62.0	4m 43s		

Page Size: 10

<< 1 >> A total of 1 page(s) Page to GO

2.4.1 View the Current Information of Clients

The clients are divided into two types: User and Guest. Users are the clients connected to the EAP wireless network without the [Portal Authentication](#). Guests are the clients connected to the EAP wireless network with the [Portal Authentication](#).

You can click the following tabs to respectively view the detailed information of users and guests.

All Clients | Users | Guests

All Clients	The page will display the information of all clients including users and guests.
Users	The page will display the information of Users.
Guests	The page will display the information of Guests.

2.4.2 Manage Clients in the Action Column

You can execute the corresponding operation to the EAP by clicking an icon in the **Action** column:

Action	
	
	
	


	Reconnect the client to the network.
---	--------------------------------------

	Restrict the client's access to the network.
---	--

	If the client is Guest, you can click this icon to cancel the authorization for it.
---	---

2.5 View Clients Statistics During the Specified Period

The **Clients Statistics** page under the **Insight** tab displays the information of clients that have connected to the EAPs network during a specified period.



MAC Address	Hostname	Download	Upload	Duration	Last Seen	Action
08-63-61-16-ED-C3	android-1cfb95d6c5004125	0 Bytes	0 Bytes	4m 32s	2016-09-16 14:24:30	
58-A2-B5-E2-C9-B9	android-4814cd2ba4fa66b1	19.07 K	53.04 K	19s	2016-09-16 14:27:52	
EC-DF-3A-D5-6A-94	android-5e5a80335fb9d762	54.17 K	111.87 K	30m 27s	2016-09-16 14:36:35	

2.5.1 Select a Specified Period

Select a period from the drop-down menu. Then the page will display clients that have connected to the EAPs network during the period.

Last Seen: 1 Day
Last Seen: 1 Day
Last Seen: 3 Days
Last Seen: 7 Days
Last Seen: 14 Days
Last Seen: 30 Days
Last Seen: 60 Days

2.5.2 View the History Information of Clients

You can click the client's MAC address to get its connection history or click the following tabs to view the information of different types of clients:

All	User	Guest	Blocked
-----	------	-------	---------

All	The page will display the history information of all the clients.
User	The page will display the history information of Users. Users are the clients connected to the EAP wireless network without the Portal Authentication .
Guest	The page will display the history information of Guests. Guests are the clients connected to the EAP wireless network with the Portal Authentication .
Blocked	The page will display the clients that have been blocked.

All Offline Only

All	The page will display the history information of all clients.
Offline Only	The page will display the history information of the offline clients.

2.5.3 Manage Clients in the Action Column

You can execute the corresponding operation to the EAP by clicking an icon in the **Action** column:

	Block the client's access to the network.
	Resume the client's access.

2.6 Manage the Rogue APs List

A Rogue AP is an access point that has been installed on a secure network without explicit authorization from a system administrator. The EAP Controller can scan all channels to detect all nearby EAPs. If rogue APs are detected, they will be shown on the **Untrusted Rogue APs** list. Besides, you can move the untrusted rogue APs to the **Trusted Rogue APs** list.

2.6.1 Manage the Untrusted Rogue APs List

The **Untrusted Rogue APs** page displays the detailed information of untrusted rogue APs.

tp-link

Sites: Default

APs: 2 Connected, 0 Disconnected, 0 Pending

Stations: 2 Users, 0 Guests

↺

⚙

➦

Map

Statistics

Access Points

Clients

Insight

Log

Untrusted Rogue APs

Clients Statistics

Untrusted Rogue APs

Trusted Rogue APs

Past Guest Authorization

MAC, SSID

🔍

🗑 Delete All

MAC	SSID	Band	Channel	Security	Beacon	Signal	Last Seen	Action
50:C7:BF:1B:E6:75	TP-LINK_Extender_5GHz	5G	36	OFF	100	-97	2016-09-16 14:42:00	👤🗑
0C:4A:00:13:50:0B	TP-LINK_500C_5G	5G	36	ON	100	-104	2016-09-16 14:42:00	👤🗑
C4:E9:84:79:C2:1A	TP-LINK_C21A	2.4G	7	ON	100	-81	2016-09-16 14:42:00	👤🗑
00:0A:EB:20:02:40	TP-LINK_0241_5G	5G	149	ON	100	-97	2016-09-16 14:42:00	👤🗑
00:35:00:07:18:02	TP-LINK_Extender_5GHz	5G	36	OFF	100	-99	2016-09-16 14:42:00	👤🗑
00:0A:EB:0A:36:84	TP-LINK_AP_3684	2.4G	6	ON	100	-99	2016-09-16 14:42:00	👤🗑
C0:4A:00:0A:A4:A3	LL_3600_5G	5G	36	OFF	100	-99	2016-09-16 14:42:00	👤🗑
74:DE:AD:3A:D1:B2	TP-LINK_Extender_5GHz	5G	36	OFF	100	-109	2016-09-16 14:42:00	👤🗑
D8:5D:4C:BF:60:3A	TP-LINK_603A	2.4G	3	ON	100	-65	2016-09-16 14:42:00	👤🗑
50:C7:BF:1B:E0:0C	TP-LINK_E00C	2.4G	1	ON	100	-83	2016-09-16 14:42:00	👤🗑

Page Size: 10

⏪

⏴

1

2

3

⏵

⏩

A total of 9 page(s) Page to

GO

You can execute the corresponding operation to the EAP by clicking an icon in the **Action** column:



Move the untrusted rogue AP to the Trusted Rogue APs list.



Delete this record.



Delete All

Delete all records.

2.6.2 Manage the Trusted Rogue APs List

The Trusted Rogue APs page displays the detailed information of trusted rogue APs.

tp-link

Sites: Default

APs

2 Connected0 Disconnected0 Pending

Stations:

2 Users0 Guests

Refresh

Settings

Help

Map

Statistics

Access Points

Clients

Insight

Log

Trusted Rogue APs

Clients Statistics | Untrusted Rogue APs | Trusted Rogue APs | Past Guest Authorization

MAC, SSID

Search

Import

Export

MAC	SSID	Band	Channel	Security	Last Seen	Action
50:C7:BF:1B:E6:75	TP-LINK_Extender_5GHz	5G	36	OFF	2016-09-16 14:43:20	Details
C4:E9:84:79:C2:1A	TP-LINK_C21A	2.4G	7	ON	2016-09-16 14:43:10	Details

Page Size

10

Navigation: << < 1 > >>

A total of 1 page(s)

Page to

GO

You can execute the corresponding operation to the EAP by clicking an icon in the **Action** column:



Move the trusted rogue AP to the Untrusted Rogue APs list.



Export

Export and download the current Trusted Rogue APs list and save it on your PC.



Import a saved Trusted Rogue APs list. If the MAC address of an AP appears in list, it will not be detected as a rogue AP.

Import Trusted AP List

Import Mode: ☒ Replace ☐ Merge

Import Source File:

Browse


Import

Please follow the steps below:

1. Select **Replace** (replace the current Trusted Rogue APs list with the one you import) or **Merge** (add the APs in the file to the current Trusted Rogue APs list).
2. Click **Browse** to locate the file and choose it.
3. Click **Import** to import the Trusted Rogue APs list.


2.7 View Past Guest Authorization

The Past Guest Authorization page displays the details about all the clients that accessed the network during a certain time period. You can select a period in the drop-down list.




2.8 View Logs

The logs of the EAP Controller can effectively record, classify and manage the system information of the managed EAPs, providing powerful support for network administrator to monitor network operation and diagnose malfunctions. The Logs page displays EAP's MAC address, level, occurred time and content.



2.9 View Alerts


You can see the status change of your EAPs on the **Unarchived Alerts** page. You can click  or [Archive All](#) to move unarchived alerts to the Archived Alerts page.



The screenshot shows the TP-Link Omada web interface. The top navigation bar includes 'Map', 'Statistics', 'Access Points', 'Clients', 'Insight', and 'Log'. The 'Log' tab is selected. Below the navigation bar, the 'Unarchived Alerts' section is displayed. It features a search bar for 'AP MAC, Model, Content' and a table with columns: 'AP MAC', 'Model', 'Time', 'Content', and 'Action'. The table contains two rows of alerts, both indicating disconnection of APs. The 'Action' column for each row has an 'Archive All' button. The page footer shows 'Page Size: 10' and 'A total of 1 page(s)'. The 'Log' tab is highlighted with a red box.

AP MAC	Model	Time	Content	Action
00:14:78:c0:a0:7b	EAP115-Wall	2016-09-16 09:33:29	AP 00:14:78:c0:a0:7b was disconnected	
00:14:78:b0:c0:02	EAP220	2016-09-16 09:33:29	AP 00:14:78:b0:c0:02 was disconnected	

As follows, the Archived Alerts page displays the alerts archived by you. You can click  or [Delete All](#) to delete the records.



The screenshot shows the TP-Link Omada web interface. The top navigation bar includes 'Map', 'Statistics', 'Access Points', 'Clients', 'Insight', and 'Log'. The 'Log' tab is selected. Below the navigation bar, the 'Archived Alerts' section is displayed. It features a search bar for 'AP MAC, Model, Content' and a table with columns: 'AP MAC', 'Model', 'Time', 'Content', and 'Action'. The table contains two rows of alerts, both indicating disconnection of APs. The 'Action' column for each row has a 'Delete All' button. The page footer shows 'Page Size: 10' and 'A total of 1 page(s)'. The 'Log' tab is highlighted with a red box.

AP MAC	Model	Time	Content	Action
00:14:78:c0:a0:7b	EAP115-Wall	2016-09-16 09:33:29	AP 00:14:78:c0:a0:7b was disconnected	
00:14:78:b0:c0:02	EAP220	2016-09-16 09:33:29	AP 00:14:78:b0:c0:02 was disconnected	

3 **Configure the EAPs Globally**

This chapter introduces the global configurations applied to all the managed EAPs. To configure a specific EAP, please refer to [Chapter 4 Configure the EAPs Separately](#).

In global configurations, you can configure the following items:

- *Wireless Network*
- *Access Control*
- *Portal Authentication*
- *Free Authentication Policy*
- *MAC Filter*
- *Scheduler*
- *System*

3.1 Wireless Network

In addition to the wireless network you created in Quick Start, you can add more wireless networks and configure the advanced wireless parameters to improve the quality of the wireless network.

3.1.1 Add Wireless Networks

To add wireless networks, follow the steps below.

1. Go to **Wireless Settings > Basic Wireless Setting**.

The screenshot shows the 'Basic Wireless Setting' page. At the top, there are tabs for 'Wireless Settings', 'Wireless Control', 'System', and 'Admin'. The 'Wireless Settings' tab is active. Below the tabs, there are sub-tabs for 'Basic Wireless Setting', 'Advanced Wireless Setting', and 'Band Steering'. The 'Basic Wireless Setting' sub-tab is active. On the left, there are buttons for '2.4GHz' and '5GHz'. On the right, there is a 'WLAN Group' dropdown menu set to 'Default' with a '+' icon to its right. Below this, there is a table with the following columns: ID, SSID Name, Security, SSID Isolation, Portal, Access Control Rule, Rate Limit, and Action. The table contains one row with ID '1', SSID Name 'SSID1', Security 'WPA-PSK', SSID Isolation 'disable', Portal 'disable', Access Control Rule 'None', Rate Limit 'disable', and Action icons. At the bottom right of the table, there is a '+ Add' button. Below the table, there are pagination controls showing '<< < 1 > >>' and 'A total of 1 page(s) Page to [] GO'.

2. Select a band frequency **2.4GHz** **5GHz** and click **+** at the right of **WLAN Group** **Default** to add a WLAN group. If you have no need to group your wireless networks, you can use the default WLAN group and skip this step.
3. Specify a name for the group and click **Apply**.

The screenshot shows a 'WLAN Group' dialog box. It has a title bar with 'WLAN Group' and a close button. Inside, there is a 'Name' label and a text input field containing 'Group1'. Below the input field is an 'Apply' button.

4. Select the brand frequency **2.4GHz** **5GHz** and WLAN group **WLAN Group** **Default**.
5. Click **+** **Add** to add an SSID to the specific WLAN group.
6. Configure the parameters in the following window.

Add 2.4GHz SSID

Basic Info

SSID Name:

Wireless Vlan ID:

0

(0-4094, 0 is used to disable VLAN tagging.)

SSID Broadcast:

☒ Enable

Security Mode:

WPA-PSK

Version:

☐ Auto
☐ WPA-PSK
☒ WPA2-PSK

Encryption:

☐ Auto
☐ TKIP
☒ AES

Wireless Password:

Group Key Update Period:

0

seconds(30-8640000,0 means no upgrade).

Portal:

☐ Enable

SSID Isolation:

☐ Enable

Access Control Rule:

None

Rate Limit

Apply

SSID Name	Enter an SSID name contains up to 32 characters.
Wireless Vlan ID	Set a VLAN ID for the wireless network. Wireless networks with the same VLAN ID are grouped to a VLAN. The value ranges from 0 to 4094. 0 means VLAN function is disabled.
SSID Broadcast	With the option enabled, EAPs will broadcast the SSID to the nearby hosts, so that those hosts can find the wireless network identified by this SSID. If this option is disabled, users must enter the SSID manually to connect to the EAP. Enabled by default.
Security Mode	Select the security mode of the wireless network. None: The hosts can access the wireless network without authentication. WEP/WPA-Enterprise/WPA-PSK: The hosts need to get authenticated before accessing the wireless network. For the network security, you are suggested to encrypt your wireless network. Settings vary in different security modes and the details are in the following introduction.
Portal	With the option enabled, the configurations in Portal will be applied. Portal provides authentication service for the clients who just need temporary access to the wireless network, such as the customers in shopping mall and restaurant. Disabled by default.
SSID Isolation	With the option enabled, the devices connected in the same SSID of the same AP cannot communicate with each other. Disabled by default.
Access Control	Select an Access Control rule for this SSID. For more information, refer to Access Control .

Following is the detailed introduction of **WEP**, **WPA-Enterprise** and **WPA-PSK**.

WEP

WEP is based on the IEEE 802.11 standard and less safe than WPA-Enterprise and WPA-PSK.

Note:

WEP is not supported in 802.11n mode or 802.11ac mode. If WEP is applied in 802.11n, 802.11 ac or 802.11n/ac mixed mode, the clients may not be able to access the wireless network. If WEP is applied in 11b/g/n mode (2.4GHz) or 11a/n (5GHz), the EAP device may work at a low transmission rate.

Security Mode:	WEP
Type:	☒ Auto ☐ Open System ☐ Shared Key
Key Selected:	Key1
WEP Key Format:	☒ ASCII ☐ Hexadecimal
Key Type:	☒ 64Bit ☐ 128Bit ☐ 152Bit
Key Value:	weppw

Type	Select the authentication type for WEP. Auto: The EAP Controller can select Open System or Shared Key automatically based on the wireless station's capability and request. Open System: Clients can pass the authentication and associate with the wireless network without password. However, correct password is necessary for data transmission. Shared Key: Clients have to input password to pass the authentication, otherwise it cannot associate with the wireless network or transmit data.
Key Selected	Select one key to specify. You can configure four keys at most.
WEP Key Format	Select ASCII or Hexadecimal as the WEP key format. ASCII: ASCII format stands for any combination of keyboard characters of the specified length. Hexadecimal: Hexadecimal format stands for any combination of hexadecimal digits (0-9, a-f, A-F) with the specified length.
Key Type	Select the WEP key length for encryption. 64Bit: Enter 10 hexadecimal digits or 5 ASCII characters. 128Bit: Enter 26 hexadecimal digits or 13 ASCII characters. 152Bit: Enter 32 hexadecimal digits or 16 ASCII characters.
Key Value	Enter the WEP keys. The length and valid characters are affected by key type.

WPA-Enterprise

The WPA-Enterprise mode requires a RADIUS server to authenticate clients. Since the WPA-Enterprise can generate different passwords for different clients, it is much safer than WPA-PSK. However, it costs much more to maintain and is usually used by enterprise.

Security Mode:	WPA-Enterprise ▼	
Version:	☐ Auto ☐ WPA ☒ WPA2	
Encryption:	☐ Auto ☐ TKIP ☒ AES	
RADIUS Server IP:	0.0.0.0	
RADIUS Port:	0	(1-65535, 0 means default port 1812.)
RADIUS Password:		
Group Key Update Period:	0	seconds(30-8640000, 0 means no upgrade).

Version	Select the version of WPA-Enterprise. Auto: The EAP will automatically choose the version used by each client device. WPA/WPA2: Two versions of Wi-Fi Protected Access.
Encryption	Select the Encryption type. Auto: The default setting is Auto and the EAP will select TKIP or AES automatically based on the client device's request. TKIP: Temporal Key Integrity Protocol. TKIP is not supported in 802.11n mode, 802.11ac mode or 802.11n/ac mixed mode. If TKIP is applied in 802.11n, 802.11ac or 802.11n/ac mixed mode, the clients may not be able to access the wireless network of the EAP. If TKIP is applied in 11b/g/n mode (2.4GHz) or 11a/n mode(5GHz), the device may work at a low transmission rate. AES: Advanced Encryption Standard. We recommend you select AES as the encryption type because it is more secure than TKIP.
RADIUS Server IP	Enter the IP address of the RADIUS Server.
RADIUS Port	Enter the port number of the RADIUS Server.
RADIUS Password	Enter the shared secret key of the RADIUS server.
Group Key Update Period	Specify a group key update period, which instructs the EAP how often it should change the encryption keys. The value can be either 0 or 30~8640000 seconds. 0 means no change of the encryption key anytime.

WPA-PSK

Based on a pre-shared key, WPA-PSK is characterized by high safety and simple settings and is mostly used by common households and small businesses.

Security Mode:	WPA-PSK
Version:	☐ Auto ☐ WPA-PSK ☒ WPA2-PSK
Encryption:	☐ Auto ☐ TKIP ☒ AES
Wireless Password:	
Group Key Update Period:	0 seconds(30-8640000,0 means no upgrade).

Version	Select the version of WPA-PSK. Auto: The EAP will automatically choose the version for each client device. WPA-PSK: Pre-shared key of WPA. WAP2-PSK: Pre-shared key of WPA2.
Encryption	Select the Encryption type. Auto: The default setting is Auto and the EAP will select TKIP or AES automatically based on the client request. TKIP: Temporal Key Integrity Protocol. TKIP is not supported in 802.11n mode, 802.11ac mode or 802.11n/ac mixed mode. If TKIP is applied in 802.11n, 802.11 ac or 802.11n/ac mixed mode, the clients may not be able to access the wireless network of the EAP. If TKIP is applied in 11b/g/n mode (2.4GHz) or 11a/n mode(5GHz), the device may work at a low transmission rate. AES: Advanced Encryption Standard. We recommend you select AES as the encryption type for it is more secure than TKIP.
Wireless Password	Configure the wireless password with ASCII or Hexadecimal characters. For ASCII, the length should be between 8 and 63 characters with combination of numbers, letters (case-sensitive) and common punctuations. For Hexadecimal, the length should be 64 characters (case-insensitive, 0-9, a-f, A-F).
Group Key Update Period	Specify a group key update period, which instructs the EAP how often it should change the encryption keys. The value can be either 0 or 30~8640000 seconds. 0 means the encryption keys will not be changed all the time.

7. Enable **Rate Limit** for the clients to guarantee the network balance. Enter the value for **Download Limit** and **Upload Limit**. 0 means unlimited.

Rate Limit		
Enable:	☐	
Download Limit:		(Kbps, 0-102400, 0 means unlimited)
Upload Limit:		(Kbps, 0-102400, 0 means unlimited)
Apply		

8. Click **Apply** to add the new SSID.

3.1.2 Configure Advanced Wireless Parameters

Proper wireless parameters can improve the network's stability, reliability and communication efficiency. The advanced wireless parameters consist of **Beacon Interval**, **DTIM Period**, **RTS Threshold**, **Fragmentation Threshold** and **Airtime Fairness**.

To configure the advanced wireless parameters, follow the steps below.

1. Go to **Wireless Settings > Advanced Wireless Setting**.

The screenshot shows the 'Advanced Wireless Setting' configuration page. The 'Wireless Settings' tab is selected, and within it, the 'Advanced Wireless Setting' sub-tab is active. The configuration is for the 2.4GHz band. The parameters are as follows:

Parameter	Value	Range/Notes
Beacon Interval	100	ms(40-100)
DTIM Period	1	(1-255)
RTS Threshold	2347	(1-2347)
Fragmentation Threshold	2346	(256-2346, works only in 11b/g mode)
Airtime Fairness	☐ Enable	

An 'Apply' button is located at the bottom left of the configuration area.

2. Select the band frequency **2.4GHz** **5GHz**.

3. Configure the following parameters.

Beacon Interval	Beacons are transmitted periodically by the EAP device to announce the presence of a wireless network for the clients. Beacon Interval value determines the time interval of the beacons sent by the device. You can specify a value between 40 and 100ms. The default is 100ms.
DTIM Period	The DTIM (Delivery Traffic Indication Message) is contained in some Beacon frames. It indicates whether the EAP device has buffered data for client devices. The DTIM Period indicates how often the clients served by this EAP device should check for buffered data still on the EAP device awaiting pickup. You can specify the value between 1-255 Beacon Intervals. The default value is 1, indicating clients check for buffered data on the EAP device at every beacon. An excessive DTIM interval may reduce the performance of multicast applications, so we recommend you keep it by default.
RTS Threshold	RTS (Request to Send) can ensure efficient data transmission. When RTS is activated, the client will send a RTS packet to EAP to inform that it will send data before it send packets. After receiving the RTS packet, the EAP notices other clients in the same wireless network to delay their transmitting of data and informs the requesting client to send data, thus avoiding the conflict of packet. If the size of packet is larger than the RTS Threshold, the RTS mechanism will be activated. If you specify a low threshold value, RTS packets are sent more frequently and help the network recover from interference or collisions that might occur on a busy network. However, it also consumes more bandwidth and reduces the throughput of the packet. We recommend you keep it by default. The recommended and default value is 2347.

Fragmentation Threshold

The fragmentation function can limit the size of packets transmitted over the network. If a packet exceeds the **Fragmentation Threshold**, the fragmentation function is activated and the packet will be fragmented into several packets.

Fragmentation helps improve network performance if properly configured. However, too low fragmentation threshold may result in poor wireless performance caused by the extra work of dividing up and reassembling of frames and increased message traffic. The recommended and default value is 2346 bytes.

Airtime Fairness

With this option enabled, each client connecting to the EAP can get the same amount of time to transmit data, avoiding low-data-rate clients to occupy too much network bandwidth and improving the network throughput. We recommend you enable this function under multi-rate wireless networks.

4. Click **Apply**.

3.1.3 Configure Band Steering

A client device that is capable of communicating on both the 2.4GHz and 5GHz frequency bands will typically connect to the 2.4 GHz band. However, if too many client devices are connected to an EAP on the 2.4 GHz band, the efficiency of communication will be diminished. Band Steering can steer clients capable of communication on both bands to the 5GHz frequency band which supports higher transmission rates and more client devices, and thus to greatly improve the network quality.

To configure Band Steering, follow the steps below.

1. Go to **Wireless Settings > Band Steering**.

The screenshot shows a web-based configuration interface. At the top, there is a navigation bar with tabs: 'Wireless Settings' (highlighted with a red box), 'Wireless Control', 'System', and 'Admin'. Below the navigation bar, there is a sub-navigation bar with links: 'Basic Wireless Setting', 'Advanced Wireless Setting', and 'Band Steering' (highlighted with a red box). The main content area is titled 'Band Steering' and contains the following settings:

- Band Steering:** A checkbox that is currently unchecked.
- Connection Threshold:** A numeric input field with the value '20' and a range '(2-40)'.
- Difference Threshold:** A numeric input field with the value '4' and a range '(1-8)'.
- Max Failures:** A numeric input field with the value '10' and a range '(0-100)'.

At the bottom left of the configuration area, there is a blue 'Apply' button.

2. Check the box to enable the Band Steering function.
3. Configure the following parameters to balance the clients on both frequency bands:

Connection Threshold/Difference Threshold

When the number of clients on the 5GHz band reaches the value of **Connection Threshold** and the difference value between the number of clients on the 2.4GHz band and the 5GHz band reaches the value of **Difference Threshold**, EAPs will refuse the requests of communication on the 5GHz band from other clients and no longer steer other clients to the 5GHz band.

The value of **Connection Threshold** is from 2 to 40, and the default is 20.

The value of **Difference Threshold** is from 1 to 8, and the default is 4.

Max Failures

If a client repeatedly attempts to associate with the EAP on the 5GHz band and the number of rejections reaches the value of **Max Failures**, the EAP will accept the request.


The value is from 0 to 100, and the default is 10.

4. Click **Apply**.

3.2 Access Control

Access Control is used to block or allow the clients to access specific subnets. To configure Access Control rules, follow the steps below.

1. Go to **Wireless Control > Access Control**.



2. Click **+ Add Access Control Rule** to add a new Access Control rule.

The 'Add Access Control Rule' dialog box is shown. It has a title bar with a close button. Inside, there are three main sections: 'Rule Name:' with a text input field, 'Rule Mode:' with a dropdown menu set to 'Block', and 'Rule Members:' which is divided into 'Subnets:' and 'Except Subnets:'. Both 'Subnets:' and 'Except Subnets:' have a text input field containing '0.0.0.0/24' and an 'Add New' button below it. At the bottom left of the dialog is an 'Apply' button.

3. Configure the following parameters.


Rule Name	Specify a name for this rule.
Rule Mode	Select the mode for this rule. Block: Select this mode to block the rule members to access the network. Allow: Select this mode to allow the rule members to access the network.
Rule Memebers	Subnets: Clients of the subnet will be controlled by the rule. Enter the subnet for this rule in the format X.X.X.X/X and click Add New . Up to 16 subnets can be added. Except Subnets: Clients of the subnet will be controlled by the rule. Enter the subnet that does not follow this rule in the format X.X.X.X/X and click Add New . Up to 16 subnets can be added. The rule will not apply to the subnets that is in both the Subnets list and the Except Subnets list.

- Click **Apply**.
- Go to **Wireless Settings > Basic Wireless Setting** and enable Access Control function of a selected SSID.


3.3 Portal Authentication

Portal authentication enhances the network security by providing authentication service to the clients that just need temporary access to the wireless network. Such clients have to log into a web page to establish verification, after which they will access the network as guests. What's more, you can customize the authentication login page and specify a URL which the newly authenticated clients will be redirected to.

To configure Portal Authentication, go to **Wireless Control > Portal** and click [+ Add a New Portal](#) .



Then the following window will pop up:




These authentication methods are available: No Authentication, Simple Password, Local User, Voucher, SMS, Facebook, External RADIUS Server and External Portal Server. The following sections introduce how to configure each Portal authentication.

3.3.1 No Authentication

With No Authentication configured, clients can access the network without any authentication.

Follow the steps below to configure No Authentication:

1. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
2. Go back to the Portal configuration page. In the **Basic Info** section, complete the basic settings for the portal authentication.



Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select No Authentication .
Authentication Timeout	The client's authentication will expire after the time period you set and the client needs to log in the web authentication page again to access the network. Options include 1 Hour, 8 Hours, 24 Hours, 7 Days, Custom. Custom allows you to define the time in days, hours, and minutes. The default value is one hour.

Redirect	If you enable this function, the portal will redirect the newly authenticated clients to the configured URL.
Redirect URL	If the Redirect function above is enabled, enter the URL that a newly authenticated client will be redirected to.

3. In the **Login Page** section, configure the login page for the Portal.

The screenshot shows the 'Login Page' configuration window. On the left, there are settings for the background (Solid Color or Picture), background picture (Choose button), logo picture (Choose button), welcome information (text input), copyright (text input), and button (text input). On the right, there is a preview of the login page on a mobile phone screen, showing a 'Log In' button and a 'Welcome' message.

Configure the following parameters:

Background	Select the background type. Two types are supported: Solid Color and Picture .
Background Color	If Solid Color is selected, configure your desired background color through the color picker or by entering the RGB value manually.
Background Picture	If Picture is selected, click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm .
Logo Picture	Click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm . In addition, you can click  and configure the logo position. The options include Middle , Upper and Lower .

Welcome Information

Specify the welcome information.

In addition, you can click  and select your desired text color for the welcome information through the color picker or by entering the RGB value manually.


Welcome Information:

(1-31 characters) 

#ffffff

(RGB value)

Welcome Information Color:



Copyright

Specify the copyright information.

In addition, you can click  and select your desired text color for Copyright information through the color picker or by entering the RGB value manually.

Copyright:

(1-200 characters) 

#A7A9AC

(RGB value)

Copyright Color:




Button

Click  and configure the button.


Button Position: Set the position of the login button. The options include **Middle**, **Upper** and **Lower**.

Button Color: Select your desired login button color through the color picker or by entering the RGB value manually.

Button Text Color: Select your desired text color for the button through the color picker or by entering the RGB value manually.



4. In the **Advertisement** section, select whether display advertisement pictures for users and configure the related parameters.



Configure the following parameters:

Advertisement

Specify whether to enable the Advertisement feature. With this feature enabled, you can add advertisement pictures on the authentication page. These advertisement pictures will be displayed before the login page appears. You can also allow users to skip the advertisement by enabling **Allow to Skip Advertisement**.

Picture Resource

Upload advertisement pictures. When several pictures are added, they will be played in a loop.

Advertisement Duration Time

Specify how long the advertisement will be displayed for. For this duration, the pictures will be played in a loop. If the duration time is not enough for all the pictures, the rest will not be displayed.

Picture Careusel Interval	Specify the picture carousel interval. For example, if this value is set as 5 seconds, the first picture will be displayed for 5 seconds, followed by the second picture for 5 seconds, and so on.
Allow Users To Skip Advertisement	Specify whether to enable this feature. With this feature enabled, the user can click the Skip button to skip the advertisement.

5. Click **Apply**.

3.3.2 Simple Password

With Simple Password configured, clients are required to enter the correct password to pass the authentication.

Follow the steps below to configure No Simple Password Portal:

1. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
2. Go back to the Portal configuration page. In the **Basic Info** section, complete the basic settings for the portal authentication.

The screenshot shows the 'Basic Info' configuration page. It contains the following fields and settings:

- Portal Name:** A text input field.
- SSID:** A dropdown menu with the text '==Please select=='.
- Authentication Type:** A dropdown menu set to 'Simple Password'.
- Password:** A text input field.
- Authentication Timeout:** A dropdown menu set to '1 Hour'.
- Redirect:** A checkbox labeled 'Enable'.
- Redirect URL:** A text input field.

Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select Simple Password .
Password	Set the password for authentication.
Authentication Timeout	The client's authentication will expire after the time period you set and the client needs to log in the web authentication page again to access the network. Options include 1 Hour, 8 Hours, 24 Hours, 7 Days, Custom. Custom allows you to define the time in days, hours, and minutes. The default value is one hour.
Redirect	If you enable this function, the portal will redirect the newly authenticated clients to the configured URL.
Redirect URL	If the Redirect function above is enabled, enter the URL that a newly authenticated client will be redirected to.

3. In the **Login Page** section, configure the login page for the Portal.

Login Page

Background: ☐ Solid Color ☒ Picture

Background Picture: (Maximum image size is 2MB; an aspect ratio of 5:3 is best; supported formats are .jpg, .bmp, .gif, .png, .jpeg.)

Logo Picture: (Maximum image size is 2MB; an aspect ratio of 1:1 is best; supported formats are .jpg, .bmp, .gif, .png, .jpeg.)

Logo Position:

Note: The positions of Welcome Information and Logo will be set as a whole

Welcome Information: (1-31 characters)

Copyright: (1-200 characters)

Input Box:

Button:

Note: The positions of Input Box and Button will be set as a whole

PC Mobile Phone Tablet PC


Configure the following parameters:

Background	Select the background type. Two types are supported: Solid Color and Picture .
Background Color	If Solid Color is selected, configure your desired background color through the color picker or by entering the RGB value manually.
Background Picture	If Picture is selected, click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm .
Logo Picture	Click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm . In addition, you can click v and configure the logo position. The options include Middle , Upper and Lower .
Welcome Information	Specify the welcome information. In addition, you can click v and select your desired text color for the welcome information through the color picker or by entering the RGB value manually.

Copyright

Specify the copyright information.

In addition, you can click  and select your desired text color for Copyright information through the color picker or by entering the RGB value manually.



The form contains two sections. The first section, labeled 'Copyright:', has a text input field with a character count '(1-200 characters)' and a help icon. The second section, labeled 'Copyright Color:', has a color input field showing '#A7A9AC' with a '(RGB value)' label, and a color picker below it.


Button

Click  and configure the button.

Button Position: Set the position of the login button. The options include **Middle**, **Upper** and **Lower**.

Button Color: Select your desired login button color through the color picker or by entering the RGB value manually.

Button Text Color: Select your desired text color for the button through the color picker or by entering the RGB value manually.



The form contains three sections. The first section, labeled 'Button:', has a dropdown menu for 'Button Position' with 'Middle' selected, and a note: 'Note: The positions of Input Box and Button will be set as a whole.' The second section, labeled 'Button Color:', has a color input field showing '#4acbd6' with a '(RGB value)' label, and a color picker below it. The third section, labeled 'Button Text Color:', has a color input field showing '#ffffff' with a '(RGB value)' label, and a color picker below it.

4. In the **Advertisement** section, select whether display advertisement pictures for users and configure the related parameters.

Configure the following parameters:

Advertisement	Specify whether to enable the Advertisement feature. With this feature enabled, you can add advertisement pictures on the authentication page. These advertisement pictures will be displayed before the login page appears. You can also allow users to skip the advertisement by enabling Allow to Skip Advertisement .
Picture Resource	Upload advertisement pictures. When several pictures are added, they will be played in a loop.
Advertisement Duration Time	Specify how long the advertisement will be displayed for. For this duration, the pictures will be played in a loop. If the duration time is not enough for all the pictures, the rest will not be displayed.
Picture Careusel Interval	Specify the picture carousel interval. For example, if this value is set as 5 seconds, the first picture will be displayed for 5 seconds, followed by the second picture for 5 seconds, and so on.
Allow Users To Skip Advertisement	Specify whether to enable this feature. With this feature enabled, the user can click the Skip button to skip the advertisement.

5. Click **Apply**.

3.3.3 Local User

With Local User configured, clients are required to enter the correct username and password of the login account to pass the authentication. You can create multiple accounts and assign different accounts for different users.

Configure Local User Portal

Follow the steps below to configure Local User Portal:

1. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
2. Go back to the Portal configuration page. In the **Basic Info** section, complete the basic settings for the portal authentication.

Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select Local User .
User Management	You can click this button to configure user accounts for authentication later. Please refer to Create Local User Accounts .
Redirect	If you enable this function, the portal will redirect the newly authenticated clients to the configured URL.
Redirect URL	If the Redirect function above is enabled, enter the URL that a newly authenticated client will be redirected to.

3. In the **Login Page** section, configure the login page for the Portal.

The screenshot displays the 'Login Page' configuration window. On the left, there are settings for the background (Solid Color or Picture), background picture (Choose button), logo picture (Choose button), logo position (Middle), welcome information (1-31 characters), copyright (1-200 characters), input box, and button. On the right, a preview shows a mobile phone screen with a login form and a background image.

Configure the following parameters:

Background	Select the background type. Two types are supported: Solid Color and Picture .
Background Color	If Solid Color is selected, configure your desired background color through the color picker or by entering the RGB value manually.
Background Picture	If Picture is selected, click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm .
Logo Picture	Click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm . In addition, you can click  and configure the logo position. The options include Middle , Upper and Lower .

The screenshot shows the 'Logo Picture' configuration section. It includes a 'Logo Picture' field with a 'Choose' button and a 'Logo Position' dropdown menu set to 'Middle'. A note indicates the maximum image size is 2MB and supported formats are .jpg, .bmp, .gif, .png, .jpeg.

Welcome Information

Specify the welcome information.

In addition, you can click  and select your desired text color for the welcome information through the color picker or by entering the RGB value manually.


Welcome Information:

(1-31 characters) 

#ffffff

(RGB value)

Welcome Information Color:



Copyright

Specify the copyright information.

In addition, you can click  and select your desired text color for Copyright information through the color picker or by entering the RGB value manually.

Copyright:

(1-200 characters) 

#A7A9AC

(RGB value)

Copyright Color:




Button

Click  and configure the button.

Button Position: Set the position of the login button. The options include **Middle**, **Upper** and **Lower**.

Button Color: Select your desired login button color through the color picker or by entering the RGB value manually.

Button Text Color: Select your desired text color for the button through the color picker or by entering the RGB value manually.



Button: 


Button Position:

Note: The positions of Input Box and Button will be set as a whole.

Button Color: (RGB value)

Button Text Color: (RGB value)

4. In the **Advertisement** section, select whether display advertisement pictures for users and configure the related parameters.



Configure the following parameters:

Advertisement

Specify whether to enable the Advertisement feature. With this feature enabled, you can add advertisement pictures on the authentication page. These advertisement pictures will be displayed before the login page appears. You can also allow users to skip the advertisement by enabling **Allow to Skip Advertisement**.

Picture Resource

Upload advertisement pictures. When several pictures are added, they will be played in a loop.

Advertisement Duration Time

Specify how long the advertisement will be displayed for. For this duration, the pictures will be played in a loop. If the duration time is not enough for all the pictures, the rest will not be displayed.

Picture Careusel Interval	Specify the picture carousel interval. For example, if this value is set as 5 seconds, the first picture will be displayed for 5 seconds, followed by the second picture for 5 seconds, and so on.
Allow Users To Skip Advertisement	Specify whether to enable this feature. With this feature enabled, the user can click the Skip button to skip the advertisement.

5. Click **Apply**.

Create Local User Accounts

Follow the steps below to create the user accounts for authentication:

1. In the **Basic Info** section on the portal configuration page, select the authentication type as **Local User** and click **User Management**. The management page will appear. Go to the **User** page and click **Create User**.



2. The following window will pop up. Configure the required parameters and click **Apply**.

Create New User

Username

(1-100 letters, digits or special characters)

Password

(1-100 letters, digits or special characters)

Authentication Timeout

2017-12-31

(Format: YYYY-MM-DD)

MAC Address Binding Type

No Binding

Maximum Users

1

(1-2048)

Name

(1-50 characters, optional)

Telephone

(1-50 characters, optional)

Rate Limit(Download)

☐

Rate Limit(Download)

Kbps (2-102400)

Rate Limit(Upload)

☐

Rate Limit(Upload)

Kbps (2-102400)

Traffic Limit

☐

Traffic Limit

MBytes (1-1048576)

Apply

Configure the following parameters:

Username	Specify the username. The username should not be the same as any existing one.
Password	Specify the password. Users will be required to enter the username and password when they attempt to access the network.
Authentication Timeout	Specify the authentication timeout for formal users. After the timeout, the users need to log in at the web authentication page again to access the network.
MAC Address Binding Type	There are three types of MAC binding: No Binding, Static Binding and Dynamic Binding. Static Binding: Specify a MAC address for this user account. Then only the user with the this MAC address can use the username and password to pass the authentication. Dynamic Binding: The MAC address of the first user that passes the authentication will be bound. Then only this user can use the username and password to pass the authentication.
Maximum Users	Specify the maximum number of users able to use this account to pass the authentication. This option is available only when the MAC Address Binding Type is set as No Binding .
Name	Specify a name for identification.
Telephone	Specify a telephone number for identification.
Rate Limit (Download)	Select whether to enable download rate limit. With this option enabled, you can specify the limit of download rate.
Rate Limit (Upload)	Select whether to enable upload rate limit. With this option enabled, you can specify the limit of upload rate.
Traffic Limit	Select whether to enable traffic limit. With this option enabled, you can specify the total traffic limit for the user. Once the limit is reached, the user can no longer use this account to access the network.

- In the same way, you can add more user accounts. The created user accounts will be displayed in the list. Users can use the username and password of the account to pass the portal authentication.

By default, the account Status is , which means that the user account is enabled and valid. You can also click this icon to disable the user account. The icon will be changed to , which means that the user account is disabled.



ID	Username	Expiration Time	MAC Address	Status	Action
1	user2	2017-12-31	-		 
2	user1	2017-12-31	-		 


Additionally, you can click [Export Users](#) to backup all the user account information into a CSV file or XLS file and save the file to your PC. If needed, you can click [Import Users](#) and select the file to import the account information to the list.

Note:

Using Excel to open the CSV file may cause some numerical format changes, and the number may be displayed incorrectly. If you use Excel to edit the CSV file, please set the cell format as text.

Manage the Guests

On the Guest page, you can view the information of clients that have passed the portal authentication and manage the clients.



You can select an icon to execute the corresponding operation:



Disconnect client.



Extend the effective time.

Create Operator Accounts

Operator account can be used to remotely manage the Local User Portal and Voucher Portal. Other users can visit the URL **https://EAP Controller Host's IP Address:8043/hotspot** (For example: https://192.168.0.64:8043/hotspot) and use the Operator account to enter the portal management page.

Note:


The users who enter the portal management page by Operator account can only create local user accounts and vouchers and manage the clients.

Follow the steps below to create Operator account.

1. Go to the **Operator** page.



2. Click  [Create Operator](#) and the following window will pop up.



The 'Create Operator' dialog box contains the following fields and options:

- Name:** Operator1
- Password:** 123456
- Notes:** 123
- Site Privileges:** ☒ Default ☐ Office A
- Apply:** A blue button at the bottom left.

3. Specify the **Name**, **Password** and **Notes** of the Operator account.
4. Choose **Site Privileges** (more than one options can be chosen) for the Operator account.
5. Click **Apply** to create an Operator account. Then other users can use this account to enter the hotspot management page.


3.3.4 Voucher

With Voucher configured, you can distribute the vouchers automatically generated by the EAP Controller to the clients. Clients can use the vouchers to access the network.

Configure Voucher Portal

Follow the steps below to configure Voucher Portal:

1. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
2. Go back to the Portal configuration page. In the **Basic Info** section, complete the basic settings for the portal authentication.




The 'Basic Info' configuration page includes the following fields:

- Portal Name:** A text input field.
- SSID:** A dropdown menu with the placeholder text '==Please select=='.
- Authentication Type:** A dropdown menu with 'Voucher' selected. Below it is a link labeled 'Voucher Manager'.
- Redirect:** A checkbox labeled 'Enable'.
- Redirect URL:** A text input field.



Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select Voucher .
User Management	You can click this button to configure vouchers for authentication later. Please refer to Create Vouchers .
Redirect	If you enable this function, the portal will redirect the newly authenticated clients to the configured URL.
Redirect URL	If the Redirect function above is enabled, enter the URL that a newly authenticated client will be redirected to.

3. In the **Login Page** section, configure the login page for the Portal.




Configure the following parameters:

Background	Select the background type. Two types are supported: Solid Color and Picture .
Background Color	If Solid Color is selected, configure your desired background color through the color picker or by entering the RGB value manually.
Background Picture	If Picture is selected, click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm .
Logo Picture	Click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm. In addition, you can click  and configure the logo position. The options include Middle, Upper and Lower. 
Welcome Information	Specify the welcome information. In addition, you can click  and select your desired text color for the welcome information through the color picker or by entering the RGB value manually. 

Copyright

Specify the copyright information.

In addition, you can click  and select your desired text color for Copyright information through the color picker or by entering the RGB value manually.



The form contains two sections. The first section, labeled 'Copyright:', has a text input field with a placeholder '(1-200 characters)' and a small icon to its right. The second section, labeled 'Copyright Color:', has a color input field with the value '#A7A9AC' and a label '(RGB value)' to its right. Below the color input is a color picker interface with a square color field and a vertical color bar.


Button

Click  and configure the button.

Button Position: Set the position of the login button. The options include **Middle**, **Upper** and **Lower**.

Button Color: Select your desired login button color through the color picker or by entering the RGB value manually.

Button Text Color: Select your desired text color for the button through the color picker or by entering the RGB value manually.



The form contains three sections. The first section, labeled 'Button:', has a dropdown menu with the value 'Middle' and a small icon to its right. Below the dropdown is a note: 'Note: The positions of Input Box and Button will be set as a whole.' The second section, labeled 'Button Color:', has a color input field with the value '#4acbd6' and a label '(RGB value)' to its right. Below the color input is a color picker interface with a square color field and a vertical color bar. The third section, labeled 'Button Text Color:', has a color input field with the value '#ffffff' and a label '(RGB value)' to its right. Below the color input is a color picker interface with a square color field and a vertical color bar.

4. In the **Advertisement** section, select whether display advertisement pictures for users and configure the related parameters.

Configure the following parameters:

Advertisement	Specify whether to enable the Advertisement feature. With this feature enabled, you can add advertisement pictures on the authentication page. These advertisement pictures will be displayed before the login page appears. You can also allow users to skip the advertisement by enabling Allow to Skip Advertisement .
Picture Resource	Upload advertisement pictures. When several pictures are added, they will be played in a loop.
Advertisement Duration Time	Specify how long the advertisement will be displayed for. For this duration, the pictures will be played in a loop. If the duration time is not enough for all the pictures, the rest will not be displayed.
Picture Careusel Interval	Specify the picture carousel interval. For example, if this value is set as 5 seconds, the first picture will be displayed for 5 seconds, followed by the second picture for 5 seconds, and so on.
Allow Users To Skip Advertisement	Specify whether to enable this feature. With this feature enabled, the user can click the Skip button to skip the advertisement.

5. Click **Apply**.

Create Vouchers

Follow the steps below to create vouchers for authentication:

1. In the **Basic Info** section, select the authentication type as **Voucher** and click **Voucher Manager**. The voucher management page will appear. Go to the **Voucher** page and click

Create Vouchers.

2. The following window will pop up. Configure the required parameters and click **Apply**.

Create Vouchers

Code Length

(6-10)

Amount

(1-10000)

Type

Single Use

Duration

8 hours

Rate Limit (Download):

☐ Enable

Rate Limit (Download):

Kbps (2-102400)

Rate Limit (Upload):

☐ Enable

Rate Limit (Upload):

Kbps (2-102400)

Traffic Limit:

☐ Enable

Traffic Limit:

MBytes (1-1048576)

Notes

Apply

Configure the following parameters:

Code Length	Specify the length of the voucher codes to be created.
Amount	Enter the voucher amount to be generated.
Type	Select Single Use or Multi Use. Single Use means one voucher can only be distributed to one client. Multi Use means one voucher can be distributed to several clients, who can use the same voucher to access the network at the same time. If you select Multi Use, enter the value of Max Users. When the number of clients who are connected to the network with the same voucher reaches the value, no more clients can use this voucher to access the network.
Duration	Select the period of validity of the Voucher. The options include 8 hours, 2 days and User-defined. The period of valid of the voucher is reckoned from the time when it is used for the first time.
Rate Limit (Download)	Select whether to enable download rate limit. With this option enabled, you can specify the limit of download rate.
Rate Limit (Upload)	Select whether to enable upload rate limit. With this option enabled, you can specify the limit of upload rate.
Traffic Limit	Specify the total traffic limit for one voucher. Once the limit is reached, the client can no longer access the network using the voucher.
Notes	Enter a description for the Voucher (optional).

3. The Vouchers will be generated and displayed on the page.

tp-link

Sites: Default

Guest

Voucher

User

Operator

Code, Notes

Print All Unused

Create Vouchers

# Code	# Created Time	# Notes	# Duration	Status	Action
010-359	2017-06-25 10:14:44		8h	Valid to single use	
182-250	2017-06-25 10:14:44		8h	Valid to single use	
572-659	2017-06-25 10:14:44		8h	Valid to single use	
587-843	2017-06-25 10:14:44		8h	Valid to single use	
823-450	2017-06-25 10:14:44		8h	Valid to single use	
873-860	2017-06-25 10:14:44		8h	Valid to single use	
166-444	2017-06-25 10:14:44		8h	Valid to single use	
089-692	2017-06-25 10:14:44		8h	Valid to single use	
360-275	2017-06-25 10:14:44		8h	Valid to single use	
447-993	2017-06-25 10:14:44		8h	Valid to single use	

Page Size

10

1

2

3

4

A total of 1 page(s)

Page to

GO

4. Click  or  **Print All Unused** to print and save the vouchers.

20170625 Voucher							
Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use
447-993	360-275	089-692	166-444				
Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use	Valid for 8h with single use
873-860	823-450	587-843	572-659				
Valid for 8h with single use	Valid for 8h with single use						
182-250	010-359						
https://127.0.0.1:8084/tp-link/voucher/print.html 1/1							

5. Distribute the vouchers to clients, and then they can use the codes to pass authentication.

6. When the vouchers are invalid, you can click  to delete the Voucher or click  to delete all of them.

Manage the Guests

On the Guest page, you can view the information of clients that have passed the portal authentication and manage the clients.

tp-link Sites: Default Guest Voucher User Operator								
MAC, SSID No entries.								
MAC Address	SSID	WLAN Group	Radio	Authorized By	Download	Upload	Status	Action

You can select an icon to execute the corresponding operation:

	Restrict the client to access the network.
	Extend the effective time.

Create Operator Accounts

Operator account can be used to remotely manage the Local User Portal and Voucher Portal. Other users can visit the URL **https://EAP Controller Host's IP Address:8043/hotspot** (For example: https://192.168.0.64:8043/hotspot) and use the Operator account to enter the portal management page.

Note:

The users who enter the portal management page by Operator account can only create local user accounts and vouchers and manage the clients.

Follow the steps below to create Operator account.

1. Go to the **Operator** page.



2. Click  **Create Operator** and the following window will pop up.

Create Operator

Name

Operator1

Password

123456

Notes

123

Site Privileges

☒ Default ☐ Office A

Apply


3. Specify the **Name**, **Password** and **Notes** of the Operator account.
4. Choose **Site Privileges** (more than one options can be chosen) for the Operator account.
5. Click **Apply** to create an Operator account. Then other users can use this account to enter the hotspot administrative system.

3.3.5 SMS

With SMS portal configured, client can get verification codes using their mobile phones and enter the received codes to pass the authentication.

Follow the steps below to configure SMS Portal:

1. Go to www.twilio.com/try-twilio and get a Twilio account. Buy the Twilio service for SMS. Then get the account information, including ACCOUNT SID, AUTH TOKEN and Phone number.
2. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
3. Go back to the Portal configuration page. In the **Basic Info** section, complete the basic settings for the portal authentication.



Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select SMS .
Twilio SID	Enter the Account SID for Twilio API Credentials.
Auth Token	Enter the Authentication Token for Twilio API Credentials.
Phone Number	Enter the phone number that is used to send verification messages to the clients.
Maximum Users	A telephone can get several codes via messages one by one, and different clients can use different codes to pass the authentication. However, the number of clients that are allowed to be authenticated using the same telephone at the same time has a upper limit. Specify the upper limit in this field.
Authentication Timeout	The client's authentication will expire after the time period you set and the client needs to log in the web authentication page again to access the network. Options include 1 Hour, 8 Hours, 24 Hours, 7 Days, Custom. Custom allows you to define the time in days, hours, and minutes. The default value is one hour.

Preset Country Code	Set the default country code that will be filled automatically on the authentication page.
Redirect	If you enable this function, the portal will redirect the newly authenticated clients to the configured URL.
Redirect URL	If the Redirect function above is enabled, enter the URL that a newly authenticated client will be redirected to.

4. In the **Login Page** section, configure the login page for the Portal.

Login Page

Background: ☐ Solid Color ☒ Picture

Background Picture: [Choose](#) (Maximum image size is 2MB; an aspect ratio of 5:3 is best; supported formats are .jpg, .bmp, .gif, .png, .jpeg)

Logo Picture: [Choose](#) (Maximum image size is 2MB; an aspect ratio of 1:1 is best; supported formats are .jpg, .bmp, .gif, .png, .jpeg)

Logo Position: [Middle](#)

Note: The positions of Welcome Information and Logo will be set as a whole.

Welcome Information: (1-31 characters)

Copyright: (1-200 characters)

Input Box:

Button:

Note: The positions of Input Box and Button will be set as a whole.

PC Mobile Phone Tablet PC

Preview: A mobile phone screen showing a login form with fields for Phone Number, Verification Code, and a Log In button.

Configure the following parameters:

Background	Select the background type. Two types are supported: Solid Color and Picture .
Background Color	If Solid Color is selected, configure your desired background color through the color picker or by entering the RGB value manually.
Background Picture	If Picture is selected, click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm .
Logo Picture	Click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm . In addition, you can click ⌵ and configure the logo position. The options include Middle , Upper and Lower .

Logo Picture: [Choose](#) (Maximum image size is 2MB; an aspect ratio of 1:1 is best; supported formats are .jpg, .bmp, .gif, .png, .jpeg)

Logo Position: [Middle](#)

Welcome Information

Specify the welcome information.

In addition, you can click  and select your desired text color for the welcome information through the color picker or by entering the RGB value manually.


Welcome Information:

(1-31 characters) 

#ffffff

(RGB value)

Welcome Information Color:



Copyright

Specify the copyright information.

In addition, you can click  and select your desired text color for Copyright information through the color picker or by entering the RGB value manually.


Copyright:

(1-200 characters) 

#A7A9AC

(RGB value)

Copyright Color:




Button

Click  and configure the button.


Button Position: Set the position of the login button. The options include **Middle**, **Upper** and **Lower**.

Button Color: Select your desired login button color through the color picker or by entering the RGB value manually.

Button Text Color: Select your desired text color for the button through the color picker or by entering the RGB value manually.



5. In the **Advertisement** section, select whether display advertisement pictures for users and configure the related parameters.



Configure the following parameters:

Advertisement

Specify whether to enable the Advertisement feature. With this feature enabled, you can add advertisement pictures on the authentication page. These advertisement pictures will be displayed before the login page appears. You can also allow users to skip the advertisement by enabling **Allow to Skip Advertisement**.

Picture Resource

Upload advertisement pictures. When several pictures are added, they will be played in a loop.

Advertisement Duration Time

Specify how long the advertisement will be displayed for. For this duration, the pictures will be played in a loop. If the duration time is not enough for all the pictures, the rest will not be displayed.

Picture Careusel Interval	Specify the picture carousel interval. For example, if this value is set as 5 seconds, the first picture will be displayed for 5 seconds, followed by the second picture for 5 seconds, and so on.
Allow Users To Skip Advertisement	Specify whether to enable this feature. With this feature enabled, the user can click the Skip button to skip the advertisement.

6. Click **Apply**.

For more details about how to configure SMS Portal, you can go to <http://www.tp-link.com/en/configuration-guides.html> and download the configuration guide for SMS Portal.

3.3.6 Facebook

With Facebook Portal configured, when clients connect to your Wi-Fi, they will be redirected to your Facebook page. To access the internet, clients need to pass the authentication on the page.

Follow the steps below to configure Facebook Portal:

1. Go to www.facebook.com and get a Facebook account. Create your Facebook page according to your needs.
2. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
3. Go back to the Portal configuration page. In the **Basic Info** section, complete the settings for the portal authentication.

Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select Facebook .
Facebook Page Configuration	Click this button to specify the Facebook Page.
Facebook Checkin Location	If the Facebook page is successfully got by the EAP Controller, the name of the Facebook page will be displayed here.


For more details about how to configure Facebook Portal, you can go to <http://www.tp-link.com/en/configuration-guides.html> and download the configuration guide for Facebook Portal.

3.3.7 External RADIUS Server

If you have a RADIUS server, you can configure External RADIUS Server Portal. With this type of portal, you can get two types of portal customization: Local Web Portal and External Web Portal. The authentication login page of Local Web Portal is provided by the built-in portal server of the EAP. The External Web Portal is provided by external portal server.

Follow the steps below to configure External RADIUS Server Portal:

1. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
2. Go back to the Portal configuration page. In the **Basic Info** section, complete the basic settings for the portal authentication.



Configure the following parameters:

Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select Simple Password .
RADIUS Server IP	Enter the IP address of the RADIUS server.
RADIUS Port	Enter the port number you have set on the RADIUS server.
RADIUS Password	Enter the password you have set on the RADIUS Server.
Authentication Timeout	The client's authentication will expire after the time period you set and the client needs to log in the web authentication page again to access the network. Options include 1 Hour, 8 Hours, 24 Hours, 7 Days, Custom. Custom allows you to define the time in days, hours, and minutes. The default value is one hour.
Redirect	If you enable this function, the portal will redirect the newly authenticated clients to the configured URL. Disabled by default.

Redirect URL	If the Redirect function above is enabled, enter the URL that a newly authenticated client will be redirected to.
Portal Customization	Select Local Web Portal or External Web Portal. Local Web Portal: If this option is selected, refer to step 4 to configure the login page and step 5 to configure the advertisement. External Web Portal: If this option is selected, follow the steps below. 1. Configure the external RADIUS server. 2. Enter the authentication login page's URL provided by the external portal server in the External Web Portal URL field. 3. Put the external web portal server to a whitelist of Free Authentication Policy, otherwise clients cannot access it before authenticated.

4. **Local Web Portal** is configured, configure the login page for the Portal in the **Login Page** section.

Configure the following parameters:

Background	Select the background type. Two types are supported: Solid Color and Picture .
Background Color	If Solid Color is selected, configure your desired background color through the color picker or by entering the RGB value manually.
Background Picture	If Picture is selected, click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm .
Logo Picture	Click the Choose button and select a picture from your PC. Drag and scale the clipping region to edit the picture and click Confirm. In addition, you can click  and configure the logo position. The options include Middle, Upper and Lower.

Welcome Information

Specify the welcome information.

In addition, you can click  and select your desired text color for the welcome information through the color picker or by entering the RGB value manually.


Welcome Information:

(1-31 characters) 

#ffffff

(RGB value)

Welcome Information Color:



Copyright

Specify the copyright information.

In addition, you can click  and select your desired text color for Copyright information through the color picker or by entering the RGB value manually.


Copyright:

(1-200 characters) 

#A7A9AC

(RGB value)

Copyright Color:




Button

Click  and configure the button.


Button Position: Set the position of the login button. The options include **Middle**, **Upper** and **Lower**.

Button Color: Select your desired login button color through the color picker or by entering the RGB value manually.

Button Text Color: Select your desired text color for the button through the color picker or by entering the RGB value manually.



5. If **Local Web Portal** is configured, select whether display advertisement pictures for users and configure the related parameters in the **Advertisement** section, .



Configure the following parameters:

Advertisement

Specify whether to enable the Advertisement feature. With this feature enabled, you can add advertisement pictures on the authentication page. These advertisement pictures will be displayed before the login page appears. You can also allow users to skip the advertisement by enabling **Allow to Skip Advertisement**.

Picture Resource

Upload advertisement pictures. When several pictures are added, they will be played in a loop.

Advertisement Duration Time

Specify how long the advertisement will be displayed for. For this duration, the pictures will be played in a loop. If the duration time is not enough for all the pictures, the rest will not be displayed.

Picture Careusel Interval	Specify the picture carousel interval. For example, if this value is set as 5 seconds, the first picture will be displayed for 5 seconds, followed by the second picture for 5 seconds, and so on.
Allow Users To Skip Advertisement	Specify whether to enable this feature. With this feature enabled, the user can click the Skip button to skip the advertisement.

6. Click **Apply**.

3.3.8 External Portal Server

The option of External Portal Server is designed for the developers. They can customize their own authentication type according to the interface provided by EAP Controller, e.g. message authentication and WeChat authentication etc.

1. Go to **Wireless Settings > Basic Wireless Settings** and create an SSID for the Portal.
2. Go back to the Portal configuration page. In the **Basic Info** section, complete the settings for the portal authentication.


Portal Name	Specify a name for the Portal.
SSID	Select an SSID for the Portal.
Authentication Type	Select External Portal Server .
External Portal Server	Enter the complete authentication URL that redirect to an external portal server, for example: http://192.168.0.147:8880/portal/index.php or http://192.168.0.147/portal/index.html
HTTPS Redirect	With this function enabled, the unauthorized clients will be redirected to the Portal page when they are trying to browse HTTPS websites. With this function disabled, the unauthorized clients cannot browse HTTPS websites or be redirected to the Portal page.

3. Click **Apply**.

3.4 Free Authentication Policy

Free Authentication Policy allows some specified clients to access the network resources without authentication. Follow the steps below to add free authentication policy.

1. Go to **Wireless Control > Free Authentication Policy**.



2. Click **+ Add** and the following window will pop up.

A screenshot of the 'Add Policy' dialog box. It contains the following fields: 'Policy Name' (text input), 'Source IP Range' (text input) and 'Destination IP Range' (text input) with a slash separator and '(Optional)' label, 'Source MAC' (text input) with '(Optional)' label, and 'Destination Port' (text input) with '(Optional)' label. There is a 'Status' section with an 'Enable' checkbox. At the bottom is an 'Apply' button.

3. Configure the following parameters. When all conditions are met, the client can access the network without authentication.

Policy Name	Specify a name for the policy.
Source IP Range	Set the Source IP Range with the subnet and mask length of the clients.
Destination IP Range	Set the Destination IP Range with the subnet and mask length of the server.
Source MAC	Set the MAC address of client.
Destination Port	Enter the port the service uses.
Status	Check the box to enable the policy.


4. Click **Apply** and the policy is successfully added.

3.5 MAC Filter

MAC filter can be used to allow or block the listed clients to access the network. Thereby it can effectively control client's access to the wireless network.

Follow the steps below to configure MAC Filter.

1. Go to **Wireless Control > MAC Filter** to add MAC Filter group and group members.




- 1) Click **+ Add a Group** and specify a name for the group.

Add a Group [Close]

MAC Filter Name:

Apply

- 2) Click **Apply** and the group will be successfully added as shown below.




- 3) Click **+ Add a Group Member** and enter a MAC address in the format as shown below.

Add a Group Member [Close]

MAC Address:

Apply

- 4) Click **Apply** to add the MAC address into the MAC filter group.



2. You can add more groups or members according to your need.

Note:

You can click [Import Group Members](#) to export the group members to a excel file and save the file on your PC. If needed, you can also click [Export Group Members](#) to import the group members to the EAP Controller.

3. Go to **Wireless Control > MAC Filter Association** to associate the added MAC Filter group with SSID.

Wireless Settings | **Wireless Control** | System | Admin

Access Control | Portal | Free Authentication Policy | MAC Filter | **MAC Filter Association** | Scheduler | Scheduler Association | QoS

MAC Filtering: ☒ Enable Apply

2.4GHz 5GHz Default

ID	SSID Name	Band	MAC Filter Name	Action	Setting
1	SSID1	2.4GHz	Group1	Allow	Apply

<< < 1 > >> A total of 1 page(s) Page to GO

- 1) Check the box and click **Apply** to enable MAC Filtering function.
- 2) Select a band frequency (2.4GHz or 5GHz) and a WLAN group.
- 3) In the MAC Filter Name column of the specified SSID, select a MAC Filter group in the drop-down list. Then select **Allow/Deny** in the Action column to allow/deny the clients in the MAC Filter group to access the network.
- 4) Click **Apply** in the Setting column.

3.6 Scheduler

With the Scheduler, the EAPs or its' wireless network can automatically turn on or off at the time you set. For example, you can use this feature to schedule the radio to operate only during the office working time in order to achieve security goals and reduce power consumption. You can also use the Scheduler to make clients can only access the wireless network during the time period you set in the day.

Follow the steps below to configure Scheduler.

1. Go to **Wireless Control > Scheduler**.

Wireless Settings | **Wireless Control** | System | Admin

Access Control | Portal | Free Authentication Policy | MAC Filter | MAC Filter Association | **Scheduler** | Scheduler Association | QoS

+ Add a Profile

Profile Configuration	Action
No entry in the table.	

- 1) Click  **Add a Profile** and specify a name for the profile.

Add a Profile

Profile Name:

Apply

- 2) Click **Apply** and the profile will be added.

Profile Configuration				Action
Profile1				 

ID	Day of Week	Start Time	End Time	Action
No entry in the table.				

- 3) Click **Add an Item** and configure the parameters to specify a period of time.

Add an Item

Day Mode:

☒ Weekday

☐ Weekend

☐ Everyday

☐ Custom

☒ Mon

☒ Tue

☒ Wed

☒ Thu

☒ Fri

☐ Sat

☐ Sun

Time:

☐ all day-24 hours

Start Time:

00

:

00

End Time:

00

:

00

Apply

- 4) Click **Apply** and the profile is successfully added in the list.

2. Go to **Wireless Control > Scheduler Association**.

Wireless Settings

Wireless Control

System

Admin

Access Control | Portal | Free Authentication Policy | MAC Filter | MAC Filter Association | Scheduler | Scheduler Association | QoS

Scheduler:

☒ Enable

Association Mode:

Associated with SSID

Apply

2.4GHz

5GHz

Default

ID	SSID Name	Band	Profile Name	Action	Setting
1	SSID1	2.4GHz	Profile1	Radio On	Apply

<<

<

1

>

>>

A total of 1 page(s)

Page to

GO

- 1) Check the box to enable Scheduler function.

- 2) Select **Associated with SSID** (the profile will be applied to the specific SSID on all the EAPs) or **Associated with AP** (the profile will be applied to all SSIDs on the specific EAP). Then click **Apply**.
- 3) Select a band frequency (2.GHz or 5GHz) and a WLAN group.
- 4) In the Profile Name column of the specified SSID or AP, select a profile you added before in the drop-down list. Select **Radio Off/Radio On** to turn on or off the wireless network during the time interval set for the profile.
- 5) Click **Apply** in the Setting column.

3.7 QoS

The EAP Controller software allows you to configure the quality of service (QoS) on the EAP device for optimal throughput and performance when handling differentiated wireless traffic, such as Voice-over-IP (VoIP), other types of audio, video, streaming media, and traditional IP data.

To configure QoS on the EAP device, you should set parameters on the transmission queues for different types of wireless traffic and specify minimum and maximum wait times (through contention windows) for transmission. In normal use, we recommend you keep the default values for the EAP devices and station EDCA (Enhanced Distributed Channel Access).

Follow the steps below to configure QoS.

1. Go to **Wireless Control > QoS**.

2. Enable or disable the following features.

Wi-Fi Multimedia (WMM)	By default enabled. With WMM enabled, the EAP devices have the QoS function to guarantee the high priority of the transmission of audio and video packets. If 802.11n only mode is selected in 2.4GHz (or 802.11n only, 802.11ac only, or 802.11 n/ac mixed mode in 5GHz), the WMM should be enabled. If WMM is disabled, the 802.11n only mode cannot be selected in 2.4GHz (or 802.11n only, 802.11ac only, or 802.11 n/ac mixed mode in 5GHz).
NoAcknowledgement	By default disabled. You can enable this function to specify that the EAP devices should not acknowledge frames with QosNoAck. NoAcknowledgement is recommended if VoIP phones access the network through the EAP device.
Unscheduled Automatic Power Save Delivery	By default enabled. As a power management method, it can greatly improve the energy-saving capacity of clients.

3. Click **AP EDCA Parameters** and the following page will appear. AP EDCA parameters affect traffic flowing from the EAP device to the client station. We recommend you use the defaults.

AP EDCA Parameters:

Queue	Arbitration Inter-Frame Space	Minimum Contention Window	Maximum Contention Window	Maximum Burst
Data 0(Voice)	1	3	7	1504
Data 1(Video)	1	7	15	3008
Data 2(Best Effort)	3	15	63	0
Data 3(Background)	7	15	1023	0

Queue	Queue displays the transmission queue. By default, the priority from high to low is Data 0, Data 1, Data 2, and Data 3. The priority may be changed if you reset the EDCA parameters. Data 0 (Voice)—Highest priority queue, minimum delay. Time-sensitive data such as VoIP and streaming media are automatically sent to this queue. Data 1 (Video)—High priority queue, minimum delay. Time-sensitive video data is automatically sent to this queue. Data 2 (Best Effort)—Medium priority queue, medium throughput and delay. Most traditional IP data is sent to this queue. Data 3 (Background)—Lowest priority queue, high throughput. Bulk data that requires maximum throughput and is not time-sensitive is sent to this queue (FTP data, for example).
Arbitration Inter-Frame Space	A wait time for data frames. The wait time is measured in slots. Valid values for Arbitration Inter-Frame Space are from 0 to 15.
Minimum Contention Window	A list to the algorithm that determines the initial random backoff wait time (window) for retry of a transmission. This value can not be higher than the value for the Maximum Contention Window.

Maximum Contention Window	The upper limit (in milliseconds) for the doubling of the random backoff value. This doubling continues until either the data frame is sent or the Maximum Contention Window size is reached. This value must be higher than the value for the Minimum Contention Window.
----------------------------------	--

Maximum Burst	Maximum Burst specifies the maximum burst length allowed for packet bursts on the wireless network. A packet burst is a collection of multiple frames transmitted without header information. The decreased overhead results in higher throughput and better performance.
----------------------	---

- Click **Station EDCA Parameters** and the following page will appear. Station EDCA parameters affect traffic flowing from the client station to the EAP device. We recommend you use the defaults.

Station EDCA Parameters:				
Queue	Arbitration Inter-Frame Space	Minimum Contention Window	Maximum Contention Window	TXOP Limit
Data 0(Voice)	2	3	7	1504
Data 1(Video)	2	7	15	3008
Data 2(Best Effort)	3	15	1023	0
Data 3(Background)	7	15	1023	0

Queue	Queue displays the transmission queue. By default, the priority from high to low is Data 0, Data 1, Data 2, and Data 3. The priority may be changed if you reset the EDCA parameters. Data 0 (Voice)—Highest priority queue, minimum delay. Time-sensitive data such as VoIP and streaming media are automatically sent to this queue. Data 1 (Video)—High priority queue, minimum delay. Time-sensitive video data is automatically sent to this queue. Data 2 (Best Effort)—Medium priority queue, medium throughput and delay. Most traditional IP data is sent to this queue. Data 3 (Background)—Lowest priority queue, high throughput. Bulk data that requires maximum throughput and is not time-sensitive is sent to this queue (FTP data, for example).
--------------	---

Arbitration Inter-Frame Space	A wait time for data frames. The wait time is measured in slots. Valid values for Arbitration Inter-Frame Space are from 0 to 15.
--------------------------------------	---

Minimum Contention Window	A list to the algorithm that determines the initial random backoff wait time (window) for retry of a transmission. This value can not be higher than the value for the Maximum Contention Window.
----------------------------------	---

Maximum Contention Window	The upper limit (in milliseconds) for the doubling of the random backoff value. This doubling continues until either the data frame is sent or the Maximum Contention Window size is reached. This value must be higher than the value for the Minimum Contention Window.
----------------------------------	--

TXOP Limit

The **TXOP Limit** is a station EDCA parameter and only applies to traffic flowing from the client station to the EAP device. The Transmission Opportunity (TXOP) is an interval of time, in milliseconds, when a WME client station has the right to initiate transmissions onto the wireless medium (WM) towards the EAP device. The valid values are multiples of 32 between 0 and 8192.

5. Click **Apply**.

3.8 System

3.8.1 Reboot Schedule

You can reboot all the EAPs in the network periodically as needed. Follow the steps below to configure Reboot Schedule.

1. Go to **System > Reboot Schedule**.

The screenshot shows the 'System' menu with 'Reboot Schedule' highlighted. The configuration options are: 'Enable' (unchecked checkbox), 'Timing Mode' (dropdown menu set to 'Daily'), and 'Reboot Time' (three dropdown menus set to '00 : 00 : 00'). An 'Apply' button is at the bottom.

2. Check the box to enable the function.
3. Choose **Daily**, **Weekly** or **Monthly** in the **Timing Mode** drop-down list and set a specific time to reboot the EAPs.
4. Click **Apply**.

3.8.2 Log Setting

Follow the steps below to choose the way to receive system logs.

1. Go to **System > Log Setting**.

The screenshot shows the 'System' menu with 'Log Setting' highlighted. The configuration options are: 'Auto Mail Feature' (unchecked checkbox), 'Enable Server' (unchecked checkbox), and 'Enable Nvram' (unchecked checkbox). An 'Apply' button is at the bottom.

2. Check the box to choose the way to receive system logs (you can choose more than one) and click **Apply**. Three ways are available: **Auto Mail Feature**, **Server** and **Nvram**.

Auto Mail Feature

If Auto Mail Feature is enabled, system logs will be sent to a specified mailbox. Check the box to enable the feature and configure the parameters.

☒ **Auto Mail Feature**

From Address:

To Address:

SMTP Server:

☐ Enable Authentication

Username:

Password:

Confirm Password:

Time Mode:

☒ Fixation Time ☐ Period Time

Fixation Time:

00

:

00

(HH:MM)

From Address	Enter the sender's E-mail address.
To Address	Enter the receiver's E-mail address.
SMTP Server	Enter the IP address of the SMTP server.
Enable Authentication	You can check the box to enable mail server authentication. Enter the sender's mail account name and password.
Time Mode	Select Time Mode. System logs can be sent at specific time or time interval.
Fixation Time	If you select Fixation Time, specify a fixed time to send the system log mails. For example, 08:30 indicates that the mail will be sent at 8:30 am everyday. Time Mode: ☒ Fixation Time ☐ Period Time Fixation Time: 00 : 00 (HH:MM)
Period Time	If you select Period Time, specify a period time to regularly send the system log mail. For example, 6 indicates that the mail will be sent every six hours. Time Mode: ☐ Fixation Time ☒ Period Time Period Time: Hours(1-24)

Server

If Server is enabled, system logs will be sent to a server. You can enable the feature and enter its IP address and port.

☒ **Enable Server**

System Log Server IP:

0.0.0.0

System Log Server Port:

514

Nvram


Nvram (Non-volatile Random Access Memory) is a RAM that can still save data even if a device is power off. All TP-Link EAPs are equipped with Nvram. With this option enabled, the Nvram feature can help reserve the system logs when an EAP device is power off.

3.8.3 Device Account

When the EAP devices are adopted at the first time, their username and password will become the same as those of the EAP Controller which are specified at Basic Configurations. You can specify a new username and password for the adopted EAPs in batches.

Follow the steps below to change EAP devices' username and password.

1. Go to **System > Device Account**.



Wireless Settings | Wireless Control | **System** | Admin

Reboot Schedule | Log Setting | **Device Account** | LED | SSH | Management VLAN | Backup&Restore | Batch Upgrade | About

Current Username: Administrator1

Current Password: 123456

New Username:

New Password:

Apply

2. Specify a new username and password for the EAP devices.

3. Click **Apply**.


Note::

The new account will be applied to EAP devices but not the EAP Controller. To change the EAP Controller's username and password, please refer to [User Account](#).

3.8.4 LED

Follow the steps below to turn on or off the LED lights of the EAPs.

1. Go to **System > LED**.



Wireless Settings | Wireless Control | **System** | Admin

Reboot Schedule | Log Setting | Device Account | **LED** | SSH | Management VLAN | Backup&Restore | Batch Upgrade | About

LED: ☒ Turn On Apply


2. By default, the LED lights are on. You can check the box to change the light status.

3. Click **Apply** to save the configurations.

3.8.5 SSH

You can login to the EAP Controller via SSH. Deploy an SSH server on your network and follow the steps below to configure SSH on the EAP Controller:

1. Go to **System > SSH**.



The screenshot shows the configuration page for SSH. The top navigation bar has tabs for 'Wireless Settings', 'Wireless Control', 'System', and 'Admin'. The 'System' tab is selected. Below the navigation bar, there is a sub-menu with links: 'Reboot Schedule', 'Log Setting', 'Device Account', 'LED', 'SSH', 'Management VLAN', 'Backup&Restore', 'Batch Upgrade', and 'About'. The 'SSH' link is highlighted. The main content area contains the following fields:

- SSH Server Port:** A text input field with the value '22'. To its right, the range '(22, 1025-65535)' is displayed.
- SSH Login:** A checkbox that is currently unchecked.
- Apply:** A blue button to save the configuration.


2. Enter the port number of the SSH server.
3. Check the box to enable SSH Login.
4. Click **Apply**.

3.8.6 Management VLAN

Management VLAN provides a safer way for you to manage the EAP. With Management VLAN enabled, only the hosts in the management VLAN can manage the EAP. Since most hosts cannot process VLAN TAGs, connect the management host to the network via a switch, and set up correct VLAN settings for the switches on the network to ensure the communication between the host and the EAP in the management VLAN.

Follow the steps below to configure Management VLAN.

1. Go to **System > Management VLAN**.



The screenshot shows the configuration page for Management VLAN. The top navigation bar has tabs for 'Wireless Settings', 'Wireless Control', 'System', and 'Admin'. The 'System' tab is selected. Below the navigation bar, there is a sub-menu with links: 'Reboot Schedule', 'Log Setting', 'Device Account', 'LED', 'SSH', 'Management VLAN', 'Backup&Restore', 'Batch Upgrade', and 'About'. The 'Management VLAN' link is highlighted. The main content area contains the following fields:

- Management VLAN:** A checkbox labeled 'Enable' that is currently unchecked.
- Management VLAN ID:** A text input field with the value '1'. To its right, the range '(1-4094)' is displayed.
- Apply:** A blue button to save the configuration.


2. Check the box to enable Management VLAN.
3. Specify the Management VLAN ID.
4. Click **Apply**.

3.8.7 Backup&Restore

You can save the current configuration of the EAPs as a backup file and if necessary, and restore the configuration using the backup file. We recommend you back up the settings before upgrading the device.

Follow the steps below to backup and restore the configuration.

1. Go to **System > Backup&Restore**.




The screenshot shows the 'System' menu with 'Backup&Restore' highlighted. The page has two main sections: 'Backup' and 'Restore'. The 'Backup' section has a 'Backup' button. The 'Restore' section has a 'Restore File:' label, a text input field, a 'Browse' button, and a 'Restore' button.

2. Click **Backup** and save the backup file.
3. If necessary, click **Browse** to locate and choose the backup file. Then click **Restore** to restore the configuration.

3.8.8 Batch Upgrade

Follow the steps below to upgrade the EAP devices in batches according to their model.

1. Visit <http://www.tp-link.com/en/support/download/> to download the latest firmware file of the corresponding model.
2. Go to **System > Batch Upgrade**.



The screenshot shows the 'System' menu with 'Batch Upgrade' highlighted. The page has three main sections: 'EAP Amount' with a value of '0', 'EAP Model' with a dropdown menu showing 'EAP330 2.0', and 'Upgrade File' with a text input field, a 'Browse' button, and an 'Upgrade' button. A note at the bottom states: 'Note : In all the sites, all the managed EAPs matched with the selected model will be upgraded.'

3. Select the EAP model.
4. Click **Browse** to locate and choose the proper firmware file for the model.
5. Click **Upgrade** to upgrade the device.
6. After upgrading, the device will reboot automatically.

Note::

To avoid damage, please do not turn off the device while upgrading.

4 Configure the EAPs Separately

In addition to global configuration, you can configure the EAPs separately and the configuration results will be applied to a specified EAP device.

To configure a specified EAP, please click the EAP's name on the **Access Points** tab or click  of connected EAP on the map. Then you can view the EAP's detailed information and configure the EAP on the pop-up window.


This chapter includes the following contents:

- *View the Information of the EAP*
- *View Clients Connecting to the EAP*
- *Configure the EAP*

4.1 View the Information of the EAP


4.1.1 Overview

Click **Overview** to view the basic information including EAP's MAC address (or name you set), IP address, model, firmware version, the usage rate of CPU and Memory and uptime (indicates how long the EAP has been running without interruption).




4.1.2 LAN

Click **LAN** to view the traffic information of the LAN port, including the total number of packets, the total size of data, the total number of packets loss, and the total size of error data in the process of receiving and transmitting data.



4.1.3 Radio


Click **Radio** to view the radio information including the frequency band, the wireless mode, the channel width, the channel, and the transmitting power. At 2.4GHz, you can also view parameters of receiving/transmitting data.



4.2 View Clients Connecting to the EAP


4.2.1 User

The **User** page displays the information of clients connecting to the SSID with Portal disabled, including their MAC addresses and connected SSIDs. You can click the client's MAC address to get its connection history.



4.2.2 Guest

The **Guest** page displays the information of clients connecting to the SSID with Portal enabled, including their MAC addresses and connected SSIDs. You can click the client's MAC address to get its connection history.




The screenshot shows a web interface for a connected client with MAC address 00:0a:eb:21:23:24. The 'Guest' tab is selected. Below the tabs is a search bar labeled 'MAC, SSID'. A table displays the following information:

MAC Address	SSID
E8-80-2E-EB-6B-EB	SSID1

At the bottom, there are pagination controls showing '<<' '<' '1' '>' '>>' and '1/1', along with a 'GO' button.

4.3 Configure the EAP


The **Configuration** page allows you to configure the EAP. All the configurations will only take effect on this device.



The screenshot shows the 'Configuration' page for the same client. The 'Configuration' tab is selected. The 'Basic Config' section is expanded, showing a 'Name' field with the value '00:0a:eb:99:97:c7' and an 'Apply' button. Below this are several other sections: 'IP Setting', 'Radio', 'Load Balance', 'WLANS', 'Rogue AP Detection', and 'Forget this AP', each with a collapse icon.

4.3.1 Basic Config


Here you can change the name of the EAP.



This is a close-up of the 'Basic Config' section from the previous screenshot. It shows the 'Name' field containing '00:0a:eb:99:97:c7' and the 'Apply' button.

4.3.2 IP Setting

You can configure an IP address for this EAP. Two options are provided: DHCP and Static.



The IP Setting window has a title bar with 'IP Setting' and a close button. It contains two radio buttons: 'DHCP' (selected) and 'Static'. Below these are four fields: 'Fallback IP:' with a checked 'Enable' checkbox, 'Fallback IP Address:' with the value '192.168.0.254', 'Fallback IP Mask:' with the value '255.255.255.0', and 'Fallback Gateway:' which is empty. An 'Apply' button is at the bottom left.

Get a Dynamic IP Address From the DHCP Server


1. Configure your DHCP server.
2. Select **DHCP** on the page above.
3. Enable the Fallback IP feature. When the device cannot get a dynamic IP address, the fallback IP address will be used.
4. Set IP address, IP mask and gateway for the fallback address and click **Apply**.

Manually Set a Static IP Address for the EAP

1. Select **Static**.
2. Set the IP address, IP mask and gateway for the static address and click **Apply**.

4.3.3 Radio

Radio settings directly control the behavior of the radio in the EAP device and its interaction with the physical medium; that is, how and what type of signal the EAP device emits.



The Radio window has a title bar with 'Radio' and a close button. It features two tabs: '2.4GHz' (selected) and '5GHz'. Below the tabs are five settings: 'Status:' with a checked 'Enable' checkbox, 'Mode:' with a dropdown menu showing '802.11b/g/n mix', 'Channel Width:' with a dropdown menu showing '20 / 40MHz', 'Channel:' with a dropdown menu showing 'Auto', and 'Tx Power:' with a dropdown menu showing 'High'. An 'Apply' button is at the bottom left.

Select the frequency band (2.4GHz/5GHz) and configure the following parameters.

Status	Enabled by default. If you disable the option, the radio on the frequency band will turn off.
Mode	Select the IEEE 802.11 mode the radio uses. When the frequency of 2.4GHz is selected, 802.11b/g/n mixed, 802.11b/g mixed, and 802.11n only modes are available: 802.11b/g/n mixed: All of 802.11b, 802.11g, and 802.11n clients operating in the 2.4GHz frequency can connect to the EAP device. We recommend you select the 802.11b/g/n mixed mode. 802.11b/g mixed: Both 802.11b and 802.11g clients can connect to the EAP device. 802.11n only: Only 802.11n clients can connect to the EAP device. When the frequency of 5GHz is selected, 802.11 n/ac mixed, 802.11a/n mixed, 802.11 ac only, 802.11a only, and 802.11n only modes are available: 802.11n/ac mixed: Both 802.11n clients and 802.11ac clients operating in the 5GHz frequency can connect to the EAP device. 802.11a/n mixed: Both 802.11a clients and 802.11n clients operating in the 5GHz frequency can connect to the EAP device. 802.11ac only: Only 802.11ac clients can connect to the EAP device. 802.11a only: Only 802.11a clients can connect to the EAP device. 802.11n only: Only 802.11n clients can connect to the EAP device.
Channel Width	Select the channel width of the EAP device. For EAP 110/120/220, the options includes 20MHz, 40MHz and 20/40MHz. For EAP 320/330, the options includes 20MHz, 40MHz, 80MHz and 20/40/80MHz. The 20/40 MHz and 20/40/80MHz channels enable higher data rates but leave fewer channels available for use by other 2.4GHz and 5GHz devices. When the radio mode includes 802.11n, we recommend you set the channel bandwidth to 20/40 MHz or 20/40/80MHz to improve the transmission speed.
Channel	Select the channel used by the EAP device to improve wireless performance. The range of available channels is determined by the radio mode and the country setting. If you select Auto for the channel setting, the EAP device scans available channels and selects a channel where the least amount of traffic is detected.
Tx Power	Select the TX Power (transmit power) in the 4 options: Low, Medium, High and Custom. Low, Medium and High are based on the Max TxPower (maximum transmit power. It may vary among different countries and regions). Low: Max TxPower * 20% (round off the value) Medium: Max TxPower * 60% (round off the value) High: Max TxPower Custom: Enter a value manually.

4.3.4 Load Balance

By setting the maximum number of clients accessing the EAPs, Load Balance helps to achieve rational use of network resources.

Load Balance

2.4GHz5GHz

Max Associated Clients:

☐ Enable

1

(1-99)

RSSI Threshold:

☐

0

(-95-0 dBm)

Apply

Select the frequency band (2.4GHz/5GHz) and configure the parameters.

Max Associated Clients	Enable this function and specify the maximum number of connected clients. While more clients requesting to connect, the EAP will disconnect those with weaker signals.
RSSI Threshold	Enable this function and enter the threshold of RSSI (Received Signal Strength Indication). When the clients' signal is weaker than the RSSI Threshold you've set, the clients will be disconnected from the EAP.

4.3.5 WLANs

You can specify a different SSID name and password to override the previous SSID. After that, clients can only see the new SSID and use the new password to access the network. Follow the steps below to override the SSID.

WLANs

2.4GHz5GHz

WLAN Group

Default

Name	Overrides	Action
SSID1		

1. Select the frequency band and WLAN group.
2. Click and the following window will pop up.

SSID Override(SSID1)

Enable: ☒ Enable On AP

VLAN: ☐ Use VLAN ID (1-4094)

SSID:

PSK: (WPA-PSK)

Apply

3. Check the box to enable the feature.
4. You can join the overridden SSID in to a VLAN. Check the **Use VLAN ID** box and specify a VLAN ID.
5. Specify a new name and password for the SSID.
6. Click **Apply** to save the configuration.

4.3.6 Trunk Settings

Only EAP330 supports this function.

The trunk function can bundles multiple Ethernet links into a logical link to increase bandwidth and improve network reliability.

Trunk Settings

Status: ☐ Enable

Mode:

Apply

Status	Enable this function. The EAP330 has two 1000Mbps Ethernet ports. If the Trunk function is enabled and the ports are in the speed of 1000Mbps Full Duplex, the whole bandwidth of the trunk link is up to 4Gbps (2000Mbps * 2).
Mode	Select the applied mode of Trunk Arithmetic. • SRC MAC + DST MAC: When this option is selected, the arithmetic will be based on the source and destination MAC addresses of the packets. • DST MAC: When this option is selected, the arithmetic will be based on the destination MAC addresses of the packets. • SRC MAC: When this option is selected, the arithmetic will be based on the source MAC addresses of the packets.

4.3.7 Rouge AP Detection

With this option enabled, the EAP device will detect rouge APs in all channels.

Rogue AP Detection

Rogue Status:
☐ Enable
☒ Disable

Apply

4.3.8 Forget this AP

If you no longer want to manage this EAP, you may remove it. All the configurations and history about this EAP will be deleted. It is recommended to back up the configurations of this EAP before you forget it.

Forget this AP

If you no longer wish to manage this AP, you may remove it. Note that all configurations and history with respect to this AP will be lost.

Forget

4.3.9 Local LAN Port VLAN Settings

Only EAP115-Wall supports this function.

This feature is used to add the EAP to a specific VLAN. With this feature enabled, the hosts connected to this EAP can only communicate with the devices in the same VLAN.

Local LAN Port VLAN Settings

Status:
☐ Enable

VLAN ID:
(1-4094)

Apply

Status	Enable this function.
Mode	Specify the VLAN that the EAP is added to. The valid values are from 1 to 4094, and the default is 1.

5


Manage the EAP Controller

This chapter mainly introduces how to manage the user account and configure system settings. This chapter includes the following contents.

- *Information About the Software*
- *User Account*
- *Controller Settings*

5.1 Information About the Software

You can view the EAP Controller's version and copyright information on the **About** page.




5.2 User Account

You can use different user account to log in to the EAP Controller. User has three roles: administrator, operator and observer. The administration authority varies among different roles.

Administrator	The first administrator account is created in the Basic Configuration process and this account can not be deleted. An administrator can change the settings of the EAP network and create and delete user accounts.
Operator	An operator account can be created or deleted by the administrator. The operator can change the settings of the EAP network.
Observer	An observer account can be created or deleted by the administrator. The observer can only view the status and settings of the EAP network but not change the settings.

Follow the steps below to add user account.

1. Go to **Admin > User Settings**.



2. Click **+ Add** and the following window will pop up.

The screenshot shows the 'Add User' dialog box. It has the following fields: Username (text input), Email (text input), Role (dropdown menu with 'operator' selected), Password (password input), Confirm Password (password input), and Site Privileges (checkboxes for 'Default' and 'Office A'). There is an 'Apply' button at the bottom left.

3. Specify the username, Email and password of the account.
4. Select the role from the drop-down list.
 - If you select **operator** or **observer**, you also need to select the **Site Privileges**.
 - If you select **administrator**, the **Site Privileges** option will not appear and all sites are available for the administrator user.
5. Click **Apply** to add the user account.

Note:

You can refer to the **Role** page to view the user role's type, description information, permission scope and created time.


5.3 Controller Settings

You can configure the EAP Controller's hostname and IP address. In addition, we recommend you configure the Mail server to reset your login password when you forget it.

5.3.1 Configure Controller Hostname/IP

Follow the steps below to configure the hostname or IP address of the EAP Controller.

1. Go to **Admin > Controller Settings** and click **EAP Controller**.



The screenshot shows the 'Admin' tab selected in the top navigation bar. Below it, the 'Controller Settings' link is highlighted in the breadcrumb trail. The main content area is titled 'EAP Controller:'. It contains a text input field for 'Controller Hostname/IP' with the value '127.0.0.1'. Below the input field is a blue 'Apply' button. At the bottom of the section, there is a 'Mail Server:' label and a collapsed section indicated by a downward arrow.

2. Enter the hostname or IP address of the EAP Controller.
3. Click **Apply** to save the configuration.

5.3.2 Configure Mail Server

With the Mail Server, you can reset the password of the user account and receive notifications from the EAP Controller. It is different from the SMTP Server, which is just for the syslog emails sending.

Follow the steps below to configure mail server.

1. Go to **Admin > Controller Settings**.

2. Click **Mail Server**, check the box to enable SMTP Server, and then the following screen will appear.

The screenshot shows the 'Admin' tab selected in the top navigation bar. Below it, the 'Controller Settings' link is highlighted. The main content area is titled 'EAP Controller:' and contains a 'Mail Server:' section. In this section, the 'Enable SMTP Server' checkbox is checked. The 'Mail Server' field is empty, and the 'Port' field contains the value '25'. There is an 'Enable SSL' checkbox which is unchecked. Below these are fields for 'Enable Auth' (unchecked), 'Username', 'Password', and 'Specify Sender Address', all of which are currently empty. An 'Apply' button is located at the bottom left of the configuration area.

3. Configure the following parameters.

Mail Server	Enter the IP address or domain of SMTP Server.
Port	The default is 25. You can enable SSL (Security Socket Layer) to enhance secure communications over the Internet. If SSL is enabled, the port number will automatically change to 465.
Enable Auth	Select this option to enable authentication.
Username/Password	If you enable authentication, enter the username and password required by the mail server.
Specify Sender Address	Specify the sender's mail address. Enter the email address that will appear as the sender of the warning email.

4. Click **Apply** to save the configuration.

Note:

Specify the account email address based on the Mail server to receive the notifications.

6 *Application Example*

A restaurant has a wireless network with three EAPs managed by the EAP Controller. The network administrator wants to :


- Monitor the EAPs with the Map.
- Enable Portal function to drive customers' attention to the ads of the supermarket when customers attempt to access the network. The costumers need to use a simple password to pass the authentication.
- Allow the employees of the restaurant to access the network resources without portal authentication.
- Schedule the radio to operate only during the working time (8:00 am to 22:00 pm) in order to reduce power consumption.

Follow the steps below to achieve the requirements above.

6.1 Basic Configuration

Follow the steps below to do the basic configuration.

1. Connect the hardware by referring to the following topology.



2. Install the EAP Controller on Host A.
3. Launch the software and follow the instructions to complete some initial configurations.
4. Log into the management interface.
5. Adopt the pending EAP devices.


6.2 Advanced Settings

After the basic configuration, refer to the following content to meet the network administrator's requirements.

6.2.1 Monitor the EAPs with Map

Follow the steps below to create a map and monitor the EAPs with the map.

1. Go to the **Map**.
2. Import a local map and set the map scale.
3. Drag the EAPs to the appropriate locations on the map.
4. Click **Coverage** and you can see the representation of the EAPs' wireless coverage.



6.2.2 Configure Portal Authentication

Follow the steps below to configure Portal function.

1. Go to **Basic Wireless Settings** and edit the SSID we created in the basic configuration.

Edit SSID

Basic Info

SSID Name:

SSID1

Wireless Vlan ID:

0

(0-4094, 0 is used to disable VLAN tagging.)

SSID Broadcast:

☒ Enable

Security Mode:

None

SSID Isolation:

☐ Enable

Access Control Rule:

None

Rate Limit

Apply

To make it easier for customers to connect, change the Security Mode from WPA-PSK to None. Customers can connect to the EAPs without password and be redirected to the Portal Authentication where the correct password will be required.

2. Open the global configuration window and go to **Portal**. Click **+ Add a New Portal**. The configuration window will pop up.
3. In the **Basic Info** section, complete the basic settings for the portal.

Basic Info

Portal Name:

Guest

SSID:

SSID1

Authentication Type:

Simple Password

Password:

restaurantabc

Authentication Timeout:

1 Hour

Redirect:

☒ Enable

Redirect URL:

http://www.restaurant.com

- 1) Specify a name for the portal.
 - 2) Select an SSID for the portal.
 - 3) Select the Authentication Type as Simple Password. Specify a simple password for the guests.
 - 4) Select the **Authentication Timeout**. For example, 1 Hour is suitable for the customers at the restaurant.
 - 5) Enable the **Redirect** to drive the costumers to the restaurant's homepage after successful login. We can put some promotion information on the page.
4. In the **Login Page** section, configure the login page.

5. In the Advertisement section, upload two pictures of the restaurant and set the related parameters.

6. Click **Apply**.

6.2.3 Create a SSID for the Employees

We have created a SSID in the basic configuration for the customers. Here we need to create another SSID for the employees to allow them to access the network without portal authentication. In addition, the new SSID should be invisible for the customers.

Follow the steps below to create a SSID for the employees.

1. Open the global configuration window and go to **Basic Wireless Settings**.

2. Click **Add** to add a new SSID.

The screenshot shows a configuration window titled "Add 2.4GHz SSID". It has a "Basic Info" tab. The fields are as follows:

- SSID Name: SSID2
- Wireless Vlan ID: 0 (0-4094, 0 is used to disable VLAN tagging.)
- SSID Broadcast: ☒ Enable
- Security Mode: WPA-PSK (dropdown)
- Version: ☐ Auto ☐ WPA-PSK ☒ WPA2-PSK
- Encryption: ☐ Auto ☐ TKIP ☒ AES
- Wireless Password: restaurant123
- Group Key Update Period: 0 seconds(30-8640000, 0 means no upgrade).
- SSID Isolation: ☐ Enable
- Access Control Rule: None (dropdown)

At the bottom, there is a "Rate Limit" section and an "Apply" button.

Configure the parameters.

- 1) Disable the **SSID Broadcast** to hide this SSID from the customers.
- 2) Specify the **SSID Name**, **Security Mode** and **Wireless Password**. Let the employees manually enter the SSID name and password, and choose the security mode you set to access the network.
- 3) Click **Apply** to save the configuration.

6.2.4 Configure Scheduler

Follow the steps below to schedule the radio to operate only during the working time (from 8:00 to 22:00).

1. Open the global configuration window and go to **Scheduler**.

- 1) Add a profile.

The screenshot shows a configuration window titled "Add a Profile". It has a single field:

- Profile Name: Working-time on

At the bottom, there is an "Apply" button.

- 2) Add an item for the profile. The parameters are set as shown on the following screen.

Add an Item

Day Mode:
☐ Weekday
☐ Weekend
☒ Everyday
☐ Custom

☒ Mon
☒ Tue
☒ Wed
☒ Thu
☒ Fri
☒ Sat
☒ Sun

Time:
☐ all day-24 hours

Start Time:
08 : 00

End Time:
22 : 00

Apply

2. Go to **Scheduler Association** tab.

Wireless Settings
Wireless Control
System
Admin

Access Control | Portal | Free Authentication Policy | MAC Filter | MAC Filter Association | Scheduler | Scheduler Association | QoS

Scheduler:
☒ Enable

Association Mode:
Associated with SSID

Apply

2.4GHz
5GHz
Default

ID	SSID Name	Band	Profile Name	Action	Setting
1	SSID1	2.4GHz	Working-time on	Radio On	Apply
2	SSID2	2.4GHz	Working-time on	Radio On	Apply

<<
<
1
>
>>
A total of 1 page(s)
Page to
GO

- 1) Enable the function and select **Associated with SSID**. Click **Apply**.
- 2) In the **Profile Name** column of both SSIDs, select the profile we just created.
- 3) In the **Action** column of both SSIDs, select **Radio On**.
- 4) Click **Apply** in the **Setting** column of both SSIDs.
- 5) Select **5GHz** and do the same configurations as above.

COPYRIGHT & TRADEMARKS

Specifications are subject to change without notice.  **tp-link** is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders.

No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-Link Technologies Co., Ltd. Copyright © 2017 TP-Link Technologies Co., Ltd.. All rights reserved.