

FCC RF EXPOSURE REPORT


FCC ID: 2AXJ4EAP6100D

Project No. : 2101C073A
Equipment : AX1800 Indoor/Outdoor Wi-Fi 6 Access Point
Brand Name : tp-link
Test Model : EAP610-Outdoor
Series Model : N/A
Applicant : TP-Link Corporation Limited
Address : Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road,
Tsim Sha Tsui, Kowloon, Hong Kong
Manufacturer : TP-Link Corporation Limited
Address : Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road,
Tsim Sha Tsui, Kowloon, Hong Kong
Date of Receipt : Mar. 04, 2021
Date of Test : Apr. 12, 2021 ~ Jul. 22, 2021
Issued Date : Aug. 13, 2021
Report Version : R00
Test Sample : Engineering Sample No.: DG202105205
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Sheldon Ou



Approved by : Ethan Ma



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's
Republic of China
Tel: +86-769-8318-3000
Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Aug. 13, 2021

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Antenna Specification:

For 2.4GHz:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.53
2	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.48

Note:

- 1) This EUT supports CDD, and all antenna gains are not equal, Directional gain=10log[(10^{G1/20}+10^{G2/20}+...10^{GN/20})²/N]dBi, that is Directional gain=10log[(10^{4.53/20}+10^{4.48/20})²/2]dBi =7.52. So, the output power limit is 30-(7.52-6)=28.48, the power spectral density limit is 8-(7.52-6)=6.48.
- 2) Beamforming Gain: 3 dB. Then, Directional gain=3+4.53=7.53. So the output power limit is 30-(7.53-6)=28.47.
- 3) The antenna gain and beamforming gain are provided by the manufacturer.

For 5GHz:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)	Note
1	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.53	UNII-1
2	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.14	
1	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.95	UNII-3
2	tp-link	EAP610-Outdoor 1.0	Internal	N/A	5.04	

Note:

- 1) This EUT supports CDD, and all antenna gains are not equal, Directional gain=10log[(10^{G1/20}+10^{G2/20}+...10^{GN/20})²/N]dBi. Then,
For UNII-1: Directional gain=10log[(10^{4.53/20}+10^{4.14/20})²/2]dBi =7.35. So, the output power limit is 30-(7.35-6)=28.65, the power spectral density limit is 17-(7.35-6)=15.65.
For UNII-3: Directional gain=10log[(10^{4.95/20}+10^{5.04/20})²/2]dBi =8.01. So, the output power limit is 30-(8.01-6)=27.99, the power spectral density limit is 30-(8.01-6)=27.99.
- 2) Beamforming Gain: 3 dB. Then,
For UNII-1: Directional gain=3+4.53=7.53. So the output power limit is 30-(7.53-6)=28.47.
For UNII-3: Directional gain=3+5.04=8.04. So the output power limit is 30-(8.04-6)=27.96.
- 3) The antenna gain and beamforming gain are provided by the manufacturer.

Table for Antenna Configuration:
For 2.4GHz Non Beamforming:

Operating Mode TX Mode	2TX
IEEE 802.11b	V (Ant. 1+Ant. 2)
IEEE 802.11g	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT20)	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)	V (Ant. 1+Ant. 2)

For 2.4GHz Beamforming:

Operating Mode TX Mode	2TX
IEEE 802.11n(HT20)	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)	V (Ant. 1+Ant. 2)

For 5GHz Non Beamforming:

Operating Mode TX Mode	2TX
IEEE 802.11a	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT20)	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT20)	V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT80)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE80)	V (Ant. 1+Ant. 2)

For 5GHz Beamforming:

Operating Mode	TX Mode	2TX
IEEE 802.11n(HT20)		V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)		V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT20)		V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT40)		V (Ant. 1+Ant. 2)
IEEE 802.11ac(VHT80)		V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)		V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)		V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE80)		V (Ant. 1+Ant. 2)

3. TEST RESULTS

For 2.4GHz Non Beamforming:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.52	5.6494	27.73	592.9253	0.42671	1	Complies

For 2.4GHz Beamforming:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.53	5.6624	27.08	510.5050	0.36824	1	Complies

For 5GHz Non Beamforming:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.01	6.3241	27.60	575.4399	0.46359	1	Complies

For 5GHz Beamforming:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.04	6.3680	27.11	514.0437	0.41699	1	Complies

For the max simultaneous transmission MPE:

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4GHz	5GHz			
0.42671	0.46359	0.8903	1	Complies

Note: The calculated distance is 25 cm.
Output power including tune up tolerance.

End of Test Report