FCC Radio Test Report

FCC ID: 2AXJ4EAP610OD

This report concerns: Original Grant

Project No.	:	2101C073A
Equipment	:	AX1800 Indoor/Outdoor Wi-Fi 6 Access Point
Brand Name	:	tp-link
Test Model	:	EAP610-Outdoor
Series Model	:	N/A
Applicant	:	TP-Link Corporation Limited
Address	:	Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road, Tsim Sha Tsui, Kowloon, Hong Kong
Manufacturer	:	TP-Link Corporation Limited
Address	:	Room 901, 9/F. , New East Ocean Centre, 9 Science Museum Road, Tsim Sha Tsui, Kowloon, Hong Kong
Date of Receipt	:	Mar. 04, 2021
Date of Test	:	Apr. 12, 2021 ~ Jul. 22, 2021
Issued Date	:	Aug. 13, 2021
Report Version	:	R00
Test Sample	:	Engineering Sample No.: DG202105205 for conducted, DG202105206 for radiated.
Standard(s)	:	FCC CFR Title 47, Part 15, Subpart C FCC KDB 558074 D01 15.247 Meas Guidance v05r02 FCC KDB 662911 D01 Multiple Transmitter Output v02r01 ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Sheldon Ou

Approved by : Ethan Ma

TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.
Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents Page

REPORT ISSUED HISTORY 6

1 . SUMMARY OF TEST RESULTS 7

1.1 TEST FACILITY 8

1.2 MEASUREMENT UNCERTAINTY 8

1.3 TEST ENVIRONMENT CONDITIONS 9

2 . GENERAL INFORMATION 10

2.1 GENERAL DESCRIPTION OF EUT 10

2.2 DESCRIPTION OF TEST MODES 12

2.3 PARAMETERS OF TEST SOFTWARE 14

2.4 DUTY CYCLE 15

2.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 17

2.6 SUPPORT UNITS 17

3 . AC POWER LINE CONDUCTED EMISSIONS 18

3.1 LIMIT 18

3.2 TEST PROCEDURE 18

3.3 DEVIATION FROM TEST STANDARD 18

3.4 TEST SETUP 19

3.5 EUT OPERATION CONDITIONS 19

3.6 TEST RESULTS 19

4 . RADIATED EMISSIONS 20

4.1 LIMIT 20

4.2 TEST PROCEDURE 21

4.3 DEVIATION FROM TEST STANDARD 22

4.4 TEST SETUP 22

4.5 EUT OPERATION CONDITIONS 23

4.6 TEST RESULTS - 9 KHZ TO 30 MHZ 23

4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ 23

4.8 TEST RESULTS - ABOVE 1000 MHZ 23

5 . BANDWIDTH 24

5.1 LIMIT 24

5.2 TEST PROCEDURE 24

5.3 DEVIATION FROM STANDARD 24

5.4 TEST SETUP 24

Table of Contents Page

5.5 EUT OPERATION CONDITIONS 24
5.6 TEST RESULTS 24
6 . MAXIMUM AVERAGE OUTPUT POWER 25
6.1 LIMIT 25
6.2 TEST PROCEDURE 25
6.3 DEVIATION FROM STANDARD 25
6.4 TEST SETUP 25
6.5 EUT OPERATION CONDITIONS 25
6.6 TEST RESULTS 25
7 . CONDUCTED SPURIOUS EMISSIONS 26
7.1 LIMIT 26
7.2 TEST PROCEDURE 26
7.3 DEVIATION FROM STANDARD 26
7.4 TEST SETUP 26
7.5 EUT OPERATION CONDITIONS 26
7.6 TEST RESULTS 26
8 . POWER SPECTRAL DENSITY 27
8.1 LIMIT 27
8.2 TEST PROCEDURE 27
8.3 DEVIATION FROM STANDARD 27
8.4 TEST SETUP 27
8.5 EUT OPERATION CONDITIONS 27
8.6 TEST RESULTS 27
9 . MEASUREMENT INSTRUMENTS LIST 28
10 . EUT TEST PHOTO 30
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS 35
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ 38
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ 43
APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ 46
APPENDIX E - BANDWIDTH 167
APPENDIX F - MAXIMUM AVERAGE OUTPUT POWER 174
APPENDIX G - CONDUCTED SPURIOUS EMISSIONS 185

Table of Contents

Page

APPENDIX H - POWER SPECTRAL DENSITY **210**

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Aug. 13, 2021

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	**Test Item**	**Test Result**	**Judgment**	**Remark**
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	------
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	------
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	------
15.247(b)(3)	Maximum Average Output Power	APPENDIX F	PASS	------
15.247(d)	Conducted Spurious Emissions	APPENDIX G	PASS	------
15.247(e)	Power Spectral Density	APPENDIX H	PASS	------
15.203	Antenna Requirement	------	PASS	Note(2)

Note:

(1) “N/A” denotes test is not applicable in this test report.

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China.
BTL's Test Firm Registration Number for FCC: 357015
BTL's Designation Number for FCC: CN1240

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))
The BTL measurement uncertainty as below table:

A. AC power line conducted emissions test:

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150kHz ~ 30MHz	2.68

B. Radiated emissions test:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9kHz ~ 30MHz	-	3.02
		30MHz ~ 200MHz	V	4.26
		30MHz ~ 200MHz	H	3.38
		200MHz ~ 1,000MHz	V	3.98
		200MHz ~ 1,000MHz	H	3.94
		1GHz ~ 6GHz	-	3.96
		6GHz ~ 18GHz	-	5.24
		18GHz ~ 26.5GHz	-	3.62
		26.5GHz ~ 40GHz	-	4.00

C. Other Measurement:

Test Item	Uncertainty
Bandwidth	±3.8 %
Maximum Output Power	±0.95 dB
Conducted Spurious Emission	±2.71 dB
Power Spectral Density	±0.86 dB
Temperature	±0.08 °C
Humidity	±1.5%

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	25°C	53%	AC 120V/60Hz	Wade Liang
Radiated Emissions-9kHz to 30 MHz	25°C	60%	AC 120V/60Hz	Laughing Zhang
Radiated Emissions-30MHz to 1000MHz	26°C	52%	AC 120V/60Hz	Hayden Chen
Radiated Emissions-Above 1000MHz	24°C	60%	AC 120V/60Hz	Berton Luo
Bandwidth	22°C	53%	AC 120V/60Hz	Jesse Wang
Maximum Average Output Power	23°C	52%	AC 120V/60Hz	Howard Wei
Conducted Spurious Emissions	22°C	53%	AC 120V/60Hz	Jesse Wang
Power Spectral Density	22°C	53%	AC 120V/60Hz	Jesse Wang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	AX1800 Indoor/Outdoor Wi-Fi 6 Access Point
Brand Name	tp-link
Test Model	EAP610-Outdoor
Series Model	N/A
Model Difference(s)	N/A
Power Source	1# DC voltage supplied from POE adapter. Model: TL-POE4824G 2# Supplied from Switch.
Power Rating	1# I/P: 100-240V~ 50/60Hz 0.8A O/P: 48V ⎓ 0.5A +4,5pins; -7,8pins 2# 802.3at PoE 42-57V
Operation Frequency	2412 MHz ~ 2462 MHz
Modulation Type	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: OFDM IEEE 802.11ax: OFDMA
Bit Rate of Transmitter	IEEE 802.11b: 11/5.5/2/1 Mbps IEEE 802.11g: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 300 Mbps IEEE 802.11ax: up to 573.6 Mbps
Maximum Average Output Power _Non Beamforming	IEEE 802.11g: 27.53 dBm (0.5662 W)
Maximum Average Output Power _Beamforming	IEEE 802.11ax(HE20): 26.88 dBm (0.4875 W)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

CH01 - CH11 for IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20), IEEE 802.11ax(HE20) CH03 - CH09 for IEEE 802.11n(HT40), IEEE 802.11ax(HE40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Antenna Specification:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.53
2	tp-link	EAP610-Outdoor 1.0	Internal	N/A	4.48

Note:

1) This EUT supports CDD, and all antenna gains are not equal, Directional gain=10log[$(10^{G1/20}+10^{G2/20}+...10^{GN/20})^2$/N]dBi, that is Directional gain=10log[$(10^{4.53/20}+10^{4.48/20})^2$/2]dBi =7.52. So, the output power limit is 30-(7.52-6)=28.48, the power spectral density limit is 8-(7.52-6)=6.48.
2) Beamforming Gain: 3 dB. Then, Directional gain=3+4.53=7.53. So the output power limit is 30-(7.53-6)=28.47.
3) The antenna gain and beamforming gain are provided by the manufacturer.

4. Table for Antenna Configuration:
For Non Beamforming:

Operating Mode / TX Mode	2TX
IEEE 802.11b	V (Ant. 1+Ant. 2)
IEEE 802.11g	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT20)	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)	V (Ant. 1+Ant. 2)

For Beamforming:

Operating Mode / TX Mode	2TX
IEEE 802.11n(HT20)	V (Ant. 1+Ant. 2)
IEEE 802.11n(HT40)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE20)	V (Ant. 1+Ant. 2)
IEEE 802.11ax(HE40)	V (Ant. 1+Ant. 2)

2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX B Mode Channel 01/06/11
Mode 2	TX G Mode Channel 01/06/11
Mode 3	TX N(HT20) Mode Channel 01/06/11
Mode 4	TX N(HT40) Mode Channel 03/06/09
Mode 5	TX AX(HE20) Mode Channel 01/06/11
Mode 6	TX AX(HE40) Mode Channel 03/06/09
Mode 7	TX G Mode Channel 06
Mode 8	TX B Mode Channel 01/02/06/10/11
Mode 9	TX G Mode Channel 01/02/06/10/11
Mode 10	TX N(HT20) Mode Channel 01/02/06/10/11
Mode 11	TX N(HT40) Mode Channel 03/04/06/08/09
Mode 12	TX AX(HE20) Mode Channel 01/02/06/10/11
Mode 13	TX AX(HE40) Mode Channel 03/04/06/08/09

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 7	TX G Mode Channel 06

Radiated emissions test - Below 1GHz	
Final Test Mode	Description
Mode 7	TX G Mode Channel 06

Radiated emissions test- Above 1GHz_Non Beamforming	
Final Test Mode	Description
Mode 8	TX B Mode Channel 01/02/06/10/11
Mode 9	TX G Mode Channel 01/02/06/10/11
Mode 10	TX N(HT20) Mode Channel 01/02/06/10/11
Mode 11	TX N(HT40) Mode Channel 03/04/06/08/09
Mode 12	TX AX(HE20) Mode Channel 01/02/06/10/11
Mode 13	TX AX(HE40) Mode Channel 03/04/06/08/09

Maximum Average Output Power test_Non Beamforming	
Final Test Mode	Description
Mode 1	TX B Mode Channel 01/06/11
Mode 2	TX G Mode Channel 01/06/11
Mode 3	TX N(HT20) Mode Channel 01/06/11
Mode 4	TX N(HT40) Mode Channel 03/06/09
Mode 5	TX AX(HE20) Mode Channel 01/06/11
Mode 6	TX AX(HE40) Mode Channel 03/06/09

Maximum Average Output Power test_Beamforming	
Final Test Mode	Description
Mode 3	TX N(HT20) Mode Channel 01/06/11
Mode 4	TX N(HT40) Mode Channel 03/06/09
Mode 5	TX AX(HE20) Mode Channel 01/06/11
Mode 6	TX AX(HE40) Mode Channel 03/06/09

Other Conducted test_Non Beamforming	
Final Test Mode	Description
Mode 1	TX B Mode Channel 01/06/11
Mode 2	TX G Mode Channel 01/06/11
Mode 3	TX N(HT20) Mode Channel 01/06/11
Mode 4	TX N(HT40) Mode Channel 03/06/09
Mode 5	TX AX(HE20) Mode Channel 01/06/11
Mode 6	TX AX(HE40) Mode Channel 03/06/09

NOTE:
(1) All the bit rate of transmitter have been tested and found the lowest rate is found to be the worst case and recorded.
(2) For AC power line conducted emissions and radiated emission below 1 GHz test, the TX G Mode Channel 06 is found to be the worst case and recorded.
(3) For radiated emission above 1 GHz test, the spurious points of 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
(4) The measurements for Output Power are tested, the Non Beamforming and Beamforming are recorded in the report. The worst case is Non Beamforming and only the worst case is documented for other test items.
(5) IEEE 802.11ax mode only supports full RU, so only the full RU is evaluated and measured inside report.

2.3 PARAMETERS OF TEST SOFTWARE

Test Software Version	QSPR

2.4 DUTY CYCLE

If duty cycle is ≥ 98 %, duty factor is not required.
If duty cycle is < 98 %, duty factor shall be considered.
The output power = measured power + duty factor.

IEEE 802.11b



Date: 17.MAR.2021 16:51:18

Duty cycle = 1.984 ms / 2.088 ms = 95.02%
Duty Factor = 10 log(1/Duty cycle) = 0.22

IEEE 802.11g



Date: 17.MAR.2021 16:51:31

Duty cycle = 1.990 ms / 2.095 ms = 94.99%
Duty Factor = 10 log(1/Duty cycle) = 0.22

IEEE 802.11n(HT20)



Date: 17.MAR.2021 16:52:03

Duty cycle = 5.446 ms / 5.670 ms = 96.05%
Duty Factor = 10 log(1/Duty cycle) = 0.18

IEEE 802.11n(HT40)



Date: 17.MAR.2021 16:52:36

Duty cycle = 5.432 ms / 5.656 ms = 96.04%
Duty Factor = 10 log(1/Duty cycle) = 0.18

IEEE 802.11ax(HE20)



Date: 17.MAR.2021 16:53:58

Duty cycle = 5.480 ms / 5.700 ms = 96.14%
Duty Factor = 10 log(1/Duty cycle) = 0.17

IEEE 802.11ax(HE40)



Date: 17.MAR.2021 16:54:49

Duty cycle = 5.474 ms / 5.695 ms = 96.12%
Duty Factor = 10 log(1/Duty cycle) = 0.17

NOTE:
For IEEE 802.11b:
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 504 Hz.

For IEEE 802.11g:
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 503 Hz.

For IEEE 802.11n(HT20):
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 184 Hz.

For IEEE 802.11n(HT40):
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 184 Hz.

For IEEE 802.11ax(HE20):
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 182 Hz.

For IEEE 802.11ax(HE40):
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 183 Hz.

2.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.6 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.
A	Notebook	Dell	Inspiron 15-7559	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	RJ45 Cable	NO	NO	10m
2	Network Cable	NO	NO	1m
3	AC Cable	NO	NO	1.5m

3. AC POWER LINE CONDUCTED EMISSIONS

3.1 LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.3 DEVIATION FROM TEST STANDARD

No deviation.

3.4 TEST SETUP



3.5 EUT OPERATION CONDITIONS

EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULTS

Please refer to the APPENDIX A.

4. RADIATED EMISSIONS

4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

NOTE:
(1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.
(2) The tighter limit applies at the band edges.
(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2 TEST PROCEDURE

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
i. For the actual test configuration, please refer to the related Item -EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value

Receiver Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5 GHz for PK/AVG detector

4.3 DEVIATION FROM TEST STANDARD

No deviation.

4.4 TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz



Above 1 GHz



4.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULTS - 9 KHZ TO 30 MHZ

Please refer to the APPENDIX B.

Remark:

(1) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
(2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ

Please refer to the APPENDIX C.

4.8 TEST RESULTS - ABOVE 1000 MHZ

Please refer to the APPENDIX D.

Remark:

(1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH

5.1 LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6 dB Bandwidth	Minimum 500 kHz
	99% Emission Bandwidth	-

5.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span Frequency	> Measurement Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span Frequency	Between 1.5 times and 5.0 times the OBW
RBW	300 kHz For 20MHz 1 MHz For 40MHz
VBW	1 MHz For 20MHz 3 MHz For 40MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULTS

Please refer to the APPENDIX E.

6. MAXIMUM AVERAGE OUTPUT POWER

6.1 LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Average Output Power	1.0000 Watt or 30.00 dBm

6.2 TEST PROCEDURE

a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below.
b. The maximum conducted output power was performed in accordance with method 11.9.2.3.1 of ANSI C63.10-2013 and FCC KDB 662911 D01 v02r01 Multiple Transmitter Output.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX F.

7. CONDUCTED SPURIOUS EMISSIONS

7.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

7.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

For Reference Level:

Spectrum Parameters	Setting
Span Frequency	⩾ 1.5 times the bandwidth.
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For Emission Level:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX G.

8. POWER SPECTRAL DENSITY

8.1 LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

8.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	25 MHz (20 MHz) / 60 MHz (40 MHz)
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX H.

9. MEASUREMENT INSTRUMENTS LIST

AC Power Line Conducted Emissions					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Feb. 28, 2022
2	LISN	EMCO	3816/2	52765	Feb. 27, 2022
3	TWO-LINE V-NETWORK	R&S	ENV216	101447	Feb. 27, 2022
4	50Ω Terminator	SHX	TF5-3	15041305	Feb. 27, 2022
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	Cable	N/A	RG223	12m	Mar. 09, 2022
7	643 Shield Room	ETS	6*4*3m	N/A	N/A

Radiated Emissions - 9 kHz to 30 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Loop Antenna	EM	EM-6876-1	230	Apr. 28, 2022
2	Cable	N/A	RG 213/U	N/A	May 27, 2022
3	EMI Test Receiver	R&S	ESCI	100895	Feb. 27, 2022
4	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
5	966 Chambe Room	RM	9*6*6m	N/A	Jul. 25, 2021

Radiated Emissions - 30 MHz to 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3232	Mar. 15, 2022
2	Amplifier	HP	8447D	2944A08742	Feb. 28, 2022
3	Receiver	Agilent	N9038A	MY52130039	Jul. 25, 2021
4	Cable	emci	LMR-400(30MHz-1 GHz)(8m+5m)	N/A	May 20, 2022
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	966 Chambe Room	RM	9*6*6m	N/A	Jul. 25, 2021

Radiated Emissions - Above 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Guide Antenna	ETS	3115	75789	May 10, 2022
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 30, 2022
3	Amplifier	Agilent	8449B	3008A02584	Jul. 25, 2021
4	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Feb. 28, 2022
5	Receiver	Agilent	N9038A	MY52130039	Jul. 25, 2021
6	Controller	CT	SC100	N/A	N/A
7	Controller	MF	MF-7802	MF780208416	N/A
8	Cable	N/A	EMC104-SM-SM-6 000	N/A	Oct. 16, 2021
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
10	Filter	STI	STI15-9912	N/A	Jul. 25, 2021
11	966 Chambe Room	RM	9*6*6m	N/A	Jul. 25, 2021

Bandwidth & Conducted Spurious Emissions & Power Spectral Density					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Jul. 25, 2021
2	Attenuator	WOKEN	6SM3502	VAS1214NL	Feb. 07, 2022
3	RF Cable	Tongkaichuan	N/A	N/A	N/A
4	DC Block	Mini	N/A	N/A	N/A

Maximum Average Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Peak Power Analyzer	Keysight	8990B	MY51000506	Aug. 07, 2021
2	Wideband power sensor	Keysight	N1923A	MY58310004	Jul. 25, 2021
3	Attenuator	WOKEN	6SM3502	VAS1214NL	Feb. 07, 2022
4	RF Cable	Tongkaichuan	N/A	N/A	N/A

Remark: ”N/A” denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

10. EUT TEST PHOTO

AC Power Line Conducted Emissions Test Photos

Radiated Emissions Test Photos

9 kHz to 30 MHz





Radiated Emissions Test Photos

30 MHz to 1 GHz





Radiated Emissions Test Photos

Above 1 GHz





Conducted Test Photos



APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode	TX G Mode Channel 06	Phase	Line



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1500	43.77	9.67	53.44	66.00	-12.56	Peak	
2	0.1500	32.50	9.67	42.17	56.00	-13.83	AVG	
3 *	0.4470	40.31	9.91	50.22	56.93	-6.71	Peak	
4	0.4470	29.60	9.91	39.51	46.93	-7.42	AVG	
5	0.7980	33.96	9.96	43.92	56.00	-12.08	Peak	
6	0.7980	21.50	9.96	31.46	46.00	-14.54	AVG	
7	1.1040	35.49	9.99	45.48	56.00	-10.52	Peak	
8	1.1040	24.60	9.99	34.59	46.00	-11.41	AVG	
9	1.3695	35.65	10.00	45.65	56.00	-10.35	Peak	
10	1.3695	24.80	10.00	34.80	46.00	-11.20	AVG	
11	2.4405	33.73	10.09	43.82	56.00	-12.18	Peak	
12	2.4405	22.10	10.09	32.19	46.00	-13.81	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode Channel 06	Phase	Neutral



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1590	44.01	9.81	53.82	65.52	-11.70	Peak	
2	0.1590	32.60	9.81	42.41	55.52	-13.11	AVG	
3 *	0.4380	39.68	10.09	49.77	57.10	-7.33	Peak	
4	0.4380	28.10	10.09	38.19	47.10	-8.91	AVG	
5	1.0815	35.98	10.28	46.26	56.00	-9.74	Peak	
6	1.0815	24.59	10.28	34.87	46.00	-11.13	AVG	
7	2.2515	35.99	10.40	46.39	56.00	-9.61	Peak	
8	2.2515	24.21	10.40	34.61	46.00	-11.39	AVG	
9	2.6790	36.56	10.44	47.00	56.00	-9.00	Peak	
10	2.6790	25.31	10.44	35.75	46.00	-10.25	AVG	
11	3.8085	37.02	10.53	47.55	56.00	-8.45	Peak	
12	3.8085	25.99	10.53	36.52	46.00	-9.48	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ

Test Mode	TX G Mode Channel 06	Polarization	Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	0.0186	45.26	13.65	58.91	122.21	-63.30	AVG			
2		0.1154	19.87	12.73	32.60	106.36	-73.76	AVG			
3		0.1367	25.73	12.73	38.46	104.89	-66.43	AVG			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode Channel 06	Polarization	Ant 0°

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		0.4020	37.69	12.25	49.94	95.52	-45.58	AVG			
2	*	2.2132	38.37	11.19	49.56	69.54	-19.98	QP			
3		3.5843	35.64	10.89	46.53	69.54	-23.01	QP			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode Channel 06	Polarization	Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	0.0185	46.81	13.68	60.49	122.26	-61.77	AVG			
2		0.1267	23.96	12.73	36.69	105.55	-68.86	AVG			
3		0.1454	25.47	12.74	38.21	104.36	-66.15	AVG			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode Channel 06	Polarization	Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		0.4020	37.72	12.25	49.97	95.52	-45.55	AVG			
2	*	2.0660	37.43	11.27	48.70	69.54	-20.84	QP			
3		3.4174	36.85	10.87	47.72	69.54	-21.82	QP			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

Test Mode	TX G Mode Channel 06	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	76.5600	42.17	-17.65	24.52	40.00	-15.48	Peak	
2	155.1300	31.78	-12.49	19.29	43.50	-24.21	Peak	
3	319.0600	32.92	-10.54	22.38	46.00	-23.62	Peak	
4	364.6500	37.72	-9.62	28.10	46.00	-17.90	Peak	
5	600.3600	32.68	-4.54	28.14	46.00	-17.86	Peak	
6	806.0000	30.06	-0.68	29.38	46.00	-16.62	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode Channel 06	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	74.6200	37.00	-17.24	19.76	40.00	-20.24	Peak	
2	117.3000	34.23	-14.40	19.83	43.50	-23.67	Peak	
3	240.4900	33.72	-13.36	20.36	46.00	-25.64	Peak	
4	319.0600	35.97	-10.54	25.43	46.00	-20.57	Peak	
5	600.3600	32.75	-4.54	28.21	46.00	-17.79	Peak	
6 *	777.8700	30.15	-1.24	28.91	46.00	-17.09	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ

Test Mode	TX B Mode 2412 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2385.2500	48.80	9.97	58.77	74.00	-15.23	Peak	
2	2385.2500	43.98	9.97	53.95	54.00	-0.05	AVG	
3	2390.0000	47.35	9.98	57.33	74.00	-16.67	Peak	
4	2390.0000	38.10	9.98	48.08	54.00	-5.92	AVG	
5 *	2411.1500	102.55	9.98	112.53	54.00	58.53	AVG	No Limit
6	2411.8000	107.27	9.98	117.25	74.00	43.25	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2412 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4824.4700	22.25	6.84	29.09	54.00	-24.91	AVG	
2	4824.5419	35.90	6.84	42.74	74.00	-31.26	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2412 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	43.71	9.98	53.69	74.00	-20.31	Peak	
2	2390.0000	35.94	9.98	45.92	54.00	-8.08	AVG	
3 *	2411.1500	93.29	9.98	103.27	54.00	49.27	AVG	No Limit
4	2412.0000	96.93	9.98	106.91	74.00	32.91	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2412 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4822.0250	35.76	6.83	42.59	74.00	-31.41	Peak	
2 *	4823.9350	22.59	6.84	29.43	54.00	-24.57	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2417 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	50.88	9.98	60.86	74.00	-13.14	Peak	
2	2390.0000	43.91	9.98	53.89	54.00	-0.11	AVG	
3 *	2416.2000	102.50	9.99	112.49	54.00	58.49	AVG	No Limit
4	2416.7500	107.07	9.99	117.06	74.00	43.06	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2417 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4832.6600	22.05	6.86	28.91	54.00	-25.09	AVG	
2	4835.0630	35.36	6.87	42.23	74.00	-31.77	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2417 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	44.93	9.98	54.91	74.00	-19.09	Peak	
2	2390.0000	36.03	9.98	46.01	54.00	-7.99	AVG	
3	2415.9000	103.05	9.99	113.04	74.00	39.04	Peak	No Limit
4 *	2416.2000	99.29	9.99	109.28	54.00	55.28	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2417 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4833.3250	22.09	6.86	28.95	54.00	-25.05	AVG	
2	4835.7950	35.36	6.87	42.23	74.00	-31.77	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2437 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2436.2000	102.51	9.99	112.50	54.00	58.50	AVG	No Limit
2	2436.8500	107.31	9.99	117.30	74.00	43.30	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2437 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4874.6300	35.24	6.96	42.20	74.00	-31.80	Peak	
2 *	4876.3180	21.98	6.96	28.94	54.00	-25.06	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2437 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2435.9000	102.88	9.99	112.87	74.00	38.87	Peak	No Limit
2 *	2436.3000	99.24	9.99	109.23	54.00	55.23	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2437 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4874.9670	36.09	6.96	43.05	74.00	-30.95	Peak	
2 *	4876.0550	21.90	6.96	28.86	54.00	-25.14	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2457 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2456.1000	102.36	10.00	112.36	54.00	58.36	AVG	No Limit
2	2456.8500	107.03	10.00	117.03	74.00	43.03	Peak	No Limit
3	2483.5000	48.09	10.01	58.10	74.00	-15.90	Peak	
4	2483.5000	42.05	10.01	52.06	54.00	-1.94	AVG	
5	2485.2500	48.38	10.01	58.39	74.00	-15.61	Peak	
6	2485.2500	43.57	10.01	53.58	54.00	-0.42	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2457 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4913.1850	22.47	7.05	29.52	54.00	-24.48	AVG	
2	4913.8250	35.70	7.05	42.75	74.00	-31.25	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2457 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2457.0000	106.56	10.00	116.56	74.00	42.56	Peak	No Limit
2 *	2457.7500	101.65	10.00	111.65	54.00	57.65	AVG	No Limit
3	2483.5000	42.98	10.01	52.99	74.00	-21.01	Peak	
4	2483.5000	36.32	10.01	46.33	54.00	-7.67	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2457 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4911.6269	22.27	7.05	29.32	54.00	-24.68	AVG	
2	4912.9770	35.54	7.05	42.59	74.00	-31.41	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2462 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2461.2500	102.52	10.00	112.52	54.00	58.52	AVG	No Limit
2	2461.8500	107.15	10.00	117.15	74.00	43.15	Peak	No Limit
3	2483.5000	46.98	10.01	56.99	74.00	-17.01	Peak	
4	2483.5000	37.83	10.01	47.84	54.00	-6.16	AVG	
5	2487.2000	52.54	10.01	62.55	74.00	-11.45	Peak	
6	2487.2000	43.54	10.01	53.55	54.00	-0.45	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2462 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4923.9129	35.25	7.08	42.33	74.00	-31.67	Peak	
2 *	4924.4000	22.14	7.08	29.22	54.00	-24.78	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2462 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2461.2500	101.73	10.00	111.73	74.00	37.73	Peak	No Limit
2 *	2462.0000	106.62	10.00	116.62	54.00	62.62	AVG	No Limit
3	2483.5000	45.87	10.01	55.88	74.00	-18.12	Peak	
4	2483.5000	37.66	10.01	47.67	54.00	-6.33	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX B Mode 2462 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4924.2730	22.13	7.08	29.21	54.00	-24.79	AVG	
2	4925.5680	35.22	7.08	42.30	74.00	-31.70	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2412 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2389.4000	56.36	9.98	66.34	74.00	-7.66	Peak	
2	2389.4000	43.16	9.98	53.14	54.00	-0.86	AVG	
3	2390.0000	55.72	9.98	65.70	74.00	-8.30	Peak	
4	2390.0000	42.77	9.98	52.75	54.00	-1.25	AVG	
5 *	2408.7500	99.34	9.98	109.32	54.00	55.32	AVG	No Limit
6	2408.9500	108.71	9.98	118.69	74.00	44.69	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2412 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4823.1580	35.07	6.84	41.91	74.00	-32.09	Peak	
2 *	4823.2599	22.32	6.84	29.16	54.00	-24.84	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2412 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	52.18	9.98	62.16	74.00	-11.84	Peak	
2	2390.0000	38.75	9.98	48.73	54.00	-5.27	AVG	
3	2415.2000	105.76	9.99	115.75	74.00	41.75	Peak	No Limit
4 *	2415.2500	96.21	9.99	106.20	54.00	52.20	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2412 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4823.8700	22.28	6.84	29.12	54.00	-24.88	AVG	
2	4824.2400	35.45	6.84	42.29	74.00	-31.71	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2417 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	54.14	9.98	64.12	74.00	-9.88	Peak	
2	2390.0000	43.48	9.98	53.46	54.00	-0.54	AVG	
3 *	2412.3500	101.60	9.98	111.58	54.00	57.58	AVG	No Limit
4	2422.6500	110.74	9.99	120.73	74.00	46.73	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2417 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4832.2970	22.03	6.86	28.89	54.00	-25.11	AVG	
2	4834.8070	35.71	6.87	42.58	74.00	-31.42	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2417 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	50.89	9.98	60.87	74.00	-13.13	Peak	
2	2390.0000	39.19	9.98	49.17	54.00	-4.83	AVG	
3	2414.9500	106.15	9.99	116.14	74.00	42.14	Peak	No Limit
4 *	2419.8500	96.06	9.99	106.05	54.00	52.05	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2417 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4833.5730	35.18	6.86	42.04	74.00	-31.96	Peak	
2 *	4834.0400	21.93	6.86	28.79	54.00	-25.21	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2437 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2439.7000	109.89	10.00	119.89	74.00	45.89	Peak	No Limit
2 *	2439.7000	100.55	10.00	110.55	54.00	56.55	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2437 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4874.6900	34.96	6.96	41.92	74.00	-32.08	Peak	
2 *	4875.9480	21.93	6.96	28.89	54.00	-25.11	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2437 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2439.6000	97.05	10.00	107.05	54.00	53.05	AVG	No Limit
2	2439.8000	107.24	10.00	117.24	74.00	43.24	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2437 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4872.4670	35.28	6.96	42.24	74.00	-31.76	Peak	
2 *	4875.9620	22.02	6.96	28.98	54.00	-25.02	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2457 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2459.4000	109.95	10.00	119.95	74.00	45.95	Peak	No Limit
2 *	2459.7500	100.66	10.00	110.66	54.00	56.66	AVG	No Limit
3	2483.5000	49.40	10.01	59.41	74.00	-14.59	Peak	
4	2483.5000	42.98	10.01	52.99	54.00	-1.01	AVG	
5	2484.2000	50.34	10.01	60.35	74.00	-13.65	Peak	
6	2484.2000	43.11	10.01	53.12	54.00	-0.88	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2457 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4911.7919	22.22	7.05	29.27	54.00	-24.73	AVG	
2	4913.1100	35.77	7.05	42.82	74.00	-31.18	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2457 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2462.1000	106.30	10.00	116.30	74.00	42.30	Peak	No Limit
2 *	2462.1500	97.19	10.00	107.19	54.00	53.19	AVG	No Limit
3	2483.5000	45.30	10.01	55.31	74.00	-18.69	Peak	
4	2483.5000	36.29	10.01	46.30	54.00	-7.70	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2457 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4912.2599	22.36	7.05	29.41	54.00	-24.59	AVG	
2	4914.2950	36.35	7.06	43.41	74.00	-30.59	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2462 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2459.5000	97.44	10.00	107.44	54.00	53.44	AVG	No Limit
2	2464.1000	106.95	10.01	116.96	74.00	42.96	Peak	No Limit
3	2483.5000	55.51	10.01	65.52	74.00	-8.48	Peak	
4	2483.5000	43.46	10.01	53.47	54.00	-0.53	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2462 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4922.9270	22.16	7.08	29.24	54.00	-24.76	AVG	
2	4926.1180	35.50	7.08	42.58	74.00	-31.42	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2462 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2467.0500	105.99	10.01	116.00	74.00	42.00	Peak	No Limit
2 *	2467.2000	96.53	10.01	106.54	54.00	52.54	AVG	No Limit
3	2483.5000	49.67	10.01	59.68	74.00	-14.32	Peak	
4	2483.5000	38.43	10.01	48.44	54.00	-5.56	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX G Mode 2462 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4923.4800	22.01	7.08	29.09	54.00	-24.91	AVG	
2	4925.1720	36.01	7.08	43.09	74.00	-30.91	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2412 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	54.41	9.98	64.39	74.00	-9.61	Peak	
2	2390.0000	43.25	9.98	53.23	54.00	-0.77	AVG	
3	2409.9000	108.01	9.98	117.99	74.00	43.99	Peak	No Limit
4 *	2410.0500	98.38	9.98	108.36	54.00	54.36	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2412 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4822.1300	35.91	6.83	42.74	74.00	-31.26	Peak	
2 *	4824.1130	22.31	6.84	29.15	54.00	-24.85	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2412 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	46.83	9.98	56.81	74.00	-17.19	Peak	
2	2390.0000	36.49	9.98	46.47	54.00	-7.53	AVG	
3 *	2408.2500	95.52	9.98	105.50	54.00	51.50	AVG	No Limit
4	2409.4000	106.33	9.98	116.31	74.00	42.31	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2412 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4821.5520	35.91	6.83	42.74	74.00	-31.26	Peak	
2 *	4823.8470	22.43	6.84	29.27	54.00	-24.73	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2417 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2388.3000	54.92	9.98	64.90	74.00	-9.10	Peak	
2	2388.3000	43.86	9.98	53.84	54.00	-0.16	AVG	
3	2390.0000	54.36	9.98	64.34	74.00	-9.66	Peak	
4	2390.0000	43.46	9.98	53.44	54.00	-0.56	AVG	
5	2418.6000	110.24	9.99	120.23	74.00	46.23	Peak	No Limit
6 *	2419.2000	101.35	9.99	111.34	54.00	57.34	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2417 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4833.8400	22.16	6.86	29.02	54.00	-24.98	AVG	
2	4835.6150	35.07	6.87	41.94	74.00	-32.06	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2417 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	51.82	9.98	61.80	74.00	-12.20	Peak	
2	2390.0000	40.16	9.98	50.14	54.00	-3.86	AVG	
3	2413.2000	106.80	9.99	116.79	74.00	42.79	Peak	No Limit
4 *	2414.2000	96.76	9.99	106.75	54.00	52.75	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2417 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4832.0700	22.25	6.86	29.11	54.00	-24.89	AVG	
2	4833.1770	36.16	6.86	43.02	74.00	-30.98	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2437 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2431.6000	100.51	9.99	110.50	54.00	56.50	AVG	No Limit
2	2432.6500	109.97	9.99	119.96	74.00	45.96	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2437 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4872.4650	35.06	6.96	42.02	74.00	-31.98	Peak	
2 *	4873.1400	21.99	6.96	28.95	54.00	-25.05	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2437 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2442.0500	97.79	10.00	107.79	54.00	53.79	AVG	No Limit
2	2442.7500	107.41	10.00	117.41	74.00	43.41	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2437 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4873.5970	34.94	6.96	41.90	74.00	-32.10	Peak	
2 *	4875.9950	22.03	6.96	28.99	54.00	-25.01	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2457 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2455.4000	110.27	10.00	120.27	74.00	46.27	Peak	No Limit
2 *	2464.9500	101.09	10.01	111.10	54.00	57.10	AVG	No Limit
3	2483.5000	59.21	10.01	69.22	74.00	-4.78	Peak	
4	2483.5000	43.89	10.01	53.90	54.00	-0.10	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2457 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4915.4480	22.36	7.06	29.42	54.00	-24.58	AVG	
2	4916.3680	35.68	7.06	42.74	74.00	-31.26	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2457 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2455.7000	99.68	10.00	109.68	54.00	55.68	AVG	No Limit
2	2456.2000	109.20	10.00	119.20	74.00	45.20	Peak	No Limit
3	2483.5000	57.14	10.01	67.15	74.00	-6.85	Peak	
4	2483.5000	40.27	10.01	50.28	54.00	-3.72	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2457 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4812.8020	36.21	6.81	43.02	74.00	-30.98	Peak	
2 *	4813.2500	22.36	6.81	29.17	54.00	-24.83	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2462 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2467.0000	97.69	10.01	107.70	54.00	53.70	AVG	No Limit
2	2467.2000	107.48	10.01	117.49	74.00	43.49	Peak	No Limit
3	2483.5000	54.54	10.01	64.55	74.00	-9.45	Peak	
4	2483.5000	43.25	10.01	53.26	54.00	-0.74	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2462 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4924.9270	22.14	7.08	29.22	54.00	-24.78	AVG	
2	4925.9580	35.10	7.08	42.18	74.00	-31.82	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2462 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2459.4500	104.73	10.00	114.73	74.00	40.73	Peak	No Limit
2 *	2467.1000	94.53	10.01	104.54	54.00	50.54	AVG	No Limit
3	2483.5000	47.87	10.01	57.88	74.00	-16.12	Peak	
4	2483.5000	36.32	10.01	46.33	54.00	-7.67	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT20) Mode 2462 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4921.8300	35.03	7.07	42.10	74.00	-31.90	Peak	
2 *	4923.4980	22.19	7.08	29.27	54.00	-24.73	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2422 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2385.4000	53.46	11.10	64.56	74.00	-9.44	Peak	
2	2385.4000	42.28	11.10	53.38	54.00	-0.62	AVG	
3	2390.0000	49.64	11.10	60.74	74.00	-13.26	Peak	
4	2390.0000	37.84	11.10	48.94	54.00	-5.06	AVG	
5	2415.3000	102.73	11.12	113.85	74.00	39.85	Peak	No Limit
6 *	2425.4000	93.19	11.13	104.32	54.00	50.32	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2422 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4843.0280	36.11	6.88	42.99	74.00	-31.01	Peak	
2 *	4843.3580	21.65	6.89	28.54	54.00	-25.46	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2422 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	48.24	11.10	59.34	74.00	-14.66	Peak	
2	2390.0000	37.15	11.10	48.25	54.00	-5.75	AVG	
3	2417.1000	98.02	11.12	109.14	74.00	35.14	Peak	No Limit
4 *	2417.8000	88.80	11.12	99.92	54.00	45.92	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2422 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4841.5150	36.55	6.88	43.43	74.00	-30.57	Peak	
2 *	4844.2950	21.74	6.89	28.63	54.00	-25.37	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2427 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	54.62	11.10	65.72	74.00	-8.28	Peak	
2	2390.0000	42.13	11.10	53.23	54.00	-0.77	AVG	
3	2428.2000	103.47	11.13	114.60	74.00	40.60	Peak	No Limit
4 *	2429.2000	93.83	11.13	104.96	54.00	50.96	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2427 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4854.7350	34.59	6.91	41.50	74.00	-32.50	Peak	
2 *	4855.4670	21.52	6.91	28.43	54.00	-25.57	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2427 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	47.51	11.10	58.61	74.00	-15.39	Peak	
2	2390.0000	36.09	11.10	47.19	54.00	-6.81	AVG	
3 *	2422.8000	89.54	11.12	100.66	54.00	46.66	AVG	No Limit
4	2432.9000	99.57	11.13	110.70	74.00	36.70	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2427 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4853.8630	21.50	6.91	28.41	54.00	-25.59	AVG	
2	4854.7900	34.54	6.91	41.45	74.00	-32.55	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2437 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	52.70	11.10	63.80	74.00	-10.20	Peak	
2	2390.0000	42.51	11.10	53.61	54.00	-0.39	AVG	
3	2428.5000	105.77	11.13	116.90	74.00	42.90	Peak	No Limit
4 *	2429.4000	96.12	11.13	107.25	54.00	53.25	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2437 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4873.7430	35.37	6.96	42.33	74.00	-31.67	Peak	
2 *	4876.0570	21.94	6.96	28.90	54.00	-25.10	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2437 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2443.0000	99.89	11.14	111.03	74.00	37.03	Peak	No Limit
2 *	2443.3000	89.90	11.14	101.04	54.00	47.04	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2437 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4872.0650	35.15	6.95	42.10	74.00	-31.90	Peak	
2 *	4876.3200	21.91	6.96	28.87	54.00	-25.13	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2447 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2442.6000	101.87	8.37	110.24	74.00	36.24	Peak	No Limit
2 *	2452.4000	94.38	8.38	102.76	54.00	48.76	AVG	No Limit
3	2483.5000	55.70	8.42	64.12	74.00	-9.88	Peak	
4	2483.5000	45.28	8.42	53.70	54.00	-0.30	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2447 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4893.7780	22.47	7.01	29.48	54.00	-24.52	AVG	
2	4896.2150	35.28	7.01	42.29	74.00	-31.71	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2447 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2459.2000	85.51	11.15	96.66	54.00	42.66	AVG	No Limit
2	2459.5000	95.61	11.15	106.76	74.00	32.76	Peak	No Limit
3	2483.5000	45.48	11.16	56.64	74.00	-17.36	Peak	
4	2483.5000	34.37	11.16	45.53	54.00	-8.47	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2447 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4891.5299	35.87	7.00	42.87	74.00	-31.13	Peak	
2 *	4892.4450	22.88	7.00	29.88	54.00	-24.12	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2452 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2462.4000	94.78	8.40	103.18	54.00	49.18	AVG	No Limit
2	2462.8000	103.14	8.40	111.54	74.00	37.54	Peak	No Limit
3	2483.5000	54.53	8.42	62.95	74.00	-11.05	Peak	
4	2483.5000	44.71	8.42	53.13	54.00	-0.87	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2452 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4906.1580	22.58	7.04	29.62	54.00	-24.38	AVG	
2	4906.2080	35.47	7.04	42.51	74.00	-31.49	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2452 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2454.4000	94.73	11.14	105.87	74.00	31.87	Peak	No Limit
2 *	2454.7000	84.73	11.14	95.87	54.00	41.87	AVG	No Limit
3	2483.5000	43.20	11.16	54.36	74.00	-19.64	Peak	
4	2483.5000	33.67	11.16	44.83	54.00	-9.17	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX N(HT40) Mode 2452 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4901.6349	22.43	7.02	29.45	54.00	-24.55	AVG	
2	4905.0630	35.84	7.03	42.87	74.00	-31.13	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2412 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	55.54	9.98	65.52	74.00	-8.48	Peak	
2	2390.0000	43.38	9.98	53.36	54.00	-0.64	AVG	
3 *	2409.6500	97.71	9.98	107.69	54.00	53.69	AVG	No Limit
4	2409.7500	108.36	9.98	118.34	74.00	44.34	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2412 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4823.6629	35.68	6.84	42.52	74.00	-31.48	Peak	
2 *	4823.8630	22.30	6.84	29.14	54.00	-24.86	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2412 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	47.94	9.98	57.92	74.00	-16.08	Peak	
2	2390.0000	37.15	9.98	47.13	54.00	-6.87	AVG	
3 *	2416.7000	96.04	9.99	106.03	54.00	52.03	AVG	No Limit
4	2417.7000	107.21	9.99	117.20	74.00	43.20	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2412 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4824.9770	22.23	6.84	29.07	54.00	-24.93	AVG	
2	4825.1150	35.27	6.84	42.11	74.00	-31.89	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2417 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	57.95	9.98	67.93	74.00	-6.07	Peak	
2	2390.0000	43.49	9.98	53.47	54.00	-0.53	AVG	
3 *	2418.2000	99.75	9.99	109.74	54.00	55.74	AVG	No Limit
4	2419.0500	110.01	9.99	120.00	74.00	46.00	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2417 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4833.9720	35.41	6.86	42.27	74.00	-31.73	Peak	
2 *	4834.1500	22.24	6.86	29.10	54.00	-24.90	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2417 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	50.48	9.98	60.46	74.00	-13.54	Peak	
2	2390.0000	39.63	9.98	49.61	54.00	-4.39	AVG	
3 *	2412.6000	98.86	9.98	108.84	54.00	54.84	AVG	No Limit
4	2422.1000	109.92	9.99	119.91	74.00	45.91	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2417 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4833.7650	22.33	6.86	29.19	54.00	-24.81	AVG	
2	4834.2950	35.19	6.86	42.05	74.00	-31.95	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2437 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2442.0500	110.12	10.00	120.12	74.00	46.12	Peak	No Limit
2 *	2444.2500	100.14	10.00	110.14	54.00	56.14	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2437 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4874.7730	35.19	6.96	42.15	74.00	-31.85	Peak	
2 *	4874.9200	21.94	6.96	28.90	54.00	-25.10	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2437 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2432.4500	108.29	9.99	118.28	74.00	44.28	Peak	No Limit
2 *	2433.2000	96.73	9.99	106.72	54.00	52.72	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2437 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4875.5250	35.38	6.96	42.34	74.00	-31.66	Peak	
2 *	4876.1300	21.90	6.96	28.86	54.00	-25.14	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2457 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2459.4500	109.35	10.00	119.35	74.00	45.35	Peak	No Limit
2 *	2464.1500	98.80	10.01	108.81	54.00	54.81	AVG	No Limit
3	2483.5000	57.25	10.01	67.26	74.00	-6.74	Peak	
4	2483.5000	43.55	10.01	53.56	54.00	-0.44	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2457 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4912.2879	22.35	7.05	29.40	54.00	-24.60	AVG	
2	4915.2000	35.89	7.06	42.95	74.00	-31.05	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2457 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2461.5000	106.65	10.00	116.65	74.00	42.65	Peak	No Limit
2 *	2461.9000	94.39	10.00	104.39	54.00	50.39	AVG	No Limit
3	2483.5000	52.05	10.01	62.06	74.00	-11.94	Peak	
4	2483.5000	38.24	10.01	48.25	54.00	-5.75	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2457 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4912.6150	36.04	7.05	43.09	74.00	-30.91	Peak	
2 *	4915.2799	22.29	7.06	29.35	54.00	-24.65	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2462 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2458.8500	96.51	10.00	106.51	54.00	52.51	AVG	No Limit
2	2459.6500	108.62	10.00	118.62	74.00	44.62	Peak	No Limit
3	2483.5000	55.21	10.01	65.22	74.00	-8.78	Peak	
4	2483.5000	43.44	10.01	53.45	54.00	-0.55	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2462 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4922.8280	35.46	7.08	42.54	74.00	-31.46	Peak	
2 *	4924.0800	22.10	7.08	29.18	54.00	-24.82	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2462 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2458.3500	93.68	10.00	103.68	54.00	49.68	AVG	No Limit
2	2458.6500	105.21	10.00	115.21	74.00	41.21	Peak	No Limit
3	2483.5000	51.24	10.01	61.25	74.00	-12.75	Peak	
4	2483.5000	37.27	10.01	47.28	54.00	-6.72	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE20) Mode 2462 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4922.5280	22.20	7.07	29.27	54.00	-24.73	AVG	
2	4923.9150	35.29	7.08	42.37	74.00	-31.63	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2422 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	53.01	11.10	64.11	74.00	-9.89	Peak	
2	2390.0000	42.85	11.10	53.95	54.00	-0.05	AVG	
3 *	2420.7000	92.15	11.12	103.27	54.00	49.27	AVG	No Limit
4	2422.3000	103.67	11.12	114.79	74.00	40.79	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2422 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4842.7200	21.70	6.88	28.58	54.00	-25.42	AVG	
2	4843.0920	35.27	6.88	42.15	74.00	-31.85	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2422 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	47.38	11.10	58.48	74.00	-15.52	Peak	
2	2390.0000	36.21	11.10	47.31	54.00	-6.69	AVG	
3 *	2430.7000	83.59	11.13	94.72	54.00	40.72	AVG	No Limit
4	2431.0000	95.20	11.13	106.33	74.00	32.33	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2422 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4843.8630	21.72	6.89	28.61	54.00	-25.39	AVG	
2	4846.4800	34.82	6.89	41.71	74.00	-32.29	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2427 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	55.87	11.10	66.97	74.00	-7.03	Peak	
2	2390.0000	42.46	11.10	53.56	54.00	-0.44	AVG	
3 *	2419.6000	92.12	11.12	103.24	54.00	49.24	AVG	No Limit
4	2420.0000	103.78	11.12	114.90	74.00	40.90	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2427 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4852.4000	34.60	6.91	41.51	74.00	-32.49	Peak	
2 *	4852.6420	21.46	6.91	28.37	54.00	-25.63	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2427 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	44.66	11.10	55.76	74.00	-18.24	Peak	
2	2390.0000	34.71	11.10	45.81	54.00	-8.19	AVG	
3 *	2425.9000	84.06	11.13	95.19	54.00	41.19	AVG	No Limit
4	2426.4000	97.25	11.13	108.38	74.00	34.38	Peak	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2427 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4852.2670	21.40	6.91	28.31	54.00	-25.69	AVG	
2	4852.4150	34.18	6.91	41.09	74.00	-32.91	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2437 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	53.02	11.10	64.12	74.00	-9.88	Peak	
2	2390.0000	42.50	11.10	53.60	54.00	-0.40	AVG	
3	2428.0000	106.10	11.13	117.23	74.00	43.23	Peak	No Limit
4 *	2429.5000	95.45	11.13	106.58	54.00	52.58	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2437 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4871.6400	35.09	6.95	42.04	74.00	-31.96	Peak	
2 *	4875.8280	21.91	6.96	28.87	54.00	-25.13	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2437 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2434.2000	100.32	11.13	111.45	74.00	37.45	Peak	No Limit
2 *	2434.2000	89.32	11.13	100.45	54.00	46.45	AVG	No Limit

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2437 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4874.5630	35.44	6.96	42.40	74.00	-31.60	Peak	
2 *	4875.5280	21.95	6.96	28.91	54.00	-25.09	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2447 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2433.4000	102.74	8.36	111.10	74.00	37.10	Peak	No Limit
2 *	2453.6000	93.73	8.39	102.12	54.00	48.12	AVG	No Limit
3	2483.5000	53.16	8.42	61.58	74.00	-12.42	Peak	
4	2483.5000	45.11	8.42	53.53	54.00	-0.47	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2447 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4894.2300	22.50	7.01	29.51	54.00	-24.49	AVG	
2	4896.2300	35.79	7.01	42.80	74.00	-31.20	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2447 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2449.6000	84.36	11.14	95.50	54.00	41.50	AVG	No Limit
2	2451.6000	96.08	11.14	107.22	74.00	33.22	Peak	No Limit
3	2483.5000	44.29	11.16	55.45	74.00	-18.55	Peak	
4	2483.5000	33.29	11.16	44.45	54.00	-9.55	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2447 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4891.9980	36.26	7.00	43.26	74.00	-30.74	Peak	
2 *	4894.4500	22.50	7.01	29.51	54.00	-24.49	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2452 MHz	Polarization	Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2453.4000	104.41	8.39	112.80	74.00	38.80	Peak	No Limit
2 *	2463.0000	94.35	8.40	102.75	54.00	48.75	AVG	No Limit
3	2483.5000	53.78	8.42	62.20	74.00	-11.80	Peak	
4	2483.5000	44.68	8.42	53.10	54.00	-0.90	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2452 MHz	Polarization	Vertical

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4904.3550	22.47	7.03	29.50	54.00	-24.50	AVG	
2	4905.6420	35.27	7.03	42.30	74.00	-31.70	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2452 MHz	Polarization	Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	2453.4000	84.54	11.14	95.68	54.00	41.68	AVG	No Limit
2	2462.8000	96.51	11.15	107.66	74.00	33.66	Peak	No Limit
3	2483.5000	44.49	11.16	55.65	74.00	-18.35	Peak	
4	2483.5000	34.37	11.16	45.53	54.00	-8.47	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX AX(HE40) Mode 2452 MHz	Polarization	Horizontal

No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4904.8700	22.42	7.03	29.45	54.00	-24.55	AVG	
2	4906.1400	36.31	7.04	43.35	74.00	-30.65	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX E - BANDWIDTH

Test Mode	TX B Mode

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	6 dB Bandwidth Min. Limit (MHz)	Result
01	2412	12.11	16.00	0.50	Complies
06	2437	12.08	16.16	0.50	Complies
11	2462	12.11	16.16	0.50	Complies

CH01



Date: 27.MAY.2021 14:50:07

CH06

6 dB Bandwidth



Date: 27.MAY.2021 13:56:27

CH11



Date: 27.MAY.2021 13:58:27



Date: 27.MAY.2021 14:50:14

99 % Occupied Bandwidth



Date: 27.MAY.2021 13:56:33



Date: 27.MAY.2021 13:58:33