

FCC TEST REPORT

FCC ID: 2AXJ7-ULTRAANC

Report No. : SSP24030113-1E

Applicant : MIXX LIMITED

Product Name : Bluetooth Wireless Earphone

Model Name : MIXX Ultra ANC

Test Standard : FCC Part 15.247

Date of Issue : 2024-05-16



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	MIXX LIMITED
Address of Applicant:	Unit 5 The Pavilions Brighton Road, Pease Pottage, RH11 9B, United Kingdom
Manufacturer:	Shenzhen Kingvie Technology Co.,Ltd
Address of Manufacturer:	201, 301, No.2 Building, 84# Fuqian Rd, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, China
Product Name:	Bluetooth Wireless Earphone
Brand Name:	MIXX
Main Model:	MIXX Ultra ANC
Series Models:	SBUL-ANC-BK-403, SBUL-ANC-XX-XXX, USUL-ANC-BK-025, USUL-ANC-XX-XXX
Test Standard:	FCC Part 15 Subpart C ANSI C63.4-2014 ANSI C63.10-2013
Date of Test	2024-04-30 to 2024-05-06
Test Result:	PASS
Tested By	<u>Walker Wu</u> (Walker Wu)
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.	



CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	8
2. Summary of Test Results	9
3. Antenna Requirement.....	10
3.1 Standard and Limit.....	10
3.2 Test Result	10
4. Conducted Emissions	11
4.1 Standard and Limit.....	11
4.2 Test Procedure.....	11
4.3 Test Data and Results	12
5. Radiated Emissions	15
5.1 Standard and Limit.....	15
5.2 Test Procedure.....	15
5.3 Test Data and Results	17
6. Band-edge Emissions(Radiated)	21
6.1 Standard and Limit.....	21
6.2 Test Procedure.....	21
6.3 Test Data and Results	21
7. Frequency Hopping System.....	23
7.1 Standard and Limit.....	23
7.2 Test Procedure.....	23
7.3 Test Data and Results	24
8. Dwell Time.....	25
8.1 Standard and Limit.....	25
8.2 Test Procedure.....	25
8.3 Test Data and Results	26
9. Maximum Peak Conducted Output Power	31
9.1 Standard and Limit.....	31
9.2 Test Procedure.....	31
9.3 Test Data and Results	31
10. Occupied Bandwidth(-20dB)	35
10.1 Standard and Limit.....	35
10.2 Test Procedure.....	35
10.3 Test Data and Results	35
11. Carrier Frequencies Separation.....	39
11.1 Standard and Limit.....	39
11.2 Test Procedure.....	39
11.3 Test Data and Results	39
12. Number of Hopping Channel.....	43
12.1 Standard and Limit.....	43
12.2 Test Procedure.....	43
12.3 Test Data and Results	43
13. Band-edge Emission(Conducted).....	46
13.1 Standard and Limit.....	46
13.2 Test Procedure.....	46
13.3 Test Data and Results	46
14. Conducted RF Spurious Emissions.....	56
14.1 Standard and Limit.....	56
14.2 Test Procedure.....	56
14.3 Test Data and Results	56

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-05-16	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Bluetooth Wireless Earphone
Trade Name:	MIXX
Main Model:	MIXX Ultra ANC
Series Models:	SBUL-ANC-BK-403, SBUL-ANC-XX-XXX, USUL-ANC-BK-025, USUL-ANC-XX-XXX
Rated Voltage:	DC 3.6V by battery, USB 5V charging
Battery:	DC 3.6V, 45mAh
Hardware Version:	BW-T25-V04
Software Version:	V1.6.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.	
Note3: XXX represents number, representing a different color.	

Wireless Specification	
Wireless Standard:	Bluetooth BR/EDR
Operating Frequency:	2402MHz ~ 2480MHz
RF Output Power:	2.19dBm
Number of Channel:	79
Channel Separation:	1MHz
Modulation:	GFSK, Pi/4 DQPSK
Antenna Gain:	0.41dBi
Type of Antenna:	FPCB Antenna
Type of Device:	☒ Portable Device ☐ Mobile Device ☐ Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Lowest Channel	2402MHz(DH5/2DH5)	
TM2	Middle Channel	2441MHz(DH5/2DH5)	
TM3	Highest Channel	2480MHz(DH5/2DH5)	
TM4	Hopping	2402MHz~2480MHz	
TM5	Charging	AC 120V/60Hz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
USB Cable	100	Unshielded	Without Ferrite
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	Huawei	HW-100225C00	HC78E2N6A23645
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	21	2422	41	2442	61	2462
02	2403	22	2423	42	2443	62	2463
03	2404	23	2424	43	2444	63	2464
04	2405	24	2425	44	2445	64	2465
05	2406	25	2426	45	2446	65	2466
~	~	~	~	~	~	~	~
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2023-10-21	2024-10-20
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2023-07-31	2024-07-30
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2023-07-31	2024-07-30
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2023-07-31	2024-07-30
Amplifier	SCHWARZBECK	BBV 9743B	00251	2023-07-31	2024-07-30
Amplifier	HUABO	YXL0518-2.5-45	--	2023-07-31	2024-07-30
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2023-07-31	2024-07-30
Loop Antenna	DAZE	ZN30900C	21104	2023-08-07	2024-08-06
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2023-08-07	2024-08-06
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2023-08-07	2024-08-06
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2023-08-07	2024-08-06
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2023-07-31	2024-07-30

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(a)(1), (g), (h)	Frequency Hopping System	Passed
FCC Part 15.247(a)(1)(iii)	Dwell Time	Passed
FCC Part 15.247(b)(1)	Maximum Peak Conducted Output Power	Passed
FCC Part 15.215(c)	Occupied Bandwidth(-20dB)	Passed
FCC Part 15.247(a)(1)	Carrier Frequencies Separation	Passed
FCC Part 15.247(a)(1)(iii)	Number of Hopping Channel	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an FPCB antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit


Test Plots and Data of Conducted Emissions

Tested Mode: TM5

Test Voltage: AC 120V/60Hz

Test Power Line: Neutral

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1815	27.30	9.32	36.62	64.42	-27.80	QP	P	
2	0.1815	11.25	9.32	20.57	54.42	-33.85	AVG	P	
3 *	0.6765	27.74	9.64	37.38	56.00	-18.62	QP	P	
4	0.6765	10.88	9.64	20.52	46.00	-25.48	AVG	P	
5	1.4640	21.06	10.03	31.09	56.00	-24.91	QP	P	
6	1.4640	6.97	10.03	17.00	46.00	-29.00	AVG	P	
7	4.5104	18.72	10.19	28.91	56.00	-27.09	QP	P	
8	4.5104	-0.10	10.19	10.09	46.00	-35.91	AVG	P	
9	5.5725	19.27	10.22	29.49	60.00	-30.51	QP	P	
10	5.5725	0.81	10.22	11.03	50.00	-38.97	AVG	P	
11	18.8385	15.01	10.31	25.32	60.00	-34.68	QP	P	
12	18.8385	-1.51	10.31	8.80	50.00	-41.20	AVG	P	


Test Plots and Data of Conducted Emissions

Tested Mode: TM5

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1860	24.95	9.01	33.96	64.21	-30.25	QP	P	
2	0.1860	11.89	9.01	20.90	54.21	-33.31	AVG	P	
3 *	0.6900	25.21	9.85	35.06	56.00	-20.94	QP	P	
4	0.6900	11.85	9.85	21.70	46.00	-24.30	AVG	P	
5	1.5990	19.59	10.03	29.62	56.00	-26.38	QP	P	
6	1.5990	6.41	10.03	16.44	46.00	-29.56	AVG	P	
7	4.5600	20.79	10.19	30.98	56.00	-25.02	QP	P	
8	4.5600	2.25	10.19	12.44	46.00	-33.56	AVG	P	
9	5.7975	21.25	10.24	31.49	60.00	-28.51	QP	P	
10	5.7975	1.50	10.24	11.74	50.00	-38.26	AVG	P	
11	9.1274	18.83	10.12	28.95	60.00	-31.05	QP	P	
12	9.1274	-0.96	10.12	9.16	50.00	-40.84	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54
Note: The more stringent limit applies at transition frequencies.	

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.


5.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as DH5_2402MHz below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	43.2017	26.56	-8.82	17.74	40.00	-22.26	QP	100	41	P	
2	64.6594	26.52	-10.36	16.16	40.00	-23.84	QP	100	307	P	
3	163.1818	26.48	-9.17	17.31	43.50	-26.19	QP	100	30	P	
4	452.7197	26.98	-4.91	22.07	46.00	-23.93	QP	100	113	P	
5 *	787.8513	27.96	1.97	29.93	46.00	-16.07	QP	100	194	P	
6	948.7610	26.18	3.20	29.38	46.00	-16.62	QP	100	0	P	

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Vertical

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	36.0007	27.64	-8.57	19.07	40.00	-20.93	QP	100	52	P	
2	151.5972	26.02	-8.70	17.32	43.50	-26.18	QP	100	144	P	
3	276.1235	27.09	-8.95	18.14	46.00	-27.86	QP	100	328	P	
4	508.2582	27.27	-3.37	23.90	46.00	-22.10	QP	100	256	P	
5 *	787.8513	30.68	1.97	32.65	46.00	-13.35	QP	100	134	P	
6	945.4399	27.62	3.23	30.85	46.00	-15.15	QP	100	165	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
GFSK Lowest Channel (2441MHz)							
4804	79.18	-14.72	64.46	74	-9.54	H	PK
4804	59.29	-14.72	44.57	54	-9.43	H	AV
7206	64.82	-8.41	56.41	74	-17.59	H	PK
7206	48.8	-8.41	40.39	54	-13.61	H	AV
4804	74.02	-14.72	59.3	74	-14.7	V	PK
4804	59.31	-14.72	44.59	54	-9.41	V	AV
7206	65.98	-8.41	57.57	74	-16.43	V	PK
7206	49.85	-8.41	41.44	54	-12.56	V	AV
GFSK Middle Channel (2441MHz)							
4882	74.45	-14.64	59.81	74	-14.19	H	PK
4882	60.49	-14.64	45.85	54	-8.15	H	AV
7323	64.85	-8.28	56.57	74	-17.43	H	PK
7323	47.97	-8.28	39.69	54	-14.31	H	AV
4882	77.74	-14.64	63.1	74	-10.9	V	PK
4882	57.84	-14.64	43.2	54	-10.8	V	AV
7323	62.79	-8.28	54.51	74	-19.49	V	PK
7323	49.22	-8.28	40.94	54	-13.06	V	AV
GFSK Highest Channel (2480MHz)							
4960	78.35	-14.53	63.82	74	-10.18	H	PK
4960	61.13	-14.53	46.6	54	-7.4	H	AV
7440	65.93	-8.13	57.8	74	-16.2	H	PK
7440	47.31	-8.13	39.18	54	-14.82	H	AV
4960	73.78	-14.53	59.25	74	-14.75	V	PK
4960	57.75	-14.53	43.22	54	-10.78	V	AV
7440	63.33	-8.13	55.2	74	-18.8	V	PK
7440	50.58	-8.13	42.45	54	-11.55	V	AV

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded in report. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.


6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel GFSK (2402MHz)							
2310	69.07	-21.34	47.73	74	-26.27	H	PK
2310	52.32	-21.34	30.98	54	-23.02	H	AV
2390	68.41	-20.96	47.45	74	-26.55	H	PK
2390	51.03	-20.96	30.07	54	-23.93	H	AV
2400	68.46	-20.91	47.55	74	-26.45	H	PK
2400	53.77	-20.91	32.86	54	-21.14	H	AV
2310	67.47	-21.34	46.13	74	-27.87	V	PK
2310	52.85	-21.34	31.51	54	-22.49	V	AV
2390	66.67	-20.96	45.71	74	-28.29	V	PK
2390	50.78	-20.96	29.82	54	-24.18	V	AV
2400	70.81	-20.91	49.9	74	-24.1	V	PK
2400	55.8	-20.91	34.89	54	-19.11	V	AV
Highest Channel GFSK (2480MHz)							
2483.50	71.56	-20.51	51.05	74	-22.95	H	PK
2483.50	55.62	-20.51	35.11	54	-18.89	H	AV
2500	68.17	-20.43	47.74	74	-26.26	H	PK
2500	52.26	-20.43	31.83	54	-22.17	H	AV
2483.50	67.54	-20.51	47.03	74	-26.97	V	PK
2483.50	52.2	-20.51	31.69	54	-22.31	V	AV
2500	64.61	-20.43	44.18	74	-29.82	V	PK
2500	50.21	-20.43	29.78	54	-24.22	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

7. Frequency Hopping System

7.1 Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.2 Test Procedure

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

7.3 Test Data and Results

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8. Dwell Time

8.1 Standard and Limit

According to 15.247 (a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
- 3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- 4) Sweep Time is more than once pulse time.
- 5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- 6) Measure the maximum time duration of one single pulse.
- 7) Set the EUT for packet transmitting.
- 8) Measure the maximum time duration of one single pulse.
- 9) The EUT was set to the Hopping Mode for Dwell Time Test.



Test Setup Block Diagram

8.3 Test Data and Results

Left earphone:

Test Mode	Data Packet	Channel (MHz)	Pulse Duration (ms)	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	2441	0.383	122.56	<400	Pass
	DH3	2441	1.638	258.804	<400	Pass
	DH5	2441	2.887	245.395	<400	Pass
Pi/4 DQPSK	2DH1	2441	0.391	124.729	<400	Pass
	2DH3	2441	1.643	244.807	<400	Pass
	2DH5	2441	2.891	277.536	<400	Pass


Right earphone:

Test Mode	Data Packet	Channel (MHz)	Pulse Duration (ms)	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	2441	0.382	121.476	<400	Pass
	DH3	2441	1.639	250.767	<400	Pass
	DH5	2441	2.887	337.779	<400	Pass
Pi/4 DQPSK	2DH1	2441	0.392	124.656	<400	Pass
	2DH3	2441	1.644	267.972	<400	Pass
	2DH5	2441	2.892	309.444	<400	Pass


Left earphone:

GFSK (2441MHz)


Burst(DH1)




Accumulate(DH1)




Burst(DH3)




Accumulate(DH3)



Burst(DH5)




Accumulate(DH5)




Pi/4 DQPSK (2441MHz)


Burst(2DH1)




Accumulate(2DH1)



Burst(2DH3)




Accumulate(2DH3)



Burst(2DH5)




Accumulate(2DH5)




Right earphone:

GFSK (2441MHz)


Burst(DH1)




Accumulate(DH1)



Burst(DH3)




Accumulate(DH3)



Burst(DH5)




Accumulate(DH5)




Pi/4 DQPSK (2441MHz)


Burst(2DH1)




Accumulate(2DH1)



Burst(2DH3)




Accumulate(2DH3)



Burst(2DH5)



Accumulate(2DH5)



9. Maximum Peak Conducted Output Power

9.1 Standard and Limit

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 2MHz, VBW = 6MHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

9.3 Test Data and Results


Left earphone:

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
GFSK	2402	1.24	21	Pass
	2441	1.22	21	Pass
	2480	1.3	21	Pass
Pi/4 DQPSK	2402	2.14	21	Pass
	2441	2.11	21	Pass
	2480	2.19	21	Pass


Right earphone:

Test Mode	Test Channel MHz	Conducted Output Power (dBm)	Limit (dBm)	Test Result
GFSK	2402	-0.08	21	Pass
	2441	0.12	21	Pass
	2480	0.34	21	Pass
Pi/4 DQPSK	2402	0.82	21	Pass
	2441	1.03	21	Pass
	2480	1.21	21	Pass

Left earphone:



Right earphone:



10. Occupied Bandwidth(-20dB)

10.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

10.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.



Test Setup Block Diagram

10.3 Test Data and Results


Left earphone:

Test Mode	Test Channel (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
GFSK	2402	0.952	0.86254
	2441	0.949	0.86474
	2480	0.938	0.85478
Pi/4 DQPSK	2402	1.305	1.1798
	2441	1.277	1.1763
	2480	1.276	1.1812


Right earphone:

Test Mode	Test Channel (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
GFSK	2402	0.947	0.86597
	2441	0.954	0.85749
	2480	0.944	0.85751
Pi/4 DQPSK	2402	1.31	1.1910
	2441	1.301	1.1753
	2480	1.301	1.1773

Left earphone:



Right earphone:




11. Carrier Frequencies Separation

11.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

11.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 30kHz, VBW = 100kHz, Sweep = Auto, Detector = Peak.
- 4) By using the Max Hold function, record the separation of two adjacent channels.
- 5) Measure the frequency difference of these two adjacent channels by spectrum analyzer mark function. and then plot the result on the screen of the spectrum analyzer.
- 6) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

11.3 Test Data and Results

Left earphone:


Test Mode	Test Channel	Test Freq. 1 (MHz)	Test Freq. 2 (MHz)	CFS (MHz)	Limit (MHz)
GFSK	Lowest	2402.074	2403.026	0.952	0.635
	Middle	2441.002	2442.004	1.002	0.633
	Highest	2478.996	2479.992	0.996	0.625
Pi/4 DQPSK	Lowest	2401.85	2402.834	0.984	0.87
	Middle	2440.834	2441.844	1.01	0.851
	Highest	2478.982	2479.884	0.902	0.851

Right earphone:


Test Mode	Test Channel	Test Freq. 1 (MHz)	Test Freq. 2 (MHz)	CFS (MHz)	Limit (MHz)
GFSK	Lowest	2401.928	2403.002	1.074	0.631
	Middle	2441.012	2442.026	1.014	0.636
	Highest	2479.02	2480.044	1.024	0.629
Pi/4 DQPSK	Lowest	2402.008	2403.004	0.996	0.873
	Middle	2440.864	2442.014	1.15	0.867
	Highest	2478.862	2480.186	1.324	0.867

Note: $CFS(\text{Channel Frequency Separation}) = \text{Test Freq. 2} - \text{Test Freq. 1}$

Left earphone:



Right earphone:



12. Number of Hopping Channel

12.1 Standard and Limit

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

12.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Set the spectrum analyzer on Max hold mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- 5) Set the spectrum analyzer on View mode and then plot the result on the screen of the spectrum analyzer.
- 6) Repeat the above procedures until all frequencies measured were complete.



12.3 Test Data and Results

Left earphone:

Test Mode	Number of Hopping Channel	Limit	Test Result
GFSK	79	15	Pass
Pi/4 DQPSK	79	15	Pass

Right earphone:

Test Mode	Number of Hopping Channel	Limit	Test Result
GFSK	79	15	Pass
Pi/4 DQPSK	79	15	Pass

Number of Hopping Channel

GFSK

Keysight Spectrum Analyzer - Sweep SA

Center Freq 2.441750000 GHz

Bandwidth: 100 kHz

Resolution: 100 Hz

Span: 100 kHz

Reference Level: -100 dBm

Trace 1: 100 dBm

Trace 2: 100 dBm

Trace 3: 100 dBm

Trace 4: 100 dBm

Trace 5: 100 dBm

Trace 6: 100 dBm

Trace 7: 100 dBm

Trace 8: 100 dBm

Trace 9: 100 dBm

Trace 10: 100 dBm

Trace 11: 100 dBm

Trace 12: 100 dBm

Trace 13: 100 dBm

Trace 14: 100 dBm

Trace 15: 100 dBm

Trace 16: 100 dBm

Trace 17: 100 dBm

Trace 18: 100 dBm

Trace 19: 100 dBm

Trace 20: 100 dBm

Trace 21: 100 dBm

Trace 22: 100 dBm

Trace 23: 100 dBm

Trace 24: 100 dBm

Trace 25: 100 dBm

Trace 26: 100 dBm

Trace 27: 100 dBm

Trace 28: 100 dBm

Trace 29: 100 dBm

Trace 30: 100 dBm

Trace 31: 100 dBm

Trace 32: 100 dBm

Trace 33: 100 dBm

Trace 34: 100 dBm

Trace 35: 100 dBm

Trace 36: 100 dBm

Trace 37: 100 dBm

Trace 38: 100 dBm

Trace 39: 100 dBm

Trace 40: 100 dBm

Trace 41: 100 dBm

Trace 42: 100 dBm

Trace 43: 100 dBm

Trace 44: 100 dBm

Trace 45: 100 dBm

Trace 46: 100 dBm

Trace 47: 100 dBm

Trace 48: 100 dBm

Trace 49: 100 dBm

Trace 50: 100 dBm

Trace 51: 100 dBm

Trace 52: 100 dBm

Trace 53: 100 dBm

Trace 54: 100 dBm

Trace 55: 100 dBm

Trace 56: 100 dBm

Trace 57: 100 dBm

Trace 58: 100 dBm

Trace 59: 100 dBm

Trace 60: 100 dBm

Trace 61: 100 dBm

Trace 62: 100 dBm

Trace 63: 100 dBm

Trace 64: 100 dBm

Trace 65: 100 dBm

Trace 66: 100 dBm

Trace 67: 100 dBm

Trace 68: 100 dBm

Trace 69: 100 dBm

Trace 70: 100 dBm

Trace 71: 100 dBm

Trace 72: 100 dBm

Trace 73: 100 dBm

Trace 74: 100 dBm

Trace 75: 100 dBm

Trace 76: 100 dBm

Trace 77: 100 dBm

Trace 78: 100 dBm

Trace 79: 100 dBm

Trace 80: 100 dBm

Trace 81: 100 dBm

Trace 82: 100 dBm

Trace 83: 100 dBm

Trace 84: 100 dBm

Trace 85: 100 dBm

Trace 86: 100 dBm

Trace 87: 100 dBm

Trace 88: 100 dBm

Trace 89: 100 dBm

Trace 90: 100 dBm

Trace 91: 100 dBm

Trace 92: 100 dBm

Trace 93: 100 dBm

Trace 94: 100 dBm

Trace 95: 100 dBm

Trace 96: 100 dBm

Trace 97: 100 dBm

Trace 98: 100 dBm

Trace 99: 100 dBm

Trace 100: 100 dBm

Trace 101: 100 dBm

Trace 102: 100 dBm

Trace 103: 100 dBm

Trace 104: 100 dBm

Trace 105: 100 dBm

Trace 106: 100 dBm

Trace 107: 100 dBm

Trace 108: 100 dBm

Trace 109: 100 dBm

Trace 110: 100 dBm

Trace 111: 100 dBm

Trace 112: 100 dBm

Trace 113: 100 dBm

Trace 114: 100 dBm

Trace 115: 100 dBm

Trace 116: 100 dBm

Trace 117: 100 dBm

Trace 118: 100 dBm

Trace 119: 100 dBm

Trace 120: 100 dBm

Trace 121: 100 dBm

Trace 122: 100 dBm

Trace 123: 100 dBm

Trace 124: 100 dBm

Trace 125: 100 dBm

Trace 126: 100 dBm

Trace 127: 100 dBm

Trace 128: 100 dBm

Trace 129: 100 dBm

Trace 130: 100 dBm

Trace 131: 100 dBm

Trace 132: 100 dBm

Trace 133: 100 dBm

Trace 134: 100 dBm

Trace 135: 100 dBm

Trace 136: 100 dBm

Trace 137: 100 dBm

Trace 138: 100 dBm

Trace 139: 100 dBm

Trace 140: 100 dBm

Trace 141: 100 dBm

Trace 142: 100 dBm

Trace 143: 100 dBm

Trace 144: 100 dBm

Trace 145: 100 dBm

Trace 146: 100 dBm

Trace 147: 100 dBm

Trace 148: 100 dBm

Trace 149: 100 dBm

Trace 150: 100 dBm

Trace 151: 100 dBm

Trace 152: 100 dBm

Trace 153: 100 dBm

Trace 154: 100 dBm

Trace 155: 100 dBm

Trace 156: 100 dBm

Trace 157: 100 dBm

Trace 158: 100 dBm

Trace 159: 100 dBm

Trace 160: 100 dBm

Trace 161: 100 dBm

Trace 162: 100 dBm

Trace 163: 100 dBm

Trace 164: 100 dBm

Trace 165: 100 dBm

Trace 166: 100 dBm

Trace 167: 100 dBm

Trace 168: 100 dBm

Trace 169: 100 dBm

Trace 170: 100 dBm

Trace 171: 100 dBm

Trace 172: 100 dBm

Trace 173: 100 dBm

Trace 174: 100 dBm

Trace 175: 100 dBm

Trace 176: 100 dBm

Trace 177: 100 dBm

Trace 178: 100 dBm

Trace 179: 100 dBm

Trace 180: 100 dBm

Trace 181: 100 dBm

Trace 182: 100 dBm

Trace 183: 100 dBm

Trace 184: 100 dBm

Trace 185: 100 dBm

Trace 186: 100 dBm

Trace 187: 100 dBm

Trace 188: 100 dBm

Trace 189: 100 dBm

Trace 190: 100 dBm

Trace 191: 100 dBm

Trace 192: 100 dBm

Trace 193: 100 dBm

Trace 194: 100 dBm

Trace 195: 100 dBm

Trace 196: 100 dBm

Trace 197: 100 dBm

Trace 198: 100 dBm

Trace 199: 100 dBm

Trace 200: 100 dBm

Trace 201: 100 dBm

Trace 202: 100 dBm

Trace 203: 100 dBm

Trace 204: 100 dBm

Trace 205: 100 dBm

Trace 206: 100 dBm

Trace 207: 100 dBm

Trace 208: 100 dBm

Trace 209: 100 dBm

Trace 210: 100 dBm

Trace 211: 100 dBm

Trace 212: 100 dBm

Trace 213: 100 dBm

Trace 214: 100 dBm

Trace 215: 100 dBm

Trace 216: 100 dBm

Trace 217: 100 dBm

Trace 218: 100 dBm

Trace 219: 100 dBm

Trace 220: 100 dBm

Trace 221: 100 dBm

Trace 222: 100 dBm


Trace 223: 100 dBm

Trace 224: 100 dBm


Trace 225: 100 dBm

Trace 226: 100 dBm

Trace 227: 100 dB




Pi/4 DQPSK	
------------	--




Right earphone:

Number of Hopping Channel

GFSK



Pi/4 DQPSK



13. Band-edge Emission(Conducted)

13.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

13.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
- 6) Measure the emission and marking the edge frequency.
- 7) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

13.3 Test Data and Results

Left earphone:

Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
No-Hopping					
GFSK	Lowest	2402	-45.86	-20	Pass
	Highest	2480	-51.56	-20	Pass
Pi/4 DQPSK	Lowest	2402	-45.13	-20	Pass
	Highest	2480	-53.45	-20	Pass
Hopping					
GFSK	Lowest	2402	-53.06	-20	Pass
	Highest	2480	-52.96	-20	Pass
Pi/4 DQPSK	Lowest	2402	-54.03	-20	Pass
	Highest	2480	-54.57	-20	Pass

Right earphone:

Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
No-Hopping					
GFSK	Lowest	2402	-47.54	-20	Pass
	Highest	2480	-50.34	-20	Pass
Pi/4 DQPSK	Lowest	2402	-48.98	-20	Pass
	Highest	2480	-53.11	-20	Pass
Hopping					
GFSK	Lowest	2402	-51.79	-20	Pass
	Highest	2480	-50.4	-20	Pass
Pi/4 DQPSK	Lowest	2402	-53.09	-20	Pass
	Highest	2480	-53.61	-20	Pass


Left earphone:

No-Hopping GFSK Lowest

Reference Power



Band-edge Emission




No-Hopping GFSK Highest

Reference Power



Band-edge Emission




No-Hopping Pi/4 DQPSK Lowest

Reference Power



Band-edge Emission




No-Hopping Pi/4 DQPSK Highest

Reference Power



Band-edge Emission




Hopping GFSK Lowest

Reference Power



Band-edge Emission




Hopping GFSK Highest

Reference Power



Band-edge Emission




Hopping Pi/4 DQPSK Lowest

Reference Power



Band-edge Emission




Hopping Pi/4 DQPSK Highest

Reference Power



Band-edge Emission




Right earphone:

No-Hopping GFSK Lowest

Reference Power




Band-edge Emission




No-Hopping GFSK Highest

Reference Power




Band-edge Emission




No-Hopping Pi/4 DQPSK Lowest

Reference Power




Band-edge Emission




No-Hopping Pi/4 DQPSK Highest

Reference Power



Band-edge Emission




Hopping GFSK Lowest

Reference Power



Band-edge Emission




Hopping GFSK Highest

Reference Power



Band-edge Emission




Hopping Pi/4 DQPSK Lowest

Reference Power



Band-edge Emission




Hopping Pi/4 DQPSK Highest

Reference Power



Band-edge Emission



14. Conducted RF Spurious Emissions


14.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

14.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.7.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Measure the spurious emissions with frequency range from 9kHz to 26.5GHz.
- 6) Repeat above procedures until all measured frequencies were complete.



Test Setup Block Diagram

14.3 Test Data and Results

Note: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions measurement data.

	GFSK Lowest
--	-------------

Reference Power

Center Freq 2.402000000 GHz

Ref Offset 1.69 dB
Ref 11.69 dBm

Mkr1 2.401 865 0 GHz
0.886 dBm


Center Freq 13.265000000 GHz

Ref Offset 1.69 dB
Ref 11.69 dBm

Mkr1 2.402 6 GHz
0.861 dBm

MARK	MODE	TRIG	F (GHz)	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(A)	2.402 6 GHz	(A)	-0.861 dBm	
2	N	1	f		9.802 4 GHz		-38.892 dBm	
3	N	1	f		4.804 3 GHz		-54.637 dBm	
4	N	1	f		7.199 8 GHz		-47.883 dBm	
6	N	1	f		9.802 4 GHz		-38.892 dBm	

Spurious Emissions



Reference Power

Keysight Spectrum Analyzer - Sweep 5A

Center Freq 2.441000000 GHz

Ref Offset 1.71 dB
Ref 11.71 dBm

Mkr1 2.441 171 0 GHz
1.032 dBm

Start 2.44100000 GHz
#Res BW 100 kHz

Span 1.500 MHz
Sweep 1.000 ms (1001 pts)

#VBW 300 kHz

#Avg Type: RMS
Avgfhold: 100/100

Trig: Free Run
#Atten: 20 dB

11:01:43 PM Apr 30, 2024

THRESH: 0.7, 1.4, 2.1
TYPE: MIN/MAX
REF: 11.71 dBm

Spurious Emissions

Keysight Spectrum Analyzer - Sweep 5A

Center Freq 13.265000000 GHz

Ref Offset 1.71 dB
Ref 11.71 dBm

Mkr1 2.441 4 GHz
0.308 dBm

Start 30 MHz
#Res BW 100 kHz

Span 26.50 GHz
Sweep 2.530 s (30001 pts)

#VBW 300 kHz

#Avg Type: RMS
Avgfhold: 10/10


Trig: Free Run
#Atten: 20 dB

11:01:34 PM Apr 30, 2024

THRESH: 0.7, 1.4, 2.1
TYPE: MIN/MAX
REF: 11.71 dBm

MARK	MODE	FREQ (GHz)	LEVEL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	(Δ)	2.441 4 GHz (Δ)	0.308 dBm
2	N	1	f		9.767 7 GHz	-35.192 dBm
3	N	1	f		4.882 0 GHz	-52.852 dBm
4	N	1	f		7.317 2 GHz	-48.983 dBm
5	N	1	f		9.767 7 GHz	-35.192 dBm

Spurious Emissions



Reference Power

Center Freq 2.480000000 GHz

Ref Offset 1.71 dB
Ref 11.71 dBm

Mkr1 2.480 171.0 GHz
1.047 dBm

Center 2.4800000 GHz
Span 1.500 MHz
Res BW 100 kHz
VBW 300 kHz
Sweep 1.000 ms (1001 pts)

Spurious Emissions

Center Freq 13.265000000 GHz


Ref Offset 1.71 dB
Ref 11.71 dBm

Mkr1 2.480 2 GHz
0.819 dBm

Start 30 MHz
Res BW 100 kHz
VBW 300 kHz
Sweep 2.530 s (30001 pts)

MN	MODE	FREQ	TRF	ICLI	X	Y	FUNCTION	FUNCTION-MATH	FUNCTION-JULI8
1	N	1	f	(A)	2.480 2 GHz	(A)	0.819 dBm		
2	N	1	f		9.913 9 GHz		-35.370 dBm		
3	N	1	f		4.898 6 GHz		-51.850 dBm		
4	N	1	f		7.433 7 GHz		-49.324 dBm		
5	N	1	f		9.913 9 GHz		-35.370 dBm		

Spurious Emissions




Pi/4 DQPSK Lowest

Reference Power



Spurious Emissions




Pi/4 DQPSK Middle

Reference Power



Spurious Emissions




Pi/4 DQPSK Highest

Reference Power



Spurious Emissions




Right earphone:

GFSK Lowest

Reference Power



Spurious Emissions




GFSK Middle

Reference Power



Spurious Emissions




GFSK Highest

Reference Power



Spurious Emissions




Pi/4 DQPSK Lowest

Reference Power



Spurious Emissions




Pi/4 DQPSK Middle

Reference Power



Spurious Emissions




Pi/4 DQPSK Highest

Reference Power



Spurious Emissions



***** END OF REPORT *****