

FCC Test Report

Report No.: 2605T28028EA
Applicant: Shenzhen weiyucheng Technology Co.,Ltd
Address: 201, building C, building B, C, D,Dingfeng hi tech park, shapuwei community,Songgang street, Bao'an District, Shenzhen, China
Product Name: Bluetooth keyboard
Product Model: WY-030
Multiple Models: N/A
Trade Mark: N/A
FCC ID: 2AXK9-WY030
Standards: FCC CFR Title 47 Part 15C (§15.247)
Test Date: 2026-05-26 to 2026-05-28
Test Result: Complied
Report Date: 2026-06-04

Reviewed by:

James fu

James fu
Project Engineer

Approved by:

Jacob Kong

Jacob Kong
Manager

Prepared by:

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen,
Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

Announcement

1. This test report shall not be reproduced except in full, without the written approval of World Alliance Testing & Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
4. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description
00	2026-06-04	Original

Contents

1	General Information	4
1.1	Client Information	4
1.2	Product Description of EUT	4
1.3	Antenna information	4
1.4	Related Submittal(s)/Grant(s).....	5
1.5	Measurement Uncertainty	5
1.6	Laboratory Location.....	5
1.7	Test Methodology	5
2	Description of Measurement.....	6
2.1	Test Configuration.....	6
2.2	Test Auxiliary Equipment	7
2.3	Interconnecting Cables.....	7
2.4	Block Diagram of Connection between EUT and AE	7
2.5	Test Setup.....	8
2.6	Test Procedure	10
2.7	Measurement Method.....	11
2.8	Measurement Equipment	12
3	Test Results	13
3.1	Test Summary.....	13
3.2	Limit	14
3.3	AC Line Conducted Emissions Test Data.....	15
3.4	Radiated emission Test Data.....	17
3.5	RF Conducted Test Data	32
3.5.1	6 dB Emission Bandwidth	32
3.5.2	99% Occupied Bandwidth	33
3.5.3	Maximum Conducted Peak Output Power.....	34
3.5.4	Power Spectral Density.....	35
3.5.5	100 kHz Bandwidth of Frequency Band Edge	36
3.5.6	Conducted Spurious Emission	37
3.5.7	Duty Cycle	38
4	Test Setup Photo.....	39
5	E.U.T Photo	40

1 General Information

1.1 Client Information

Applicant:	Shenzhen weiyucheng Technology Co.,Ltd
Address:	201, building C, building B, C, D,Dingfeng hi tech park, shapuwei community,Songgang street, Bao'an District, Shenzhen, China
Manufacturer:	Shenzhen weiyucheng Technology Co.,Ltd
Address:	201, building C, building B, C, D,Dingfeng hi tech park, shapuwei community,Songgang street, Bao'an District, Shenzhen, China

1.2 Product Description of EUT

The EUT is a Bluetooth keyboard that contains BLE radio, this report covers the full testing of the BLE radio.

Sample Serial Number	3MUU-3 for CE&RE test, 3MUU-2 for RF conducted test (assigned by WATC)
Sample Received Date	2026-05-26
Sample Status	Good Condition
Frequency Range	2402MHz - 2480MHz(BLE1M)
Maximum Conducted Peak Output Power	-0.79dBm
Modulation Technology	GFSK
Spatial Streams	SISO (1TX, 1RX)
Antenna Gain [#]	3.36dBi
Power Supply	DC 3.7V from battery or DC 5V from USB port
Adapter Information	N/A
Modification	Sample No Modification by the test lab

1.3 Antenna information

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
Device Antenna information:	
The BLE antenna is an internal antenna which cannot replace by end-user, please see product internal photos for details.	

1.4 Related Submittal(s)/Grant(s)

FCC Part 15, Subpart C, Equipment Class: DTS, FCC ID: 2AXK9-WY-213

1.5 Measurement Uncertainty

Parameter		Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
AC Power Lines Conducted Emissions		±3.14dB
Emissions, Radiated	Below 30MHz	±2.78dB
	Below 1GHz	±4.84dB
	Above 1GHz	±5.44dB
Emissions, Conducted		1.75dB
Conducted Power		0.74dB
Frequency Error		150Hz
Bandwidth		0.34%
Power Spectral Density		0.74dB
Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.		

1.6 Laboratory Location

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: qa@watc.com.cn

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

1.7 Test Methodology

FCC CFR 47 Part 2

FCC CFR 47 Part 15

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2020

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method

2 Description of Measurement

2.1 Test Configuration

Operating channels:					
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	19	2440	38	2478
1	2404	20	2442	39	2480
...	...	...	...	/	/
18	2438	...	...	/	/
According to ANSI C63.10-2020 chapter 5.6.1 Table 11 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	19	2440	39	2480

Test Mode:				
Transmitting mode:		Keep the EUT in continuous transmitting with modulation		
Exercise software [#] :		N/A, EUT was configured to engineering mode by applicant		
Mode	Data rate	Power Level Setting [#]		
		Low Channel	Middle Channel	High Channel
BLE 1M	1Mbps	default	default	default
The maximum power setting that provided by manufacturer.				

Worst-Case Configuration:
For radiated emissions, EUT was investigated in three orthogonal orientation, the worst-case orientation was recorded in report
For AC power line conducted emission and radiated emission 9kHz-1GHz and above 18GHz were performed with the EUT transmits at the channel with highest output power as worst-case scenario.
For radiated emissions below 30MHz, three antenna orientations (parallel, perpendicular, gound-parallel) were tested, only record the worse case test data in report.


2.2 Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number
Govee	Adapter	BI12T-050200-BdUU	Unknown

2.3 Interconnecting Cables

Manufacturer	Description	Length(m)	From	To
Unknown	USB Cable	1.0	Adapter	EUT


2.4 Block Diagram of Connection between EUT and AE



Note: for reference only, the actual connection setup used for testing please refer to the test photos.

2.5 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:


Below 30MHz (3m SAC)




30MHz-1GHz (3m SAC)




1GHz-18GHz



Above 18GHz



3) RF Conducted Test



2.6 Test Procedure

Conducted emission:

1. The E.U.T is placed on a non-conducting table 40cm from the vertical ground plane and 80cm above the horizontal ground plane (Please refer to the block diagram of the test setup and photographs).
2. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
3. Line conducted data is recorded for both Line and Neutral

Radiated Emission Procedure:

a) For below 30MHz

1. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz- 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were $40 \cdot \log(\text{test distance} / \text{specification distance})$.
2. Loop antenna use, investigation was done on the three antenna orientations (parallel, perpendicular, ground-parallel)
3. The RBW/VBW of receiver is set to 200Hz/1kHz for 9kHz to 150kHz range, to 9kHz/30kHz for 150kHz to 30MHz range for scan Peak emission, 200Hz/9kHz IF BW was used for final measurement in the Quasi-peak or average detection mode for frequency range 9~150kHz/150kHz~30MHz respectively.
4. If the Peak emission complies with the QP limit, then perform final measurement is optional.

b) For 30MHz-1GHz:

1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. The RBW/VBW of receiver is set to 100kHz/300kHz for scan Peak emission, 120kHz IF BW was used for final measurement in the Quasi-peak detection mode.
4. If the Peak emission complies with the QP limit, then perform final measurement is optional.

c) For above 1GHz:

1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m chamber. The measurement distance from the EUT to the receiving antenna is 3 m (1-18GHz) and 1.5 m (above 18GHz).
2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. The RBW/VBW of spectrum analyzer is set to 1MHz/3MHz for scan Peak emission, for measured

average emission, reduce the VBW to 10Hz. (Note: a high VBW (for example 1kHz) may used to scan average emissions to avoid long sweep time.)

4. If the Peak emission complies with the Average limit, then perform average measurement is optional.
5. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
6. Base on FCC 15.31 (f): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

RF Conducted Test:

1. The antenna port of EUT was connected to the RF port of the test equipment (Spectrum analyzer) through Attenuator and RF cable.
2. The cable assembly insertion loss of 6.5/7.5dB (including 6.0 dB Attenuator and 0.5/1.5dB cable) was entered as an offset in the test equipment. Note: Actual cable loss was unavailable at the time of testing, therefore a loss of 0.5dB was assumed as worst case (except for conducted spurious emission test the worst case loss is 1.5dB for up to 25GHz). This was later verified to be true by laboratory. (if the RF cable provided by client, the cable loss declared by client)
3. The EUT is keeping in continuous transmission mode and tested in all modulation modes.

2.7 Measurement Method

Description of Test	Measurement Method
AC Line Conducted Emissions	ANSI C63.10-2020 Section 6.2
Maximum Conducted Output Power	ANSI C63.10-2020 Section 11.9.1.1
Power Spectral Density	ANSI C63.10-2020 Section 11.10.2
6 dB Emission Bandwidth	ANSI C63.10-2020 Section 11.8.1
99% Occupied Bandwidth	ANSI C63.10-2020 Section 6.9.3
100kHz Bandwidth of Frequency Band Edge	ANSI C63.10-2020 Section 6.10
Antenna-port conducted emission	ANSI C63.10-2020 Section 11.11
Radiated emission	ANSI C63.10-2020 Section 63.&6.4&6.5&6.6&11.12.1
Duty Cycle	ANSI C63.10-2020 Section 11.6

2.8 Measurement Equipment

Manufacturer	Description	Model	Management No.	Calibration Date	Calibration Due Date
AC Line Conducted Emission Test					
ROHDE& SCHWARZ	EMI TEST RECEIVER	ESR	101817	2026/4/23	2027/4/22
R&S	LISN	ENV216	101748	2026/4/23	2027/4/22
N/A	Coaxial Cable	NO.12	N/A	2026/4/23	2027/4/22
Farad	Test Software	EZ-EMC	Ver. EMEC-3A1	/	/
Radiated Emission Test					
R&S	EMI test receiver	ESR3	102758	2026/4/23	2027/4/22
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40-N	101608	2026/4/23	2027/4/22
SONOMA INSTRUMENT	Low frequency amplifier	310	186014	2026/4/23	2027/4/22
A.H. Systems	PREAMPLIFIER	PAM-0118P	531	2026/4/23	2027/4/22
COM-POWER	Amplifier	PAM-840A	461306	2026/4/23	2027/4/22
BACL	Loop Antenna	1313-1A	4010611	2024/2/7	2027/2/6
SCHWARZBECK	Log - periodic wideband antenna	VULB 9163	9163-872	2023/7/7	2026/7/6
Astro Antenna Ltd	Horn antenna	AHA-118S	3015	2023/7/6	2026/7/5
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2023/7/10	2026/7/9
Oulitong	Band Reject Filter	OBSF-2400-248 3.5-50N	OE02103119	2026/4/23	2027/4/22
Unknown	6.7G High Pass Filter	Unknown	6.7G	2026/4/23	2027/4/22
N/A	Coaxial Cable	NO.9	N/A	2026/4/23	2027/4/22
N/A	Coaxial Cable	NO.13	N/A	2026/4/23	2027/4/22
N/A	Coaxial Cable	NO.15	N/A	2026/4/23	2027/4/22
N/A	Coaxial Cable	NO.16	N/A	2026/4/23	2027/4/22
Audix	Test Software	E3	191218 V9	/	/
RF Conducted Test					
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV-26	200680/026	2026/4/23	2027/4/22
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40	101419	2026/4/23	2027/4/22
narda	6dB attenuator	603-06-1	N/A	2026/4/23	2027/4/22

Note: All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or International standards.

3 Test Results

3.1 Test Summary


FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
-	99% Occupied Bandwidth	Report only
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.205, §15.209, §15.247(d)	Unwanted emission	Compliance
-	Duty Cycle	Report only


3.2 Limit

Test items	Limit
AC Line Conducted Emissions	See details §15.207 (a)
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Spurious Emissions, 100kHz Bandwidth of Frequency Band Edge	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.3 AC Line Conducted Emissions Test Data

Test Date:	2026-05-27	Test By:	Ryan Zhang
Environment condition:	Temperature: 26°C; Relative Humidity:56%; ATM Pressure: 101.3kPa		





Remark:

Measurement (dBuV)= Reading Level (dBuV) + Correct Factor(dB)


Correct Factor(dB)= LISN Voltage Division Factor (dB)+ Cable loss(dB)


Over Limit = Measurement – Limit

3.4 Radiated emission Test Data

9 kHz-30MHz:

Test Date:	2026-05-27	Test By:	Bard Huang
Environment condition:	Temperature: 25.8°C; Relative Humidity: 69%; ATM Pressure: 100.2kPa		






Project No. : 2605T28028E-RF
Test Mode : Transmitting
Test Voltage : DC 5V
Environment : 25.8°C/69%R.H./100.2kPa
Tested by : Bard Huang
Polarization : PARALLEL
Remark : BLE 1M 2480

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	0.196	30.28	12.36	42.64	101.77	-59.13	Peak
2	0.427	31.30	7.05	38.35	94.99	-56.64	Peak
3	1.247	29.94	-0.21	29.73	65.52	-35.79	Peak
4	3.316	32.10	-3.33	28.77	69.54	-40.77	Peak
5	7.646	37.59	-3.88	33.71	69.54	-35.83	Peak
6	20.631	36.10	-3.13	32.97	69.54	-36.57	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain
Result = Reading + Factor
Over Limit = Result - Limit
SA setting: RBW/VBW: 10kHz/30kHz, DET: PK

30MHz-1GHz:


Test Date:	2026-05-26	Test By:	Bard Huang
Environment condition:	Temperature: 25.6°C; Relative Humidity:71%; ATM Pressure: 100.1kPa		



Project No. : 2605T28028E-RF
Test Mode : Transmitting
Test Voltage : DC 5V
Environment : 25.6°C/71%R.H./100.1kPa
Tested by : Bard Huang
Polarization : horizontal
Remark : BLE 1M 2480

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	47.742	28.66	-12.08	16.58	40.00	-23.42	Peak
2	122.996	36.49	-16.32	20.17	43.50	-23.33	Peak
3	168.045	34.93	-16.35	18.58	43.50	-24.92	Peak
4	239.987	40.56	-12.65	27.91	46.00	-18.09	Peak
5	361.714	36.06	-9.49	26.57	46.00	-19.43	Peak
6	988.235	29.06	-0.69	28.37	54.00	-25.63	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain
Result = Reading + Factor
Over Limit = Result - Limit
SA setting: Pre-scan: RBW/VBW: 100kHz/300kHz, DET: PK
Final measure: RBW: 120kHz, DET: QP



Project No. : 2605T28028E-RF
Test Mode : Transmitting
Test Voltage : DC 5V
Environment : 25.6°C/71%R.H./100.1kPa
Tested by : Bard Huang
Polarization : vertical
Remark : BLE 1M 2480

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	43.013	35.97	-12.30	23.67	40.00	-16.33	Peak
2	112.229	30.87	-14.43	16.44	43.50	-27.06	Peak
3	210.140	46.89	-13.82	33.07	43.50	-10.43	Peak
4	264.050	37.72	-12.07	25.65	46.00	-20.35	Peak
5	361.555	35.26	-9.50	25.76	46.00	-20.24	Peak
6	955.020	29.80	-1.12	28.68	46.00	-17.32	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain
Result = Reading + Factor
Over Limit = Result - Limit
SA setting: Pre-scan: RBW/VBW: 100kHz/300kHz, DET: PK
Final measure: RBW: 120kHz, DET: QP

Above 1GHz:

Test Date:	2026-05-26~2026-05-27	Test By:	Bard Huang
Environment condition:	Temperature: 25.6~25.8°C; Relative Humidity:69~71%; ATM Pressure:100.1~100.2k Pa		

Frequency (MHz)	Reading level (dBμV)	Polar	Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
BLE 1M							
Low Channel							
4804.000	51.25	horizontal	-2.42	48.83	74.00	-25.17	Peak
4804.000	47.48	vertical	-2.42	45.06	74.00	-28.94	Peak
Middle Channel							
4880.000	47.98	horizontal	-1.88	46.10	74.00	-27.90	Peak
4880.000	47.57	vertical	-1.88	45.69	74.00	-28.31	Peak
High Channel							
4960.000	48.39	horizontal	-1.70	46.69	74.00	-27.31	Peak
4960.000	50.37	vertical	-1.70	48.67	74.00	-25.33	Peak

Remark:

Corrected Amplitude= Reading level + corrected Factor

Corrected Factor = Antenna factor + Cable loss – Amplifier gain


Margin = Corrected Amplitude – Limit


For the test result of Peak below the Peak limit more than 20dB, which can compliance with the average limit, just the Peak level was recorded.


The emission levels of other frequencies that were lower than the limit 20dB, not show in test report.


For emissions in 18GHz-25GHz range, all emissions were investigated and in the noise floor level.


Test plot for worst case as below:


















Radiated Band edge:









3.5 RF Conducted Test Data

Test Date:	2026-05-27~2026-05-28	Test By:	Ryan Zhang
Environment condition:	Temperature: 25.2~25.4°C; Relative Humidity: 55~57%; ATM Pressure: 101.1~101.3kPa		


3.5.1 6 dB Emission Bandwidth

Chain 0, BLE 1M


Channel	Result (MHz)	Limit (MHz)	Verdict
Low	0.952	≥0.5	Pass
Middle	0.920	≥0.5	Pass
High	0.884	≥0.5	Pass

BLE 1M


BLE_1M_Low_Channel



BLE_1M_Middle_Channel



BLE_1M_High_Channel




3.5.2 99% Occupied Bandwidth

Chain 0, BLE 1M


Channel	99% OBW (MHz)
Low	1.384
Middle	1.316
High	1.288

BLE_1M_Low_Channel




ProjectNo.:2605T28028E-RF Tester:Ryan Zhang
Date: 27.MAY.2026 10:01:18

BLE_1M_Middle_Channel



ProjectNo.:2605T28028E-RF Tester:Ryan Zhang
Date: 27.MAY.2026 14:21:02

BLE_1M_High_Channel




ProjectNo.:2605T28028E-RF Tester:Ryan Zhang
Date: 27.MAY.2026 14:17:14

3.5.3 Maximum Conducted Peak Output Power


Chain 0, BLE 1M

Channel	Peak Output Power (dBm)	Limit (dBm)	Verdict
Low	-0.94	30.00	Pass
Middle	-0.84	30.00	Pass
High	-0.79	30.00	Pass


BLE_1M_Low_Channel



BLE_1M_Middle_Channel



BLE_1M_High_Channel




3.5.4 Power Spectral Density


Chain 0, BLE 1M

Channel	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low	-17.02	8	Pass
Middle	-16.52	8	Pass
High	-15.89	8	Pass


BLE_1M_Low_Channel



BLE_1M_Middle_Channel



BLE_1M_High_Channel




3.5.5 100 kHz Bandwidth of Frequency Band Edge

Chain 0, BLE 1M


Channel	Result (dB)	Limit (dB)	Verdict
Low	46.72	20	Pass
High	46.67	20	Pass

BLE_1M_Low_Channel



ProjectNo.:2605T28028E-RF Tester:Ryan Zhang
Date: 27 MAY 2026 14:21:02

BLE_1M_High_Channel




ProjectNo.:2605T28028E-RF Tester:Ryan Zhang
Date: 27 MAY 2026 14:19:10

3.5.6 Conducted Spurious Emission


Chain 0, BLE 1M

Channel	Result (dB)	Limit (dB)	Verdict
Low	28.40	20	Pass
Middle	28.07	20	Pass
High	27.59	20	Pass


BLE_1M_Low_Channel



BLE_1M_Middle_Channel



BLE_1M_High_Channel




3.5.7 Duty Cycle

Chain 0, BLE 1M

Channel	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
Middle	0.444	0.624	71.15	1.48	2252	3

BLE_1M_Middle_Channel



ProjectNo.:2605T28028E-RF Tester:Ryan Zhang
 Date: 27.MAY.2026 09:59:16

4 Test Setup Photo

Please refer to the attachment 2605T28028E Test Setup photo.

5 E.U.T Photo

Please refer to the attachment 2605T28028E External photo and 2605T28028E Internal photo.

---End of Report---