FCC REPORT
(Bluetooth)

Applicant:	UbiqiSense Aps
Address of Applicant:	Bryghusgade 8, DK-1473 Copenhagen K, Denmark
Equipment Under Test (EUT)	
Product Name:	Wireless Object Detector
Model No.:	UC2-N, UC2-W
Trade mark:	Ubiqisense
FCC ID:	2AXKGUC2NW
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	27 Oct., 2020
Date of Test:	28 Oct., to 25 Nov., 2020
Date of report issued:	26 Nov., 2020
Test Result:	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	*26 Nov., 2020*	*Original*

Tested by: YT Yang ***Date:*** *26 Nov., 2020*

Test Engineer

Reviewed by: Winner zhang ***Date:*** *26 Nov., 2020*

Project Engineer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 CLIENT INFORMATION 5
5.2 GENERAL DESCRIPTION OF E.U.T. 5
5.3 TEST ENVIRONMENT AND MODE, AND TEST SAMPLES PLANS 6
5.4 DESCRIPTION OF SUPPORT UNITS 6
5.5 MEASUREMENT UNCERTAINTY 6
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD 6
5.7 LABORATORY FACILITY 6
5.8 LABORATORY LOCATION 7
5.9 TEST INSTRUMENTS LIST 7

6 TEST RESULTS AND MEASUREMENT DATA 8

6.1 ANTENNA REQUIREMENT 8
6.2 CONDUCTED EMISSIONS 9
6.3 CONDUCTED OUTPUT POWER 12
6.4 20DB OCCUPY BANDWIDTH 15
6.5 CARRIER FREQUENCIES SEPARATION 18
6.6 HOPPING CHANNEL NUMBER 22
6.7 DWELL TIME 24
6.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 27
6.9 BAND EDGE 28
6.9.1 Conducted Emission Method 28
6.9.2 Radiated Emission Method 32
6.10 SPURIOUS EMISSION 45
6.10.1 Conducted Emission Method 45
6.10.2 Radiated Emission Method 48

7 TEST SETUP PHOTO 53

8 EUT CONSTRUCTIONAL DETAILS 55

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna Requirement	15.203 & 15.247 (b)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Spurious Emission	15.205 & 15.209	Pass
Band Edge	15.247(d)	Pass

Remark:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *N/A: Not Applicable.*
3. *The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).*

Test Method:	*ANSI C63.10-2013* *KDB 558074 D01 15.247 Meas Guidance v05r02*

5 General Information

5.1 Client Information

Applicant:	UbiqiSense Aps
Address:	Bryghusgade 8, DK-1473 Copenhagen K, Denmark
Manufacturer:	SHENZHEN XUANTONGWEI TECHNOLOGY CO., LTD.
Address:	Rm301, Building 4, Shenzhen Software Park, Kejizhong 2nd Road, HI-TECH PARK, Nanshan District, Shenzhen City, China.
Factory:	XUANTONGWEI（CHONGQING）ELECTRONICS TECHNOLOGY CO., LTD.
Address:	Building 11, Phase 2, Jinfeng Electronic Information Industry Park, Jiulongpo District, Chongqing, China

5.2 General Description of E.U.T.

Product Name:	Wireless Object Detector
Model No.:	UC2-N, UC2-W
Operation Frequency:	2402MHz~2480MHz
Transfer rate:	1/2/3 Mbits/s
Number of channel:	79
Modulation type:	GFSK, π/4-DQPSK, 8DPSK
Modulation technology:	FHSS
Antenna Type:	Internal Antenna
Antenna gain:	2.0 dBi
AC adapter:	Model: CW1201000RE Input: AC100-240V, 50/60Hz, 0.4A Output: DC 12V, 1A
Remark:	Model: UC2-N and UC2-W are the same internally, with the same circuit design, layout, components used and internal wiring. The only difference is the camera: UC2-N uses a standard camera UC2-W uses a wide-angle camera
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel for GFSK, π/4-DQPSK, 8DPSK							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
…	…	…	…	…	…	…	…
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		
Remark: Channel 0, 39 &78 selected for GFSK, π/4-DQPSK and 8DPSK.							

5.3 Test environment and mode, and test samples plans

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test Modes:	
Non-hopping mode:	Keep the EUT in continuous transmitting mode with worst case data rate.
Hopping mode:	Keep the EUT in hopping mode.
Remark	GFSK (1 Mbps) is the worst case mode.

Radiated Emission: The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

5.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.
Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.9 Test Instruments list

Radiated Emission:

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2020	07-21-2021
Loop Antenna	SCHWARZBECK	FMZB1519B	044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
				11-18-2020	11-17-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
				11-18-2020	11-17-2021
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021
RF Switch Unit	MWRFTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTEST	MTS8200	Version: 2.0.0.0		

Conducted Emission:

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2020	07-20-2021
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and measurement data

6.1 Antenna Requirement

Standard requirement:	FCC Part 15 C Section 15.203 & 247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The Bluetooth antenna is an Internal antenna which permanently attached, and the best case gain of the antenna is 2.0 dBi.	

6.2 Conducted Emissions

Test Requirement:	FCC Part 15 C Section 15.207
Test Frequency Range:	150 kHz to 30 MHz
Class / Severity:	Class B
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement.

Test Instruments:	Refer to section 5.9 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data:

Product name:	Wireless Object Detector	**Product model:**	UC2-N
Test by:	YT	**Test mode:**	BT Tx mode
Test frequency:	150 kHz ~ 30 MHz	**Phase:**	Line
Test voltage:	AC 120 V/60 Hz	**Environment:**	Temp: 22.5℃ Huni: 55%



	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.178	34.65	-0.58	-0.12	10.77	44.72	64.59	-19.87	QP
2	0.246	22.45	-0.57	-0.21	10.75	32.42	51.91	-19.49	Average
3	0.385	21.01	-0.49	0.33	10.72	31.57	48.17	-16.60	Average
4	0.489	21.98	-0.44	-0.26	10.76	32.04	46.19	-14.15	Average
5	0.529	35.91	-0.45	-0.36	10.76	45.86	56.00	-10.14	QP
6	0.585	25.36	-0.48	-0.37	10.76	35.27	46.00	-10.73	Average
7	0.589	38.36	-0.48	-0.37	10.76	48.27	56.00	-7.73	QP
8	0.611	27.04	-0.49	-0.38	10.77	36.94	46.00	-9.06	Average
9	1.106	30.78	-0.60	0.35	10.88	41.41	56.00	-14.59	QP
10	1.602	30.64	-0.54	-0.07	10.93	40.96	56.00	-15.04	QP
11	1.654	20.46	-0.54	-0.11	10.94	30.75	46.00	-15.25	Average
12	9.913	30.87	-0.72	1.92	10.93	43.00	60.00	-17.00	QP

Notes:

1. *An initial pre-scan was performed on the line and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.*

Product name:	Wireless Object Detector	**Product model:**	UC2-N
Test by:	YT	**Test mode:**	BT Tx mode
Test frequency:	150 kHz ~ 30 MHz	**Phase:**	Neutral
Test voltage:	AC 120 V/60 Hz	**Environment:**	Temp: 22.5℃ Huni: 55%



	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.494	33.01	-0.65	0.03	10.76	43.15	56.10	-12.95	QP
2	0.505	24.09	-0.65	0.03	10.76	34.23	46.00	-11.77	Average
3	0.527	33.58	-0.65	0.03	10.76	43.72	56.00	-12.28	QP
4	0.601	38.94	-0.64	0.04	10.77	49.11	56.00	-6.89	QP
5	0.611	30.19	-0.64	0.04	10.77	40.36	46.00	-5.64	Average
6	0.938	20.74	-0.67	0.07	10.85	30.99	46.00	-15.01	Average
7	0.953	31.99	-0.67	0.07	10.86	42.25	56.00	-13.75	QP
8	1.088	20.76	-0.68	0.09	10.88	31.05	46.00	-14.95	Average
9	1.552	19.97	-0.70	0.14	10.93	30.34	46.00	-15.66	Average
10	1.671	34.52	-0.70	0.15	10.94	44.91	56.00	-11.09	QP
11	7.062	32.92	-0.75	0.85	10.80	43.82	60.00	-16.18	QP
12	10.233	13.73	-0.79	1.47	10.94	25.35	50.00	-24.65	Average

Notes:

1. *An initial pre-scan was performed on the line and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level =Receiver Read level + LISN Factor + Aux Factor + Cable Loss.*

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(1)
Receiver setup:	RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz) RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz and < 3MHz)
Limit:	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:

Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK mode			
Lowest channel	7.51	30.00	Pass
Middle channel	7.73	30.00	Pass
Highest channel	7.60	30.00	Pass
π/4-DQPSK mode			
Lowest channel	6.34	21.00	Pass
Middle channel	6.52	21.00	Pass
Highest channel	6.40	21.00	Pass
8DPSK mode			
Lowest channel	6.40	21.00	Pass
Middle channel	6.49	21.00	Pass
Highest channel	6.43	21.00	Pass

Test plot as follows:

Modulation mode: GFSK



Date: 7.NOV.2020 13:01:51

Lowest channel



Date: 7.NOV.2020 13:02:03

Middle channel



Date: 7.NOV.2020 13:02:19

Highest channel

Modulation mode: π/4-DQPSK



Date: 7.NOV.2020 13:03:07

Lowest channel



Date: 7.NOV.2020 13:03:23

Middle channel



Date: 7.NOV.2020 13:03:49

Highest channel

Modulation mode: 8DPSK



Date: 7.NOV.2020 13:04:13

Lowest channel



Date: 7.NOV.2020 13:04:26

Middle channel



Date: 7.NOV.2020 13:04:38

Highest channel

6.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Receiver setup:	RBW=30 kHz, VBW=100 kHz, detector=Peak
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:

Test channel	20dB Occupy Bandwidth (kHz)		
	GFSK	π/4-DQPSK	8DPSK
Lowest	844	1128	1176
Middle	832	1122	1170
Highest	832	1128	1170

Test plot as follows:

Modulation mode: GFSK



Date: 7.NOV.2020 13:05:51

Lowest channel



Date: 7.NOV.2020 13:06:32

Middle channel



Date: 7.NOV.2020 13:07:15

Highest channel

Modulation mode: π/4-DQPSK



Date: 7.NOV.2020 13:08:11

Lowest channel



Date: 7.NOV.2020 13:08:50

Middle channel



Date: 7.NOV.2020 13:09:30

Highest channel

Modulation mode: 8DPSK



Date: 7.NOV.2020 13:10:16

Lowest channel



Date: 7.NOV.2020 13:10:49

Middle channel



Date: 7.NOV.2020 13:11:55

Highest channel

6.5 Carrier Frequencies Separation

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Receiver setup:	RBW=100 kHz, VBW=300 kHz, detector=Peak
Limit:	a) 0.025MHz or the 20dB bandwidth (whichever is greater) b) 0.025MHz or two-thirds of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data:

Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
GFSK			
Lowest	1004	844	Pass
Middle	1004	844	Pass
Highest	1004	844	Pass
π/4-DQPSK mode			
Lowest	1004	752	Pass
Middle	1004	752	Pass
Highest	1004	752	Pass
8DPSK mode			
Lowest	1004	784	Pass
Middle	1004	784	Pass
Highest	1004	784	Pass

Note: According to section 6.4

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	844	844
π/4-DQPSK	1128	752
8DPSK	1176	784

Test plot as follows:

Modulation mode: GFSK



Date: 7.NOV.2020 13:41:00

Lowest channel



Date: 7.NOV.2020 13:41:29

Middle channel



Date: 7.NOV.2020 13:42:08

Highest channel

Modulation mode: π/4-DQPSK



Date: 7.NOV.2020 13:43:43

Lowest channel



Date: 7.NOV.2020 13:44:55

Middle channel



Date: 7.NOV.2020 13:45:46

Highest channel

Modulation mode: 8DPSK



Date: 7.NOV.2020 13:46:53

Lowest channel



Date: 7.NOV.2020 13:47:52

Middle channel



Date: 7.NOV.2020 13:49:05

Highest channel

6.6 Hopping Channel Number

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Center Frequency=2441MHz, Span= 100MHz, Detector=Peak
Limit:	15 channels
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK, π/4-DQPSK, 8DPSK	79	15	Pass

Test plot as follows:

GFSK



Date: 7.NOV.2020 14:01:57

π/4-DQPSK



Date: 7.NOV.2020 14:14:09

8DPSK



Date: 7.NOV.2020 14:25:00

6.7 Dwell Time

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1)
Receiver setup:	RBW=1 MHz, VBW=1 MHz, Span=0 Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data (Worse case):

Mode	Packet	Dwell time (second)	Limit (second)	Result
GFSK	DH1	0.12608	0.4	Pass
	DH3	0.26592		
	DH5	0.31147		
π/4-DQPSK	2-DH1	0.12736	0.4	Pass
	2-DH3	0.26688		
	2-DH5	0.31317		
8DPSK	3-DH1	0.12800	0.4	Pass
	3-DH3	0.26880		
	3-DH5	0.31232		

Note:
The test period = 0.4 Second/Channel x 79 Channel = 31.6 s
Calculation Formula: Dwell time = Ton time per hop * Hopping numbers * Period
For example:
DH1 time slot=0.394*(1600/ (2*79)) * 31.6=126.08ms
DH3 time slot=1.662*(1600/ (4*79)) * 31.6=265.92ms
DH5 time slot=2.920*(1600/ (6*79)) * 31.6=311.47ms

Test plot as follows:

Modulation mode: GFSK



Date: 7.NOV.2020 13:32:15

DH1

Modulation mode: π/4-DQPSK



Date: 7.NOV.2020 13:33:50

2-DH1



Date: 7.NOV.2020 13:32:51

DH3



Date: 7.NOV.2020 13:35:12

2-DH3



Date: 7.NOV.2020 13:33:23

DH5



Date: 7.NOV.2020 13:35:59

2-DH5

Modulation mode: 8DPSK



Date: 7.NOV.2020 13:37:00

3-DH1



Date: 7.NOV.2020 13:37:42

3-DH3



Date: 7.NOV.2020 13:38:28

3-DH5

6.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 2^9 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6.9 Band Edge

6.9.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Non-hopping mode and hopping mode
Test results:	Pass

Test plot as follows:

GFSK

Lowest Channel



Date: 7.NOV.2020 13:13:11

No-hopping mode



Date: 7.NOV.2020 13:14:08

Hopping mode

Highest Channel



Date: 7.NOV.2020 13:23:02

No-hopping mode



Date: 7.NOV.2020 13:23:41

Hopping mode

π/4-DQPSK

Lowest Channel



Date: 7.NOV.2020 13:15:19

No-hopping mode



Date: 7.NOV.2020 13:17:15

Hopping mode

Highest Channel



Date: 7.NOV.2020 13:24:55

No-hopping mode



Date: 7.NOV.2020 13:26:37

Hopping mode

8DPSK

Lowest Channel



Date: 7.NOV.2020 13:17:55

No-hopping mode



Date: 7.NOV.2020 13:21:51

Hopping mode

Highest Channel



Date: 7.NOV.2020 13:27:39

No-hopping mode



Date: 7.NOV.2020 13:30:43

Hopping mode

6.9.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	2310 MHz to 2390 MHz and 2483.5 MHz to 2500 MHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency	Limit (dBuV/m @3m)	Remark		
	Above 1GHz	54.00	Average Value		
		74.00	Peak Value		
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 5.9 for details				
Test mode:	Non-hopping mode				
Test results:	Passed				

GFSK Mode:

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	DH1 Tx mode
Test Channel:	Lowest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.31	27.03	4.28	1.68	0.00	54.30	74.00	-19.70	Peak
2	2390.000	11.25	27.03	4.28	1.68	0.00	44.24	54.00	-9.76	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	DH1 Tx mode
Test Channel:	Lowest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.44	27.03	4.28	1.68	0.00	54.43	74.00	-19.57	Peak
2	2390.000	10.47	27.03	4.28	1.68	0.00	43.46	54.00	-10.54	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	DH1 Tx mode
Test Channel:	Highest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.38	27.27	4.38	1.70	0.00	55.73	74.00	-18.27	Peak
2	2483.500	11.46	27.27	4.38	1.70	0.00	44.81	54.00	-9.19	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	DH1 Tx mode
Test Channel:	Highest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.59	27.27	4.38	1.70	0.00	54.94	74.00	-19.06	Peak
2	2483.500	10.58	27.27	4.38	1.70	0.00	43.93	54.00	-10.07	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

π/4-DQPSK mode

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	2DH1 Tx mode
Test Channel:	Lowest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	22.98	27.03	4.28	1.68	0.00	55.97	74.00	-18.03	Peak
2	2390.000	12.24	27.03	4.28	1.68	0.00	45.23	54.00	-8.77	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	2DH1 Tx mode
Test Channel:	Lowest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.57	27.03	4.28	1.68	0.00	53.56	74.00	-20.44	Peak
2	2390.000	10.35	27.03	4.28	1.68	0.00	43.34	54.00	-10.66	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	2DH1 Tx mode
Test Channel:	Highest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	23.01	27.27	4.38	1.70	0.00	56.36	74.00	-17.64	Peak
2	2483.500	12.55	27.27	4.38	1.70	0.00	45.90	54.00	-8.10	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	2DH1 Tx mode
Test Channel:	Highest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.20	27.27	4.38	1.70	0.00	54.55	74.00	-19.45	Peak
2	2483.500	11.23	27.27	4.38	1.70	0.00	44.58	54.00	-9.42	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

8DPSK mode

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	3DH1 Tx mode
Test Channel:	Lowest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.71	27.03	4.28	1.68	0.00	53.70	74.00	-20.30	Peak
2	2390.000	10.55	27.03	4.28	1.68	0.00	43.54	54.00	-10.46	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	3DH1 Tx mode
Test Channel:	Lowest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.08	27.03	4.28	1.68	0.00	54.07	74.00	-19.93	Peak
2	2390.000	10.55	27.03	4.28	1.68	0.00	43.54	54.00	-10.46	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	3DH1 Tx mode
Test Channel:	Highest channel	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.70	27.27	4.38	1.70	0.00	54.05	74.00	-19.95	Peak
2	2483.500	11.48	27.27	4.38	1.70	0.00	44.83	54.00	-9.17	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	3DH1 Tx mode
Test Channel:	Highest channel	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.07	27.27	4.38	1.70	0.00	54.42	74.00	-19.58	Peak
2	2483.500	10.25	27.27	4.38	1.70	0.00	43.60	54.00	-10.40	Average

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*

6.10 Spurious Emission

6.10.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Non-hopping mode
Test results:	Pass

Test plot as follows:

GFSK

Lowest channel



Date: 7.NOV.2020 13:50:16

π/4-DQPSK

Lowest channel



Date: 7.NOV.2020 13:55:27

Middle channel



Date: 7.NOV.2020 13:52:28

Middle channel



Date: 7.NOV.2020 13:55:59

Highest channel



Date: 7.NOV.2020 13:54:02

Highest channel



Date: 7.NOV.2020 13:56:47

8DPSK

Lowest channel



Date: 7.NOV.2020 13:58:32

Middle channel



Date: 7.NOV.2020 13:59:05

Highest channel



Date: 7.NOV.2020 13:59:47

6.10.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209				
Test Frequency Range:	9 kHz to 25 GHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value

Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test setup:

Below 1GHz



Above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna

	tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Non-hopping mode
Test results:	Pass
Remark:	1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 2. 9 kHz to 30 MHz is noise floor and lower than the limit 20dB, so only shows the data of above 30MHz in this report.

Measurement Data (worst case):

Below 1GHz:

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	BT Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Vertical
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	35.499	54.53	12.62	0.34	0.00	29.94	37.55	40.00	-2.45	QP
2	85.298	56.64	11.47	0.48	0.00	29.60	38.99	40.00	-1.01	QP
3	137.420	54.80	13.65	0.60	0.00	29.29	39.76	43.50	-3.74	QP
4	149.486	55.04	14.26	0.62	0.00	29.22	40.70	43.50	-2.80	QP
5	169.599	52.87	16.40	0.65	0.00	29.05	40.87	43.50	-2.63	QP
6	400.432	51.39	19.10	0.99	0.00	28.78	42.70	46.00	-3.30	QP

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*
3. *The Aux Factor is a notch filter switch box loss, this item is not used.*

Product Name:	Wireless Object Detector	**Product Model:**	UC2-N
Test By:	YT	**Test mode:**	BT Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Horizontal
Test Voltage:	AC 120/60Hz	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	171.393	49.35	16.58	0.66	0.00	29.04	37.55	43.50	-5.95	QP
2	220.617	49.62	18.39	0.74	0.00	28.70	40.05	46.00	-5.95	QP
3	400.432	51.15	19.10	0.99	0.00	28.78	42.46	46.00	-3.54	QP
4	451.135	49.06	19.21	1.05	0.00	28.87	40.45	46.00	-5.55	QP
5	721.726	47.35	20.55	1.34	0.00	28.58	40.66	46.00	-5.34	QP
6	801.786	46.45	20.93	1.40	0.00	28.19	40.59	46.00	-5.41	QP

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*
3. *The Aux Factor is a notch filter switch box loss, this item is not used.*

Above 1GHz (GFSK is Worst case):

Test channel: Lowest channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	56.50	30.78	6.80	2.44	41.81	54.71	74.00	-19.29	Vertical
4804.00	54.17	30.78	6.80	2.44	41.81	52.38	74.00	-21.62	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	46.65	30.78	6.80	2.44	41.81	44.86	54.00	-9.14	Vertical
4804.00	45.18	30.78	6.80	2.44	41.81	43.39	54.00	-10.61	Horizontal
Test channel: Middle channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	55.15	30.96	6.86	2.47	41.84	53.60	74.00	-20.40	Vertical
4882.00	56.19	30.96	6.86	2.47	41.84	54.64	74.00	-19.36	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	47.45	30.96	6.86	2.47	41.84	45.90	54.00	-8.10	Vertical
4882.00	48.63	30.96	6.86	2.47	41.84	47.08	54.00	-6.92	Horizontal
Test channel: Highest channel									
Detector: Peak Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	55.18	31.11	6.91	2.49	41.87	53.82	74.00	-20.18	Vertical
4960.00	54.79	31.11	6.91	2.49	41.87	53.43	74.00	-20.57	Horizontal
Detector: Average Value									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	49.95	31.11	6.91	2.49	41.87	48.59	54.00	-5.41	Vertical
4960.00	48.33	31.11	6.91	2.49	41.87	46.97	54.00	-7.03	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss + Aux Factor – Preamplifier Factor.*
2. *The emission levels of other frequencies are lower than the limit 20dB and not show in test report.*