



SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V06
Report Template Revision Date: 2026-01-30

RF Exposure Evaluation Report

Report No.: CQASZ20260701407E-03
Applicant: AC Infinity Inc.
Address of Applicant: 21880 Baker Parkway, City of Industry, CA 91789 USA
Equipment Under Test (EUT):
Product: AIR CIRCULATOR
Model No.: AC-SCD5-W, AC-SCD5-B, AC-SCD5-G, AC-SCD5-S, AC-SCD5-R, AC-SCD7-W, AC-SCD7-B, AC-SCD7-G, AC-SCD7-S, AC-SCD7-R, AC-SCF5-W, AC-SCF5-B, AC-SCF5-G, AC-SCF5-S, AC-SCF5-R, AC-SCF7-W, AC-SCF7-B, AC-SCF7-G, AC-SCF7-S, AC-SCF7-R
Test Model No.: AC-SCF7-W
Brand Name: AC INFINITY
FCC ID: 2AXMF-SCD
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2026-07-14
Date of Test: 2026-07-14 to 2026-08-06
Date of Issue: 2026-9-4
Test Result: **PASS***
***In the configuration tested, the EUT complied with the standards specified above**

Tested By: Azir Wang
(Azir Wang)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260701407E-03	Rev.01	Initial report	2026-9-4

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	4
3.4 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
4 RF EXPOSURE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.2 1.1.3 EUT RF EXPOSURE EVALUATION	7

3 General Information

3.1 Client Information

Applicant:	AC Infinity Inc.
Address of Applicant:	21880 Baker Parkway, City of Industry, CA 91789 USA
Manufacturer:	AC Infinity Inc.
Address of Manufacturer:	21880 Baker Parkway, City of Industry, CA 91789 USA
Factory:	Jiangmen Honetian Technology Co.,Ltd.
Address of Factory:	No.71, Third Road Xinle, Lile, Jianghai District, JIANGMEN, Guangdong

3.2 General Description of EUT

Product Name:	AIR CIRCULATOR
Model No.:	AC-SCD5-W, AC-SCD5-B, AC-SCD5-G, AC-SCD5-S, AC-SCD5-R, AC-SCD7-W, AC-SCD7-B, AC-SCD7-G, AC-SCD7-S, AC-SCD7-R, AC-SCF5-W, AC-SCF5-B, AC-SCF5-G, AC-SCF5-S, AC-SCF5-R, AC-SCF7-W, AC-SCF7-B, AC-SCF7-G, AC-SCF7-S, AC-SCF7-R
Test Model No.:	AC-SCF7-W
Trade Mark:	AC INFINITY
Software Version:	V1.1
Hardware Version:	V1.1
EUT Power Supply:	Adapter: MODEL:LY049AHU240200 INPUT:100-240~50/60Hz 1.5A OUTPUT:24V $\pm$ 2A

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.3
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps, 2Mbps
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	3.37dBi

3.4 General Description of 2.4G WIFI Classic

Operation Frequency:	IEEE 802.11b/g/n(HT20)/ax(HE20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11ax(HE20) : OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20/ax HE20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps IEEE for 802.11ax(HE20): 8.6Mbps/17.2Mbps/25.8Mbps/34.4Mbps/51.6Mbps/68.8Mbps/77.4Mbps /86.7Mbps/103.3Mbps/114.7Mbps/129.0Mbps/143.4Mbps
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	3.37dBi

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For BLE

Antenna Gain: 3.37dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.17 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.41	2.5±1	3.5	2.24
Middle(2440MHz)	3.73	3.5±1	4.5	2.82
Highest(2480MHz)	3.89	4.0±1	5	3.16

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
3.16	3.37	0.0013668760	1.0	PASS

Note: 1) Refer to report No. CQASZ20260701407E-03 for EUT test Max Conducted Peak Output Power value.

$$2) P_d = (P_{out} * G) / (4 * \pi * R^2) = (3.16 * 2.17) / (4 * 3.1416 * 20^2) = 0.0013668760$$

2) For 2.4G WIFI

Antenna Gain: 3.37dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.17 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

DSSS mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	13.99	14.0±1	15.0	31.62
Middle(2437MHz)	14.66	14.5±1	15.5	35.48
Highest(2462MHz)	13.82	14.0±1	15.0	31.62

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
35.48	3.37	0.0153366014	1.0	PASS

Note: 1) Refer to report No. CQASZ20260701407E-01 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (35.48 * 2.17) / (4 * 3.1416 * 20^2) = 0.0153366014$