TEST REPORT

Applicant:	GuangZhou Muka Intelligent technology Co.,Ltd
Address of Applicant:	Room 806, No.2 Ruifeng Third Street, Huangpu District, Guangzhou City, Guangdong, China
Manufacturer/Factory :	GuangZhou Muka Intelligent technology Co.,Ltd
Address of Manufacturer/Factory :	Room 806, No.2 Ruifeng Third Street, Huangpu District, Guangzhou City, Guangdong, China

Equipment Under Test (EUT)

Product Name:	AMUK Smart Microphone
Model No.:	M200 M300
Trade Mark:	AMUK
FCC ID:	2AXNB-M200
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	Sep. 14, 2020
Date of Test:	Sep. 14, 2020 to Sep. 22, 2020
Date of report issued:	Sep. 22, 2020
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*Sep. 22, 2020*	*Original*

Prepared By: ***Date:*** *Sep. 22, 2020*

Project Engineer

Check By: ***Date:*** *Sep. 22, 2020*

Reviewer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 DESCRIPTION OF SUPPORT UNITS 7
5.4 DEVIATION FROM STANDARDS 7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS 7
5.6 TEST FACILITY 7
5.7 TEST LOCATION 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED PEAK OUTPUT POWER 14
7.4 20DB EMISSION BANDWIDTH 21
7.5 CARRIER FREQUENCIES SEPARATION 28
7.6 HOPPING CHANNEL NUMBER 35
7.7 DWELL TIME 38
7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 46
7.9 BAND EDGE 47
7.9.1 Conducted Emission Method 47
7.9.2 Radiated Emission Method 51
7.10 SPURIOUS EMISSION 53
7.10.1 Conducted Emission Method 53
7.10.2 Radiated Emission Method 60

8 TEST SETUP PHOTO 68

9 EUT CONSTRUCTIONAL DETAILS 68

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Remarks:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10:2013*

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	AMUK Smart Microphone
Model No.:	M200 M300
Test sample(s) ID:	GTS202009000159-1
Sample(s) Status:	Engineer sample
Serial No.:	N/A
Hardware Version:	H1.0
Software Version:	S1.0
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, π/4-DQPSK, 8-DPSK
Antenna Type:	Ceramic antenna
Antenna gain:	0dBi
Power supply:	DC 5V or DC 3.7V Battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 25 2020	June. 24 2021
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 25 2020	June. 24 2021
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 25 2020	June. 24 2021
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 25 2020	June. 24 2021
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 25 2020	June. 24 2021

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 25 2020	June. 24 2021
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 25 2020	June. 24 2021
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 25 2020	June. 24 2021
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 25 2020	June. 24 2021
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 25 2020	June. 24 2021
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 25 2020	June. 24 2021
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 25 2020	June. 24 2021

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 25 2020	June. 24 2021
2	Barometer	ChangChun	DYM3	GTS255	June. 25 2020	June. 24 2021

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The antenna is Ceramic antenna, the best case gain of the is 0dBi, reference to the appendix II for details	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Class / Severity:	Class B
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data:

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3975	32.42	11.01	43.43	57.91	-14.48	QP	P	
2	0.3975	25.49	11.01	36.50	47.91	-11.41	AVG	P	
3	1.0500	11.40	10.43	21.83	56.00	-34.17	QP	P	
4	1.1040	-0.66	10.41	9.75	46.00	-36.25	AVG	P	
5	2.0040	11.08	10.19	21.27	56.00	-34.73	QP	P	
6	2.0040	2.11	10.19	12.30	46.00	-33.70	AVG	P	
7	6.0000	13.61	8.61	22.22	60.00	-37.78	QP	P	
8	6.3150	10.30	8.60	18.90	50.00	-31.10	AVG	P	
9	12.1155	15.64	8.76	24.40	60.00	-35.60	QP	P	
10	12.2910	4.87	8.78	13.65	50.00	-36.35	AVG	P	
11	18.8070	20.80	9.69	30.49	60.00	-29.51	QP	P	
12	18.8070	8.43	9.69	18.12	50.00	-31.88	AVG	P	

Neutral:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3975	32.42	11.01	43.43	57.91	-14.48	QP	P	
2	0.3975	25.95	11.01	36.96	47.91	-10.95	AVG	P	
3	1.1805	12.45	10.39	22.84	56.00	-33.16	QP	P	
4	1.1849	5.29	10.39	15.68	46.00	-30.32	AVG	P	
5	3.2370	1.97	9.79	11.76	46.00	-34.24	AVG	P	
6	3.3585	11.40	9.71	21.11	56.00	-34.89	QP	P	
7	8.8260	17.60	8.51	26.11	60.00	-33.89	QP	P	
8	8.8260	10.44	8.51	18.95	50.00	-31.05	AVG	P	
9	13.2315	13.94	8.91	22.85	60.00	-37.15	QP	P	
10	13.2315	5.08	8.91	13.99	50.00	-36.01	AVG	P	
11	15.6660	17.83	9.25	27.08	60.00	-32.92	QP	P	
12	15.6660	5.97	9.25	15.22	50.00	-34.78	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	30dBm(for GFSK),20.97dBm(for EDR)
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	2.105	30.00	Pass
	Middle	2.847		
	Highest	3.001		
π/4-DQPSK	Lowest	3.701	20.97	Pass
	Middle	3.530		
	Highest	3.125		
8-DPSK	Lowest	1.999	20.97	Pass
	Middle	2.234		
	Highest	1.912		

Test plot as follows:

Test mode:	GFSK mode

Lowest channel



Middle channel



Highest channel



Test mode:	π/4-DQPSK mode

Lowest channel



Middle channel



Highest channel



Test mode:	8-DPSK mode

Lowest channel



Middle channel



Highest channel



7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.9167	Pass
	Middle	0.8622	
	Highest	0.8647	
π/4-DQPSK	Lowest	1.234	Pass
	Middle	1.374	
	Highest	1.306	
8-DPSK	Lowest	1.253	Pass
	Middle	1.282	
	Highest	1.265	

Test plot as follows:

Test mode:	GFSK mode

Lowest channel



Middle channel



Highest channel



Test mode:	π/4-DQPSK mode

Lowest channel



Middle channel



Highest channel



Test mode:	8-DPSK mode

Lowest channel



Middle channel



Highest channel



7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	GFSK: 20dB bandwidth π/4-DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Mode	Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
GFSK	Lowest	966	917	Pass
	Middle	1080	862	Pass
	Highest	951	865	Pass
π/4-DQPSK	Lowest	1002	823	Pass
	Middle	987	916	Pass
	Highest	1026	871	Pass
8-DPSK	Lowest	1020	835	Pass
	Middle	1011	855	Pass
	Highest	1176	843	Pass

Test plot as follows:

Modulation mode:	GFSK

Lowest channel

Middle channel

Highest channel

Test mode:	π/4-DQPSK

Lowest channel



Middle channel



Highest channel



Test mode:	8-DPSK

Lowest channel



Middle channel



Highest channel



7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
π/4-DQPSK	79	15	Pass
8-DPSK	79	15	Pass

Test plot as follows:

Test mode:	GFSK



Test mode:	π/4-DQPSK



Test mode:	8-DPSK



7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

GFSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2402MHz	DH1	124.57	400	Pass
2402MHz	DH3	262.31	400	Pass
2402MHz	DH5	275.63	400	Pass

Remarks:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test channel: 2402MHz as blow

DH1 time slot=0.394 (ms)*(1600/ (2*79))*31.6=124.57ms

DH3 time slot=1.66 (ms)*(1600/ (4*79))*31.6=262.31ms

DH5 time slot=2.908 (ms)*(1600/ (6*79))*31.6=275.63ms

π/4-DQPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	2DH1	120.68	400	Pass
2441MHz	2DH3	257.52	400	Pass
2441MHz	2DH5	272.31	400	Pass

Remarks:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test channel: 2441MHz as blow

DH1 time slot=0.382 (ms)*(1600/ (2*79))*31.6=120.68ms

DH3 time slot=1.63 (ms)*(1600/ (4*79))*31.6=257.52ms

DH5 time slot=2.873 (ms)*(1600/ (6*79))*31.6=272.31ms

8-DPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2480MHz	3DH1	121.15	400	Pass
2480MHz	3DH3	257.62	400	Pass
2480MHz	3DH5	272.36	400	Pass

Remarks:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test channel: 2480MHz as blow

DH1 time slot=0.383 (ms)*(1600/ (2*79))*31.6=121.15ms

DH3 time slot=1.63 (ms)*(1600/ (4*79))*31.6=257.62ms

DH5 time slot=2.873 (ms)*(1600/ (6*79))*31.6=272.36ms

Test plot as follows:

GFSK mode:

Test channel:	2402MHz

DH1



DH3



DH5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.402000000 GHz
Trig Delay-1.000 ms
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
09:56:57 AM Sep 17, 2020
Ref Offset 6.76 dB
10 dB/div
Ref 26.76 dBm
ΔMkr1 2.908 ms
-0.84 dB
1Δ2
Center 2.402000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 5.000 ms (10001 pts)
1 Δ2 1 t (Δ) 2.908 ms (Δ) -0.84 dB
2 F 1 t 1.007 ms -2.70 dBm

π/4-DQPSK mode:

Test channel:	2441MHz

DH1



DH3



DH5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
Trig Delay-1.000 ms
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
10:00:15 AM Sep 17, 2020
PNO: Fast
IFGain:Low
Ref Offset 6.83 dB
10 dB/div
Ref 26.83 dBm
ΔMkr1 2.873 ms
0.09 dB
1Δ2
TRIG LVL
Center 2.441000000 GHz
Span 0 Hz
Res BW 1.0 MHz
#VBW 3.0 MHz
Sweep 5.000 ms (10001 pts)
1 Δ2 1 t (Δ) 2.873 ms (Δ) 0.09 dB
2 F 1 t 1.021 ms -8.14 dBm

8-DPSK mode:

Test channel:	2480MHz

DH1



DH3



DH5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
Trig Delay-1.000 ms
Trig: Video
Atten: 30 dB
Avg Type: Log-Pwr
10:05:11 AM Sep 17, 2020
PNO: Fast
IFGain:Low
Ref Offset 6.8 dB
10 dB/div
Ref 26.80 dBm
ΔMkr1 2.873 ms
-0.92 dB
1Δ2
TRIG LVL
Center 2.480000000 GHz
Span 0 Hz
Res BW 1.0 MHz
#VBW 3.0 MHz
Sweep 5.000 ms (10001 pts)
1 Δ2 1 t (Δ) 2.873 ms (Δ) -0.92 dB
2 F 1 t 1.022 ms -6.12 dBm

7.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)/g/h requirement:

a(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

EUT Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- *Number of shift register stages: 9*
- *Length of pseudo-random sequence: 2^9 -1 = 511 bits*
- *Longest sequence of zeros: 8 (non-inverted signal)*



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

it permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted.

7.9 Band Edge

7.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

GFSK Mode:

Test channel:	Lowest channel

No-hopping mode



Hopping mode



Test channel:	Highest channel

No-hopping mode



Hopping mode



π/4-DQPSK Mode:

Test channel:	Lowest channel

No-hopping mode



Hopping mode



Test channel:	Highest channel

No-hopping mode



Hopping mode



8-DPSK Mode:

Test channel:	Lowest channel

No-hopping mode



Hopping mode



Test channel:	Highest channel

No-hopping mode



Hopping mode



7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10:2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Remark
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
Above 1GHz	54.00	Average Value
	74.00	Peak Value

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel:	Lowest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	53.51	39.55	7.77	25.66	47.39	74.00	-26.61	Horizontal
2400.00	51.60	38.33	7.3	24.55	45.12	74.00	-28.88	Horizontal
2390.00	53.85	39.55	7.77	25.66	47.73	74.00	-26.27	Vertical
2400.00	52.49	38.33	7.3	23.55	45.01	74.00	-28.99	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	43.37	39.55	7.77	25.66	37.25	54.00	-16.75	Horizontal
2400.00	43.98	38.33	7.3	24.55	37.50	54.00	-16.50	Horizontal
2390.00	43.70	39.55	7.77	25.66	37.58	54.00	-16.42	Vertical
2400.00	43.75	38.33	7.3	23.22	35.94	54.00	-18.06	Vertical

Test channel:	Highest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.53	38.75	7.38	25.45	45.61	74.00	-28.39	Horizontal
2485.50	54.74	38.65	7.15	24.78	48.02	74.00	-25.98	Horizontal
2483.50	52.32	38.75	7.38	25.45	46.40	74.00	-27.60	Vertical
2485.50	53.91	38.65	7.15	24.78	47.19	74.00	-26.81	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	43.77	38.75	7.38	25.45	37.85	54.00	-16.15	Horizontal
2485.50	43.98	38.65	7.15	24.78	37.26	54.00	-16.74	Horizontal
2483.50	43.99	38.75	7.38	25.45	38.07	54.00	-15.93	Vertical
2485.50	43.85	38.65	7.15	24.78	37.13	54.00	-16.87	Vertical

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*
4. *During the test, pre-scan the GFSK, π/4-DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.*

7.10 Spurious Emission

7.10.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

GFSK mode:

Test channel:	Lowest channel



30MHz~25GHz

Test channel:	Middle channel



30MHz~25GHz

Test channel:	Highest channel



30MHz~25GHz

π/4-DQPSK mode:

Test channel:	Lowest channel



30MHz~25GHz

Test channel:	Middle channel



30MHz~25GHz

Test channel:	Highest channel



30MHz~25GHz

8-DPSK mode:

Test channel:	Lowest channel



30MHz~25GHz

Test channel:	Middle channel



30MHz~25GHz

Test channel:	Highest channel



30MHz~25GHz

7.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	30m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



	For radiated emissions from 30MHz to1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details

Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Remarks:

1. *During the test, pre-scan the GFSK, π/4-DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ **Below 1GHz**

Pre-scan all test modes, found worst case at GFSK 2480MHz, and so only show the test result of GFSK 2480MHz

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	44.9006	28.54	-14.09	14.45	40.00	-25.55	QP	125	88		
2	59.4405	28.67	-14.22	14.45	40.00	-25.55	QP	117	91		
3	98.8326	39.15	-19.87	19.28	43.50	-24.22	QP	128	154		
4	113.7143	40.98	-19.10	21.88	43.50	-21.62	QP	215	212		
5	243.8043	39.50	-17.57	21.93	46.00	-24.07	QP	154	302		
6	466.4165	31.19	-15.30	15.89	46.00	-30.11	QP	122	38		

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	35.4371	41.74	-17.54	24.20	40.00	-15.80	QP	110	26		
2	43.3534	30.99	-17.01	13.98	40.00	-26.02	QP	102	165		
3	80.0806	41.45	-21.87	19.58	40.00	-20.42	QP	113	201		
4	102.3597	36.98	-21.27	15.71	43.50	-27.79	QP	117	185		
5	113.7143	40.80	-21.46	19.34	43.50	-24.16	QP	104	201		
6	134.3235	37.83	-21.40	16.43	43.50	-27.07	QP	100	157		

■ **Above 1GHz**

Test channel:	Lowest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	52.22	39.55	7.77	25.66	46.10	74.00	-27.90	Vertical
7206.00	53.16	38.33	7.30	24.55	46.68	74.00	-27.32	Vertical
15450.00	53.25	35.23	6.60	26.59	51.21	74.00	-22.79	Vertical
4804.00	51.03	39.55	7.77	25.66	44.91	74.00	-29.09	Horizontal
7206.00	52.44	38.33	7.30	23.55	44.96	74.00	-29.04	Horizontal
15450.00	53.13	35.45	6.60	27.88	52.16	74.00	-21.84	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	43.21	39.55	7.77	25.66	37.09	54.00	-16.91	Vertical
7206.00	42.16	38.33	7.30	24.55	35.68	54.00	-18.32	Vertical
15450.00	42.36	35.23	6.60	26.59	40.32	54.00	-13.68	Vertical
4804.00	43.10	39.55	7.77	25.66	36.98	54.00	-17.02	Horizontal
7206.00	42.33	38.33	7.30	23.55	34.85	54.00	-19.15	Horizontal
15450.00	43.06	35.45	6.60	27.88	42.09	54.00	-11.91	Horizontal

Test channel:	Middle channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	50.23	39.55	7.77	25.66	44.11	74.00	-29.89	Vertical
7323.00	51.36	38.33	7.30	24.55	44.88	74.00	-29.12	Vertical
15450.00	53.26	35.23	6.60	26.59	51.22	74.00	-22.78	Vertical
4882.00	53.11	39.55	7.77	25.66	46.99	74.00	-27.01	Horizontal
7323.00	52.65	38.33	7.30	23.55	45.17	74.00	-28.83	Horizontal
15450.00	51.36	35.45	6.60	27.88	50.39	74.00	-23.61	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	43.21	39.55	7.77	25.66	37.09	54.00	-16.91	Vertical
7323.00	42.36	38.33	7.30	24.55	35.88	54.00	-18.12	Vertical
15450.00	43.65	35.23	6.60	26.59	41.61	54.00	-12.39	Vertical
4882.00	43.16	39.55	7.77	25.66	37.04	54.00	-16.96	Horizontal
7323.00	42.05	38.33	7.30	23.55	34.57	54.00	-19.43	Horizontal
15450.00	41.33	35.45	6.60	27.88	40.36	54.00	-13.64	Horizontal

Test channel:	Highest channel

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	51.32	39.55	7.77	25.66	45.20	74.00	-28.80	Vertical
7440.00	51.36	38.33	7.30	24.55	44.88	74.00	-29.12	Vertical
15450.00	53.25	35.23	6.60	26.59	51.21	74.00	-22.79	Vertical
4960.00	53.11	39.55	7.77	25.66	46.99	74.00	-27.01	Horizontal
7440.00	52.42	38.33	7.30	23.55	44.94	74.00	-29.06	Horizontal
15450.00	51.36	35.45	6.60	27.88	50.39	74.00	-23.61	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	42.38	39.55	7.77	25.66	36.26	54.00	-17.74	Vertical
7440.00	43.27	38.33	7.30	24.55	36.79	54.00	-17.21	Vertical
15450.00	43.66	35.23	6.60	26.59	41.62	54.00	-12.38	Vertical
4960.00	44.23	39.55	7.77	25.66	38.11	54.00	-15.89	Horizontal
7440.00	43.29	38.33	7.30	23.55	35.81	54.00	-18.19	Horizontal
15450.00	42.34	35.45	6.60	27.88	41.37	54.00	-12.63	Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *The test data shows only the worst case GFSK mode*

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------