

TEST REPORT

Product Name : GPS Tracker for Large Dogs
Model Number : HY-913T
FCC ID : 2AXOF-HY913T

Prepared for : Shenzhen Macross Automation Technology Co., Ltd.
Address : Room 301-3, No.5, Jianghao (Sakata) Industrial Factory,
No.430Jihua Road, Sakata Community, Bantian Street,
LonggangDistrict, Shenzhen City, Guangdong Pr. China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2601200075W00402R
Date of sample receipt : January 20, 2026
Date(s) of Tests : January 20, 2026 to March 13, 2026
Date of issue : March 13, 2026

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
RF EXPOSURE EVALUATION	6
FRIIS TRANSMISSION FORMULA: $PD = (P_{OUT} * G) / (4 * \pi * R^2)$	6
3. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Shenzhen Macross Automation Technology Co., Ltd.
Address : Room 301-3, No.5, Jianghao (Sakata) Industrial Factory, No.430Jihua Road, Sakata Community, Bantian Street, LonggangDistrict, Shenzhen City, Guangdong Pr. China
Manufacturer : Shenzhen Macross Automation Technology Co., Ltd.
Address : Room 301-3, No.5, Jianghao (Sakata) Industrial Factory, No.430Jihua Road, Sakata Community, Bantian Street, LonggangDistrict, Shenzhen City, Guangdong Pr. China
Factory : Shenzhen Macross Automation Technology Co., Ltd.
Address : Room 301-3, No.5, Jianghao (Sakata) Industrial Factory, No.430Jihua Road, Sakata Community, Bantian Street, LonggangDistrict, Shenzhen City, Guangdong Pr. China
EUT : GPS Tracker for Large Dogs
Model Name : HY-913T
Trademark : N/A
Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : January 20, 2026 to March 13, 2026

Prepared by :

Yu Xiaolan

Yu Xiaolan /Editor

Reviewer :

Xia Lilu

Xia Lilu/Supervisor

Wang Li

Approve & Authorized Signer :

Wang Li/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2601200075W00402R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	GPS Tracker for Large Dogs
Model Number:	HY-913T
Sample:	1#
Operating Frequency Range(s) :	915.8MHz
Number of Channels:	1 channel
Max Field Strength	105.660 dBuV@3m
Antenna Type:	Black whip antenna
Power Supply	DC 3.7V from Battery DC 5V from USB
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

According to ANSI C63.10-2020

9.5 Equations to calculate EIRP

Calculate the EIRP from the radiated field strength in the far field using Equation (22):

$$EIRP = E + 20 \log(d) - 104.7 \quad (22)$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E is the field strength of the emission at the measurement distance, in dBμV/m

d is the measurement distance, in m

3. Measurement Result

915.8MHz SRD

FCC MPE

Gain(dBi)	-0.42	Gain(num)	0.0013 70882					
Channel Freq. (MHz)	Max Field Strength (dBuV/m)	peak output power (dBm)	Tune up Power (dBm)	Max tune up power(dBm)	Max tune up power(mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
915.8	105.66	10.08	10±1	11	12.589254	0.00227368	1	PASS

According to KDB 447498, no stand-alone required for antenna, and no simultaneous SAR measurement is required.

*** End of Report ***