

FCC PART 15.407



TEST REPORT

For

Beijing Wiseasy Technology CO., Ltd.

Room 2701-01, 24th Floor, Building 1, No. 16 Guangshun South Street, Chaoyang District, Beijing, China

FCC ID: 2AXOJ-P5PRO

Report Type: Original Report	Product Name: EMV Android POS
Report Number: RKSA260311002-00E	
Report Date: 2026-04-30	
Reviewed By: Bard Liu	
Approved By: Kyle Xu	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	9
EQUIPMENT MODIFICATIONS	15
SUPPORT EQUIPMENT LIST AND DETAILS	15
EXTERNAL I/O CABLE.....	15
BLOCK DIAGRAM OF TEST SETUP	15
SUMMARY OF TEST RESULTS.....	17
TEST EQUIPMENT LIST	18
FCC §1.1307(b) & §2.1093 - RF EXPOSURE.....	20
APPLICABLE STANDARD	20
FCC §15.203 – ANTENNA REQUIREMENT.....	21
APPLICABLE STANDARD	21
ANTENNA CONNECTOR CONSTRUCTION	21
FCC §15.407 (b) (9) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS.....	22
APPLICABLE STANDARD	22
TEST SYSTEM SETUP.....	22
EMI TEST RECEIVER SETUP.....	22
TEST PROCEDURE	23
TEST RESULTS SUMMARY	23
FCC §15.205 & §15.209 & §15.407(B) – UNDESIRABLE EMISSION & RESTRICTED BANDS	24
APPLICABLE STANDARD	24
TEST SYSTEM SETUP.....	24
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	27
TEST PROCEDURE	27
FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
FCC §15.407(a) – CONDUCTED TRANSMITTER OUTPUT POWER.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
FCC §15.407(a) - POWER SPECTRAL DENSITY	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
APPENDIX - TEST DATA.....	31
CONDUCTED EMISSIONS	31
TRANSMITTER UNWANTED EMISSIONS & RESTRICTED FREQUENCY BANDS.....	34
EMISSION BANDWIDTH.....	107

CONDUCTED TRANSMITTER OUTPUT POWER	125
POWER SPECTRAL DENSITY	127
EUT PHOTOGRAPHS	136
TEST SETUP PHOTOGRAPHS	137

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA260311002-00E	R1V1	2026-04-30	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Beijing Wiseasy Technology CO., Ltd.				
Tested Model:	P5-PRO				
Product Name:	EMV Android POS				
Power Supply:	DC 5V from adapter or DC 7.4V from battery				
Operating Frequency:	B1: 5150-5250 MHz, B2: 5250-5350 MHz B3: 5470-5725 MHz, B4: 5725-5850 MHz				
Maximum Output Power:	Mode:	5G Wi-Fi Band 1:	Band 2:	Band 3:	Band 4:
	802.11a:	17.93 dBm	17.04 dBm	14.14 dBm	15.28 dBm
	802.11ac20:	17.77 dBm	16.85 dBm	14.53 dBm	15.15 dBm
	802.11ac40:	14.26 dBm	13.73 dBm	12.66 dBm	15.38 dBm
	802.11ac80:	13.56 dBm	11.72 dBm	11.01 dBm	15.00 dBm
Channel Number:	B1:7; B2: 7; B3: 21; B4: 8				
Channel Separation	802.11a/n20/ac20: 20 MHz; 802.11n40/ac40: 40 MHz, 802.11ac80: 80 MHz				
Modulation Type:	OFDM				
Antenna Type:	FPC Antenna				
★Maximum Antenna Gain:	Band 1: 0.34 dBi; Band 2: -0.47 dBi; Band 3: -0.52 dBi; Band 4: -0.57 dBi;				
Sample/EUT Status	Good condition				

Adapter Information:

Model: TPA-418G050200UU01

Input: 100-240V, 50/60Hz, 0.3A

Output: 5.0V, 2.0A, 10.0W

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RKSA260311002-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2026-03-11.)

Objective

This type approval report is prepared for *Beijing Wiseasy Technology CO., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions' rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

The system support 802.11a/n20/n40/ac20/ac40/ ac80, the 802.11 n20/n40 were reduced since the identical parameters with 802.11ac20 and ac40.

For **5150~5250 MHz** band, test channel list is as below,

802.11a/ac20 mode Channel 36, 40, 48 were tested.

802.11ac40 mode Channel 38, 46 were tested.

802.11ac80 mode Channel 42 were tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For **5250~5350 MHz** band, test channel list is as below,

802.11a/ac20 mode Channel 52, 60, 64 were tested.

802.11ac40 mode Channel 54, 62 were tested.

802.11ac80 mode Channel 58 were tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
54	5270	62	5310
56	5280	64	5320
58	5290	/	/

For **5470~5725 MHz** band, test channel list is as below,

802.11a/ac20 mode Channel 100, 120, 140, 144 were tested, Cross channel 144.

802.11ac40 mode Channel 102, 118, 134, 142 were tested, Cross channel 142.

802.11ac80 mode Channel 106, 122, 138 were tested. Cross channel 138.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	118	5590	136	5680
102	5510	120	5600	138	5690
104	5520	122	5610	140	5700
106	5530	124	5620	142	5710
108	5540	126	5630	144	5720
110	5550	128	5640	/	/
112	5560	132	5660	/	/
116	5580	134	5670	/	/

For **5725~5850 MHz** band,

802.11a/ac20 mode Channel 149, 157, 165 were tested.

802.11ac40 mode Channel 151, 159 were tested.

802.11ac80 mode Channel 155 were tested.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	159	5795
151	5755	161	5805
153	5765	165	5825
155	5775	/	/
157	5785	/	/

EUT Exercise Software

QRCT3

The worst case was performed under:

U-NII	Mode	Data rate	★Power Level		
			Low Channel	Middle Channel	High Channel
5150~5250MHz	802.11a	6Mbps	19.5	19.5	19.5
	802.11ac20	MCS0	19.5	19.5	19.5
	802.11ac40	MCS0	16	/	16
	802.11ac80	MCS0	/	15	/

U-NII	Mode	Data rate	★Power Level		
			Low Channel	Middle Channel	High Channel
5250~5350MHz	802.11a	6Mbps	18.5	18.5	18.5
	802.11ac20	MCS0	18.5	18.5	18.5
	802.11ac40	MCS0	16	/	16
	802.11ac80	MCS0	/	14	/

U-NII	Mode	Data rate	★Power Level			
			Low Channel	Middle Channel	High Channel	Cross Channel
5470~5725MHz	802.11a	6Mbps	17	17	17	17
	802.11ac20	MCS0	18	18	18	18
	802.11ac40	MCS0	15	15	15	15
	802.11ac80	MCS0	13	/	13	13

U-NII	Mode	Data rate	★Power Level		
			Low Channel	Middle Channel	High Channel
5725~5850MHz	802.11a	6Mbps	19.5	19.5	19.5
	802.11ac20	MCS0	19.5	19.5	19.5
	802.11ac40	MCS0	19.5	/	19.5
	802.11ac80	MCS0	/	19.5	/

Note: The power level was declared by the applicant.


Duty Cycle:

Environmental Conditions & Test Information


Test Date:	2026-04-08 to 2026-04-09
Temperature:	21.2-22.7°C
Relative Humidity:	50-53 %
ATM Pressure:	100.5-102.1 kPa
Test Engineer:	Neil Zhou

5150MHz-5250MHz Band:


802.11a mode




802.11ac20 mode




802.11ac40 mode




802.11ac80 mode




5250MHz-5350MHz Band:**802.11a mode**


ProjectNo.:RKSA260311002 Tester:Neil Zhou
Date: 8 APR 2026 18:52:25

802.11ac20 mode

ProjectNo.: RKSA260311002 Tester:Neil Zhou
Date: 9 APR 2026 17:16:08

802.11ac40 mode


ProjectNo.:RKSA260311002 Tester:Neil Zhou
Date: 9 APR 2026 14:32:27

802.11ac80 mode


ProjectNo.: RKSA260311002 Tester:Neil Zhou
Date: 9 APR 2026 14:36:08

5470MHz-5725MHz Band:


802.11a mode




802.11ac20 mode




802.11ac40 mode




802.11ac80 mode




5725MHz-5850MHz Band:**802.11a mode**


ProjectNo.: RKSA260311002 Tester: Neil Zhou
Date: 9 APR 2026 15:18:43

802.11ac20 mode

ProjectNo.: RKSA260311002 Tester: Neil Zhou
Date: 9 APR 2026 15:25:17

802.11ac40 mode

ProjectNo.: RKSA260311002 Tester: Neil Zhou
Date: 9 APR 2026 15:30:55

802.11ac80 mode

ProjectNo.: RKSA260311002 Tester: Neil Zhou
Date: 9 APR 2026 15:32:24

Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

5150MHz-5250MHz:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)
802.11a	5200	4.058	4.235	95.82	0.19
802.11ac20	5200	3.796	3.986	95.23	0.21
802.11ac40	5230	1.874	2.036	92.04	0.36
802.11ac80	5210	0.91	1.085	83.87	0.76

5250MHz-5350MHz:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)
802.11a	5300	4.058	4.234	95.84	0.18
802.11ac20	5300	3.802	3.969	95.79	0.19
802.11ac40	5310	1.87	2.045	91.44	0.39
802.11ac80	5290	0.912	1.081	84.37	0.74

5470MHz-5725MHz:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)
802.11a	5700	4.056	4.235	95.77	0.19
802.11ac20	5700	3.798	3.999	94.97	0.22
802.11ac40	5670	1.872	2.051	91.27	0.4
802.11ac80	5610	0.912	1.183	77.09	1.13

5725MHz-5850MHz:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)
802.11a	5785	4.056	4.271	94.97	0.22
802.11ac20	5785	3.772	4.086	92.32	0.35
802.11ac40	5795	1.872	2.05	91.32	0.39
802.11ac80	5775	0.91	1.088	83.64	0.78

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To Port
USB Cable	1.0	EUT	Adapter
Power Cable	1.0	Power strip	LISN/AC Source

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1 GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207 & §15.407(b) (9)	AC Power Line Conducted Emissions	Compliant
§ 15.205 & §15.209 & §15.407(b)	Undesirable Emission & Restricted Bands	Compliant
§15.407(a) & §15.407(e)	Emission Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407(a)	Power Spectral Density	Compliant
§1.1307(b)(1)& §2.1093	RF EXPOSURE	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2026-03-13	2027-03-12
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2024-11-08	2027-11-07
Narda	6dB Attenuator	773-6	10690812-2-1	2024-11-08	2027-11-07
BACL	Active Loop Antenna	1313-1A	4041511	2025-08-10	2028-08-09
Sonoma Instrument	Pre-amplifier	310N	171205	2026-03-13	2027-03-12
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2026-03-13	2027-03-12
MICRO-COAX	Coaxial Cable	Cable-9	009	2026-03-13	2027-03-12
MICRO-COAX	Coaxial Cable	Cable-10	010	2026-03-13	2027-03-12
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2026-03-16	2027-03-15
EMCO	Horn Antenna	3115	9207-3900	2024-11-03	2027-11-02
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2026-03-16	2027-03-15
SELECTOR	Amplifier	EM18G40G	060726	2026-03-16	2027-03-15
MICRO-TRONICS	Band Reject Filter	BRM50716	G059	2026-04-08	2027-04-07
Eastsheep	Attenuator	2W-N-JK-18G	10dB-01	2026-03-12	2027-03-11
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2026-03-16	2027-03-15
MICRO-COAX	Coaxial Cable	Cable-11	011	2026-03-16	2027-03-15
MICRO-COAX	Coaxial Cable	Cable-12	012	2026-03-16	2027-03-15
MICRO-COAX	Coaxial Cable	Cable-13	013	2026-03-16	2027-03-15
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2026-03-16	2027-03-15
Eastsheep	Attenuator	2W-N-JK-18G	10dB-01	2026-03-12	2027-03-11
Anritsu	Power Sensor	MA24418A	12621	2026-03-13	2027-03-12
XHFDZ	RG316 Coaxial Cable	SMA-316	XHF-1175	Each time	N/A

Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	101746	2026-03-13	2027-03-12
Rohde & Schwarz	LISN	ENV216	101115	2026-03-12	2027-03-11
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2026-04-08	2027-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2026-03-13	2027-03-12

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1307, §2.1093.

Measurement Result

Result: Please refer to the SAR report: RKSA260311002-20B.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407, if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

Antenna permanently attached to the unit. fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	Frequency Range	Max. Antenna Gain	Input impedance
FPC	5150~5250 MHz	0.34 dBi	50Ω
	5250~5350 MHz	-0.47 dBi	50Ω
	5470~5725 MHz	-0.52 dBi	50Ω
	5725~5850 MHz	-0.57 dBi	50Ω


Result: Compliant.

FCC §15.407 (b) (9) §15.207 (a) – AC POWER LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), §15.407(b) (9)

Test System Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz - 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the EUT or adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\begin{aligned}\text{Factor (dB)} &= \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)} \\ \text{Level (dB}\mu\text{V)} &= \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)}\end{aligned}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Level (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.205 & §15.209 & §15.407(B) – UNDESIRABLE EMISSION & RESTRICTED BANDS

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:


(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000MHz shall be performed using a minimum resolution bandwidth of 1MHz.


According to 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP [dBm] + 95.2$, for $d = 3$ meters.

Test System Setup


9kHz-30 MHz:




30MHz-1GHz:



1 GHz-18GHz:



18-40GHz:



The radiated emission tests were performed in the 3 meters test site for below 18GHz and 1.5m for 18-40 GHz, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209 and FCC 15.407 limits. According to ANSI C63.10 - 2020,9.2.1: For field strength measurements made at other than the distance specified by the limit, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of

$$E_{SpecLimit} = E_{Meas} + 20 \log \left(\frac{D_{Meas}}{D_{SpecLimit}} \right)$$

distance)

Where

- $E_{SpecLimit}$ is the field strength of the emission at the distance specified by the limit, in dBuV/m
- E_{Meas} is the field strength of the emission at the measurement distance, in dBuV/m
- D_{Meas} is the measurement distance, in m
- $D_{SpecLimit}$ is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1.5/3) = -6.0$ dB, for 18 - 40GHz range, the limit of 1.5m distance was added by 6.0dB from limit of 3m to compared with the result measurement at 1.5m distance.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement	Detector
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	Peak/QP/Average	Peak/QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	Peak/QP/Average	Peak/QP/Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak	Peak
	/	/	120 kHz	QP	QP
Above 1GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	3 MHz	/	Average	Average

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Test Procedure

During the radiated emission test, the adapter was connected to AC floor outlet. Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Corrected factor (dB/m)}$$

$$\text{Corrected factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Note: The QuasiPeak (dB μ V/m), MaxPeak (dB μ V/m), Average (dB μ V/m) which shown in the data table are all Corrected Amplitude.

Test Data: See Appendix

FCC §15.407(a) & §15.407(e)–EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max-hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Data: See Appendix

FCC §15.407(a) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: Offset (10.5dB) = Attenuator(10dB) + Cable loss(0.5dB)

Test Data: See Appendix

FCC §15.407(a) - POWER SPECTRAL DENSITY

Applicable Standard

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.


Test Procedure

The measurements are base on C63.10:2020

Duty cycle $\geq 98\%$,Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$,Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$,Method SA-3 should be applied.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Data: See Appendix

APPENDIX - TEST DATA


CONDUCTED EMISSIONS

Environmental Conditions & Test Information

Test Date:	2026-04-14
Temperature:	18.9 °C
Relative Humidity:	71 %
ATM Pressure:	101.5 kPa
Test Result:	Pass
Test Engineer:	Aiden Feng

EUT operation mode: Transmitting in 802.11a mode 5240MHz (maximum output power)


AC 120V/60 Hz, Line



Site : CE
Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Line
: DET:Peak
Project No. : RKSA260311002
Model : P5-PRO
Phase : L
Voltage : 120V/60Hz
Mode : 5G WIFI
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 18.9℃
Humidity : 71%
Atmospheric pressure: 101.5kPa
Test Engineer : Aiden Feng
Check by : Bard Liu

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBUV	dB	dBUV	dBUV	dB	
1	0.262	25.80	20.41	46.21	61.36	-15.15	Peak
2	0.429	22.95	20.29	43.24	57.26	-14.02	Peak
3	0.570	22.65	20.19	42.84	56.00	-13.16	Peak
4	0.672	22.86	20.26	43.12	56.00	-12.88	Peak
5	0.829	21.10	20.24	41.34	56.00	-14.66	Peak
6	15.930	18.76	20.31	39.07	60.00	-20.93	Peak

AC 120V/60 Hz, Neutral



Site : CE
Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Neutral
: DET:Peak
Project No. : RKSA260311002
Model : P5-PRO
Phase : N
Voltage : 120V/60Hz
Mode : 5G WIFI
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 18.9℃
Humidity : 71%
Atmospheric pressure: 101.5kPa
Test Engineer : Aiden Feng
Check by : Bard Liu

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.267	26.63	20.38	47.01	61.20	-14.19	Peak
2	0.383	24.75	20.32	45.07	58.22	-13.15	Peak
3	0.562	24.51	20.20	44.71	56.00	-11.29	Peak
4	0.689	23.81	20.26	44.07	56.00	-11.93	Peak
5	16.251	26.69	20.33	47.02	60.00	-12.98	Peak
6	20.438	22.30	20.52	42.82	60.00	-17.18	Peak

TRANSMITTER UNWANTED EMISSIONS & RESTRICTED FREQUENCY BANDS**Environmental Conditions & Test Information**


Test Item:	SPURIOUS EMISSIONS			
	9kHz – 30MHz	30MHz - 1GHz	1 GHz - 18 GHz	18 GHz - 40 GHz
Test Date:	2026-04-28	206-03-14	2026-04-02 to 2026-04-27	2026-04-14
Temperature:	21.3 °C	16.7°C	18.4-18.7 °C	18.9°C
Relative Humidity:	52 %	43 %	49-50 %	71 %
ATM Pressure:	101.8 kPa	103.3 kPa	101.5-102.0 kPa	101.5 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Scarf Yang	Scarf Yang	Destine Hu	Hugh Wu

After pre-scan in the X, Y and Z axes of orientation, the worst case at Y axis is below:

9kHz-150kHz

Common Information

Project No:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	Transmitting in 802.11a mode low channel
Standard:	FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.407
Test Equipment:	ESCI, 1313-1A, 310N
Receiver Setting:	RBW: 200 Hz, VBW: 1 kHz, Sweep Time: Auto
Temperature:	21.3°C
Humidity:	52%
Barometric Pressure:	101.8 kPa
Test Engineer:	Scarf Yang
Check by:	Jason Lu
Test Date:	2026/4/28




Critical_Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
0.020403	44.97	121.40	76.43	Parallel	-0.1
0.028528	58.29	118.50	60.21	Parallel	0.0
0.056870	58.25	112.51	54.26	Parallel	-4.1
0.085598	51.83	108.95	57.12	Parallel	-7.3
0.113692	49.37	106.49	57.12	Parallel	-9.1
0.142421	44.75	104.53	59.78	Parallel	-10.3

150kHz-30MHz**Common Information**


Project No: RKSA260311002
EUT Model: P5-PRO
Test Mode: Transmitting in 802.11a mode low channel
Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.407
Test Equipment: ESCI, 1313-1A, 310N
Receiver Setting: RBW:9k Hz, VBW:30 kHz, Sweep Time: Auto
Temperature: 21.3°C
Humidity: 52%
Barometric Pressure: 101.8kPa
Test Engineer: Scarf Yang
Check by: Jason Lu
Test Date: 2026/4/28

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
0.168656	52.08	103.01	50.94	Parallel	-11.4
1.232062	42.36	65.63	23.27	Parallel	-27.9
1.508175	38.72	63.96	25.24	Parallel	-28.8
4.433475	34.11	69.54	35.43	Parallel	-31.3
6.433425	30.71	69.54	38.83	Parallel	-31.6
13.970550	29.40	69.54	40.14	Parallel	-32.2

30MHz-1GHz: Transmitting in 802.11a mode 5240MHz (maximum output power)**Common Information**


Project No:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	Transmitting in 802.11a mode high channel
Standard:	FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.407
Test Equipment:	ESCI, JB3, 310N
Receiver Setting:	RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature:	16.7°C
Humidity:	43%
Barometric Pressure:	103.3kPa
Test Engineer:	Scarf Yang
Check by:	Jason Lu
Test Date:	2026/3/14

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.363750	28.74	40.00	11.26	V	-5.0
60.676250	26.71	40.00	13.29	V	-17.1
137.548750	29.20	43.50	14.30	V	-11.2
195.748750	29.25	43.50	14.25	H	-12.3
551.496250	29.64	46.00	16.36	H	-4.7
921.308750	34.87	46.00	11.13	H	1.4

1GHz-18GHz (5150-5250MHz Band):**802.11a Mode:****Low Channel: 5180MHz****Common Information**


Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11a mode Low Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1℃
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	37.15	---	68.20	31.05	V	-11.7
2897.200000	---	27.50	54.00	26.50	V	-8.8
2897.200000	35.69	---	74.00	38.31	V	-8.8
6905.800000	56.48	---	68.20	11.72	V	1.2
7558.600000	49.56	---	74.00	24.44	V	3.3
7558.600000	---	42.45	54.00	11.55	V	3.3
12060.200000	51.99	---	74.00	22.01	H	9.0
12060.200000	---	45.09	54.00	8.91	H	9.0
14481.000000	---	44.18	54.00	9.82	H	11.1
14481.000000	53.80	---	74.00	20.20	H	11.1
17996.600000	55.04	---	74.00	18.96	H	13.8
17996.600000	---	46.52	54.00	7.48	H	13.8

Middle Channel: 5200MHz**Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11a mode Middle Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	36.35	---	68.20	31.85	H	-11.7
2890.400000	---	27.44	54.00	26.56	H	-8.8
2890.400000	35.63	---	74.00	38.37	H	-8.8
6933.000000	54.06	---	68.20	14.14	H	1.3
7490.600000	---	40.00	54.00	14.00	H	3.3
7490.600000	50.51	---	74.00	23.49	H	3.3
12060.200000	51.75	---	74.00	22.25	H	9.0
12060.200000	---	45.28	54.00	8.72	H	9.0
14477.600000	---	44.49	54.00	9.51	H	11.1
14477.600000	52.30	---	74.00	21.70	H	11.1
17966.000000	53.53	---	74.00	20.47	V	13.6
17966.000000	---	46.56	54.00	7.44	V	13.6

High Channel: 5240MHz**Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11a mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	36.86	---	68.20	31.34	H	-11.7
2897.200000	---	26.34	54.00	27.66	H	-8.8
2897.200000	35.75	---	74.00	38.25	H	-8.8
6987.400000	52.66	---	68.20	15.54	H	1.6
7694.600000	50.15	---	74.00	23.85	H	3.4
7694.600000	---	40.15	54.00	13.85	H	3.4
12063.600000	52.19	---	74.00	21.81	H	9.0
12063.600000	---	44.67	54.00	9.33	H	9.0
14484.400000	---	43.58	54.00	10.42	V	11.1
14484.400000	53.96	---	74.00	20.04	V	11.1
17969.400000	53.53	---	74.00	20.47	V	13.6
17969.400000	---	45.78	54.00	8.22	V	13.6

802.11ac20 Mode:**Low Channel: 5180MHz****Common Information**


Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11ac20 mode Low Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1℃
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µV/m)	Average (dB µV/m)	Limit (dB µV/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	36.40	---	68.20	31.80	V	-11.7
2897.200000	---	26.45	54.00	27.55	V	-8.8
2897.200000	35.94	---	74.00	38.06	V	-8.8
6905.800000	56.32	---	68.20	11.88	V	1.2
7477.000000	---	40.32	54.00	13.68	H	3.2
7477.000000	49.94	---	74.00	24.06	H	3.2
12060.200000	54.65	---	74.00	19.35	H	9.0
12060.200000	---	44.06	54.00	9.94	H	9.0
14494.600000	---	45.06	54.00	8.94	H	11.1
14494.600000	52.56	---	74.00	21.44	H	11.1
17996.600000	---	46.75	54.00	7.25	H	13.8
17996.600000	53.35	---	74.00	20.65	H	13.8

Middle Channel: 5200MHz**Common Information**

Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac20 mode Middle Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1°C
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	36.11	---	68.20	32.09	V	-11.7
2887.000000	34.78	---	74.00	39.22	V	-8.8
2887.000000	---	25.57	54.00	28.43	V	-8.8
6933.000000	55.23	---	68.20	12.97	V	1.3
7562.000000	---	40.63	54.00	13.37	V	3.3
7562.000000	49.86	---	74.00	24.14	V	3.3
11961.600000	---	43.06	54.00	10.94	H	9.0
11961.600000	54.68	---	74.00	19.32	H	9.0
14494.600000	52.53	---	74.00	21.47	H	11.1
14494.600000	---	44.87	54.00	9.13	H	11.1
17996.600000	54.16	---	74.00	19.84	V	13.8
17996.600000	---	46.75	54.00	7.25	V	13.8

High Channel: 5240MHz

Common Information

Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11ac20 mode High Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1℃
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27




Critical Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2887.000000	---	25.77	54.00	28.23	H	-8.8
2887.000000	35.45	---	74.00	38.55	H	-8.8
4729.800000	---	31.73	54.00	22.27	V	-3.7
4729.800000	43.13	---	74.00	30.87	V	-3.7
6987.400000	52.70	---	68.20	15.50	V	1.6
10302.400000	52.18	---	68.20	16.02	V	6.5
11999.000000	---	43.57	54.00	10.43	H	9.0
11999.000000	53.83	---	74.00	20.17	H	9.0
14491.200000	---	45.07	54.00	8.93	H	11.1
14491.200000	52.45	---	74.00	21.55	H	11.1
17993.200000	---	46.59	54.00	7.41	H	13.8
17993.200000	54.73	---	74.00	19.27	H	13.8

802.11ac40 Mode:**Low Channel: 5190MHz****Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac40 mode Low Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	35.83	---	68.20	32.37	V	-11.7
2893.800000	---	26.45	54.00	27.55	V	-8.8
2893.800000	34.81	---	74.00	39.19	V	-8.8
6919.400000	56.51	---	68.20	11.69	V	1.2
7728.600000	50.33	---	74.00	23.67	V	3.4
7728.600000	---	39.63	54.00	14.37	V	3.4
12080.600000	54.51	---	74.00	19.49	H	9.0
12080.600000	---	44.04	54.00	9.96	H	9.0
14494.600000	---	45.44	54.00	8.56	H	11.1
14494.600000	52.45	---	74.00	21.55	H	11.1
17898.000000	---	46.22	54.00	7.78	V	13.2
17898.000000	52.84	---	74.00	21.16	V	13.2

High Channel: 5230MHz**Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac40 mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1197.200000	40.51	---	74.00	33.49	H	-15.3
1197.200000	---	23.69	54.00	30.31	H	-15.3
2897.200000	---	25.88	54.00	28.12	H	-8.8
2897.200000	35.63	---	74.00	38.37	H	-8.8
5998.000000	47.93	---	68.20	20.27	V	-0.7
6973.800000	54.94	---	68.20	13.26	V	1.5
7606.200000	---	40.53	54.00	13.47	H	3.3
7606.200000	49.99	---	74.00	24.01	H	3.3
12084.000000	---	45.09	54.00	8.91	H	9.0
12084.000000	51.82	---	74.00	22.18	H	9.0
17979.600000	54.08	---	74.00	19.92	V	13.7
17979.600000	---	45.99	54.00	8.01	V	13.7

802.11ac80 Mode:**Channel: 5210MHz****Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac80
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	36.19	---	68.20	32.01	V	-11.7
2887.000000	34.68	---	74.00	39.32	V	-8.8
2887.000000	---	26.09	54.00	27.91	V	-8.8
6946.600000	55.25	---	68.20	12.95	V	1.4
7585.800000	---	40.19	54.00	13.81	V	3.3
7585.800000	49.96	---	74.00	24.04	V	3.3
12084.000000	54.14	---	74.00	19.86	H	9.0
12084.000000	---	43.84	54.00	10.16	H	9.0
14487.800000	52.59	---	74.00	21.41	V	11.1
14487.800000	---	44.90	54.00	9.10	V	11.1
17972.800000	54.90	---	74.00	19.10	H	13.7
17972.800000	---	46.26	54.00	7.74	H	13.7

1GHz-18GHz(5250-5350MHz Band):**802.11a Mode:****Low Channel: 5260MHz****Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11a mode Low Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1°C
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental Test with Band Reject Filter**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	36.58	---	68.20	31.62	H	-11.7
2893.800000	34.98	---	74.00	39.02	H	-8.8
2893.800000	---	25.98	54.00	28.02	H	-8.8
4791.000000	41.44	---	74.00	32.56	V	-3.5
4791.000000	---	33.72	54.00	20.28	V	-3.5
7011.200000	51.57	---	68.20	16.63	V	1.7
12063.600000	55.03	---	74.00	18.97	V	9.0
12063.600000	---	44.68	54.00	9.32	V	9.0
14487.800000	54.78	---	74.00	19.22	H	11.1
14487.800000	---	44.92	54.00	9.08	H	11.1
17976.200000	---	45.90	54.00	8.10	H	13.7
17976.200000	53.65	---	74.00	20.35	H	13.7

Middle Channel: 5300MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11a mode Middle Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental Test with Band Reject Filter**Critical Freqs**


Frequency (MHz)	MaxPeak (dB µV/m)	Average (dB µV/m)	Limit (dB µV/m)	Margin (dB)	Pol	Corr. (dB/m)
2893.800000	34.24	---	74.00	39.76	H	-8.8
2893.800000	---	27.46	54.00	26.54	H	-8.8
4648.200000	---	33.56	54.00	20.44	V	-3.9
4648.200000	42.31	---	74.00	31.69	V	-3.9
7065.600000	52.14	---	68.20	16.06	V	1.8
9921.600000	52.74	---	68.20	15.46	V	6.1
12060.200000	52.93	---	74.00	21.07	H	9.0
12060.200000	---	45.52	54.00	8.48	H	9.0
14487.800000	52.59	---	74.00	21.41	V	11.1
14487.800000	---	45.32	54.00	8.68	V	11.1
17915.000000	52.80	---	74.00	21.20	V	13.3
17915.000000	---	46.14	54.00	7.86	V	13.3

High Channel: 5320MHz**Common Information**

Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11a mode High Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

Fundamental Test with Band Reject Filter


Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1996.200000	36.07	---	68.20	32.13	V	-11.7
2897.200000	35.64	---	74.00	38.36	V	-8.8
2897.200000	---	25.87	54.00	28.13	V	-8.8
4750.200000	43.12	---	74.00	30.88	V	-3.6
4750.200000	---	32.16	54.00	21.84	V	-3.6
7092.800000	51.40	---	68.20	16.80	V	1.9
8160.400000	---	40.02	54.00	13.98	V	3.9
8160.400000	49.75	---	74.00	24.25	V	3.9
12060.200000	52.71	---	74.00	21.29	H	9.0
12060.200000	---	45.11	54.00	8.89	H	9.0
17969.400000	54.92	---	74.00	19.08	V	13.6
17969.400000	---	46.17	54.00	7.83	V	13.6

802.11ac20 Mode:**Low Channel: 5260MHz****Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac20 mode Low Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental Test with Band Reject Filter**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2893.800000	---	26.88	54.00	27.12	V	-8.8
2893.800000	35.12	---	74.00	38.88	V	-8.8
4655.000000	---	34.05	54.00	19.95	V	-3.9
4655.000000	43.31	---	74.00	30.69	V	-3.9
7011.200000	51.22	---	68.20	16.98	V	1.7
8745.200000	51.04	---	68.20	17.16	V	4.8
12063.600000	---	44.96	54.00	9.04	H	9.0
12063.600000	52.57	---	74.00	21.43	H	9.0
14491.200000	53.61	---	74.00	20.39	H	11.1
14491.200000	---	44.89	54.00	9.11	H	11.1
17996.600000	---	46.15	54.00	7.85	V	13.8
17996.600000	53.97	---	74.00	20.03	V	13.8

Middle Channel: 5300MHz**Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac20 mode Middle Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

Fundamental Test with Band Reject Filter Full Spectrum**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1996.200000	38.71	---	68.20	29.49	V	-11.7
2887.000000	35.54	---	74.00	38.46	V	-8.8
2887.000000	---	26.66	54.00	27.34	V	-8.8
4641.400000	42.60	---	74.00	31.40	V	-3.9
4641.400000	---	32.76	54.00	21.24	V	-3.9
7038.400000	51.07	---	68.20	17.13	V	1.7
12026.200000	52.14	---	74.00	21.86	H	9.0
12026.200000	---	44.96	54.00	9.04	H	9.0
14494.600000	---	44.19	54.00	9.81	V	11.1
14494.600000	53.65	---	74.00	20.35	V	11.1
17996.600000	54.16	---	74.00	19.84	H	13.8
17996.600000	---	46.30	54.00	7.70	H	13.8

High Channel: 5320MHz**Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac20 mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1°C
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental Test with Band Reject Filter**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1996.200000	36.96	---	68.20	31.24	V	-11.7
2897.200000	34.87	---	74.00	39.13	V	-8.8
2897.200000	---	26.06	54.00	27.94	V	-8.8
4733.200000	42.60	---	74.00	31.40	V	-3.6
4733.200000	---	31.99	54.00	22.01	V	-3.6
7092.800000	51.40	---	68.20	16.80	V	1.9
12056.800000	52.05	---	74.00	21.95	H	9.0
12056.800000	---	45.22	54.00	8.78	H	9.0
14491.200000	---	44.39	54.00	9.61	H	11.1
14491.200000	53.29	---	74.00	20.71	H	11.1
17979.600000	53.62	---	74.00	20.38	H	13.7
17979.600000	---	46.07	54.00	7.93	H	13.7

802.11ac40 Mode:**Low Channel: 5270MHz****Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac40 mode Low Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental Test with Band Reject Filter**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2897.200000	34.62	---	74.00	39.38	H	-8.8
2897.200000	---	25.22	54.00	28.78	H	-8.8
4736.600000	---	32.61	54.00	21.39	H	-3.6
4736.600000	42.41	---	74.00	31.59	H	-3.6
7024.800000	52.60	---	68.20	15.60	V	1.7
7562.000000	---	40.46	54.00	13.54	V	3.3
7562.000000	49.91	---	74.00	24.09	V	3.3
12080.600000	---	45.31	54.00	8.69	H	9.0
12080.600000	51.54	---	74.00	22.46	H	9.0
14545.600000	54.41	---	68.20	13.79	V	10.9
17996.600000	54.32	---	74.00	19.68	V	13.8
17996.600000	---	46.28	54.00	7.72	V	13.8

High Channel: 5310MHz**Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac40 mode High Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

Fundamental Test with Band Reject Filter Full Spectrum**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2880.200000	---	25.09	54.00	28.91	H	-8.8
2880.200000	34.64	---	74.00	39.36	H	-8.8
4651.600000	---	32.79	54.00	21.21	H	-3.9
4651.600000	42.66	---	74.00	31.34	H	-3.9
7079.200000	51.74	---	68.20	16.46	V	1.9
8701.000000	51.48	---	68.20	16.72	V	4.8
12050.000000	52.79	---	74.00	21.21	V	9.0
12050.000000	---	44.75	54.00	9.25	V	9.0
14474.200000	52.50	---	74.00	21.50	V	11.1
14474.200000	---	44.64	54.00	9.36	V	11.1
17989.800000	54.81	---	74.00	19.19	V	13.8
17989.800000	---	45.96	54.00	8.04	V	13.8

802.11ac80 Mode:**Channel: 5290MHz****Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac80
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental Test with Band Reject Filter**Critical Freqs**


Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2893.800000	---	26.14	54.00	27.86	H	-8.8
2893.800000	35.14	---	74.00	38.86	H	-8.8
4842.000000	---	32.58	54.00	21.42	H	-3.3
4842.000000	42.97	---	74.00	31.03	H	-3.3
7052.000000	52.62	---	68.20	15.58	H	1.8
7531.400000	48.15	---	74.00	25.85	H	3.3
7531.400000	---	41.44	54.00	12.56	H	3.3
12056.800000	---	45.47	54.00	8.53	H	9.0
12056.800000	52.67	---	74.00	21.33	V	9.0
14056.000000	54.45	---	68.20	13.75	V	10.7
17996.600000	---	46.33	54.00	7.67	V	13.8
17996.600000	54.50	---	74.00	19.50	V	13.8

1GHz-18GHz(5470-5725MHz Band):**802.11a Mode:****Low Channel: 5500MHz****Common Information**

Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11a mode Low Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1℃
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27

Fundamental test with Band reject filter

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2897.200000	---	25.59	54.00	28.41	V	-8.8
2897.200000	34.36	---	74.00	39.64	V	-8.8
4770.600000	---	32.17	54.00	21.83	V	-3.5
4770.600000	42.30	---	74.00	31.70	V	-3.5
7334.200000	54.66	---	74.00	19.34	H	2.7
7334.200000	---	43.39	54.00	10.61	H	2.7
12114.600000	52.29	---	74.00	21.71	H	9.0
12114.600000	---	44.80	54.00	9.20	H	9.0
14487.800000	52.42	---	74.00	21.58	V	11.1
14487.800000	---	43.96	54.00	10.04	V	11.1
17966.000000	54.11	---	74.00	19.89	V	13.6
17966.000000	---	46.50	54.00	7.50	V	13.6

Middle Channel: 5600MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11a mode Middle Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental test with Band reject filter Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2897.200000	---	26.06	54.00	27.94	V	-8.8
2897.200000	34.09	---	74.00	39.91	V	-8.8
4804.600000	---	32.15	54.00	21.85	V	-3.4
4804.600000	42.02	---	74.00	31.98	V	-3.4
7466.800000	54.03	---	74.00	19.97	H	3.2
7466.800000	---	44.66	54.00	9.34	H	3.2
12104.400000	52.66	---	74.00	21.34	H	9.0
12104.400000	---	45.31	54.00	8.69	H	9.0
14487.800000	---	44.01	54.00	9.99	V	11.1
14487.800000	54.07	---	74.00	19.93	V	11.1
17976.200000	55.29	---	74.00	18.71	V	13.7
17976.200000	---	47.10	54.00	6.90	V	13.7

High Channel: 5700MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11a mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1°C
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental test with Band reject filter

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB µV/m)	Average (dB µV/m)	Limit (dB µV/m)	Margin (dB)	Pol	Corr. (dB/m)
2887.000000	---	25.56	54.00	28.44	V	-8.8
2887.000000	34.49	---	74.00	39.51	V	-8.8
4757.000000	---	32.56	54.00	21.44	V	-3.6
4757.000000	41.63	---	74.00	32.37	V	-3.6
7422.600000	---	39.95	54.00	14.05	V	3.0
7422.600000	50.78	---	74.00	23.22	V	3.0
12141.800000	51.00	---	74.00	23.00	V	9.0
12141.800000	---	44.37	54.00	9.63	V	9.0
14491.200000	52.03	---	74.00	21.97	H	11.1
14491.200000	---	44.31	54.00	9.69	H	11.1
17966.000000	53.61	---	74.00	20.39	H	13.6
17966.000000	---	46.51	54.00	7.49	H	13.6

802.11ac20 Mode:**Low Channel: 5500MHz****Common Information**

Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac20 mode Low Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

Fundamental test with Band reject filter

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	39.57	---	68.20	28.63	H	-11.7
2897.200000	---	26.50	54.00	27.50	H	-8.8
2897.200000	34.47	---	74.00	39.53	H	-8.8
4811.400000	---	31.91	54.00	22.09	H	-3.4
4811.400000	42.60	---	74.00	31.40	H	-3.4
7334.200000	---	42.58	54.00	11.42	V	2.7
7334.200000	53.60	---	74.00	20.40	V	2.7
12121.400000	---	44.78	54.00	9.22	H	9.0
12121.400000	51.79	---	74.00	22.21	H	9.0
14600.000000	54.05	---	68.20	14.15	H	10.8
17983.000000	54.36	---	74.00	19.64	H	13.7
17983.000000	---	46.20	54.00	7.80	H	13.7

Middle Channel: 5600MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac20 mode Middle Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27


Fundamental test with Band reject filter

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2893.800000	---	25.51	54.00	28.49	H	-8.8
2893.800000	34.21	---	74.00	39.79	H	-8.8
4294.600000	---	31.77	54.00	22.23	H	-4.6
4294.600000	42.28	---	74.00	31.72	H	-4.6
7466.800000	51.75	---	74.00	22.25	H	3.2
7466.800000	---	43.25	54.00	10.75	H	3.2
12118.000000	51.02	---	74.00	22.98	V	9.0
12118.000000	---	44.62	54.00	9.38	V	9.0
14484.400000	---	44.42	54.00	9.58	V	11.1
14484.400000	52.61	---	74.00	21.39	V	11.1
17966.000000	55.04	---	74.00	18.96	V	13.6
17966.000000	---	46.71	54.00	7.29	V	13.6

High Channel: 5700MHz**Common Information**

Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11ac20 mode High Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1°C
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27


Fundamental test with Band reject filter Full Spectrum**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2870.000000	---	25.46	54.00	28.54	V	-8.9
2870.000000	34.52	---	74.00	39.48	V	-8.9
4767.200000	---	32.97	54.00	21.03	V	-3.5
4767.200000	42.47	---	74.00	31.53	V	-3.5
7500.800000	50.25	---	74.00	23.75	V	3.3
7500.800000	---	40.76	54.00	13.24	V	3.3
12145.200000	52.34	---	74.00	21.66	H	9.0
12145.200000	---	44.91	54.00	9.09	H	9.0
14484.400000	51.73	---	74.00	22.27	H	11.1
14484.400000	---	44.30	54.00	9.70	H	11.1
17983.000000	53.15	---	74.00	20.85	H	13.7
17983.000000	---	47.06	54.00	6.94	H	13.7

802.11ac40 Mode:**Low Channel: 5510MHz****Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac40 mode Low Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental test with Band reject filter


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	37.28	---	68.20	30.92	H	-11.7
4243.600000	42.11	---	74.00	31.89	H	-4.7
4243.600000	---	31.11	54.00	22.89	H	-4.7
7344.400000	---	43.71	54.00	10.29	H	2.8
7344.400000	53.88	---	74.00	20.12	H	2.8
12070.400000	---	45.00	54.00	9.00	V	9.0
12070.400000	53.64	---	74.00	20.36	V	9.0
14130.800000	54.72	---	68.20	13.48	V	10.8
14487.800000	53.37	---	74.00	20.63	V	11.1
14487.800000	---	43.87	54.00	10.13	V	11.1
17972.800000	---	46.76	54.00	7.24	V	13.7
17972.800000	54.71	---	74.00	19.29	V	13.7

Middle Channel: 5590MHz**Common Information**

Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac40 mode Middle Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

Fundamental test with Band reject filter

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	39.46	---	68.20	28.74	V	-11.7
2893.800000	---	26.10	54.00	27.90	V	-8.8
2893.800000	35.00	---	74.00	39.00	V	-8.8
4566.600000	42.04	---	74.00	31.96	V	-4.2
4566.600000	---	32.07	54.00	21.93	V	-4.2
7453.200000	52.37	---	74.00	21.63	H	3.1
7453.200000	---	43.51	54.00	10.49	H	3.1
12114.600000	---	45.10	54.00	8.90	H	9.0
12114.600000	52.55	---	74.00	21.45	H	9.0
14147.800000	55.07	---	68.20	13.13	H	10.8
17993.200000	---	46.92	54.00	7.08	H	13.8
17993.200000	53.79	---	74.00	20.21	H	13.8

High Channel: 5670MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac40 mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Full Spectrum

Fundamental test with Band reject filter


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2856.400000	---	25.26	54.00	28.74	H	-8.9
2856.400000	34.90	---	74.00	39.10	H	-8.9
4740.000000	---	32.48	54.00	21.52	H	-3.6
4740.000000	42.36	---	74.00	31.64	H	-3.6
7443.000000	---	40.29	54.00	13.71	H	3.1
7443.000000	50.47	---	74.00	23.53	H	3.1
12080.600000	---	44.78	54.00	9.22	V	9.0
12080.600000	52.01	---	74.00	21.99	V	9.0
14487.800000	52.93	---	74.00	21.07	V	11.1
14487.800000	---	44.14	54.00	9.86	V	11.1
17976.200000	---	46.79	54.00	7.21	V	13.7
17976.200000	54.40	---	74.00	19.60	V	13.7

802.11ac80 Mode:**Low Channel: 5530MHz****Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac80 mode Low Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental test with Band reject filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2887.000000	---	25.28	54.00	28.72	V	-8.8
2887.000000	34.84	---	74.00	39.16	V	-8.8
5052.800000	---	32.88	54.00	21.12	V	-2.7
5052.800000	43.06	---	74.00	30.94	V	-2.7
7371.600000	55.09	---	74.00	18.91	H	2.9
7371.600000	---	45.42	54.00	8.58	H	2.9
12077.200000	---	43.84	54.00	10.16	H	9.0
12077.200000	53.21	---	74.00	20.79	H	9.0
14487.800000	---	43.98	54.00	10.02	H	11.1
14487.800000	52.39	---	74.00	21.61	H	11.1
17993.200000	---	46.57	54.00	7.43	H	13.8
17993.200000	53.76	---	74.00	20.24	H	13.8

Middle Channel: 5610MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac80 mode Middle Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental test with Band reject filter Full Spectrum

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2893.800000	---	26.33	54.00	27.67	V	-8.8
2893.800000	34.97	---	74.00	39.03	V	-8.8
4787.600000	---	32.74	54.00	21.26	V	-3.5
4787.600000	41.78	---	74.00	32.22	V	-3.5
7480.400000	53.99	---	74.00	20.01	H	3.2
7480.400000	---	43.88	54.00	10.12	H	3.2
12152.000000	51.78	---	74.00	22.22	V	8.9
12152.000000	---	45.05	54.00	8.95	V	8.9
14487.800000	52.87	---	74.00	21.13	H	11.1
14487.800000	---	43.80	54.00	10.20	H	11.1
17989.800000	54.19	---	74.00	19.81	H	13.8
17989.800000	---	46.11	54.00	7.89	H	13.8

High Channel: 5690MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac80 mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1°C
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

Fundamental test with Band reject filter


Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2122.000000	33.82	---	68.20	34.38	H	-11.3
4784.200000	---	32.85	54.00	21.15	H	-3.5
4784.200000	42.54	---	74.00	31.46	H	-3.5
7585.800000	51.68	---	74.00	22.32	V	3.3
7585.800000	---	42.55	54.00	11.45	V	3.3
12087.400000	---	45.46	54.00	8.54	H	9.0
12087.400000	52.35	---	74.00	21.65	H	9.0
12162.200000	---	44.56	54.00	9.44	H	8.9
12162.200000	54.50	---	74.00	19.50	H	8.9
17694.000000	55.33	---	68.20	12.87	H	12.0
17989.800000	---	47.17	54.00	6.83	V	13.8
17989.800000	54.74	---	74.00	19.26	V	13.8

1GHz-18GHz(5725-5850MHz Band):**802.11a Mode:****Low Channel: 5745MHz****Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11a mode Low Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40.3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2880.200000	---	24.77	54.00	29.23	H	-8.8
2880.200000	34.54	---	74.00	39.46	H	-8.8
4726.400000	---	32.51	54.00	21.49	H	-3.7
4726.400000	42.01	---	74.00	31.99	H	-3.7
7660.600000	---	40.86	54.00	13.14	V	3.4
7660.600000	50.84	---	74.00	23.16	V	3.4
12053.400000	---	43.24	54.00	10.76	V	9.0
12053.400000	53.63	---	74.00	20.37	V	9.0
14491.200000	54.02	---	74.00	19.98	H	11.1
14491.200000	---	45.23	54.00	8.77	H	11.1
17989.800000	55.61	---	74.00	18.39	H	13.8
17989.800000	---	46.75	54.00	7.25	H	13.8

Middle Channel: 5785MHz**Common Information**


Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11a mode Middle Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2887.000000	---	25.02	54.00	28.98	V	-8.8
2887.000000	34.34	---	74.00	39.66	V	-8.8
4661.800000	---	33.08	54.00	20.92	V	-3.9
4661.800000	42.97	---	74.00	31.03	V	-3.9
7432.800000	---	40.52	54.00	13.48	V	3.1
7432.800000	50.68	---	74.00	23.32	V	3.1
11985.400000	---	44.40	54.00	9.60	V	9.0
11985.400000	53.96	---	74.00	20.04	V	9.0
14494.600000	52.92	---	74.00	21.08	H	11.1
14494.600000	---	45.06	54.00	8.94	H	11.1
17996.600000	54.83	---	74.00	19.17	H	13.8
17996.600000	---	46.63	54.00	7.37	H	13.8

High Channel: 5825MHz**Common Information**


Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11a mode High Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1°C
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2887.000000	35.07	---	74.00	38.93	H	-8.8
2887.000000	---	26.00	54.00	28.00	H	-8.8
4519.000000	42.69	---	74.00	31.31	H	-4.3
4519.000000	---	32.69	54.00	21.31	H	-4.3
7429.400000	50.48	---	74.00	23.52	V	3.1
7429.400000	---	40.64	54.00	13.36	V	3.1
12080.600000	54.46	---	74.00	19.54	V	9.0
12080.600000	---	45.46	54.00	8.54	V	9.0
14481.000000	54.08	---	74.00	19.92	V	11.1
14481.000000	---	45.62	54.00	8.38	V	11.1
17932.000000	54.98	---	74.00	19.02	V	13.4
17932.000000	---	47.14	54.00	6.86	V	13.4

802.11ac 20 Mode:**Low Channel: 5745MHz****Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac20 mode Low Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1℃
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2880.200000	---	24.77	54.00	29.23	H	-8.8
2880.200000	34.60	---	74.00	39.40	H	-8.8
4661.800000	---	32.60	54.00	21.40	V	-3.9
4661.800000	42.37	---	74.00	31.63	V	-3.9
7640.200000	---	39.99	54.00	14.01	V	3.3
7640.200000	50.61	---	74.00	23.39	V	3.3
12056.800000	---	44.01	54.00	9.99	V	9.0
12056.800000	53.75	---	74.00	20.25	V	9.0
14491.200000	52.28	---	74.00	21.72	H	11.1
14491.200000	---	44.77	54.00	9.23	H	11.1
17993.200000	55.11	---	74.00	18.89	H	13.8
17993.200000	---	46.86	54.00	7.14	H	13.8

Middle Channel: 5785MHz**Common Information**


Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac20 mode Middle Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1°C
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2897.200000	---	25.80	54.00	28.20	H	-8.8
2897.200000	35.33	---	74.00	38.67	H	-8.8
4519.000000	---	32.58	54.00	21.42	H	-4.3
4519.000000	41.67	---	74.00	32.33	H	-4.3
7711.600000	---	41.71	54.00	12.29	H	3.4
7711.600000	51.05	---	74.00	22.95	H	3.4
12067.000000	---	44.02	54.00	9.98	V	9.0
12067.000000	53.72	---	74.00	20.28	V	9.0
14491.200000	52.67	---	74.00	21.33	H	11.1
14491.200000	---	45.17	54.00	8.83	H	11.1
17993.200000	54.45	---	74.00	19.55	V	13.8
17993.200000	---	46.62	54.00	7.38	V	13.8

High Channel: 5825MHz**Common Information**

Project No.: RKSA260311002
 EUT Model: P5-PRO
 Test Mode: 5G WIFI 802.11ac20 mode High Channel
 Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 20.1°C
 Humidity: 50%
 Atmospheric Pressure: 101.5kPa
 Test Engineer: Destine Hu
 Check by: Bard Liu
 Test Date: 2026/4/27


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2883.600000	---	25.51	54.00	28.49	V	-8.8
2883.600000	35.75	---	74.00	38.25	V	-8.8
4767.200000	---	32.12	54.00	21.88	V	-3.5
4767.200000	42.48	---	74.00	31.52	V	-3.5
7449.800000	---	40.43	54.00	13.57	H	3.1
7449.800000	51.10	---	74.00	22.90	H	3.1
12087.400000	---	43.15	54.00	10.85	H	9.0
12087.400000	54.47	---	74.00	19.53	H	9.0
14491.200000	---	---	74.00	19.69	H	11.1
14491.200000	---	45.70	54.00	8.30	H	11.1
17932.000000	53.64	---	74.00	20.36	V	13.4
17932.000000	---	46.21	54.00	7.79	V	13.4

802.11ac40 Mode:**Low Channel: 5755MHz****Common Information**

Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11ac40 mode Low Channel
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1℃
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1996.200000	36.59	---	68.20	31.61	V	-11.7
4655.000000	43.11	---	74.00	30.89	V	-3.9
4655.000000	---	33.13	54.00	20.87	V	-3.9
7674.200000	50.82	---	74.00	23.18	V	3.4
7674.200000	---	40.74	54.00	13.26	V	3.4
12016.000000	---	44.79	54.00	9.21	H	9.0
12016.000000	52.58	---	74.00	21.42	H	9.0
14049.200000	55.03	---	68.20	13.17	H	10.7
14491.200000	53.33	---	74.00	20.67	H	11.1
14491.200000	---	44.95	54.00	9.05	H	11.1
17989.800000	---	46.43	54.00	7.57	V	13.8
17989.800000	54.39	---	74.00	19.61	V	13.8

High Channel: 5795MHz**Common Information**

Project No.: RKSA260311002
EUT Model: P5-PRO
Test Mode: 5G WIFI 802.11ac40 mode High Channel
Standard: FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 20.1℃
Humidity: 50%
Atmospheric Pressure: 101.5kPa
Test Engineer: Destine Hu
Check by: Bard Liu
Test Date: 2026/4/27


Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1159.800000	35.89	---	74.00	38.11	V	-15.5
1159.800000	---	21.90	54.00	32.10	V	-15.5
1992.800000	34.61	---	68.20	33.59	V	-11.7
3584.000000	40.45	---	68.20	27.75	V	-6.0
4665.200000	43.01	---	74.00	30.99	V	-3.9
4665.200000	---	31.86	54.00	22.14	V	-3.9
8412.000000	---	40.95	54.00	13.05	H	4.5
8412.000000	51.02	---	74.00	22.98	H	4.5
11995.600000	---	43.47	54.00	10.53	V	9.0
11995.600000	53.42	---	74.00	20.58	V	9.0
17996.600000	55.87	---	74.00	18.13	V	13.8
17996.600000	---	47.39	54.00	6.61	V	13.8

802.11ac80 Mode:**Channel: 5775MHz****Common Information**

Project No.:	RKSA260311002
EUT Model:	P5-PRO
Test Mode:	5G WIFI 802.11ac80
Standard:	FCC Part 15.407& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	20.1℃
Humidity:	50%
Atmospheric Pressure:	101.5kPa
Test Engineer:	Destine Hu
Check by:	Bard Liu
Test Date:	2026/4/27

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2890.400000	---	25.62	54.00	28.38	V	-8.8
2890.400000	34.65	---	74.00	39.35	V	-8.8
4757.000000	---	32.79	54.00	21.21	H	-3.6
4757.000000	43.84	---	74.00	30.16	H	-3.6
7698.000000	---	41.57	54.00	12.43	H	3.4
7698.000000	50.51	---	74.00	23.49	H	3.4
12121.400000	---	43.54	54.00	10.46	V	9.0
12121.400000	53.67	---	74.00	20.33	V	9.0
14491.200000	53.58	---	74.00	20.42	H	11.1
14491.200000	---	45.08	54.00	8.92	H	11.1
17976.200000	53.88	---	74.00	20.12	H	13.7
17976.200000	---	47.07	54.00	6.93	H	13.7