

TEST REPORT

Product Name : 802.11ah WIFI module
Model Number : TX-AH-R900ATR
FCC ID : 2AXPI-TX-AH-R900ATR

Prepared for : Zhuhai Huge-ic Co.,Ltd.
Address : 3rd Floor, 11 Building, 1st Jin Tang Road, Hi-tech Zone
Zhuhai China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ES200901011W
Date(s) of Tests : August 24,2020 to September 27,2020
Date of issue : September 27,2020

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION.....	3
2 EUT TECHNICAL DESCRIPTION.....	4
3 SUMMARY OF TEST RESULT.....	5
4 TEST METHODOLOGY.....	6
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	6
4.2 MEASUREMENT EQUIPMENT USED.....	6
4.3 DESCRIPTION OF TEST MODES.....	7
4.4 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING.....	9
5 FACILITIES AND ACCREDITATIONS.....	10
5.1 FACILITIES.....	10
5.2 LABORATORY ACCREDITATIONS AND LISTINGS.....	10
6 TEST SYSTEM UNCERTAINTY.....	11
7 SETUP OF EQUIPMENT UNDER TEST.....	12
7.1 RADIO FREQUENCY TEST SETUP 1.....	12
7.2 RADIO FREQUENCY TEST SETUP 2.....	12
7.3 CONDUCTED EMISSION TEST SETUP.....	13
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	14
7.5 SUPPORT EQUIPMENT.....	14
8 TEST REQUIREMENTS.....	15
8.1 DTS (6DB)BANDWIDTH.....	15
8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	22
8.3 MAXIMUM POWER SPECTRAL DENSITY.....	23
8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS.....	30
8.5 RADIATED SPURIOUS EMISSION.....	47
8.6 CONDUCTED EMISSIONS TEST.....	52
8.7 ANTENNA APPLICATION.....	55

1 TEST RESULT CERTIFICATION

Applicant:	Zhuhai Huge-ic Co.,Ltd. 3rd Floor, 11 Building, 1st Jin Tang Road, Hi-tech Zone Zhuhai China
Manufacturer:	Zhuhai Huge-ic Co.,Ltd. 3rd Floor, 11 Building, 1st Jin Tang Road, Hi-tech Zone Zhuhai China
Factory:	Zhuhai Huge-ic Co.,Ltd. 3rd Floor, 11 Building, 1st Jin Tang Road, Hi-tech Zone Zhuhai China
EUT Description:	802.11ah WIFI module
Model Number:	TX-AH-R900ATR
Trade Mark:	N/A

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 24,2020 to September 27,2020

Prepared by : 
Sewen Guo /Editor

Reviewer : 
Joe Xia /Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
IEEE 802.11 WLAN Mode Supported	☒ 802.11ah(1MHz channel bandwidth) ☒ 802.11ah(2MHz channel bandwidth) ☒ 802.11ah(4MHz channel bandwidth) ☒ 802.11ah(8MHz channel bandwidth)
Data Rate	802.11ah:150Kbps,32.5Mbps;
Modulation	OFDM with BPSK/QPSK/16QAM/64QAM
Operating Frequency Range	903.5-926.5MHz for 802.11ah(1MHz channel bandwidth); 905-925MHz for 802.11ah(2MHz channel bandwidth); 906-926MHz for 802.11ah(4MHz channel bandwidth); 908-924MHz for 802.11ah(8MHz channel bandwidth);
Number of Channels	24 channels for 802.11ah(1MHz channel bandwidth); 11 Channels for 802.11ah(2MHz channel bandwidth); 6 Channels for 802.11ah(4MHz channel bandwidth); 3 Channels for 802.11ah(8MHz channel bandwidth);
Transmit Power Max	802.11ah(1MHz channel bandwidth):26.25 dBm 802.11ah(1MHz channel bandwidth):26.02 dBm 802.11ah(1MHz channel bandwidth):26.13 dBm 802.11ah(1MHz channel bandwidth):26.08 dBm
Antenna:	External Antenna
Antenna Gain:	0 dBi
Test Voltage:	DC 5V
Temperature Range	-20°C ~ +70° C

3 SUMMARY OF TEST RESULT

FCC PartClause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted EmissionTest	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1:N/A (Not Applicable) NOTE2:According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AXPI-TX-AH-R900ATR filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/22/2020
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/22/2020
50Ω Coaxial Switch	Anritsu	MP59B	M20531	05/22/2020
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/22/2020
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/22/2020
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/22/2020

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/22/2020
Pre-Amplifier	HP	8447D	2944A07999	05/22/2020
Bilog Antenna	Schwarzbeck	VULB9163	142	05/22/2020
Loop Antenna	ARA	PLA-1030/B	1029	05/22/2020
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/22/2020
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/22/2020
Cable	Schwarzbeck	AK9513	ACRX1	05/22/2020
Cable	Rosenberger	N/A	FP2RX2	05/22/2020
Cable	Schwarzbeck	AK9513	CRPX1	05/22/2020
Cable	Schwarzbeck	AK9513	CRRX2	05/22/2020

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/22/2020
Signal Analyzer	Agilent	N9010A	My53470879	05/22/2020
Power meter	Anritsu	ML2495A	0824006	05/22/2020
Power sensor	Anritsu	MA2411B	0738172	05/22/2020

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11ah:150Kbps,32.5Mbps) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11ah(1MHz channel bandwidth):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	903.5	11	913.5	22	924.5
2	904.5	12	914.5	23	925.5
3	905.5	13	915.5	24	926.5
...	...	...	...	...	...

Note: $f_c = 903.5\text{MHz} + (k-1) \times 1\text{MHz}$ $k=1$ to 24

Frequency and Channel list for 802.11ah(2MHz channel bandwidth):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	905	5	913	9	921
2	907	6	915	10	923
3	909	7	917	11	925
4	911	8	919		

Frequency and Channel list for 802.11ah(4MHz channel bandwidth):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	906	3	914	5	922
2	910	4	918	6	926

Frequency and Channel list for 802.11ah(8MHz channel bandwidth):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	908	2	916	3	924

Test Frequency and Channel for 802.11ah(1MHz channel bandwidth):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	903.5	12	914.5	24	926.5

Test Frequency and channel for 802.11ah(2MHz channel bandwidth):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	905	6	915	11	925

Test Frequency and channel for 802.11ah(4MHz channel bandwidth):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	906	3	914	6	926

Test Frequency and channel for 802.11ah(8MHz channel bandwidth):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	908	2	916	3	924

4.4 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version:	SecureCRT
power level	20



5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: Accredited by CNAS, 2018.11.30
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)
The Certificate Registration Number is L2291.

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA, August 31, 2020

The Certificate Registration Number is 4321.01.

Accredited by Industry Canada, November 09, 2018

The Conformity Assessment Body Identifier is CN0008.

Name of Firm

Site Location

: EMTEK(SHENZHEN) CO., LTD.
: Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	acer	ZR1	LXTECOCO76643158 372500

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 DTS (6DB)BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB558074 D01 15.247 Meas Guidance v05

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) = 300kHz.

Set Span = 2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.


8.1.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	6 dB Bandwidth MHz	Limit (kHz)	Verdict
802.11ah 1M	1	903.5	941	>500	PASS
	12	914.5	926	>500	PASS
	24	926.5	918	>500	PASS
802.11ah 2M	1	905	1905	>500	PASS
	6	915	1841	>500	PASS
	11	925	1841	>500	PASS
802.11ah 4M	1	906	3693	>500	PASS
	3	914	3647	>500	PASS
	6	926	3693	>500	PASS
802.11ah 8M	1	908	7572	>500	PASS
	2	916	7363	>500	PASS
	3	924	6808	>500	PASS


Test Model

DTS (6dB) Bandwidth
802.11ah 1M
Channel 1: 903.5MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 1M
Channel 12: 914.5MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 1M
Channel 24: 926.5MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 2M
Channel 1: 905MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 2M
Channel 6: 915MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 2M
Channel 11: 925MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 4M
Channel 1: 906MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 4M
Channel 3: 914MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 4M
Channel 6: 926MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 8M
Channel 1: 908MHz




Test Model

DTS (6dB) Bandwidth
802.11ah 8M
Channel 2: 916MHz



Test Model

DTS (6dB) Bandwidth
802.11ah 8M
Channel 3: 924MHz



8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB558074 D01 15.247 Meas Guidance v05

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 902-928 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part 15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain- 6)

8.2.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
802.11ah 1M	1	903.5	26.25	30	PASS
	12	914.5	26.03	30	PASS
	24	926.5	25.98	30	PASS
802.11ah 2M	1	905	26.02	30	PASS
	6	915	25.96	30	PASS
	11	925	25.96	30	PASS
802.11ah 4M	1	906	26.13	30	PASS
	3	914	26.07	30	PASS
	6	926	25.98	30	PASS
802.11ah 8M	1	908	25.95	30	PASS
	2	916	26.03	30	PASS
	3	924	26.08	30	PASS

8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB558074 D01 15.247 Meas Guidance v05

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to:10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain- 6)

8.3.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

For 1T1R

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11ah 1M	1	903.5	6.91	8	PASS
	12	914.5	6.88	8	PASS
	24	926.5	6.75	8	PASS
802.11ah 2M	1	905	3.00	8	PASS
	6	915	4.39	8	PASS
	11	925	4.19	8	PASS
802.11ah 4M	1	906	-0.45	8	PASS
	3	914	1.31	8	PASS
	6	926	1.08	8	PASS
802.11ah 8M	1	908	-4.24	8	PASS
	2	916	-3.15	8	PASS
	3	924	-2.37	8	PASS

Test Model

Power Spectral Density
802.11ah 1M
Channel 1: 903.5MHz



Test Model

Power Spectral Density
802.11ah 1M
Channel 12: 914.5MHz




Test Model

Power Spectral Density
802.11ah 1M
Channel 24: 926.5MHz




Test Model

Power Spectral Density
802.11ah 2M
Channel 1: 905MHz




Test Model

Power Spectral Density
802.11ah 2M
Channel 6: 915MHz




Test Model

Power Spectral Density
802.11ah 2M
Channel 11: 925MHz




Test Model

Power Spectral Density
802.11ah 4M
Channel 1: 906MHz




Test Model

Power Spectral Density
802.11ah 4M
Channel 3: 914MHz




Test Model

Power Spectral Density
802.11ah 4M
Channel 6: 926MHz




Test Model

Power Spectral Density
802.11ah 8M
Channel 1: 908MHz




Test Model

Power Spectral Density
802.11ah 8M
Channel 2: 916MHz



Test Model

Power Spectral Density
802.11ah 8M
Channel 3: 924MHz



8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB558074 D01 15.247 Meas Guidance v05

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results

For 1T1R

PSD(Power Spectral Density) RBW=100kHz
802.11ah 1M

Test Model


Channel 1: 903.5MHz



Unwanted Emissions in non-restricted frequency bands
802.11ah 1M

Test Model

Channel 1: 903.5MHz



Test Model

Band edge
802.11ah 1M

Channel 1: 903.5MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 1M


Channel 12: 914.5MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 1M

Channel 12: 914.5MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 1M


Channel 24: 926.5MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 1M

Channel 24: 926.5MHz



Test Model

Band edge
802.11ah 1M

Channel 24: 926.5MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 2M


Channel 1: 905MHz



Test Model

Unwanted Emissions in non-restricted frequency bands
802.11ah 2M


Channel 1: 905MHz



Test Model

Band edge
802.11ah 2M


Channel 1: 905MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 2M


Channel 6: 915MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 2M

☒ Channel 6: 915MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 2M


☒ Channel 11: 925MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 2M

☒ Channel 11: 925MHz



Test Model

Band edge
802.11ah 2M


☒ Channel 11: 925MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 4M


☒ Channel 1: 906MHz



Test Model

Unwanted Emissions in non-restricted frequency bands
802.11ah 4M


☒ Channel 1: 906MHz



Test Model

Band edge
802.11ah 4M

☒ Channel 1: 906MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 4M


☒ Channel 3: 914MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 4M

☒ Channel 3: 914MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 4M


☒ Channel 6: 926MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 4M

☒ Channel 6: 926MHz



Test Model

Band edge
802.11ah 4M

☒ Channel 6: 926MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 8M


☒ Channel 1: 908MHz



Test Model

Unwanted Emissions in non-restricted frequency bands
802.11ah 8M


☒ Channel 1: 908MHz



Test Model

Band edge
802.11ah 8M


☒ Channel 1: 908MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 8M


☒ Channel 2: 916MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 8M

☒ Channel 2: 916MHz



Test Model

PSD(Power Spectral Density) RBW=100kHz
802.11ah 8M


☒ Channel 3: 924MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11ah 8M

☒ Channel 3: 924MHz



Test Model

Band edge
802.11ah 8M

☒ Channel 3: 924MHz



8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB558074 D01 15.247 Meas Guidance v05

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (μV/m)	300
0.490-1.705	2400/F(KHz)	20 log (μV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All modulation modes have been tested, the worst mode is (802.11ah 1M), the data is recorded on the following page, other modulation modes do not exceed this limit. Please refer to the following data.

Test mode: 802.11ah 1M Frequency: Channel 1: 903.5MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1807.00	V	54.87	30.75	74	54	-19.13	-23.25
2710.50	V	53.02	33.34	74	54	-20.98	-20.66
3614.00	V	55.56	31.37	74	54	-18.44	-22.63
1807.00	H	65.71	43.42	74	54	-8.29	-10.58
2710.50	H	60.56	34.83	74	54	-13.44	-19.17
3614.00	H	53.51	38.05	74	54	-20.49	-15.95

Test mode: 802.11ah 1M Frequency: Channel 1: 914.5MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1829.00	V	54.1	32.51	74	54	-19.90	-21.49
2743.50	V	53.44	30.43	74	54	-20.56	-23.57
3658.00	V	50.88	35.62	74	54	-23.12	-18.38
1829.00	H	62.09	42.41	74	54	-11.91	-11.59
2743.50	H	60.3	34.89	74	54	-13.70	-19.11
3658.00	H	59.82	32.11	74	54	-14.18	-21.89

Test mode: 802.11ah 1M Frequency: Channel 1: 926.5MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1853.00	V	54.76	33.25	74	54	-19.24	-20.75
2779.50	V	56.74	33.37	74	54	-17.26	-20.63
3706.00	V	50.77	31.13	74	54	-23.23	-22.87
1853.00	H	60.69	39.36	74	54	-13.31	-14.64
2779.50	H	62.08	36.56	74	54	-11.92	-17.44
3706.00	H	55.33	32.37	74	54	-18.67	-21.63

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor +Cable Loss.

(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission below 1GHz (30MHz to 1GHz)

All modes 802.11ah have been tested, the worst mode is (802.11ah 1M), the data is recorded on the following page, other modulation modes do not exceed this limit.



Site: Chamber #1
Limit: FCC PART 15 C 3m(RE)
Note: TX903.5-1M
Polarization: **Horizontal**
Power: DC 5V
Temperature: 24.1
Humidity: 50 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		143.8295	50.63	-21.66	28.97	43.50	-14.53	QP		
2		202.8104	47.92	-17.28	30.64	43.50	-12.86	QP		
3		231.7180	51.77	-16.25	35.52	46.00	-10.48	QP		
4		386.6338	42.92	-11.26	31.66	46.00	-14.34	QP		
5		444.8514	41.35	-10.05	31.30	46.00	-14.70	QP		
6	*	810.2654	40.53	-3.22	37.31	46.00	-8.69	QP		

*:Maximum data x:Over limit !:over margin

Operator: Tom



Site Chamber #1

Polarization: **Vertical**

Temperature: 24.1

Limit: FCC PART 15 C 3m(RE)

Power: DC 5V

Humidity: 50 %

Note: TX903.5-1M

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		62.8708	46.98	-17.46	29.52	40.00	-10.48	QP		
2		168.4138	51.62	-20.22	31.40	43.50	-12.10	QP		
3		289.0021	45.88	-14.17	31.71	46.00	-14.29	QP		
4	!	406.0880	51.59	-10.92	40.67	46.00	-5.33	QP		
5		520.8882	44.83	-8.53	36.30	46.00	-9.70	QP		
6	*	810.2654	44.55	-3.22	41.33	46.00	-4.67	QP		

*:Maximum data x:Over limit !:over margin

Operator: Tom

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.


Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site site #1

Phase: **N**

Temperature: 25

Limit: (CE)FCC PART 15 C_QP

Power: AC 120V/60Hz

Humidity: 55 %

Mode: TX903.5-1M


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1620	41.72	10.02	51.74	65.36	-13.62	QP	
2		0.1620	24.11	10.02	34.13	55.36	-21.23	AVG	
3		0.2420	35.08	10.05	45.13	62.03	-16.90	QP	
4		0.2420	16.56	10.05	26.61	52.03	-25.42	AVG	
5		0.3180	27.37	10.09	37.46	59.76	-22.30	QP	
6		0.3180	11.09	10.09	21.18	49.76	-28.58	AVG	
7		0.4140	26.58	10.14	36.72	57.57	-20.85	QP	
8		0.4140	8.25	10.14	18.39	47.57	-29.18	AVG	
9		0.4980	27.29	10.18	37.47	56.03	-18.56	QP	
10		0.4980	10.18	10.18	20.36	46.03	-25.67	AVG	
11	*	0.7980	35.17	10.18	45.35	56.00	-10.65	QP	
12		0.7980	20.37	10.18	30.55	46.00	-15.45	AVG	

*:Maximum data x:Over limit !:over margin

Comment: Factor build in receiver.

Operator: Tom



Site site #1

Phase: **L1**

Temperature: 25

Limit: (CE)FCC PART 15 C_QP

Power: AC 120V/60Hz

Humidity: 55 %

Mode: TX903.5-1M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1620	41.05	10.02	51.07	65.36	-14.29	QP	
2		0.1620	23.78	10.02	33.80	55.36	-21.56	AVG	
3		0.2420	35.26	10.05	45.31	62.03	-16.72	QP	
4		0.2420	17.99	10.05	28.04	52.03	-23.99	AVG	
5		0.3180	28.33	10.09	38.42	59.76	-21.34	QP	
6		0.3180	12.18	10.09	22.27	49.76	-27.49	AVG	
7		0.4140	26.59	10.14	36.73	57.57	-20.84	QP	
8		0.4140	8.86	10.14	19.00	47.57	-28.57	AVG	
9		0.4860	26.45	10.17	36.62	56.24	-19.62	QP	
10		0.4860	11.26	10.17	21.43	46.24	-24.81	AVG	
11	*	0.7980	35.33	10.18	45.51	56.00	-10.49	QP	
12		0.7980	20.45	10.18	30.63	46.00	-15.37	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Tom

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

The EUT has 1 antennas: an External Antenna for WIFI 802.11ah, the gain is 0 dBi;

Note: ☐ Antenna use a permanently attached antenna which is not replaceable.
☒ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效；

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.