



RF Exposure Evaluation

FOR

Zhongshan Dottsun Electronic Co., Ltd

Work Light

Test Model: FSI 90-1680-8K

Additional Model No.: Please Refer to Page 6

Prepared for : Zhongshan Dottsun Electronic Co., Ltd
Address : 2nd road of guanglong, jinlong industrial park Zhongshan City,
Guangdong, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : July 14, 2026
Number of tested samples : 2
Sample No. : B260622027-1, B260622027-2
Serial number : Prototype
Date of Test : July 14, 2026 ~ July 23, 2026
Date of Report : July 24, 2026



**RF Exposure Evaluation****Report Reference No. : LCSA05296021EB**

Date of Issue..... : July 24, 2026

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name..... : Zhongshan Dottsun Electronic Co., Ltd**Address..... : 2nd road of guanglong, jinlong industrial park Zhongshan City,
Guangdong, China**Test Specification**Standard..... : FCC KDB publication 447498 D01 General RF Exposure Guidance v06
FCC CFR 47 part1 1.1310
FCC CFR 47 part2 2.1091

Test Report Form No..... : TRF-4-E-214 A/0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Work Light

Trade Mark..... : N/A

Test Model..... : FSI 90-1680-8K

Ratings..... : Please Refer to Page 6

Result : Pass**Compiled by:**

Nick Peng/ Administrator

Supervised by:

Kevin Huang/ RF Manager

Approved by:

Gavin Liang/ Manager





RF Exposure Evaluation

Test Report No. : LCSA05296021EB	<u>July 24, 2026</u> Date of issue
---	---------------------------------------

Test Model.....	: FSI 90-1680-8K
EUT.....	: Work Light
Applicant.....	: Zhongshan Dottsun Electronic Co., Ltd
Address.....	: 2nd road of guanglong, jinlong industrial park Zhongshan City, Guangdong, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Fresh Source International (Cambodia) Co., Ltd
Address.....	: National Road No.3, Cham Pol Village, Popel Commune, Tram Kak, District, Takeo Province, Kingdom of Cambodia.
Telephone.....	: /
Fax.....	: /
Factory.....	: Fresh Source International (Cambodia) Co., Ltd
Address.....	: National Road No.3, Cham Pol Village, Popel Commune, Tram Kak, District, Takeo Province, Kingdom of Cambodia.
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	July 24, 2026	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information	6
2. Evaluation Method	7
3. Limit	7
4. MPE Calculation Method	8
5. Conducted Power	8
6. Manufacturing Tolerance	8
7. Measurement Results	9
8. Conclusion	9
9. Description of Test Facility	9
10.Measurement Uncertainty	9





1. Product Information

EUT	: Work Light
Test Model	: FSI 90-1680-8K
Additional Model No.	: 25687
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Ratings	: Input: AC 120V/60Hz Output: USB-A+USB-C: 5V $\overline{=}$ 2A Light : 8000LM
Hardware Version	: /
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V6.0 (DSS)
Channel Spacing	: 1MHz for Bluetooth V6.0 (DSS)
Modulation Type	: GFSK, π /4-DQPSK, 8-DPSK for Bluetooth V6.0 (DSS)
Bluetooth Version	: V6.0
Antenna Description	: PCB Antenna, -0.58dBi(Max.)

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$S=PG/4\pi R^2$

Where: S=power density
P=power input to antenna
G=power gain of the antenna in the direction of interest relative to an isotropic radiator
R=distance to the center of radiation of the antenna

5. Conducted Power

[BT]			
Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-2.53
	39	2441	0.53
	78	2480	-0.33
$\pi/4$ DQPSK	0	2402	-3.19
	39	2441	-0.11
	78	2480	-0.83
8DPSK	0	2402	-2.79
	19	2441	0.28
	39	2480	-0.49

6. Manufacturing Tolerance

[BT]			
GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-2.0	0	0
Tolerance ±(dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-3.0	0	0
Tolerance ±(dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-2.0	0	0
Tolerance ±(dB)	1.0	1.0	1.0





7. Measurement Results

7.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	1.0	1.2589	-0.58	0.8750	0.0002	1.0000
$\pi/4$ -DQPSK	1.0	1.2589	-0.58	0.8750	0.0002	1.0000
8-DPSK	1.0	1.2589	-0.58	0.8750	0.0002	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7.2 Simultaneous Transmission MPE Evaluation

The sample support only one BT Module, so no need consider simultaneous transmission;

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

9. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

10. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

-----THE END OF REPORT-----



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity